Instantiation

Abhijeet Gupta* IMS, Stuttgart University Gemma Boleda^{**} Universitat Pompeu Fabra

Sebastian Padó[†] IMS, Stuttgart University

In computational linguistics, a large body of work exists on distributed modeling of lexical relations, focussing largely on lexical relations such as hypernymy (scientist – person) that hold between two categories, as expressed by common nouns. In contrast, computational linguistics has paid little attention to entities denoted by proper nouns (Marie Curie, Mumbai, ...). These have investigated in detail by the Knowledge Representation and Semantic Web communities, but generally not with regard to their linguistic properties.

Our paper closes this gap by investigating and modeling the lexical relation of instantiation, which holds between an entity-denoting and a category-denoting expression (Marie Curie – scientist or Mumbai – city). We present a new, principled dataset for the task of instantiation detection as well as experiments and analyses on this dataset. We obtain the following results: (a), entities belonging to one category form a region in distributional space, but the embedding for the category word is typically located outside this subspace; (b) it is easy to learn to distinguish entities from categories from distributional evidence, but due to (a), instantiation proper is much harder to learn when using common nouns as representations of categories; (c) this problem can be alleviated by using category representations based on entity rather than category word embeddings.

1. Introduction

A fundamental ontological distinction in language and cognition is that between *categories* and *entities*: Categories are equivalence classes that help us handle entities in the world as we perceive and conceptualize them (objects, people, events, ...), for instance by predicting the behavior of new entities based on the category we assign it to (Murphy 2002; Neelakantan and Chang 2015). For example, the entity *Emmy Noether* instantiates the *scientist* category, and consequently we expect her to be associated with academic institutions, to have publications, etc. In language, entities are typically expressed by proper nouns, and categories by common nouns. Copular sentences such as *Noether is a scientist* arguably express *instantiation*, the most prominent relationship between entities and categories.

This paper presents a distributional exploration of instantiation. Instantiation, and entities in general, have received little attention in linguistics and computational linguistics compared to categories and relations among categories such as hypernymy

^{*} E-mail: abhijeet.gupta@ims.uni-stuttgart.de

^{**} E-mail: gemma.boleda@upf.edu

[†] E-mail: sebastian.pado@ims.uni-stuttgart.de

(see below and Section 6 for background). In this article, we ask the question *Can generic distributed representations be used to model instantiation?* and address it with analysis and experiments. Our ultimate research goal is to advance the understanding of the notions of entity vs. category and their relation to language; the immediate goals of this article are to test the hypotheses that 1) entities and categories are represented differently in distributional space, and 2) not only the broad distinction between entities and categories, but also instantiation proper, is recoverable from distributional representations.

Background on Instantiation. In formal semantics — concretely model-theoretical semantics and type theory — common nouns are modeled as predicates, that is, sets of entities. The entities are referents in the universe or the utterance situation (Gamut 1991).¹ Proper nouns refer to individual entities.² From this perspective, instantiation is simply the set inclusion relationship, and traditionally instantiation has been assumed rather than investigated: For example, it is postulated that, in a given model of the world, Jane Goodall belongs to the set denoted by scientist (that is, Jane Goodall instantiates the category *scientist*), but no attempt is made at establishing the conditions under which a certain entity instantiates a category.³ In turn, lexical semantics has mostly been concerned with category-denoting words and relations between them, such as synonymy, hypernymy or meronymy (Cruse 1986; Geeraerts 2010), and has traditionally not focused much on entities. Hypernymy and its mirror hyponymy are the relationship between two common nouns, one denoting a subcategory of the other: For instance, scientist is a hyponym of person, and person a hypernym of scientist. In this case, like in instantiation, one is more specific than the other; unlike in instantiation, however, both denote categories.

In Knowledge Representation (KR), as a field of Artificial Intelligence, the situation is different, since KR is interested in modelling any kind of knowledge. A prominent approach in Knowledge Representation is Description Logics (DL), a fragment of firstorder predicate logic specifically designed to model the structure of typical world knowledge (Baader 2003). Central foundations in DL are classes (analogous to categories), roles, and individuals (analogous to entities). DL actually distinguishes two types of knowledge: terminological knowledge, as captured in a typical ontology, i.e., knowledge about the relationships among classes. This includes *is-a*, which is like hyponymy. On the other side there is assertional knowledge, that is, knowledge about relationships between individuals, on the one hand, and roles and classes, on the other. Instantiation belongs to the latter, and corresponds to the *type* relationship in RDF, a representation framework commonly used in the Semantic Web (Hitzler, Krotzsch, and Rudolph 2009). Traditional knowledge bases (Cyc: Lenat (1995); SUMO: Niles and Pease (2001)) concentrate on terminological knowledge. Current knowledge bases (FreeBase, Bollacker et al. (2008); YAGO: Suchanek, Kasneci, and Weikum (2007)) tend do be rather short on terminological knowledge and see themselves mostly as repositories of assertional knowledge about large numbers of entities (although instantiation is sometimes included under the name of 'entity type', Neelakantan and Chang (2015)). WordNet (Fellbaum 1998) has a kind of

¹ This is actually the case for nouns with one argument. Relational arguments like *father* are typically modeled as sets of entity pairs.

² There is a philosophical discussion about the status of definite descriptions and generalized quantifiers; see (Textor 2011).

³ For certain predicates, such as vague adjectives, this issue has been thoroughly investigated (Kamp 1975, and subsequent work), but not so much for category-forming predicates such as nouns – though see Sassoon (2013).

hybrid status: It started as a terminological resource (with the difference to Knowledge Representation resources that it was structured around word senses), but was later on extended with knowledge about entities with a new relation, *instance_hypernym*, that encodes instantiation (Alfonseca and Manandhar 2002).

Most work on distributional semantics has followed traditional lexical semantics in its focus on categories (mostly common nouns, but content words in general), examining semantic similarity and relatedness as well as lexical semantic relations such as hypernymy, besides other conceptual aspects of meaning like selectional restrictions (Baroni and Lenci 2010, 2011; Erk, Padó, and Padó 2010; Roller, Erk, and Boleda 2014; Levy et al. 2015). In recent years, a few studies have started examining entities (Herbelot 2015; Herbelot and Vecchi 2015; Gupta et al. 2015), and an initial study of our own (Boleda, Gupta, and Padó 2017) investigated the modeling of instantiation with distributional methods.

To sum up, previous work either has traditionally not included instantiation in its purview (formal, lexical, and distributional semantics) or has tackled it from a rather applied perspective. To address this situation, we make the following contributions:

- A dataset to evaluate the ability of computational models to capture instantiation, analogous to previous datasets built around lexical relations such as synonymy and hypernymy (Baroni and Lenci 2011; Roller, Erk, and Boleda 2014).
- Experiments on this dataset suggesting that when using generic word embeddings, 1) entities and categories are represented in different regions of distributional space, 2) instantiation is hard but largely recoverable from distributed representations using nonlinear models, 3) it is easier to model instantiation using entities as a basis for category representation than using common nouns, which may have implications for the understanding of the relationship between language and cognition.
- On the methodological level, we show that memorization issues that had been previously shown to affect learning in lexical semantic relations such as hypernymy (Roller, Erk, and Boleda 2014; Levy et al. 2015) are also an issue with instantiation, and build the dataset so as to avoid these issues.

Compared to our previous pilot study on this topic (Boleda, Gupta, and Padó 2017), the current article is extended as follows: (a), the dataset⁴ is substantially improved: we add information about ontological classes for analysis and confounder selection purposes (Section 2.1), we add a more challenging set of confounders (Section 2.2), and our data splits prevent models form performing well simply by memorizing (Section 2.3)); (b), we present a detailed exploration of the properties of categories and entities in the embedding space (Section 3); (c), our experiments include a wider range of models (Section 4) and investigate an alternative method for representing categories (Section 5)⁵.

⁴ The dataset is available at http://www.ims.uni-stuttgart.de/data/Instantiation.html.

⁵ The models will be made available at publication.



Figure 1: Mapping between WordNet synsets and Google News targets.

2. A Dataset for Instantiation

Since there is no previous dataset on instantiation (with the exception of our own pilot study (Boleda, Gupta, and Padó 2017)), our first contribution is the creation of a benchmark dataset for this relation with positive and negative examples (word pairs of entities and categories). For entities, we work with representations of Named Entities in the public domain such as *Italy* or *George Washington* because it is possible to obtain distributed representations for those using standard methods in distributional semantics and deep learning. This is common to related work on entities in distributional semantics (Herbelot 2015; Gupta et al. 2015).

We follow the procedures of previous studies that created benchmark datasets for lexical relations (Baroni and Lenci 2011; Roller, Erk, and Boleda 2014; Levy et al. 2015), and extract the positive examples, such as *Virginia Woolf – writer*, from WordNet. We pair them with confounders (*Virginia Woolf – athlete*) in a principled way, partially inspired by (Baroni and Lenci 2011), to enable a structured investigation of the different aspects involved in instantiation, in particular the distinction between instance and category in general vs. instantiation proper and the role of similarity. The next two subsections discuss the positive datapoints and the confounders, respectively.

2.1 Positive Datapoints

Our method for obtaining positive datapoints is shown in Figure 1. We start out with WordNet and extract all pairs of WordNet synsets (e, c) that are linked with the *instance_hypernym* relation. This ensures that e is an entity and c a category. Next, we retain only those pairs for which we have coverage in a very large distributional resource, the Google News vector space (Mikolov et al. (2013), see below for details). The targets for this vector space space were drawn from one of the largest repositories of entities at the time, the FreeBase knowledge base (Bollacker et al. 2008). Mapping between WordNet synsets and FreeBase identifiers requires some heuristics. Notably, WordNet synsets with multiple elements can map onto several FreeBase identifiers. For example, the synset (*Washington, George Washington, President Washington*) maps onto two FreeBase identifiers,

and thus, two embeddings, that for 'Washington' and that for 'George Washington'.⁶ We choose the FreeBase identifier that matches the longest element of the synset, as it will be the least ambiguous: While *Washington* can refer to different entities (a person, a state, or a city), *George Washington* almost always refers to the former president of the USA. Of course the embedding for *George Washington* will be built from fewer occurrences; our dataset design favors precision over recall. Note that this strategy reduces, but does not completely remove, the incidence of short FreeBase identifiers.

The resulting dataset is a collection of 5,469 positive cases of instantiation, with 4,750 unique entities and 577 unique categories (see Table 1). There are more positive word pairs than entities because some entities in WordNet belong to more than one category: For example, (*George Washington – president of the United States*), (*George Washington – general*). There is also some remaining ambiguity, in the form of different entities with the same name that belong to different categories – e.g. *William Gilbert the poet* vs. *the physicist*. Since these result from natural properties of instantiation, we perform no further filtering.

Note that there are many more entities than categories, which is to be expected because there are more entities than (lexicalized) categories, and some categories contain a large number of entities. The effect may however be reinforced by the way the Google News space was built: Its vocabulary consists of the nodes in FreeBase, a database primarily geared towards entities, though it also had nodes for categories.

For analysis (see Section 3) and negative datapoint selection, we additionally use the WordNet 'lexicographer file' labels, which can be used as proxies for semantic categories or ontological classes (Rigau, Atserias, and Agirre 1997; Curran 2005).⁷ These are shown as rows in Table 1 (also see Figure 1). Most of the datapoints belong to ontological classes *person* and *location*. The *person* class consists of popular and well known, fictional and non-fictional, historical as well as modern day people; *location* contains geopolitical entities, like countries or cities; *object* mostly consists of geographical and natural entities; *communication* includes literary texts but also computer programs and operating systems; *artifact* covers all kinds of man-made entities; finally, *act* consists of famous events.

2.2 Confounders

As mentioned above, we include different types of confounders in our dataset. In our experiments in instantiation detection (Sections 4 and 5), we ask the models to distinguish between positive examples and confounders. More specifically, we generate four sets of confounders by transforming each entity-category positive example (e, c) as follows:

Inverse Swap the positions of entity and category, yielding (c, e).

Inst2Inst Replace the correct category by a different random entity e' of the same ontological class, yielding (e, e').

NotInst-global Replace the correct category c by a random wrong category c'', from the global distribution of categories, yielding (e, c'').

⁶ Some multi-word named entities were included in Mikolov et al.'s space as single tokens, including 'George Washington' (but not the expression 'President Washington'). Prior to building the space, they lowercased all words and combined multi-word expressions such that they were considered a single token during space construction; see Mikolov et al. (2013) for details on how they identified multi-word expressions.

⁷ If the entity and category are assigned different lexicographer files, we use the one of the entity; if one of them is missing a class, we use the other one. This affects a total of 329 (6%) datapoints. Also, we collapse all ontological classes with fewer than 50 occurrences in our data into a class *other*.

#Entities	Example	#Categories	Example	#Datapoints
2330	Madame Curie	294	chemist	2742
1512	Oaxaca	99	city	1746
630	Nile	59	river	633
118	Bastille	55	fortress	121
97	Iliad	43	epos	98
67	Alamo	20	siege	69
60	Paleocene	26	epoch	60
4750	_	577	_	5469
	#Entities 2330 1512 630 118 97 67 67 60 4750	#Entities Example 2330 Madame Curie 1512 Oaxaca 630 Nile 118 Bastille 97 Iliad 67 Alamo 60 Paleocene 4750 –	#Entities Example #Categories 2330 Madame Curie 294 1512 Oaxaca 99 630 Nile 59 118 Bastille 55 97 Iliad 43 67 Alamo 20 60 Paleocene 26 4750 – 577	#Entities Example #Categories Example 2330 Madame Curie 294 chemist 1512 Oaxaca 99 city 630 Nile 59 river 118 Bastille 55 fortress 97 Iliad 43 epos 67 Alamo 20 siege 60 Paleocene 26 epoch 4750 – 577 –

Table 1: Positive datapoints: Statistics and examples by ontological class.

Table 2: Examples of confounders. POTUS = President of the United States.

Туре	Example 1	Example 2
Positive	George Washington – POTUS	Mumbai – city
Inverse	POTUS – George Washington	city – Mumbai
Inst2Inst	George Washington – Peter Behrens	Mumbai – Vicksburg
NotInst-global	George Washington – river	Mumbai – statesman
NotInst-inClass	George Washington – astronomer	Mumbai – residential area

NotInst-inClass Replace the correct category c by a wrong category c', this time sampling from the same ontological class, yielding (e, c').

Inverse tests that the models correctly capture the asymmetric nature of instantiation. *Inst2Inst* checks that the models are not fooled by similarity (entities in the same ontological class are similar to each other, see Section 3). Finally, *NotInst-global* and *NotInst-inClass* aim at testing that models actually learn the relation between a specific entity and a specific category, as opposed to learning to classify entities vs. categories in general (Levy et al. 2015). The difference between *NotInst-inClass* and *NotInst-global* is one of difficulty: In *NotInst-inClass*, confounder categories come from the same ontological class as the correct categories, and thus are semantically more similar to the correct category (e.g. pairing *George Washington* with *astronomer*) than in *NotInst-global* (where *George Washington* is paired with *river*). Table 2 shows two examples of a positive datapoint with its corresponding confounders.

When pairing confounders with the positive examples, we obtain in four different balanced subsets, consisting of pairs of expressions for which the instantiation relationship either holds (positive examples) or does not (confounders): Pos+*Inverse*, Pos+*Inst2Inst*, Pos+*NotInst-global* and Pos+*NotInst-inClass*. Two final variants, Pos+*Union-inClass* and Pos+*Union-global*, combine the positive examples with *Inverse*, *Inst2Inst*, and one of the two *NotInst* variants, respectively. These two variants are more challenging in that they require models to distinguish positive examples from confounders of different types, and have a 1:3 positive-to-negative ratio. A. Gupta, G. Boleda, S. Padó

2.3 Dataset Partitioning and Memorization

We split each dataset variant into training, validation and test sets (80, 10, and 10% respectively). This is however not enough to make sure that the models can generalize: the related task of hypernymy detection has been shown to suffer from the problem of *memorization* (Roller, Erk, and Boleda 2014; Levy et al. 2015), that is, models learning by heart that certain words (such as *animal*) make good hypernyms instead of truly learning the hypernymy relation. The problem is that, in a naïve random split of the datapoints, even if the pairs are not reused across partitions, individual members of the pair can be. Thus, good results can hide a lack of generalization, in particular for frequent categories.

To address this issue, we adapt the methodology of Roller, Erk, and Boleda (2014) which ensures that there is zero lexical overlap between training, validation, and test sets. Specifically, we split the test set into many equal-sized test folds and remove overlap with the training and validation data: For example, if (*George Washington, President of the United States*) occurs in a test fold, then all pairs containing either *George Washington* or *President of the United States* are removed from the corresponding training and validation data.⁸ Leave-one-out evaluation, as chosen by Roller and Erk (2016), would have increased computational load substantially.

2.4 Distributional Space

For the analysis and experiments below, we represent both entities and categories in terms of their Google News embeddings (Mikolov et al. 2013). Mikolov et al.'s space constitutes, to our knowledge, the largest existing source for entity embeddings. The space consists of about 1.4 million 1000-dimensional embeddings whose targets are drawn from FreeBase (Bollacker et al. 2008). The embeddings were extracted from a 100 billion word Google news dataset using the Skip-gram algorithm (Mikolov et al. 2013). As mentioned above, the vast majority of these entries are entities; however, the space also models category-denoting nouns. By the definition of our data selection strategy, the space contains, for each entity, the category it instantiates. We rescale the embedding values column-wise so they lie within the [-1, 1] range.

We treat the embeddings as static, rather than optimizing them for the task at hand, because we are interested in the geometric structures present in a generic word meaning space, following the rationale of the Distributional Memory (Baroni and Lenci 2010). Moreover, optimizing the vectors might overfit on the instantiation relation on our relatively small dataset.

3. Exploratory Data Analysis

We perform exploratory data analysis on the positive portion of our dataset (Section 2.1) to understand the properties of entities vs. categories in distributional space. We ask the following questions: 1) Are entities and categories represented distinctly in distributional space? (following up on Boleda, Gupta, and Padó (2017)); and, 2) What is the relationship between entities and their corresponding categories?

⁸ We choose the number of test folds so that the average size of the training set after removing the lexical overlap is 90% of the original training data (fewer, and therefore larger, test folds lead to more excluded training data). This results in 83 test folds.

3.1 Instances and Concepts in Space

Figures 2a and 2b represent the first two dimensions of a Principal Component Analysis (PCA) transformation of the original 1000-dimensional embeddings. Figure 2a shows that, while entities and categories are not in distinct (or even linearly separable) regions of this reduced space, categories (purple triangles) are concentrated in the middle region of the graph, creating a radial structure. This constitutes initial evidence of the distinction between entities and categories in distributional space.

Figure 2b shows that the data is also sensitive to ontological distinctions such as those encoded in WordNet (see Table 1, Section 2). The figure shows a clear division between animate (*person*, left) and inanimate entities/categories (*location* and *object*, right; although these two classes largely overlap, *object* is more concentrated in the upper right part and *location* in the lower right part). In the middle, partially overlapping with the classes above, we find the smaller classes *artifact*, *act* (human-centered events), and *communication*, as well as the catch-all *other* class.

A clustering analysis supports these findings. We use the standard *k-means* algorithm to compute clustering solutions with 2 to 15 clusters and analyze results against the entity/category axis as well as WordNet ontological classes.⁹ Figure 3a shows a representative selection of clustering solutions along with the distribution of entities and categories for each of the clusters within a solution. They range from 4 clusters at the top left to 11 clusters at the bottom right.

The figure shows a similar trend to Figure 2a: On the one hand, the clustering algorithm does not use the division between entities and categories as its primary organizing principle for cluster solutions, especially not with a small numbers of clusters (we will see below that it uses the animate/inanimate division); on the other, for solutions with a higher number of clusters, categories tend to group together in a single cluster (cluster 3 in clustering solution 6 or CS6 as well as CS10, cluster 0 in CS7 and CS11, cluster 1 in CS8). This is consistently found in all solutions with higher number of clusters (not shown). This 'conceptual cluster' is mainly a concentration of *person* categories which reflect professional/societal roles, like *musician*, *physicist*, *minister*, *king*, *environmentalist*, *engineer*, *artist*, etc. Note that this cluster also contains many entities; they are related to these categories.

Figure 3b presents the same 6 clustering solutions, this time showing the distribution of the WordNet ontological classes. As could be expected, the animate/inanimate distinction appears prominently: Clusters 0 and 3 in CS4 contain most *object* and *location* datapoints, whereas clusters 1 and 2 contain most *person* datapoints. However, while the *person/location/object* distinction is relevant throughout the clustering solutions, we do not see a clear mapping between clusters and ontological classes in general. Manual inspection reveals the relevance of topical distinctions, with clusters partitioned by differences like American vs. Eurasian locations (see Table 3).

To sum up, both the PCA reduction and the clustering analysis suggest the primacy of ontological and topical dimensions in distributional space, at the same time suggesting a role for the entity/category axis, as categories tend to cluster together (also see next subsection).

⁹ Since the centroid seeds are randomly initialized, the algorithm is run 10 times with different seeds and the model with the best performance in terms of inertia is selected. The number of iterations for each model run is set to a maximum of 10000 with convergence at tolerance value of 1.0.

Instantiation



Figure 2: Exploratory data analysis

(a) Entities and categories in distributional space, first two PCA dimensions.

(b) Ontological classes





Figure 3: Representative clustering solutions.

(a) Distribution of entities vs. categories.

A. Gupta, G. Boleda, S. Padó

Instantiation

Clustering	person	location	object
6 clusters	0: Political, Academics, Science and other professions	2: American	2: American
	3: Historical and Religious 4: Writers 5: Musicians, Composers and Painters	6: Eurasia	6: Eurasia
11 clusters	 Political and Science Composers Writers Astronomers Historical and Religious Explorers Painters Musicians, other professions 	2: America 7: Eurasia	4: Astronomy 5: Larger Geography - (Seas, Oceans, Islands, Continents, Countries) 8: Small Geography - (Rivers, Canals, Parks)

Table 3: Prominent themes in representative clustering solutions (from manual analysis).

3.2 Categories: Concept vs. Centroid-based Representation

The above analysis suggests that entities and categories live in somewhat different parts of the space and that there is no simple relationship between entities and the categories they instantiate. This observation motivates a departure from a *concept*-based representation of categories based on the occurrences of the noun denoting the category (e.g., *scientist*). We experiment with an alternative representation of categories, namely the *centroid* of the entities that instantiate the category: *Madame Curie, Einstein, Lavoisier, Mendel*, etc. A centroid is a dimension-wise average vector, so if computed over entities of the same category it can be expected to represent that category, smoothing out idiosyncracies of particular instances. This representation resonates with two classical models in Cognitive Science: On the one hand, exemplar models (Nosofsky 1986), because it bases categories on specific instances; on the other, prototype theory (Rosch 1975), as the centroid can also be seen as a prototype because of the "smoothing out" effect (see Murphy (2002) for discussion). Both have demonstrated desirable properties in Machine Learning and NLP studies (Jäkel, Schölkopf, and Wichmann 2008; Reisinger and Mooney 2010).

For our dataset, Table 4 shows that the centroid-based representation appears to be promisingly well-behaved. While the average similarity of each entity to its category is 0.16 (e.g. *Madame Curie - scientist*), the average inter-entity similarity within categories is 0.22 (*Madame Curie - Einstein, Mendel, ...*).¹⁰ This means that distributional representations of entities belonging to a certain category are more similar to each other than to the common noun denoting the category they all instantiate. Moreover, the fact that the average similarity between centroids and categories is higher than between entities and their categories (0.29 vs. 0.16) suggests that centroids make good category representations,

¹⁰ The similarity to the centroid is 0.55; a high similarity is to be expected here simply from the definition of centroid.

Table 4: Cosine similarities across and within categories (means and standard deviations). "Across-categories" compares an entity/category to all other entities/categories: *Madame Curie* vs. *George Washington, Einstein, Mumbai, Nile,* etc., and *scientist* vs. *president of the United States, city, river,* etc. "Within-categories" restricts comparison to a single category: *Madame Curie* vs. *Einstein, Mendel,* etc.

	Across-categories	Within-categories
Entities	0.05 (0.07)	0.22 (0.11)
Categories	0.06 (0.06)	-
Centroids	0.20 (0.12)	-
Entity-Category	0.04 (0.05)	0.16 (0.09)
Entity-Centroid	0.10 (0.09)	0.55 (0.11)
Category-Centroid	0.08 (0.07)	0.29 (0.14)

Figure 4: Entities, centroid embeddings, and common noun embeddings for categories *patriarch* and *geneticist*.



indeed smoothing out idiosyncratic differences between the entities as expected. Figure 4 illustrates this, showing a PCA reduced representation of categories *patriarch* and *geneticist*. The entity embeddings are shown as small dots, linked to their respective category centroids (shown as red stars). The category embeddings are shown as large dots. We see that not only are the common noun embeddings marginal in terms of the overall data distribution, they are in fact more similar to the other categories' entities than to their own.

These results motivate Experiment 2 in Section 5, where we show that the benefits of centroid-based representations carry over to the actual task of instantiation classification.

Instantiation

4. Experiment 1: Instantiation Detection as Classification

We frame instantiation detection as a supervised binary classification task. The model needs to decide, given an entity-category pair as input, whether there is an instantiation relation between the entity and the category.

4.1 Evaluation

We use F_1 -score on the positive data samples as our evaluation measure.¹¹ We compute F_1 -scores on individual folds and micro-average them (the difference between micro and macro average is negligible in our case, due to the equal number of datapoints in each test fold; see Section 2.3).

4.2 Models

We test two generic model architectures. The first one is a simple logistic regression (LR) classifier. The second one is a feed-forward neural network (NN) classifier. ¹² The input and output of both classifiers are identical: for each datapoint (i.e., an *entity–category* pair (e, c)), the input is a function of the two embeddings, $f(\vec{e}, \vec{c})$. For the moment, we only consider concatenation (*Conc*): $f(\vec{e}, \vec{c}) = \langle e_1, \ldots, e_n, c_1, \ldots, c_n \rangle$; in Section 4.5 we will consider the difference between the vectors. The output is a binary value indicating whether the entity e instantiates the category c.

We choose LR and NN for their comparability: The LR classifier has no hidden layers, thus treating all features as independent, while the NN model introduces hidden layers that can model non-linear relationships between input and output and facilitates interactive behavior between the input features. This setup allows us to gauge to what extent these aspects affect instantiation while staying within the same general modeling framework. For the NN classifier, we experimented with 1-4 hidden layers but found a decline in model performance from 3 layers onwards. Hence, we report results only on the architectures with one hidden layer (NN-1HL) and two hidden layers (NN-2HL).

Model Optimization. We use mean cross-entropy as loss function and *softmax* as activation function for the output layer. All hidden layers use *tanh* as activation function. The number of units in each hidden layer of the NN models is optimized for each model separately. We consider the following values: 5, 10, 50–800 (step size 50). All models are trained using Adadelta optimization (Zeiler 2012) to a maximum of 2000 epochs with early stopping (we found that models typically converge at 50–100 epochs). To reduce overfitting, we introduce a dropout layer in front of each hidden layer with a standard dropout value of 0.5 (Baldi and Sandowski 2013).¹³

Baselines. We consider two baselines. A frequency baseline (BL_{freq}) assigns the positive class randomly with the true class probability (50% for the balanced variants and 25% for the union variants). We do not consider a most frequent class baseline, because this baseline would not make any positive predictions on the union variants, where

¹¹ While accuracy would be a simple alternative evaluation measure on the balanced variants of our dataset (Pos+*NotInst-inClass*, Pos+*NotInst-global*, Pos+*Inst2Inst*, Pos+*Inverse*), F₁ generalizes well to minority-class setups like Pos+*Union-inClass*, Pos+*Union-global*.

¹² The NN classifiers were built with the Keras toolkit, https://keras.io

¹³ We experimented with additional L₂ weight regularization but did not find any benefits.

Dataset	BL _{freq}	BL _{pos}	LR	NN-1HL	NN-2HL
Pos + Inverse	0.50	0.67	0.96	0.96	0.96
Pos + Inst2Inst	0.50	0.67	0.90	0.91	0.91
Pos + NotInst-global	0.50	0.67	0.55	0.85	0.82
Pos + NotInst-inClass	0.50	0.67	0.55	0.70	0.69
Pos + Union-global Pos + Union-inClass	0.25 0.25	0.40 0.40	0.55 0.55	0.75 0.57	0.76 0.63

Table 5: F₁ scores for instantiation detection, concatenated embeddings.

the negative class is dominant. Instead, we consider a baseline that *always* assigns the positive class (BL_{pos}). This baseline should show strong results in our evaluation scheme (F_1 score on positive class) since it always yields a perfect recall.

4.3 Main results

Table 5 reports the main results for the three models and the baselines. The top part of the table lists results for the balanced dataset variants, all of which have a positive class baseline of 0.67. The bottom part shows results for the *Union* variants, where the positive class is now a minority class, with a correspondingly lower positive class baseline of 0.40. The dataset variants are arranged in their expected level of increasing difficulty in classification from top to bottom. Indeed, we see a clear trend of decreasing F-Scores. Since the first two types of negative examples (*Inverse* and *Inst2Inst*) can be classified correctly solely by learning to distinguish categories and entities, we concur with Boleda, Gupta, and Padó (2017) that the high-level distinction between categories and entities can be made quite easily with standard embeddings.

In contrast, *NotInst* (the setup where the confounders are also *entity–category* pairs, just not ones that exemplify the instantiation relation, like *Madame Curie - lawyer*) is a quite difficult setup for which the scores decrease markedly. Thus, it is the presence or absence of the specific instantiation relationship, over and above the general 'type signature', that is difficult to determine. In line with this interpretation, we see that for *NotInst* and *Union*, the *inClass* variants, where the confounders are more semantically similar to the correct answers, are much harder than the *global* variants, with models outperforming the baseline by at most 3 points (0.70 vs. 0.67).

LR beats the baseline for *Inverse* and *Inst2Inst* but not for *NotInst* or the *Union* variants. The failure of LR – a linear classifier – to properly learn instantiation is in line with the observations by Roller and Erk (2016) and Levy et al. (2015), who found that linear classifiers are generally unable to learn semantic relations from vanilla embeddings.

In contrast, the NN models beat the baseline for all variants, even though they also see a decrease in performance for the harder variants. The benefit of the NN architecture compared to LR correlates strongly with the difficulty of the task: For the easiest *Inverse* and *Inst2Inst* variants, LR and NN perform at par, while the hard *NotInst* cases see differences of more than 10 and 30 percent, respectively.

The two NN models perform similarly. On the easiest variants (*Inverse* and *Inst2Inst*), both models do equally well. The model with one hidden layer performs better on the balanced *NotInst* variants but is beaten by the two-layer model on the *Union* variants. This

indicates that the combination of different confounders calls for a model that can perform substantial transformations of the feature space. Note also that all models perform worse on the *Union* variants than the average of their performances on the individual variants, indicating that the different kinds of confounders call for different transformations from the input through the hidden layers. In the remainder of this section we focus on the neural network model with two hidden layers because it is the best on the hardest variants.

4.4 Error Analysis

An error analysis of the predictions made by our best model, NN-2HL, shows that most errors stem from *semantic relatedness*, which is a well known problem of distributional semantics (Radovanović, Nanopoulos, and Ivanović 2010; Baroni and Lenci 2011).

More concretely, we find two distinct linguistic phenomena leading to errors affecting categories and two phenomena affecting entities. The first problematic phenomenon for categories is conceptual similarity. For example, *Edna Ferber*, a *writer*, is also predicted to be a *composer*, probably due to the similarities between the two artistic occupations (compare the use of English *to compose* for the production of both text and of music). The second problematic phenomenon is association. For example, the *Cheshire Cat* from the book *Alice in Wonderland* is correctly recognized as a *fictional character*, but it is also wrongly predicted to be a *writer*, presumably because it is often discussed in the context of literature and literary theory.

As for entities, the first source of errors is referential ambiguity: While many names are unambiguous when given in their full form, texts often use abbreviated versions that can refer to multiple entities (remember our earlier *Washington* example: the person, the state, or the city). For some names, even the full form is ambiguous, like for *Albert Smith*, the name of various politicians, cricketers and footballers. In the absence of large-scale reliable co-reference resolution and entity linking methods, researchers need to resort to heuristics to map corpus occurrences onto concrete entities, and wrong decisions result in biased embeddings. This type of error is analogous to the pervasive issue of ambiguity in lexical semantics (Cruse 1986), though from a referential perspective. Occasionally, this problem also spills over into the category domain: When frequent entity names include the category name (*gulf – Gulf of Patras*), the embedding for the category term *gulf* may be biased by occurrences that are really parts of entity names.¹⁴

The second source of errors for entities is *changes in the world over time*. For example, *Stagira* was a city in ancient Greece, and is recorded as such in WordNet. It was however not predicted as such, presumably because the newswire texts underlying the embeddings only refer to it as a ruins or more generally as a historical site. Similarly, *Etruria* used to be an independent *country* in pre-Roman times, but is not predicted to be a country, probably due to the predominance of occurrences related to when it was a region of the Roman empire. Thus, for entities we find a strong effect of referential aspects of meaning, which are understudied in Computational Linguistics and Linguistics (McNally and Boleda 2017).

Occasionally, we also encountered errors due to missing relational information in WordNet. For example, *Richard Brinsley Sheridan* was both a *playwright* and a British

¹⁴ Recall from Section 2 that our vocabulary is lowercased. For English, this problem could be alleviated by not lowercasing, which however introduces large amounts of wrong ambiguity. For languages which capitalize all nouns, such as German, or logogrammatic writing systems such as Chinese, the problem persists even when lowercasing.

Table 6: Effects of input function (concatenation vs.	difference) on F	l score for best r	nodel
(NN-2HL).				

Dataset	Conc	Diff
Pos + Inverse	0.96	0.97
Pos + Inst2Inst	0.91	0.91
Pos + NotInst-global	0.82	0.82
Pos + NotInst-inClass	0.69	0.72
Pos + Union-global	0.76	0.75
Pos + Union-inClass	0.63	0.67

member of parliament, i.e., a *politician*. Only the former relation appears in WordNet, but our model predicts also the second. Similarly, *Yalta* is only listed as a resort *city* on the Black Sea in WordNet, but our classifier adds the information that it is a *port*. These observations are in line with the known incompleteness of knowledge bases and the usefulness of distributional methods to complete them (Min et al. 2013).

4.5 Effect of input representations

We next test a different function to combine the representations of the two input elements. Above, we only considered concatenation, which enables the model to freely combine the information of the two embeddings, but does not make the dimension-wise correspondence between them explicit. We now use the difference function (*Diff*), defined as $f(\vec{e}, \vec{c}) = \langle e_1 - c_1, \ldots, e_n - c_n \rangle$. This representation, inspired by Mikolov et al. (2013) and Roller, Erk, and Boleda (2014), explicitly links the information in the input pair by dimension. Thus, the difference input provides the model with a clearer notion of how the category and entity embeddings are located *relative* to one another, at the loss of their *absolute* positions in embedding space. Note also that *Conc* produces 2,000-dimensional while *Diff* produces only 1,000-dimensional input embeddings.

As Table 6 shows, the input representation does not play a major role. Results across variants are generally very close, with one exception: *Diff* yields better results for the *inClass* variants, which are the most difficult. This could be due to an advantage of the *Diff* embeddings for the case of highly similar confounders: While *Conc* also contains the necessary information to make the decision, this information is distributed over components in the embeddings whose correspondences by dimension the model must recover.

4.6 Impact of Memorization

Section 2.3 discussed our strategy to counteract possible memorization effects. This section demonstrates that memorization issues, identified in previous literature for hypernymy detection (Roller and Erk 2016), affect instantiation as well. Table 7 shows the results of Experiment 1 with our filtering (same as above; left column) and without counter-memorization filtering (middle column), as well as the difference in results between the two set-ups (right column). Recall from above that the counter-memorization

Instantiation

Dataset	Filtering	No filtering	Δ
Pos + Inverse	0.96	0.98	0.02
Pos + Inst2Inst	0.91	0.99	0.08
Pos + NotInst-global	0.82	0.90	0.08
Pos + NotInst-inClass	0.69	0.83	0.14
Pos + Union-global Pos + Union-inClass	0.76 0.63	0.89 0.81	0.13 0.18

Table 7: Effects of memorization on F₁ score for best model (NN-2HL).

filtering removes all lexical overlap between the test set and the training and validation sets. Therefore, models are not asked to learn from *Einstein - scientist* and then generalize to *Mendel - scientist* or *Einstein - physicist*, but to learn from certain categories and entities and then generalize to completely unseen categories and entities.

It is therefore not surplising that without the filtering the model achieves substantially higher scores (between 2 and 18% increase), which are arguably the result of learning which concepts make good categories in general or the specific relationship between certain categories and the entities that instantiate them.

5. Experiment 2: Entity-Based vs. Concept-Based Instantiation Detection

Experiment 2 is motivated by the results of the analysis in Section 3, namely that the entity embeddings of a category tend to form a cloud in space, but that the corresponding category embedding, when computed as a *concept embedding* from occurrences of the noun denoting the category, is often located further away. Experiment 1 has demonstrated that it is possible to learn instantiation to some extent based on the entity and category embeddings. At the same time, the fact that the best performance came from a network with two hidden layers and especially the difficulty of the model dealing with *NotInst* confounders shows that it is a rather challenging task. The purpose of Experiment 2 is to test whether *centroid-based embeddings*, as defined in Section 3.2, make learning easier.

5.1 Experimental Setup

For Experiment 2 we cannot use exactly the same dataset as in Experiment 1, since some categories have a very small number of entities. We filter out all categories with less than 5 entities. This reduces the original set of 577 categories to 159 categories.¹⁵

We train and evaluate the same models as in Experiment 1 on the reduced dataset (using the same anti-memorization methodology and hyperparameters), with either concept-based or centroid-based embeddings for categories. The concept-based embeddings are the same as in Experiment 2. As for centroid embeddings, they are constructed as the average of all entity embeddings for this category *in the training set*. Recall that the construction of our datasets (Section 2 ensures that train, development, and test sets are disjoint. Thus, for each entity in the test set, it is guaranteed that its embedding was not used in the construction of any centroid embedding. Also, the centroid-based embedding

¹⁵ This dataset is also available at

http://www.ims.uni-stuttgart.de/data/Instantiation.html.

		Concept-based		Centroi	d-based
Dataset	BL _{Pos}	NN-1HL	NN-2HL	NN-1HL	NN-2HL
Pos + Inverse	0.67	0.98	0.97	0.98	0.94
Pos + Inst2Inst	0.67	0.90	0.91	0.91	0.86
Pos + NotInst-global	0.67	0.85	0.84	0.90	0.89
Pos + NotInst-inClass	0.67	0.71	0.67	0.79	0.75
Pos + Union-global	0.40	0.73	0.76	0.84	0.76
Pos + Union-inClass	0.40	0.51	0.65	0.76	0.67

Table 8: F_1 scores for instantiation detection, concept-based vs. centroid-based category representation (concatenated input). These results are computed on the 159 categories with at least 5 entities.

approach, exactly like the concept-based embedding approach, uses embedding as the representation for the category that does not change across folds. Thus, we believe that this setup is as robust to memorization issues as is the concept-based setup.

5.2 Results

Table 8 shows the results. We focus on the two neural network models, which performed well in Experiment 1. The positive class baseline performs as before, since the class distributions do not change. The results using a concept-based embedding to represent categories (middle columns) can be compared with the corresponding numbers in Table 5. The results are rather similar, around 1–2% higher than before. This indicates that the reduced dataset is comparable in difficulty to the original dataset from Experiment 1.

Comparing to the centroid-based approach (right-hand columns), we see that the centroid-based approach does equally well or outperforms the concept-based one on all variants. A notable difference from Experiment 1 is that this time the neural network with a single hidden layer performs best (see column NN-1HL), consistently across all variants. We take this as evidence that the centroid-based representation requires less transformation of the input, compared to the concept-based representation. This is consistent with the analysis in Section 3, which showed that entities are closer in space to their category centroid than to category-denoting nouns.

As for the different variants, Table 8 shows that the centroid-based representation confers gains only for the hardest variants. On *Inverse* and *Inst2Inst*, we obtain the same performance, which makes sense because these variants require the model to distinguish between entities and categories and deal with similarity as a confounder. The centroid-based representation does not provide further help in this case, presumably for the same reason as above (categories are more different than entities in the concept-based representation, so it's easier to distinguish them from entities in the latter case). It is however noteworthy that it doesn't harm results either.

In contrast, representing categories as centroids of entities yields big gains for the *NotInst* and *Union* cases. *NotInst-global* and *Union-global* reach 0.90 and 0.84 performance, respectively, making them almost comparable to the easier settings (*Inverse* and *Inst2Inst* have 0.98 and 0.91 F-score). The hardest setups, *NotInst-inClass* and *Union-inClass*, improve by 8 and 11 points to 0.79 and 0.76 F-score, respectively.

A. Gupta, G. Boleda, S. Padó

We conclude that, in our setup, recovering the instantiation relation is much easier from centroid-based representations than from concept-based representations.

6. Related Work

Distributional Semantics, Lexical Relations, Entities. Distributional representations of word meaning have been used widely to address various linguistic phenomena in computational linguistics (Lenci 2008; Turney and Pantel 2010; Baroni and Lenci 2011). These include paradigmatic relations like synonym (Landauer and Dumais 1997) as well as syntagmatic relations like predicate-argument relations (Erk, Padó, and Padó 2010; Baroni and Lenci 2010), or relations within noun compounds (Moldovan et al. 2004)

Among individual lexical relations, hypernymy plays a prominent role. It was among the first relations to be acquired computationally by Hearst (1992), although with a pattern-based approach (see Roller and Erk (2016) for a recent study combining both approaches). There is a comprehensive body of work on distributional modeling of hypernymy (Baroni and Lenci 2011; Lenci and Benotto 2012; Roller, Erk, and Boleda 2014; Santus et al. 2014; Shwartz, Goldberg, and Dagan 2016). Hypernymy is arguably popular because it plays a critical role in many NLP tasks such as lexical entailment (Geffet and Dagan 2005; Vulić et al. 2017), taxonomy detection (Shwartz, Santus, and Schlechtweg 2017), question-answering (Huang, Thint, and Qin 2008) and cross-lingual inference detection (Upadhyay et al. 2018). However, almost all computational linguistic work on semantic relations focuses on "classical" lexical relations that hold between categories. In contrast, there is hardly any work specifically on the distributional representation of entities. These which the exception of Herbelot (2015) which analyses the properties specifically of distributional representations of person names extracted from novels, as well as our own previous work on extracting entity attributes (Gupta et al. 2015; Gupta, Boleda, and Padó 2017) and on instantiation (Boleda, Gupta, and Padó 2017).

Knowledge Base Population and Completion. A largely separate line of research, pursued in the semantic web and machine learning communities, has evolved around the use of structured knowledge from knowledge bases. NLP applications such as Question Answering have been attracted by the potential of such knowledge bases to provide factual and world knowledge about relations among categories and entities that is arguably necessary for many NLP tasks such as question answering or semantic inference. This line of research has seen a huge boost in the last ten years with the availability of large structured knowledge sources like Wikipedia, DBPedia (Auer et al. 2007), Freebase (Bollacker et al. 2008) or Yago (Suchanek, Kasneci, and Weikum 2007). However, even very large knowledge sources are known to suffer from incomplete coverage (Min et al. 2013). Therefore, the automatic extension and updating of such resources on the basis of textual information (known as knowledge base population and completion) has formed its own research area within which distributional representation play a prominent role.

Freitas et al. (2012) discuss the applicability of using distributional representations for question-answering systems on large-scale commonsense knowledge bases. Socher et al. (2013) subsequently show that performance of relational querying models improves when entities are represented as an average of their constituting word representations built from unsupervised large-scale corpora. Bordes et al. (2013) use such distributional representations to indentify the connectivity patterns between entities in a multi-relational learning setup on knowledge bases to link entities and predict new relations, while Freitas et al. (2014) introduce a complementary distributional semantic layer to cope with semantic approximation and incompleteness of common-sense information.

Basile et al. (2016) populate object-location relations in a knowledge-base by computing the prototypicality between objects and locations extracted from text.

In recent times, the focus has shifted towards constructing optimized embeddings for task specific application. Link prediction - connecting two entities through a binary relation, is a popular evaluation setup for such embeddings. Toutanova et al. (2015) jointly learn continuous representations for entities and textual relations, Nickel, Rosasco, and Poggio (2016) use distributional representations to generate optimized Holographic embeddings to generate compostional embeddings of binary relational data and, Trouillon et al. (2017) demonstrate that complex embeddings are more optimized as compared to real valued embeddings for link prediction. The underlying objective for all of the above is to find expressive yet generalized representations which can cope with the ever increasing scalability challenges within the scope of this research area. The gap that we see in this line of research is that it typically induces task-specific embeddings that optimize the performance on the task at hand, while we consider vanilla embeddings as they fall out of the corpus in the spirit of a generic 'distributional memory' (Baroni and Lenci 2010). In addition, it is typically evaluated in terms of total performance across all relations and rarely provides in-depth analyses of individual relations like instantiation. In contrast, we follow a recently emerged direction of research that specifically aims at a better understanding of the nature and structure of information that is encoded within such representations (Lin et al. 2015; Herbelot and Vecchi 2015; Gupta et al. 2015; Xie et al. 2016; Beltagy et al. 2016).

Named Entity Recognition and Classification. Named Entity Recognizion (NER) deals with the identification of named entities in running and is typically combined with a classification (NEC) of these entities into categories. Not surprisingly, distributional representations have found a steady place in both NER and NEC (Xiao and Guo 2014; Gouws and Søgaard 2015; Moreno, Romá-Ferri, and Moreda 2017).

Traditionally, the recognized categories are rather coarse-grained (e.g., location, person, organization, other); however, there is a tendency towards more fine-grained named entity classification. Ling and Weld (2012) were among the first studies in this direction, performing NEC on a set of 112 classes. Abhishek and Awekar (2017) and Shimaoka et al. (2017) present neural architectures for fine-grained NEC applied to between 47 and 128 classes.

Our setup is somewhat similar to fine-grained NEC in that we also experiment with Named Entities within the bounds of a classification setup. However, our set of 577 classes is considerably larger than those normally considered in fine-grained NEC. We also ask our models not to disambiguate corpus occurrences of named entities in context, but to assess pairs of entities and categories without context, just on the basis of embeddings for the entities. We believe that this tests the models' ability to acquire the range of possible categories for the entities.

7. Discussion and Conclusion

In this work, we have addressed the *instantiation* relation between entities and categories, which has received relatively little attention in linguistics, computational linguistics, and cognitive science. We started from the observation that the connection between the theoretical properties of instantiation (e.g., as set membership in formal semantics) and its practical operationalization in terms of data-driven meaning representations remains under-explored.

Building on a large body of previous work that has shown that distributional semantic representations are a reasonable proxy for conceptual aspects of meaning (Landauer and Dumais 1997; Baroni and Lenci 2010; Mikolov et al. 2013, among many others), and on much less work on distributed representations of entities that has also given encouraging results (Mikolov, Yih, and Zweig 2013; Herbelot 2015; Gupta et al. 2015), we have provided a systematic investigation of the potential of current distributed representations to capture instantiation. Our main contributions are the release of a comprehensive dataset for instantiation, which enables future work in this area, and the insights obtained through a set of computational analyses and experiments.

Our findings suggest that the general distinction between categories and entities, as represented in our data, is easy to recover from distributional representations, as a simple linear classifier performs very well in a variety of settings. In contrast, the instantiation relationship proper is much more difficult, particularly when using common nouns as the representation of categories and when the confounders come from a similar domain: Even with a supervised approach using non-linear combinations of features (a two-layer neural network classifier), when controling for memorization it is difficult to distinguish instantiation from mere semantic relatedness. The interference of semantic relatedness is common to lexical semantic phenomena such as synonymy, hypernymy, or meronymy, as identified in previous work (Baroni and Lenci 2011; Santus et al. 2014; Levy et al. 2015). An additional difficulty in our case is posed by referential aspects of meaning, such as the referential ambiguity of names and changes in the world over time.

Our experiments also contribute towards a better understanding of entities and categories as represented in distributional space. A result we did not anticipate is that our entity embeddings are much more compatible with centroid-based categories, a representation that bases the definition of the category on its instances, than with concept-based categories, or representations based on common nouns denoting categories. A possible confounder here is that our entity embeddings are obtained from names only (*George Washington, Oaxaca, Nile*); by design, other referential expressions are excluded, and it could be that our results are due to this design choice. In this case, the observed difference would be due to the difference in use between proper and common nouns, rather than between entities and categories represented as common nouns. Future work should examine this possibility further.

However, our results mesh well with previous work showing that the so-called Distributional Inclusion Hypothesis for hypernymy (Geffet and Dagan 2005) is not borne out for generic vectors (Roller, Erk, and Boleda 2014) – but see Chang et al. (2018) for a positive result on a task-optimized embedding space. In linguistics, hypernymy is traditionally represented in terms of set inclusion (all dogs, cats, spiders, etc. are animals, so *animal* is taken to denotes the superset of *dog*, *cat*, *spider*, etc.). Distributional representations are extracted from contexts of use; Geffet and Dagan (2005) translated the set inclusion treatment to distributional semantics, hypothesizing that the *contexts* of use of, e.g., animal, would be a superset of the context of use of its hyponyms, which would be mirrored in an inclusion relation in the dimensions of the respective distributed representations. However, this hypothesis did not hold up empirically, possibly because the word *animal* is actually used in different contexts than the union of its hypernyms. This result, as well as our own, suggests that the identification of common nouns and other content word with ontological categories, as has been explicitly or implicitly done in much work in e.g. formal semantics and Knowledge Representation, may not be warranted. Therefore, our results potentially speak to the broader issue of the relationship between nouns and other content words, on the one hand, and ontological categories, on the other. Elucidating this issue further seems like a fruitful avenue for future work.

Future work could also test whether the centroid-based representation is also useful for hypernymy detection: Based on our results and the considerations above, we would expect the average of the hyponyms to be a more useful representation of the category than the hypernym itself. Similarly, it should explore the practical implications of our results (if any) for Natural Language Processing tasks related to grounding language in the external world, such as Knowledge Base Population, various forms of Entity Linking, co-reference resolution, and Referential Expression Generation.

As for instantiation and entity representations, we need to move beyond the representation of entities via their names, and also towards "private" entities such as my neighbor or the bird I saw this morning (most work on entities in distributional semantics is on "public" entities such as George Washington or Nile; Boleda et al. (2017) is an exception). The problem here is twofold: On the one hand, distributional methods are extremely data-hungry, such that it is hard to build meaningful representations from small samples (this is an area of active research, see e.g. Herbelot and Baroni (2017)). On the other, current co-reference annotation tools are not reliable enough to build representations based on all types of referential expressions, as opposed to relying on names, which can be detected via surface cues. These are challenges that need addressing if we are to use distributional methods to better understand the relationship between entities and categories as expressed in language, and between language and cognition more generally.

Acknowledgments. AG and SP received funding from Deutsche Forschungsgemeinschaft (DFG) through Sonderforschungsbereich 732, project D10. GB received funding from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme (grant agreement No 715154), the Ramón y Cajal programme (grant RYC-2015-18907), and the Catalan government (SGR 2017 1575). We gratefully acknowledge the support of NVIDIA Corporation with the donation of GPUs used for this research. This paper reflects the authors' view only, and the EU is not responsible for any use that may be made of the information it contains.



References

- Abhishek, Ashish Anand and Amit Awekar. 2017. Fine-grained entity type classification by jointly learning representations and label embeddings. In *Proceedings of the Conference of the European Chapter of the Association for Computational Linguistics*, pages 797–807, Valencia, Spain.
- Alfonseca, Enrique and Suresh Manandhar. 2002. Distinguishing concepts and instances in WordNet. In Proceedings of the First International Conference of Global WordNet Association, Mysore, India.
- Auer, Sören, Christian Bizer, Georgi Kobilarov, Jens Lehmann, Richard Cyganiak, and Zachary Ives. 2007. Dbpedia: A nucleus for a web of open data. In *The semantic web*. Springer, pages 722–735.

- Baader, Franz. 2003. *The description logic handbook: Theory, implementation and applications*. Cambridge University Press.
- Baldi, Pierre and Peter Sandowski. 2013. Understanding dropout. In *Proceedings of Advances in Neural Information Processing Systems*, pages 2814–2822.
- Baroni, Marco and Alessandro Lenci. 2010. Distributional Memory: A General Framework for Corpus-Based Semantics. *Computational Linguistics*, 36(4):1–49.
- Baroni, Marco and Alessandro Lenci. 2011. How we blessed distributional semantic evaluation. In *Proceedings of the GEMS 2011 Workshop on GEometrical Models of Natural Language Semantics*, pages 1–10, Edinburgh, UK.
- Basile, Valerio, Soufian Jebbara, Elena Cabrio, and Philipp Cimiano. 2016. Populating a knowledge base with object-location

A. Gupta, G. Boleda, S. Padó

relations using distributional semantics. In *European Knowledge Acquisition Workshop*, pages 34–50.

- Beltagy, Islam, Stephen Roller, Pengxiang Cheng, Katrin Erk, and Raymond J Mooney. 2016. Representing meaning with a combination of logical and distributional models. *Computational Linguistics*, 42(4):763–808.
- Boleda, Gemma, Abhijeet Gupta, and Sebastian Padó. 2017. Instances and concepts in distributional space. In Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics, pages 79–85, Valencia, Spain.
- Boleda, Gemma, Sebastian Padó, Nghia The Pham, and Marco Baroni. 2017. Living a discrete life in a continuous world: Reference with distributed representations. In *Proceedings of the International Conference on Computational Semantics*, Montpellier, France.
- Bollacker, Kurt, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. 2008. Freebase: a collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD international conference on Management of data*, pages 1247–1250.
- Bordes, Antoine, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. 2013. Translating embeddings for modeling multi-relational data. In *Proceedings of Advances in neural information processing systems*, pages 2787–2795.
- Chang, Haw-Shiuan, Ziyun Wang, Luke Vilnis, and Andrew McCallum. 2018. Distributional inclusion vector embedding for unsupervised hypernymy detection. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics*, pages 485–495, New Orleans, LA.
- Cruse, D.A. 1986. *Lexical Semantics*. Cambridge Textbooks in Linguistics. Cambridge University Press.
- Curran, James. 2005. Supersense tagging of unknown nouns using semantic similarity. In Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics, pages 26–33, Ann Arbor, MI.
- Erk, Katrin, Sebastian Padó, and Ulrike Padó. 2010. A flexible, corpus-driven model of regular and inverse selectional preferences. *Computational Linguistics*, 36(4):723–763.
- Fellbaum, Christiane, editor. 1998. *WordNet* An Electronic Lexical Database. The MIT Press, Cambridge, MA; London.

- Freitas, André, Edward Curry, Joao Gabriel Oliveira, and Sean O'Riain. 2012. Querying heterogeneous datasets on the linked data web: challenges, approaches, and trends. *IEEE Internet Computing*, 16(1):24–33.
- Freitas, André, Joao Carlos Pereira da Silva, Edward Curry, and Paul Buitelaar. 2014. A distributional semantics approach for selective reasoning on commonsense graph knowledge bases. In *International Conference on Applications of Natural Language to Data Bases/Information Systems*, pages 21–32, Salford, UK.
- Gamut, L.T.F. 1991. Logic, Language, and Meaning. University of Chicago Press. Geeraerts, Dirk. 2010. Theories of Lexical
- Semantics. Oxford University Press.
- Geffet, Maayan and Ido Dagan. 2005. The distributional inclusion hypotheses and lexical entailment. In *Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics*, pages 107–114, Ann Arbor, MI.
- Gouws, Stephan and Anders Søgaard. 2015. Simple task-specific bilingual word embeddings. In *Proceedings of the Conference* of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 1386–1390.
- Gupta, Abhijeet, Gemma Boleda, Marco Baroni, and Sebastian Padó. 2015. Distributional vectors encode referential attributes. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 12–21, Lisbon, Portugal.
- Gupta, Abhijeet, Gemma Boleda, and Sebastian Padó. 2017. Distributed prediction of relations for entities: The easy, the difficult, and the impossible. In *Proceedings of the 6th Joint Conference on Lexical and Computational Semantics* (*STARSEM 2017*), pages 104–109. Hearst, Marti A. 1992. Automatic acquisition
- Hearst, Marti A. 1992. Automatic acquisition of hyponyms from large text corpora. In *Proceedings of the 14th conference on Computational linguistics-Volume 2*, pages 539–545.
- Herbelot, Aurélie. 2015. Mr Darcy and Mr Toad, Gentlemen: Distributional names and their kinds. In *Proceedings of the International Conference on Computational Semantics*, pages 151–161, Berlin, Germany.
- Herbelot, Aurélie and Marco Baroni. 2017. High-risk learning: acquiring new word vectors from tiny data. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 304–309,

Instantiation

Copenhagen, Denmark.

- Herbelot, Aurélie and Eva Maria Vecchi. 2015. Building a shared world: mapping distributional to model-theoretic semantic spaces. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 22–32, Lisbon, Portugal.
- Hitzler, Pascal, Markus Krotzsch, and Sebastian Rudolph. 2009. *Foundations of semantic web technologies*. CRC Press.
- Huang, Zhiheng, Marcus Thint, and Zengchang Qin. 2008. Question classification using head words and their hypernyms. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 927–936.
- Jäkel, Frank, Bernhard Schölkopf, and Felix Wichmann. 2008. Generalization and similarity in exemplar models of categorization: Insights from machine learning. *Psychonomic Bulletin & Review*, 15(2):256–271.
- Kamp, J A W. 1975. Two theories about adjectives. In E L Keenan, editor, *Formal Semantics of Natural Language*. Cambridge University Press, Cambridge, pages 123–155.
- Landauer, Thomas K and Susan T Dumais. 1997. A solution to Plato's problem: The latent semantic analysis theory of acquisition, induction, and representation of knowledge. *Psychological review*, 104(2):211.
- Lenat, Douglas. 1995. Cyc: A large-scale investment in knowledge infrastructure. *Communications of the ACM*, 11:33–38.
- Lenci, Alessandro. 2008. Distributional semantics in linguistic and cognitive research. *Italian journal of linguistics*, 20(1):1–31.
- Lenci, Alessandro and Giulia Benotto. 2012. Identifying hypernyms in distributional semantic spaces. In *Proceedings of the First Joint Conference on Lexical and Computational Semantics*, pages 75–79, Montreal, Canada.
- Levy, Omer, Steffen Remus, Chris Biemann, and Ido Dagan. 2015. Do supervised distributional methods really learn lexical inference relations? In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics*, pages 970–976, Denver, Colorado.
- Lin, Yankai, Zhiyuan Liu, Maosong Sun, Yang Liu, and Xuan Zhu. 2015. Learning entity and relation embeddings for knowledge graph completion. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 2181–2187, Austin, TX.

- Ling, Xiao and Daniel S. Weld. 2012. Fine-grained entity recognition. In Proceedings of the AAAI Conference on Artificial Intelligence, pages 94–100, Toronto Canada.
- McNally, Louise and Gemma Boleda. 2017. Conceptual vs. referential affordance in concept composition. In Yoad Winter and James Hampton, editors, *Compositionality and Concepts in Linguistics and Psychology*. Springer.
- Mikolov, Tomas, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. 2013. Distributed representations of words and phrases and their compositionality. In *Proceedings of Advances in Neural Information Processing Systems*, pages 3111–3119.
- Mikolov, Tomas, Wen-tau Yih, and Geoffrey Zweig. 2013. Linguistic Regularities in Continuous Space Word Representations. In Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 746–751, Atlanta, GA.
- Min, Bonan, Ralph Grishman, Li Wan, Chang Wang, and David Gondek. 2013. Distant supervision for relation extraction with an incomplete knowledge base. In *Proceedings* of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 777–782, Atlanta, Georgia.
- Moldovan, Dan, Adriana Badulescu, Marta Tatu, Daniel Antohe, and Roxana Girju. 2004. Models for the semantic classification of noun phrases. In *Proceedings of the HLT-NAACL Workshop on Computational Lexical Semantics*, pages 60–67.
- Moreno, Isabel, MT Romá-Ferri, and Paloma Moreda. 2017. Named entity classification based on profiles: a domain independent approach. In *International Conference on Applications of Natural Language to Information Systems*, pages 142–146.
- Murphy, Greogry L. 2002. The Big Book of Concepts. MIT Press.
- Neelakantan, Arvind and Ming-Wei Chang. 2015. Inferring missing entity type instances for knowledge base completion: New dataset and methods. In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics*, Denver, CO.
- Nickel, Maximilian, Lorenzo Rosasco, and Tomaso A Poggio. 2016. Holographic embeddings of knowledge graphs. In Proceedings of the AAAI Conference on Artificial Intelligence, pages 1955–1961, Phoenix, AZ.

A. Gupta, G. Boleda, S. Padó

- Niles, Ian and Adam Pease. 2001. Towards a standard upper ontology. In *Proceedings of the International Conference on Formal Ontology in Information Systems*, pages 2–9, Ogunquit, ME.
- Nosofsky, Robert M. 1986. Attention, similarity, and the identificationcategorization relationship. *Journal of Experimental Psychology General*, 115(1):39–61.
- Radovanović, Miloš, Alexandros Nanopoulos, and Mirjana Ivanović. 2010. Hubs in space: Popular nearest neighbors in high-dimensional data. *Journal of Machine Learning Research*, 11:2487–2531.
- Reisinger, Joseph and Raymond J. Mooney. 2010. Multi-prototype vector-space models of word meaning. In *Proceedings of the Annual Conference of the North American Chapter of the Association for Computational Linguistics*, pages 109–117, Los Angeles, CA.
- Rigau, German, Jordi Atserias, and Eneko Agirre. 1997. Combining unsupervised lexical knowledge methods for word sense disambiguation. In *Proceedings of the 35th Annual Meeting of the Association for Computational Linguistics*, pages 48–55, Madrid, Spain.
- Roller, Stephen and Katrin Erk. 2016. Relations such as hypernymy: Identifying and exploiting hearst patterns in distributional vectors for lexical entailment. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 2163–2172, Austin, Texas.
- Roller, Stephen, Katrin Erk, and Gemma Boleda. 2014. Inclusive yet selective: Supervised distributional hypernymy detection. In *Proceedings of the 25th International Conference on Computational Linguistics*, pages 1025–1036, Dublin, Ireland.
- Rosch, Eleanor. 1975. Cognitive representations of semantic categories. *Journal of Experimental Psychology: General*, 104:192–233.
- Santus, Enrico, Alessandro Lenci, Qin Lu, and Sabine Schulte im Walde. 2014. Chasing hypernyms in vector spaces with entropy. In Proceedings of the Conference of the European Chapter of the Association for Computational Linguistics, pages 38–42, Gothenburg, Sweden.
- Sassoon, Galit Weidman. 2013. Vagueness, gradability and typicality: The interpretation of adjectives and nouns. Brill.
- Shimaoka, Sonse, Pontus Stenetorp, Kentaro Inui, and Sebastian Riedel. 2017. Neural

- architectures for fine-grained entity type classification. In *Proceedings of the Conference of the European Chapter of the Association for Computational Linguistics*, pages 1271–1280, Valencia, Spain.
- Shwartz, Vered, Yoav Goldberg, and Ido Dagan. 2016. Improving hypernymy detection with an integrated path-based and distributional method. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, pages 2389–2398, Berlin, Germany.
- Shwartz, Vered, Enrico Santus, and Dominik Schlechtweg. 2017. Hypernyms under siege: Linguistically-motivated artillery for hypernymy detection. In Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics, pages 65–75.
- Socher, Richard, Danqi Chen, Christopher D Manning, and Andrew Ng. 2013. Reasoning with neural tensor networks for knowledge base completion. In *Proceedings* of Advances in Neural Information Processing Systems, pages 926–934.
- Suchanek, Fabian M, Gjergji Kasneci, and Gerhard Weikum. 2007. Yago: a core of semantic knowledge. In Proceedings of the 16th international conference on World Wide Web, pages 697–706, Calgary, Canada.
- Textor, Mark. 2011. (Frege On) Sense and Reference. In Claudia Maienborn, Klaus von Heusinger, and Paul Portner, editors, *Semantics: An International Handbook of Natural Language Meaning*, volume 1. De Gruyter, pages 25–49.
- Toutanova, Kristina, Danqi Chen, Patrick Pantel, Hoifung Poon, Pallavi Choudhury, and Michael Gamon. 2015. Representing text for joint embedding of text and knowledge bases. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 1499–1509, Lisbon, Portugal.
- Trouillon, Théo, Christopher R Dance, Éric Gaussier, Johannes Welbl, Sebastian Riedel, and Guillaume Bouchard. 2017.
 Knowledge graph completion via complex tensor factorization. *The Journal of Machine Learning Research*, 18(1):4735–4772.
- Turney, Peter D. and Patrick Pantel. 2010. From Frequency to Meaning: Vector Space Models of Semantics. *Journal of Artificial Intelligence Research*, 37(1):141–188.
- Upadhyay, Shyam, Yogarshi Vyas, Marine Carpuat, and Dan Roth. 2018. Robust cross-lingual hypernymy detection using dependency context. In *Proceedings of the Conference of the North American Chapter of*

Instantiation

Volume 1, Number 1

the Association for Computational Linguistics, pages 607–618, New Orleans, LA.

- Vulić, Ivan, Daniela Gerz, Douwe Kiela, Felix Hill, and Anna Korhonen. 2017. Hyperlex: A large-scale evaluation of graded lexical entailment. *Computational Linguistics*, 43(4):781–835.
- Xiao, Min and Yuhong Guo. 2014. Distributed word representation learning for cross-lingual dependency parsing. In *Proceedings of the Conference on Computational Natural Language Learning*, pages 119–129, Baltimore, MD.
- Xie, Ruobing, Zhiyuan Liu, Jia Jia, Huanbo Luan, and Maosong Sun. 2016. Representation learning of knowledge graphs with entity descriptions. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 2659–2665, Phoenix, AZ.
- Zeiler, Matthew D. 2012. Adadelta: An adaptive learning rate method. In *CoRR*, *abs*/1212.5701.