Embedding Grammars

David Wingate

wingated@cs.byu.edu

Nancy Fulda

nfulda@byu.edu

Abstract

Classic grammars and regular expressions can be used for a variety of purposes, including parsing, intent detection, and However, the comparisons matching. are performed at a structural level, with constituent elements (words or characters) matched exactly. Recent advances in word embeddings show that semantically related words share common features in a vector-space representation, suggesting the possibility of a hybrid grammar and word embedding. In this paper, we blend the structure of standard context-free grammars with the semantic generalization capabilities of word embeddings to create hybrid semantic grammars. These semantic grammars generalize the specific terminals used by the programmer to other words and phrases with related meanings, allowing the construction of compact grammars that match an entire region of the vector space rather than matching specific elements.

1 Introduction

Consider the problem of intent detection for natural language processing: to estimate intent, a natural language sentence must be analyzed to determine the underlying goal of the speaker. Ideally, such analysis would be insensitive to the specific words and phrases used, implying the need for a general semantic metric for equivalence.

One way to approach this problem would be to craft a simple rule—say, a regular expression—that describes a set of semantic equivalences. A regex for detecting an intent to deliver a compliment might resemble the following:

William Myers

mwilliammyers@byu.edu

Tyler Etchart

tyler.etchart@byu.edu

(i think)? (you're|you are)
 (beautiful|gorgeous|cute)

This would match sentences such as I think you are beautiful, you are cute, and you're gorgeous. However, the ability of this regex to match input sentences is limited by the mental lexicon of the regex designer. What the designer intended was to match any phrase that could be construed as a compliment regarding the auditor's general physical appearance, but the produced regex provides only a compact set of examples. The regex does not include all possible synonyms for beautiful, and so it would not, for example, match the sentence I think you are lovely. The power of grammars and regular expressions lie in the compact and efficient representation of combinatorially large sets of sentences, but it is always assumed that terminal matches must be exact. Here, we relax that assumption.

This paper sketches out how to combine the strengths of context-free grammars with the generalization capability of word embeddings to create semantic regular expressions. The grammar provides the coarse overall structure, but individual tokens serve primarily as exemplars that define a region in a word embedding feature space. Any token whose feature representation lies within this region is considered a match. The result is semantic, rather than structural expression evaluation.

2 Background

Word embeddings (Bengio et al., 2003; Pennington et al., 2014; Mikolov et al., 2013a; Bojanowski et al., 2016) represent the meaning of a word as a vector of learned features with interesting linear properties. They have not only been used to evaluate analogies (Mikolov et al.,

2013b)(Nematzadeh et al., 2017), but also for document retrieval(Brokos et al., 2016), affordance detection (Fulda et al., 2017), and the generation of sentence-level embeddings (Kiros et al., 2015). Multimodal embedding algorithms inspired by language models have also been used for text and image alignment (Frome et al., 2013; Weston et al., 2011; Garcia-Gasulla et al., 2015),

Algorithms for learning word embeddings typically assume that words in similar contexts should have feature representations that are close to one another, implying that semantically related words will be proximately located. Our work utilizes 300-dimensional fastText embeddings trained on a Wikipedia corpus (Bojanowski et al., 2016) which, like word2vec (Mikolov et al., 2013a), GLoVE (Pennington et al., 2014), and related vector sets, were trained using a neural network tasked with predicting local context. Unlike previous methods, fastText utilizes subword information to speed the training process and generate compositional embeddings for previously unseen words.

Known weaknesses of word embeddings include susceptibility to triangle inequalities and breakdowns in symmetry (Nematzadeh et al., 2017) as well as an inability to represent different semantic meanings of the same word. Researchers are currently exploring disambiguation methods to distinguish between multiple senses of a given word (Reisinger and Mooney, 2010; Huang et al., 2012) or to combine the strengths of several models (Ghannay et al., 2016).

3 Embedding Grammars

A context-free grammar (CFG) is defined as a tuple (N,W,R,S) where N is a finite set of nonterminal symbols, W is a finite set of terminal symbols, R is a finite set of productions of the form $A \to B$ with $A \in N$, $B \in (W \cup N) *$ (where * is the Kleene star), and where $S \in N$ is a distinguished start symbol. The language generated by the grammar is the yield of the terminal strings generated with all possible (recursive) substitutions of right-hand side nonterminals with left-hand side nonterminals.

An embedding grammar generalizes classic CFGs: instead of considering terminals W to be "grounded" in discrete tokens, we instead consider terminals to be grounded in a well-defined region of a feature space. We therefore replace the set of symbols W with a set of subregions W_e , where

each $r \in W_e$ is defined as some $r \subset \mathbb{R}^d$, where d is the dimension of the feature space.

To connect tokens and the grammar, we require a word embedding using one of the methods described in Sec. 2 that defines a function f that maps tokens $w \in W$ to points in \mathbb{R}^d . We then say that a production $A \to B$ is valid if $B \in W_e, w \in W$, and $f(w) \in B$.

This naturally raises the question: how should the subregions be specified? We adopt an exemplar based approach: the grammar designer specifies the subregions indirectly by giving several exemplars, which are then used in conjunction with the word embedding database to automatically generate the subregion.

Figure 1 illustrates the idea for a simple BNF grammar given by:

where nonterminals are given in all capital letters. Naively, this simple grammar would yield only the single sentence "Your mother was a hamster and your father smelt of elderberries" (Gilliam et al., 1975). However, using embedding grammars, we can interpret the production REL ::= elderberries as an exemplar, and define the subregion r as (for example) an epsilon ball centered at f (elderberries). This naturally generalizes the yield of the grammar to a wide variety of familial relationships, pets, and berries.

3.1 Subspace region definition

Subspace definition is independent of the overall grammar structure, and different methods can be used as needed. Here, we outline four possible approaches to subspace definition. (In practical application, we found the neighbor expansion method to be most effective, and use it in our examples throughout the paper.)

Bounding Box: A naive subspace can be defined by taking a bounding box of the exemplars. As one might expect, this method does not work particularly well, and it also cannot be applied to productions consisting of only a single exemplar. **Epsilon ball:** In this approach, the centroid of the exemplar set is taken, and all vectors whose cosine distance is less than a predefined value ϵ from the centroid are considered to fulfill the production rule. **Covariance subspace:** We define a Mahalanobis distance metric based on the empiri-

(son|father|wife|mother|daughter|parents|
daughters|grandfather|aunt|grandmother|
siblings|maternal|granddaughter|niece|
grandparents|remarried|widowed|adoptive|
stepmother|fiancée|aunts|godmother|
fiance|grandchild|stepsister|
fiancee|nieces|stepdaughter|paternal|
granddaughters|grandmothers|mothered|
motherly|fathering|remarries|goddaughter|
stepmothers|stepfathers|grandmotherly|
stepdaughters|stepfather|grandaughter)

(hamster| hamsters| roborovskihamsters) (strawberries|cherries|cranberries|
berries|raspberries|bilberries|
currant|blueberries|apricots|blackberries|
bilberry|elderberry|currants|dandelions|
serviceberry|gooseberries|lingonberry|
redcurrant|loganberry|elderflower|
huckleberries|mulberries|winterberry|
elderberries|lingonberries|wolfberries|
blackcurrants|lowbush|cloudberries)

Figure 1: Sample regexy expansions obtained using the 500,000 most common tokens in the English-language fastText corpus. Matches were selected using the neighbor expansion method with ϵ =0.35.

cal (possibly regularized) covariance of the exemplars. We expected this method to outperform the epsilon ball, since it takes into account the idea that certain components of the vector space have a greater influence on word semantics. In reality, the opposite was true. **Neighbor expansion:** We found this method to be the most successful. In this case, each exemplar in a given production defines a subspace consisting of all vectors whose cosine distance to said exemplar is less than ϵ . Thus, a vector which is within the epsilon ball of any exemplar is considered to match the production rule. This many-bubbles approach results in close matches for the entire set of exemplars.

4 A Python Implementation

To test our ideas, we experimented with a simple integration of embeddings and Python's regular expression package (re). The Python regex package (van Rossum et al., 2017) provides a concise notation for describing sets of character strings, allowing complex string matching based on search patterns entered by a human designer. In Python, regex uses a backtracking algorithm rather than translating the regex into an equivalent deterministic finite automaton (DFA) or non-deterministic finite automaton (NFA). We took advantage of re's dynamic nature by defining and calling a wrapper function which applies regexy before calling each of re's public API methods.

5 Experiments

Our experiments used 300-dimensional FastText vectors trained on Wikipedia. A coarse parameter search suggests that $\epsilon < 0.5$ represents a strong semantic similarity. However, because polar opposites (e.g. beautiful/ugly) appear in highly sim-

ilar contexts and tend to fall within this range of each other, we adopted a stricter match threshold of ϵ =0.35. The neighbor expansion method discussed in Section 3.1 was used for all experiments.

5.1 Word extensions

Sample word expansions are shown in Figure 1. The common and socially-integral term 'mother' (777th most common token) produces a wide range of matches, whereas the less common word 'hamster' (33651st most common token) defines a relatively sparse subspace.

Note that grammatically incorrect matches such as 'widowed' or 'motherly' are unlikely to cause poor system performance, as human-generated text will almost never contain syntactically implausible phrases like "Your widowed was a hamster". The same holds true for unusual and entertaining words such as 'roborovskihamsters'. The most problematic error modes involve words that are polar opposites: hot/cold, happy/sad, high/low, because they tend to appear in similar contexts.

Multi-word phrase matching was accomplished by treating each input phrase as the vector average of its individual words, an approach that to our surprise functioned quite well. For example, the vectors for 'clever' and 'man', when averaged together, produce a vector that is highly similar to the vector for 'genius'. Further examples are shown in Table 1.

5.2 Intent matching

Figure 2 illustrates another example of intent matching. If the string one expects is something like "I would like to call a taxi", then people could also say "I would like to call a car" and intend the same directive. Typical grammars might define a

Regex String: "I would like to call a [taxi]"

regex: "I would like to call a (taxi|car)"

matches: "I would like to call a taxi", "I would like to call a car"

regexv: "I would like to call a \(\taxi, \car\)"

post expansion: "I would like to call a (taxi|taxis|minibus|taxicab|taxicabs|car|cars|vehicle|driver|

driving | truck | automobile | suv | roadster | motorbike | racecar | minivan | motorcar | racecars)"

matches: "I would like to call a minibus", "I would like to call a taxicab", etc.

Figure 2: Comparison between regex and regexv. Here, [taxi] is shorthand for the intent that would include all words that are synonymous with taxi.

| match phrase | exemplar | cos distance |
|------------------|----------|--------------|
| clever man | genius | .3934 |
| clever car | genius | .5776 |
| smart boy | genius | .4822 |
| smart car | genius | .6859 |
| fast car | genius | .7700 |
| smart car | tesla | .5758 |
| smart car | porsche | .4609 |
| a guy who | | |
| knows everything | genius | .5060 |
| a guy who | | |
| knows everything | porsche | .7767 |

Table 1: Cosine distance between single-word vectors and compositional vectors created by averaging the elements of a multi-word phrase. The resulting distances correlate with many human estimations of semantic similarity.

pattern, "I would like to call a (taxi|car)", in order to match these semantically equivalent sentences. The problem is that the developer must enumerate all the possible words that could mean the same thing as "taxi" in this pattern. Regexv solves this issue by allowing a user to define intent words, then automatically expands these to a large list of words that have the same semantic meaning. Figure 2 shows how regexv to expands two terms to an entire list, including taxi, minibus, taxicab, car, vehicle, driver, racecar, etc.

6 Learning and Extensions to PCFGs

The fact that terminals in embedding grammars are defined as regions in a continuous feature space suggest a natural extension to probabilistic context-free grammars (PCFGs). A PCFG is a tuple (N, W, R, S, θ) , where (N, W, R, S) are defined as for a normal CFG, but where each production $A \rightarrow B$ is annotated with a probability

 $\theta_{A \to B}$, st $\sum_{A \to B \in R_A} \theta_{A \to B} = 1$, where R_A is the subset of productions in R with left-hand side A. Informally, $\theta_{A \to B}$ is the probability of expanding the nonterminal A using the rule $A \to B$. This naturally defines a probabilistic generative model, and can be used to (for example) rank parses of ambiguous sentences according to some prior.

Embedding grammars offer an additional generalization: instead of defining matches as hard regions in \mathbb{R}^d , soft matches could be defined using (eg) Gaussians; this suggests fully probabilistic learning algorithms that could take advantage of soft matches and the continuous nature of word embeddings. When combined with, for example, recent probabilistic grammars such as adaptor grammars (Johnson et al., 2007) and fragment grammars (O'Donnell et al., 2009) that combine Bayesian nonparametrics and PCFGs, this could potentially result in efficient grammar learning algorithms: learnt grammars could be more compact because of the natural generalization inherent in the word embeddings.

7 Conclusion

Word embeddings can be combined with classic grammars to enable semantic matching of regular expressions. This is advantageous because it reduces human cognitive effort, allowing grammar designers to say what they want more compactly.

Importantly, the matching power of the expression is not limited by the designer's lexicon, but can include words that the designer is not familiar with. Recent advances in word embeddings, including fastText, provide for generalization to previously unseen words based on subword structure.

We have only scratched the surface of the possibilities of embedding grammars. Extensions to PCFGs and the advantages of embeddings visavis grammar learning are exciting directions for future work.

References

- Guido van Rossum et al. 2017. Cpython github, re.py.
- Yoshua Bengio, Rjean Ducharme, Pascal Vincent, and Christian Jauvin. 2003. A neural probabilistic language model. *Journal of Machine Learning Research*, 3:1137–1155.
- Piotr Bojanowski, Edouard Grave, Armand Joulin, and Tomas Mikolov. 2016. Enriching word vectors with subword information. *arXiv preprint arXiv:1607.04606*.
- Georgios-Ioannis Brokos, Prodromos Malakasiotis, and Ion Androutsopoulos. 2016. Using centroids of word embeddings and word mover's distance for biomedical document retrieval in question answering. *CoRR*, abs/1608.03905.
- Andrea Frome, Greg S. Corrado, Jonathon Shlens,Samy Bengio, Jeffrey Dean, and Tomas Mikolov.2013. Devise: A deep visual-semantic embedding model. In *In NIPS*.
- Nancy Fulda, Daniel Ricks, Ben Murdoch, and David Wingate. 2017. What can you do with a rock? affordance extraction via word embeddings. In *Proceed*ings of the Twenty-Sixth International Joint Conference on Artificial Intelligence, IJCAI-17, pages 1039–1045.
- Dario Garcia-Gasulla, Javier Béjar, Ulises Cortés, Eduard Ayguadé, and Jesús Labarta. 2015. Extracting visual patterns from deep learning representations. *CoRR*, abs/1507.08818.
- Sahar Ghannay, Benoit Favre, Yannick Esteve, and Nathalie Camelin. 2016. Word embedding evaluation and combination. In *LREC*.
- Terry Gilliam, Terry Jones, Graham Chapman, John Cleese, Eric Idle, and Michael Palin. 1975. Monty python and the holy grail.
- Eric H. Huang, Richard Socher, Christopher D. Manning, and Andrew Y. Ng. 2012. Improving word representations via global context and multiple word prototypes. In *Proceedings of the 50th Annual Meeting of the Association for Computational Linguistics: Long Papers Volume 1*, ACL '12, pages 873–882. Association for Computational Linguistics.
- Mark Johnson, Thomas L Griffiths, and Sharon Goldwater. 2007. Adaptor grammars: A framework for specifying compositional nonparametric bayesian models. In *Advances in neural information processing systems*, pages 641–648.
- Ryan Kiros, Yukun Zhu, Ruslan Salakhutdinov, Richard S. Zemel, Antonio Torralba, Raquel Urtasun, and Sanja Fidler. 2015. Skip-thought vectors. pages 3294–3302.
- Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013a. Efficient estimation of word representations in vector space. *CoRR*, abs/1301.3781.

- Tomas Mikolov, Wen-tau Yih, and Geoffrey Zweig.
 2013b. Linguistic regularities in continuous space word representations. Association for Computational Linguistics.
- Aida Nematzadeh, Stephan C Meylan, and Thomas L Griffiths. 2017. Evaluating vector-space models of word representation, or, the unreasonable effectiveness of counting words near other words. In *The Cognitive Science Society*.
- Timothy J O'Donnell, Joshua B Tenenbaum, and Noah D Goodman. 2009. Fragment grammars: Exploring computation and reuse in language.
- Jeffrey Pennington, Richard Socher, and Christopher D. Manning. 2014. Glove: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing, EMNLP 2014, October 25-29, 2014, Doha, Qatar, A meeting of SIGDAT, a Special Interest Group of the ACL, pages 1532–1543.*
- Joseph Reisinger and Raymond J. Mooney. 2010. Multi-prototype vector-space models of word meaning. In *Proceedings of the 11th Annual Conference of the North American Chapter of the Association for Computational Linguistics (NAACL-2010)*, pages 109–117.
- Jason Weston, Samy Bengio, and Nicolas Usunier. 2011. Wsabie: Scaling up to large vocabulary image annotation. In *IJCAI*, pages 2764–2770. IJ-CAI/AAAI.