

Tackling Online Abuse: A Survey of Automated Abuse Detection Methods

Pushkar Mishra[★], Helen Yannakoudakis[♣], Ekaterina Shutova[♣]

[★] Facebook AI, London, United Kingdom

[♣] Department of Informatics, King's College London, United Kingdom

[♣] Institute for Logic, Language and Computation, University of Amsterdam, The Netherlands
pushkarmishra@fb.com, helen.yannakoudakis@kcl.ac.uk, e.shutova@uva.nl

Abstract

Abuse on the Internet represents an important societal problem of our time. Millions of Internet users face harassment, racism, personal attacks, and other types of abuse on online platforms. The psychological effects of such abuse on individuals can be profound and lasting. Consequently, over the past few years, there has been a substantial research effort towards automated abuse detection in the field of natural language processing (NLP). In this paper, we aim to present a comprehensive view of the field, hence providing a platform for further development of this area. We first describe the existing datasets and review the computational approaches to abuse detection, analyzing their strengths and weaknesses. We then discuss the main trends that emerge, highlight the challenges that remain, and outline possible solutions. Finally, taking note of the developments in the field, we propose guidelines for ethics and explainability.

1 Introduction

With the advent of social media, anti-social and abusive behavior has become a prominent occurrence online. Undesirable psychological effects of abuse on individuals make it an important societal problem of our time. Munro (2011) studied the ill-effects of online abuse on children, concluding that children may develop depression, anxiety, and other mental health problems as a result of their encounters online. *Pew Research Center*, in its latest report on online harassment (Duggan, 2017), revealed that 40% of adults in the United States have experienced abusive behavior online, of which 18% have faced severe forms of harassment, e.g., that of sexual nature. The report goes on to say that harassment need not be experienced first-hand to have an impact: 13% of American Internet users admitted that they stopped using an online service after witnessing abusive and unruly behavior of their fellow users. These statistics stress the need for automated abuse detection and moderation systems. Therefore, in the recent years, a new research effort on abuse detection has sprung up in NLP.

That said, the notion of abuse has proven elusive and difficult to formalize. Different norms across (online) communities can affect what is considered abusive (Chandrasekharan et al., 2018). In the context of natural language, *abuse* is a term that encompasses many different types of fine-grained negative expressions. For example, Nobata et al. (2016) use it to collectively refer to hate speech, derogatory language and profanity, while Mishra et al. (2018a) use it to discuss racism and sexism. The definitions for different types of abuse tend to be overlapping and ambiguous. However, regardless of the specific type, we define abuse as *any expression that is meant to denigrate or offend a particular person or group*. Taking a course-grained view, Waseem et al. (2017) classify abuse into broad categories based on *explicitness* and *directness*. *Explicit* abuse comes in the form of expletives, derogatory words or threats, while *implicit* abuse has a more subtle appearance characterized by the presence of ambiguous terms and figures of speech such as metaphor or sarcasm. *Directed* abuse targets a particular individual as opposed to *generalized* abuse, which is aimed at a larger group such as a particular gender or ethnicity.

This categorization exposes some of the intricacies that lie within the task of automated abuse detection. While directed and explicit abuse is relatively straightforward to detect for humans and machines alike, the same is not true for implicit or generalized abuse. This is illustrated in the works of Dadvar et al. (2013) and Waseem and Hovy (2016): Dadvar et al. observed an inter-annotator agreement of 93%

on their cyber-bullying dataset. Cyber-bullying is a classic example of directed and explicit abuse since there is typically a single target who is harassed with personal attacks. On the other hand, Waseem and Hovy noted that 85% of all the disagreements in annotation of their dataset occurred on the sexism class. Sexism is typically both generalized and implicit.

This paper aims to provide a comprehensive view of the field of automated abuse detection. We make various contributions that differ from *traditional* surveys of the field (Schmidt and Wiegand, 2017; Fortuna and Nunes, 2018; Salminen et al., 2018; Castelle, 2018). Firstly, we present a review of the commonly-used datasets. We then discuss the various methods for abuse detection that have been investigated by the NLP community, including ones based on neural networks which previous surveys have omitted. Next, we summarize the main trends that emerge, highlight the challenges that remain, and outline possible solutions. Lastly, taking note of the direction of developments, we propose guidelines for ethics and explainability that align with the aforementioned categorization of abuse per explicitness and directness.

2 Annotated datasets

Supervised learning approaches to abuse detection require annotated datasets for training and evaluation purposes. To date, several manually annotated datasets have been made available by researchers. Before describing the commonly-used ones,¹ we highlight the two respects in which these datasets differ:

- *Source*: the platform from which the data samples were collected. For example, data samples can be posts from *Reddit* or tweets from Twitter. Source governs many properties of the dataset such as linguistic style and structure, level of grammatical correctness, extent of (deliberate) obfuscation of words, etc. Essentially, source affects both explicitness and directness of the abusive samples in it.
- *Composition*: the composition of a dataset is governed by the nature of data samples it contains. Most datasets are annotated for or compiled to cover only certain subset of types of abuse, e.g., racism and sexism, or personal attack and racism, or hate speech and profanity.

Early datasets. The earliest dataset published in this field was from Spertus (1997). It consisted of 1,222 private messages written in English taken from web-masters of controversial web resources such as *NewtWatch*. These messages were marked as *flame* (containing insults or abuse; 7.5%), *maybe flame* (13%), or *okay* (79.5%). We refer to this dataset as DATA-SMOKEY. Yin et al. (2009) constructed three English datasets and annotated them for *harassment*, which they defined as “systematic efforts by a user to belittle the contributions of other users”. The samples were taken from three social media platforms: *Kongregate* (4,802 posts; 0.87% harassment), *Slashdot* (4,303 posts; 1.4% harassment), and *MySpace* (1,946 posts; 3.3% harassment). We refer to the three datasets jointly as DATA-HARASS.

Yahoo! as source. Many datasets have been compiled using samples taken from portals of *Yahoo!*, specifically the *News* and *Finance* ones. Djuric et al. (2015) created a dataset of 951,736 user comments in English from the *Yahoo! Finance* website that were editorially labeled as *hate speech* (5.9%) or *clean* (DATA-YAHOO-FIN-DJ). Nobata et al. (2016) produced four more datasets with comments from *Yahoo! News* and *Yahoo! Finance*, each labeled *abusive* or *clean*: 1) DATA-YAHOO-FIN-A: 759,402 comments, 7.0% abusive; 2) DATA-YAHOO-NEWS-A: 1,390,774 comments, 16.4% abusive; 3) DATA-YAHOO-FIN-B: 448,436 comments, 3.4% abusive; and 4) DATA-YAHOO-NEWS-B: 726,073 comments, 9.7% abusive.

Twitter as source. Several groups have investigated abusive language in Twitter. Waseem and Hovy (2016) created a corpus of 16,907 tweets, each annotated as one of *racism* (11.7%), *sexism*, (20.0%) or *neither* (DATA-TWITTER-WH). We note that although certain tweets in the dataset lack explicit abusive traits (e.g., *@Mich_McConnell Just “her body” right?*), they have nevertheless been marked as racist or sexist as the annotators took the wider discourse into account; however, such discourse information is not preserved in the dataset. Inter-annotator agreement was reported at $\kappa = 84\%$, with a further insight that 85% of all the disagreements occurred on the sexism class alone. Waseem (2016) later released a

¹Some datasets are directly described in the later sections where methods applied on them are discussed. Additionally, in the appendix, we also provide summaries of the datasets that are publicly available along with links to them.

dataset of 6,909 tweets annotated as *racism* (1.41%), *sexism* (13.08%), *both* (0.70%), or *neither* (DATA-TWITTER-W). DATA-TWITTER-W and DATA-TWITTER-WH have 2,876 tweets in common. It should, however, be noted that the inter-annotator agreement between the two datasets is low (mean pairwise $\kappa = 14\%$) (Waseem, 2016). Davidson et al. (2017) created a dataset of approximately 25k tweets, manually annotated as one of *racist* (5%), *offensive but not racist* (76%), or *clean* (19%). We note, however, that their data sampling procedure relied on the presence of certain abusive words and, as a result, the distribution of classes does not follow a real-life distribution. Recently, Founta et al. (2018) crowd-sourced a dataset (DATA-TWITTER-F) of 80k tweets, of which 59% were rated *normal*, 22.5% *spam*, 7.5% *hateful*, and 11% *abusive*. The *OffensEval* 2019 shared task used a recently released dataset of 14,100 tweets (Zampieri et al., 2019), each hierarchically labeled as: offensive (33%) or not, offense is targeted (29%) or not, and whether the target is an individual (17.8%), a group (8.2%) or otherwise (3%).

Other English sources. Wulczyn et al. (2017a) crowd-sourced annotations for English comments from *Wikipedia’s talk pages* and released three datasets: one focusing on personal attacks (115,864 comments; 11.7% abusive), one on aggression (115,864 comments), and one on toxicity (159,686 comments; 9.6% abusive) (DATA-WIKI-ATT, DATA-WIKI-AGG, and DATA-WIKI-TOX respectively). DATA-WIKI-AGG contains the exact same comments as DATA-WIKI-ATT but annotated for aggression – the two datasets show a high correlation in the nature of abuse (*Pearson’s* $r = 0.972$). Gao and Huang (2017) released a dataset of 1,528 Fox News user comments (DATA-FOX-NEWS) annotated as *hateful* (28.5%) or *non-hateful*. The dataset preserves context information for each comment, including user’s screen-name, all comments in the same thread, and the news article for which the comment is written. Salminen et al. (2018) sourced 137k comments from under videos posted on YouTube and Facebook (DATA-YTUBE-FB). They self-annotated the corpus per a fine-grained hierarchical taxonomy consisting of 13 main categories and 16 sub-categories that cover both nature of abuse (e.g., humiliation) as well as targets (e.g., religion).

Non-English datasets. Some researchers investigated abuse in languages other than English. Van Hee et al. (2015) gathered 85,485 Dutch posts from *ask.fm* to form a dataset on cyber-bullying (DATA-BULLY; 6.7% cyber-bullying cases). Pavlopoulos et al. (2017b) released a dataset of ca. 1.6M comments in Greek provided by the news portal *Gazzetta* (DATA-GAZZETTA). The comments were marked as *accept* or *reject*, and are divided into 6 splits with similar distributions (the training split is the largest one: 66% accepted and 34% rejected comments). As part of the *GermEval* shared task on identification of offensive language in German tweets (Wiegand et al., 2018c), a dataset of 8,541 tweets was released, of which 21% were labeled as *abuse*, 11.4% as *insult*, 1.39% as *profanity*, and 66.16% as *other*. Around the same time, 15k Facebook posts and comments, each in Hindi (in both Roman and Devanagari script) and English, were released (DATA-FACEBOOK) as part of the *COLING 2018* shared task on aggression identification (Kumar et al., 2018). 35.3% of the comments were *covertly aggressive*, 22.8% *overtly aggressive* and 41.9% *non-aggressive*. We note, however, that some issues were raised by the participants regarding the quality of the annotations. The *HatEval* 2019 shared task focused on detecting hate speech against immigrants and women using a dataset of 5k tweets in Spanish and 10k in English annotated hierarchically as hateful or not; and, in turn, as aggressive or not, and whether the target is an individual or a group.

Remarks. In their study, Ross et al. (2016) stressed the difficulty of reliably annotating abuse, which stems from multiple factors such as the lack of *standard* definitions for the myriad types of abuse, differences in annotators’ cultural background and experiences, and ambiguity in the annotation guidelines. That said, Waseem et al. (2017) and Nobata et al. (2016) observed that annotators with prior expertise provide good-quality annotations with high levels of agreement amongst themselves. That aside, most datasets contain discrete labels only; abuse detection systems trained on such datasets would be deprived of the notion of *severity*, which is vital in real-world settings. In fact, all existing datasets cover only a subset of abuse types. Moreover, recent studies have also found substantial and systematic bias in existing datasets, which they primarily attributed to the sampling strategy, e.g., topic or word-based (Wiegand et al., 2019).

Rules and Lexicon-based	Computational
<p>Spertus (1997):</p> <ul style="list-style-type: none"> Employed 47 hand-crafted linguistic rules to extract binary feature vectors for feeding to a decision tree generator to train a classification model. 64% recall on the <i>flame</i> and 98% on the <i>non-flame</i> messages in the test set of the DATA-SMOKEY dataset. <p>Razavi et al. (2010):</p> <ul style="list-style-type: none"> First to propose a lexicon-based method for abuse detection whereby they constructed an <i>insulting and abusing language</i> dictionary of words and phrases, with each entry having an associated weight indicating its abusive impact; Njagi et al. (2015) also adopted such a lexicon-based approach later on. 96% accuracy on a dataset of 1,525 messages (32% <i>flame</i> and the rest <i>okay</i>) extracted from the <i>Usenet</i> newsgroup and the employee conversation threads of the <i>Natural Semantic Module</i> company. <p>Wiegand et al. (2018b):</p> <ul style="list-style-type: none"> Automated framework for creating lexicons whereby they first constructed a <i>base lexicon</i> of <i>negative polar expressions</i> with 33% annotated as abusive, and then trained an SVM on multiple hand-crafted linguistic and semantic features which yielded an F_1 of 81.6% on the base lexicon; they applied this SVM to a set of unlabeled negative polar expressions to expand the base lexicon with more abusive expressions. 63.8% F_1 on DATA-TWITTER-WH and 78.4% F_1 on DATA-WIKI-ATT with an SVM trained on hand-crafted rank features derived from the expanded lexicon. 	<p>Yin et al. (2009):</p> <ul style="list-style-type: none"> Extracted local features (TF-IDF weights of words), sentiment-based features (TF-IDF weights of foul words and pronouns), and also contextual features (e.g., similarity of a post to its neighboring posts) which captured aspects not covered by former two. 91%, 90.8%, and 48.1% F_1 respectively on the DATA-HARASS datasets, i.e., <i>MySpace</i>, <i>Slashdot</i>, and <i>Kongregate</i>, with a linear SVM. <p>Sood et al. (2012):</p> <ul style="list-style-type: none"> Word bi-gram features combined with a word-list baseline utilizing a <i>Levenshtein distance</i> based heuristic. 69% F_1 using an SVM on a dataset of 6,354 comments from a social news site labeled <i>profanity</i> (9%) or not. <p>Warner and Hirschberg (2012):</p> <ul style="list-style-type: none"> Framed their task as word-sense disambiguation, i.e., whether a term carried an <i>anti-semitic</i> sense or not, and employed a template-based strategy alongside <i>Brown clustering</i> to extract surface-level BOW features. 63% F_1 using an SVM on a dataset of 1000 paragraphs annotated as <i>anti-semitic</i> (9%) or not. <p>Dinakar et al. (2011), Burnap et al. (2014), Hee et al. (2015):</p> <ul style="list-style-type: none"> Word n-grams plus features such as typed-dependency relations and scores based on sentiment lexicons. 55.9% best F_1 on the DATA-BULLY dataset. <p>Salminen et al. (2018):</p> <ul style="list-style-type: none"> TF-IDF weighted n-grams constituted the best feature. 74% macro-F_1 using an SVM on DATA-YTUBE-FB.
<p>Advantages noted by Wiegand et al. (2018b) are that hand-crafted rules and lexicons generalize well across data from different domains, and that they can capture targeted aspects which are not easily learnable just from labeled data.</p>	<p>Advantages include faster modeling since lesser human inputs are required in comparison. Moreover, features like character n-grams are robust to spelling, punctuation and grammatical variations (Nobata et al., 2016).</p>
<p>Disadvantages noted by Spertus (1997) and Wiegand et al. (2018b) included the inability of rules and lexicons to deal with implicit abuse and sarcasm, and their vulnerability to errors in spelling, punctuation and grammar.</p>	<p>Disadvantages include features being relatively difficult to interpret directly. Additionally, features generated by this approach may only capture surface-level patterns but not deeper semantic properties (Wiegand et al., 2018b).</p>

Table 1: The two approaches to textual feature engineering. First row discusses some of the works across the two, and second and third rows highlight some advantages and disadvantages of the two respectively.

3 Feature engineering based abuse detection

The first documented method for abuse detection was that of Spertus (1997) who hand-crafted rules over texts to generate feature vectors for learning. Since then, several methods have been proposed that rely on manual *feature engineering*. Such feature engineering happens on two fronts, either on the text of the sample (*textual*) or on the user(s) who created or interacted with the sample (*social*).

Textual feature engineering. This kind of feature engineering models directed and explicit traits of abuse within samples. Researchers have adopted two approaches to textual feature engineering: hand-crafted rules cum lexicon-based approach and computational approach. The former includes features extracted from text based on linguistic rules (e.g., text contains the pronoun *you* followed by profanity) or some curated lexicon of abusive words and expressions (e.g., *hatebase.org*). The latter on the other hand includes bag-of-words (BOW) counts, TF-IDF weighted features, features based on similarity clustering, etc. Both approaches are summarized in Table 1.

Social feature engineering. Several researchers have directly incorporated features and identity traits of users in order to model the likeliness of abusive behavior from users with certain traits, a process known as *user profiling*. Dadvar et al. (2013) included the age of users alongside other traditional lexicon-based features to detect cyber-bullying, while Galán-García et al. (2016) utilized the time of publication,

geo-position and language in the profile of Twitter users. Waseem and Hovy (2016) exploited gender of Twitter users alongside character n-gram counts to improve detection of sexism and racism in tweets from DATA-TWITTER-WH (F_1 increased from 73.89% to 73.93%). Using the same setup, Unsvåg and Gambäck (2018) showed that the inclusion of social network-based (i.e., number of followers and friends) and activity-based (i.e., number of status updates and favorites) information of users alongside their gender further enhances performance (3 points gain in F_1).

4 Neural networks based abuse detection

Advancements in computational capabilities have led researchers to explore methods for abuse detection that rely on neural architectures. Such methods can be broadly divided into three categories: 1) those that simply consume distributed representations generated by neural networks, 2) those that perform deep learning on texts, and 3) those that use neural networks for modeling social aspects.

Distributed representations. Djuric et al. (2015) were the first to adopt neural networks for abuse detection. They utilized *paragraph2vec* (Le and Mikolov, 2014) to obtain low-dimensional representations for comments in DATA-YAHOO-FIN-DJ and trained a logistic regression (LR) classifier. Their model outperformed other classifiers trained on BOW-based representations (AUROC 80.07% vs. 78.89%). The authors noted that words and phrases in hate speech tend to be obfuscated, leading to high dimensionality and sparsity of BOW-based representations, which in turn causes classifiers to over-fit in training.

Building on the work of Djuric et al., Nobata et al. (2016) examined the performance of a variety of features on the *Yahoo!* datasets (DATA-YAHOO-*) using a regression model: 1) word and character n-grams, 2) linguistic features like number of polite/hate words and punctuation count, 3) syntactic features like parent and grandparent of node in a dependency tree, and 4) distributional-semantic features like *paragraph2vec* comment representations. Although the best results were achieved with all the features combined (79.5% F_1 on DATA-YAHOO-FIN-A, 81.7% F_1 on DATA-YAHOO-NEWS-A), character n-grams on their own contributed significantly more than the other features due to their robustness to noise such as obfuscations, misspellings, unseen words. The *paragraph2vec* representations, in comparison, performed at par with character n-grams only on DATA-YAHOO-NEWS-A, which was noted to be less noisy than DATA-YAHOO-FIN-A. Working with the DATA-YAHOO-FIN-DJ dataset, Mehdad and Tetreault (2016) investigated whether character-level features are more indicative of abuse than word-level ones. Their experiments demonstrated the superiority of character-level features, revealing that SVM classifiers trained on Bayesian log-ratio vectors of average counts of character n-grams improve not only upon the more intricate approach of Nobata et al. (AUROC from 91% to 92%), but also upon other recurrent neural networks (RNN) based character and word-level models.

Samghabadi et al. (2017) started with a similar set of features as Nobata et al. (2016) and augmented it with hand-engineered ones such as polarity scores derived from *SentiWordNet*, scores based on the *LIWC* program, and features based on emoticons. They applied their method to three different datasets: DATA-WIKI-ATT, a *Kaggle* dataset annotated for insult, and a dataset of questions and answers (each labeled as *invective* or *neutral*) that they created by crawling *ask.fm*. Distributional-semantic features combined with the aforementioned features constituted an effective feature space for the task (65%, 68%, 56% F_1 on DATA-WIKI-ATT, *Kaggle*, *ask.fm* respectively). In line with the results of Nobata et al. and Mehdad and Tetreault, the authors found character n-grams to be performing well on these datasets too.

Deep learning on texts. With the advent of deep learning, many researchers have explored its efficacy in abuse detection. Badjatiya et al. (2017) evaluated several neural architectures on the DATA-TWITTER-WH dataset. Their best setup involved a two-step approach wherein they used a word-level long-short term memory (LSTM) model, to tune GLoVe or randomly-initialized word embeddings, and then trained a gradient-boosted decision tree (GBDT) classifier on the average of the tuned embeddings in each tweet. They achieved the best results using randomly-initialized embeddings (weighted F_1 of 93%). However, working with a similar setup, Mishra et al. (2018a) reported that GLoVe initialization provided superior performance; a mismatch was attributed to the fact that Badjatiya et al. tuned the embeddings on the entire dataset, including the test set, to which the randomly-initialized ones overfit better.

Park and Fung (2017) utilized character and word-level CNNs to classify comments in the dataset

that they formed by combining DATA-TWITTER-W and DATA-TWITTER-WH. Their experiments demonstrated that combining the two levels of granularity using two input channels achieves the best results, improving upon a character n-grams based LR baseline (weighted F_1 from 81.4% to 82.7%). Several other works have also demonstrated the efficacy of CNNs in detecting abusive social media posts (Singh et al., 2018). Some researchers (Wang, 2018; Zhang et al., 2018) have shown that sequentially combining CNNs with gated recurrent unit (GRU) RNNs can enhance performance by taking advantage of properties of both architectures, e.g., 1-2% increase in F_1 compared to only using CNNs.

Pavlopoulos et al. (2017a; 2017b) applied deep learning to the DATA-WIKI-ATT, DATA-WIKI-TOX, and DATA-GAZZETTA datasets. Their most effective setups were: 1) a word-level GRU followed by an LR layer, and 2) setup 1 extended with an attention mechanism on words. Both setups outperformed a simple word-list baseline as well as the character n-grams based LR classifier (DETOX) from Wulczyn et al. (2017a). Setup 1 achieved the best performance on DATA-WIKI-ATT (AUROC 97.71%) and DATA-WIKI-TOX (AUROC 98.42%), while setup 2 performed the best on DATA-GAZZETTA (AUROC 84.69%). Additionally, the attention mechanism was shown to be able to highlight abusive words and phrases within the comments, exhibiting a high level of agreement with annotators on the task. Lee et al. (2018) worked with a subset of the DATA-TWITTER-F dataset and showed that a word-level bi-GRU model along with *latent topic clustering*, where topic information is extracted from the hidden states of the GRU (Yoon et al., 2018), yielded the best weighted F_1 of 80.5%.

The *GermEval 2018* shared task on identification of offensive language in German tweets (Wiegand et al., 2018c) saw submission of both deep learning and feature engineering based methods. The winning system (Montani, 2018), with macro F_1 of 76.77%, employed multiple character and token n-gram classifiers alongside distributional semantic features obtained by averaging word embeddings. The second best approach (von Grünigen et al., 2018), with macro F_1 75.52%, on the other hand, employed an ensemble of CNNs whose outputs were fed to a meta classifier for final prediction. Most of the remaining submissions (Risch et al., 2018; Wiegand et al., 2018a) used deep learning with CNNs and RNNs alongside techniques such as transfer learning (e.g., via machine translation or joint representation learning for words across languages) from abuse-annotated datasets in other languages (mainly English). Wiegand et al. (2018c) noted that simple deep learning approaches themselves were quite effective, and the addition of other techniques did not necessarily provide substantial gains.

Kumar et al. (2018) noted similar trends in the shared task for aggression identification on the DATA-FACEBOOK dataset. The top approach on the task’s English dataset (Aroyehun and Gelbukh, 2018), with macro F_1 of 64.25%, comprised RNNs and CNNs along with transfer learning via machine translation. The top approach for Hindi (Samghabadi et al., 2018), with F_1 of 62.92%, utilized lexical features based on word and character n-grams. In order to further understand the pros and cons of both, Aken et al. (2018) performed a systematic comparison of neural and non-neural approaches to toxic comment classification, concluding that ensembles of the two were most effective.

The *GermEval 2019* shared task on identification of offensive language in German tweets (Stru et al., 2019) consisted of three sub-tasks: 1) coarse-grained classification of samples as *offense* or *other*, 2) fine-grained classification of samples as *offense*, *profanity*, *insult* or *other*, and 3) classification of offensive samples as *implicit* or *explicit*. All three sub-tasks saw submission of a range of methods, including those based on deep contextualized language models like BERT (Devlin et al., 2019). The organizers noted that in fact the winning submissions across all three sub-tasks utilized some form of BERT. Paraschiv and Cercel (2019) made the winning submission on sub-tasks 1 (76.95% F_1) and 2 (53.59% average F_1) that comprised a BERT model pre-trained on German Wikipedia and German Twitter corpora prior to being fine-tuned on the sub-task datasets. Risch et al. (2019) had the winning submission on sub-task 3 (53.93% F_1) that again comprised a BERT model pre-trained on German texts. While the organizers noted that methods based on traditional CNN and RNN models didn’t feature in the top 3 on any sub-task, they found that ensemble models trained on character and token n-grams (Montani and Schller, 2019) and lexicon-based features (Schmid et al., 2019) fared well.

Researchers have recently started exploring multi-task learning with neural networks for the purpose of abuse detection. Rajamanickam et al. (2020) demonstrated that jointly learning over emotion clas-

sification and abuse detection tasks leads to better performance on the latter. Detecting the affective nature of comments (e.g., disgust, anger, joy, fear, optimism) helps to detect abuse more accurately on Twitter posts, achieving an F_1 of 79.55 and 76.03 on DATA-TWITTER-WH and *OffensEval* respectively. Samghabadi et al. (2019) utilize an emotion-aware attention mechanism, achieving a macro- F_1 of 83.56 on *Kaggle* and 88.27 on DATA-WIKI-ATT.

Modeling social aspects with neural networks. More recently, researchers have employed neural networks to extract representations or *profiles* for users instead of manually leveraging traits like gender, location, etc. as discussed before. Working with the DATA-GAZZETTA dataset, Pavlopoulos et al. (2017c) incorporated user embeddings into Pavlopoulos’ setup 1 (2017a; 2017b) described above. They divided all the users whose comments are included in DATA-GAZZETTA into 4 *types* based on proportion of abusive comments (e.g., *red* users if > 10 comments and $\geq 66\%$ abusive comments), *yellow* (users with > 10 comments and $33\% - 66\%$ abusive comments), *green* (users with > 10 comments and $\leq 33\%$ abusive comments), and *unknown* (users with ≤ 10 comments). They then assigned unique randomly-initialized embeddings to users and added them as additional input to the LR layer alongside representations of comments obtained from the GRU. This increased the AUROC from 79.24% to 80.71%. Qian et al. (2018) used LSTMs for modeling inter and intra-user relationships on DATA-TWITTER-WH, with sexist and racist tweets combined into one category. The authors applied a bi-LSTM to users’ recent tweets in order to generate intra-user representations that capture their historic behavior. To improve robustness against noise present in tweets, they also used locality sensitive hashing to form sets of semantically similar user tweets. The authors then trained a policy network to select tweets from sets that a bi-LSTM could use to generate inter-user representations. When these inter and intra-user representations were utilized alongside representations of tweets from an LSTM baseline, F_1 increased from 70.3% to 77.4%.

Mishra et al. (2018a) constructed a community graph of all the users whose tweets are in the DATA-TWITTER-WH dataset. Nodes were the users and edges denoted the follower-following relationship among them on *Twitter*. The authors applied *node2vec* (Grover and Leskovec, 2016) to this graph to generate user embeddings, i.e., profiles. Inclusion of these embeddings into the character n-gram based baselines yielded significant gains on DATA-TWITTER-WH whereby F_1 scores on the racism and sexism classes increased from 72.28% and 72.09% to 75.09% and 82.75% respectively. The gains were attributed to the fact that user embeddings captured not only information about online communities, but also elements of the wider conversation amongst connected users. Ribeiro et al. (2018) and Mishra et al. (2019) applied graph neural networks (Kipf and Welling, 2017; Hamilton et al., 2017) to community graphs to generate embeddings for users that capture not only their surrounding community but also their linguistic behavior. Mishra et al. (2019) recorded 79.49% F_1 on the racism and 84.44% F_1 on the sexism classes of DATA-TWITTER-WH.

5 Discussion

5.1 Current trends and outstanding challenges in modeling abuse

English has been the dominant language so far in terms of focus, followed by German, Hindi and Dutch. However, recent efforts have focused on compilation of datasets in other languages such as Slovene and Croatian (Ljubešić et al., 2018), Chinese (Su et al., 2017), Arabic (Mubarak et al., 2017), and even some unconventional ones such as *Hinglish* (Mathur et al., 2018). Most of the research to date has been on racism, sexism, personal attacks, toxicity, and harassment. Other types of abuse such as obscenity, threats, insults, and grooming remain relatively unexplored. That said, we note that the majority of methods investigated to date and described herein are (in principle) applicable to a range of abuse types.

The recent approaches that rely on word-level CNNs and RNNs remain vulnerable to obfuscation of words (Mishra et al., 2018b). On the other hand, the use of sub-word units, both in feature engineering (e.g. character n-grams) and as tokenized inputs to models like BERT, remains one of the most effective techniques for addressing obfuscation since sub-word units are robust to spelling variations. Many researchers to date have exclusively relied on text based features for abuse detection. But recent works have shown that personal and community-based profiling features of users significantly enhance the state of the art. Since posts on social media often includes data of multiple modalities (e.g., a combination

of images and text), abuse detection systems would also need to incorporate a multi-modal component. Facebook recently released a dataset consisting of multi-modal hateful memes (Kiela et al., 2020) under the *Hateful Memes Challenge* to foster research in this area.

Despite the fast-paced progress in this field, an important challenge that remains mostly unsolved is that of recognizing implicit abuse (van Aken et al., 2018). Implicit abuse comes in the form of figurative language, such as sarcasm, irony or metaphor, rhetorical questions, analogies and comparisons. Metaphor and sarcasm are particularly common, and tend to express stronger emotions and sentiments than the literally-used words and phrases (Mohammad et al., 2016). Nobata et al. (2016) (among others) noted that sarcastic comments are hard for abuse detection methods to deal with since surface features are not sufficient; typically the knowledge of the context or background of the user is also required. Mishra (2018) found that metaphors are more frequent in abusive samples as opposed to non-abusive ones. However, to fully understand the impact of figurative devices on abuse detection, datasets with more pronounced presence of these are required.

The key to modeling implicit abuse, and detecting abuse more accurately in general, might lie in shifting focus from modeling individual comments to modeling online conversations and how they evolve and escalate towards abuse. Abuse is inherently contextual; it can only be interpreted as part of a wider conversation between users on the Internet. This means that, in practice, individual comments can be difficult to classify without modeling their respective contexts. Mishra et al. (2018a) have pointed out that some tweets in DATA-TWITTER-WH do not contain sufficient lexical or semantic information to detect abuse even in principle, e.g., *@user: Logic in the world of Islam <http://t.co/xxxxxxx>*, and techniques for modeling discourse and elements of pragmatics are needed. To address this issue, Gao and Huang (2017), working with DATA-FOX-NEWS, incorporate features from two sources of context: the title of the news article for which the comment was posted, and the screen name of the user who posted it. Yet this is only a first step towards modeling the wider context in abuse detection; more sophisticated techniques are needed to capture the history of the conversation and the behavior of the users as it develops over time. NLP techniques for modeling discourse and dialogue can be a good starting point in this line of research.

Another challenge in modeling abuse is presented by its ever-changing nature, as societies and technologies evolve. New abusive words and phrases continue to enter the language (Wiegand et al., 2018b). Working with the DATA-YAHOO-*-B datasets, Nobata et al. (2016) found that a classifier trained on more recent data outperforms one trained on older data. They noted that a prominent factor in this is the continuous evolution of the Internet jargon. We would like to add that, given the *situational* and topical nature of abuse (Chandrasekharan et al., 2018), contextual features learned by detection methods may become irrelevant over time. A similar trend also holds for abuse detection across domains. Wiegand et al. (2018b) showed that the performance of the (then) state of the art classifiers (Nobata et al., 2016; Pavlopoulos et al., 2017b) decreases substantially when tested on data drawn from domains different to that of the training set. They attributed this trend to lack of domain-specific learning. Chandrasekharan et al. (2017) propose an approach that utilizes similarity scores between posts to improve in-domain performance based on out-of-domain data. Possible solutions for improving cross-domain abuse detection can be found in the literature of (adversarial) multi-task learning and domain adaptation (Daumé III, 2009; Ganin et al., 2016; Wu and Huang, 2015), and also in works such as that of Sharifirad et al. (2018) who utilize knowledge graphs to augment the training of a sexist tweet classifier. Recently, Waseem et al. (2018) and Karan and Šnajder (2018) exploited multi-task learning frameworks to train models that are robust across data from different distributions or data annotated under different guidelines.

5.2 Ethical questions around automated abuse detection

Identifying experiences as abusive provides validation to victims of abuse and enables observers to grasp the scope of the problem. It also creates new descriptive norms, suggesting what types of behavior constitute abuse, and outlines existing expectations around appropriate behavior. On the other hand, automated systems can invalidate abusive experiences, particularly for victims whose experiences may not lie in the realm of *typical* ones (Blackwell et al., 2017). This points to a critical issue: automated systems embody

the morals and values of their creators and annotators (Bowker and Star, 2000; Blackwell et al., 2017). It is therefore imperative that we design systems that are robust to such issues, e.g., some recent works have investigated ways to mitigate gender bias in models (Binns et al., 2017; Park et al., 2018).

That said, unfortunately, whilst the research community has started incorporating signals from user profiling, there has not yet been a discussion of ethical guidelines for doing so. To encourage such a discussion, we lay out four ethical considerations in the design of such approaches:

- The profiling approach should not compromise the *privacy* of the user. So a researcher might ask themselves such questions as: is the profiling based on identity traits of users (e.g., gender, race etc.) or solely on their online behavior? And is an appropriate generalization from (identifiable) user traits to population-level behavioral trends performed?
- One needs to reflect on the possible *bias* in the training procedure; is the approach likely to induce a bias against users with certain traits?
- The *visibility* aspect needs to be accounted for; is the profiling visible to the users, i.e., can users directly or indirectly observe how they (or others) have been profiled?
- One needs to carefully consider the *purpose* of such profiling; is it intended to take actions against users, or is it more benign (e.g. to better understand the content produced by them and make task-specific generalizations)?

While we do not intend to provide answers to these questions within this paper, we hope that the above considerations can help to start a debate on these important issues.

5.3 Explainable abuse detection

Explainability has become an important aspect within NLP, and within AI generally. Yet there has been no discussion of this issue in the context of abuse detection systems. We hereby propose three properties that an *explainable* abuse detection system should aim to exhibit.

- It needs to *establish intent* of abuse (or the lack of it) and provide evidence for it, hence convincingly segregating abuse from other phenomena such as sarcasm and humor.
- It needs to *capture abusive language*, i.e., highlight instances of abuse if present, be they explicit (i.e., use of expletives) or implicit (e.g., dehumanizing comparisons).
- It needs to *identify the target(s)* of abuse (or the absence thereof), be it an individual or a group.

These properties align well with the categorizations of abuse we discussed in the introduction. They also aptly motivate the advances needed in the field: (1) developments in areas such as sarcasm detection and user profiling for precise segregation of abusive intent from humor, satire, etc.; (2) better identification of implicit abuse, which requires improvements in modeling of figurative language; (3) effective detection of generalized abuse and inference of target(s), which require advances in areas such as domain adaptation and conversation modeling.

6 Conclusions

Online abuse stands as a significant challenge before society. Its nature and characteristics constantly evolve, making it a complex phenomenon to study and model. Methods for automated abuse detection have seen a lot of development in recent years: from simple rule-based ones aimed at identifying directed and explicit abuse to sophisticated ones that can capture rich semantic information and even aspects of user behavior. By providing a comprehensive review of the field to date, our paper aims to lay a platform for future research, facilitating progress in this important effort. While we see an array of challenges that lie ahead, e.g., modeling extra-propositional aspects of language, user behavior and wider conversation, we believe that recent progress in the areas of semantics, dialogue modeling and social media analysis put the research community in a strong position to address them. The notion of abuse has been rather hard to

define due to differing opinions on sarcasm, self-deprecating humor, and terms seen as offensive, to name a few issues. In fact, attempts to impose a definition may also curb the diversity that exists across various abuse datasets since what constitutes abuse varies from culture to culture. But we do believe that the NLP community can and should work towards standardizing the understanding of different characteristics of abuse, examples of which are presented in the paper: directed, generalized, implicit and explicit. This will allow for more comparable and systematic modeling of different types of abuse (including those that might emerge in the future) and also facilitate transfer learning across them.

References

- Segun Taofeek Aroyehun and Alexander Gelbukh. 2018. Aggression detection in social media: Using deep neural networks, data augmentation, and pseudo labeling. In *Proceedings of the First Workshop on Trolling, Aggression and Cyberbullying (TRAC-2018)*, pages 90–97.
- Pinkesh Badjatiya, Shashank Gupta, Manish Gupta, and Vasudeva Varma. 2017. Deep learning for hate speech detection in tweets. In *Proceedings of the 26th International Conference on World Wide Web Companion, WWW '17 Companion*, pages 759–760. The International World Wide Web Conference Committee.
- Reuben Binns, Michael Veale, Max Van Kleek, and Nigel Shadbolt. 2017. Like trainer, like bot? inheritance of bias in algorithmic content moderation. In *International Conference on Social Informatics*, pages 405–415. Springer.
- Lindsay Blackwell, Jill Dimond, Sarita Schoenebeck, and Cliff Lampe. 2017. Classification and its consequences for online harassment: Design insights from heartmob. *Proceedings of the ACM on Human-Computer Interaction*, 1(CSCW):24.
- Piotr Bojanowski, Edouard Grave, Armand Joulin, and Tomas Mikolov. 2017. Enriching word vectors with subword information. *Transactions of the Association for Computational Linguistics*, 5:135–146.
- Geoffrey C Bowker and Susan Leigh Star. 2000. *Sorting things out: Classification and its consequences*. MIT press.
- Peter Burnap and Matthew Leighton Williams. 2014. Hate speech, machine classification and statistical modelling of information flows on twitter: Interpretation and communication for policy decision making. In *Proceedings of Internet, Policy & Politics, IPP '14*, pages 1–18.
- Michael Castelle. 2018. The linguistic ideologies of deep abusive language classification. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 160–170, Brussels, Belgium, October. Association for Computational Linguistics.
- Eshwar Chandrasekharan, Mattia Samory, Anirudh Srinivasan, and Eric Gilbert. 2017. The bag of communities: Identifying abusive behavior online with preexisting internet data. In *Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems*, pages 3175–3187. ACM.
- Eshwar Chandrasekharan, Mattia Samory, Shagun Jhaver, Hunter Charvat, Amy Bruckman, Cliff Lampe, Jacob Eisenstein, and Eric Gilbert. 2018. The internet’s hidden rules: An empirical study of reddit norm violations at micro, meso, and macro scales. *Proceedings of the ACM on Human-Computer Interaction*, 2(CSCW):32.
- Maral Dadvar, Dolf Trieschnigg, Roeland Ordelman, and Franciska de Jong. 2013. Improving cyberbullying detection with user context. In *Proceedings of the 35th European Conference on Advances in Information Retrieval, ECIR'13*, pages 693–696.
- Hal Daumé III. 2009. Frustratingly easy domain adaptation. *arXiv preprint arXiv:0907.1815*.
- Thomas Davidson, Dana Warmusley, Michael Macy, and Ingmar Weber. 2017. Automated hate speech detection and the problem of offensive language. In *Proceedings of the 11th International AAAI Conference on Web and Social Media, ICWSM '17*.
- Jesse Davis and Mark Goadrich. 2006. The relationship between precision-recall and roc curves. In *Proceedings of the 23rd International Conference on Machine Learning, ICML '06*, pages 233–240, New York, NY, USA. ACM.

- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota, June. Association for Computational Linguistics.
- Karthik Dinakar, Roi Reichart, and Henry Lieberman. 2011. Modeling the detection of textual cyberbullying. In *Association for the Advancement of Artificial Intelligence*.
- Nemanja Djuric, Jing Zhou, Robin Morris, Mihajlo Grbovic, Vladan Radosavljevic, and Narayan Bhamidipati. 2015. Hate speech detection with comment embeddings. In *Proceedings of the 24th International Conference on World Wide Web, WWW '15 Companion*, pages 29–30. Association for Computing Machinery.
- Maeve Duggan. 2017. Online harassment 2017.
- Paula Fortuna and Sérgio Nunes. 2018. A survey on automatic detection of hate speech in text. *ACM Comput. Surv.*, 51(4):85:1–85:30, July.
- Antigoni Founta, Constantinos Djouvas, Despoina Chatzakou, Ilias Leontiadis, Jeremy Blackburn, Gianluca Stringhini, Athena Vakali, Michael Sirivianos, and Nicolas Kourtellis. 2018. Large scale crowdsourcing and characterization of twitter abusive behavior. In *International AAAI Conference on Web and Social Media*.
- Patxi Galán-García, José Gaviria de la Puerta, Carlos Laorden Gómez, Igor Santos, and Pablo García Bringas. 2016. Supervised machine learning for the detection of troll profiles in twitter social network: Application to a real case of cyberbullying. *Logic Journal of the IGPL*, 24(1):42–53.
- Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. 2016. Domain-adversarial training of neural networks. *The Journal of Machine Learning Research*, 17(1):2096–2030.
- Lei Gao and Ruihong Huang. 2017. Detecting online hate speech using context aware models. In *Proceedings of Recent Advances in Natural Language Processing (RANLP)*, pages 260–266.
- Aditya Grover and Jure Leskovec. 2016. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*.
- Will Hamilton, Zhitao Ying, and Jure Leskovec. 2017. Inductive representation learning on large graphs. In *Advances in Neural Information Processing Systems*, pages 1024–1034.
- L. A. Jeni, J. F. Cohn, and F. De La Torre. 2013. Facing imbalanced data—recommendations for the use of performance metrics. In *2013 Humaine Association Conference on Affective Computing and Intelligent Interaction*, pages 245–251, Sept.
- Mladen Karan and Jan Šnajder. 2018. Cross-domain detection of abusive language online. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 132–137. Association for Computational Linguistics.
- Douwe Kiela, Hamed Firooz, Aravind Mohan, Vedanuj Goswami, Amanpreet Singh, Pratik Ringshia, and Davide Testuggine. 2020. The hateful memes challenge: Detecting hate speech in multimodal memes.
- Thomas N. Kipf and Max Welling. 2017. Semi-supervised classification with graph convolutional networks. In *Proceedings of the 5th International Conference on Learning Representations, ICLR '17*.
- Ritesh Kumar, Atul Kumar Ojha, Shervin Malmasi, and Marcos Zampieri. 2018. Benchmarking aggression identification in social media. In *Proceedings of the First Workshop on Trolling, Aggression and Cyberbullying (TRAC-2018)*, pages 1–11.
- Quoc Le and Tomas Mikolov. 2014. Distributed representations of sentences and documents. In *Proceedings of the 31st International Conference on Machine Learning*.
- Younghun Lee, Seunghyun Yoon, and Kyomin Jung. 2018. Comparative studies of detecting abusive language on twitter. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 101–106. Association for Computational Linguistics.
- Nikola Ljubešić, Tomaž Erjavec, and Darja Fišer. 2018. Datasets of slovene and croatian moderated news comments. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 124–131. Association for Computational Linguistics.

- Puneet Mathur, Ramit Sawhney, Meghna Ayyar, and Rajiv Shah. 2018. Did you offend me? classification of offensive tweets in hinglish language. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 138–148. Association for Computational Linguistics.
- Yashar Mehdad and Joel Tetreault. 2016. Do characters abuse more than words? In *Proceedings of the 17th Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pages 299–303. Association for Computational Linguistics.
- Pushkar Mishra, Marco Del Tredici, Helen Yannakoudakis, and Ekaterina Shutova. 2018a. Author profiling for abuse detection. In *Proceedings of COLING 2018*, pages 1088–1098. Association for Computational Linguistics.
- Pushkar Mishra, Ekaterina Shutova, and Helen Yannakoudakis. 2018b. Neural character-based composition models for abuse detection. In *Proceedings of the EMNLP Workshop on Abusive Language Online (ALW2)*, pages 1–10. Association for Computational Linguistics.
- Pushkar Mishra, Marco Del Tredici, Helen Yannakoudakis, and Ekaterina Shutova. 2019. Abusive language detection with graph convolutional networks. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*. Association for Computational Linguistics.
- Pushkar Mishra. 2018. CleanInternet. Bachelor’s thesis, University of Cambridge, United Kingdom.
- Saif M Mohammad, Ekaterina Shutova, and Peter D Turney. 2016. Metaphor as a medium for emotion: An empirical study. In *Proceedings of *SEM 2016*.
- Joaquin Padilla Montani and Peter Schller. 2019. Tuwienkbs19 at germeval task 2, 2019: Ensemble learning for german offensive language detection. In *Proceedings of the 15th Conference on Natural Language Processing (KONVENS 2019)*, pages 418–422, Erlangen, Germany. German Society for Computational Linguistics & Language Technology.
- Joaquin Padilla Montani. 2018. Tuwienkbs at germeval 2018: German abusive tweet detection. In *Proceedings of GermEval 2018, 14th Conference on Natural Language Processing (KONVENS 2018)*, KONVENS 2018.
- Hamdy Mubarak, Kareem Darwish, and Walid Magdy. 2017. Abusive language detection on Arabic social media. In *Proceedings of the First Workshop on Abusive Language Online (ALW)*.
- Emily R. Munro. 2011. The protection of children online: a brief scoping review to identify vulnerable groups, 8.
- Dennis Njagi, Z Zuping, Damien Hanyurwimfura, and Jun Long. 2015. A lexicon-based approach for hate speech detection. *International Journal of Multimedia and Ubiquitous Engineering*, 10:215–230, 04.
- Chikashi Nobata, Joel Tetreault, Achint Thomas, Yashar Mehdad, and Yi Chang. 2016. Abusive language detection in online user content. In *Proceedings of the 25th International Conference on World Wide Web, WWW ’16*, pages 145–153. The International World Wide Web Conference Committee.
- Andrei Paraschiv and Dumitru-Clementin Cercel. 2019. Upb at germeval-2019 task 2: Bert-based offensive language classification of german tweets. In *Proceedings of the 15th Conference on Natural Language Processing (KONVENS 2019)*, pages 398–404, Erlangen, Germany. German Society for Computational Linguistics & Language Technology.
- Ji Ho Park and Pascale Fung. 2017. One-step and two-step classification for abusive language detection on twitter. In *Proceedings of the 1st Workshop on Abusive Language Online*, pages 41–45. Association for Computational Linguistics.
- Ji Ho Park, Jamin Shin, and Pascale Fung. 2018. Reducing gender bias in abusive language detection. *arXiv preprint arXiv:1808.07231*.
- John Pavlopoulos, Prodromos Malakasiotis, and Ion Androutsopoulos. 2017a. Deep learning for user comment moderation. In *Proceedings of the 1st Workshop on Abusive Language Online*, pages 25–35. Association for Computational Linguistics.
- John Pavlopoulos, Prodromos Malakasiotis, and Ion Androutsopoulos. 2017b. Deeper attention to abusive user content moderation. In *Proceedings of EMNLP 2017*, pages 1125–1135. Association for Computational Linguistics.

- John Pavlopoulos, Prodromos Malakasiotis, Juli Bakagianni, and Ion Androutsopoulos. 2017c. Improved abusive comment moderation with user embeddings. In *Proceedings of the 2017 EMNLP Workshop: Natural Language Processing meets Journalism*, pages 51–55. Association for Computational Linguistics.
- Jing Qian, Mai ElSherief, Elizabeth Belding, and William Yang Wang. 2018. Leveraging intra-user and inter-user representation learning for automated hate speech detection. In *Proceedings of the 2018 Conference of the NAACL: Human Language Technologies, Volume 2 (Short Papers)*, pages 118–123. Association for Computational Linguistics.
- Santhosh Rajamanickam, Pushkar Mishra, Helen Yannakoudakis, and Ekaterina Shutova. 2020. Joint modelling of emotion and abusive language detection. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4270–4279, Online, July. Association for Computational Linguistics.
- Amir H. Razavi, Diana Inkpen, Sasha Uritsky, and Stan Matwin. 2010. Offensive language detection using multi-level classification. In *Proceedings of the 23rd Canadian Conference on Advances in Artificial Intelligence, AI'10*, pages 16–27.
- Manoel Ribeiro, Pedro Calais, Yuri Santos, Virglio Almeida, and Wagner Meira Jr. 2018. Characterizing and detecting hateful users on twitter. In *International AAAI Conference on Web and Social Media*.
- Julian Risch, Eva Krebs, Alexander Lser, Alexander Riese, and Ralf Krestel. 2018. Fine-grained classification of offensive language. In *Proceedings of GermEval 2018, 14th Conference on Natural Language Processing (KONVENS 2018)*.
- Julian Risch, Anke Stoll, Marc Ziegele, and Ralf Krestel. 2019. hpidedis at germeval 2019: Offensive language identification using a german bert model. In *Proceedings of the 15th Conference on Natural Language Processing (KONVENS 2019)*, pages 405–410, Erlangen, Germany. German Society for Computational Linguistics & Language Technology.
- Björn Ross, Michael Rist, Guillermo Carbonell, Ben Cabrera, Nils Kurowsky, and Michael Wojatzki. 2016. Measuring the Reliability of Hate Speech Annotations: The Case of the European Refugee Crisis. In *Proceedings of NLP4CMC III: 3rd Workshop on NLP for Computer-Mediated Communication*, pages 6–9.
- Joni Salminen, Hind Almerkhi, Milica Milenkovi, Soon gyo Jung, Jisun An, Haewoon Kwak, and Bernard Jansen. 2018. Anatomy of online hate: Developing a taxonomy and machine learning models for identifying and classifying hate in online news media. In *International AAAI Conference on Web and Social Media*.
- Niloofer Safi Samghabadi, Suraj Maharjan, Alan Sprague, Raquel Diaz-Sprague, and Thamar Solorio. 2017. Detecting nastiness in social media. In *Proceedings of the 1st Workshop on Abusive Language Online*, pages 63–72. Association for Computational Linguistics.
- Niloofer Safi Samghabadi, Deepthi Mave, Sudipta Kar, and Thamar Solorio. 2018. RiTUAL-UH at TRAC 2018 Shared Task: Aggression Identification. In *Proceedings of the First Workshop on Trolling, Aggression and Cyberbullying*, pages 12–18.
- Niloofer Safi Samghabadi, Afsheen Hatami, Mahsa Shafaei, Sudipta Kar, and Thamar Solorio. 2019. Attending the emotions to detect online abusive language. *arXiv preprint arXiv:1909.03100*.
- Florian Schmid, Justine Thielemann, Anna Mantwill, Jian Xi, Dirk Labudde, and Michael Spranger. 2019. Fossil - offensive language classification of german tweets combining svms and deep learning techniques. In *Proceedings of the 15th Conference on Natural Language Processing (KONVENS 2019)*, pages 382–386, Erlangen, Germany. German Society for Computational Linguistics & Language Technology.
- Anna Schmidt and Michael Wiegand. 2017. A survey on hate speech detection using natural language processing. In *Proceedings of the 5th International Workshop on Natural Language Processing for Social Media*, pages 1–10. Association for Computational Linguistics.
- Sima Sharifirad, Borna Jafarpour, and Stan Matwin. 2018. Boosting text classification performance on sexist tweets by text augmentation and text generation using a combination of knowledge graphs. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 107–114, Brussels, Belgium, October. Association for Computational Linguistics.
- Vinay Singh, Aman Varshney, Syed Sarfaraz Akhtar, Deepanshu Vijay, and Manish Shrivastava. 2018. Aggression detection on social media text using deep neural networks. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 43–50. Association for Computational Linguistics.

- Sara Owsley Sood, Judd Antin, and Elizabeth F Churchill. 2012. Using crowdsourcing to improve profanity detection. In *AAAI Spring Symposium: Wisdom of the Crowd*, volume 12, page 06.
- Ellen Spertus. 1997. Smokey: Automatic recognition of hostile messages. In *Proceedings of the 14th AAAI and 9th IAAI, AAAI'97/IAAI'97*, pages 1058–1065. AAAI Press.
- Julia Maria Stru, Melanie Siegel, Josep Ruppenhofer, Michael Wiegand, and Manfred Klenner. 2019. Overview of germeval task 2, 2019 shared task on the identification of offensive language. In *Proceedings of the 15th Conference on Natural Language Processing (KONVENS 2019)*, pages 354–365, Erlangen, Germany. German Society for Computational Linguistics & Language Technology.
- Huei-Po Su, Chen-Jie Huang, Hao-Tsung Chang, and Chuan-Jie Lin. 2017. Rephrasing Profanity in Chinese Text. In *Proceedings of the Workshop on Abusive Language Online (ALW)*.
- Elise Fehn Unsvåg and Björn Gambäck. 2018. The effects of user features on twitter hate speech detection. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 75–85. Association for Computational Linguistics.
- Betty van Aken, Julian Risch, Ralf Krestel, and Alexander Löser. 2018. Challenges for toxic comment classification: An in-depth error analysis. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 33–42, Brussels, Belgium, October. Association for Computational Linguistics.
- Vincent Van Asch. 2013. Macro-and micro-averaged evaluation measures [[basic draft]]. *Computational Linguistics & Psycholinguistics, University of Antwerp, Belgium*.
- Cynthia Van Hee, Els Lefever, Ben Verhoeven, Julie Mennes, Bart Desmet, Guy De Pauw, Walter Daelemans, and Veronique Hoste. 2015. Detection and fine-grained classification of cyberbullying events. In *Proceedings of the International Conference Recent Advances in Natural Language Processing*, pages 672–680. INCOMA Ltd. Shoumen, BULGARIA.
- Dirk von Grünigen, Fernando Benites, Pius von Däniken, Mark Cieliebak, Ralf Grubenmann, and AG Spinning-Bytes. 2018. spmmmp at germeval 2018 shared task: Classification of offensive content in tweets using convolutional neural networks and gated recurrent units. In *Proceedings of GermEval 2018, 14th Conference on Natural Language Processing (KONVENS 2018)*.
- Cindy Wang. 2018. Interpreting neural network hate speech classifiers. In *Proceedings of the 2nd Workshop on Abusive Language Online (ALW2)*, pages 86–92. Association for Computational Linguistics.
- William Warner and Julia Hirschberg. 2012. Detecting hate speech on the world wide web. In *Proceedings of the 2nd Workshop on Language in Social Media, LSM '12*, pages 19–26. Association for Computational Linguistics.
- Zeeraq Waseem and Dirk Hovy. 2016. Hateful symbols or hateful people? Predictive features for hate speech detection on twitter. In *Proceedings of the NAACL SRW*, pages 88–93. Association for Computational Linguistics, June.
- Zeeraq Waseem, Thomas Davidson, Dana Warmusley, and Ingmar Weber. 2017. Understanding abuse: A typology of abusive language detection subtasks. In *Proceedings of the 1st Workshop on Abusive Language Online*, pages 78–84. Association for Computational Linguistics.
- Zeeraq Waseem, James Thorne, and Joachim Bingel. 2018. Bridging the gaps: Multi task learning for domain transfer of hate speech detection. In *Online Harassment*, pages 29–55. Springer.
- Zeeraq Waseem. 2016. Are you a racist or am I seeing things? annotator influence on hate speech detection on twitter. In *Proceedings of the 1st Workshop on NLP and Computational Social Science*, pages 138–142. Association for Computational Linguistics.
- Michael Wiegand, Anastasija Amann, Tatiana Anikina, Aikaterini Azoidou, Anastasia Borisenkov, Kirstin Kolmorgen, Insa Kroger, and Christine Schäfer. 2018a. Saarland university's participation in the germeval task 2018 (udsw) – examining different types of classifiers and features. In *Proceedings of GermEval 2018, 14th Conference on Natural Language Processing (KONVENS 2018)*.
- Michael Wiegand, Josef Ruppenhofer, Anna Schmidt, and Clayton Greenberg. 2018b. Inducing a lexicon of abusive words – a feature-based approach. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 1046–1056. Association for Computational Linguistics.

- Michael Wiegand, Melanie Siegel, and Josef Ruppenhofer. 2018c. Overview of the GermEval 2018 Shared Task on the Identification of Offensive Language. In *Proceedings of GermEval 2018, 14th Conference on Natural Language Processing (KONVENS 2018)*.
- Michael Wiegand, Josef Ruppenhofer, and Thomas Kleinbauer. 2019. Detection of abusive language: the problem of biased datasets. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 602–608.
- Fangzhao Wu and Yongfeng Huang. 2015. Collaborative multi-domain sentiment classification. In *2015 IEEE International Conference on Data Mining*, pages 459–468. IEEE.
- Ellery Wulczyn, Nithum Thain, and Lucas Dixon. 2017a. Ex machina: Personal attacks seen at scale. In *Proceedings of the 26th International Conference on World Wide Web, WWW '17*, pages 1391–1399. The International World Wide Web Conference Committee.
- Ellery Wulczyn, Nithum Thain, and Lucas Dixon. 2017b. Wikipedia Talk Corpus, 1.
- Dawei Yin, Brian D. Davison, Zhenzhen Xue, Liangjie Hong, April Kontostathis, and Lynne Edwards. 2009. Detection of harassment on web 2.0. In *Processings of the Content Analysis in the WEB 2.0*.
- Seunghyun Yoon, Joongbo Shin, and Kyomin Jung. 2018. Learning to rank question-answer pairs using hierarchical recurrent encoder with latent topic clustering. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 1575–1584. Association for Computational Linguistics.
- Marcos Zampieri, Shervin Malmasi, Preslav Nakov, Sara Rosenthal, Noura Farra, and Ritesh Kumar. 2019. Predicting the Type and Target of Offensive Posts in Social Media. In *Proceedings of the 17th Annual Conference of the North American Chapter of the Association for Computational Linguistics*.
- Ziqi Zhang, David Robinson, and Jonathan Tepper. 2018. Detecting hate speech on twitter using a convolution-gru based deep neural network. In Aldo Gangemi, Roberto Navigli, Maria-Esther Vidal, Pascal Hitzler, Raphaël Troncy, Laura Hollink, Anna Tordai, and Mehwish Alam, editors, *The Semantic Web*, pages 745–760, Cham. Springer International Publishing.

Appendix A Summaries of public datasets

In table 2, we summarize the datasets described in this paper that are publicly available and provide links to them.

Appendix B A discussion of metrics

The performance results we have reported highlight that, throughout work on abuse detection, different researchers have utilized different evaluation metrics for their experiments – from area under the receiver operating characteristic curve (AUROC) (Wulczyn et al., 2017a; Djuric et al., 2015) to micro and macro F_1 (Mishra et al., 2018b) – regardless of the properties of their datasets. This makes the presented techniques more difficult to compare. In addition, as abuse is a relatively infrequent phenomenon, the datasets are typically skewed towards non-abusive samples (Waseem, 2016). Metrics such as AUROC may, therefore, be unsuitable since they may mask poor performance on the abusive samples as a side-effect of the large number of non-abusive samples (Jeni et al., 2013). *Macro-averaged* precision, recall, and F_1 , as well as precision, recall, and F_1 on specifically the abusive classes, may provide a more informative evaluation strategy; the primary advantage being that macro-averaged metrics provide a sense of effectiveness on the minority classes (Van Asch, 2013). Additionally, area under the precision-recall curve (AUPRC) might be a better alternative to AUROC in imbalanced scenarios (Davis and Goadrich, 2006).

Appendix C Embeddings and OOV words

Djuric et al. (2015) and Nobata et al. (2016) observed that abusive language tends to contain obfuscations (e.g., *w0m3n*). This poses a particular problem for abuse detection methods (Blackwell et al., 2017) and specifically for those that rely on word-level neural networks as they operate with a finite vocabulary of words and map all unknown words in the test set to a single out-of-vocabulary (OOV) embedding. This has the undesired effect that deliberately obfuscated words and benign misspellings get conflated, leading to loss in performance (Mishra et al., 2018a; Qian et al., 2018). Spelling correction and edit-distance techniques for resolving obfuscations can provide some level of mitigation; however, they do not help in cases where obfuscation is severe, e.g., *a55h0le*, or is by concatenation, e.g., *idiotb*tch*. While one way around the problem is to have character-level models, Mishra et al. (2018b) showed that such models perform worse than word-level ones with pre-trained embeddings. Hence, techniques to generate embeddings for OOV words on the fly (Bojanowski et al., 2017; Mishra et al., 2018b) have been exploited.

Dataset link	Associated paper	Language	Size	Source	Composition
DATA-TWITTER-WH	(Waseem and Hovy, 2016)	English	17k	Twitter	<i>Racism, Sexism, Neither</i>
DATA-TWITTER-W	(Waseem, 2016)	English	7k	Twitter	<i>Racism, Sexism, Both, Neither</i>
DATA-TWITTER-DAVID	(Davidson et al., 2017)	English	25k	Twitter	<i>Racist, Offensive, Clean</i>
DATA-TWITTER-F	(Founta et al., 2018)	English	80k	Twitter	<i>Abusive, Spam, Hateful, Normal</i>
DATA-WIKI-ATT	(Wulczyn et al., 2017b)	English	116k	Wikipedia talk page	<i>Personal attack, Clean</i>
DATA-WIKI-AGG	(Wulczyn et al., 2017b)	English	116k	Wikipedia talk page	<i>Aggressive, Clean</i>
DATA-WIKI-TOX	(Wulczyn et al., 2017b)	English	160k	Wikipedia talk page	<i>Toxic, Clean</i>
DATA-FOX-NEWS	(Gao and Huang, 2017)	English	1.5k	Fox news	<i>Hateful, Non-hateful</i>
DATA-GAZZETTA	(Pavlopoulos et al., 2017b)	Greek	1.6M	Gazzetta	<i>Accept, Reject</i>
DATA-FACEBOOK	(Kumar et al., 2018)	Hindi & English	15k	Facebook	<i>{Covertly, Overtly, Non}-aggressive</i>
<i>Arabic News</i>	(Mubarak et al., 2017)	Arabic	32k	Aljazeera News	<i>Obscene, Offensive, Clean</i>
<i>GermEval 2018</i>	(Wiegand et al., 2018c)	German	8.5k	Twitter	<i>Abuse, Insult, Profanity, Other</i>
<i>Ask.fm</i>	(Samghabadi et al., 2017)	English	5.6k	Ask.fm	<i>Invective, Neutral</i>

Table 2: Links and summaries of datasets mentioned in the paper that are publicly available.