Engineering Boolean Matrix Multiplication for Multiple-Accelerator Shared-Memory Architectures

MATTI KARPPA, Aalto University, Finland

PETTERI KASKI, Aalto University, Finland

We study the problem of multiplying two bit matrices with entries either over the Boolean algebra $(0, 1, \lor, \land)$ or over the binary field $(0, 1, +, \cdot)$. We engineer high-performance open-source algorithm implementations for contemporary multiple-accelerator shared-memory architectures, with the objective of time-and-energy-efficient scaling up to input sizes close to the available shared memory capacity. For example, given two terabinary-bit square matrices as input, our implementations compute the Boolean product in approximately 2100 seconds (1.0 Pbop/s at 3.3 pJ/bop for a total of 2.1 kWh/product) and the binary product in less than 950 seconds (2.4 effective Pbop/s at 1.5 effective pJ/bop for a total of 0.92 kWh/product) on an NVIDIA DGX-1 with power consumption at peak system power (3.5 kW).

Our contributions are (a) for the binary product, we use alternative-basis techniques of Karstadt and Schwartz [SPAA'17] to design novel alternative-basis variants of Strassen's recurrence for 2×2 block multiplication [Numer. Math. 13 (1969)] that have been optimized for both the number of additions and low working memory, (b) structuring the parallel block recurrences and the memory layout for coalescent and register-localized execution on accelerator hardware, (c) low-level engineering of the innermost block products for the specific target hardware, and (d) structuring the top-level shared-memory implementation to feed the accelerators with data and integrate the results for input and output sizes beyond the aggregate memory capacity of the available accelerators.

CCS Concepts: • Computing methodologies \rightarrow Linear algebra algorithms; Shared memory algorithms; • Mathematics of computing \rightarrow Mathematical software performance; • Computer systems organization \rightarrow Single instruction, multiple data.

Additional Key Words and Phrases: shared-memory, heterogeneous architecture, gpu, binary matrix multiplication, Boolean matrix multiplication

1 INTRODUCTION

Matrix multiplication is one of the most widely deployed primitives in computing. In a combinatorial context, one often encounters the task of multiplying *Boolean* matrices with entries in $\{0, 1\}$, and with the arithmetic taking place either over the Boolean algebra $(0, 1, \lor, \land)$ or over the binary field $(0, 1, +, \cdot)$. Fast algorithms for the Boolean product and the binary product of two bit matrices underlie the fastest known algorithms for a wide range of tasks, such as transitive closure, context-free parsing, and triangle detection [11, 12, 17, 36, 38].

Our interest in this paper is to engineer high-performance open-source implementations of Boolean and binary matrix multiplication for shared-memory platforms connected to multiple vector-parallel accelerator devices. Such platforms are the state of the art in terms of delivering both

- (i) speed through extensive parallelism available in the accelerator devices, and
- (ii) energy-efficiency for moderately large data through shared memory.¹

Configurations of this type are not only powerful individual systems; indeed, shared-memory platforms with multiple accelerator devices are individual compute nodes in larger distributed-memory systems ranging from a few compute

¹For example, a representative configuration of this type is the NVIDIA DGX-1, with eight Tesla V100 SXM2 accelerator devices (in total 40960 32-bit cores running at 1530-MHz boost clock), 512 GiB of shared DDR4-2133 memory, and 3.5-kW peak power consumption. This configuration can execute, at peak, $40960 \cdot 1530 \cdot 10^6 \cdot 32 = 2.01 \cdot 10^{15}$ bit operations per second (2.01 Pbop/s), which at peak power consumption translates to $1.8 \cdot 10^{-12}$ Joules of energy consumed per bit operation (1.8 pJ/bop).

nodes to current leading-edge supercomputers.² Thus, scalability to distributed-memory systems starts from carefully engineered shared-memory-accelerated implementations.

To our knowledge, the present paper constitutes the first study of Boolean matrix multiplication that seeks to push the envelope towards peak hardware performance on shared-memory-accelerated platforms simultaneously in terms of speed, energy consumption, and input sizes of up to one terabinary-bit (1048576 × 1048576 = $2^{20} \times 2^{20} = 2^{40}$ bits = 1 Tib = 128 GiB) per operand matrix.³ For example, given two terabinary-bit square matrices as input, our present open-source implementation computes the Boolean product in approximately 2100 seconds (1.0 Pbop/s at 3.3 pJ/bop for a total of 2.1 kWh/product) and the binary product in less than 950 seconds (2.4 effective Pbop/s at 1.5 effective pJ/bop for a total of 0.92 kWh/product) on an NVIDIA DGX-1 with power consumption at peak system power (3.5 kW).

1.1 Engineering Challenges

Before outlining our specific contributions in more detail, let us introduce some of the challenges when engineering for peak performance on inputs that nearly occupy the available capacity of shared memory and exceed the total memory available on the accelerators in a platform.

First, the mathematical framework for algorithm design needs fine-grained optimization beyond coarse tools offered by traditional asymptotic analysis. Algorithms for fast matrix multiplication are a canonical example of this phenomenon, where the asymptotically fastest known algorithm designs [8, 10, 22, 37] hide in their asymptotic analysis very large constants, which make these designs infeasible to use in practice; we refer to the recent survey by Pan [33] for an extensive discussion. For bit matrices, a natural first measure for the concrete efficiency of an algorithm design is the number of bit operations executed. For example, the elementary algorithm to multiply two $n \times n$ bit matrices uses $2n^3 - n^2$ bit operations, and the Strassen–Winograd algorithm [35, 41] for the binary field uses $6n^{\log_2 7} - 5n^2$ bit operations when n is a power of two. Already here one observes a leading constant that is three times the leading constant for the elementary algorithm, which necessitates $n \ge 512$ before the Strassen–Winograd algorithm uses fewer bit operations than the elementary algorithm. The Strassen–Winograd algorithm is known to be an optimal implementation of matrix multiplication relying on recursive 2×2 multiplications [5, 34], assuming one works in the standard basis. Recently, Karstadt and Schwartz [20] introduce an alternative-basis framework that reduces the number of bit operations of Strassen's algorithm to $5n^{\log_2 7} - 4n^2$, assuming the input and output are represented in an alternative basis. (The transformation of an $n \times n$ bit matrix between the standard basis and the alternative basis uses $n^2 \log_2 n$ bit operations.)

Second, accelerator hardware is designed to give peak performance when executing an identical instruction on each entry of a fixed-length vector of words. Thus, all recurrences of bit operations must be designed to support vectorization and coalesced memory accesses across words of bits. Due to pipelining and long latencies in accelerator hardware (cf. Mei and Chu [25] and Volkov [39]), recurrences should make use of the available lowest-latency memory (registers) and expose sufficient parallelism to enable a large number of threads simultaneously in execution compared with the number of cores for effective latency hiding. Furthermore, the bottom layer of recursion needs to be engineered for compatibility with the available low-level instruction set, such as vector-shuffles and custom bit operations given by a truth table. While the word- and vector-level hardware is at the moment rapidly evolving towards integrating increasingly domain-specific hardware units—for example, units that that perform small-size numerical matrix multiplication—the high-level

²For example, the Summit supercomputer at Oak Ridge National Laboratory—the first-ranked supercomputer on the June 2019 Top500-list (https: //top500.org)—consists of 4608 compute nodes, each of which has 512 GiB of shared DDR4 memory and six Tesla V100 SXM2 accelerator devices. ³Here we note that *numerical* rather than Boolean matrix multiplication has been extensively studied from an implementation engineering perspective

both in the setting of shared memory and in the setting of distributed memory—we postpone a discussion of related work to §1.3.

architecture with vectorization, pipelining, and long latencies is likely to remain more stable over time. In particular, this requires designs and engineering for the on-accelerator memory hierarchy that saturates the bandwidth of the dedicated hardware units.

Third, assuming each accelerator can be engineered to perform close to the peak available bandwidth in terms of bit operations per second, the host-level algorithm must be engineered to make effective use of the accelerators. This in particular means feeding the accelerators with input and aggregating their output in comparatively low-bandwidth shared memory across a low-bandwidth interconnect between the accelerators and the host. Our objective of engineering for inputs that are near the capacity of shared memory presents a further challenge in that at the host level we must use designs with a low memory footprint. We expect also these traits to withstand the test of time and thus warrant the present engineering effort.

1.2 Our Contributions

Let us now proceed to our specific contributions to address the aforementioned engineering challenges.

Fine-grained optimization of the base design. First, we proceed with a fine-grained optimization of Strassen's algorithm [35] using the alternative-basis framework of Karstadt and Schwartz [20] for the binary field. Essentially, we investigate all possible alternative bases over the binary field, and optimize (i) the number of Boolean operations for the alternative-basis multiplication, (ii) the weight distribution of linear combinations in the alternative basis, and (iii) the number of Boolean operations for changing between bases. Further desirable properties include in-place-computability and self-invertibility of the basis changes, as well as the ability to make chains of matrix multiplications in the alternative basis.

THEOREM 1.1 (MAIN, SELF-INVERSE AND IN-PLACE BASIS CHANGES). There exists an alternative-basis bilinear algorithm that multiplies two 2×2 input matrices over the binary field using

- (a) 3 additions to preprocess each input,
- (b) 7 noncommutative multiplications, and
- (c) 6 additions for postprocessing to obtain the output.

Moreover, the weight distribution in the alternative bases is 1, 1, 1, 1, 2, 2, 2. The basis changes between the standard basis and the alternative bases each use 2 additions, are self-inverse, and can be computed in-place.

Applied recursively in the alternative basis, Theorem 1.1 gives binary matrix multiplication using $5n^{\log_2 7} - 4n^2$ bit operations when *n* is a power of two. Changing between the standard basis and the alternative bases takes $\frac{1}{2}n^2\log_2 n$ bit operations and can be done in-place in memory, which presents a minor improvement over the original Karstadt–Schwartz design, but comes at the cost of losing the chain-multiplication property, which is desirable in many applications. The next theorem summarizes a new design that supports chain multiplication but is slightly less efficient than Theorem 1.1 in terms of its weight distributions, which results in slightly less efficiency when aggregating solutions of sub-instances in tight working memory at the host.

THEOREM 1.2 (MAIN, CHAIN-MULTIPLICATION). There exists an alternative-basis bilinear algorithm that multiplies two 2×2 input matrices over the binary field using

- (a) 3 additions to preprocess each input,
- (b) 7 noncommutative multiplications, and

(c) 6 additions for postprocessing to obtain the output.

Moreover, the weight distributions are 1, 1, 1, 1, 2, 2, 2 and 1, 1, 1, 1, 2, 3, 3 for taking linear combinations of the operands and the results of noncommutative multiplications, respectively. The basis changes between the standard basis and the alternative basis each use 2 additions, can be computed in-place, and support chain-multiplication in the alternative basis.

The proofs of Theorem 1.1 and Theorem 1.2 are presented in §2 together with a development of the alternativebasis framework using Kronecker products and Yates's algorithm [42] that enables easy parallelization on vectorized accelerator hardware.

Engineering for performance on accelerator hardware. Second, beyond optimizing the base design, we engineer an implementation suitable for vectorized accelerator hardware with extensive bit-operation-and-memory bandwidth but long latencies. Here the key engineering principle is to expose sufficient parallelism to saturate the compute cores with work and hide latency, but not to exceed the available on-accelerator memory. It is well known (e.g. [2, 23]) that bilinear block-recursive algorithm designs for matrix multiplication enable a tradeoff between

- parallel processing (executing the recursive block multiplications in parallel, or "breadth-first", using independent memory for each recursive case) and
- (2) serial processing (by processing the recursive multiplications serially one after another, or "depth-first", reusing memory).

We observe that this tradeoff also applies to alternative-basis algorithms, and illustate its application with a recursive design whose upper levels proceed serially through recursive calls to lower levels executed in parallel, relying on the recurrences underlying Theorems 1.1 and 1.2. The lower parallel levels consist of (i) parallel preprocessing for both inputs, (ii) parallel low-level optimized 64×64 bit-matrix-multiplication, and (iii) parallel postprocessing to recover the output. We fine-tune the performance of these levels for the target hardware by (a) merging consecutive levels so that the intermediate results are stored in per-thread registers and (b) working with the widest available per-thread load and store instructions for communicating between the per-thread registers and the on-accelerator memory.

For an $n \times n$ binary product for large enough n, these engineering considerations together with Theorem 1.1 and 1.2 enable us to obtain on a single Tesla V100 SXM2 accelerator an empirical effective bit-operation bandwidth that exceeds the theoretical boost-clock peak bandwidth for bit operations. Here by *effective* bandwidth we mean $\frac{2n^3-n^2}{T}$ bit operations per second, where $2n^3 - n^2$ is the number of bit operations to compute an $n \times n$ binary product with the elementary algorithm, and T is the measured wall-clock running time to compute an $n \times n$ binary product. We postpone a detailed review of empirical performance to §4.

Host-level implementation with a low memory footprint. Third, we engineer host-level subroutines that in parallel feed multiple accelerators with recursive subproblems and aggregate the results obtained to the host-level buffers. Here we follow a strategy of using multiple groups of threads on the host CPUs, where each group contains exactly one thread for each accelerator. Each group is responsible for a specific task in a pipeline of tasks, such as preparing subproblems from the host-level input, solving subproblems on accelerators, and integrating the results of subproblems into the host-level output. The threads coordinate their work through standard synchronization primitives such as mutexes and blocking. To maintain a low working-memory footprint in host memory, we use *q*-fold Kronecker products of the decomposition matrices underlying Theorems 1.1 and 1.2 to produce subproblems and aggregate the sub-results. This strategy in particular benefits from optimization of the weights of the decomposition matrices discussed above.

For the binary product, this strategy suffices to obtain aggregate effective bandwidth that exceeds the aggregate peak boost-clock bandwidth of the accelerators on inputs whose size is beyond the aggregate memory capacity of the accelerators. In particular, we consider it a very satisfactory engineering outcome as well as benchmark that we can deliver the binary product of two one-terabinary-bit square matrices in less than one thousand seconds and with less than one kilowatt-hour of energy consumption.

Open source. We release our present experimental algorithm implementations as open source⁴ to enable further engineering and to communicate precisely the lowest-level design decisions for current microarchitectures.

1.3 Earlier and Related Work

From a theory perspective, the study of fast algorithms for Boolean matrix multiplication has proceeded along essentially two lines of study. The first line of study either relies on the binary field directly or embeds the Boolean algebra to a ring, employing techniques for fast matrix multiplication over rings to obtain the result. Asymptotically the fastest known such algorithms run in time $O(n^{\omega+o(1)})$, where $2 \le \omega < 2.3728639$ is the exponent of matrix multiplication [8, 10, 22, 37].

While such algorithms are the fastest known in terms of asymptotic efficiency, practical algorithms for fast matrix multiplication over rings rely on recursive tensor techniques using small base tensors (e.g. [2, 4, 6, 9, 13– 15, 20, 21, 23, 24]) or trilinear aggregation–cancellation techniques [31, 32] for a small number of independent matrix multiplications (e.g. [18, 19]). These practical studies differ from our present work in that they consider numerical (floating-point) matrix multiplication for CPU-based shared- or distributed-memory systems, whereas we optimize for bit matrices and a multiple-accelerator shared-memory system. Furthermore, we rely on an alternative-basis approach optimized for bit matrices, whereas most of the earlier work—with the exception of Karstadt and Schwartz [20]—operates in the standard basis.

A second line of study on Boolean matrix multiplication seeks combinatorial rather than algebraic techniques to obtain competitive algorithms [1, 3, 7, 38, 43]. Currently, the fastest such algorithm runs asymptotically in time $\hat{O}(n^3/\log^4 n)$ [43]. However, we are not aware of engineering work to bring algorithms in this second line of study to the computing practice on contemporary parallel architectures.

2 ALTERNATIVE-BASIS MATRIX-MULTIPLICATION

This section develops the mathematical framework for alternative-basis matrix multiplication over the binary field $(0, 1, +, \cdot)$. We start by recalling the Strassen–Winograd standard-basis design, and then proceed to introduce two novel alternative-basis designs for use with the binary field as well as establishing our main theorems (Theorem 1.1 and Theorem 1.2). In essence, both new designs are variants of the design in Karstadt and Schwartz [20], with some further optimization of the designs in particular as pertains to the additive complexity and in-place computability of the basis changes. The rest of the section develops the mathematical framework of fast alternative-basis matrix multiplication with no claim on originality, apart perhaps from an expositionary choice to work with Kronecker products and Yates's algorithm [42] to highlight the symmetries and the easily vector-parallelizable sum-product-sum-layered structure of the framework. As discussed in the introduction, we expect this framework to withstand the test of time with further designs and evolving computing hardware.

⁴Cf. https://github.com/mkarppa/matmul.

2.1 The Strassen-Winograd Recurrences

We start by recalling the classical Strassen–Winograd design that works in the standard basis. It will be convenient to first state all algorithms as straight-line programs to highlight their additive complexity. Toward this end, suppose we are to multiply two matrices

$$A = \begin{bmatrix} A_{00} & A_{01} \\ A_{10} & A_{11} \end{bmatrix} \text{ and } B = \begin{bmatrix} B_{00} & B_{01} \\ B_{10} & B_{11} \end{bmatrix}$$
(1)

with entries over the binary field $(0, 1, +, \cdot)$.

The Strassen-Winograd design is as follows. First, compute the linear combinations

$$T_{0} \leftarrow A_{10} + A_{11}, \ T_{1} \leftarrow A_{01}, \ T_{2} \leftarrow A_{01} + A_{11}, \ T_{3} \leftarrow A_{10} + T_{2}, \ T_{4} \leftarrow A_{00} + T_{3}, \ T_{5} \leftarrow A_{10}, \qquad T_{6} \leftarrow A_{00},$$

$$S_{0} \leftarrow B_{10} + B_{11}, \ S_{1} \leftarrow B_{10}, \ S_{2} \leftarrow B_{01} + B_{11}, \ S_{3} \leftarrow B_{10} + S_{2}, \ S_{4} \leftarrow B_{01}, \qquad S_{5} \leftarrow B_{00} + S_{3}, \ S_{6} \leftarrow B_{00}.$$

(2)

Then, multiply the linear combinations to obtain the products

$$Q_0 \leftarrow T_0 S_0, \quad Q_1 \leftarrow T_1 S_1, \quad Q_2 \leftarrow T_2 S_2, \quad Q_3 \leftarrow T_3 S_3, \quad Q_4 \leftarrow T_4 S_4, \quad Q_5 \leftarrow T_5 S_5, \quad Q_6 \leftarrow T_6 S_6.$$
 (3)

Finally, compute the linear combinations of products

$$U_{0} \leftarrow Q_{1} + Q_{3}, \qquad U_{1} \leftarrow Q_{2} + U_{0}, \qquad U_{2} \leftarrow Q_{4} + U_{0},$$

$$C_{00} \leftarrow Q_{1} + Q_{6}, \qquad C_{01} \leftarrow Q_{0} + U_{2}, \qquad C_{10} \leftarrow Q_{5} + U_{1}, \qquad C_{11} \leftarrow Q_{0} + U_{1}.$$
(4)

In total, this straight-line program makes exactly 15 additions and 7 multiplications. Furthermore, a direct calculation shows that the straight-line program correctly computes the product

$$C = \begin{bmatrix} C_{00} & C_{01} \\ C_{10} & C_{11} \end{bmatrix} = \begin{bmatrix} A_{00}B_{00} + A_{01}B_{10} & A_{00}B_{01} + A_{01}B_{11} \\ A_{10}B_{00} + A_{11}B_{10} & A_{10}B_{01} + A_{11}B_{11} \end{bmatrix} = AB.$$
(5)

2.2 An Alternative-Basis Algorithm with Self-Inverse Basis Changes

Let us now turn to alternative-basis designs. We continue to assume that the input is given in 2×2 block form, as in (1). Our first new alternative-basis algorithm is as follows. First, change basis by computing

$$\hat{A}_{00} \leftarrow A_{00}, \qquad \hat{A}_{01} \leftarrow A_{01}, \qquad \hat{A}_{10} \leftarrow A_{10}, \qquad \hat{A}_{11} \leftarrow A_{01} + A_{10} + A_{11},
\hat{B}_{00} \leftarrow B_{00}, \qquad \hat{B}_{01} \leftarrow B_{01}, \qquad \hat{B}_{10} \leftarrow B_{10}, \qquad \hat{B}_{11} \leftarrow B_{01} + B_{10} + B_{11},$$
(6)

We observe that the same basis change is applied for both matrices A and B. Next, compute the linear combinations

$$\hat{T}_{0} \leftarrow \hat{A}_{00}, \quad \hat{T}_{1} \leftarrow \hat{A}_{01}, \quad \hat{T}_{2} \leftarrow \hat{A}_{10}, \qquad \hat{T}_{3} \leftarrow \hat{A}_{11}, \quad \hat{T}_{4} \leftarrow \hat{A}_{00} + \hat{A}_{11}, \quad \hat{T}_{5} \leftarrow \hat{A}_{01} + \hat{A}_{11}, \quad \hat{T}_{6} \leftarrow \hat{A}_{10} + \hat{A}_{11}, \\ \hat{S}_{0} \leftarrow \hat{B}_{00}, \quad \hat{S}_{1} \leftarrow \hat{B}_{10}, \quad \hat{S}_{2} \leftarrow \hat{B}_{00} + \hat{B}_{11}, \quad \hat{S}_{3} \leftarrow \hat{B}_{11}, \quad \hat{S}_{4} \leftarrow \hat{B}_{01}, \qquad \hat{S}_{5} \leftarrow \hat{B}_{01} + \hat{B}_{11}, \quad \hat{S}_{6} \leftarrow \hat{B}_{10} + \hat{B}_{11}.$$

Multiply the linear combinations to obtain the products

$$\hat{Q}_0 \leftarrow \hat{T}_0 \hat{S}_0, \quad \hat{Q}_1 \leftarrow \hat{T}_1 \hat{S}_1, \quad \hat{Q}_2 \leftarrow \hat{T}_2 \hat{S}_2, \quad \hat{Q}_3 \leftarrow \hat{T}_3 \hat{S}_3, \quad \hat{Q}_4 \leftarrow \hat{T}_4 \hat{S}_4, \quad \hat{Q}_5 \leftarrow \hat{T}_5 \hat{S}_5, \quad \hat{Q}_6 \leftarrow \hat{T}_6 \hat{S}_6.$$
(8)

Compute the linear combinations of products

$$\hat{C}_{00} \leftarrow \hat{Q}_0 + \hat{Q}_1, \quad \hat{C}_{01} \leftarrow \hat{Q}_4 + \hat{Q}_6, \quad \hat{C}_{10} \leftarrow \hat{Q}_2 + \hat{Q}_5, \quad \hat{C}_{11} \leftarrow \hat{Q}_1 + \hat{Q}_3 + \hat{Q}_5 + \hat{Q}_6.$$
 (9)

Finally, transform \hat{C} back to the standard basis with

$$C_{00} \leftarrow \hat{C}_{00}, \qquad C_{01} \leftarrow \hat{C}_{01} + \hat{C}_{11}, \qquad C_{10} \leftarrow \hat{C}_{10} + \hat{C}_{11}, \qquad C_{11} \leftarrow \hat{C}_{11}.$$
 (10)

A direct calculation shows that the product (5) is correctly evaluated. This establishes Theorem 1.1 with the exception of the claim on weights, which can be easily verified from (46) in what follows.

Compared with the design of Karstadt and Schwartz [20], we observe that the basis transformations (6) and (10) over the binary field use only two additions per matrix, whereas their design uses three additions per matrix, but works over an arbitrary ring. Furthermore, our transformations (6) and (10) admit straightforward in-place computation as well as in-place inversion—indeed, both (6) and (10) are easily verified to be self-inverses over the binary field.

Remark. A drawback of the design above is that it does not enable alternative-basis chaining of matrix multiplications in the sense that the transformations (6) and (10) are not inverses of *each other*, which would be advantageous in applications that seek chain-multiplication. Our next design removes this drawback but loses the appealing self-inverse property.

2.3 An Alternative-Basis Algorithm with Chaining

Our second algorithm retains the arithmetic advantage in basis changes over the Karstadt–Schwartz [20] design and works in an alternative basis for the matrix ring. For a matrix in the standard basis

$$X = \left[\begin{array}{cc} X_{00} & X_{01} \\ X_{10} & X_{11} \end{array} \right],$$

we transform to the alternative basis by computing

$$\hat{X}_{00} \leftarrow X_{00}, \quad \hat{X}_{01} \leftarrow X_{01}, \quad \hat{X}_{11} \leftarrow X_{01} + X_{11}, \quad \hat{X}_{10} \leftarrow \hat{X}_{11} + X_{10}.$$
 (11)

The inverse transform from the alternative basis to the standard basis is given by

$$X_{00} \leftarrow \hat{X}_{00}, \quad X_{01} \leftarrow \hat{X}_{01}, \quad X_{10} \leftarrow \hat{X}_{10} + \hat{X}_{11}, \quad X_{11} \leftarrow \hat{X}_{01} + \hat{X}_{11}.$$
 (12)

The algorithm now proceeds as follows. Given two matrices *A* and *B* as input, we transform both to the alternative basis using (11) to obtain the matrices \hat{A} and \hat{B} . Then, compute the linear combinations

$$\hat{T}_{0} \leftarrow \hat{A}_{00}, \quad \hat{T}_{1} \leftarrow \hat{A}_{01}, \qquad \hat{T}_{2} \leftarrow \hat{A}_{10}, \quad \hat{T}_{3} \leftarrow \hat{A}_{11}, \quad \hat{T}_{4} \leftarrow \hat{A}_{00} + \hat{A}_{10}, \quad \hat{T}_{5} \leftarrow \hat{A}_{01} + \hat{A}_{10}, \quad \hat{T}_{6} \leftarrow \hat{A}_{10} + \hat{A}_{11}, \\ \hat{S}_{0} \leftarrow \hat{B}_{00}, \quad \hat{S}_{1} \leftarrow \hat{B}_{10} + \hat{B}_{11}, \quad \hat{S}_{2} \leftarrow \hat{B}_{10}, \quad \hat{S}_{3} \leftarrow \hat{B}_{11}, \quad \hat{S}_{4} \leftarrow \hat{B}_{01}, \qquad \hat{S}_{5} \leftarrow \hat{B}_{01} + \hat{B}_{10}, \quad \hat{S}_{6} \leftarrow \hat{B}_{00} + \hat{B}_{10}.$$

$$(13)$$

Multiply the linear combinations to obtain the products

 $\hat{Q}_0 \leftarrow \hat{T}_0 \hat{S}_0, \quad \hat{Q}_1 \leftarrow \hat{T}_1 \hat{S}_1, \quad \hat{Q}_2 \leftarrow \hat{T}_2 \hat{S}_2, \quad \hat{Q}_3 \leftarrow \hat{T}_3 \hat{S}_3, \quad \hat{Q}_4 \leftarrow \hat{T}_4 \hat{S}_4, \quad \hat{Q}_5 \leftarrow \hat{T}_5 \hat{S}_5, \quad \hat{Q}_6 \leftarrow \hat{T}_6 \hat{S}_6.$ (14)

Compute the linear combinations of products

$$\hat{R} \leftarrow \hat{Q}_1 + \hat{Q}_2 + \hat{Q}_4, \quad \hat{C}_{00} \leftarrow \hat{Q}_0 + \hat{Q}_1, \quad \hat{C}_{01} \leftarrow \hat{R} + \hat{Q}_5, \quad \hat{C}_{10} \leftarrow \hat{R} + \hat{Q}_6, \quad \hat{C}_{11} \leftarrow \hat{Q}_3 + \hat{Q}_4.$$
 (15)

Finally, transform the matrix \hat{C} back to the standard basis using (12) to obtain the product matrix *C*. A direct calculation shows that C = AB. Furthermore, since the transformations (11) and (12) are mutual inverses, multiplications $(\hat{A}, \hat{B}) \mapsto \hat{C}$ in the alternative basis may be chained without transforming back to the standard basis in between multiplications; this

property will become immediate from our exposition in §2.7 and §2.8. This establishes Theorem 1.2 with the exception of the claim on weights, which can be easily verified from (48) in what follows.

2.4 Arrays, Vectors, and Matrices

This section develops preliminaries and notational conventions for working with binary matrices used throughout the rest of this paper. The basic data structure we work with is an *array* of *m* entries, indexed by the set $[m] = \{0, 1, ..., m-1\}$. A *tensor* is an array with an associated *shape* $m_1 \times m_2 \times \cdots \times m_d$ for nonnegative integers $m_1, m_2, ..., m_d$ with $m = m_1 m_2 \cdots m_d$. In this case we say that the tensor has *d* modes and that the mode $\ell = 1, 2, ..., d$ has *length* m_ℓ . A tensor with one mode is called a *vector* and a tensor with two modes is called a *matrix*.

We index the entries of a tensor *T* of shape $m_1 \times m_2 \times \cdots \times m_d$ using tuples $(i_1, i_2, \dots, i_d) \in [m_1] \times [m_2] \times \cdots \times [m_d]$, with the convention that the tuple refers to the entry indexed by

$$i = i_1 m_2 m_3 \cdots m_d + i_2 m_3 m_4 \cdots m_d + \ldots + i_{d-1} m_d + i_d$$
 (16)

in the underlying array of length *m*. In other words, in linearizing the tuple $(i_1, i_2, \ldots, i_d) \in [m_1] \times [m_2] \times \cdots \times [m_d]$ to a linear index $i \in [m]$, the first index $i_1 \in [m_1]$ is the most significant, the next index $i_2 \in [m_2]$ is the next most significant, and so forth. We write $T_{(i_1, i_2, \ldots, i_d)}$ for the entry of *T* indexed by (i_1, i_2, \ldots, i_d) . To lighten the notation, we may also write simply $T_{i_1i_2\cdots i_d}$ assuming the indexing is immediate from the context. When working with modes of composite length $m_{\ell} = m_{\ell,1}m_{\ell,2}\cdots m_{\ell,k}$ for nonnegative integers $m_{\ell,1}, m_{\ell,2}, \ldots, m_{\ell,k}$, for convenience we often choose to index such a mode with tuples in $[m_{\ell,1}] \times [m_{\ell,2}] \times \cdots \times [m_{\ell,k}]$, with the understanding that we follow the first-index-major convention (16) to arrive at the linear index in $[m_{\ell}]$.

We use the following notation for subtensors of tensors indexed along the most significicant modes. For a tensor *T* of shape $m_1 \times m_2 \times \cdots \times m_d$ and a tuple $(i_1, i_2, \ldots, i_\ell) \in [m_1] \times [m_2] \times \cdots \times [m_\ell]$ of indices, we write $T_{i_1 i_2 \cdots i_\ell}$ for the tensor of shape $m_{\ell+1} \times m_{\ell+2} \times \cdots \times m_d$ with entries $(T_{i_1 i_2 \cdots i_\ell})_{i_{\ell+1} i_{\ell+2} \cdots i_d}$ for all $(i_{\ell+1}, i_{\ell+2}, \ldots, i_d) \in [m_{\ell+1}] \times [m_{\ell+2}] \times \cdots \times [m_d]$. In particular, we find it convenient to use the same notation for entries and subarrays of a tensor *T*, as the structure of the indexing tuple will indicate whether an entry or a subarray is meant.

In what follows let us assume that all arrays have their entries in the binary field $(0, 1, +, \cdot)$ unless indicated otherwise. For an $s \times t$ matrix μ , write write μ^{\top} for the $t \times s$ transpose of μ with entries defined for all $i \in [s]$ and $j \in [t]$ by the rule $\mu_{ij}^{\top} = \mu_{ji}$. For an $s \times t$ matrix μ and a $t \times u$ matrix v, we write μv for the $s \times u$ product matrix with entries defined for all $i \in [s]$ and $k \in [u]$ by $(\mu v)_{ik} = \sum_{j \in [t]} \mu_{ij} v_{jk}$. We write $I = I_n$ for the $n \times n$ identity matrix. For an $s \times t$ matrix μ and a $p \times q$ matrix v, the *Kronecker product* $\mu \otimes v$ is the $sp \times tq$ matrix with entries defined for all $i \in [s], j \in [t], k \in [p]$, and $\ell \in [q]$ by the rule $(\mu \otimes v)_{ikj\ell} = \mu_{ij}v_{k\ell}$. For an $s \times t$ matrix μ , a $t \times u$ matrix σ , a $p \times q$ matrix v, and a $q \times r$ matrix τ , let us recall the *composition rule* for Kronecker products

$$(\mu\sigma) \otimes (\nu\tau) = (\mu \otimes \nu)(\sigma \otimes \tau) \,. \tag{17}$$

Let us also recall the transposition rule

$$(\mu \otimes \nu)^{\top} = \mu^{\top} \otimes \nu^{\top} . \tag{18}$$

For two tensors σ and τ of identical shape, the *entrywise product* $\sigma \odot \tau$ has the same shape, with entries defined by the rule $(\sigma \odot \tau)_i = \sigma_i \tau_i$ for all indices *i*.

2.5 The Triple Product Property and Matrix Multiplication

This section recalls the triple product of matrix multiplication and its closure under taking of Kronecker products. For an $su \times r$ matrix ζ , an $r \times st$ matrix ξ , and an $r \times tu$ matrix η , we say that the three-tuple $(\zeta | \xi, \eta)$ has the *triple product property* with parameters $\langle s, t, u \rangle_r$ if for all $i, i' \in [s], j, j' \in [t]$, and $k, k' \in [u]$ it holds that

$$\sum_{h \in [r]} \zeta_{i'k'h} \xi_{hij} \eta_{hj'k} = \begin{cases} 1 & \text{if } i = i', j = j', \text{ and } k = k', \\ 0 & \text{otherwise}. \end{cases}$$
(19)

For example, the Strassen-Winograd design (2), (3), (4) gives rise to the matrices

$$\xi = \begin{bmatrix} 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 1 \\ 0 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 \\ 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 0 \end{bmatrix}, \quad \eta = \begin{bmatrix} 0 & 0 & 1 & 1 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 \\ 0 & 1 & 0 & 0 \\ 1 & 1 & 1 & 1 \\ 1 & 0 & 0 & 0 \end{bmatrix}, \quad \text{and} \quad \zeta = \begin{bmatrix} 0 & 1 & 0 & 0 & 0 & 0 & 1 \\ 1 & 1 & 0 & 1 & 1 & 0 & 0 \\ 0 & 1 & 1 & 1 & 0 & 1 & 0 \\ 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 0 & 0 & 0 \end{bmatrix}, \quad (20)$$

which are readily verified to satisfy the triple product property with s = t = u = 2 and r = 7.

Let $(\zeta | \xi, \eta)$ satisfy the triple product rule with parameters $\langle s, t, u \rangle_r$. Let *A* be an $s \times t$ matrix and *B* be a $t \times u$ matrix. Define an $s \times u$ matrix *C* for all $i' \in [s]$ and $k' \in [u]$ by the rule

$$C_{i'k'} = \sum_{h \in [r]} \zeta_{i'k'h} \sum_{i \in [s]} \sum_{j \in [t]} \xi_{hij} A_{ij} \sum_{j' \in [t]} \sum_{k \in [u]} \eta_{hj'k} B_{j'k}$$

$$= \sum_{i \in [s]} \sum_{j \in [t]} \sum_{j' \in [t]} \sum_{k \in [u]} A_{ij} B_{j'k} \sum_{h \in [r]} \zeta_{i'k'h} \xi_{hij} \eta_{hj'k}$$

$$= \sum_{j \in [t]} A_{i'j} B_{jk'},$$

(21)

where the second equality follows by changing the order of summation and the last equality follows from the triple product property (19). Viewing A, B, and C as vectors of length st, tu, and su, respectively, from (21) it immediately follows that

$$C = \zeta(\xi A \odot \eta B) \,. \tag{22}$$

In other words, we observe that a three-tuple ($\zeta | \xi, \eta$) with the triple product property reduces multiplication of the matrices *A* and *B* to (i) taking linear combinations ξA and ηB of entries of *A* and *B* independently, (ii) multiplying these linear combinations pointwise to obtain $\xi A \odot \eta B$, and (iii) taking linear combinations $\zeta (\xi A \odot \eta B)$ to obtain the product matrix *C* of *A* and *B*.

The triple product property gains its computational power from closure under Kronecker products and the composition rule. Indeed, let $(\zeta_{\ell}|\xi_{\ell},\eta_{\ell})$ satisfy the triple product property with parameters $\langle s_{\ell}, t_{\ell}, u_{\ell} \rangle_{r_{\ell}}$ for $\ell = 1, 2, ..., d$. Let A be a vector of length $s_1t_1s_2t_2\cdots s_dt_d$, let B be a vector of length $t_1u_1t_2u_2\cdots t_du_d$, and let C be a vector of length $s_1t_us_2u_2\cdots s_du_d$. Similarly to (21), for all $(i'_1, i'_2, ..., i'_d) \in [s_1] \times [s_2] \times \cdots \times [s_d]$ and $(k'_1, k'_2, ..., k'_d) \in [u_1] \times [u_2] \times \cdots \times [u_d]$, by the triple product property (19) we now have

$$C_{i_{1}'k_{1}'i_{2}'k_{2}'\cdots i_{d}'k_{d}'} = \\ = \sum_{\substack{h_{1}\in[r_{1}]\\h_{2}\in[r_{2}]\\\vdots\\h_{d}\in[r_{d}]}} \zeta_{i_{1}'h_{1}'h_{1}}^{(1)}\cdots\zeta_{i_{d}'k_{d}'}^{(d)}h_{d}\sum_{\substack{i_{1}\in[s_{1}]\\j_{1}\in[t_{1}]\\j_{2}\in[s_{2}]\\j_{2}\in[t_{2}]\\\vdots\\i\\i\\d_{d}\in[s_{d}]j_{d}\in[t_{d}]}} \sum_{\substack{j_{1}\in[t_{1}]\\j_{2}\in[t_{d}]\\j_{d}\in[t_{d}]}} \zeta_{i_{1}'h_{1}'h_{1}'\cdots}^{(1)}\gamma_{h_{d}j_{d}'k_{d}}^{(1)}h_{d}\sum_{\substack{i_{1}\in[s_{1}]\\j_{1}\in[t_{1}]\\j_{2}\in[t_{d}]}} \sum_{\substack{k_{1}\in[t_{1}]\\j_{2}\in[t_{d}]}} \gamma_{i_{1}'h$$

Similarly to (22), from (23) we observe that

$$C = (\zeta^{(1)} \otimes \cdots \otimes \zeta^{(d)}) ((\xi^{(1)} \otimes \cdots \otimes \xi^{(d)}) A \odot (\eta^{(1)} \otimes \cdots \otimes \eta^{(d)}) B).$$
⁽²⁴⁾

In other words, to multiply A and B, it suffices to first compute the two matrix-vector products

$$T \leftarrow (\xi^{(1)} \otimes \cdots \otimes \xi^{(d)}) A, \qquad S \leftarrow (\eta^{(1)} \otimes \cdots \otimes \eta^{(d)}) B,$$
(25)

then multiply the resulting vectors elementwise

$$Q \leftarrow T \odot S, \tag{26}$$

and finally compute the matrix-vector product

$$C \leftarrow (\zeta^{(1)} \otimes \dots \otimes \zeta^{(d)})Q \tag{27}$$

to recover the product *C* of *A* and *B* as a vector of length $s_1u_1s_2u_2\cdots s_du_d$.

2.6 Yates's Algorithm and Fast Matrix Multiplication

This section develops fast matrix multiplication in the above framework by reduction to Yates's algorithm. The computational bottleneck of the matrix-multiplication algorithm $(A, B) \mapsto C$ given by (25), (26), and (27) occurs with matrix-vector multiplications of the following form. For $\ell = 1, 2, ..., d$, let $\mu^{(\ell)}$ be a matrix of shape $b_{\ell} \times a_{\ell}$, and let U be a vector of length $a_1a_2 \cdots a_d$. We want to compute the vector V of length $b_1b_2 \cdots b_d$ with

$$V = (\mu^{(1)} \otimes \mu^{(2)} \otimes \cdots \otimes \mu^{(d)}) U.$$

The key idea is to rely on the composition rule (17) to implement multiplication with $\mu^{(1)} \otimes \mu^{(2)} \otimes \cdots \otimes \mu^{(d)}$ one component matrix $\mu^{(\ell)}$ at a time, via a sequence of sparse matrices $\bar{\mu}^{[\ell]}$ defined in what follows. Let $\pi : \{1, 2, \ldots, d\} \rightarrow \{1, 2, \ldots, d\}$ be an arbitrary permutation that encodes the order in which the matrices $\mu^{(\ell)}$ will be applied.⁵ For all $k, \ell \in \{1, 2, \ldots, d\}$, let

$$m_{k,\ell}^{\pi} = m_{k,\ell}^{\pi}(b,a) = \begin{cases} a_k & \text{if } k \in \pi(\{1,2,\dots,\pi^{-1}(\ell)\}); \\ b_k & \text{otherwise.} \end{cases}$$

 $^{^5\}mathrm{At}$ first reading, it may be convenient to assume that π is the identity permutation.

Let us recall that we write I_n for an $n \times n$ identity matrix. From the composition rule (17) of Kronecker products, we obtain the decomposition

$$\mu^{(1)} \otimes \mu^{(2)} \otimes \dots \otimes \mu^{(d)} = \bar{\mu}^{[\pi(1)]} \bar{\mu}^{[\pi(2)]} \cdots \bar{\mu}^{[\pi(d)]}$$
(28)

with

$$\bar{\mu}^{[\ell]} = I_{m_{1,\ell}^{\pi}} \otimes I_{m_{2,\ell}^{\pi}} \otimes \cdots \otimes I_{m_{\ell-1,\ell}^{\pi}} \otimes \mu^{(\ell)} \otimes I_{m_{\ell+1,\ell}^{\pi}} \otimes I_{m_{\ell+2,\ell}^{\pi}} \otimes \cdots \otimes I_{m_{d,\ell}^{\pi}}$$
(29)

for $\ell = 1, 2, ..., d$. In essence, each matrix $\bar{\mu}^{[\ell]}$ implements $\prod_{k=1, k \neq \ell}^{d} m_{k,\ell}^{\pi}$ independent matrix-vector multiplications with the matrix $\mu^{(\ell)}$. Accordingly, $\bar{\mu}^{[\ell]}$ is sparse with at most $a_{\ell}b_{\ell} \prod_{k=1, k \neq \ell}^{d} m_{k,\ell}^{\pi}$ nonzero entries. Furthermore, if matrix-vector multiplication with the $b_{\ell} \times a_{\ell}$ matrix $\mu^{(\ell)}$ has a straight-line-program implementation consisting of $P_{\ell} \leq b_{\ell}(a_{\ell} - 1)$ binary additions, the total number of binary additions in the algorithm

$$U^{[d]} \leftarrow U, \quad U^{[d-1]} \leftarrow \bar{\mu}^{[\pi(d)]} U^{[d]}, \quad U^{[d-2]} \leftarrow \bar{\mu}^{[\pi(d-1)]} U^{[d-1]}, \quad U^{[0]} \leftarrow \bar{\mu}^{[\pi(1)]} U^{[1]}, \quad V \leftarrow U^{[0]},$$
(30)

is

$$\sum_{\ell=1}^{d} P_{\ell} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi} \,. \tag{31}$$

The algorithm (30) is known as *Yates's algorithm* [42] for multiplying a Kronecker-product-structured matrix with a given vector.

Yates's algorithm is known to admit highly efficient parallelization. Indeed, since each $layer U^{[\ell-1]} \leftarrow \bar{\mu}^{[\pi(\ell)]}U^{[\ell]}$ in Yates's algorithm consists of a large number of independent matrix-vector multiplications with the same matrix $\mu^{(\pi(\ell))}$, Yates's algorithm admits immediate vector-parallelization (single-instruction-multiple-data parallelization). Furthermore, multiple consecutive layers may be aggregated into one layer to optimize use of local storage such as per-scalar-thread registers in vectorized parallel execution. Here the ability to permute layers arbitrarily yields considerable freedom to optimize both the arithmetic cost as well as the vectorized execution and the use of local storage in applications.

For matrix multiplication, using Yates's algorithm with permutations $\pi_{\zeta}, \pi_{\xi}, \pi_{\eta} : \{1, 2, ..., d\} \rightarrow \{1, 2, ..., d\}$ to implement the matrix-vector multiplications in (25) and (27), we obtain an algorithm design that multiplies an $s_1s_2 \cdots s_d \times t_1t_2 \cdots t_d$ matrix with a $t_1t_2 \cdots t_d \times u_1u_2 \cdots u_d$ matrix using exactly

$$\sum_{\ell=1}^{d} P_{\ell}^{\zeta} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi_{\zeta}}(s \odot u, r) + \sum_{\ell=1}^{d} P_{\ell}^{\xi} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi_{\zeta}}(r, s \odot t) + \sum_{\ell=1}^{d} P_{\ell}^{\eta} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi_{\eta}}(r, t \odot u)$$
(32)

binary additions and $r_1r_2\cdots r_d$ binary multiplications, where P_{ℓ}^{ζ} , P_{ℓ}^{ξ} , and P_{ℓ}^{η} are the number of additions in a straightline program that multiplies the matrix $\zeta^{(\ell)}$, $\xi^{(\ell)}$, and $\eta^{(\ell)}$, respectively, with a vector, $\ell = 1, 2, ..., d$.

2.7 Fast Alternative-Basis Matrix Multiplication

Let us now review the key idea of Karstadt and Schwartz [20] to change basis to reduce the total additive cost within the previous framework. For $\ell = 1, 2, ..., d$, let $(\zeta^{(\ell)} | \xi^{(\ell)}, \eta^{(\ell)})$ satisfy the triple product property with parameters $\langle s_{\ell}, t_{\ell}, u_{\ell} \rangle_{r_{\ell}}$. For each $\ell = 1, 2, ..., d$, let us now decompose the matrices $\zeta^{(\ell)}, \xi^{(\ell)}, \eta^{(\ell)}$ into

$$\zeta^{(\ell)} = \chi^{(\ell)} \gamma^{(\ell)}, \quad \xi^{(\ell)} = \alpha^{(\ell)} \phi^{(\ell)}, \quad \eta^{(\ell)} = \beta^{(\ell)} \psi^{(\ell)}, \tag{33}$$

where $\phi^{(\ell)}$, $\psi^{(\ell)}$, and $\chi^{(\ell)}$ are arbitrary invertible matrices. Applying the decomposition (33) together with the composition rule (17) of Kronecker products, the key observation of Karstadt and Schwartz [20] in the present framework is

that the multiplication identity (24) decomposes as

$$C = (\zeta^{(1)} \otimes \dots \otimes \zeta^{(d)}) \left((\xi^{(1)} \otimes \dots \otimes \xi^{(d)}) A \odot (\eta^{(1)} \otimes \dots \otimes \eta^{(d)}) B \right)$$

$$= (\chi^{(1)} \gamma^{(1)} \otimes \dots \otimes \chi^{(d)} \gamma^{(d)}) \left((\alpha^{(1)} \phi^{(1)} \otimes \dots \otimes \alpha^{(d)} \phi^{(d)}) A \odot (\beta^{(1)} \psi^{(1)} \otimes \dots \otimes \beta^{(d)} \psi^{(d)}) B \right)$$

$$= (\chi^{(1)} \otimes \dots \otimes \chi^{(d)}) (\gamma^{(1)} \otimes \dots \otimes \gamma^{(d)}) \left((\alpha^{(1)} \otimes \dots \otimes \alpha^{(d)}) (\phi^{(1)} \otimes \dots \otimes \phi^{(d)}) A \right)$$

$$\odot (\beta^{(1)} \otimes \dots \otimes \beta^{(d)}) (\psi^{(1)} \otimes \dots \otimes \psi^{(d)}) B \right).$$
(34)

From (34) we can immediately extract the following *alternative-basis* multiplication algorithm, which we state in a form that relies on Yates's algorithm for multiplying with each Kronecker-product-structured matrix in (34).

Let *A* be a vector of length $s_1t_1s_2t_2\cdots s_dt_d$ and let *B* be a vector of length $t_1u_1t_2u_2\cdots t_du_d$. Let $\pi_{\phi}, \pi_{\psi}, \pi_{\chi}, \pi_{\alpha}, \pi_{\beta}, \pi_{\gamma}$: {1,2,...,*d*} \rightarrow {1,2,...,*d*} be arbitrary permutations. To multiply *A* and *B*, first change basis for both inputs by computing

$$\hat{A} \leftarrow \bar{\phi}^{[\pi_{\phi}(1)]} \cdots \bar{\phi}^{[\pi_{\phi}(d)]} A, \qquad \hat{B} \leftarrow \bar{\psi}^{[\pi_{\psi}(1)]} \cdots \bar{\psi}^{[\pi_{\psi}(d)]} B.$$
(35)

Then compute linear combinations in the new bases

$$\hat{T} \leftarrow \bar{\alpha}^{[\pi_{\alpha}(1)]} \cdots \bar{\alpha}^{[\pi_{\alpha}(d)]} \hat{A}, \qquad \hat{S} \leftarrow \bar{\beta}^{[\pi_{\beta}(1)]} \cdots \bar{\beta}^{[\pi_{\beta}(d)]} \hat{B}.$$
(36)

Multiply the resulting vectors elementwise

$$\hat{Q} \leftarrow \hat{T} \odot \hat{S} \,. \tag{37}$$

Take linear combinations of the products

$$\hat{C} \leftarrow \bar{\gamma}^{[\pi_{\gamma}(1)]} \cdots \bar{\gamma}^{[\pi_{\gamma}(d)]} \hat{Q} .$$
(38)

Finally change basis

$$C \leftarrow \bar{\chi}^{[\pi_{\chi}(1)]} \cdots \bar{\chi}^{[\pi_{\chi}(d)]} \hat{C}$$
⁽³⁹⁾

to recover the product *C* of *A* and *B* as a vector of length $s_1u_1s_2u_2\cdots s_du_d$.

The key insight of Karstadt and Schwartz [20] is that the additive straight-line-program cost of the matrix-vector multiplications with the basis-transformed matrices $\alpha^{(\ell)}$, $\beta^{(\ell)}$, and $\gamma^{(\ell)}$ may be strictly lower than the corresponding cost for the matrices $\xi^{(\ell)}$, $\eta^{(\ell)}$, and $\zeta^{(\ell)}$. Furthermore, one may engineer the basis changes $\phi^{(\ell)}$, $\psi^{(\ell)}$, and $\chi^{(\ell)}$ to such an effect.

In more precise terms, implementing each of the transformations (35), (36), (38), and (39) using Yates's algorithm (30) with the identity permutation, we obtain that the alternative-basis algorithm uses exactly

$$\sum_{\ell=1}^{d} P_{\ell}^{\chi} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi_{\chi}}(s \odot u, s \odot u) + \sum_{\ell=1}^{d} P_{\ell}^{\phi} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi_{\phi}}(s \odot t, s \odot t) + \sum_{\ell=1}^{d} P_{\ell}^{\psi} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi_{\psi}}(t \odot u, t \odot u)$$
(40)

binary additions for the basis changes,

$$\sum_{\ell=1}^{d} P_{\ell}^{\gamma} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi_{\gamma}}(s \odot u, r) + \sum_{\ell=1}^{d} P_{\ell}^{\alpha} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi_{\alpha}}(r, s \odot t) + \sum_{\ell=1}^{d} P_{\ell}^{\beta} \prod_{\substack{k=1\\k\neq\ell}}^{d} m_{k,\ell}^{\pi_{\beta}}(r, t \odot u)$$
(41)

Engineering Boolean Matrix Multiplication for Multiple-Accelerator Shared-Memory Architectures

binary additions for the linear combinations, and

$$r_1 r_2 \cdots r_d$$
 (42)

binary multiplications.

In the diagonal case with $r = r_{\ell}$, $s = s_{\ell}$, $t = t_{\ell}$, $u = u_{\ell}$, $\alpha = \alpha^{(\ell)}$, $\beta = \beta^{(\ell)}$, $\gamma = \gamma^{(\ell)}$, $\phi = \phi^{(\ell)}$, $\psi = \psi^{(\ell)}$, and $\gamma = \gamma^{(\ell)}$ for $\ell = 1, 2, ..., d$, and s = t = u with $r > s^2$, we obtain that the alternative-basis algorithm uses

$$(P^{\chi} + P^{\phi} + P^{\psi})s^{2(d-1)}d$$
(43)

binary additions for the basis changes,

$$(P^{\gamma} + P^{\alpha} + P^{\beta}) \sum_{\ell=1}^{d} s^{2(\ell-1)} r^{d-\ell} = (P^{\gamma} + P^{\alpha} + P^{\beta}) \frac{r^d - s^{2d}}{r - s^2}$$
(44)

binary additions for the linear combinations, and r^d binary multiplications. In particular, from (43) and (44) we see that optimizing the additive costs P^{γ} , P^{α} , and P^{β} optimizes the leading constant of the dominant cost for large d. In the non-diagonal case, more fine-grained optimization may be performed by optimizing the components of the decomposition and the permutations to minimize (40) and (41).

A useful subfamily of alternative-basis algorithms are the alternative-basis algorithms that satisfy $\phi^{(\ell)} = \psi^{(\ell)}$ and $\chi^{(\ell)} = (\phi^{(\ell)})^{-1}$ for all $\ell = 1, 2, ..., d$. We say that such algorithms support *matrix chain multiplication* or *chaining* in the alternative basis. Indeed, for such an algorithm, one may chain multiplications $(\hat{A}, \hat{B}) \mapsto \hat{C}$ in the alternative basis using (36), (37), and (38) only, without changing back to the standard basis in between multiplications.

2.8 The Two New Algorithms in Matrix Form

Let us first express the new alternative-basis algorithm in §2.2 in matrix form. The change-of-basis matrices are -

г

$$\phi = \psi = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 1 & 1 \end{bmatrix}, \qquad \chi = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 1 \\ 0 & 0 & 1 & 1 \\ 0 & 0 & 0 & 1 \end{bmatrix}.$$
(45)

We readily observe that $\phi = \psi = \chi^{\top}$ and that $\phi = \phi^{-1}$ and $\chi = \chi^{-1}$ over the binary field. This self-inverse property and the ease of in-place computation of matrix-vector multiplication with (45) are appealing properties when working with inputs with tight space constraints. From (6) we observe that we can take $P^{\phi} = P^{\psi} = 2$ and from (10) we observe that we can take $P^{\chi} = 2$. The alternative-basis decomposition is defined by the matrices

$$\alpha = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 \\ 0 & 1 & 0 & 1 \\ 0 & 0 & 1 & 1 \end{bmatrix}, \quad \beta = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 1 \\ 0 & 1 & 0 & 1 \\ 0 & 1 & 0 & 1 \\ 0 & 0 & 1 & 1 \end{bmatrix}, \quad \text{and} \quad \gamma = \begin{bmatrix} 1 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 & 1 \\ 0 & 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 & 0 & 1 & 1 \end{bmatrix}.$$
(46)

We readily verify that matrix-vector multiplication with the matrices α and β can be implemented using the recurrences (7) so that $P^{\alpha} = P^{\beta} = 3$, and matrix-vector multiplication with the matrix γ can be implemented with $P^{\gamma} = 6$ using (9). We observe that the three-tuple $(\chi \gamma | \alpha \phi, \beta \psi)$ with ϕ, α, β , and γ given by (45) and (46) satisfies the triple product property (19) with parameters $\langle 2, 2, 2 \rangle_7$.

Let us now turn to the alternative-basis algorithm in §2.3. The change-of-basis matrices are

$$\phi = \psi = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 1 & 1 & 1 \\ 0 & 1 & 0 & 1 \end{bmatrix} \quad \text{and} \quad \chi = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 1 \end{bmatrix},$$
(47)

We observe that $\chi = \phi^{-1} = \psi^{-1}$, so we have an alternative-basis algorithm that supports chaining. From (11) we observe that $P^{\phi} = P^{\psi} = 2$. From (12) we observe that $P^{\chi} = 2$. The alternative-basis decomposition is defined by the matrices

$$\alpha = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 1 \end{bmatrix}, \quad \beta = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 1 \\ 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 0 \\ 0 & 1 & 1 & 0 \\ 1 & 0 & 1 & 0 \end{bmatrix}, \quad \text{and} \quad \gamma = \begin{bmatrix} 1 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 & 1 & 1 & 0 \\ 0 & 1 & 1 & 0 & 1 & 1 & 0 \\ 0 & 0 & 0 & 1 & 1 & 0 & 0 \end{bmatrix}.$$
(48)

We readily verify that matrix-vector multiplication with the matrices α and β can be implemented using the recurrences (13) so that $P^{\alpha} = P^{\beta} = 3$, and matrix-vector multiplication with the matrix γ can be implemented using (15) so that $P^{\gamma} = 6$. Finally, we have that the three-tuple $(\chi \gamma | \alpha \phi, \beta \psi)$ with $\phi, \psi, \chi, \alpha, \beta$, and γ given by (47) and (48) satisfies the triple product property (19) with parameters $\langle 2, 2, 2 \rangle_7$.

3 IMPLEMENTATION ENGINEERING

This section describes our algorithm engineering effort in more detail, with a focus on implementing the binary product of two matrices; our implementation of Boolean products is described more concisely at the end of this section. We strive for generality of exposition in terms of the target platform and in terms of enabling the use of future advances in specific alternative-basis decompositions beyond our new decompositions presented in §2.2 and §2.3.

The high-level exposition withstanding, our goal with the present engineering effort is that a careful low-level implementation of our engineering framework will be able to utilize specific hardware configurations across a range of configurations efficiently, which we seek to demonstrate in our experiments across a range of current platforms in the subsequent section. Furthermore, we would like to highlight that detailed low-level parameterization and specific optimizations for current target platforms can always be found in the accompanying open-source release.

3.1 The Family of Target Platforms

Let us recall from the introduction that we seek generality towards a family of target platforms that consist of a single shared-memory compute node (the *host*) equipped with *N* independent and identical vectorized accelerator devices (the *accelerators*), each joined to the host by a low-bandwidth interconnect compared with the bandwidth available at each device.

While the detailed parameters of such a configuration are expected to vary and evolve over time, this overall topology of the configuration—that is, a large-capacity shared-memory host joined by a low-bandwidth interconnect to *N* independent high-bandwidth accelerators with restricted memory capacity and vectorized parallelism based on thread arrays—can perhaps be expected to remain more stable over time and thus warrant engineering attention with the goal of providing a design that can be fine-tuned to the varying parameters of each specific configuration. A modern typical configuration of this type is a one-or-more-CPU-based shared-memory host joined by a peripheral component interconnect to *N* GPU accelerators.

A further specific goal in our engineering effort is to enable consideration of input sizes that are close to the shared-memory capacity of the host. Accordingly, our present design at the host level has been structured for a low shared-memory footprint in terms of working memory, but with the understanding that, memory permitting, a faster design can be obtained by following a series-parallel strategy at the host, similarly to the present framework employed at each accelerator.

One further design choice in the present framework is that we assume that the accelerators work independently and asynchronously, apart from synchronization enforced by the host. This choice scopes out platforms where the accelerators may be joined to each other by a fast interconnect; indeed, making use of such an interconnect would require at least partial synchronization between the accelerators.

3.2 Accelerators and Thread Arrays

Let us now review our more detailed conventions for working with components of a target platform, starting with the accelerators. We assume the accelerator devices are vector processors designed to execute a large number of threads in parallel, working asynchronously with one or more arrays of data residing in accelerator memory. Each of these data arrays has a shape, which makes it convenient to assume that the array of threads working on the data has a shape to structure the workload.

More precisely, we say that a parallel workload of $L = L_1 L_2 \cdots L_r$ asynchronous threads for positive integers L_1, L_2, \ldots, L_r is a *thread array* of *volume* L and *shape*

$$L_1 \times L_2 \times \cdots \times L_r$$

This assumption enables us to index a thread t = 0, 1, ..., L - 1 inside a thread array of volume *L* alternatively by its linear index *t* or by the unique tuple $(t_1, t_2, ..., t_r) \in [L_1] \times [L_2] \times \cdots \times [L_r]$ with

$$t = t_1 L_2 L_3 \cdots L_r + t_2 L_3 L_4 \cdots L_r + \ldots + t_{r-1} L_r + t_r$$
(49)

for compatibility with our convention for linearization of data arrays (16). Workloads based on thread arrays are also essentially immediately translatable to modern GPU platforms.

With current and envisaged future platforms in mind, a key property for a thread-array based design is that of *coalescence*. We say that a thread array of shape $L_1 \times L_2 \times \cdots \times L_r$ is *coalescent* up to *c* modes if any two threads threads whose tuple-indices agree in all but least significant *c* modes $L_{r-c+1}, L_{r-c+2}, \ldots, L_r$ execute an identical stream of instructions; furthermore, whenever an instruction in the stream is a memory access, either a single address or consecutive addresses of words in accelerator memory are accessed across consecutive threads in the *c* least significant modes. Here it is important to note that we do not assume that the threads in a thread array execute synchronously, although the underlying hardware in most cases has a vectorized structure that is optimized for synchronized execution of the workload in groups of *V* coalescent threads for a hardware-dependent parameter *V*.

Further engineering principles for accelerators include the following:

- (1) work with a large enough L to expose sufficient parallelism to saturate the accelerator hardware;
- (2) seek coalescent execution by careful design and ordering of the modes of the thread array and the modes of the data tensors; and
- (3) make sure each thread in the array works with enough local data to make use of low-latency and high-bandwidth storage available to each thread or groups of threads, for example, in the form of per-thread registers and per-thread-group cache memory.

3.3 The Host and Coordinating the Work

The role of the host is to coordinate the work of the *N* accelerators through multithreading and synchronization primitives at the host. Furthermore, our assumption is that the input and the output require memory capacity in excess of what is available at the accelerators, thus requiring the host to prepare workloads for the accelerators and aggregate the results obtained from the accelerators. We also recall that we are seeking a design that has a low working-memory footprint at the host to enable processing of large inputs.

Our engineering principles for the host-side implementation include the following:

- design for efficient use of the host-side memory hierarchy; each host-thread works with at least one cache line of data at a time, utilizing the cache hierarchy available;
- (2) the N accelerators are coordinated asynchronously in parallel so that each accelerator has its own pipeline implemented using host-side threads, with synchronization on buffers and submatrices of the output to avoid data races;
- (3) each of the N accelerator-pipelines involves four stages, implemented using dedicated host-threads: (i) prepare left input to accelerator in host memory, (ii) prepare right input to accelerator in host memory, (iii) upload input from host memory to accelerator, compute at accelerator, download result from accelerator to host memory, and (iv) aggregate the result in host memory to output;
- (4) the accelerators must be supplied with extensive-enough workloads if possible to hide the running time of the other stages of the pipeline behind the accelerator-side compute on the workloads;
- (5) the accelerator memory and the available low bandwidth between the host and the accelerators constrain the size of the workloads, which we ease by adopting a series/parallel approach on the accelerators; and
- (6) the memory budget at the host is tight due to our goal of scaling to large inputs and the need to buffer of workloads for N accelerators in host memory—we use low-memory-footprint designs to prepare and aggregate the workloads, including in-place basis changes and other primitives help with the memory budget.

3.4 The High-Level Design

We are now ready for a high-level exposition of the algorithm design engineered for our target platforms. Once the high-level description is done, we proceed to review more detailed implementation considerations. We will use the alternative-basis framework of §2.

Let d be a positive integer that represents the *depth* of the algorithm design in terms of the number of three-tuples of matrices that satisfy the triple-product property (19) used to structure the arithmetic. The exact implementation of this arithmetic will vary somewhat from the ideal design (35), (36), (37), (38), and (39) given in §2, in particular due to storage and bandwidth considerations both at the host and at the accelerators, and due to the need to supply independent

and asynchronous parallel workloads to each of the *N* accelerators. Each accelerator will in turn work both serially (recursively) and in parallel with its specific subproblems delegated to it by the host.

We will split *d* according to the high-level *layers* of the design. We work with four layers:

- (1) host layer,
- (2) accelerator serial layer,
- (3) accelerator parallel layer, and
- (4) accelerator inner layer.

It will be convenient to indicate the layers in our notation with the symbols "h" (host), "s" (accelerator serial), "p" (accelerator parallel), and "i" (inner). Accordingly, we have

$$d = d^{(h)} + d^{(s)} + d^{(p)} + d^{(i)},$$

where the nonnegative integers $d^{(h)}$, $d^{(s)}$, $d^{(p)}$, and $d^{(i)}$ indicate the number of decomposition matrices employed at each high-level layer.

For each type of layer $t \in \{h, s, p, i\}$ and each level $\ell = 1, 2, \dots, d^{(t)}$ inside a layer, let the three-tuple

$$(\chi^{(\mathfrak{t},\ell)}\gamma^{(\mathfrak{t},\ell)}|\alpha^{(\mathfrak{t},\ell)}\phi^{(\mathfrak{t},\ell)},\beta^{(\mathfrak{t},\ell)}\psi^{(\mathfrak{t},\ell)})$$

satisfy the triple product property with parameters $\langle s_{\ell}^{(t)}, t_{\ell}^{(t)}, u_{\ell}^{(t)} \rangle_{r_{\ell}^{(t)}}$, where $\chi^{(t,\ell)}, \phi^{(t,\ell)}$, and $\psi^{(t,\ell)}$ are invertible matrices.

Our task is to multiply a given matrix A' of shape $s \times t$ with a given matrix B' of shape $t \times u$ to yield as output the product matrix C' = A'B' of shape $s \times u$, where

$$s = s_{1}^{(h)} \cdots s_{d^{(h)}}^{(h)} \cdot s_{1}^{(s)} \cdots s_{d^{(s)}}^{(s)} \cdot s_{1}^{(p)} \cdots s_{d^{(p)}}^{(p)} \cdot s_{1}^{(1)} \cdots s_{d^{(i)}}^{(1)},$$

$$t = t_{1}^{(h)} \cdots t_{d^{(h)}}^{(h)} \cdot t_{1}^{(s)} \cdots t_{d^{(s)}}^{(s)} \cdot t_{1}^{(p)} \cdots t_{d^{(p)}}^{(p)} \cdot t_{1}^{(i)} \cdots t_{d^{(i)}}^{(i)},$$

$$u = u_{1}^{(h)} \cdots u_{d^{(h)}}^{(h)} \cdot u_{1}^{(s)} \cdots u_{d^{(s)}}^{(s)} \cdot u_{1}^{(p)} \cdots u_{d^{(p)}}^{(p)} \cdot u_{1}^{(i)} \cdots u_{d^{(i)}}^{(i)}.$$
(50)

The following subsections will expose the more detailed algorithm design. We will first present the flow of computation from the host to the accelerators and back to the host one layer at a time, and then present in detail how the host coordinates its own work and the work of the accelerators through host-side threading and appropriate synchronization primitives. Finally, we will parameterize the algorithm implementation.

Our expositionary focus will be on the implementation of the alternative-basis phase (36), (37), and (38) of the algorithm, with less attention and optimization effort devoted to the pre-and-postprocessing phases of data permutation and the basis changes at the host; the latter can be found in the accompanying source code.

Linearization and indexing conventions recalled. At this point it is convenient to recall that we tacitly employ the first-index-major linearization convention (16) when linearizing bit arrays to words of memory; that is, changing the most significant (leftmost) indices in a tuple of indices causes the largest stride in memory addressing, and the least significant (rightmost) indices will index bits inside a word of memory as appropriate. We follow a similar convention when linearizing thread arrays on accelerators (49); that is, hardware vectorization occurs with the least significant (rightmost) indices of a tuple indexing a thread in an array of asynchronous threads that implements a workload on an accelerator. We assume that the accelerator hardware computes with vectors of *V* synchronous threads with consecutive linear indices and that each thread can load and store *W*-bit words.

3.5 Input Permutation at the Host

S

To obtain coalesecent execution of the layered design on vectorized accelerator hardware, it will be convenient to permute the input matrices A' and B' from the $s \times t$ and $t \times u$ layouts with (50) into the interleaved-layout vectors A and B of lengths

$${}^{(h)}_{1}t^{(h)}_{1}\cdots s^{(h)}_{d^{(h)}}t^{(h)}_{d^{(h)}}s^{(s)}_{1}t^{(s)}_{1}\cdots s^{(s)}_{d^{(s)}}t^{(s)}_{d^{(s)}}s^{(p)}_{1}t^{(p)}_{1}\cdots s^{(p)}_{d^{(p)}}t^{(p)}_{d^{(p)}}s^{(i)}_{1}t^{(i)}_{1}\cdots s^{(i)}_{d^{(i)}}t^{(i)}_{d^{(i)}}$$
(51)

and

$$t_{1}^{(h)}u_{1}^{(h)}\cdots t_{d^{(h)}}^{(h)}u_{d^{(h)}}^{(h)}t_{1}^{(s)}u_{1}^{(s)}\cdots t_{d^{(s)}}^{(s)}u_{d^{(s)}}^{(p)}t_{1}^{(p)}u_{1}^{(p)}\cdots t_{d^{(p)}}^{(p)}u_{d^{(p)}}^{(p)}t_{1}^{(i)}u_{1}^{(i)}\cdots t_{d^{(i)}}^{(i)}u_{d^{(i)}}^{(i)},$$
(52)

respectively. This permutation is executed in host memory, using appropriate parallelization, vectorization primitives, and cache-blocking at the host for efficiency. For uniform implementation of Boolean and binary matrix multiplication, our low-level implementation also transposes the right-hand side operand at this point by transposing the roles of t and u in (52). The innermost transpose is implemented for 64×64 submatrices recursively using word operations on 32-bit words, cf. [40].

3.6 Input Basis Change at the Host

After input permutation, we execute basis changes $\hat{A} \leftarrow \bar{\phi}A$ and $\hat{B} \leftarrow \bar{\psi}B$ at the host. Both basis changes are executed in parallel using Yates's algorithm (30) on *d* levels. The innermost $d^{(i)}$ levels employ the identity basis change and thus are omitted; indeed, we work with the standard-basis cubic multiplication algorithm in the accelerator inner layer in §3.10, so no basis changes will be required.

3.7 Instance Generation at the Host

We now proceed to describe the sub-instances that the host generates and forwards to the *N* accelerators for processing. In particular, we assume that the alternative-basis inputs \hat{A} and \hat{B} have been prepared and reside in shared memory for parallel access by multiple host-threads working in parallel to keep all the *N* accelerators saturated with work; we postpone the precise description of the host-side threading and synchronization to §3.16.

In essence, the sub-instances are generated from \hat{A} and \hat{B} as the sub-arrays obtained by aggregating the linear combinations at the $d^{(h)}$ first levels of the base design (36) at once, which results in increased arithmetic cost compared with (36) implemented using Yates's algorithm, but keeps the working memory needs low at the host, as per our engineering goal to scale up to large inputs on a single host.

In precise terms, the sub-instance indexed by $(h_1, h_2, \dots, h_{d^{(h)}}) \in [r_1^{(h)}] \times [r_2^{(h)}] \times \dots \times [r_{d^{(h)}}^{(h)}]$ consists of the vectors

$$\hat{T}_{h_{1}h_{2}\cdots h_{d^{(h)}}}^{[h]} \leftarrow \sum_{\substack{(i_{1},i_{2},\dots,i_{d^{(h)}})\in[s_{1}^{(h)}]\times[s_{2}^{(h)}]\times\cdots\times[s_{d^{(h)}}^{(h)}]}_{(j_{1},j_{2},\dots,j_{d^{(h)}})\in[t_{1}^{(h)}]\times[s_{2}^{(h)}]\times\cdots\times[s_{d^{(h)}}^{(h)}]}} \alpha_{h_{1}i_{1}j_{1}}^{(h,1)}\alpha_{h_{2}i_{2}j_{2}}^{(h,2)}\cdots\alpha_{h_{d^{(h)}}i_{d^{(h)}}j_{d^{(h)}}}^{(h)}\hat{A}_{i_{1}j_{1}i_{2}j_{2}\cdots i_{d^{(h)}}j_{d^{(h)}}}, \\
\hat{S}_{h_{1}h_{2}\cdots h_{d^{(h)}}}^{[h]} \leftarrow \sum_{\substack{(j_{1},j_{2},\dots,j_{d^{(h)}})\in[t_{1}^{(h)}]\times[t_{2}^{(h)}]\times\cdots\times[t_{d^{(h)}}]\\(k_{1},k_{2},\dots,k_{d^{(h)}})\in[t_{1}^{(h)}]\times[t_{2}^{(h)}]\times\cdots\times[t_{d^{(h)}}]}} \beta_{h_{1}j_{1}k_{1}}^{(h,1)}\beta_{h_{2}j_{2}k_{2}}^{(h,2)}\cdots\beta_{h_{d^{(h)}}j_{d^{(h)}}k_{d^{(h)}}}^{(h,d^{(h)})}\hat{B}_{j_{1}k_{1}j_{2}k_{2}\cdots j_{d^{(h)}}k_{d^{(h)}}}.$$
(53)

We compute these vectors by aggregating the sums of subvectors in (53) as they are stated, taking care to not consider subvectors whose associated α -product (respectively, β -product) in (53) is zero. At low level, subroutines for performing the XOR and memory copy operations on subvectors have been handcrafted to make use of the 256-bit AVX2-registers in CPU hardware. The routines also perform reads and writes of 512 bits at a time, which corresponds to the length of cache lines on the target CPU. We leave these low-level implementation details to the accompanying source code.

In total thus $r_1^{(h)}r_2^{(h)}\cdots r_{d^{(h)}}^{(h)}$ sub-instances are generated and forwarded for solution by the *N* accelerators. Such solving of a sub-instance $(\hat{T}_{h_1h_2\cdots h_{d^{(h)}}}^{[h]}, \hat{S}_{h_1h_2\cdots h_{d^{(h)}}}^{[h]})$ by an accelerator consists of (i) uploading the sub-instance to one of the accelerators, (ii) having the accelerator compute the solution $\hat{Q}_{h_1h_2\cdots h_{d^{(h)}}}^{[h]}$, and (iii) downloading the solution from the accelerator to shared memory at the host. We next describe how each accelerator proceeds to solve a given sub-instance, and then describe how each downloaded solution $\hat{Q}_{h_1h_2\cdots h_{d^{(h)}}}^{[h]}$ is aggregated to the master solution \hat{C} at the host.

3.8 Accelerator Serial Layer

Suppose the sub-instance $(\hat{T}_{h_1h_2\cdots h_{d^{(h)}}}^{[h]}, \hat{S}_{h_1h_2\cdots h_{d^{(h)}}}^{[h]})$ has been uploaded to an accelerator. The accelerator then proceeds to solve the instance using three layers. First, a serial layer works with the instance recursively, at the bottom of the recursion switching to parallel work with three parts, the expanding parallel layer, the inner layer, and the compressing parallel layer. We start with a description of the serial (recursive) layer. Let the uploaded instance

$$\begin{split} \hat{T}^{[\mathrm{s},0]} &= \hat{T}^{[\mathrm{h}]}_{h_1 h_2 \cdots h_{d^{(\mathrm{h})}}} , \\ \hat{S}^{[\mathrm{s},0]} &= \hat{S}^{[\mathrm{h}]}_{h_1 h_2 \cdots h_{d^{(\mathrm{h})}}} \end{split}$$

be the input to the serial layer. The serial layer consists of $d^{(s)}$ levels.

Each recursive invocation at level $\ell = 1, 2, ..., d^{(s)}$ can be indexed by a tuple $(h_1, h_2, ..., h_{\ell-1}) \in [r_1^{(s)}] \times [r_2^{(s)}] \times \cdots \times [r_{\ell-1}^{(s)}]$. In particular, the initial invocation at $\ell = 1$ is indexed by the empty tuple and with input consisting of the vectors $\hat{T}^{[s,0]}$ and $\hat{S}^{[s,0]}$. More generally, the input to invocation $(h_1, h_2, \cdots, h_{\ell-1})$ consists of vectors $\hat{T}^{[s,\ell-1]}_{h_1h_2\cdots h_{\ell-1}}$ and $\hat{S}^{[s,\ell-1]}_{h_1h_2\cdots h_{\ell-1}}$. For $h_{\ell} \in [r_{\ell}^{(s)}]$, the invocation computes the vectors

$$\hat{T}_{h_{1}h_{2}\cdots h_{\ell}}^{[s,\ell]} \leftarrow \sum_{\substack{i_{\ell}\in[s_{\ell}^{(s)}]\\j_{\ell}\in[t_{\ell}^{(s)}]}} \alpha_{h_{\ell}i_{\ell}j_{\ell}}^{(s,\ell-1)} \hat{T}_{h_{1}h_{2}\cdots h_{\ell-1}i_{\ell}j_{\ell}}^{[s,\ell-1]}, \qquad \hat{S}_{h_{1}h_{2}\cdots h_{\ell}}^{[s,\ell]} \leftarrow \sum_{\substack{j_{\ell}\in[t_{\ell}^{(s)}]\\k_{\ell}\in[u_{\ell}^{(s)}]}} \beta_{h_{\ell}i_{\ell}j_{\ell}}^{(s,\ell-1)} \hat{S}_{h_{1}h_{2}\cdots h_{\ell-1}i_{\ell}j_{\ell}}^{(s,\ell-1)}, \tag{54}$$

and makes the recursive invocation with index $(h_1, h_2, \ldots, h_\ell)$ and input consisting of the vectors $\hat{T}_{h_1h_2\cdots h_\ell}^{[s,\ell]}$ and $\hat{S}_{h_1h_2\cdots h_\ell}^{[s,\ell]}$, obtaining as return value and storing the solution $\hat{Q}_{h_1h_2\cdots h_\ell}^{[s,\ell]}$. At the bottom level of recursion when $\ell = d^{(s)}$, the expanding parallel layer (described in the following section) is invoked with the input, and the return value is obtained from the output of that layer. Once all $r_\ell^{(s)}$ return values $\hat{Q}_{h_1h_2\cdots h_\ell}^{[s,\ell]}$ for $h_\ell \in [r_\ell^{(s)}]$ are available, the invocation computes and returns the value $\hat{Q}_{h_1h_2\cdots h_{\ell-1}}^{[s,\ell]}$ defined for all $i_\ell \in [s_\ell^{(s)}]$ and $j_\ell \in [t_\ell^{(s)}]$ by

$$\hat{Q}_{h_{1}h_{2}\cdots h_{\ell-1}i_{\ell}j_{\ell}}^{[s,\ell-1]} \leftarrow \sum_{h_{\ell}\in[r_{\ell}^{(s)}]} \gamma_{i_{\ell}j_{\ell}h_{\ell}}^{(s,\ell)} \hat{Q}_{h_{1}h_{2}\cdots h_{\ell}}^{[s,\ell-1]} \,.$$
(55)

The array-arithmetic in (54) and (55) is implemented with thread arrays on the accelerator so that each thread produces one *W*-bit word of output using optimized straight-line programs for matrix-vector multiplication with the α , β , and γ matrices.

3.9 Accelerator Expanding Parallel Layer

We now turn to the layer that implements Yates's algorithm with each of the α and β matrices, as follows. Each input to the expanding parallel layer arrives from the bottom level of recursion in the serial layer. Let us write $\hat{T}^{[p,0]}$ and $\hat{S}^{[p,0]}$ for the input vectors to the parallel layer. These vectors have lengths

$$s_{1}^{(p)}t_{1}^{(p)}s_{2}^{(p)}t_{2}^{(p)}\cdots s_{d^{(p)}}^{(p)}t_{d^{(p)}}^{(p)}t_{1}^{(i)}t_{1}^{(i)}s_{2}^{(i)}t_{2}^{(i)}\cdots s_{d^{(i)}}^{(i)}t_{d^{(i)}}^{(i)} \quad \text{and} \quad t_{1}^{(p)}u_{1}^{(p)}t_{2}^{(p)}u_{2}^{(p)}\cdots t_{d^{(p)}}^{(p)}u_{d^{(p)}}^{(p)}t_{1}^{(i)}u_{1}^{(i)}t_{2}^{(i)}u_{2}^{(i)}\cdots t_{d^{(i)}}^{(i)}u_{d^{(i)}}^{(i)},$$

respectively. We describe the processing of the input $\hat{T}^{[p,0]}$ only, with the understanding that the processing of $\hat{S}^{[p,0]}$ is similar but utilizes the β matrices in place of the α matrices.

Let us write $\bar{\alpha}^{[p]}$ for the matrix

$$\bar{\alpha}^{[\mathbf{p}]} = \alpha^{(\mathbf{p},1)} \otimes \alpha^{(\mathbf{p},2)} \otimes \dots \otimes \alpha^{(\mathbf{p},d^{(\mathbf{p})})} \otimes I_{s_1^{(i)}t_1^{(i)}s_2^{(i)}t_2^{(i)} \dots s_{d^{(i)}}^{(i)}t_{d^{(i)}}^{(i)}}$$

and decompose the matrix using Yates's decomposition (28) with respect to the reversal permutation as

$$\bar{\alpha}^{[p]} = \bar{\alpha}^{[p, d^{(p)}]} \bar{\alpha}^{[p, d^{(p)} - 1]} \cdots \bar{\alpha}^{[p, 1]}$$

The parallel layer proceeds to compute $\bar{\alpha}^{[p]}\hat{T}^{[p,0]}$ by a sequence of matrix-vector multiplications $\hat{T}^{[p,\ell]} \leftarrow \tilde{\alpha}^{[p,\ell]}T^{[p,\ell-1]}$ for $\ell = 1, 2, \ldots, d^{(p)}$. Each multiplication in the sequence is implemented with vectorization using *W*-bit words⁶ and parallelization via a thread array of

$$r_{1}^{(p)}r_{2}^{(p)}\cdots r_{\ell-1}^{(p)}s_{\ell+1}^{(p)}t_{\ell+1}^{(p)}s_{\ell+2}^{(p)}t_{\ell+2}^{(p)}\cdots s_{d^{(p)}}^{(p)}t_{d^{(p)}}^{(p)}s_{1}^{(i)}t_{1}^{(i)}s_{2}^{(i)}t_{2}^{(i)}\cdots s_{d^{(i)}}^{(i)}t_{d^{(i)}}^{(i)} / W$$

threads working asynchronously, so that each thread loads $s_{\ell}^{(p)} t_{\ell}^{(p)}$ words from the array $\hat{T}^{[p,\ell-1]}$ to its local registers, word-bit-parallel multiplies in registers with W copies of the matrix $\alpha^{(p,\ell)}$ using an optimized straight-line program, and saves $r_{\ell}^{(p)}$ words to the array $\hat{T}^{[p,\ell]}$. We illustrate the design in pseudocode with Algorithm 1, where we assume that w is a nonnegative integer with $W = s_{d^{(i)}-w+1}^{(i)} t_{d^{(i)}-w+1}^{(i)} \cdots s_{d^{(i)}}^{(i)} t_{d^{(i)}}^{(i)}$, and that the parameterization of the inner layer is such that such a w exists; this will be the case in what follows.

The output of the layer consists of the expanded vectors $\hat{T}^{[p, d^{(p)}]}$ and $\hat{S}^{[p, d^{(p)}]}$ of lengths

$$r_1^{(p)}r_2^{(p)}\cdots r_{d^{(p)}}^{(p)}s_1^{(i)}t_1^{(i)}s_2^{(i)}t_2^{(i)}\cdots s_{d^{(i)}}^{(i)}t_{d^{(i)}}^{(i)} \quad \text{and} \quad r_1^{(p)}r_2^{(p)}\cdots r_{d^{(p)}}^{(p)}t_1^{(i)}u_1^{(i)}t_2^{(i)}u_2^{(i)}\cdots t_{d^{(i)}}^{(i)}u_{d^{(i)}}^{(i)},$$

respectively, which are in turn given as input to the inner layer.

3.10 Accelerator Inner Layer

The inner layer is the most performance-critical part of the design since it works with the expanded vectors and thus with the most data aggregated over the execution of the algorithm. The inner layer takes as input two vectors $\hat{T}^{[i]}$ and $\hat{S}^{[i]}$. The output of the layer is the product

$$\hat{Q}^{[i]} = \bar{\gamma}^{[i]} (\bar{\alpha}^{[i]} \hat{T}^{[i]} \odot \bar{\beta}^{[i]} \hat{S}^{[i]}),$$

 $[\]overline{{}^{6}We}$ tacitly assume in what follows that W divides the product $s_{1}^{(i)}t_{1}^{(i)}s_{2}^{(i)}t_{2}^{(i)}\cdots s_{d}^{(i)}t_{d}^{(i)}$. Indeed, W is in most cases a power of two, and the product can be similarly chosen to be a power of two by careful design of the inner layer.

Algorithm 1 The accelerator expanding parallel layer illustrated in pseudocode. This pseudocode illustrates the procedure implemented using a thread array for level $\ell = 1, 2, ..., d^{(p)}$ that takes as input $\hat{T}^{[p, \ell-1]}$ and yields the output $\hat{T}^{[p, \ell]}$. Each thread in the array reads $s_{\ell}^{(p)} t_{\ell}^{(p)}$ words to its local registers, multiplies with the matrix $\alpha^{(p, \ell)}$ in registers, and writes $r_{\ell}^{(p)}$ words. This procedure illustrates operation for the left input only; the procedure for the right input is similar.

1: procedure $AcceleratorExpandingParallelLeft(\hat{T}^{[p, \ell-1]}, \ell)$ 2: parallel for thread $(h_1^{(p)}, \dots, h_{\ell-1}^{(p)}, i_{\ell+1}^{(p)}, j_{\ell+1}^{(p)}, \dots, i_{d^{(p)}}^{(p)}, j_{d^{(p)}}^{(p)}, i_1^{(i)}, j_1^{(i)}, \dots, i_{d^{(i)}-w}^{(i)}, j_{d^{(i)}-w}^{(i)}) \in \\ [r_1^{(p)}] \times \dots \times [r_{\ell-1}^{(p)}] \times [s_{\ell+1}^{(p)}] \times [t_{\ell+1}^{(p)}] \times \dots \times [s_{d^{(p)}}^{(p)}] \times [t_d^{(p)}] \times [s_1^{(i)}] \times [t_1^{(i)}] \times \dots \times [s_{d^{(i)}-w}^{(i)}] \times [t_d^{(i)}] \times [t_d^{(i)$ $\begin{aligned} & \mathbf{do} \\ & \mathbf{for} \ (i_{\ell}^{(p)}, j_{\ell}^{(p)}) \in [s_{\ell}^{(p)}] \times [t_{\ell}^{(p)}] \, \mathbf{do} \\ & \hat{T}_{[local, \ell-1]}^{[local, \ell-1]} \leftarrow \hat{T}_{h_{1}^{(p)} \cdots h_{\ell-1}^{(p)} i_{\ell}^{(p)} j_{\ell}^{(p)} i_{\ell+1}^{(p)} j_{\ell+1}^{(p)} \cdots i_{d^{(p)}}^{(p)} j_{d^{(p)}}^{(p)} i_{1}^{(i)} j_{1}^{(i)} \cdots i_{d^{(i)} - w}^{(i)} j_{d^{(i)} - w}^{(i)} \end{aligned}$ 3: 4: 5: $\hat{T}^{[\text{local},\ell]} \leftarrow \alpha^{(\mathrm{p},\ell)} \hat{T}^{[\text{local},\ell-1]}$ [[Implemented with word-bit-operations using an optimized 6: straight-line program for multiplying the $r_{\ell}^{(p)} \times s_{\ell}^{(p)} t_{\ell}^{(p)}$ matrix $\alpha^{(p,\ell)}$ with the $s_{\ell}^{(p)} t_{\ell}^{(p)}$ vector $\hat{T}^{[\text{local},\ell-1]}$, such as (7) or (13).]] $\begin{array}{l} \text{for } h_{\ell}^{(\mathrm{p})} \in [r_{\ell}^{(\mathrm{p})}] \text{ do} \\ \hat{T}_{1}^{[\mathrm{p},\ell]} \\ h_{1}^{(\mathrm{p})\cdots}h_{\ell-1}^{(\mathrm{p})}h_{\ell}^{(\mathrm{p})}i_{\ell+1}^{(\mathrm{p})}j_{\ell+1}^{(\mathrm{p})}\cdots i_{d^{(\mathrm{p})}}^{(\mathrm{p})}j_{d^{(\mathrm{p})}}^{(\mathrm{p})}i_{1}^{(\mathrm{i})}j_{1}^{(\mathrm{i})}\cdots i_{d^{(\mathrm{i})}-w}^{(\mathrm{i})}j_{d^{(\mathrm{i})}-w}^{(\mathrm{i})} \leftarrow \hat{T}_{\ell}^{[\mathrm{local},\ell]} \\ h_{\ell}^{(\mathrm{p})} \end{array}$ 7: 8: 9 end for 10: end for 11: end procedure

where

$$\begin{split} \bar{\alpha}^{[\mathbf{i}]} &= I_{r_1^{(\mathbf{p})} r_2^{(\mathbf{p})} \cdots r_{d^{(\mathbf{p})}}^{(\mathbf{p})}} \otimes \alpha^{(\mathbf{i},1)} \otimes \alpha^{(\mathbf{i},2)} \otimes \cdots \otimes \alpha^{(\mathbf{i},d^{(\mathbf{i})})} \,, \\ \bar{\beta}^{[\mathbf{i}]} &= I_{r_1^{(\mathbf{p})} r_2^{(\mathbf{p})} \cdots r_{d^{(\mathbf{p})}}^{(\mathbf{p})}} \otimes \beta^{(\mathbf{i},1)} \otimes \beta^{(\mathbf{i},2)} \otimes \cdots \otimes \beta^{(\mathbf{i},d^{(\mathbf{i})})} \,, \\ \bar{\gamma}^{[\mathbf{i}]} &= I_{r_1^{(\mathbf{p})} r_2^{(\mathbf{p})} \cdots r_{d^{(\mathbf{p})}}^{(\mathbf{p})}} \otimes \gamma^{(\mathbf{i},1)} \otimes \gamma^{(\mathbf{i},2)} \otimes \cdots \otimes \gamma^{(\mathbf{i},d^{(\mathbf{i})})} \,. \end{split}$$

As the inner layer works with the least significant bit positions of the bit vectors, in most cases the implementation of the inner layer is hardware-specific and amounts to making the best possible use of the available bit- and word-operations in the instruction set as well as the available vectorization and associated vector-shuffling instructions.

For example, with *W*-bit words and length-*V* hardware vectorization of thread arrays with $M^2 = WV$, one possibility to implement the inner layer is to perform $r_1^{(p)}r_2^{(p)}\cdots r_{d^{(p)}}^{(p)}$ independent $M \times M$ binary matrix multiplications in parallel using the elementary cubic algorithm implemented with word operations and a thread array of $r_1^{(p)}r_2^{(p)}\cdots r_{d^{(p)}}^{(p)}V$ threads, so that each thread works with one *W*-bit-word-size fragment from each of the $M \times M$ operand matrices and the result matrix, with hardware *V*-vector shuffle instructions used to communicate words between threads. This is essentially how our low-level implementation of the inner layer is structured, though some optimizations remain to be discussed in §3.15. This part of the framework is also the most sensitive to changes in underlying hardware, and so is perhaps the least likely to withstand the test of time.

3.11 Accelerator Compressing Parallel Layer

Once the inner layer is complete, its output $\hat{Q}^{[i]}$ is given as input to a further parallel layer that implements Yates's algorithm with the γ matrices, as follows. Let us write $\hat{Q}^{[p, d^{(p)}]}$ for the input vector to the compressing parallel layer. Similarly to the expanding layer, let us write $\bar{\gamma}^{[p]}$ for the matrix

$$\bar{\gamma}^{[p]} = \gamma^{(p,1)} \otimes \gamma^{(p,2)} \otimes \cdots \otimes \gamma^{(p,d^{(p)})} \otimes I_{s_1^{(i)}u_1^{(i)}s_2^{(i)}u_2^{(i)}\cdots s_{d^{(i)}}^{(i)}u_{d^{(i)}}^{(i)}$$

and decompose the matrix using Yates's decomposition (28) with respect to the identity permutation as

$$\bar{v}^{[p]} = \bar{v}^{[p,1]} \bar{v}^{[p,2]} \cdots \bar{v}^{[p,d^{(p)}]}$$

The parallel layer proceeds to compute $\bar{\gamma}^{[p]} \hat{Q}^{[p, d^{(p)}]}$ by a sequence of matrix-vector multiplications $\hat{Q}^{[p, \ell-1]} \leftarrow \bar{\gamma}^{[p, \ell]} Q^{[p, \ell]}$ for $\ell = d^{(p)}, d^{(p)} - 1, \ldots, 1$. Each multiplication in the sequence is implemented with vectorization using *W*-bit words and parallelization via a thread array of

$$r_1^{(\mathbf{p})}r_2^{(\mathbf{p})}\cdots r_{\ell-1}^{(\mathbf{p})}s_{\ell+1}^{(\mathbf{p})}u_{\ell+1}^{(\mathbf{p})}s_{\ell+2}^{(\mathbf{p})}u_{\ell+2}^{(\mathbf{p})}\cdots s_{d^{(\mathbf{p})}}^{(\mathbf{p})}u_{d^{(\mathbf{p})}}^{(\mathbf{p})}s_1^{(\mathbf{i})}u_1^{(\mathbf{i})}s_2^{(\mathbf{i})}u_2^{(\mathbf{i})}\cdots s_{d^{(\mathbf{i})}}^{(\mathbf{i})}u_{d^{(\mathbf{i})}}^{(\mathbf{i})} / W$$

threads working asynchronously, so that each thread loads $r_{\ell}^{(p)}$ words from the array $\hat{Q}^{[p,\ell]}$ to its local registers, word-bit-parallel multiplies in registers with W copies of the matrix $\gamma^{(p,\ell)}$ using an optimized straight-line program, and stores $s_{\ell}^{(p)}u_{\ell}^{(p)}$ words to the array $\hat{Q}^{[p,\ell-1]}$. We illustrate the design in pseudocode with Algorithm 2, where, analogously to Algorithm 1, we assume that w is a nonnegative integer with $W = s_{d}^{(i)}u_{d}^{(i)}-w+1}u_{d}^{(i)}\cdots s_{d}^{(i)}u_{d}^{(i)}$.

The output of the layer consists of the compressed vector $\hat{Q}^{[p,0]}$ of length

$$s_1^{(\mathbf{p})}u_1^{(\mathbf{p})}s_2^{(\mathbf{p})}u_2^{(\mathbf{p})}\cdots s_{d^{(\mathbf{p})}}^{(\mathbf{p})}u_{d^{(\mathbf{p})}}^{(\mathbf{i})}s_1^{(\mathbf{i})}u_1^{(\mathbf{i})}s_2^{(\mathbf{i})}u_2^{(\mathbf{i})}\cdots s_{d^{(\mathbf{i})}}^{(\mathbf{i})}u_{d^{(\mathbf{i})}}^{(\mathbf{i})},$$

which is in turn given as output to the serial layer.

3.12 Instance Aggregation at the Host

The aggregation of a solution obtained at an accelerator proceeds as follows at the host, again with a focus on obtaining a design with a low working memory footprint in host memory at the price of increased arithmetic cost. Before any solutions are accepted, the output vector \hat{C} is initialized to all-0 values. Suppose that the solution $\hat{Q}_{h_1h_2\cdots h_{d^{(h)}}}^{[h]}$ for $(h_1, h_2, \ldots, h^{d^{(h)}}) \in [r_1^{(h)}] \times [r_2^{(h)}] \times \cdots \times [r_{d^{(h)}}^{(h)}]$ has been downloaded from an accelerator to host memory. We then execute the following aggregation procedure. For each $(i_1, i_2, \ldots, i_{d^{(h)}}) \in [s_1^{(h)}] \times [s_2^{(h)}] \times \cdots \times [s_{d^{(h)}}^{(h)}]$ and each $(k_1, k_2, \ldots, k_{d^{(h)}}) \in [u_1^{(h)}] \times [u_2^{(h)}] \times \cdots \times [u_{d^{(h)}}^{(h)}]$, whenever it holds that $\gamma_{i_1k_1h_1}^{(h, 1)} \gamma_{i_2k_2h_2}^{(h, 2)} \cdots \gamma_{i_{d^{(h)}}k_{d^{(h)}}h_{d^{(h)}}}^{(h, d^{(h)})} = 1$, then aggregate the solution to the output by

$$\hat{C}_{i_1k_1i_2k_2\cdots i_{d^{(h)}}k_{d^{(h)}}} \leftarrow \hat{C}_{i_1k_1i_2k_2\cdots i_{d^{(h)}}k_{d^{(h)}}} + \hat{Q}_{h_1h_2\cdots h_{d^{(h)}}}^{[h]} .$$
(56)

When multiple host-threads execute aggregation in parallel, appropriate synchronization primitives need to be employed to avoid conflicts between threads when executing (56). This will be described in detail in §3.16.

3.13 Output Basis Change at the Host

After the alternative-basis output \hat{C} has been aggregated, we execute the basis change $C \leftarrow \bar{\chi}\hat{C}$ at the host, in parallel using Yates's algorithm (30) on *d* levels. In our implementation, the innermost $d^{(i)}$ levels employ the identity basis change (since the accelerator inner-layer uses the standard-basis cubic multiplication algorithm) and thus are omitted.

Algorithm 2 The accelerator compressing parallel layer illustrated in pseudocode. This pseudocode illustrates the procedure implemented using a thread array for level $\ell = d^{(p)}, d^{(p)} - 1, \ldots, 1$ that takes as input $\hat{Q}^{[p,\ell]}$ and yields the output $\hat{Q}^{[p,\ell-1]}$. Each thread in the array reads $r_{\ell}^{(p)}$ words to its local registers, multiplies with the matrix $\gamma^{(p,\ell)}$ in registers, and writes $s_{\ell}^{(p)} u_{\ell}^{(p)}$ words.

1: **procedure** AcceleratorCompressingParallel($\hat{Q}^{[p, \ell]}, \ell$) 2: parallel for thread $(h_{1}^{(p)}, \dots, h_{\ell-1}^{(p)}, i_{\ell+1}^{(p)}, k_{\ell+1}^{(p)}, \dots, i_{d^{(p)}}^{(p)}, k_{d^{(p)}}^{(p)}, i_{1}^{(i)}, k_{1}^{(i)}, \dots, i_{d^{(i)}-w}^{(i)}, k_{d^{(i)}-w}^{(i)}) \in \\ [r_{1}^{(p)}] \times \dots \times [r_{\ell-1}^{(p)}] \times [s_{\ell+1}^{(p)}] \times [u_{\ell+1}^{(p)}] \times \dots \times [s_{d^{(p)}}^{(p)}] \times [u_{d^{(p)}}^{(p)}] \times [s_{1}^{(i)}] \times [u_{1}^{(i)}] \times \dots \times [s_{d^{(i)}-w}^{(i)}] \times [u_{d^{(i)}-w}^{(i)}]$ **do for** $h_{\ell}^{(p)} \in [r_{\ell}^{(p)}]$ **do** $\hat{Q}_{h_{\ell}^{(p)}}^{[local, \ell]} \leftarrow \hat{Q}_{h_{1}^{(p)} \cdots h_{\ell-1}^{(p)}}^{[p, \ell]} h_{\ell}^{(p)} i_{\ell+1}^{(p)} k_{\ell+1}^{(p)} \cdots i_{d(p)}^{(p)} k_{d(p)}^{(p)} i_{1}^{(i)} k_{1}^{(i)} \cdots i_{d(i)-w}^{(i)} k_{d(i)-w}^{(i)}$ If Implemented with word-bit-c 3: 4: 5: end for $\hat{Q}^{[\text{local}, \ell-1]} \leftarrow \gamma^{(p, \ell)} \hat{Q}^{[\text{local}, \ell]}$ [[Implemented with word-bit-operations using an optimized $\hat{Q}^{[\text{local}, \ell-1]} \leftarrow \gamma^{(p, \ell)} \hat{Q}^{[\text{local}, \ell]}$ 6: straight-line program for multiplying the $s_{\ell}^{(p)} u_{\ell}^{(p)} \times r_{\ell}^{(p)}$ matrix $\gamma^{(p,\ell)}$ with the $r_{\ell}^{(p)}$ vector $\hat{Q}^{[\text{local},\ell]}$, such as (9) or (15).]] $\mathbf{for} (i_{\ell}^{(p)}, k_{\ell}^{(p)}) \in [s_{\ell}^{(p)}] \times [u_{\ell}^{(p)}] \mathbf{do} \\ \hat{\mathcal{Q}}_{h_{1}^{(p)} \cdots h_{\ell-1}^{(p)} i_{\ell}^{(p)} k_{\ell}^{(p)} i_{\ell+1}^{(p)} k_{\ell+1}^{(p)} \cdots i_{d(p)}^{(p)} k_{d(p)}^{(p)} i_{1}^{(i)} i_{1}^{(i)} \cdots i_{d(i)-w}^{(i)} k_{d(i)-w}^{(i)} \leftarrow \hat{\mathcal{Q}}_{i_{\ell}^{(p)} k_{\ell}^{(p)}}^{[local, \ell-1]} \\ \hat{\mathcal{Q}}_{i_{\ell}^{(p)} k_{\ell}^{(p)}}^{(p)} (i_{\ell+1}^{(p)} k_{\ell+1}^{(p)} \cdots i_{d(p)}^{(p)} k_{d(p)}^{(p)} i_{1}^{(i)} i_{1}^{(i)} \cdots i_{d(i)-w}^{(i)} k_{d(i)-w}^{(i)} \leftarrow \hat{\mathcal{Q}}_{i_{\ell}^{(p)} k_{\ell}^{(p)}}^{[local, \ell-1]}$ 7: 8: 9: end fo end for 10: 11: end procedure

3.14 Output Permutation at the Host

The last layer of the framework permutes the interleaved-layout vector C of length

$$s_{1}^{(h)}u_{1}^{(h)}\cdots s_{d^{(h)}}^{(h)}u_{d^{(h)}}^{(h)}s_{1}^{(s)}u_{1}^{(s)}\cdots s_{d^{(s)}}^{(s)}u_{d^{(s)}}^{(s)}s_{1}^{(p)}u_{1}^{(p)}\cdots s_{d^{(p)}}^{(p)}u_{d^{(p)}}^{(p)}s_{1}^{(i)}u_{1}^{(i)}\cdots s_{d^{(i)}}^{(i)}u_{d^{(i)}}^{(i)}$$
(57)

to an $s \times u$ output matrix C' with s and u as in (50). This completes the description of the layers of the algorithm design.

3.15 Further Optimization by Merging Levels and Shifting Levels Between Layers

The previous framework can be further optimized at the accelerators by making more extensive use of the registers local to each thread in a thread array, assuming such registers are available in sufficient quantity. This section documents two techniques towards this end.

Merging levels. Assuming the parameters $r_{\ell}^{(p)}$, $s_{\ell}^{(p)}$, $t_{\ell}^{(p)}$, $u_{\ell}^{(p)}$ of the expanding levels $\ell = 1, 2, ..., d^{(p)}$ in the expanding layer (cf. §3.9) are small enough, one may utilize the per-thread registers and compute two consecutive levels, ℓ and $\ell + 1$, instead of only one level ℓ . In this case one works with a thread array of

$$r_1^{(p)}r_2^{(p)}\cdots r_{\ell-1}^{(p)}s_{\ell+2}^{(p)}t_{\ell+2}^{(p)}s_{\ell+3}^{(p)}t_{\ell+3}^{(p)}\cdots s_{d^{(p)}}^{(p)}t_{d^{(p)}}^{(p)}s_1^{(i)}t_1^{(i)}s_2^{(i)}t_2^{(i)}\cdots s_{d^{(i)}}^{(i)}t_{d^{(i)}}^{(i)} / W$$

threads, so that each thread loads $s_{\ell}^{(p)} t_{\ell}^{(p)} s_{\ell+1}^{(p)} t_{\ell+1}^{(p)}$ words from accelerator memory to its local registers, then multiplies word-bit-parallel in registers with *W* copies of the matrix $\alpha^{(p,\ell)} \otimes \alpha^{(p,\ell+1)}$ using optimized straight-line programs for both component matrices (that is, one implements with register arithmetic Yates's algorithm using straight-line programs for $\alpha^{(p,\ell)}$ and $\alpha^{(p,\ell+1)}$ for the levels ℓ and $\ell + 1$ computed in registers), and finally saves $r_{\ell}^{(p)} r_{\ell+1}^{(p)}$ words to accelerator memory. Similar merging of levels may be used for the compressing layer (cf. §3.11). Our low-level implementation uses this two-level merging for pairs of levels closest to the inner layer. In particular one wants to optimize at levels closest to the inner layer because these layers process the longest vectors and thus do the most work. If more per-thread registers are available, more consecutive levels can be merged and computed in registers.

Shifting levels between layers. The inner layer can use per-thread registers more efficiently by shifting expanding/compressing levels to the inner layer from the expanding/compressing layers. Assuming that the parameters of the expansion/compression are $r_{\ell}^{(p)}$, $s_{\ell}^{(p)}$, $t_{\ell}^{(p)}$, $u_{\ell}^{(p)}$, and that the inner layer originally implements $M \times M$ standardbasis matrix multiplication (cf. §3.10) using one *W*-bit-word per thread, the inner layer with shifting (i) first loads $s_{\ell}t_{\ell} + t_{\ell}u_{\ell}$ words to each thread, (ii) expands in registers using straight-line programs for $\alpha^{(p,\ell)}$ and $\beta^{(p,\ell)}$ to $r_{\ell} + r_{\ell}$ words of operands per thread, (iii) executes in registers r_{ℓ} independent $M \times M$ matrix multiplications (essentially repeating the original inner layer r_{ℓ} times in registers) to obtain r_{ℓ} words of expanded results, and (iv) finally compresses to $s_{\ell}u_{\ell}$ words of results per thread using a straight-line program for $\gamma^{(p,\ell)}$ and writes these results to accelerator memory. Our low-level implementation follows this strategy of shifting one level of expansion/compression to the inner layer to make more efficient use of per-thread registers and to perform less accelerator-memory transactions at the inner layer.

3.16 Coordinating the Workload

This section describes how the entire workload for the host and the *N* accelerators is coordinated at the host using host-threads and appropriate synchronization.

Let us start by recalling that the top-level alternative-basis workload $(\hat{A}, \hat{B}) \mapsto \hat{C}$ consists of $r_1^{(h)}r_2^{(h)}\cdots r_{d^{(h)}}^{(h)}$ subinstances that need to be (i) generated from \hat{A} and \hat{B} on the host, (ii) solved in an accelerator, and (iii) the solution aggregated to \hat{C} on the host. This suggests processing the workload with N essentially independent pipelines implemented by one or more host-threads each so that each pipeline is responsible for keeping exactly one accelerator busy with work. Synchronization between pipelines is also required because the aggregation steps (56) of different pipelines can access and update the same subarray of \hat{C} , which can lead to data races unless synchronization is used to ensure serial updates to each subarray.

Our strategy is to implement the pipeline for each accelerator $\ell \in [N]$ using three buffers $T_{\ell}, S_{\ell}, Q_{\ell}$ in host memory and four host-threads: one thread to prepare the left input T_{ℓ} in host memory, one thread to prepare the right input S_{ℓ} in host memory, one thread to multiply T_{ℓ}, S_{ℓ} on accelerator ℓ to obtain the result Q_{ℓ} (including uploading the input and downloading the result), and one thread to aggregate the result Q_{ℓ} to the result \tilde{C} .

Pseudocode for coordinating work at the host is given in Algorithm 3. This workload of 4N host-threads is deadlockfree due to the design of the pipeline—blocking is needed to prevent race conditions occurring on the arrays T_{ℓ} , S_{ℓ} , Q_{ℓ} , the accelerator devices, and subarrays of the array \hat{C} , but each pipeline will always be flushed eventually. We also observe that the order in which the subproblems $(h_1, \ldots, h_{d(h)})$ are processed is insignificant as long as the order is well-defined, which is guaranteed by the locks on subarrays of \hat{C} . Here we have presented a 4N-thread design with a single 4-thread pipeline for each of the N accelerators; the design can be easily extended to multiple pipelines competing for a single accelerator device to better saturate the accelerators with data as appropriate.

3.17 Parameterizing the Implementation

Let us now turn to the detailed parameterization of the framework. Our current implementation uses the framework in a diagonal setting based on either of the two $\langle 2, 2, 2 \rangle_7$ alternative-basis decompositions developed in §2.2 and §2.3,

Engineering Boolean Matrix Multiplication for Multiple-Accelerator Shared-Memory Architectures

Algorithm 3 Procedure for coordinating work at a host joined to *N* accelerators. The input arrays are \hat{A} and \hat{B} and the output array is \hat{C} . The workload is formed of 4*N* threads. Each thread is associated with one of the *N* accelerators and a specific part of the pipeline for this accelerator.

1:	procedure HostCoordinate (\hat{A}, \hat{B}) ,
2:	Let T_{ℓ} for $\ell \in [N]$ be an array of shape $s_1^{(s)} t_1^{(s)} \cdots s_{d^{(s)}}^{(s)} t_{d^{(s)}}^{(s)} s_1^{(p)} t_1^{(p)} \cdots s_{d^{(p)}}^{(p)} t_{d^{(p)}}^{(p)} s_1^{(i)} t_1^{(i)} \cdots s_{d^{(i)}}^{(i)} t_{d^{(i)}}^{(i)}$
3:	Let S_{ℓ} for $\ell \in [N]$ be an array of shape $t_1^{(s)}u_1^{(s)}\cdots t_{d^{(s)}}^{(s)}u_{d^{(s)}}^{(p)}t_1^{(p)}u_1^{(p)}\cdots t_{d^{(p)}}^{(p)}u_{d^{(p)}}^{(p)}t_1^{(i)}u_1^{(i)}\cdots t_{d^{(i)}}^{(i)}u_{d^{(i)}}^{(p)}$
4:	Let Q_{ℓ} for $\ell \in [N]$ be an array of shape $s_1^{(s)}u_1^{(s)}\cdots s_{d(s)}^{(s)}u_{d(s)}^{(s)}s_1^{(p)}u_1^{(p)}\cdots s_{d(p)}^{(p)}u_{d(p)}^{(p)}s_1^{(i)}u_1^{(i)}\cdots s_{d(i)}^{(i)}u_{d(p)}^{(i)}$
5:	Initialize \hat{C} as zero $a \oplus a $
6:	parallel for thread $t \in [4N]$ do
7:	$\ell \leftarrow t \mod N$
8:	for $(h_1, \ldots, h_{d^{(h)}}) \in [r_1^{(h)}] \times \cdots \times [r_{d^{(h)}}^{(h)}]$ such that $\ell \equiv \sum_{i=1}^{d^{(h)}} h_i \prod_{j=i+1}^{d^{(h)}} r_j^{(h)} \pmod{N}$ do
9:	if $0 \le t \le N - 1$ then
10:	Block until I_{ℓ} is free
11:	Initialize I_{ℓ} as zero
12:	$\operatorname{for}(i_1, j_1, \dots, i_{d^{(h)}}, j_{d^{(h)}}) \in [s_1^{-1}] \times [t_1^{-1}] \times \dots \times [s_{d^{(h)}}] \times [t_{d^{(h)}}] \operatorname{do}$ $\operatorname{if} \alpha_{\cdot}^{(h, 1)} \cdots \alpha_{\cdot}^{(h, d^{(h)})} \neq 0 \text{ then}$
	$= h_1 i_1 j_1 \qquad h_d(\mathbf{h}) i_d(\mathbf{h}) j_d(\mathbf{h}) $
14:	$I_{\ell} \leftarrow I_{\ell} + A_{i_1 j_1 \cdots i_d (h)} j_{d(h)}$
15: 16:	end if end for
17:	Mark T_{ℓ} occupied
18:	else if $N \le t \le 2N - 1$ then
19:	Block until S_{ℓ} is free
20:	Initialize S_{ℓ} as zero
21:	for $(j_1, k_1, \dots, j_{d^{(h)}}, k_{d^{(h)}}) \in [t_1^{(h)}] \times [u_1^{(h)}] \times \dots \times [t_{d^{(h)}}^{(h)}] \times [u_{d^{(h)}}^{(h)}]$ do
22:	$ if \ \beta_{h_{1}j_{1}k_{1}}^{(h,1)} \cdots \beta_{h_{d}(h)j_{d}(h)k_{d}(h)}^{(h,d^{(h)})} \neq 0 \ then $
23:	$S_{\ell} \leftarrow S_{\ell} + \hat{B}_{j_1 k_1 \cdots j_d (h)} k_{d^{(h)}}$
24:	end if
25.	Mark Se occupied
20.	else if $2N < t < 3N - 1$ then
28.	Block until T_e and S_e are occupied and Q_e is free
29:	Unload T_{ℓ} and S_{ℓ} to accelerator ℓ
30:	Mark T_e and S_f free
31:	Multiply T_{ℓ} and S_{ℓ} on accelerator ℓ to obtain the result Q_{ℓ}
32:	Download O_{ℓ} from accelerator ℓ
33:	Mark Q_ℓ occupied
34:	else if $3N \le t \le 4N - 1$ then
35:	Block until Q_ℓ is occupied
36:	for $(i_1, k_2, \dots, i_{d^{(h)}}, k_{d^{(h)}}) \in [s_1^{(h)}] \times [u_1^{(h)}] \times \dots \times [s_{d^{(h)}}^{(h)}] \times [u_{d^{(h)}}^{(h)}]$ do
37:	if $\gamma_{i_1k_1h_1}^{(h,1)} \cdots \gamma_{i_d(h)k_d(h)h_d(h)}^{(h,d(h))} \neq 0$ then
38:	Acquire the lock for $\hat{C}_{i_1k_1\cdots i_{d(h)}k_{d(h)}}$
39:	$\hat{C}_{i_1k_1\cdots i_d(\mathbf{h})k_d(\mathbf{h})} \leftarrow \hat{C}_{i_1k_1\cdots i_d(\mathbf{h})k_d(\mathbf{h})} + Q_\ell$
40:	Release the lock for $\hat{C}_{i_1k_1\cdots i_{J(h)}k_{J(h)}}$
41:	end if
42:	end for
43:	Mark Q_ℓ free
44:	end if
45:	end for
46:	end for
47:	end procedure

respectively. Accordingly, we set

$$\begin{split} s_j^{d^{(\mathrm{l})}} &= s_j^{d^{(\mathrm{s})}} = s_j^{d^{(\mathrm{p})}} = 2 \,, \\ t_j^{d^{(\mathrm{h})}} &= t_j^{d^{(\mathrm{s})}} = t_j^{d^{(\mathrm{p})}} = 2 \,, \\ u_j^{d^{(\mathrm{h})}} &= u_j^{d^{(\mathrm{s})}} = u_j^{d^{(\mathrm{p})}} = 2 \,, \\ r_j^{d^{(\mathrm{h})}} &= r_j^{d^{(\mathrm{s})}} = r_j^{d^{(\mathrm{p})}} = 7 \,. \end{split}$$

When more efficient decompositions are discovered, these can be immediately used in the present framework.

The present accelerator hardware has *V*-length vectorization of threads with V = 32, and the maximum word length supported per thread for memory transactions is W = 128 bits.⁷ We structure the inner layer to work with $M \times M$ matrices, M = 64, so that $M^2 = VW$ and the $M \times M$ multiplication can work with instructions for shuffling data between threads across each *V*-length vector of threads in a thread array. Accordingly, we let the inner layer consists of a single level with

$$d^{(i)} = 1,$$
 $s_1^{(i)} = t_1^{(i)} = u_1^{(i)} = M.$

This level works in the standard basis and does not use basis changes.

The setting of the parameters $d^{(h)}$, $d^{(s)}$, and $d^{(p)}$ for best performance depends on the details of the target platform, such as the communication bandwidth available between the host and the accelerators, and the memory capacities in each component. Here we will give a discussion of considerations for parameterization that we expect to generalize and withstand the test of time. In the present case we have up to N = 8 accelerator devices available in the host.

The following considerations affect the detailed parameterization:

- (1) The host layer should consist of as few levels $d^{(h)}$ as possible since the *N* accelerators with their parallel capacity have far superior aggregate instruction bandwidth and they should shoulder the bulk of the workload. Constraints on decreasing $d^{(h)}$ include the memory capacity at the host for maintaining the arrays T_{ℓ} , S_{ℓ} , Q_{ℓ} associated with each of the *N* host-side accelerator pipelines, as well as the bandwidth of the communication interconnect between the host and the accelerators—large subinstances and their solutions take more time to transfer over the interconnect, but on the other hand take more time to solve on the accelerator, leaving the interconnect idle and thus enabling the hiding of transfer latency. When working with inputs close to the memory capacity of the host as per our engineering goal, the memory capacity at the host is the primary constraint that determines how many levels need to be performed at the host layer.
- (2) The accelerator serial layer in its $d^{(s)}$ levels enables each accelerator to accept larger inputs than would be otherwise possible by resorting to the accelerator parallel layer only. That is, because of limited memory available at the accelerator, the data-expanding/-compressing accelerator parallel layers can only be invoked on input sizes that tolerate a constant-factor expansion in the size of the data at each level, up to the inner layer. The serial layer is more space-efficient by working through the $r_{\ell}^{(s)}$ cases at each level recursively and serially, reusing space, but becomes time-inefficient when the size of a case becomes so small that its parallel processing does not saturate the parallel hardware at the accelerator.
- (3) The accelerator parallel layer should consist of sufficiently many levels $d^{(p)}$ to saturate the parallel hardware of the accelerator and to enable utilization of the optimizations in §3.15.

⁷The latter implemented with instructions that work with four consecutive 32-bit words.

The setting of the parameters $d^{(h)}$, $d^{(s)}$, and $d^{(p)}$ that gives the fastest overall performance may be done by first identifying the memory-capacity-induced constraints on the parameters and then, subject to these constraints, empirically finding the best parameter combination that optimizes performance among the relatively few choices that remain.

For the detailed target platforms considered in what follows, subproblems of shape 65536 × 65536 (512 MiB per matrix) are small enough to be accommodated in the host-side arrays T_{ℓ} , S_{ℓ} , Q_{ℓ} for $\ell \in [N]$ alongside the input arrays. For example, with subproblems of shape 65536 × 65536 = $2^{16} \times 2^{16}$ delegated to the accelerators, an input of shape 1048576 × 1048576 = $2^{20} \times 2^{20}$ (1 Tib; or what is the same, 128 GiB per matrix) will perform $d^{(h)} = 20 - 16 = 4$ levels in the host layer using a $\langle 2, 2, 2 \rangle_7$ -decomposition. On an input of shape 65536 × 65536 = $2^{16} \times 2^{16}$, we parameterize the layers on the accelerators so that each accelerator performs two levels in the accelerator serial layer ($d^{(s)} = 2$) using a $\langle 2, 2, 2 \rangle_7$ -decomposition, and then proceeds with the accelerator parallel layer. That is, the parallel layer is started with inputs of shape 16384 × 16384 = $2^{14} \times 2^{14}$ (32 MiB per matrix).

3.18 Boolean Multiplication

We also provide reference implementations for both Boolean and binary multiplication using the elementary cubic algorithm distributed to the accelerators. For an $s \times t$ by $t \times u$ multiplication to yield an $s \times u$ product, the *N* accelerators each work with subproblems of size $\underline{s} \times \underline{t}$ by $\underline{t} \times \underline{u}$ such that \underline{s} divides s, \underline{t} divides t, and \underline{u} divides u. That is, the total workload of volume stu (in precise terms, stu + s(t-1)u bit operations) gets executed on the accelerators so that each unit of work for an accelerator has volume \underline{stu} . Each accelerator executes a thread array of shape $\frac{\underline{s}}{M} \times \frac{\underline{u}}{M} \times \frac{M \cdot M}{W}$ such that the least significant M^2/W threads are responsible for aggregating one $M \times M$ block of the $\underline{s} \times \underline{u}$ output, with low-level vectorization and vector shuffle operations used for each work unit of volume M^3 . Empirically, $\underline{s} = \underline{t} = \underline{u} = 131072$ and M = 64 give best parameterization for our target hardware with W = 128 and $V = \frac{M \cdot M}{W} = 32$. Coordination at the host is simplified compared with Algorithm 3; namely, we partition the $s \times u$ result matrix to disjoint segments of size $\underline{s} \times \underline{u}$, and set up threads on the host so that a single thread is responsible for each segment, which eliminates the need for synchronization between threads to guard against race conditions. In addition, we set up each host thread so that it integrates each $\underline{s} \times \underline{u}$ subresult it has downloaded from an accelerator in parallel when the next subproblem is being solved on the accelerator; this effectively hides the latency of integrating each subresult because the time to solve each subproblem is greater than the time to integrate the result.

4 EXPERIMENTS

This section describes the experiments we ran to evaluate the performance of the framework described in the previous section. In particular, our goal is to observe that a careful implementation of the framework enables efficient use of current multiple-accelerator systems at input sizes that are close to the host memory capacity of the entire system.

The implementation was written in C++ [16], and the accelerator device routines were written in CUDA C [28]. Hostlevel parallelization was prepared using the OpenMP API [30]. We ran three sets of experiments: (i) alternative-basis binary matrix multiplication, (ii) classical binary matrix multiplication, and (iii) Boolean matrix multiplication.

The single-accelerator version was evaluated at all powers of two until the subproblem size for the multiple-accelerator case. The multiple-accelerator case was evaluated up to one terabinary-bit (1 Tib) input size ($n = 2^{20}$).

4.1 Hardware configuration

The target hardware for our implementation was an NVIDIA DGX-1 system with eight NVIDIA Tesla V100 accelerators, 512 GiB of memory, and 2×20 CPU cores. We also ran experiments on two less powerful configurations: One with

System	CPUs	CPU RAM	GPUs	RAM/GPU
Dell PowerEdge	2×6 -core Xeon	8 × 16 GiB = 128 GiB	4×2 Tesla K80	12 GiB GDDR5
C4130	E5 2620v3 2.50 GHz	DDR4-2133		
	(Haswell)			
Dell PowerEdge	2×12 -core Xeon	16×16 GiB = 256 GiB	4 × Tesla P100	16 GiB HBM2
C4130	E5-2680v3 2.50 GHz	DDR4-2400		
	(Haswell)			
NVIDIA DGX-1	2×20-core Xeon E5-	16×32 GiB = 512 GiB	8 × Tesla V100	16 GiB HBM2
	2698v4 (Broadwell)	DDR4-2133	SXM2	

Table 1. Comparison of the hardware used in our experiments.

Table 2. Peak performance of the GPU accelerators used in our experiments. This presents an upper bound on the number of bit operations that could theoretically be achieved by the hardware.

GPU	#Cores	Boost clock	Peak performance
4 × Tesla K80 [26]	$8 \cdot 2496$	875 MHz	$8 \cdot 2496 \cdot 875 \cdot 10^6 \cdot 32 \approx 5.60 \cdot 10^{14} \text{ bops}$
4 × Tesla P100 [27]	$4 \cdot 3584$	1480 MHz	$4 \cdot 3584 \cdot 1480 \cdot 10^6 \cdot 32 \approx 6.79 \cdot 10^{14} \text{ bops}$
8 × Tesla V100 [29]	$8\cdot 5120$	1530 MHz	$8 \cdot 5120 \cdot 1530 \cdot 10^6 \cdot 32 \approx 2.01 \cdot 10^{15}$ bops

four NVIDIA Tesla P100 accelerators, 256 GiB of memory, and 2×12 CPU cores, and one with four NVIDIA Tesla K80 accelerators, 128 GiB of memory, and 2×6 CPU cores. A more detailed description of the hardware configurations is given in Table 1.

Table 2 lists technical details of the accelerators: the number of cores, boost clock speed, and the peak performance that presents an upper bound on the number of bit operations (bops) that could be theoretically achieved by simultaneous use of all the accelerators in each configuration. In practice, this upper bound is unattainable due to thermal effects and the need to coordinate data across the storage hierarchy ranging from per-thread registers to the global memory of each accelerator. Yet this upper bound presents an uncompromising benchmark against which to measure the performance of the actual implementation.

The power consumption of the systems used in our experiments is listed in Table 3. The table lists the nominal power consumption of the CPUs and GPUs, and the system power intake as indicated in the basic system documentation of each vendor. While one may perhaps expect the CPUs and GPUs to operate essentially at their maximum power, the given system power intake is perhaps expected to be higher than the actual power usage. While we would like to be able to measure the actual energy consumption by each system and its components during the computation more precisely, such instrumentation has been unavailable to us, so in the present experiments we resort to using the tabulated power values as the mean power over the duration of each computation, which then gives us a crude approximation of the energy used by each computation. In particular, we would like to highlight the importance of implementation engineering for low energy consumption as an important goal beyond the present study, with the hope of having in the future available more fine-grained measurement tools.

Finally, to record a rough benchmark of the performance of the different system components in our main target configuration, measurements on the bandwith for transferring data within host memory, and between the accelerator device and the host system are shown in Tables 4 and 5, respectively.

Table 3. Power consumption of the system and the GPUs.

System	CPU watts	GPU watts	System watts
C4130/K80	$2 \times 85 \text{ W}$	$4 \times 300 \text{ W}$	2000 W
C4130/P100	$2 \times 120 \text{ W}$	$4 \times 300 \text{ W}$	2000 W
DGX-1/V100	$2 \times 135 \text{ W}$	$8 \times 300 \text{ W}$	3500 W

Table 4. Measured host-memory bandwiths of the DGX-1 node. The values shown are averages of five consecutive repetitions.

Benchmark	Single core	All cores
Read from linear addresses (consecutive 64-bit words)	9.08 GiB/s	37.28 GiB/s
Write to linear addresses (consecutive 64-bit words)	6.92 GiB/s	19.93 GiB/s
Read from random addresses (individual 64-bit words)	0.17 GiB/s	3.13 GiB/s
Read from random addresses (full cache lines)	0.78 GiB/s	14.09 GiB/s

Table 5. Measured memory bandwiths of transferring data within a single GPU device or between the host and the GPU device. Measurements on the DGX-1 node.

Benchmark	Bandwith
Host to device	10.5 GiB/s
Device to host	11.8 GiB/s
Device to device	704.9 GiB/s

Table 6. Running times for the routine that transposes each of the 64×64 submatrices. The procedure is parallelized and works using 32-bit words as the base data type. All runtimes reported are the median of five repeats on the DGX-1 node.

n	64×64 submatrix transpose time
1024	$1.56 \cdot 10^{-5} \text{ s}$
2048	$3.69 \cdot 10^{-5} s$
4096	$1.23 \cdot 10^{-4} \text{ s}$
8192	$4.63 \cdot 10^{-4} \text{ s}$
16384	$1.84 \cdot 10^{-3} \text{ s}$
32768	$7.45 \cdot 10^{-3} \text{ s}$
65536	$2.98 \cdot 10^{-2} \text{ s}$
131072	$1.29 \cdot 10^{-1} s$
262144	$4.94 \cdot 10^{-1} s$
524288	$2.03 \cdot 10^0$ s
1048576	$7.99 \cdot 10^{0}$ s

4.2 Results

Runtimes, effective bit operations per second, and energy consumption at different sizes of input are shown in Tables 8, 9, 10, 11, and 12. All values shown are medians over five consecutive runs. Since the instrumentation does not permit us to measure the actual power use, two different values are shown for the energy consumption: one is computed assuming full CPU utilization with nominal CPU wattage and the maximum wattage of a single GPU accelerator times the number of GPUs in use, and the other by simply taking the maximum power intake of the entire system in account. We expect the actual energy consumption to lie somewhere between these two values, since the former ignores macroscopic

Table 7. Scalability of running times for the various change-of-basis routines. The forward columns show the running times for the forward transformations (that is, corresponding to ψ and ϕ) whereas the inverse columns show the inverse transformations (corresponding to χ). For the chaining variant, measurements were made to confirm that accounting for transposed data in the right-hand operand has no effect on the running time. The procedures have been crafted using AVX2 intrinsics and to work with 512-bit cache lines on the DGX-1 host hardware. All runtimes reported are the median of five repeats on the DGX-1 node.

n	Forward self-inverse	Inverse self-inverse	Forward chain left	Forward chain right	Inverse chain
1024	$3.28 \cdot 10^{-5}$ s	$3.42 \cdot 10^{-5}$ s	$3.41 \cdot 10^{-5}$ s	$3.44 \cdot 10^{-5}$ s	$3.41 \cdot 10^{-5}$ s
2048	$4.70 \cdot 10^{-5}$ s	$4.88 \cdot 10^{-5} s$	$5.02 \cdot 10^{-5}$ s	$5.13 \cdot 10^{-5}$ s	$5.00 \cdot 10^{-5} s$
4096	$8.10 \cdot 10^{-5} s$	$8.80 \cdot 10^{-5} s$	$9.42 \cdot 10^{-5} \text{ s}$	$9.33 \cdot 10^{-5} s$	$9.35 \cdot 10^{-5} \text{ s}$
8192	$1.80 \cdot 10^{-4} s$	$2.09 \cdot 10^{-4} s$	$2.04 \cdot 10^{-4} s$	$2.07 \cdot 10^{-4} \text{ s}$	$2.05 \cdot 10^{-4} \text{ s}$
16384	$7.15 \cdot 10^{-4} s$	$8.78 \cdot 10^{-4} s$	$8.55 \cdot 10^{-4} s$	$8.68 \cdot 10^{-4} s$	$8.67 \cdot 10^{-4} \text{ s}$
32768	$2.06 \cdot 10^{-2} s$	$2.56 \cdot 10^{-2} s$	$2.59 \cdot 10^{-2} s$	$2.61 \cdot 10^{-2} s$	$2.59 \cdot 10^{-2} \text{ s}$
65536	$9.36 \cdot 10^{-2} s$	$1.20 \cdot 10^{-1} s$	$1.20 \cdot 10^{-1} s$	$1.20 \cdot 10^{-1} s$	$1.20 \cdot 10^{-1} s$
131072	$4.10 \cdot 10^{-1} s$	$5.30 \cdot 10^{-1} \text{ s}$	$5.27 \cdot 10^{-1} \text{ s}$	$5.30 \cdot 10^{-1} s$	$5.26 \cdot 10^{-1} \text{ s}$
262144	$1.81 \cdot 10^0$ s	$2.31 \cdot 10^{0}$ s	$2.31 \cdot 10^0$ s	$2.33 \cdot 10^0$ s	$2.32 \cdot 10^0$ s
524288	$7.82 \cdot 10^0$ s	$1.01 \cdot 10^1$ s	$1.01\cdot 10^1$ s	$1.01\cdot 10^1$ s	$1.01 \cdot 10^1$ s
1048576	$3.45\cdot 10^1$ s	$4.41\cdot 10^1$ s	$4.46\cdot 10^1$ s	$4.46\cdot 10^1$ s	$4.40 \cdot 10^1$ s

factors such as memory and cooling, and the latter is simply the maximum amount of power that the entire system can supply.

In Tables 8 and 9, given runtime *T*, the exact bit operation count of $2n^3 - n^2$ is used to compute $(2n^3 - n^2)/T$, the number of individual bit operations performed in a second on average. The same number is also used in Tables 10, 11, and 12 to compute the *effective* bit operation count; that is, to highlight the relative difference in performance, we show how many elementary bit operations per second a classical implementation operating on individual bits would have to perform to achieve the same wall-clock runtime as the alternative-basis design.

The times reported here do not include the time required for data permutation or change of basis operations at the host; it is assumed that the data is already in the desired format. Table 7 shows the runtime of an implementation of the change of basis with AVX2 vector-intrinsics on the DGX-1 host. It can be seen that, in the case of the best-performing algorithm (with self-inversion), the forward-transformation takes approximately 34.5 seconds per 1-Tib input matrix, and 44.1 seconds for the inverse transformation of the result. The favorable difference is due to the structure of the transformation which means that only 1 of the 4 subarrays needs to be modified at any level of recursion. Also, to preserve linearity of access in memory, we assume that the right-hand-side operand is transposed. For Strassen-like algorithms, this needs to be only done for the 64×64 submatrices; we implemented a parallelized, recursive transpose function using word-operations that can perform the transpose for all 2^{28} submatrices of a 1-TiB input matrix in 7.99 s (median of five consecutive runs, see Table 6 for scalability).

With two 1-Tib input matrices, on the DGX-1, the classical cubic algorithm runs for 1880 and 2110 seconds, and performs over 1.23 and 1.09 peta-bit-operations per second, in the binary and Boolean cases, respectively. This means we are able to achieve over 50 % of the theoretical maximum peak performance of 2.01 Pbops per second. At the assumed level of power used, this means that one such multiplication takes at most 1.83 and 2.05 kWh of electricity, or 2.85 and 3.20 pJ/bop, in the binary and Boolean cases, respectively. In both cases, a single V100 accelerator processes a 131072 × 131072-subproblem in just under 30 seconds, meaning that the runtime obtained here is accelerator-bound. The time required for data upload and download, and result integration of individual subproblems is in the order of seconds, making it negligible in comparison and effectively hidden by the host-side pipeline design.

Due to their limited memory, the P100 and K80 systems can only be evaluated up to n = 524288. However, otherwise the results are very similar to those of the DGX-1, apart from worse energy consumption and slower processing power, owing to the older hardware in use.

As an interesting artifact of the low-level implementation, we see in the Tables 8 and 9 that, with the V100 and P100 accelerators, the Boolean version is slightly slower than the binary version of the algorithm, even though the only differences in code are with the replacement of the popcount-parity check with the nonzero test, and the replacement of XOR with OR. Furthermore, the difference is inverse with the K80 accelerator. This artifact appears to be due to the optimizations performed by the NVIDIA compiler: On the P100 and the V100, the compiler compresses several bitwise operations into one LOP3.LUT instruction, or arbitrary trinary logical instructions, and for one reason or another, the sequence is slightly more efficient in the XOR case. However, these instructions are not available on the K80.

For binary multiplication, the Strassen-Winograd design in standard basis executes in 2610 seconds, the alternative basis with self-inverse in 821 seconds, and the alternative basis with chaining in 972 seconds, on 1-Tib inputs on the DGX-1, and achieve 0.8, 2.8, and 2.3 effective Pbops per second, respectively. The best alternative-basis variant exceeds the theoretical peak hardware performance of the elementary algorithm by more than 30 %. One alternative-basis multiplication takes less than 0.8 kWh of electricity, or less than 1.26 pJ/bop. This is less than one half of that required by the cubic multiplication algorithm. Furthermore, considering that a subproblem of size n = 65536 can be solved by an accelerator in 1.87 seconds, this means that the available host-side bandwidth forms the bottleneck (cf. Tables 4 and 5). Indeed, if subproblem construction and aggregation as well as the data transfer over the PCIe link were completely free, the multiplication could be executed in $\frac{7^4}{8} \times 1.87$ s ≈ 560 s. This in particular highlights the need to carefully engineer workloads and their pipelining both at the host and at the accelerators to obtain balanced overall performance from a multiple-accelerator system. Tables 11 and 12 also show that the present approach generalizes to alternative multiple-accelerator sequires a smaller subproblem size.

ACKNOWLEDGMENTS.

The research leading to these results has received funding from the European Research Council under the European Union's Seventh Framework Programme (FP/2007-2013) / ERC Grant Agreement 338077 "Theory and Practice of Advanced Search and Enumeration". We gratefully acknowledge the use of computational resources provided by the Aalto Science-IT project at Aalto University.

REFERENCES

- V. L. Arlazarov, E. A. Dinic, M. A. Kronrod, and I. A. Faradzhev. 1970. On economical construction of the transitive closure of an oriented graph. Sov. Math., Dokl. 11 (1970), 1209–1210.
- [2] Grey Ballard, James Demmel, Olga Holtz, Benjamin Lipshitz, and Oded Schwartz. 2012. Communication-optimal parallel algorithm for Strassen's matrix multiplication. In 24th ACM Symposium on Parallelism in Algorithms and Architectures, SPAA '12, Pittsburgh, PA, USA, June 25-27, 2012, Guy E. Blelloch and Maurice Herlihy (Eds.). ACM, 193–204. https://doi.org/10.1145/2312005.2312044
- [3] Nikhil Bansal and Ryan Williams. 2012. Regularity Lemmas and Combinatorial Algorithms. Theory of Computing 8, 1 (2012), 69–94. https: //doi.org/10.4086/toc.2012.v008a004
- [4] Austin R. Benson and Grey Ballard. 2015. A framework for practical parallel fast matrix multiplication. In Proceedings of the 20th ACM SIGPLAN Symposium on Principles and Practice of Parallel Programming, PPoPP 2015, San Francisco, CA, USA, February 7-11, 2015, Albert Cohen and David Grove (Eds.). ACM, 42–53. https://doi.org/10.1145/2688500.2688513
- [5] Nader H. Bshouty. 1995. On the Additive Complexity of 2 × 2 Matrix Multiplication. Inf. Process. Lett. 56, 6 (1995), 329–335. https://doi.org/10.1016/ 0020-0190(95)00176-X

Table 8. Scalability of the running times, the bit operations per second, and the energy requirements for the classical (cubic) binary (AND/XOR) multiplication procedure. The subproblem size is 131072 for the V100 (DGX-1) and P100 accelerators, and 65536 for the K80. The number of bit operations is $2n^3 - n^2$. The first two energy columns are computed assuming full usage of CPU Watts and the Wattage of a single GPU times the number GPUs in use. The latter two columns are computed using the full system power intake.

GPU	n	d	Runtime	Bop/s	Energy/bop	Total energy	System en./bop	Total system en.
V100	1024	1	$1.07 \cdot 10^{-4} \text{ s}$	20.22 Tbop/s	132.06 pJ/bop	7.88 · 10 ⁻⁸ kWh	173.12 pJ/bop	$1.04 \cdot 10^{-7}$ kWh
V100	2048	1	$2.15 \cdot 10^{-4} s$	79.94 Tbop/s	33.40 pJ/bop	$1.60 \cdot 10^{-7}$ kWh	43.79 pJ/bop	$2.09 \cdot 10^{-7}$ kWh
V100	4096	1	$1.16 \cdot 10^{-3} s$	118.78 Tbop/s	22.48 pJ/bop	$8.59 \cdot 10^{-7}$ kWh	29.47 pJ/bop	1.13 · 10 ^{−6} kWh
V100	8192	1	$8.28 \cdot 10^{-3} s$	132.83 Tbop/s	20.10 pJ/bop	$6.14 \cdot 10^{-6}$ kWh	26.35 pJ/bop	$8.05 \cdot 10^{-6}$ kWh
V100	16384	1	$5.21 \cdot 10^{-2} \text{ s}$	169.11 Tbop/s	15.79 pJ/bop	$3.86 \cdot 10^{-5}$ kWh	20.70 pJ/bop	$5.06 \cdot 10^{-5}$ kWh
V100	32768	1	$4.09 \cdot 10^{-1} \text{ s}$	172.46 Tbop/s	15.48 pJ/bop	$3.03 \cdot 10^{-4}$ kWh	20.29 pJ/bop	$3.97 \cdot 10^{-4}$ kWh
V100	65536	1	$3.28 \cdot 10^0$ s	171.74 Tbop/s	15.55 pJ/bop	$2.44 \cdot 10^{-3}$ kWh	20.38 pJ/bop	$3.19 \cdot 10^{-3}$ kWh
V100	131072	1	$2.65\cdot 10^1$ s	170.14 Tbop/s	15.69 pJ/bop	$1.97 \cdot 10^{-2}$ kWh	20.57 pJ/bop	$2.58 \cdot 10^{-2}$ kWh
V100	262144	8	$6.76 \cdot 10^1$ s	533.46 Tbop/s	5.01 pJ/bop	$5.01 \cdot 10^{-2}$ kWh	6.56 pJ/bop	$6.57 \cdot 10^{-2}$ kWh
V100	524288	8	$2.40 \cdot 10^2$ s	1204.30 Tbop/s	2.22 pJ/bop	$1.78 \cdot 10^{-1} \text{ kWh}$	2.91 pJ/bop	$2.33 \cdot 10^{-1}$ kWh
V100	1048576	8	$1.88 \cdot 10^3$ s	1230.18 Tbop/s	2.17 pJ/bop	$1.40 \cdot 10^0$ kWh	2.85 pJ/bop	$1.83 \cdot 10^0$ kWh
P100	1024	1	$6.22 \cdot 10^{-5} \text{ s}$	34.56 Tbop/s	41.67 pJ/bop	$2.49 \cdot 10^{-8}$ kWh	57.87 pJ/bop	$3.46 \cdot 10^{-8}$ kWh
P100	2048	1	$2.96 \cdot 10^{-4} s$	58.21 Tbop/s	24.74 pJ/bop	1.19 · 10 ⁻⁷ kWh	34.36 pJ/bop	$1.64 \cdot 10^{-7}$ kWh
P100	4096	1	$1.88 \cdot 10^{-3} s$	73.31 Tbop/s	19.64 pJ/bop	$7.50 \cdot 10^{-7}$ kWh	27.28 pJ/bop	$1.05 \cdot 10^{-6}$ kWh
P100	8192	1	$1.25 \cdot 10^{-2} \text{ s}$	88.56 Tbop/s	16.26 pJ/bop	$4.97 \cdot 10^{-6}$ kWh	22.58 pJ/bop	6.90 · 10 ⁻⁶ kWh
P100	16384	1	$8.64 \cdot 10^{-2} s$	101.90 Tbop/s	14.13 pJ/bop	$3.46 \cdot 10^{-5}$ kWh	19.63 pJ/bop	$4.80 \cdot 10^{-5}$ kWh
P100	32768	1	$6.83 \cdot 10^{-1} s$	103.03 Tbop/s	13.98 pJ/bop	$2.74 \cdot 10^{-4}$ kWh	19.41 pJ/bop	$3.80 \cdot 10^{-4}$ kWh
P100	65536	1	$5.46 \cdot 10^0$ s	103.15 Tbop/s	13.96 pJ/bop	$2.19 \cdot 10^{-3}$ kWh	19.39 pJ/bop	$3.04 \cdot 10^{-3}$ kWh
P100	131072	1	$4.37\cdot 10^1$ s	103.21 Tbop/s	13.95 pJ/bop	$1.75 \cdot 10^{-2}$ kWh	19.38 pJ/bop	$2.43 \cdot 10^{-2}$ kWh
P100	262144	4	$9.57 \cdot 10^1$ s	376.85 Tbop/s	3.82 pJ/bop	$3.83 \cdot 10^{-2}$ kWh	5.31 pJ/bop	$5.32 \cdot 10^{-2}$ kWh
P100	524288	4	$7.24 \cdot 10^2$ s	398.11 Tbop/s	3.62 pJ/bop	$2.90 \cdot 10^{-1}$ kWh	5.02 pJ/bop	$4.03 \cdot 10^{-1}$ kWh
K80	1024	1	$2.27 \cdot 10^{-4} \text{ s}$	9.47 Tbop/s	144.69 pJ/bop	$8.63 \cdot 10^{-8}$ kWh	211.23 pJ/bop	$1.26 \cdot 10^{-7}$ kWh
K80	2048	1	$1.95 \cdot 10^{-3} s$	8.83 Tbop/s	155.16 pJ/bop	$7.41 \cdot 10^{-7}$ kWh	226.50 pJ/bop	1.09 · 10 ^{−6} kWh
K80	4096	1	$9.94 \cdot 10^{-3} \text{ s}$	13.84 Tbop/s	99.01 pJ/bop	$3.78 \cdot 10^{-6}$ kWh	144.54 pJ/bop	$5.52 \cdot 10^{-6}$ kWh
K80	8192	1	$6.44 \cdot 10^{-2} s$	17.09 Tbop/s	80.15 pJ/bop	$2.45 \cdot 10^{-5}$ kWh	117.00 pJ/bop	$3.58 \cdot 10^{-5}$ kWh
K80	16384	1	$4.28 \cdot 10^{-1} \text{ s}$	20.59 Tbop/s	66.52 pJ/bop	$1.63 \cdot 10^{-4}$ kWh	97.11 pJ/bop	$2.38 \cdot 10^{-4}$ kWh
K80	32768	1	$3.43 \cdot 10^0$ s	20.55 Tbop/s	66.68 pJ/bop	$1.31 \cdot 10^{-3}$ kWh	97.34 pJ/bop	$1.91 \cdot 10^{-3}$ kWh
K80	65536	1	$2.86 \cdot 10^1$ s	19.70 Tbop/s	69.54 pJ/bop	$1.09 \cdot 10^{-2}$ kWh	101.52 pJ/bop	$1.59 \cdot 10^{-2}$ kWh
K80	131072	8	$6.34\cdot 10^1$ s	71.11 Tbop/s	19.27 pJ/bop	$2.42 \cdot 10^{-2}$ kWh	28.13 pJ/bop	$3.52 \cdot 10^{-2}$ kWh
K80	262144	8	$2.51 \cdot 10^2$ s	143.73 Tbop/s	9.53 pJ/bop	$9.54 \cdot 10^{-2}$ kWh	13.91 pJ/bop	$1.40 \cdot 10^{-1}$ kWh
K80	524288	8	$1.98\cdot 10^3$ s	146.29 Tbop/s	9.36 pJ/bop	$7.50 \cdot 10^{-1} \text{ kWh}$	13.67 pJ/bop	$1.10 \cdot 10^0$ kWh

- [6] Murat Cenk and M. Anwar Hasan. 2017. On the arithmetic complexity of Strassen-like matrix multiplications. J. Symbolic Comput. 80, part 2 (2017), 484–501. https://doi.org/10.1016/j.jsc.2016.07.004
- [7] Timothy M. Chan. 2015. Speeding up the Four Russians Algorithm by About One More Logarithmic Factor. In Proceedings of the Twenty-Sixth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2015, San Diego, CA, USA, January 4-6, 2015, Piotr Indyk (Ed.). SIAM, 212–217. https://doi.org/10.1137/1.9781611973730.16
- [8] Don Coppersmith and Shmuel Winograd. 1990. Matrix multiplication via arithmetic progressions. J. Symb. Comput. 9, 3 (1990), 251-280. https://doi.org/10.1016/S0747-7171(08)80013-2
- [9] Paolo D'Alberto, Marco Bodrato, and Alexandru Nicolau. 2011. Exploiting parallelism in matrix-computation kernels for symmetric multiprocessor systems: Matrix-multiplication and matrix-addition algorithm optimizations by software pipelining and threads allocation. ACM Trans. Math. Softw. 38, 1 (2011), 2:1–2:30. https://doi.org/10.1145/2049662.2049664
- [10] A. M. Davie and A. J. Stothers. 2013. Improved bound for complexity of matrix multiplication. Proc. R. Soc. Edinb., Sect. A, Math. 143, 2 (2013), 351–369. https://doi.org/10.1017/S0308210511001648
- [11] Michael J. Fischer and Albert R. Meyer. 1971. Boolean Matrix Multiplication and Transitive Closure. In 12th Annual Symposium on Switching and Automata Theory, East Lansing, Michigan, USA, October 13-15, 1971. IEEE Computer Society, 129–131. https://doi.org/10.1109/SWAT.1971.4
- [12] M. E. Furman. 1970. Application of a method of fast multiplication of matrices in the problem of finding the transitive closure of a graph. Sov. Math., Dokl. 11 (1970), 1252.

Table 9. Scalability of the running times, the bit operations per second, and the energy requirements for the classic (cubic) Boolean (AND/OR) multiplication procedure. The subproblem size is 131072 for the V100 (DGX-1) and P100 accelerators, and 65536 for the K80. The number of bit operations is $2n^3 - n^2$. The first two energy columns are computed assuming full usage of CPU Watts and the Wattage of a single GPU times the number GPUs in use. The latter two columns are computed using the full system power intake.

GPU	n	d	Runtime	Bop/s	Energy/bop	Total energy	System en./bop	Total system en.
V100	1024	1	$9.84 \cdot 10^{-5}$ s	21.83 Tbop/s	122.33 pJ/bop	7.30 · 10 ⁻⁸ kWh	160.36 pJ/bop	9.57 · 10 ⁻⁸ kWh
V100	2048	1	$1.93 \cdot 10^{-4} s$	89.25 Tbop/s	29.92 pJ/bop	$1.43 \cdot 10^{-7}$ kWh	39.22 pJ/bop	$1.88 \cdot 10^{-7}$ kWh
V100	4096	1	$1.30 \cdot 10^{-3} \text{ s}$	106.45 Tbop/s	25.08 pJ/bop	$9.58 \cdot 10^{-7}$ kWh	32.88 pJ/bop	1.26 · 10 ⁻⁶ kWh
V100	8192	1	$7.86 \cdot 10^{-3} s$	140.00 Tbop/s	19.07 pJ/bop	$5.83 \cdot 10^{-6}$ kWh	25.00 pJ/bop	7.64 · 10 ⁻⁶ kWh
V100	16384	1	$5.94 \cdot 10^{-2} s$	148.16 Tbop/s	18.02 pJ/bop	$4.41 \cdot 10^{-5}$ kWh	23.62 pJ/bop	$5.78 \cdot 10^{-5} \text{ kWh}$
V100	32768	1	$4.69 \cdot 10^{-1} \text{ s}$	150.33 Tbop/s	17.76 pJ/bop	$3.48 \cdot 10^{-4}$ kWh	23.28 pJ/bop	$4.56 \cdot 10^{-4} \text{ kWh}$
V100	65536	1	$3.73 \cdot 10^0$ s	151.07 Tbop/s	17.67 pJ/bop	$2.77 \cdot 10^{-3}$ kWh	23.17 pJ/bop	$3.63 \cdot 10^{-3} \text{ kWh}$
V100	131072	1	$2.98 \cdot 10^1$ s	151.27 Tbop/s	17.65 pJ/bop	$2.21 \cdot 10^{-2}$ kWh	23.14 pJ/bop	$2.90 \cdot 10^{-2}$ kWh
V100	262144	8	$7.51 \cdot 10^1$ s	479.81 Tbop/s	5.56 pJ/bop	$5.57 \cdot 10^{-2}$ kWh	7.29 pJ/bop	$7.31 \cdot 10^{-2} \text{ kWh}$
V100	524288	8	$2.71 \cdot 10^2$ s	1065.59 Tbop/s	2.51 pJ/bop	$2.01 \cdot 10^{-1}$ kWh	3.28 pJ/bop	$2.63 \cdot 10^{-1}$ kWh
V100	1048576	8	$2.11 \cdot 10^3$ s	1094.98 Tbop/s	2.44 pJ/bop	$1.57 \cdot 10^0$ kWh	3.20 pJ/bop	$2.05 \cdot 10^0$ kWh
P100	1024	1	$5.09 \cdot 10^{-5} s$	42.24 Tbop/s	34.09 pJ/bop	$2.04 \cdot 10^{-8}$ kWh	47.35 pJ/bop	$2.83 \cdot 10^{-8}$ kWh
P100	2048	1	$2.72 \cdot 10^{-4} \text{ s}$	63.35 Tbop/s	22.73 pJ/bop	$1.09 \cdot 10^{-7}$ kWh	31.57 pJ/bop	$1.51 \cdot 10^{-7}$ kWh
P100	4096	1	$1.62 \cdot 10^{-3} \text{ s}$	85.13 Tbop/s	16.91 pJ/bop	$6.46 \cdot 10^{-7}$ kWh	23.49 pJ/bop	$8.97 \cdot 10^{-7}$ kWh
P100	8192	1	$1.16 \cdot 10^{-2} s$	95.10 Tbop/s	15.14 pJ/bop	$4.63 \cdot 10^{-6}$ kWh	21.03 pJ/bop	$6.43 \cdot 10^{-6}$ kWh
P100	16384	1	$8.90 \cdot 10^{-2} s$	98.89 Tbop/s	14.56 pJ/bop	$3.56 \cdot 10^{-5}$ kWh	20.22 pJ/bop	$4.95 \cdot 10^{-5}$ kWh
P100	32768	1	$7.09 \cdot 10^{-1} \text{ s}$	99.29 Tbop/s	14.50 pJ/bop	$2.84 \cdot 10^{-4}$ kWh	20.14 pJ/bop	$3.94 \cdot 10^{-4}$ kWh
P100	65536	1	$5.67 \cdot 10^0$ s	99.40 Tbop/s	14.49 pJ/bop	$2.27 \cdot 10^{-3}$ kWh	20.12 pJ/bop	$3.15 \cdot 10^{-3}$ kWh
P100	131072	1	$4.53\cdot 10^1$ s	99.45 Tbop/s	14.48 pJ/bop	$1.82 \cdot 10^{-2}$ kWh	20.11 pJ/bop	$2.52 \cdot 10^{-2}$ kWh
P100	262144	4	$9.89 \cdot 10^1$ s	364.55 Tbop/s	3.95 pJ/bop	$3.96 \cdot 10^{-2}$ kWh	5.49 pJ/bop	$5.50 \cdot 10^{-2}$ kWh
P100	524288	4	$7.50 \cdot 10^2$ s	384.46 Tbop/s	3.75 pJ/bop	$3.00 \cdot 10^{-1}$ kWh	5.20 pJ/bop	$4.17 \cdot 10^{-1}$ kWh
K80	1024	1	$2.15 \cdot 10^{-4} s$	10.03 Tbop/s	136.60 pJ/bop	$8.15 \cdot 10^{-8}$ kWh	199.41 pJ/bop	1.19 · 10 ⁻⁷ kWh
K80	2048	1	$1.21 \cdot 10^{-3} s$	14.22 Tbop/s	96.35 pJ/bop	$4.60 \cdot 10^{-7}$ kWh	140.66 pJ/bop	$6.72 \cdot 10^{-7}$ kWh
K80	4096	1	$8.08 \cdot 10^{-3} s$	17.02 Tbop/s	80.48 pJ/bop	$3.08 \cdot 10^{-6}$ kWh	117.49 pJ/bop	4.49 · 10 ^{−6} kWh
K80	8192	1	$5.52 \cdot 10^{-2} \text{ s}$	19.92 Tbop/s	68.77 pJ/bop	$2.11 \cdot 10^{-5}$ kWh	100.40 pJ/bop	$3.07 \cdot 10^{-5} \text{ kWh}$
K80	16384	1	$3.26 \cdot 10^{-1} \text{ s}$	27.06 Tbop/s	50.62 pJ/bop	$1.24 \cdot 10^{-4}$ kWh	73.90 pJ/bop	$1.81 \cdot 10^{-4} \text{ kWh}$
K80	32768	1	$2.53 \cdot 10^0$ s	27.82 Tbop/s	49.24 pJ/bop	$9.63 \cdot 10^{-4}$ kWh	71.88 pJ/bop	$1.41 \cdot 10^{-3}$ kWh
K80	65536	1	$2.11 \cdot 10^1$ s	26.72 Tbop/s	51.27 pJ/bop	$8.02 \cdot 10^{-3}$ kWh	74.84 pJ/bop	$1.18 \cdot 10^{-2}$ kWh
K80	131072	8	$4.63\cdot 10^1$ s	97.47 Tbop/s	14.06 pJ/bop	$1.76 \cdot 10^{-2}$ kWh	20.52 pJ/bop	$2.57 \cdot 10^{-2}$ kWh
K80	262144	8	$1.80 \cdot 10^2$ s	200.24 Tbop/s	6.84 pJ/bop	$6.85 \cdot 10^{-2}$ kWh	9.99 pJ/bop	$10.00 \cdot 10^{-2} \text{ kWh}$
K80	524288	8	$1.41\cdot 10^3$ s	205.47 Tbop/s	6.67 pJ/bop	$5.34 \cdot 10^{-1}$ kWh	9.73 pJ/bop	$7.80 \cdot 10^{-1} \text{ kWh}$

- [13] Brian Grayson and Robert A. van de Geijn. 1996. A High Performance Parallel Strassen Implementation. Parallel Processing Letters 6, 1 (1996), 3–12. https://doi.org/10.1142/S0129626496000029
- [14] Jianyu Huang, Leslie Rice, Devin A. Matthews, and Robert A. van de Geijn. 2017. Generating Families of Practical Fast Matrix Multiplication Algorithms. In 2017 IEEE International Parallel and Distributed Processing Symposium, IPDPS 2017, Orlando, FL, USA, May 29 - June 2, 2017. IEEE Computer Society, 656–667. https://doi.org/10.1109/IPDPS.2017.56
- [15] Jianyu Huang, Tyler M. Smith, Greg M. Henry, and Robert A. van de Geijn. 2016. Strassen's algorithm reloaded. In Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis, SC 2016, Salt Lake City, UT, USA, November 13-18, 2016, John West and Cherri M. Pancake (Eds.). IEEE Computer Society, 690–701. https://doi.org/10.1109/SC.2016.58
- [16] International Organization for Standardization. 2017. Programming Languages C++. Standard. ISO/IEC 14882:2017.
- [17] Alon Itai and Michael Rodeh. 1978. Finding a Minimum Circuit in a Graph. SIAM J. Comput. 7, 4 (1978), 413–423. https://doi.org/10.1137/0207033
 [18] Igor Kaporin. 1999. A practical algorithm for faster matrix multiplication. Numer. Linear Algebra Appl. 6, 8 (1999), 687–700. https://doi.org/10.1002/ (SICI)1099-1506(199912)6:8<687::AID-NLA177>3.0.CO;2-I
- [19] Igor Kaporin. 2004. The aggregation and cancellation techniques as a practical tool for faster matrix multiplication. Theoret. Comput. Sci. 315, 2-3 (2004), 469–510. https://doi.org/10.1016/j.tcs.2004.01.004
- [20] Elaye Karstadt and Oded Schwartz. 2017. Matrix Multiplication, a Little Faster. In Proceedings of the 29th ACM Symposium on Parallelism in Algorithms and Architectures, SPAA 2017, Washington DC, USA, July 24-26, 2017, Christian Scheideler and Mohammad Taghi Hajiaghayi (Eds.). ACM, 101–110.

Table 10. Scalability the running times, the effective bit operations per second, and the energy requirements for the standard-basis binary Strassen-Winograd multiplication procedure. The subproblem size is 65536 for the V100 (DGX-1) and P100 accelerators, and 32768 for the K80. The effective number of bit operations is computed with the same value of $2n^3 - n^2$ as in the cubic case to highlight the relative difference in performance. The first two energy columns are computed assuming full usage of CPU Watts and the Wattage of a single GPU times the number GPUs in use. The latter two columns are computed using the full system power intake. The right-hand-side input matrix is assumed to be pre-transposed; the times reported here do not include the transposition of submatrices.

GPU	n	d	Runtime	Effective bop/s	Energy/bop	Total energy	System en./bop	Total system en.
V100	1024	1	$1.67 \cdot 10^{-4} \text{ s}$	12.92 Tbop/s	206.67 pJ/bop	$1.24 \cdot 10^{-7}$ kWh	270.92 pJ/bop	$1.62 \cdot 10^{-7}$ kWh
V100	2048	1	$2.72 \cdot 10^{-4} \mathrm{s}$	63.24 Tbop/s	42.22 pJ/bop	$2.02 \cdot 10^{-7}$ kWh	55.34 pJ/bop	$2.65 \cdot 10^{-7}$ kWh
V100	4096	1	$1.05 \cdot 10^{-3} \text{ s}$	132.07 Tbop/s	20.22 pJ/bop	$7.72 \cdot 10^{-7}$ kWh	26.50 pJ/bop	$1.02 \cdot 10^{-6}$ kWh
V100	8192	1	$5.86 \cdot 10^{-3} s$	187.69 Tbop/s	14.23 pJ/bop	$4.35 \cdot 10^{-6}$ kWh	18.65 pJ/bop	$5.70 \cdot 10^{-6}$ kWh
V100	16384	1	$3.97 \cdot 10^{-2} \text{ s}$	222.03 Tbop/s	12.03 pJ/bop	$2.94 \cdot 10^{-5}$ kWh	15.76 pJ/bop	$3.86 \cdot 10^{-5}$ kWh
V100	32768	1	$2.81 \cdot 10^{-1} \text{ s}$	251.04 Tbop/s	10.64 pJ/bop	$2.08 \cdot 10^{-4}$ kWh	13.94 pJ/bop	$2.73\cdot 10^{-4}$ kWh
V100	65536	1	$1.97\cdot 10^0$ s	285.95 Tbop/s	9.34 pJ/bop	$1.47 \cdot 10^{-3}$ kWh	12.24 pJ/bop	$1.92 \cdot 10^{-3}$ kWh
V100	131072	8	$3.74\cdot 10^0$ s	1205.38 Tbop/s	2.22 pJ/bop	$2.78 \cdot 10^{-3}$ kWh	2.90 pJ/bop	$3.64 \cdot 10^{-3}$ kWh
V100	262144	8	$2.34\cdot 10^1$ s	1543.54 Tbop/s	1.73 pJ/bop	$1.74 \cdot 10^{-2}$ kWh	2.27 pJ/bop	$2.27 \cdot 10^{-2}$ kWh
V100	524288	8	$2.66 \cdot 10^2$ s	1086.54 Tbop/s	2.46 pJ/bop	$1.97 \cdot 10^{-1}$ kWh	3.22 pJ/bop	$2.58 \cdot 10^{-1}$ kWh
V100	1048576	8	$2.61 \cdot 10^3$ s	884.18 Tbop/s	3.02 pJ/bop	$1.94 \cdot 10^0$ kWh	3.96 pJ/bop	$2.54 \cdot 10^0$ kWh
P100	1024	1	$1.39 \cdot 10^{-4} s$	15.54 Tbop/s	92.64 pJ/bop	$5.53 \cdot 10^{-8}$ kWh	128.67 pJ/bop	7.68 · 10 ^{−8} kWh
P100	2048	1	$3.34 \cdot 10^{-4} s$	51.50 Tbop/s	27.96 pJ/bop	$1.34 \cdot 10^{-7}$ kWh	38.84 pJ/bop	1.86 · 10 ⁻⁷ kWh
P100	4096	1	$1.53 \cdot 10^{-3} s$	90.17 Tbop/s	15.97 pJ/bop	$6.10 \cdot 10^{-7}$ kWh	22.18 pJ/bop	$8.47 \cdot 10^{-7}$ kWh
P100	8192	1	$9.12 \cdot 10^{-3} \text{ s}$	120.55 Tbop/s	11.94 pJ/bop	$3.65 \cdot 10^{-6}$ kWh	16.59 pJ/bop	$5.07 \cdot 10^{-6}$ kWh
P100	16384	1	$5.76 \cdot 10^{-2} s$	152.77 Tbop/s	9.43 pJ/bop	$2.31 \cdot 10^{-5}$ kWh	13.09 pJ/bop	$3.20 \cdot 10^{-5}$ kWh
P100	32768	1	$4.08 \cdot 10^{-1} \text{ s}$	172.84 Tbop/s	8.33 pJ/bop	$1.63 \cdot 10^{-4}$ kWh	11.57 pJ/bop	$2.27 \cdot 10^{-4}$ kWh
P100	65536	1	$2.87 \cdot 10^0$ s	196.61 Tbop/s	7.32 pJ/bop	$1.15 \cdot 10^{-3}$ kWh	10.17 pJ/bop	$1.60 \cdot 10^{-3} \text{ kWh}$
P100	131072	4	$7.37 \cdot 10^0$ s	611.79 Tbop/s	2.35 pJ/bop	$2.95 \cdot 10^{-3}$ kWh	3.27 pJ/bop	$4.09 \cdot 10^{-3}$ kWh
P100	262144	4	$4.37 \cdot 10^1$ s	824.68 Tbop/s	1.75 pJ/bop	$1.75 \cdot 10^{-2} \text{ kWh}$	2.43 pJ/bop	$2.43 \cdot 10^{-2}$ kWh
P100	524288	4	$3.02 \cdot 10^2$ s	956.67 Tbop/s	1.51 pJ/bop	$1.21 \cdot 10^{-1}$ kWh	2.09 pJ/bop	$1.68 \cdot 10^{-1}$ kWh
K80	1024	1	$3.07 \cdot 10^{-4} \text{ s}$	7.00 Tbop/s	195.67 pJ/bop	$1.17 \cdot 10^{-7} \text{ kWh}$	285.64 pJ/bop	1.71 · 10 ^{−7} kWh
K80	2048	1	$1.19 \cdot 10^{-3} s$	14.50 Tbop/s	94.47 pJ/bop	$4.51 \cdot 10^{-7} \text{ kWh}$	137.91 pJ/bop	6.58 · 10 ⁻⁷ kWh
K80	4096	1	$6.96 \cdot 10^{-3} s$	19.77 Tbop/s	69.31 pJ/bop	$2.65 \cdot 10^{-6}$ kWh	101.18 pJ/bop	3.87 · 10 ^{−6} kWh
K80	8192	1	$4.08 \cdot 10^{-2} s$	26.99 Tbop/s	50.76 pJ/bop	1.56 · 10 ⁻⁵ kWh	74.10 pJ/bop	$2.27 \cdot 10^{-5}$ kWh
K80	16384	1	$2.35 \cdot 10^{-1} s$	37.44 Tbop/s	36.59 pJ/bop	8.95 · 10 ^{−5} kWh	53.42 pJ/bop	$1.31 \cdot 10^{-4}$ kWh
K80	32768	1	$1.62 \cdot 10^0$ s	43.51 Tbop/s	31.49 pJ/bop	$6.16 \cdot 10^{-4}$ kWh	45.97 pJ/bop	$8.99 \cdot 10^{-4}$ kWh
K80	65536	8	$2.34 \cdot 10^0$ s	241.49 Tbop/s	5.67 pJ/bop	$8.88 \cdot 10^{-4}$ kWh	8.28 pJ/bop	$1.30 \cdot 10^{-3}$ kWh
K80	131072	8	$1.36 \cdot 10^1$ s	331.26 Tbop/s	4.14 pJ/bop	$5.18 \cdot 10^{-3}$ kWh	6.04 pJ/bop	7.56 · 10 ^{−3} kWh
K80	262144	8	$1.33 \cdot 10^2$ s	272.80 Tbop/s	5.02 pJ/bop	$5.03 \cdot 10^{-2}$ kWh	7.33 pJ/bop	$7.34 \cdot 10^{-2}$ kWh
K80	524288	8	$1.60 \cdot 10^{3}$ s	180.20 Tbop/s	7.60 pJ/bop	6.09 · 10 ⁻¹ kWh	11.10 pJ/bop	8.89 · 10 ⁻¹ kWh

https://doi.org/10.1145/3087556.3087579

- [21] Bharat Kumar, Chua-Huang Huang, Rodney W. Johnson, and P. Sadayappan. 1993. A Tensor Product Formulation of Strassen's Matrix Multiplication Algorithm with Memory Reduction. In *The Seventh International Parallel Processing Symposium, Proceedings, Newport Beach, California, USA, April* 13-16, 1993. IEEE Computer Society, 582–588. https://doi.org/10.1109/IPPS.1993.262814
- [22] François Le Gall. 2014. Powers of tensors and fast matrix multiplication. In International Symposium on Symbolic and Algebraic Computation, ISSAC '14, Kobe, Japan, July 23-25, 2014, Katsusuke Nabeshima, Kosaku Nagasaka, Franz Winkler, and Ágnes Szántó (Eds.). ACM, 296–303. https://doi.org/10.1145/2608628.2608664
- [23] Benjamin Lipshitz, Grey Ballard, James Demmel, and Oded Schwartz. 2012. Communication-avoiding parallel Strassen: implementation and performance. In SC Conference on High Performance Computing Networking, Storage and Analysis, SC '12, Salt Lake City, UT, USA - November 11 - 15, 2012, Jeffrey K. Hollingsworth (Ed.). IEEE/ACM, 101. https://doi.org/10.1109/SC.2012.33
- [24] Qingshan Luo and John B. Drake. 1995. A scalable parallel Strassen's matrix multiplication algorithm for distributed-memory computers. In Proceedings of the 1995 ACM symposium on applied computing, SAC'95, Nashville, TN, USA, February 26-28, 1995, Jim Hightower, Ed Deaton, K. M. George, Janice H. Carroll, and Dave Oppenheim (Eds.). ACM, 221–226. https://doi.org/10.1145/315891.315965

Table 11. Scalability the running times, the effective bit operations per second, and the energy requirements for the alternative-basis (with self-inversion) binary multiplication procedure. The subproblem size is 65536 for the V100 (DGX-1) and P100 accelerators, and 32768 for the K80. The effective number of bit operations is computed with the same value of $2n^3 - n^2$ as in the cubic case to highlight the relative difference in performance. The first two energy columns are computed assuming full usage of CPU Watts and the Wattage of a single GPU times the number GPUs in use. The latter two columns are computed using the full system power intake. The right-hand-side input matrix is assumed to be pre-transposed and in the alternate basis; the times reported here do not include the transposition of submatrices or the change of basis.

GPU	n	d	Runtime	Effective bop/s	Energy/bop	Total energy	System en./bop	Total system en.
V100	1024	1	$1.51 \cdot 10^{-4} \text{ s}$	14.26 Tbop/s	187.30 pJ/bop	$1.12 \cdot 10^{-7}$ kWh	245.53 pJ/bop	$1.47 \cdot 10^{-7}$ kWh
V100	2048	1	$2.45 \cdot 10^{-4} \text{ s}$	70.36 Tbop/s	37.95 pJ/bop	$1.82 \cdot 10^{-7}$ kWh	49.74 pJ/bop	$2.38 \cdot 10^{-7}$ kWh
V100	4096	1	$9.97 \cdot 10^{-4} \text{ s}$	137.96 Tbop/s	19.35 pJ/bop	7.39 · 10 ^{−7} kWh	25.37 pJ/bop	9.69 · 10 ^{−7} kWh
V100	8192	1	$5.55 \cdot 10^{-3} \text{ s}$	198.32 Tbop/s	13.46 pJ/bop	$4.12 \cdot 10^{-6}$ kWh	17.65 pJ/bop	$5.39 \cdot 10^{-6}$ kWh
V100	16384	1	$3.76 \cdot 10^{-2} \text{ s}$	234.14 Tbop/s	11.40 pJ/bop	$2.79 \cdot 10^{-5}$ kWh	14.95 pJ/bop	$3.66 \cdot 10^{-5}$ kWh
V100	32768	1	$2.66 \cdot 10^{-1} s$	265.39 Tbop/s	10.06 pJ/bop	$1.97 \cdot 10^{-4}$ kWh	13.19 pJ/bop	$2.58 \cdot 10^{-4}$ kWh
V100	65536	1	$1.87\cdot 10^0$ s	301.77 Tbop/s	8.85 pJ/bop	$1.39 \cdot 10^{-3}$ kWh	11.60 pJ/bop	$1.82 \cdot 10^{-3}$ kWh
V100	131072	8	$3.33 \cdot 10^0$ s	1356.04 Tbop/s	1.97 pJ/bop	$2.47 \cdot 10^{-3}$ kWh	2.58 pJ/bop	$3.23 \cdot 10^{-3}$ kWh
V100	262144	8	$1.83 \cdot 10^1$ s	1970.12 Tbop/s	1.36 pJ/bop	$1.36 \cdot 10^{-2}$ kWh	1.78 pJ/bop	$1.78 \cdot 10^{-2} \text{ kWh}$
V100	524288	8	$1.19 \cdot 10^2$ s	2440.74 Tbop/s	1.09 pJ/bop	$8.76 \cdot 10^{-2}$ kWh	1.43 pJ/bop	$1.15 \cdot 10^{-1}$ kWh
V100	1048576	8	$8.21 \cdot 10^2$ s	2809.41 Tbop/s	0.95 pJ/bop	$6.09 \cdot 10^{-1}$ kWh	1.25 pJ/bop	$7.98 \cdot 10^{-1}$ kWh
P100	1024	1	$1.18 \cdot 10^{-4} s$	18.22 Tbop/s	79.02 pJ/bop	$4.72 \cdot 10^{-8}$ kWh	109.75 pJ/bop	$6.55 \cdot 10^{-8}$ kWh
P100	2048	1	$2.94 \cdot 10^{-4} s$	58.49 Tbop/s	24.62 pJ/bop	$1.18 \cdot 10^{-7}$ kWh	34.19 pJ/bop	$1.64 \cdot 10^{-7}$ kWh
P100	4096	1	$1.38 \cdot 10^{-3} s$	100.27 Tbop/s	14.36 pJ/bop	$5.49 \cdot 10^{-7}$ kWh	19.95 pJ/bop	$7.62 \cdot 10^{-7}$ kWh
P100	8192	1	$8.31 \cdot 10^{-3} s$	132.34 Tbop/s	10.88 pJ/bop	$3.33 \cdot 10^{-6}$ kWh	15.11 pJ/bop	$4.62 \cdot 10^{-6}$ kWh
P100	16384	1	$5.37 \cdot 10^{-2} \text{ s}$	163.82 Tbop/s	8.79 pJ/bop	$2.15 \cdot 10^{-5}$ kWh	12.21 pJ/bop	$2.99 \cdot 10^{-5}$ kWh
P100	32768	1	$3.79 \cdot 10^{-1} s$	185.81 Tbop/s	7.75 pJ/bop	$1.52 \cdot 10^{-4}$ kWh	10.76 pJ/bop	$2.11 \cdot 10^{-4}$ kWh
P100	65536	1	$2.67 \cdot 10^0$ s	211.34 Tbop/s	6.81 pJ/bop	$1.07 \cdot 10^{-3}$ kWh	9.46 pJ/bop	$1.48 \cdot 10^{-3} \text{ kWh}$
P100	131072	4	$7.12 \cdot 10^{0}$ s	633.00 Tbop/s	2.27 pJ/bop	$2.85 \cdot 10^{-3}$ kWh	3.16 pJ/bop	$3.96 \cdot 10^{-3}$ kWh
P100	262144	4	$4.12 \cdot 10^1$ s	876.27 Tbop/s	1.64 pJ/bop	$1.65 \cdot 10^{-2}$ kWh	2.28 pJ/bop	$2.29 \cdot 10^{-2}$ kWh
P100	524288	4	$2.60 \cdot 10^2$ s	1110.41 Tbop/s	1.30 pJ/bop	$1.04 \cdot 10^{-1}$ kWh	1.80 pJ/bop	$1.45 \cdot 10^{-1}$ kWh
K80	1024	1	$2.87 \cdot 10^{-4} \text{ s}$	7.50 Tbop/s	182.63 pJ/bop	1.09 · 10 ⁻⁷ kWh	266.62 pJ/bop	1.59 · 10 ⁻⁷ kWh
K80	2048	1	$1.12 \cdot 10^{-3} \text{ s}$	15.44 Tbop/s	88.74 pJ/bop	$4.24 \cdot 10^{-7}$ kWh	129.54 pJ/bop	6.19 · 10 ⁻⁷ kWh
K80	4096	1	$6.56 \cdot 10^{-3} s$	20.95 Tbop/s	65.38 pJ/bop	$2.50 \cdot 10^{-6}$ kWh	95.45 pJ/bop	$3.65 \cdot 10^{-6} \text{ kWh}$
K80	8192	1	$4.17 \cdot 10^{-2} \text{ s}$	26.40 Tbop/s	51.89 pJ/bop	1.59 · 10 ^{−5} kWh	75.75 pJ/bop	$2.32 \cdot 10^{-5}$ kWh
K80	16384	1	$2.24 \cdot 10^{-1} s$	39.43 Tbop/s	34.75 pJ/bop	8.50 · 10 ⁻⁵ kWh	50.73 pJ/bop	$1.24 \cdot 10^{-4}$ kWh
K80	32768	1	$1.52 \cdot 10^0$ s	46.45 Tbop/s	29.49 pJ/bop	$5.77 \cdot 10^{-4}$ kWh	43.05 pJ/bop	$8.42 \cdot 10^{-4}$ kWh
K80	65536	8	$2.04 \cdot 10^0$ s	276.04 Tbop/s	4.96 pJ/bop	7.77 · 10 ^{−4} kWh	7.25 pJ/bop	1.14 · 10 ^{−3} kWh
K80	131072	8	$1.24 \cdot 10^1$ s	365.09 Tbop/s	3.75 pJ/bop	$4.70 \cdot 10^{-3}$ kWh	5.48 pJ/bop	$6.86 \cdot 10^{-3} \text{ kWh}$
K80	262144	8	$7.79 \cdot 10^1$ s	462.55 Tbop/s	2.96 pJ/bop	$2.97 \cdot 10^{-2}$ kWh	4.32 pJ/bop	$4.33 \cdot 10^{-2}$ kWh
K80	524288	8	$5.64 \cdot 10^2$ s	511.71 Tbop/s	2.68 pJ/bop	$2.15 \cdot 10^{-1}$ kWh	3.91 pJ/bop	$3.13 \cdot 10^{-1}$ kWh

[25] Xinxin Mei and Xiaowen Chu. 2017. Dissecting GPU Memory Hierarchy Through Microbenchmarking. IEEE Trans. Parallel Distrib. Syst. 28, 1 (2017), 72–86. https://doi.org/10.1109/TPDS.2016.2549523

[26] NVIDIA Corporation. 2015. NVIDIA Tesla K80 GPU accelerator board specification. https://www.nvidia.com/content/dam/en-zz/Solutions/ Data-Center/tesla-product-literature/Tesla-K80-BoardSpec-07317-001-v05.pdf (retrieved 2019-01-09).

- [27] NVIDIA Corporation. 2016. NVIDIA Tesla P100 datasheet. https://www.nvidia.com/en-us/data-center/tesla-p100/ (retrieved 2019-01-09).
- [28] NVIDIA Corporation. 2018. CUDA C Programming Guide. https://docs.nvidia.com/cuda/pdf/CUDA_C_Programming_Guide.pdf (retrieved 2018-08-11). PG-02829-001_v9.2.
- [29] NVIDIA Corporation. 2018. NVIDIA Tesla V100 datasheet. https://www.nvidia.com/en-us/data-center/tesla-v100/ (retrieved 2019-01-09).
- [30] OpenMP Architecture Review Board. 2015. OpenMP Application Program Interface. https://www.openmp.org/wp-content/uploads/openmp-4.5.pdf. Version 4.5.
- [31] Victor Pan. 1984. How can we speed up matrix multiplication? SIAM Rev. 26, 3 (1984), 393-415. https://doi.org/10.1137/1026076
- [32] Victor Y. Pan. 1978. Strassen's Algorithm Is not Optimal: Trililnear Technique of Aggregating, Uniting and Canceling for Constructing Fast Algorithms for Matrix Operations. In 19th Annual Symposium on Foundations of Computer Science, Ann Arbor, Michigan, USA, 16-18 October 1978.

Table 12. Scalability the running times, the effective bit operations per second, and the energy requirements for the alternative-basis (with chaining) binary multiplication procedure. The subproblem size is 65536 for the V100 (DGX-1) and P100 accelerators, and 32768 for the K80. The effective number of bit operations is computed with the same value of $2n^3 - n^2$ as in the cubic case to highlight the relative difference in performance. The first two energy columns are computed assuming full usage of CPU Watts and the Wattage of a single GPU times the number GPUs in use. The latter two columns are computed using the full system power intake. The right-hand-side input matrix is assumed to be pre-transposed and in the alternate basis; the times reported here do not include the transposition of submatrices or the change of basis.

GPU	n	d	Runtime	Effective bop/s	Energy/bop	Total energy	System en./bop	Total system en.
V100	1024	1	$1.63 \cdot 10^{-4} \text{ s}$	13.20 Tbop/s	202.35 pJ/bop	$1.21 \cdot 10^{-7}$ kWh	265.25 pJ/bop	$1.59 \cdot 10^{-7}$ kWh
V100	2048	1	$2.53 \cdot 10^{-4} \text{ s}$	68.02 Tbop/s	39.25 pJ/bop	$1.88 \cdot 10^{-7}$ kWh	51.45 pJ/bop	$2.46 \cdot 10^{-7}$ kWh
V100	4096	1	$1.01 \cdot 10^{-3} s$	136.65 Tbop/s	19.54 pJ/bop	$7.46 \cdot 10^{-7}$ kWh	25.61 pJ/bop	9.78 · 10 ^{−7} kWh
V100	8192	1	$5.56 \cdot 10^{-3} s$	197.78 Tbop/s	13.50 pJ/bop	$4.13 \cdot 10^{-6}$ kWh	17.70 pJ/bop	$5.41 \cdot 10^{-6}$ kWh
V100	16384	1	$3.77 \cdot 10^{-2} \text{ s}$	233.70 Tbop/s	11.42 pJ/bop	$2.80 \cdot 10^{-5}$ kWh	14.98 pJ/bop	$3.66 \cdot 10^{-5}$ kWh
V100	32768	1	$2.66 \cdot 10^{-1} s$	265.02 Tbop/s	10.07 pJ/bop	$1.97 \cdot 10^{-4} \text{ kWh}$	13.21 pJ/bop	$2.59 \cdot 10^{-4}$ kWh
V100	65536	1	$1.87\cdot 10^0$ s	301.20 Tbop/s	8.86 pJ/bop	$1.39 \cdot 10^{-3}$ kWh	11.62 pJ/bop	$1.82 \cdot 10^{-3}$ kWh
V100	131072	8	$3.50\cdot 10^0$ s	1287.65 Tbop/s	2.07 pJ/bop	$2.60 \cdot 10^{-3}$ kWh	2.72 pJ/bop	$3.41 \cdot 10^{-3}$ kWh
V100	262144	8	$1.83 \cdot 10^1$ s	1976.47 Tbop/s	1.35 pJ/bop	$1.36 \cdot 10^{-2}$ kWh	1.77 pJ/bop	$1.78 \cdot 10^{-2}$ kWh
V100	524288	8	$1.37\cdot 10^2$ s	2105.28 Tbop/s	1.27 pJ/bop	$1.02 \cdot 10^{-1}$ kWh	1.66 pJ/bop	$1.34 \cdot 10^{-1}$ kWh
V100	1048576	8	$9.72 \cdot 10^2$ s	2374.71 Tbop/s	1.12 pJ/bop	$7.21 \cdot 10^{-1}$ kWh	1.47 pJ/bop	$9.45 \cdot 10^{-1}$ kWh
P100	1024	1	$1.26 \cdot 10^{-4} \text{ s}$	17.17 Tbop/s	83.89 pJ/bop	$5.01 \cdot 10^{-8}$ kWh	116.51 pJ/bop	6.95 · 10 ^{−8} kWh
P100	2048	1	$3.04 \cdot 10^{-4}$ s	56.63 Tbop/s	25.43 pJ/bop	$1.22 \cdot 10^{-7}$ kWh	35.32 pJ/bop	1.69 · 10 ^{−7} kWh
P100	4096	1	$1.38 \cdot 10^{-3} \text{ s}$	99.65 Tbop/s	14.45 pJ/bop	$5.52 \cdot 10^{-7}$ kWh	20.07 pJ/bop	7.67 · 10 ^{−7} kWh
P100	8192	1	$8.38 \cdot 10^{-3} s$	131.30 Tbop/s	10.97 pJ/bop	$3.35 \cdot 10^{-6}$ kWh	15.23 pJ/bop	$4.66\cdot 10^{-6}~\mathrm{kWh}$
P100	16384	1	$5.40 \cdot 10^{-2} \text{ s}$	163.10 Tbop/s	8.83 pJ/bop	$2.16 \cdot 10^{-5}$ kWh	12.26 pJ/bop	$3.00 \cdot 10^{-5}$ kWh
P100	32768	1	$3.82 \cdot 10^{-1} \text{ s}$	184.64 Tbop/s	7.80 pJ/bop	$1.53 \cdot 10^{-4}$ kWh	10.83 pJ/bop	$2.12 \cdot 10^{-4}$ kWh
P100	65536	1	$2.69 \cdot 10^0$ s	210.00 Tbop/s	6.86 pJ/bop	$1.08 \cdot 10^{-3}$ kWh	9.52 pJ/bop	$1.49 \cdot 10^{-3}$ kWh
P100	131072	4	$7.08 \cdot 10^0$ s	636.99 Tbop/s	2.26 pJ/bop	$2.83 \cdot 10^{-3}$ kWh	3.14 pJ/bop	$3.93 \cdot 10^{-3}$ kWh
P100	262144	4	$4.12 \cdot 10^1$ s	875.64 Tbop/s	1.64 pJ/bop	$1.65 \cdot 10^{-2}$ kWh	2.28 pJ/bop	$2.29 \cdot 10^{-2}$ kWh
P100	524288	4	$2.63 \cdot 10^2$ s	1096.61 Tbop/s	1.31 pJ/bop	$1.06 \cdot 10^{-1}$ kWh	1.82 pJ/bop	$1.47 \cdot 10^{-1}$ kWh
K80	1024	1	$2.97 \cdot 10^{-4} \text{ s}$	7.25 Tbop/s	189.02 pJ/bop	$1.13 \cdot 10^{-7}$ kWh	275.94 pJ/bop	1.65 · 10 ^{−7} kWh
K80	2048	1	$1.13 \cdot 10^{-3} \text{ s}$	15.22 Tbop/s	90.03 pJ/bop	$4.30 \cdot 10^{-7}$ kWh	131.43 pJ/bop	$6.28 \cdot 10^{-7}$ kWh
K80	4096	1	$6.70 \cdot 10^{-3} \text{ s}$	20.53 Tbop/s	66.73 pJ/bop	$2.55 \cdot 10^{-6}$ kWh	97.42 pJ/bop	$3.72 \cdot 10^{-6}$ kWh
K80	8192	1	$3.97 \cdot 10^{-2} \text{ s}$	27.71 Tbop/s	49.44 pJ/bop	$1.51 \cdot 10^{-5}$ kWh	72.17 pJ/bop	$2.21 \cdot 10^{-5}$ kWh
K80	16384	1	$2.24 \cdot 10^{-1} \text{ s}$	39.33 Tbop/s	34.84 pJ/bop	$8.52 \cdot 10^{-5}$ kWh	50.86 pJ/bop	$1.25\cdot 10^{-4}$ kWh
K80	32768	1	$1.58\cdot 10^0$ s	44.61 Tbop/s	30.71 pJ/bop	$6.01 \cdot 10^{-4}$ kWh	44.84 pJ/bop	$8.77 \cdot 10^{-4}$ kWh
K80	65536	8	$2.15\cdot 10^0$ s	262.51 Tbop/s	5.22 pJ/bop	$8.17 \cdot 10^{-4}$ kWh	7.62 pJ/bop	$1.20 \cdot 10^{-3}$ kWh
K80	131072	8	$1.31\cdot 10^1$ s	344.31 Tbop/s	3.98 pJ/bop	$4.98 \cdot 10^{-3}$ kWh	5.81 pJ/bop	$7.27 \cdot 10^{-3}$ kWh
K80	262144	8	$8.05 \cdot 10^1$ s	447.61 Tbop/s	3.06 pJ/bop	$3.07 \cdot 10^{-2}$ kWh	4.47 pJ/bop	$4.48 \cdot 10^{-2}$ kWh
K80	524288	8	$6.92 \cdot 10^2$ s	416.80 Tbop/s	3.29 pJ/bop	$2.64 \cdot 10^{-1}$ kWh	4.80 pJ/bop	$3.85 \cdot 10^{-1}$ kWh

IEEE Computer Society, 166-176. https://doi.org/10.1109/SFCS.1978.34

- [33] Victor Y. Pan. 2018. Fast Feasible and Unfeasible Matrix Multiplication. CoRR abs/1804.04102 (2018). arXiv:1804.04102 http://arxiv.org/abs/1804.04102
- [34] Robert L. Probert. 1976. On the Additive Complexity of Matrix Multiplication. SIAM J. Comput. 5, 2 (1976), 187-203. https://doi.org/10.1137/0205016
- [35] V. Strassen. 1969. Gaussian elimination is not optimal. Numer. Math. 13 (1969), 354-356. https://doi.org/10.1007/BF02165411
- [36] Leslie G. Valiant. 1975. General Context-Free Recognition in Less than Cubic Time. J. Comput. Syst. Sci. 10, 2 (1975), 308–315. https://doi.org/10. 1016/S0022-0000(75)80046-8
- [37] Virginia Vassilevska Williams. 2012. Multiplying matrices faster than Coppersmith-Winograd. In Proceedings of the 44th Symposium on Theory of Computing Conference, STOC 2012, New York, NY, USA, May 19 - 22, 2012, Howard J. Karloff and Toniann Pitassi (Eds.). ACM, 887–898. https: //doi.org/10.1145/2213977.2214056
- [38] Virginia Vassilevska Williams and Ryan Williams. 2010. Subcubic Equivalences between Path, Matrix and Triangle Problems. In 51th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2010, October 23-26, 2010, Las Vegas, Nevada, USA. IEEE Computer Society, 645–654. https://doi.org/10.1109/FOCS.2010.67

Table 13. This table presents a best-case comparison between the runtimes of the different algorithms as run on the DGX-1 with 8 GPUs and subproblem size of 131072 for the cubic binary and Boolean algorithms and 65536 for Strassen-like algorithms. The right-hand-side operand is assumed to be pre-transposed and in the desired basis; the change of basis or the transpose of the submatrices is not included in the reported times.

n	Cubic	Boolean	Strassen-Winograd	Altbasis self-inverse	Altbasis chaining
1024	$1.07 \cdot 10^{-4} \text{ s}$	$9.84 \cdot 10^{-5} s$	$1.67 \cdot 10^{-4} \text{ s}$	$1.51 \cdot 10^{-4} \text{ s}$	$1.63 \cdot 10^{-4} \text{ s}$
2048	$2.15 \cdot 10^{-4} s$	$1.93 \cdot 10^{-4} \text{ s}$	$2.72 \cdot 10^{-4} s$	$2.45 \cdot 10^{-4} s$	$2.53 \cdot 10^{-4} \text{ s}$
4096	$1.16 \cdot 10^{-3} s$	$1.30 \cdot 10^{-3} \text{ s}$	$1.05 \cdot 10^{-3} s$	$9.97 \cdot 10^{-4} \text{ s}$	$1.01 \cdot 10^{-3} s$
8192	$8.28 \cdot 10^{-3} s$	$7.86 \cdot 10^{-3} s$	$5.86 \cdot 10^{-3} s$	$5.55 \cdot 10^{-3} s$	$5.56 \cdot 10^{-3} s$
16384	$5.21 \cdot 10^{-2} s$	$5.94 \cdot 10^{-2} s$	$3.97 \cdot 10^{-2} s$	$3.76 \cdot 10^{-2} s$	$3.77 \cdot 10^{-2} \text{ s}$
32768	$4.09 \cdot 10^{-1} s$	$4.69 \cdot 10^{-1} s$	$2.81 \cdot 10^{-1} s$	$2.66 \cdot 10^{-1} s$	$2.66 \cdot 10^{-1} s$
65536	$3.28 \cdot 10^0$ s	$3.73 \cdot 10^0$ s	$1.97 \cdot 10^0$ s	$1.87 \cdot 10^0$ s	$1.87\cdot 10^0$ s
131072	$2.65 \cdot 10^1$ s	$2.98\cdot 10^1$ s	$3.74 \cdot 10^0$ s	$3.33 \cdot 10^0$ s	$3.50\cdot 10^0$ s
262144	$6.76 \cdot 10^1$ s	$7.51 \cdot 10^1$ s	$2.34 \cdot 10^1$ s	$1.83 \cdot 10^1$ s	$1.83 \cdot 10^1$ s
524288	$2.40 \cdot 10^2$ s	$2.71 \cdot 10^2$ s	$2.66 \cdot 10^2$ s	$1.19 \cdot 10^2$ s	$1.37 \cdot 10^2$ s
1048576	$1.88 \cdot 10^3$ s	$2.11 \cdot 10^3$ s	$2.61 \cdot 10^3$ s	$8.21\cdot 10^2 \ s$	$9.72\cdot 10^2$ s

[39] Vasily Volkov. 2016. Understanding Latency Hiding on GPUs. Ph.D. Dissertation. Electrical Engineering and Computer Sciences, University of California at Berkeley. Technical Report No. UCB/EECS-2016-143.

[40] Henry S. Warren. 2013. Hacker's Delight (2nd ed.). Addison-Wesley.

[41] S. Winograd. 1971. On multiplication of 2 × 2 matrices. Linear Algebra Appl. 4 (1971), 381–388. https://doi.org/10.1016/0024-3795(71)90009-7

[42] F. Yates. 1937. The Design and Analysis of Factorial Experiments. Imperial Bureau of Soil Science, Harpenden.

[43] Huacheng Yu. 2018. An improved combinatorial algorithm for Boolean matrix multiplication. Inf. Comput. 261 (2018), 240–247. https://doi.org/10. 1016/j.ic.2018.02.006