

# On-Device Text Image Super Resolution

Dhruval Jain\*

OnDevice AI

Samsung R& D Institute  
Bangalore, India

dhruval.jain@samsung.com

Arun D Prabhu\*

OnDevice AI

Samsung R& D Institute  
Bangalore, India

arun.prabhu@samsung.com

Gopi Ramena

OnDevice AI

Samsung R& D Institute  
Bangalore, India

gopi.ramena@samsung.com

Manoj Goyal

OnDevice AI

Samsung R& D Institute  
Bangalore, India

manoj.goyal@samsung.com

Debi Prasanna Mohanty

OnDevice AI

Samsung R& D Institute  
Bangalore, India

debi.m@samsung.com

Sukumar Moharana

OnDevice AI

Samsung R& D Institute  
Bangalore, India

msukumar@samsung.com

Naresh Purre

OnDevice AI

Samsung R& D Institute  
Bangalore, India

naresh.purre@samsung.com

**Abstract**—Recent research on super-resolution (SR) has witnessed major developments with the advancements of deep convolutional neural networks. There is a need for information extraction from scenic text images or even document images on device, most of which are low-resolution (LR) images. Therefore, SR becomes an essential pre-processing step as Bicubic Upsampling, which is conventionally present in smartphones, performs poorly on LR images. To give the user more control over his privacy, and to reduce the carbon footprint by reducing the overhead of cloud computing and hours of GPU usage, executing SR models on the edge is a necessity in the recent times. There are various challenges in running and optimizing a model on resource-constrained platforms like smartphones. In this paper, we present a novel deep neural network that reconstructs sharper character edges and thus boosts OCR confidence. The proposed architecture not only achieves significant improvement in PSNR over bicubic upsampling on various benchmark datasets but also runs with an average inference time of 11.7 ms per image. We have outperformed state-of-the-art on the Text330 dataset. We also achieve an OCR accuracy of 75.89% on the ICDAR 2015 TextSR dataset, where ground truth has an accuracy of 78.10%.

## I. INTRODUCTION

Compression techniques used by social media platforms significantly reduce the resolution of images adversely affecting the finer details. Due to the large amounts of images being shared over social media today, there is a growing abundance of low resolution (LR) images on smartphones. LR text images thus, pose a challenge for existing text detection and recognition frameworks on device. Moreover, it gets difficult for the user to read the text due to blurry character edges. Hence, super-resolution (SR) of text images is an intuitive solution. SR is a well-studied problem in computer vision and various approaches have been proposed in the literature.

Some very early approaches use interpolation techniques [1]–[3] based on sampling theory. Many previous studies even adopted edge-based [4] techniques and patch-based techniques [5]–[7] to approach the problem. Another study [8] showed good results using sparsity-based methods. Sparse coding assumes any image can be sparsely represented in a transform

domain, which can then be learned through a training mechanism that tries to relate the LR and HR images. Yang et al. [9], [10] introduced another approach by clustering the patch spaces and learning the corresponding functions. Dong et al. [11], [12] proposed SRCNN, the first deep learning-based image SR method. Since then, various CNN model architectures have been studied for image SR in recent years. Extending this further, other studies [13], [14] have also used Residual neural networks [15] for achieving better performances. They employ deeper neural network architectures and show that using skip connections and recursive convolutions improve SR networks by carrying forward the identity information ahead in the network. Mao et al. [16] used encoder-decoder networks and symmetric skip connections to tackle the problem as image restoration. They show that the skip connections help the model in converging faster. Stacked collaborative autoencoders are also studied in [17]. Generative Adversarial Networks (GANs) [18] introduce adversarial loss to generate impressive results in various tasks. SRGAN [19] is the first work to apply GANs to image SR.

The above mentioned SR frameworks have focussed on learning the texture present in the LR image and reproducing it in the predicted HR with refined details. So, they leverage deeper neural networks to learn hierarchical features for preserving the texture. Reconstruction of texture details is of lesser importance in improving OCR confidence than learning sharper character outline edges.

In this paper, we propose a novel text image SR solution that runs on device in real-time. Our proposed network with very less number of parameters produces comparable results with existing state-of-the-art networks on ICDAR 2015 TextSR<sup>1</sup> datasets in terms of OCR accuracy. The feature extraction pipeline pools high-level textual features for finer edge reconstruction. Our model learns upon the bicubic interpolation hence reducing model parameters to a significant extent. It shows significant improvement in text clarity compared to

\* Primary authors

<sup>1</sup><https://projet.liris.cnrs.fr/sr2015/>

## II. RELATED WORK

Earliest works in text image super-resolution include [20] and [21]. Capel et al. [21] proposed the enhancement of text images using multiple-frame SR. They introduced a MAP estimator based on Huber prior and utilized Total Variation for regularization. Extending their work, Nasonov [21] combined Bilateral Total Variation [22] and a penalty function based on bimodal prior that forces the pixel intensities of the reconstructed image to be either close to the background or the foreground (text). However, these methods need many LR observations for effective estimation and were only restricted to  $2\times$  upscaling. Banerjee et al. [23] utilized the tangent field at character edges for reconstructing sharper edges in grayscale document LR images. A Lat et al. [24] improved OCR accuracy by super-resolving document images using SRGAN [19]. Another closely related work, [25] uses deep neural network architectures for Binary Document Image Super-Resolution (BDISR) in Tamil script. These works are only restricted to document images, whereas our method solves a broader problem of text image SR while improving OCR confidence. [19] produces HR image with higher fidelity incorporating finer edge details but has used GANs which are not suitable for a smartphone environment. [26] has proposed MergeNet for enhancing the edges in the HR output from their version of EDSR [27]. Their pipelined architecture has huge memory constraints and can not be run in real-time on device.

C Dong et al. in [28] had trained 11 different variants of SRCNN on the ICDAR2015 TextSR dataset. They used Model combination [29], following "Greedy search strategy [28]" to obtain 14-best model combinations evaluated on peak signal-to-noise ratio (PSNR). The 14-model combination achieves state-of-the-art performance on the test set. More recent works, driven by the powerful capability of deep neural networks, has led to dramatic improvements in SR. Other works in text image SR [30]–[32], have trained deeper neural networks that have shown state-of-the-art performance in image super-resolution like LapSRN [33], VDSR [13] with loss functions tailored for reconstructing sharper letter edges. However, these solutions can not be deployed on the device due to their large number of parameters.

MobiSR [34] introduced hardware optimization to perform efficient image SR on mobile platforms by minimizing processing latency. Their novel scheduler estimates the upscaling difficulty patch-wise and accordingly sends them to model-engines. Model compression techniques like Knowledge Distillation [35], pruning and quantization have been utilized to reduce the inference time of the network. However, they may also result in a significant loss of high-frequency features that further affect the sharpness of reconstructed edges in the HR image. Therefore, we introduce a shallow network that focuses on learning sharper character edges for enhanced readability and faster inference time on device. To the best of our knowledge, we are the first to perform text image SR on device.

Mean Squared Error (MSE) loss tends to induce smoothness in the reconstructed HR image which results in blurry edges. H Zhang et al. [31] have trained VDSR [13] with the proposed edge-based Weighted Mean Squared error (WMSE) loss. The weight at any pixel is the value of some function  $f$  of the gradient magnitude at that pixel, where  $f$  is any monotonously increasing function. This has shown a slight improvement in OCR confidence on ICDAR 2015 TextSR test set. In our initial experiments, we tried to add edge information using different loss functions [31], [32], [36]. We found that shallower models are unable to reflect this impact in the reconstructed HR image. Our architecture is based on residual learning and thus, it learns the residual between bicubic interpolated HR and the ground truth. Various components of the model are described in detail as follows:

### A. Feature Extraction

Pre-upsampling SR networks like SRCNN [37], DRRN [38], DRCN [14] extract a set of features from bicubic interpolated LR image. A couple of convolution layers are then leveraged to perform non-linear mapping of the extracted feature maps and reconstruct the HR image. Text images suffer a significant loss in edge information due to blurring and noise amplification resulted from bicubic upsampling (Fig. 2). Reconstructing HR from the feature maps extracted from the upsampled bicubic text image does not produce expected results. Moreover, it also increases the space and time complexity as the operations are performed in the high dimensional space. So, we adopt the post-upsampling SR approach [27], [39] as shown in the Fig. 1. High frequency detailing like sharper edge transitions between text and the background is crucial for enhanced readability. For faster inference on device, we convert the RGB input to  $YCbCr$  space and only Y channel is fed to the network for training.

We use four CNN layers having 32, 24, 16, 8 filters respectively each with kernel size  $3\times 3$  to extract features from the LR input image. All the feature maps except the third layer are concatenated via skip connections to generate a total of 64 feature maps. Though, skip connections were introduced to eliminate the vanishing gradient problem in very deep neural networks. [39] has shown improved results over SRCNN, VDSR, and DRCN using dense skip connections. [40] also used skip connections in their feature extraction pipeline to extract both local and global features. Decreasing order of filters and skip connections from the outputs of initial layers ensure that high-frequency features are well incorporated. Our idea behind pooling features from initial layers is to add more emphasis on broad edges that outline the character boundaries in text images. Our shallow model has only **57K** parameters.

Additionally, we have also extracted features from Sobel edge maps of the input LR using a convolution layer having 16 filters and a kernel size of  $3\times 3$  as shown in Fig. 1. Edge feature maps are then concatenated with the existing ones. This helps in emphasizing weaker edges and in turn, fills the fine




Fig. 1: Architecture

broken edges in the reconstructed HR edge map. It has also led to a slight improvement in metrics as shown in TABLE II.

### B. Upsampling Layer

The generated feature maps are further passed to two convolution layers having 32 and  $s^2$  filters respectively, where  $s$  is the scale of resolution. Assuming input images shape is  $h \times w$ , the resultant input to the pixel shuffler layer is  $h \times w \times s^2$ . The reshaping operation is performed through pixel shuffle [41] generates the final HR image of the Y-channel input LR having the shape  $hs \times ws$ .

### C. Loss Function

Bicubic upsampled  $C_b$  and  $C_r$  channels of input LR are appended to the reconstructed Y channel. This is the residual HR image. Now, bicubic upsampled input LR image is added to it to form reconstructed HR image. Loss function is L2, which measures the mean squared pixel-wise difference between the ground truth and the reconstructed HR image.

## IV. EXPERIMENTS

### A. Experimental Setup

For all the experiments, we used Synth90k [42] dataset as the training data. It consists of 93K images. The color images were converted to  $YC_bC_r$  and only Y-channel is processed. LR images are created by downsizing the images using bicubic kernel at both scales ( $2\times$  and  $4\times$ ).  $16\times 16$  patches were generated and 20 patches are used as a mini-batch to train the model. This is the only pre-processing step.

We implemented the proposed architectures in the Tensorflow framework and all of the experiments were conducted on a GeForce GTX 1080ti GPU. We have used Adam [43] optimizer with momentum term 0.9. The initial learning rate is  $2e-3$  and it is halved after every epoch. Training is stopped once the learning rate reaches  $2e-5$ .

### B. Evaluation

We have examined the quality of character outline-edges in the reconstructed HR images, by passing canny edge maps of the text LR image as input to the model. Fig. 2 shows the sharpness of reconstructed edge maps with a scale of  $4\times$ . The performance is extensively evaluated on eight popular benchmark datasets to cover various scenarios of scenic text. TABLE II draws a comparison between bicubic upsampling and our approach using the obtained PSNR and SSIM metrics for scale 2 and scale 4. These metrics have been calculated on the entire dataset, not just the on test set. These are listed as : ICDAR 2015 TextSR, ICDAR 2003 (IC03) [44], ICDAR 2013 (IC13) [45], ICDAR 2015 (IC15) [46], SVT [47], IIT5K [48], CUTE80 [49], MLT<sup>2</sup>.

HTM Tran et al. [30] have trained LapSRN [33] with Gradient Difference Loss [36]. They have proposed a new dataset Text330<sup>3</sup> which contains plain text document images. Apart from scenic text images, our model also performs well on document images. This is illustrated in TABLE I. Fig.3 demonstrates sharper character edges in the reconstructed HR images from the Text330 test set as compared to bicubic upsampling. The given results confirm enhanced readability.

SRCNN [37] is a three layer network having basic configuration  $f_1 = 9, f_2 = 1, f_3 = 5, n_1 = 64, n_2 = 32, n_3 = 1$ . It can be denoted as 64(9)-32(1)-1(5). 14-model combination [28] proposed by C Dong et al. achieved a PSNR of around 33 dB. Their best single model 64(9)-32(7)-16(5)-1(5) with 116,382 parameters achieved a PSNR of 31.99 dB. However, our model with 57,564 parameters achieves a PSNR of 31.38 dB on the same test. We also achieve an OCR accuracy of **75.89%** on the same dataset using Tesseract<sup>4</sup>, whereas the

<sup>2</sup><https://trc.cvc.uab.es/?ch=15>

<sup>3</sup>[https://github.com/t2mhanh/LapSRN\\_TextImages\\_git](https://github.com/t2mhanh/LapSRN_TextImages_git)

<sup>4</sup>Tesseract version 3.02,<http://code.google.com/p/tesseract-ocr>




Fig. 2: Canny edge map reconstruction

TABLE I: Evaluation on Test330 dataset

| Method             | Scale | PSNR         | SSIM         |
|--------------------|-------|--------------|--------------|
| Bicubic            | 2     | 21.82        | 0.869        |
| LapSRN [33]        | 2     | 26.65        | 0.954        |
| LapSRN L1-GDL [30] | 2     | 30.10        | 0.997        |
| Ours               | 2     | <b>31.06</b> | <b>0.997</b> |
| Bicubic            | 4     | 18.21        | 0.692        |
| LapSRN [33]        | 4     | 19.64        | 0.796        |
| LapSRN L1-GDL [30] | 4     | 21.62        | 0.875        |
| Ours               | 4     | <b>21.94</b> | <b>0.883</b> |

original high-resolution images give **78.10%** OCR accuracy. Fig. 4 and Fig. 5 show our result on LR images with different resolutions at  $2\times$  and  $4\times$  scales respectively. Our solution runs on the Samsung Galaxy S10 device with an average inference time of **11.7** milliseconds per image.

## V. CONCLUSION

In this work, we have addressed the problem of enhancing text clarity in LR images, which is very common in mobile devices, and optimized our network for running on the edge. To the best of our knowledge, there are not many works trying to solve the problem of text readability with SR methods on device. Our evaluation on PSNR, SSIM, on-device inference time and OCR accuracy shows that we have gained significant improvement compared to the existing Bicubic upsampling. We have also shown impressive results on document images. Unlike previous SR solutions, our proposed method focuses on SR of the text present in the image, rather than background or texture. This makes our model the very first lightweight model that is capable of text image SR in real-time on device.

## REFERENCES

- [1] J. Allebach and P. W. Wong, "Edge-directed interpolation," in *Proceedings of 3rd IEEE International Conference on Image Processing*, vol. 3. IEEE, 1996, pp. 707–710.
- [2] X. Li and M. T. Orchard, "New edge-directed interpolation," *IEEE transactions on image processing*, vol. 10, no. 10, pp. 1521–1527, 2001.
- [3] L. Zhang and X. Wu, "An edge-guided image interpolation algorithm via directional filtering and data fusion," *IEEE transactions on Image Processing*, vol. 15, no. 8, pp. 2226–2238, 2006.
- [4] J. Sun, Z. Xu, and H.-Y. Shum, "Gradient profile prior and its applications in image super-resolution and enhancement," *IEEE Transactions on Image Processing*, vol. 20, no. 6, pp. 1529–1542, 2010.
- [5] H. Chang, D.-Y. Yeung, and Y. Xiong, "Super-resolution through neighbor embedding," in *Proceedings of the 2004 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2004. CVPR 2004.*, vol. 1. IEEE, 2004, pp. 1–I.
- [6] X. Gao, K. Zhang, D. Tao, and X. Li, "Image super-resolution with sparse neighbor embedding," *IEEE Transactions on Image Processing*, vol. 21, no. 7, pp. 3194–3205, 2012.
- [7] Y. Zhu, Y. Zhang, and A. L. Yuille, "Single image super-resolution using deformable patches," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2014, pp. 2917–2924.
- [8] J. Yang, J. Wright, T. Huang, and Y. Ma, "Image super-resolution as sparse representation of raw image patches," in *2008 IEEE conference on computer vision and pattern recognition*. IEEE, 2008, pp. 1–8.
- [9] J. Yang, Z. Lin, and S. Cohen, "Fast image super-resolution based on in-place example regression," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2013, pp. 1059–1066.
- [10] J. Yang, Z. Wang, Z. Lin, S. Cohen, and T. Huang, "Coupled dictionary training for image super-resolution," *IEEE transactions on image processing*, vol. 21, no. 8, pp. 3467–3478, 2012.
- [11] C. Dong, C. C. Loy, K. He, and X. Tang, "Learning a deep convolutional network for image super-resolution," in *European conference on computer vision*. Springer, 2014, pp. 184–199.
- [12] C. Dong, C. C. Loy, and X. Tang, "Accelerating the super-resolution convolutional neural network," in *European conference on computer vision*. Springer, 2016, pp. 391–407.
- [13] J. Kim, J. Kwon Lee, and K. Mu Lee, "Accurate image super-resolution using very deep convolutional networks," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016, pp. 1646–1654.
- [14] —, "Deeply-recursive convolutional network for image super-resolution," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016, pp. 1637–1645.
- [15] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016, pp. 770–778.

TABLE II: Evaluation on various benchmark datasets

| Method                   | Scale | Metrics | Datasets |        |        |        |        |        |        |        |
|--------------------------|-------|---------|----------|--------|--------|--------|--------|--------|--------|--------|
|                          |       |         | TextSR   | IC13   | IC15   | IC03   | SVT    | IIIT5K | CUTE80 | MLT    |
| Bicubic                  | 2     | PSNR    | 23.50    | 31.91  | 30.58  | 27.57  | 36.60  | 23.78  | 34.2   | 36.55  |
|                          |       | SSIM    | 0.879    | 0.9017 | 0.8983 | 0.8588 | 0.9570 | 0.8087 | 0.9351 | 0.9579 |
| Ours                     | 2     | PSNR    | 31.38    | 37.12  | 35.16  | 33.37  | 40.83  | 29.25  | 39.5   | 42.76  |
|                          |       | SSIM    | 0.9784   | 0.9432 | 0.9065 | 0.9083 | 0.9761 | 0.8872 | 0.9639 | 0.9846 |
| Ours (w/o edge features) | 2     | PSNR    | 31.32    | 37.05  | 35.12  | 33.33  | 40.75  | 29.2   | 39.46  | 42.64  |
|                          |       | SSIM    | 0.9712   | 0.9407 | 0.9058 | 0.9078 | 0.9740 | 0.8865 | 0.9617 | 0.9837 |
| Bicubic                  | 4     | PSNR    | -        | 25.49  | 24.02  | 21.97  | 28.11  | 18.49  | 28.85  | 29.16  |
|                          |       | SSIM    | -        | 0.6902 | 0.5949 | 0.5913 | 0.7697 | 0.5936 | 0.8431 | 0.8438 |
| Ours                     | 4     | PSNR    | -        | 29.94  | 26.47  | 26.39  | 32.05  | 21.22  | 33.49  | 36.63  |
|                          |       | SSIM    | -        | 0.7922 | 0.6205 | 0.6823 | 0.8467 | 0.6878 | 0.9046 | 0.9507 |
| Ours (w/o edge features) | 4     | PSNR    | -        | 29.88  | 26.43  | 26.32  | 31.99  | 21.19  | 33.45  | 36.55  |
|                          |       | SSIM    | -        | 0.7880 | 0.6185 | 0.6788 | 0.8467 | 0.6865 | 0.9001 | 0.9484 |



Fig. 3: Our results on Test330 dataset

[16] X. Mao, C. Shen, and Y.-B. Yang, “Image restoration using very deep convolutional encoder-decoder networks with symmetric skip connec-

tions,” in *Advances in neural information processing systems*, 2016, pp. 2802–2810.

BANANE

BANANE

BANANE

maison

maison

maison

JOURNAL

JOURNAL

JOURNAL

JIMMY'S HALL

JIMMY'S HALL

JIMMY'S HALL

Alsace

Alsace

Alsace

LIVE

LIVE

LIVE

(a) Bicubic

(b) Our result

(c) Ground Truth

Fig. 4: Our results on scale 2

JOINT

JOINT

JOINT

Philips

Philips

Philips

SUB

SUB

SUB

GALLERY

GALLERY

GALLERY

(a) Bicubic

(b) Our result

(c) Ground Truth

Fig. 5: Our results on scale 4

- [17] Z. Cui, H. Chang, S. Shan, B. Zhong, and X. Chen, "Deep network cascade for image super-resolution," in *European Conference on Computer Vision*. Springer, 2014, pp. 49–64.
- [18] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio, "Generative adversarial nets," in *Advances in neural information processing systems*, 2014, pp. 2672–2680.
- [19] C. Ledig, L. Theis, F. Huszár, J. Caballero, A. Cunningham, A. Acosta, A. Aitken, A. Tejani, J. Totz, Z. Wang *et al.*, "Photo-realistic single image super-resolution using a generative adversarial network," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2017, pp. 4681–4690.
- [20] D. Capel and A. Zisserman, "Super-resolution enhancement of text image sequences," in *Proceedings 15th International Conference on Pattern Recognition. ICPR-2000*, vol. 1. IEEE, 2000, pp. 600–605.
- [21] A. V. Nasonov and A. S. Krylov, "Text images superresolution and enhancement," in *2012 5th International Congress on Image and Signal Processing*. IEEE, 2012, pp. 617–620.
- [22] S. Farsiu, M. D. Robinson, M. Elad, and P. Milanfar, "Fast and robust multiframe super resolution," *IEEE transactions on image processing*, vol. 13, no. 10, pp. 1327–1344, 2004.
- [23] J. Banerjee and C. Jawahar, "Super-resolution of text images using edge-directed tangent field," in *2008 The Eighth IAPR International Workshop on Document Analysis Systems*. IEEE, 2008, pp. 76–83.
- [24] A. Lat and C. Jawahar, "Enhancing ocr accuracy with super resolution," in *2018 24th International Conference on Pattern Recognition (ICPR)*. IEEE, 2018, pp. 3162–3167.
- [25] R. K. Pandey, K. Vignesh, A. Ramakrishnan *et al.*, "Binary document image super resolution for improved readability and ocr performance," *arXiv preprint arXiv:1812.02475*, 2018.
- [26] C. Wang, Y. Liu, X. Bai, W. Tang, P. Lei, and J. Zhou, "Deep residual convolutional neural network for hyperspectral image super-resolution," in *International Conference on Image and Graphics*. Springer, 2017, pp. 370–380.
- [27] B. Lim, S. Son, H. Kim, S. Nah, and K. Mu Lee, "Enhanced deep residual networks for single image super-resolution," in *Proceedings of the IEEE conference on computer vision and pattern recognition workshops*, 2017, pp. 136–144.
- [28] C. Dong, X. Zhu, Y. Deng, C. C. Loy, and Y. Qiao, "Boosting optical character recognition: A super-resolution approach," *arXiv preprint arXiv:1506.02211*, 2015.
- [29] W. Ouyang, P. Luo, X. Zeng, S. Qiu, Y. Tian, H. Li, S. Yang, Z. Wang, Y. Xiong, C. Qian *et al.*, "Deepid-net: multi-stage and deformable deep convolutional neural networks for object detection," *arXiv preprint arXiv:1409.3505*, 2014.
- [30] H. T. Tran and T. Ho-Phuoc, "Deep laplacian pyramid network for text images super-resolution," in *2019 IEEE-RIVF International Conference on Computing and Communication Technologies (RIVF)*. IEEE, 2019, pp. 1–6.
- [31] H. Zhang, D. Liu, and Z. Xiong, "Cnn-based text image super-resolution tailored for ocr," in *2017 IEEE Visual Communications and Image Processing (VCIP)*. IEEE, 2017, pp. 1–4.
- [32] G. Seif and D. Androutsos, "Edge-based loss function for single image super-resolution," in *2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2018, pp. 1468–1472.
- [33] W.-S. Lai, J.-B. Huang, N. Ahuja, and M.-H. Yang, "Deep laplacian pyramid networks for fast and accurate super-resolution," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2017, pp. 624–632.
- [34] R. Lee, S. I. Venieris, L. Dudziak, S. Bhattacharya, and N. D. Lane, "Mobisr: Efficient on-device super-resolution through heterogeneous mobile processors," in *The 25th Annual International Conference on Mobile Computing and Networking*, 2019, pp. 1–16.
- [35] Q. Gao, Y. Zhao, G. Li, and T. Tong, "Image super-resolution using knowledge distillation," in *Asian Conference on Computer Vision*. Springer, 2018, pp. 527–541.
- [36] M. Mathieu, C. Couprie, and Y. LeCun, "Deep multi-scale video prediction beyond mean square error," *arXiv preprint arXiv:1511.05440*, 2015.
- [37] C. Dong, C. C. Loy, K. He, and X. Tang, "Image super-resolution using deep convolutional networks," *IEEE transactions on pattern analysis and machine intelligence*, vol. 38, no. 2, pp. 295–307, 2015.
- [38] Y. Tai, J. Yang, and X. Liu, "Image super-resolution via deep recursive residual network," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2017, pp. 3147–3155.
- [39] T. Tong, G. Li, X. Liu, and Q. Gao, "Image super-resolution using dense skip connections," in *Proceedings of the IEEE International Conference on Computer Vision*, 2017, pp. 4799–4807.
- [40] J. Yamanaka, S. Kuwashima, and T. Kurita, "Fast and accurate image super resolution by deep cnn with skip connection and network in network," in *International Conference on Neural Information Processing*. Springer, 2017, pp. 217–225.
- [41] A. Aitken, C. Ledig, L. Theis, J. Caballero, Z. Wang, and W. Shi, "Checkerboard artifact free sub-pixel convolution: A note on sub-pixel convolution, resize convolution and convolution resize," *arXiv preprint arXiv:1707.02937*, 2017.
- [42] M. Jaderberg, K. Simonyan, A. Vedaldi, and A. Zisserman, "Synthetic data and artificial neural networks for natural scene text recognition," in *Workshop on Deep Learning, NIPS*, 2014.
- [43] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," *arXiv preprint arXiv:1412.6980*, 2014.
- [44] S. M. Lucas, A. Panaretos, L. Sosa, A. Tang, S. Wong, R. Young, K. Ashida, H. Nagai, M. Okamoto, H. Yamamoto *et al.*, "Icdar 2003 robust reading competitions: entries, results, and future directions," *International Journal of Document Analysis and Recognition (IJDAR)*, vol. 7, no. 2-3, pp. 105–122, 2005.
- [45] D. Karatzas, F. Shafait, S. Uchida, M. Iwamura, L. G. i Bigorda, S. R. Mestre, J. Mas, D. F. Mota, J. A. Almazan, and L. P. De Las Heras, "Icdar 2013 robust reading competition," in *2013 12th International Conference on Document Analysis and Recognition*. IEEE, 2013, pp. 1484–1493.
- [46] D. Karatzas, L. Gomez-Bigorda, A. Nicolaou, S. Ghosh, A. Bagdanov, M. Iwamura, J. Matas, L. Neumann, V. R. Chandrasekhar, S. Lu *et al.*, "Icdar 2015 competition on robust reading," in *2015 13th International Conference on Document Analysis and Recognition (ICDAR)*. IEEE, 2015, pp. 1156–1160.
- [47] K. Wang, B. Babenko, and S. Belongie, "End-to-end scene text recognition," in *2011 International Conference on Computer Vision*. IEEE, 2011, pp. 1457–1464.
- [48] A. Mishra, K. Alahari, and C. V. Jawahar, "Scene text recognition using higher order language priors," in *BMVC*, 2012.
- [49] A. Risnumawan, P. Shivakumara, C. S. Chan, and C. L. Tan, "A robust arbitrary text detection system for natural scene images," *Expert Systems with Applications*, vol. 41, no. 18, pp. 8027–8048, 2014.