

# Encoding and Decoding Construction D' Lattices for Power-Constrained Communications

Fan Zhou\*, Arini Fitri\*\*, Khoirul Anwar\*\*, and Brian M. Kurkoski\*

\*School of Information Science, Japan Advanced Institute of Science and Technology

\*\*The University Center of Excellence for AICOMS, Telkom University

**Abstract**—This paper focuses on the encoding and decoding of Construction D' coding lattices that can be used with shaping lattices for power-constrained channels. Two encoding methods and a decoding algorithm for Construction D' lattices are given. A design of quasi-cyclic low-density parity-check (QC-LDPC) codes to form Construction D' lattices is presented. This allows construction of nested lattice codes which are good for coding, good for shaping, and have low complexity encoding and decoding. Numerical results of using  $E_8$ ,  $BW_{16}$  and Leech lattices for shaping a Construction D' lattice indicate that the shaping gains 0.65 dB, 0.86 dB and 1.03 dB are preserved, respectively.

## I. INTRODUCTION

Lattices are a natural fit for wireless communications because they provide reliable transmission using real-valued algebra and higher transmit power efficiency than conventional constellations. Lattices also form an important component of compute-and-forward relaying [1], which provides high throughput and high spectral efficiency. For power-constrained communications, nested lattice codes constructed by a coding lattice  $\Lambda_c$  and a shaping lattice  $\Lambda_s$  can achieve the additive white Gaussian noise (AWGN) channel capacity [2], if  $\Lambda_c$  is *channel-good* and the Voronoi region of  $\Lambda_s$  is hyperspherical, using dithering and minimum mean-square error (MMSE) scaling techniques. The shaping gain measures the power reduction, with a 1.53 dB theoretic limit. The well-known  $E_8$  lattice was employed for shaping Construction D lattices [3]. Lattices have also been used for shaping in [4]–[8], but never been used for shaping Construction D' lattices.

LDPC codes have been implemented in a wide variety of applications because of their capacity-achievability, efficient encoding, low-complexity decoding, and suitability for hardware implementation. For these reasons, LDPC codes are also suitable for constructing lattices. Recently Branco da Silva and Silva [9] proposed efficient encoding and decoding for Construction D' lattices, particularly for LDPC codes. A codeword and cosets of component linear codes are used to form systematic codewords for Construction D' lattices. This encoding method naturally produces lattice points in a hypercube.

However, hypercube does not provide shaping gain. A shaping lattice  $\Lambda_s$  is needed to do so. Let  $\mathbf{G}$  and  $\mathbf{G}_s$  be the generator matrix of  $\Lambda_c$  and  $\Lambda_s$ , respectively. The check matrix

of  $\Lambda_c$  is  $\mathbf{H} = \mathbf{G}^{-1}$ . To build a nested lattice code,  $\Lambda_s \subseteq \Lambda_c$  must be satisfied [10, p. 179]; this holds *iff*  $\mathbf{H} \cdot \mathbf{G}_s \in \mathbb{Z}^n$  [11, Lemma 1]. To perform shaping, the mapping from an integer vector  $\mathbf{b}$  to a lattice point  $\mathbf{x}'$  denoted  $\mathbf{x}' = \mathbf{G}\mathbf{b} - Q_{\Lambda_s}(\mathbf{G}\mathbf{b})$  [11, eq. (21)] for a shaping lattice quantizer  $Q_{\Lambda_s}$ , can be achieved as long as the integers  $b_i \in \{0, 1, \dots, M_i - 1\}$  are selected with  $M_i$  related to the diagonal elements of  $\mathbf{H}$  and  $\mathbf{G}_s$ . However, the encoding and decoding method in [9] cannot be applied to non-hypercubic shaping.

To tackle the above problem, the main contributions of this paper are as follows. We provide a definition of Construction D' using check-matrix perspective, which is equivalent to the congruences perspective [12]. We propose two encoding methods and a decoding algorithm for Construction D' suitable for power-constrained channels. *Encoding method A* encodes integers with an approximate lower triangular (ALT) check matrix. *Encoding method B* shows how binary information bits are mapped to a lattice point using the check matrices of the underlying nested linear codes of a Construction D' lattice. We present a multistage successive cancellation decoding algorithm employing binary decoders. The *re-encoding* mapping an estimated binary codeword to a lattice point is required during decoding, and this is consistent with encoding method B; these methods are distinct from [9].

Motivated by [13], we also construct QC-LDPC codes to form Construction D' lattices (termed LDPC code lattices), because QC-LDPC codes are widely used in recent wireless communication standards. A design of QC-LDPC code  $\mathcal{C}_0$  with a parity-check matrix  $\mathbf{H}_0$  is presented, where the position of non-zero blocks is found by binary linear programming. A *subcode condition*  $\mathcal{C}_0 \subseteq \mathcal{C}_1$  must be satisfied to form a 2-level Construction D' lattice, and this is not straightforward. In [9],  $\mathbf{H}_0$  was obtained from  $\mathbf{H}_1$  by performing check splitting or PEG-based check splitting. In contrast to [9] we design  $\mathbf{H}_0$  and construct  $\mathbf{H}_1$  from  $\mathbf{H}_0$ . Simulation results of using well-known low-dimensional lattices for shaping a 2304-dimensional LDPC code lattice are given, and shaping gains of  $E_8$ ,  $BW_{16}$  and Leech lattices can be preserved.

*Notation* A tilde indicates a vector or matrix which has only 0s and 1s —  $\tilde{\mathbf{x}}$  and  $\tilde{\mathbf{H}}$  are binary while  $\mathbf{x}$  and  $\mathbf{H}$  are not necessarily so. Operations over the real numbers  $\mathbb{R}$  are denoted  $+$ ,  $\cdot$  while operations over the binary field  $\mathbb{F}_2$  are denoted  $\oplus$ ,  $\odot$ . The matrix transpose is denoted  $(\cdot)^t$ . Element-wise rounding to the nearest integer is denoted  $\lfloor \cdot \rfloor$ .

This work was supported by JSPS Kakenhi Grant Number JP 19H02137. This work is also the output of the ASEAN IVO project, PATRIOT-41R-Net, financially supported by NICT, Japan.

## II. CONSTRUCTION D'

An  $n$ -dimensional lattice  $\Lambda$  is a discrete additive subgroup of  $\mathbb{R}^n$ . Let a generator matrix of  $\Lambda$  be  $\mathbf{G}$  with basis vectors in columns. For integers  $\mathbf{b} \in \mathbb{Z}^n$ , a vector  $\mathbf{x}$  is a lattice point given by  $\mathbf{x} = \mathbf{G} \cdot \mathbf{b}$ . This is equivalent to  $\mathbf{H} \cdot \mathbf{x} = \mathbf{b}$ , where the check matrix is  $\mathbf{H} = \mathbf{G}^{-1}$ .

Consider nested linear codes  $\mathcal{C}_0 \subseteq \mathcal{C}_1 \subseteq \dots \subseteq \mathcal{C}_a = \mathbb{F}_2^n$  for level  $a \geq 1$ . Let an  $n$ -by- $n$  matrix of row vectors  $\mathbf{h}_j = [h_{j1}, \dots, h_{jn}]$  be denoted  $\tilde{\mathbf{H}} = [\mathbf{h}_1, \mathbf{h}_2, \dots, \mathbf{h}_n]^t$  for  $j = 1, \dots, n$ . The parity-check matrix of  $\mathcal{C}_i$  is  $\tilde{\mathbf{H}}_i$  for  $i = 0, 1, \dots, a-1$ . The dimension of  $\mathcal{C}_i$  is  $k_i = n - m_i$ , where  $m_i$  is the number of rows in  $\tilde{\mathbf{H}}_i$ , from  $\mathbf{h}_{k_i+1}$  to  $\mathbf{h}_n$ .

Construction D' converts a set of parity-checks defining nested linear codes into congruences for a lattice.

*Definition 1 (Construction D' (congruences)):* [12, p. 235] Let  $\mathcal{C}_0 \subseteq \mathcal{C}_1 \subseteq \dots \subseteq \mathcal{C}_a = \mathbb{F}_2^n$  be nested linear codes. Let the dimension of  $\mathcal{C}_i$  be  $k_i$ . Let  $\mathbf{h}_1, \mathbf{h}_2, \dots, \mathbf{h}_n$  be a basis for  $\mathbb{F}_2^n$  such that  $\mathcal{C}_i$  is defined by  $n - k_i$  parity-check vectors  $\mathbf{h}_{k_i+1}, \dots, \mathbf{h}_n$ . Then the Construction D' lattice is the set of all vectors  $\mathbf{x} \in \mathbb{Z}^n$  satisfying the congruences:

$$\mathbf{h}_j \cdot \mathbf{x} \equiv 0 \pmod{2^{i+1}}, \quad (1)$$

for all  $i \in \{0, \dots, a-1\}$  and  $k_i + 1 \leq j \leq n$ .

*Definition 2 (Construction D' (check matrix)):* Let a unimodular matrix  $\tilde{\mathbf{H}}$  be the check matrix of nested linear codes  $\mathcal{C}_0 \subseteq \mathcal{C}_1 \subseteq \dots \subseteq \mathcal{C}_a = \mathbb{F}_2^n$ . The dimension of  $\mathcal{C}_i$  is  $k_i$ . Let  $\mathbf{D}$  be a diagonal matrix with entries  $d_{j,j} = 2^{-i}$  for  $k_{i-1} < j \leq k_i$  for  $i = 0, 1, \dots, a$  where  $k_{-1} = 0$  and  $k_a = n$ . Then the Construction D' lattice is the set of all vectors  $\mathbf{x} \in \mathbb{Z}^n$  satisfying:  $\mathbf{H} \cdot \mathbf{x}$  are integers, where  $\mathbf{H} = \mathbf{D} \cdot \tilde{\mathbf{H}}$  is the lattice check matrix.

If  $\tilde{\mathbf{H}}$  is unimodular, then the Construction D' lattice  $\Lambda \subset \mathbb{Z}^n$ . To see this,  $\mathbf{G} = \mathbf{H}^{-1} = \tilde{\mathbf{H}}^{-1} \cdot \mathbf{D}^{-1}$ . Since  $\tilde{\mathbf{H}}$  is unimodular,  $\tilde{\mathbf{H}}^{-1}$  is integer.  $\mathbf{D}^{-1}$  also is integer, thus  $\mathbf{G}$  is an integer matrix. As a matter of design, after  $\tilde{\mathbf{H}}_0$  to  $\tilde{\mathbf{H}}_{g-1}$  are fixed, the upper rows of  $\tilde{\mathbf{H}}$  should be chosen such that  $\tilde{\mathbf{H}}$  is unimodular; it is also convenient to choose these upper rows so that  $\tilde{\mathbf{H}}$  is ALT form. The two definitions are equivalent if the congruence (1) is expressed:  $\mathbf{h}'_j \cdot \mathbf{x}$  is an integer, for  $\mathbf{h}'_j = \mathbf{h}_j/2^{i+1}$  and  $\mathbf{x} \in \mathbb{Z}^n$ .

The volume-to-noise ratio (VNR) is conventionally used while measuring error-correction performance of lattices, and can be defined  $\text{VNR} = V^{2/n}(\Lambda)/2\pi e\sigma^2$ , where the volume of an  $n$ -dimensional Construction D' lattice is  $V(\Lambda) = 2^{an - \sum_{i=0}^{a-1} k_i}$ , so that VNR is the distance to the Poltyrev limit.

## III. ENCODE AND DECODE CONSTRUCTION D'

Two equivalent encoding methods and a decoding algorithm for Construction D' lattices  $\Lambda$  are given in this section. The encoding describes explicitly the mapping from bits to a lattice point. The connection between a lattice point and the modulo-value of lattice component (in short, a codeword of binary code  $\mathcal{C}_i$ ) makes it possible to decode using an optimal decoder of  $\mathcal{C}_i$ . Encoding method A finds a lattice point of  $\Lambda$  using its check matrix  $\mathbf{H}$ . Encoding method B illustrates how bits are mapped to integers, and accordingly lattice components

are produced by check matrix  $\tilde{\mathbf{H}}$  of nested linear codes. The decoding algorithm is then given in Subsection III-C.

### A. Encoding Method A

Near linear-time encoding of LDPC codes can be accomplished using check matrix in the ALT form [14]. This idea inspired us to implement encoding of Construction D' lattice  $\Lambda$  with a similar procedure. The steps are distinct from [14] because check matrix  $\mathbf{H}$  of  $\Lambda$  is a real-valued square matrix.

Integers  $\mathbf{b}$  are provided, and the corresponding lattice point  $\mathbf{x}$  is found by solving:  $\mathbf{H} \cdot \mathbf{x} = \mathbf{b}$ . If  $\mathbf{H}$  is not too big, then  $\mathbf{x}$  can be found by matrix inversion:  $\mathbf{x} = \mathbf{H}^{-1} \cdot \mathbf{b}$ . If  $\mathbf{H}$  is large but is sparse and in the ALT form, as may be expected for Construction D' lattices based on LDPC codes, then the following procedure can be used.

Suppose that  $\mathbf{H}$  is in the ALT form, that is, it is partially lower triangular. Specifically,  $\mathbf{H}$  can be written as:

$$\mathbf{H} = \begin{bmatrix} \mathbf{B} & \mathbf{T} \\ \mathbf{X} & \mathbf{C} \end{bmatrix} \quad (2)$$

where  $\mathbf{T}$  is an  $s$ -by- $s$  lower-triangular matrix with non-zero elements on the diagonal;  $\mathbf{X}$  is a  $g$ -by- $g$  square matrix. The "gap" is  $g$ —the smaller the gap, the easier the encoding. Let  $\Delta = (\mathbf{X} - \mathbf{C}\mathbf{T}^{-1}\mathbf{B})^{-1}$ . The blockwise inverse of  $\mathbf{H}$  is:

$$\mathbf{H}^{-1} = \begin{bmatrix} -\Delta\mathbf{C}\mathbf{T}^{-1} & \Delta \\ \mathbf{T}^{-1} + \mathbf{T}^{-1}\mathbf{B}\Delta\mathbf{C}\mathbf{T}^{-1} & -\mathbf{T}^{-1}\mathbf{B}\Delta \end{bmatrix} \quad (3)$$

Using the block structure,  $\mathbf{H} \cdot \mathbf{x} = \mathbf{b}$  can be written as:

$$\begin{bmatrix} \mathbf{B} & \mathbf{T} \\ \mathbf{X} & \mathbf{C} \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ \vdots \\ x_g \\ x_{g+1} \\ \vdots \\ x_n \end{bmatrix} = \begin{bmatrix} b_1 \\ \vdots \\ b_g \\ b_{g+1} \\ \vdots \\ b_n \end{bmatrix} \quad (4)$$

To perform encoding, first  $x_1, \dots, x_g$  are found using (3):

$$\begin{bmatrix} x_1 \\ \vdots \\ x_g \end{bmatrix} = [-\Delta\mathbf{C}\mathbf{T}^{-1} \quad \Delta] \cdot \mathbf{b}. \quad (5)$$

Then, coordinates  $x_{g+1}, \dots, x_n$  are found sequentially by back-substitution, using the lower triangular structure. For  $i = g+1, \dots, n$ :

$$x_i = \frac{1}{h_{j,i}} \left( b_j - \sum_{l=1}^{i-1} h_{j,l} x_l \right) \quad (6)$$

where  $j = i - g$ .

This method is efficient when  $g$  is small and  $\mathbf{H}$  is sparse. It uses pre-computation and storage of the  $g$ -by- $g$  matrix in (5). The sum in (6) is performed over non-zero terms, so few terms appear for sparse  $\mathbf{H}$ . If the parity-check matrix  $\mathbf{H}$  is purely triangular, then encoding is simply performed by back-substitution.

### B. Encoding Method B

Encoding can also be performed using information vectors  $\mathbf{u}_i \in \mathbb{F}_2^{k_i}$  of  $\mathcal{C}_i$  for  $i = 0, 1, \dots, a$  and  $\mathbf{u}_a = \mathbf{z} \in \mathbb{Z}^n$ . In this method, we show explicitly how  $\mathbf{u}_i$  and corresponding integers  $\mathbf{b}$  are related to a lattice point  $\mathbf{x}$ .

For clarity, consider  $a = 3$ . The integers  $\mathbf{b}$  are related to  $\mathbf{u}_0, \mathbf{u}_1, \mathbf{u}_2$  and  $\mathbf{z}$  as:

$$b_j = u_{0j} + 2u_{1j} + 4u_{2j} + 8z_j \quad \text{for } 1 \leq j \leq k_0 \quad (7)$$

$$b_j = u_{1j} + 2u_{2j} + 4z_j \quad \text{for } k_0 < j \leq k_1 \quad (8)$$

$$b_j = u_{2j} + 2z_j \quad \text{for } k_1 < j \leq k_2 \quad (9)$$

$$b_j = z_j \quad \text{for } k_2 < j \leq n \quad (10)$$

Let  $\mathbf{u}'_i$  be the zero-padded version of  $\mathbf{u}_i$ , to have  $n$  components:

$$\mathbf{u}'_i = [u_{i1}, u_{i2}, \dots, u_{ik_i}, \underbrace{0, \dots, 0}_{n-k_i}]^t \quad (11)$$

Then, the integer vector  $\mathbf{b}$  is written as:

$$\mathbf{b} = \mathbf{D} \cdot (\mathbf{u}'_0 + 2\mathbf{u}'_1 + 4\mathbf{u}'_2 + 8\mathbf{z}), \quad (12)$$

where  $\mathbf{D}$  is given Definition 2.

For Construction D', the lattice point  $\mathbf{x}$  may be decomposed as:

$$\mathbf{x} = \mathbf{x}_0 + 2\mathbf{x}_1 + \dots + 2^{a-1}\mathbf{x}_{a-1} + 2^a\mathbf{x}_a, \quad (13)$$

with components  $\mathbf{x}_i$  depending on  $\mathbf{u}_i$  expressed below;  $\mathbf{x}_i$  are not necessarily binary.

Now we describe how information bits are related to a lattice point, and show that recovering integers from a lattice point is possible. Using  $\mathbf{H} \cdot \mathbf{x} = \mathbf{b}$ ,  $\mathbf{H} = \mathbf{D} \cdot \tilde{\mathbf{H}}$  and (12)–(13) we have

$$\mathbf{H} \cdot \mathbf{x} = \mathbf{b} \quad (14)$$

$$\tilde{\mathbf{H}} \cdot \mathbf{x} = \mathbf{D}^{-1} \cdot \mathbf{b} \quad (15)$$

$$\tilde{\mathbf{H}} \cdot (\mathbf{x}_0 + 2\mathbf{x}_1 + \dots + 2^a\mathbf{x}_a) = \mathbf{u}'_0 + 2\mathbf{u}'_1 + \dots + 2^a\mathbf{z} \quad (16)$$

and the lattice components  $\mathbf{x}_i \in \mathbb{Z}^n$  satisfy:

$$\tilde{\mathbf{H}} \cdot \mathbf{x}_i = \mathbf{u}'_i \quad \text{for } i = 0, \dots, a-1 \quad \text{and} \quad (17)$$

$$\tilde{\mathbf{H}} \cdot \mathbf{x}_a = \mathbf{z} \quad (18)$$

Note that encoding performed using (17)–(18) is equivalent to encoding method A in the previous subsection.

### C. Decoding Construction D'

The multistage decoding for Construction D lattices first introduced in [15] can produce an estimate of information bits  $\hat{\mathbf{u}}_i$  from a binary decoder of  $\mathcal{C}_i$ , and the estimated component  $\hat{\mathbf{x}}_i$  is obtained from  $\hat{\mathbf{u}}_i$  by re-encoding  $\hat{\mathbf{x}}_i = \mathbf{G}_i \cdot \hat{\mathbf{u}}_i$  [16]. An optimal decoder of  $\mathcal{C}_i$  provides low complexity decoding. Recently multistage decoding similar to [15] and [16] was proposed for Construction D' [9], including re-encoding steps to compute the cosets using estimate of lattice component of all previous levels.

We propose a multistage successive cancellation decoding algorithm suitable for Construction D' coding lattices to be used with shaping lattices, likewise employing a binary decoder  $\text{Dec}_i$  of  $\mathcal{C}_i$ . The encoding and decoding scheme of this paper is shown in Fig. 1, where encoding method B is to demonstrate the validity of the decoding algorithm.

*Proposition 1:* For Construction D', the lattice component  $\mathbf{x}_i$  is congruent modulo 2 to a codeword  $\tilde{\mathbf{x}}_i \in \mathcal{C}_i$ , for  $i = 0, \dots, a-1$ .

*Proof:* The lattice component  $\mathbf{x}_i$  satisfies  $\tilde{\mathbf{H}} \cdot \mathbf{x}_i = \mathbf{u}'_i$  and the codeword satisfies  $\tilde{\mathbf{H}}_i \odot \tilde{\mathbf{x}}_i = \mathbf{0}$ . Recall the last  $n - k_i$




Fig. 1. Block diagram of proposed encoding and decoding Construction D' lattices.  $\text{mod}^*$  denotes the "triangle-function"  $\text{mod}^*(y_i) = \lfloor \text{mod}_2(y_i + 1) - 1 \rfloor$  where  $\text{mod}_2$  indicates a modulo-2 operation.

positions of  $\mathbf{u}'_i$  are 0s. Row  $l$  of  $\tilde{\mathbf{H}}_i$  is equal to row  $l + k_i$  of  $\tilde{\mathbf{H}}$ , call this row  $\mathbf{h}_l$ . By definition,  $\mathbf{h}_l \cdot \mathbf{x}_i = 0$  and  $\mathbf{h}_l \odot \tilde{\mathbf{x}}_i = 0$  for  $l = 1, 2, \dots, n - k_i$ . Thus,  $\mathbf{x}_i \text{ mod } 2 = \tilde{\mathbf{x}}_i$  and the proposition holds.  $\square$

Consider a lattice point  $\mathbf{x}$  transmitted over a channel and the received sequence is  $\mathbf{y}_0 = \mathbf{x} + \mathbf{w}$ , where  $\mathbf{w}$  is noise. Decoding proceeds recursively for  $i = 0, 1, \dots, a-1$ . The decoding result at level  $i-1$  is used before beginning decoding at level  $i$ . Given  $\mathbf{y}'_i \in [0, 1]$ , the decoder  $\text{Dec}_i$  produces a binary codeword  $\tilde{\mathbf{x}}_i$  closest to  $\mathbf{y}'_i$ , which is an estimate of  $\tilde{\mathbf{x}}_i$ . It is necessary to find  $\tilde{\mathbf{x}}_i$ . If  $\tilde{\mathbf{x}}_i$  is not systematic, first find  $\hat{\mathbf{u}}'_i = \tilde{\mathbf{H}} \odot \tilde{\mathbf{x}}_i$ . Then re-encoding is performed to find  $\hat{\mathbf{x}}_i$ , that is, (17). This estimated component  $\hat{\mathbf{x}}_i$  is subtracted from the input, and this is divided over reals by 2:  $\mathbf{y}_{i+1} = (\mathbf{y}_i - \hat{\mathbf{x}}_i)/2$  to form  $\mathbf{y}_{i+1}$ , which is passed as input to the next level. This process continues recursively, until  $\mathbf{y}_a$  is obtained. The integers are estimated as  $\hat{\mathbf{x}}_a = \lfloor \mathbf{y}_a \rfloor$ . The estimated lattice point is written as  $\hat{\mathbf{x}} = \hat{\mathbf{x}}_0 + 2\hat{\mathbf{x}}_1 + \dots + 2^a\hat{\mathbf{x}}_a$ .

## IV. DESIGN LDPC CODE LATTICES

Branco da Silva and Silva also addressed the design of multilevel LDPC code lattices [9]. Using row operations on the parity-check matrix  $\mathbf{H}_0$  of the first level component code  $\mathcal{C}_0$ , a parity-check matrix that has the desired row and column degree distributions is obtained—the two check matrices both describe  $\mathcal{C}_0$ . In our work, QC-LDPC codes are designed using binary linear programming to guarantee that the necessary supercode can be constructed, as well as to satisfy the column and the row weight distribution.

### A. Construction D' Lattices Formed by QC-LDPC Codes

The parity-check matrix  $\mathbf{H}_0$  is expressed as

$$\mathbf{H}_0 = \begin{bmatrix} \mathbf{P}^{p_{1,1}} & \mathbf{P}^{p_{1,2}} & \dots & \mathbf{P}^{p_{1,N}} \\ \mathbf{P}^{p_{2,1}} & \mathbf{P}^{p_{2,2}} & \dots & \mathbf{P}^{p_{2,N}} \\ \vdots & \vdots & \ddots & \vdots \\ \mathbf{P}^{p_{M,1}} & \mathbf{P}^{p_{M,2}} & \dots & \mathbf{P}^{p_{M,N}} \end{bmatrix}, \quad (19)$$

where  $\mathbf{P}^{p_{i,j}}$  is a  $Z$ -by- $Z$  matrix (or a circulant) corresponding to the element  $p_{i,j}$  of a prototype parity-check matrix. For  $p_{i,j} = -1$ , instead use the all-zeros matrix. For  $p_{i,j} = 0$ ,  $\mathbf{P}$  is






Fig. 2. Word error rate of shaping an  $n = 2304$ -dimensional Construction D' lattice (formed by QC-LDPC codes) using  $E_8$  lattice shaping and hypercube shaping.

where  $\mathbf{K}$  is a constraint matrix that includes all the constraints described in (23)–(25) and  $\mathbf{a}$  is the vectorized version of  $\mathbf{A}$ . Because this is a binary programming problem, for the set  $\mathcal{A}_q$ , only one position will contain a 1 and the remaining  $|\mathcal{A}_q| - 1$  positions will contain 0, in any column. The implementation of this optimization problem is easily solved using standard optimization packages.

### C. Resulting Design

Now we give a specific design of binary QC-LDPC codes  $\mathcal{C}_0$  and  $\mathcal{C}_1$  for 2-level Construction D' lattices. The check matrices  $\mathbf{H}_0$  and  $\mathbf{H}_1$  are designed such that: 1)  $\mathcal{C}_0 \subseteq \mathcal{C}_1$  2)  $\mathbf{H}_0$  and  $\mathbf{H}_1$  are of full rank 3)  $\mathbf{H}_0$  and  $\mathbf{H}_1$  can be easily triangularized 4)  $\mathbf{H}_0$  and  $\mathbf{H}_1$  have girth as high as possible.

To meet the design requirements, first we use the binary linear programming in previous subsection to find a binary matrix  $\mathbf{A}$  (22) with  $M = 12$  rows and  $N = 24$  columns, using degree distribution polynomials of variable nodes and check nodes:  $\lambda(x) = \frac{1}{3}x + \frac{5}{12}x^2 + \frac{1}{8}x^3 + \frac{1}{8}x^5$  and  $\rho(x) = \frac{2}{3}x^5 + \frac{1}{3}x^6$ , respectively, where  $\lambda_d x^{d-1}$  and  $\rho_d x^{d-1}$  means  $\lambda_d$  and  $\rho_d$  are the fraction of nodes with degree  $d$ . This structure is a modified version of [18, Table I]. The check matrix  $\mathbf{H}_1$  is constructed (20) with  $\mathcal{A}_1 = \{5, 7, 9, 11\}$  and  $\mathcal{A}_2 = \{6, 8, 10, 12\}$ . Using a circulant size  $Z = 96$ , the prototype matrix as shown in Table I can be generated by assigning  $p_{i,j} = -1$  for  $a_{i,j} = 0$  and choosing the powers  $-1 < p_{i,j} < Z$  for  $a_{i,j} = 1$  such that  $\mathbf{H}_0$  and  $\mathbf{H}_1$  are free of 4-cycles and 6-cycles, where  $\mathbf{H}_0$  can be constructed using (19). The resulting  $\mathbf{H}_1$  lifted from Table II has degree distribution polynomials  $\lambda(X) = X$  and  $\rho(X) = X^{23}$ . The designed QC-LDPC codes  $\mathcal{C}_0$  and  $\mathcal{C}_1$  are of block length  $n = 2304$ , with code rate  $k_0/n = 1/2$  and  $k_1/n = 11/12$ , respectively.

The check matrix  $\mathbf{H}$  of an LDPC code lattice can be then constructed from  $\mathbf{H}_0$  and  $\mathbf{H}_1$  using Definition 2. Note that we did not use offset diagonal and we assigned a double circulant




Fig. 3. Word error rate of shaping the 2304-dimensional Construction D' lattice using  $E_8$ ,  $BW_{16}$  and Leech lattice shaping. Hypercube shaping was performed at a close code rate for comparison.

$p_{12,23}^*$  such that  $\mathbf{H}_0$  and  $\mathbf{H}_1$  can be easily triangularized. This provides efficient encoding and indexing [11].

## V. NUMERICAL RESULTS

The 2304-dimensional LDPC code lattice was evaluated on the power-constrained AWGN channel. The transmitted power can be reduced by Voronoi constellations using low-dimensional lattices,  $E_8$ ,  $BW_{16}$  and Leech lattices are considered in this paper. The direct sum of scaled copies (by a factor  $K$ ) of a low-dimensional lattice produces a 2304-dimensional shaping lattice  $\Lambda_s$  adapted to the proposed LDPC code lattice  $\Lambda_c - K$  is chosen such that the two lattices satisfy  $\Lambda_s \subseteq \Lambda_c$ , and thus form a nested lattice code to be used with dithering and MMSE scaling [2]. For more details about shaping high-dimensional  $\Lambda_c$  using low-dimensional lattices, see [5], [6]. Rectangular encoding and its inverse indexing can be efficiently implemented [11]. By choosing various  $K$  we generated a variety of nested lattice codes with code rate  $R$ . For comparison, hypercube shaping was performed where lattice points were transformed into a hypercube  $\mathcal{B} = \{0, 1, \dots, L-1\}^n$  for an even integer  $L$ . The belief propagation decoder of LDPC codes ran maximum 50 iterations.

The same code rate for both  $E_8$  lattice shaping and hypercube shaping can be easily achieved. The word error rate using  $K_{E_8} = L = 8, 16, 32$  is shown in Fig. 2 as a function of  $E_b/N_0 = \text{SNR}/2R$  with conventional signal-to-noise ratio (SNR), suggesting a shaping gain of 0.65 dB. Let  $K_{BW_{16}} = 280\sqrt{2}$  and  $K_{Leech} = 168\sqrt{8}$ , then  $BW_{16}$  and Leech lattice shaping produce code rate approximately 8.2959 and 8.3090, respectively, close to  $R = 8.2993$  of choosing  $K_{E_8} = L = 472$ . Numerical results are given in Fig. 3. If we take account of the code rate differences, a 0.65 dB, 0.86 dB and 1.03 dB shaping gain is preserved respectively, as the full shaping gain of  $E_8$ ,  $BW_{16}$  and Leech lattices.

## REFERENCES

- [1] B. Nazer and M. Gastpar, "Compute-and-forward: Harnessing interference through structured codes," *IEEE Transactions on Information Theory*, vol. 57, no. 10, pp. 6463–6486, October 2011.
- [2] U. Erez and R. Zamir, "Achieving  $\frac{1}{2} \log(1 + \text{SNR})$  on the AWGN channel with lattice encoding and decoding," *IEEE Transactions on Information Theory*, vol. 50, no. 10, pp. 2293–2314, October 2004.
- [3] H. Buglia and R. R. Lopes, "Voronoi shaping with efficient encoding," 2020, arXiv:2004.09680 [eess.SP].
- [4] N. Sommer, M. Feder, and O. Shalvi, "Shaping methods for low-density lattice codes," in *Proc. Information Theory Workshop, 2009*, October 2009, pp. 238–242.
- [5] N. S. Ferdinand, M. Nokleby, B. M. Kurkoski, and B. Aazhang, "Low-dimensional shaping for high-dimensional lattice codes," *IEEE Transactions on Wireless Communications*, vol. 15, no. 11, pp. 7405–7418, November 2016.
- [6] N. di Pietro and J. J. Boutros, "Leech constellations of Construction-A lattices," *IEEE Transactions on Communications*, vol. 65, no. 11, pp. 4622–4631, November 2017.
- [7] F. Zhou and B. M. Kurkoski, "Shaping LDLC lattices using convolutional code lattices," *IEEE Communications Letters*, no. 4, pp. 730–733, April 2017.
- [8] H. Khodaiemehr, M.-R. Sadeghi, and A. Sakzad, "Practical encoder and decoder for power constrained QC LDPC-lattice codes," *IEEE Transactions on Communications*, vol. 65, no. 2, pp. 486–500, February 2017.
- [9] P. R. Branco da Silva and D. Silva, "Multilevel LDPC lattices with efficient encoding and decoding and a generalization of Construction D'," *IEEE Transactions on Information Theory*, vol. 65, no. 5, pp. 3246–3260, May 2019.
- [10] R. Zamir, *Lattice Coding for Signals and Networks*. Cambridge, UK: Cambridge, 2014.
- [11] B. M. Kurkoski, "Encoding and indexing of lattice codes," *IEEE Transactions on Information Theory*, vol. 64, no. 9, pp. 6320–6332, September 2018.
- [12] J. H. Conway and N. J. A. Sloane, *Sphere Packings, Lattices and Groups*, 3rd ed. New York, NY, USA: Springer-Verlag, 1999, ISBN 0-387-98585-9.
- [13] S. Chen, B. M. Kurkoski, and E. Rosnes, "Construction D' lattices from quasi-cyclic low-density parity-check codes," in *2018 IEEE 10th International Symposium on Turbo Codes & Iterative Information Processing (ISTC)*, Hong Kong, China, December 2018, pp. 1–5.
- [14] T. Richardson and R. Urbanke, "Efficient encoding of low-density parity-check codes," *IEEE Transactions on Information Theory*, vol. 47, no. 2, pp. 638–656, February 2001.
- [15] A. Vem, Y.-C. Huang, K. R. Narayanan, and H. D. Pfister, "Multilevel lattices based on spatially-coupled LDPC codes with applications," in *2014 IEEE International Symposium on Information Theory*, Honolulu, HI, USA, June 2014, pp. 2336–2340.
- [16] T. Matsumine, B. M. Kurkoski, and H. Ochiai, "Construction D lattice decoding and its application to BCH code lattices," in *2018 IEEE Global Communications Conference (GLOBECOM)*, Abu Dhabi, United Arab Emirates, December 2018, pp. 1–6.
- [17] W. Sulek, "Protograph based low-density parity-check codes design with mixed integer linear programming," *IEEE Access*, vol. 7, pp. 1424–1438, 2019.
- [18] E. Rosnes, Ø. Ytrehus, M. A. Ambroze, and M. Tomlinson, "Addendum to "An efficient algorithm to find all small-size stopping sets of low-density parity-check matrices"," *IEEE Transactions on Information Theory*, vol. 58, no. 1, pp. 164–171, January 2012.