
DETECTING HARMFUL CONTENT ON ONLINE PLATFORMS: WHAT PLATFORMS NEED VS. WHERE RESEARCH EFFORTS GO

Arnav Arora

Checkstep Research;
University of Copenhagen
Copenhagen, Denmark
aar@di.ku.dk

Preslav Nakov

Checkstep Research;
Mohamed bin Zayed University of Artificial Intelligence
Abu Dhabi, UAE

Momchil Hardalov

Checkstep Research;
Sofia University “St. Kliment Ohridski”
Sofia, Bulgaria

Sheikh Muhammad Sarwar

Checkstep Research;
University of Massachusetts, Amherst
USA

Vibha Nayak

Checkstep
London, UK

Yoan Dinkov

Checkstep Research
Sofia, Bulgaria

Dimitrina Zlatkova

Checkstep Research
Sofia, Bulgaria

Kyle Dent

Checkstep
London, UK

Ameya Bhatawdekar

Checkstep; Microsoft
Doimukh, Arunachal Pradesh

Guillaume Bouchard

Checkstep
London, UK

Isabelle Augenstein

Checkstep Research;
University of Copenhagen
Copenhagen, Denmark

ABSTRACT

The proliferation of harmful content on online platforms is a major societal problem, which comes in many different forms including hate speech, offensive language, bullying and harassment, misinformation, spam, violence, graphic content, sexual abuse, self harm, and many other. Online platforms seek to moderate such content to limit societal harm, to comply with legislation, and to create a more inclusive environment for their users. Researchers have developed different methods for automatically detecting harmful content, often focusing on specific sub-problems or on narrow communities, as what is considered harmful often depends on the platform and on the context. We argue that there is currently a dichotomy between what types of harmful content online platforms seek to curb, and what research efforts there are to automatically detect such content. We thus survey existing methods as well as content moderation policies by online platforms in this light and we suggest directions for future work.

1 INTRODUCTION

Online harms is a serious and growing problem, and targeted groups and individuals have suffered it for years. There are various types of harms, ranging from clearly illegal activities (e.g., child sexual abuse, human trafficking, and terrorist propaganda) to more subtle ones, such as abusive language and spam, which are not always illegal, but nevertheless harmful. As harmful content is frequent online — e.g., when surveyed for a 2019 report by the UK government, 23% of the 12–15-year-olds stated to have observed it within the last year Barker & Jurasz (2019) — it is of particular concern to online communities, governments, and social media platforms. With this in mind, we present the first computing survey that relates computational solutions to harmful content detection to online platform policies, with focus on analysing to what extent existing research efforts are suitable to address the types of harms online platforms aim to curb.

While combating harm is a high priority, preserving individuals’ rights to free expression is also vital, which makes content moderation particularly difficult; yet, some form of moderation is clearly needed. Platform providers face very challenging technical and logistical problems in limiting harmful content, while at the same time wanting to allow a level of free speech that would enable rich and productive online interactions. Aiming to strike the right balance, many platforms institute guidelines and policies to specify what content is considered inappropriate. As manual filtering is hard to scale, and can even cause post-traumatic stress disorder in human annotators (mod, 2021), there has been significant research effort to develop tools and technologies to automate or assist in the process.

There have been several surveys of computational methods to detect and to address online harm. Schmidt & Wiegand (2017) and Fortuna & Nunes (2018) surveyed automated hate speech detection methods, but focused primarily on the features shown to be most effective in classification systems. Hardalov et al. (2022) and Guo et al. (2022) surveyed automated methods to address mis- and disinformation, Salawu et al. (2017) provided an extensive survey on detecting cyberbullying, and Vidgen & Derczynski (2021) worked on cataloging abusive language training data.

There are some studies closely related to ours, that focus on the content guidelines of online platforms. Gillespie (2018) qualitatively studied several policies in the content guidelines of more than 60 platforms. They stated how content guidelines are the platforms’ “*most deliberate and carefully crafted statement of principles*” outlining what content is not permitted on the platform and why. They also suggested to look at inspecting guidelines of a variety of platforms in order to understand the overlap and the differences between them, as we do in this study. Jiang et al. (2020) analysed the relative focus that platforms place on types of abuse to moderate. They iteratively coded and analysed the community guidelines of eleven major social media platforms for coverage of 66 different types of policies. Through their analysis, they outlined the imbalance in coverage of policies, speculating that “*platforms may have chosen to focus on and made rules regarding the types of misbehaviour that is most rampant on their platform, or made explicit the rules that are most reflective of their values*”. Our work builds on their study by categorising and computationally analysing the content guidelines of a larger set of platforms.

More concretely, we aim to bridge the gap between work on harmful content detection and platform solution requirements by surveying online platforms’ content policies, and relating them to proposed approaches by the research community. We further quantify the extent of this disconnect, and identify under-explored directions by analysing the platform requirements based on the keyword usage in their T&C clauses, and comparing those to what is currently available in the literature (both in published papers and in preprints). Nonetheless, no prior work has juxtaposed these policies with research directions and assessed the alignment between what platforms need vs. what technology has to offer. Hereby, we believe that such a survey is urgently needed.

2 REQUIREMENTS OF ONLINE PLATFORMS

Harmful content on online platforms can take on different forms. A 2019 white paper on online harms by the UK government considered the following sub-problems: online bullying and abuse, videos and images of children suffering sexual abuse, cyber-flashing, “pile-on” harassment, propaganda by terrorist groups, disinformation and misinformation Barker & Jurasz (2019). The paper noted that some of these are illegal, whereas others are lawful but potentially harmful.

Online platforms is a broad term, representing various categories of digital content providers such as social media, online marketplaces, online video communities, dating websites and apps, support communities and forums, and online gaming communities. Each of them is governed by its own content moderation policies and follows its own definition of harmful content. Below, we explore how online platforms define harmful content, and what content moderation policies they put in place accordingly by analysing their Terms and Conditions. Even though these T&Cs change over time, as platforms adapt to emerging issues such as the COVID-19 infodemic (Alam et al., 2021; Nakov et al., 2022), we analyse policies that we downloaded at a specific timestamp.¹

Table 1 lists the 42 online platforms that we study. We perform this selection with diversity of domain, content moderation needs of the platform as well as diversity of its user-base in mind in

¹Our offline Terms and Conditions archive are added in the Supplementary Material

Category	Platforms
Dating	Bumble
Generic Forum	Quora, Reddit, Disqus, BG Mamma, Discord, Something Awful, Substack, Clubhouse
Specific forum - Gaming	Twitch, OverClocked UK
Specific forum - Finance	Invstr, Money Saving Expert, Finimize, Public, StockTwits, Bogleheads, Gastby, Motley Fool
Specific forum - Health	Mumsnet, Student Doctor Network, Patient, Doctissimo, Flo Health, Strava
Specific forum - Other	Fiveable, Airbnb, Blind, The Student Room, Shutterstock
Online Marketplace	Amazon, Depop, NTWRK, Rarible
Social Media	Facebook, YouTube, Twitter, Girl Tribe, TikTok
Mixed	Google, Spotify, Apple

Table 1: Classification of the 42 online platforms we study.

order to have a representative sample. Moreover, we only include platforms with publicly available content guidelines. Guidelines for what is acceptable or not on a platform is included either as part of their T&Cs document or as a separate community guidelines document. As such, for our analysis, we choose the document based on where the platform lists this information. Note that we exclude “alternative” platforms such as *Parler*, *Bitchute*, *Gab*, and *Koo*, which are often specifically designed and commonly used as a substitute to platforms like *Twitter* in order to circumvent their moderation; these are already covered in designated studies (Buckley & Schafer, 2022). We categorise the 42 platforms based on the domain in which they operate, since the domain defines the type of content they need to moderate and is thus reflected in the respective T&Cs. For instance, *Reddit* is a *generic forum* where any topic can be discussed, and thus it needs a wider range of policies compared to a *specific forum* such as *Motley Fool*, where the focus is on investing. The *Mixed* category includes platforms that provide services (and hence, T&Cs spanning multiple categories, e.g., *Google* has policies that spread across its different services including *Meet*, *Mail*, *Help Communities*, etc., each of which requires different expansiveness in its policy coverage.

2.1 QUALITATIVE ANALYSIS OF THE TERMS AND CONDITIONS OF BIG TECH PLATFORMS

We conducted qualitative analysis of the terms and conditions of big *social media* and *mixed* platforms, commonly known as *Big Tech*. Big Tech has stringent content moderation policies as well as the most advanced technology to detect harmful content. We summarise this analysis in Table 2: we observe a lot of overlap, but also many differences.

Policy Clause	Facebook [†]	Twitter	Google	Apple	Amazon
<i>Violence</i>	✓	✓	✓	☞ Intimidating, Threatening	☞ Threatening
<i>Dangerous orgs/people</i>	✓	✓	Maps, Gmail, Meet*	? Illegal act	? under illegal
<i>Glorifying crime</i>	✓	✓	Maps, Gmail, Meet*	? Illegal act	? under illegal
<i>Illegal goods</i>	✓	✓	Maps, Google Chat and Hangout, Drive, Meet*	? Illegal act	? under illegal
<i>Self-harm</i>	✓	✓	✓	✗	✗
<i>Child sexual abuse</i>	✓	✓	✓	?	✗
<i>Sexual Abuse (Adults)</i>	✓	✓	✗	?	?
<i>Animal abuse</i>	✓	? Sensitive media policy	Earth, Drive, Meet*	? Illegal act	? under illegal
<i>Human trafficking</i>	✓	✓	✓	? Illegal act	? under illegal
<i>Bullying and harassment</i>	✓	✓	✓	✓	☞ Threatening
<i>Revenge porn</i>	✓	✓	✗	✗	? obscene
<i>Hate Speech</i>	✓	✓ Hateful Conduct	✓	✓	☞ Threatening
<i>Graphic content</i>	✓	✓	Maps*	✗	?
<i>Nudity and pornography</i>	✓	✓	Earth, Meet, Drive, Chat and Hangout*	✓	? under obscene
<i>Sexual Solicitation</i>	✓	✗	Maps*	✗	✗
<i>Spam</i>	✓	✓	✓	✗	✓
<i>Impersonation</i>	✓	✓	Maps, Earth, Chat and Hangout, Gmail, Meet*	✓	✓
<i>Misinformation</i>	✓ False news	✓	Maps, Drive*	✓	✗
<i>Medical Advice</i>	?	COVID-19 specific	Drive*	✗	✗

Table 2: Summary of the terms and conditions of Big Tech. We use the following notation: ✓ – explicitly mentioned in the policy; ✗ – not mentioned in the policy; ☞ – implicitly mentioned in the policy; ? – broadly mentioned in the policy under a more generic clause; * mentioned in additional service-specific policy; † – the same policy applies to Instagram.

Facebook covers most policy clauses related to harmful language, though, e.g., the coverage of *medical advice* is described quite broadly, and it is thus unclear whether users are free to share medical advice in their posts. *Google*’s terms of service cover basic guidelines on acceptable conduct. The

more specific clauses regarding *hate speech*, *bullying*, and *harassment* are in service-specific policies, as shown in Table 2. *Amazon* and *Apple* offer very different services compared to *Facebook*, *Twitter*, and *Google*, which is reflected in the clauses covered in their terms of service.

Apple's policies very broadly mention *dangerous organisations*, *glorifying crime*, *illegal goods*, *child sexual abuse*, *sexual abuse (adults)*, *animal abuse*, and *human trafficking* under *illegal acts*. *Violence* falls under threatening and intimidating posts. Their policy does not mention *medical advice*, *spam*, *sexual solicitation*, *revenge porn*, *graphic content*, and *self-harm*. For *Amazon*, *dangerous organisations and people*, *glorifying crime*, *illegal goods*, *child sexual abuse*, *sexual abuse (adults)*, *animal abuse*, and *human trafficking* are mentioned under *illegal acts*, which leaves room for ambiguity. *Revenge porn*, *graphic content*, *nudity and pornography* are also broadly mentioned in clauses pertaining to obscenity. However, there are no policies in place that directly address *medical advice*, *misinformation*, *sexual solicitation*, and *self-harm*.

2.2 QUANTITATIVE ANALYSIS OF ALL PLATFORMS' TERMS AND CONDITIONS

In order to understand to what degree these patterns exist more widely, we further conducted a quantitative analysis of the T&Cs across the 42 platforms that we consider in our study (see Table 1).

2.2.1 METHODOLOGY

We quantified the presence of specific categories in the T&Cs by searching for policy-related keywords and by counting the number of occurrences we found. We compiled the keyword lists semi-automatically by looking for words and phrases commonly mentioned in the T&Cs when discussing a given topic. For instance, the keyword list for *hate speech* includes *racist*, *ageist*, *disablist*, and *homophobic*, among others. A caveat to note here is that the number of search keywords differs across the policy clauses, which could affect the number of matches we found. Moreover, the T&Cs are often long, wide-ranging, and spread across several documents. Thus, in order to perform a more comprehensive search, we scraped all pages hyperlinked in the main T&C document. We further converted them to lowercase and we removed emails, numbers, URLs, and punctuation.

2.2.2 RESULTS

By platform category We outline the policy presence across all platforms in Figure 1. Confirming what we observed in the qualitative analysis, we found that social media platforms tended to have the most expansive policies, with all topics being present in the T&Cs of *Facebook* and *Twitter*, while *TikTok* and *YouTube* covered all but *sexual solicitation*.

The outlier here is *Girl Tribe by MissMalini*, which is a much smaller platform exclusively for women. The expansiveness compared to other categories could be attributed to the additional level of public scrutiny that social media companies are subject to.

While on average, *generic fora* cover more categories compared to *specific fora*, there is considerable variance within the specific fora with *Gaming* having a higher average policy coverage compared to *generic fora*, whereas fora pertaining to *Finance* have the least coverage among all categories. We attribute this to the increased attention that *Gaming* fora have received in the media as well as by regulatory authorities, and to accusations that they are not taking enough action to moderate harmful content (News, 2021).

By policy Interesting patterns can be observed in a per-policy analysis of the T&C documents. Figure 2a plots the number of platforms that cover each policy, which gives a sense of relative requirement for moderation for these policies across the platforms. We can see that *Hate speech* and *graphic content* policies are included in the T&Cs of all platforms except for *Gatsby*², followed by *violence*, *illegal content* and *spam*, respectively. *Sexual Solicitation* is the least covered, with only some *Social Media* and *Gaming fora* listing it.³ *Self-harm* is covered by all *Social Media* platforms, but it is not explicitly stated in half of the *Health* fora and in the *Dating* platform *Bumble*'s policies,

²Gatsby does not cover any of the policies taken into account in this work

³Yet, this kind of content is illegal in certain parts of the world and can have wide-ranging consequences; many platforms had to scramble to remove sexual solicitation and sexual content from their websites, most notably Craigslist removed their entire personals section to deal with the issue.





Figure 1: Number of policy topics covered by each platform per category.

where it ought to be important. A similar pattern can be observed for *Sexual Abuse* and *Human Trafficking*, which have low coverage in *Dating* and *Health* fora.

Figure 2b shows the number of times each topic is mentioned across all platform T&Cs. While multiple mentions do not perfectly capture how important a particular topic is, it does give us a sense of how much focus a platform is paying to a particular policy clause across several spread out pages of its T&Cs. Similarly to Figure 2a, *Violence*, *Graphic Content* and *Hate Speech* are the most mentioned topics, demonstrating the significant attention paid to them as well as the importance of detecting policy violations regarding these topics. *Sexual Solicitation* and *Political Propaganda* are the topics with the fewest mentions. For *Political Propaganda*, this can be partly attributed to its narrower focus, e.g., *Gaming* and *Finance* fora are unlikely to host large amounts of political content. *Child Sexual Abuse* is in the same range of mentions as *Misinformation*, *Bullying and Harassment* and *Spam*, while being covered by fewer platforms.



(a) number of platform T&Cs out of 42 mentioning each topic

(b) number of mentions of each topic across all platform T&Cs

Figure 2: Topic mentions across the platform Terms and Conditions (T&Cs).

3 AUTOMATIC HARMFUL CONTENT DETECTION

Below, we first analyse the publications in arXiv and to what extent they cover the above-described topics of concern in the T&Cs, and then we discuss some specific research, with focus on offensive language.

3.1 ANALYSING PUBLICATIONS IN ARXIV

In order to estimate how much research attention has been paid to each T&C topic, we looked for mentions of policy-related keywords in arXiv⁴ within the `cs` subject classification for 2015–2021, taking the number of results as a proxy for the amount of work conducted pertaining to that topic. We show the results in Figure 3. We can see that the number of papers on *Illegal Content* is consistently higher than for the other topics. We further see that work on *Hate Speech* and *Misinformation* has seen a steep growth since 2017, which reflects the attention these topics have attracted in recent years. *Spam* is another topic with a consistently high volume of publications. In contrast, topics such as *Sexual Solicitation*, *Child Sexual Abuse*, and *Human Trafficking* have seen very little research. We attribute this to the difficulty of getting access to datasets and performing research, due to the sensitive nature of these topics.




Figure 3: Number of papers found in arXiv for the different topics over time.

Work on harmful content detection has addressed several aspects of the above issues, but we are unaware of any work that covers them comprehensively. Vidgen & Derczynski (2021) attempted to categorise the available datasets with focus on abusive language detection, analysing a total of 64 datasets. They found that around half of the datasets covered English only, with some datasets covering European languages, Hindi and Indonesian, and six datasets covering Arabic. The primary source of the data was Twitter, but there were also datasets using content from other social networks. Overall, the size of most datasets was under 50,000 instances, and under 5,000 instances for half of the datasets.

3.2 APPROACHES

There has been a lot of research effort aimed at detecting specific types of offensive content, e.g., hate speech, offensive language, cyberbullying, and cyber-aggression. Below, we briefly describe some relevant tasks, datasets, and approaches.

Hate Speech Detection This is by far the most studied harmful language detection task Waseem & Hovy (2016); Kwok & Wang (2013); Burnap & Williams (2015); Ousidhoum et al. (2019); Chung et al. (2019); Sarwar & Murdock (2022). A recent shared task on the topic is HateEval Basile et al. (2019) for English and Spanish. The problem was also studied from a multimodal perspective,

⁴<https://arxiv.org/>

e.g., Sabat et al. (2019) developed a collection of 5,020 memes for hate speech detection. More recently, the Hateful Memes Challenge by Facebook introduced a dataset consisting of more than 10K memes, annotated as hateful or non-hateful Kiela et al. (2020): the memes were generated *artificially*, so that they resemble real memes shared on social media, along with “benign confounders.” More recent work studied *harmful memes* (Pramanick et al., 2021a;b; Sharma et al., 2022) and propagandistic memes (Dimitrov et al., 2021a;b).

Offensive Language Detection One of the most widely used datasets is the one by Davidson et al. (2017), which contains over 24,000 English tweets labelled as *non-offensive*, *hate speech*, and *profanity*. There have been several shared tasks with associated datasets that focused specifically on offensive language identification, often featuring multiple languages: OffensEval 2019–2020 Zampieri et al. (2019b; 2020) for English, Arabic, Danish, Greek, and Turkish, GermEval 2018 Wiegand et al. (2018) for German, HASOC 2019 Mandl et al. (2019) for English, German, and Hindi, TRAC 2018–2020 for English, Bengali, and Hindi Fortuna et al. (2018); Kumar et al. (2020). Offensive language was also studied from a multimodal perspective, e.g., Mittos et al. (2020) analysed memes shared on 4chan as *offensive vs. non-offensive*.

Aggression Detection The TRAC shared task on Aggression Identification Kumar et al. (2018) provided participants with a dataset containing 15,000 annotated Facebook posts and comments in English and Hindi for training and validation. For testing, two different sets, one from Facebook and one from Twitter, were used. The goal was to discriminate between three classes: *non-aggressive*, *covertly aggressive*, and *overtly aggressive*.

Toxic Comment Detection The Toxic Comment Classification Challenge Jigsaw (2018) was a Kaggle competition, which provided participants with almost 160K comments from Wikipedia organised in six classes: *toxic*, *severe toxic*, *obscene*, *threat*, *insult*, and *identity hate*. The dataset was also used outside of the competition Georgakopoulos et al. (2018), including as additional training material for the TRAC shared task Fortuna et al. (2018). It task was later extended to multiple languages Jigsaw Multilingual (2020),⁵ offering 8,000 Italian, Spanish, and Turkish comments. Recently, Juuti et al. (2020) presented a systematic study of data augmentation techniques in combination with state-of-the-art pre-trained Transformer models for toxic language detection. A related Kaggle challenge features Detecting Insults in Social Commentary.⁶ Other datasets include Wikipedia Detox Wulczyn et al. (2017), and the dataset by Davidson et al. (2017).

Cyberbullying Detection Xu et al. (2012) used sentiment analysis and topic models to identify relevant topics, Dadvar et al. (2013) relied on user-related features such as the frequency of profanity in previous messages, and Rosa et al. (2019) presented a systematic review of automatic cyberbullying detection research.

Abusive Language Detection There have also been datasets that cover various types of abusive language. Founta et al. (2018) tackled hate and abusive speech on Twitter, introducing a dataset of 100K tweets. Glavaš et al. (2020) targeted hate speech, aggression, and attacks in three different domains: Fox News (from GAO), Twitter/Facebook (from TRAC), and Wikipedia (from WUL). In addition to English, it further offered parallel examples in Albanian, Croatian, German, Russian, and Turkish. However, the dataset was small, containing only 999 examples. Among the popular approaches for abusive language detection are cross-lingual embeddings Ranasinghe & Zampieri (2020), cross-lingual neighbourhood transformer representations Sarwar et al. (2022), and deep learning Founta et al. (2019). As abusive language has many aspects, there have been several proposals for multi-level taxonomies covering different types of abuse. This enables understanding how different types and targets of abusive language relate to each other, and informs efforts to detect them. For example, offensive messages targeting a group are likely *hate speech*, while when the target is an individual, this is likely *cyberbullying*. Waseem et al. (2017) presented a taxonomy that differentiates between (abusive) language directed towards a specific individual or entity, or towards a generalised group, as well as between explicit and implicit abusive content. Wiegand et al. (2018) extended this idea to German tweets: they developed a model to detect offensive vs. non-offensive tweets, and further sub-classified the former as profanity, insult, or abuse. Zampieri et al.

⁵<https://www.kaggle.com/c/jigsaw-multilingual-toxic-comment-classification>

⁶<http://www.kaggle.com/c/detecting-insults-in-social-commentary>

(2019a) developed a very popular three-level taxonomy, which considers both the type and the target of offence. The taxonomy served as the basis of the *OLID* dataset of 14,000 English tweets, which was used in two shared tasks (OffensEval) at SemEval in 2019 Zampieri et al. (2019b) and in 2020 Zampieri et al. (2020). For the latter, an additional large-scale dataset was developed, consisting of nine million English tweets labelled in a semi-supervised fashion Rosenthal et al. (2021). This new dataset enabled sizeable performance gains, especially at the lower levels of the taxonomy. The taxonomy was also adopted for Arabic Mubarak et al. (2021), Danish Sigurbergsson & Derczynski (2020), Greek Pitenis et al. (2020), and Turkish Çöltekin (2020).

Troll detection has been addressed using semantic analysis Cambria et al. (2010), domain-adapted sentiment analysis Seah et al. (2015), various lexico-syntactic features about user writing style and structure Chen et al. (2012); Mihaylov et al. (2015a); Mihaylov & Nakov (2016), as well as using graph-based approaches Ortega et al. (2012); Kumar et al. (2014). There have also been studies on general troll behaviour Herring et al. (2002); Buckels et al. (2014); Mihaylov et al. (2018); Nakov et al. (2017) and role (Mihaylov et al., 2015b; Atanasov et al., 2019), cyberbullying Galán-García et al. (2016); Sarna & Bhatia (2017); Wong et al. (2018); Sezer et al. (2015), as well as on linking fake troll profiles to real users Galán-García et al. (2016). Some studies related to cyberbullying have already been applied in real settings in order to detect and to stop cyberbullying in elementary schools using a supervised machine learning algorithm that links fake profiles to real ones on the same social medium Galán-García et al. (2016).

Identification of malicious accounts in social networks is another important research direction. This includes detecting spam accounts Almaatouq et al. (2016); McCord & Chuah (2011), fake accounts Fire et al. (2014); Cresci et al. (2015), compromised accounts and phishing accounts Adewole et al. (2017). Fake profile detection has also been studied in the context of cyberbullying Galán-García et al. (2016).

Web spam detection was addressed text classification Sebastiani (2002), e.g., using spam keyword spotting Dave et al. (2003), lexical affinity of words to spam content Hu & Liu (2004), frequency of punctuation, and word co-occurrence Li et al. (2006).

Methods The most common way to address the above tasks is to use pre-trained transformers (Vaswani et al., 2017): typically BERT Devlin et al. (2019), but also RoBERTa Liu et al. (2019), ALBERT Lan et al. (2020), and GPT-2 Radford et al. (2019). In a multi-lingual setup, also mBERT Devlin et al. (2019) and XLM-RoBERTa Conneau et al. (2020) have proved useful. CNNs Fukushima (1980), RNNs Rumelhart et al. (1986), and GRUs Cho et al. (2014), including ELMo Peters et al. (2018). Older models such as SVMs are sometimes also used, typically as part of ensembles. Moreover, lexica such as HurtLex Bassignana et al. (2018) and Hatebase⁷ are also popular. For multi-modal detection of these harms, popular approaches include Visual BERT, ViLBERT, VLP, UNITER, LXMERT, VILLA, ERNIE-Vil, Oscar and various Transformers (Li et al., 2019; Su et al., 2020; Zhou et al., 2020; Tan & Bansal, 2019; Gan et al., 2020; Yu et al., 2021; Li et al., 2020; Lippe et al., 2020; Zhu, 2020; Muennighoff, 2020; Zhang et al., 2020; Kumar & Nandakumar, 2022).

4 LESSONS LEARNED AND MAJOR CHALLENGES

Despite the stringent policies in place, the amount of harmful content online keeps growing. Research is complicated as online platforms have different understanding of harmful content, and platform’s Terms and Conditions (T&Cs) try to imagine every possible outcome of particular statements, while trying to be transparent about the areas they fall short in. The reality is that some clauses in the T&Cs are hard to automate and require human attention and understanding. Below, we describe some of these challenges in more detail. The list is not exhaustive, but it illustrates the main challenges faced by online platforms and researchers, as new issues regularly appear, policies evolve, and new detection technologies are constantly being developed.

Mismatch in Goals Table 3 shows a comparison of the number of papers on arXiv that mention a specific type of harmful content and the corresponding number of platforms that mention that type

⁷<http://hatebase.org/>

in their T&Cs. We can see that *graphic content* and *violence* are relatively less researched in spite of being covered by large number of platforms. On the other hand, *misinformation*, *illegal content*, etc. have attracted a lot of research. As is readily apparent when comparing T&Cs documents of online platforms (Section 2) to harmful content tasks tackled in research (Section 3), there is a clear disconnect between what types of content platforms seek to moderate, and what current harmful content detection research offers, as demonstrated by the high variance in the ratio column in Table 3.

Lack of participatory design. While this work focuses on platform policies and academic literature around content moderation, it is the users of a platform who are at the receiving end of decisions based on these policies and algorithms. Hence, a people-centric and participatory process model for AI-assisted content moderation is crucial (Udupa et al., 2022). Following a one-size-fits-all approach does not work when norms, values, and what is considered harmful differs across communities (Chandrasekharan et al., 2018) and cultures (Jiang et al., 2021).

Policy challenges. It is hard to define harmful content policy that is congruent with the harm that such content inflicts. For example, Facebook’s hate speech policy is tiered, where Tier 1 aims to define the kind of hate speech that is considered most harmful. The policy covers content targeting a person or a group of people based on their protected characteristics such as race, ethnicity, national origin, disability, gender, etc. According to this policy, certain offensive statements are considered more harmful than others. Moreover, a number of policies are left under-specified or are ambiguous in what content is allowed on the platform. The policies are also fluid, change based on the circumstances, and are affected by events in the real world (Vengattil & Culliford, 2022), which makes them challenging for researchers to follow.

Context. An obvious challenge that comes with the need to moderate *unlawful* content is that platforms are operating in multiple countries with a wide spectrum of legal standards. Similarly, the same content considered in different contexts can be either perfectly benign or can be perceived as harmful. Such context also changes with time, e.g., certain slur words are appropriated by their target groups as reclaimed speech. Such historical, legal, and cultural context is not explicitly encoded into machine learning models at present and makes it impossible for them to accurately detect and for platforms to moderate this content.

Dataset Availability As outlined earlier, data for sensitive policies such as *sexual solicitation* and *child sexual abuse* are hard to collect and share. However, even for categories such as *misinformation* and *bullying and harassment*, access to data is primarily at the discretion of the platforms. While there have been efforts to increase research access, these remain insufficient. Moreover, since violating content is often taken down, researchers enter a timed race with platforms in their efforts to collect content before it is removed or only have access to the content that platforms do not remove, making it incredibly hard for them to develop systems capable of detecting or assessing the potential harms caused by such content. Hence, there is a need for platforms to develop privacy-preserving ways of sharing datasets.

Content is Interlinked. People use text, images, videos, audio files, GIFs, emojis — all together — to communicate. While each modality by itself may be seemingly benign, when combined, they might make content that violates the T&Cs. Thus, there is a need for holistic understanding of the content.

Dataset Specificity Most publicly available datasets are specific to the type of harm, to the targeted group, or to other fine-grained distinctions, as harmful content can be highly context-sensitive. Further, in the hierarchical annotation schemes introduced by these datasets, lower levels of the taxonomy contain a subset of the instances in the higher levels, and thus there are fewer instances in the categories in each subsequent level. This diversity has led to the creation of many datasets, most of which are small in size, and much of the research on harmful content detection is fragmented, with very few studies viewing the problem from a holistic perspective.

Topic	arXiv Papers	Online Platforms	Ratio
sexual solicitation	1	5	0.20
child sexual abuse	12	26	0.46
sexual abuse	24	24	1.00
graphic content	79	41	1.93
human trafficking	53	15	3.53
self harm	102	22	4.64
dangerous organisations	142	29	4.90
violence	255	40	6.38
bullying and harassment	276	37	7.46
impersonation	192	19	10.11
spam	434	39	11.13
political propaganda	209	11	19.00
hate speech	1089	41	26.56
illegal content	1113	40	27.82
misinformation	1029	35	29.40

Table 3: Relative research focus in terms of number of research papers in arXiv that study a given type of harmful content and the number of online platforms that aim to moderate such content, as well as a ratio thereof.

5 CONCLUSION

We discussed recent methods for harmful content detection in the context of the content policies of online platforms. We inspected the content guidelines of 42 platforms and compared the needs highlighted there to available research. We found a substantial imbalance in the relative focus to different policy clauses in research vs. by platforms. For instance, misinformation and political propaganda are among the clauses with a high research-papers-to-platform-coverage ratio, while sexual solicitation and graphic content received limited attention, despite being critical for a number of platforms. While academic research should not aim to follow industrial needs, shedding light on this relative focus can aid in identifying major challenges and possible remedies that harmful content detection faces going forward. We argued that current research does not produce the tools for automating content moderation on online platforms that matched their needs. We further outlined some major challenges that need to be addressed.

REFERENCES

- Facebook moderators call for better mental health support, end to NDAs, 2021. Section: Social Media.
- Kayode Sakariyah Adewole, Nor Badrul Anuar, Amirrudin Kamsin, Kasturi Dewi Varathan, and Syed Abdul Razak. Malicious accounts: Dark of the social networks. *Journal of Network and Computer Applications*, 79:41–67, 2017.
- Firoj Alam, Shaden Shaar, Fahim Dalvi, Hassan Sajjad, Alex Nikolov, Hamdy Mubarak, Giovanni Da San Martino, Ahmed Abdelali, Nadir Durrani, Kareem Darwish, Abdulaziz Al-Homaid, Wajdi Zaghouni, Tommaso Caselli, Gijs Danoe, Friso Stolk, Britt Bruntink, and Preslav Nakov. Fighting the COVID-19 infodemic: Modeling the perspective of journalists, fact-checkers, social media platforms, policy makers, and the society. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pp. 611–649, Punta Cana, Dominican Republic, 2021.
- Abdullah Almaatouq, Erez Shmueli, Mariam Nouh, Ahmad Alabdulkareem, Vivek K Singh, Mansour Alsaleh, Abdulrahman Alarifi, Anas Alfaris, et al. If it looks like a spammer and behaves like a spammer, it must be a spammer: analysis and detection of microblogging spam accounts. *International Journal of Information Security*, 15(5):475–491, 2016.
- Atanas Atanasov, Gianmarco De Francisci Morales, and Preslav Nakov. Predicting the role of political trolls in social media. In *Proceedings of the 23rd Conference on Computational Natural Language Learning (CoNLL)*, pp. 1023–1034, Hong Kong, China, 2019. Association for Computational Linguistics. doi: 10.18653/v1/K19-1096. URL <https://aclanthology.org/K19-1096>.

-
- Kim Barker and Olga Jurasz. Online Harms White Paper Consultation Response, 2019.
- Valerio Basile, Cristina Bosco, Elisabetta Fersini, Debora Nozza, Viviana Patti, Francisco Manuel Rangel Pardo, Paolo Rosso, and Manuela Sanguinetti. SemEval-2019 task 5: Multilingual detection of hate speech against immigrants and women in Twitter. In *Proceedings of the 13th International Workshop on Semantic Evaluation*, pp. 54–63, Minneapolis, Minnesota, USA, 2019. Association for Computational Linguistics. doi: 10.18653/v1/S19-2007. URL <https://aclanthology.org/S19-2007>.
- Elisa Bassignana, Valerio Basile, and Viviana Patti. Hurtlex: A Multilingual Lexicon of Words to Hurt. In *Proceedings of the Fifth Italian Conference on Computational Linguistics*, volume 2253 of *CLiC-it 18*, pp. 51–56, Torino, Italy, 2018.
- Erin E Buckels, Paul D Trapnell, and Delroy L Paulhus. Trolls just want to have fun. *Personality and Individual Differences*, 67:97–102, 2014.
- Nicole Buckley and Joseph S. Schafer. ‘Censorship-free’ platforms: Evaluating content moderation policies and practices of alternative social media. *For(e)Dialogue*, 4(Vol 4, Issue 1), 2022.
- Pete Burnap and Matthew L Williams. Cyber hate speech on Twitter: An application of machine classification and statistical modeling for policy and decision making. *Policy & Internet*, 7(2): 223–242, 2015.
- Erik Cambria, Praphul Chandra, Avinash Sharma, and Amir Hussain. Do not feel the trolls. In *SDoW*, Shanghai, China, 2010.
- Eshwar Chandrasekharan, Mattia Samory, Shagun Jhaver, Hunter Charvat, Amy Bruckman, Cliff Lampe, Jacob Eisenstein, and Eric Gilbert. The internet’s hidden rules: An empirical study of reddit norm violations at micro, meso, and macro scales. *Proc. ACM Hum.-Comput. Interact.*, 2 (CSCW), 2018. doi: 10.1145/3274301.
- Ying Chen, Yilu Zhou, Sencun Zhu, and Heng Xu. Detecting offensive language in social media to protect adolescent online safety. In *International Conference on Privacy, Security, Risk and Trust and International Conference on Social Computing*, pp. 71–80, Amsterdam, Netherlands, 2012.
- Kyunghyun Cho, Bart van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using RNN encoder–decoder for statistical machine translation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 1724–1734, Doha, Qatar, 2014. Association for Computational Linguistics. doi: 10.3115/v1/D14-1179. URL <https://aclanthology.org/D14-1179>.
- Yi-Ling Chung, Elizaveta Kuzmenko, Serra Sinem Tekiroglu, and Marco Guerini. CONAN - COUNTER NARRATIVES THROUGH NICHE-SOURCING: A MULTILINGUAL DATASET OF RESPONSES TO FIGHT ONLINE HATE SPEECH. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2819–2829, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1271. URL <https://aclanthology.org/P19-1271>.
- Çağrı Çöltekin. A corpus of Turkish offensive language on social media. In *Proceedings of the 12th Language Resources and Evaluation Conference*, pp. 6174–6184, Marseille, France, 2020. European Language Resources Association. ISBN 979-10-95546-34-4. URL <https://aclanthology.org/2020.lrec-1.758>.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 8440–8451, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.747. URL <https://aclanthology.org/2020.acl-main.747>.
- Stefano Cresci, Roberto Di Pietro, Marinella Petrocchi, Angelo Spognardi, and Maurizio Tesconi. Fame for sale: Efficient detection of fake Twitter followers. *Decision Support Systems*, 80:56–71, 2015. ISSN 0167-9236.

-
- Maral Dadvar, Dolf Trieschnigg, Roeland Ordelman, and Franciska de Jong. Improving Cyberbullying Detection with User Context. In *Advances in Information Retrieval*, pp. 693–696, Berlin, Heidelberg, 2013. ISBN 978-3-642-36973-5.
- Kushal Dave, Steve Lawrence, and David M. Pennock. Mining the peanut gallery: opinion extraction and semantic classification of product reviews. In Gusztáv Hencsey, Bebo White, Yih-Farn Robin Chen, László Kovács, and Steve Lawrence (eds.), *Proceedings of the Twelfth International World Wide Web Conference, WWW 2003, Budapest, Hungary, May 20-24, 2003*, pp. 519–528. ACM, 2003. doi: 10.1145/775152.775226. URL <https://doi.org/10.1145/775152.775226>.
- Thomas Davidson, Dana Warmsley, Michael Macy, and Ingmar Weber. Automated hate speech detection and the problem of offensive language. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 11 of *ICWSM '17*, pp. 512–515, Montreal, Canada, 2017.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL <https://aclanthology.org/N19-1423>.
- Dimitar Dimitrov, Bishr Bin Ali, Shaden Shaar, Firoj Alam, Fabrizio Silvestri, Hamed Firooz, Preslav Nakov, and Giovanni Da San Martino. Detecting propaganda techniques in memes. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 6603–6617, Online, 2021a. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.516. URL <https://aclanthology.org/2021.acl-long.516>.
- Dimitar Dimitrov, Bishr Bin Ali, Shaden Shaar, Firoj Alam, Fabrizio Silvestri, Hamed Firooz, Preslav Nakov, and Giovanni Da San Martino. SemEval-2021 task 6: Detection of persuasion techniques in texts and images. In *Proceedings of the 15th International Workshop on Semantic Evaluation (SemEval-2021)*, pp. 70–98, Online, 2021b. Association for Computational Linguistics. doi: 10.18653/v1/2021.semeval-1.7. URL <https://aclanthology.org/2021.semeval-1.7>.
- Michael Fire, Dima Kagan, Aviad Elyashar, and Yuval Elovici. Friend or foe? Fake profile identification in online social networks. *Social Network Analysis and Mining*, 4(1):194, 2014.
- Paula Fortuna and Sérgio Nunes. A Survey on Automatic Detection of Hate Speech in Text. *ACM Computing Surveys (CSUR)*, 51(4), 2018. ISSN 0360-0300.
- Paula Fortuna, José Ferreira, Luiz Pires, Guilherme Routar, and Sérgio Nunes. Merging datasets for aggressive text identification. In *Proceedings of the First Workshop on Trolling, Aggression and Cyberbullying (TRAC-2018)*, pp. 128–139, Santa Fe, New Mexico, USA, 2018. Association for Computational Linguistics. URL <https://aclanthology.org/W18-4416>.
- Antigoni Founta, Constantinos Djouvas, Despoina Chatzakou, Ilias Leontiadis, Jeremy Blackburn, Gianluca Stringhini, Athena Vakali, Michael Sirivianos, and Nicolas Kourtellis. Large scale crowdsourcing and characterization of Twitter abusive behavior. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 12, 2018.
- Antigoni Maria Founta, Despoina Chatzakou, Nicolas Kourtellis, Jeremy Blackburn, Athena Vakali, and Ilias Leontiadis. A Unified Deep Learning Architecture for Abuse Detection. In *Proceedings of the ACM Conference on Web Science, WebSci '19*, pp. 105–114, Boston, Massachusetts, 2019. ISBN 9781450362023.
- Kuniyihiko Fukushima. Neocognitron: A self-organizing neural network model for a mechanism of pattern recognition unaffected by shift in position. *Biological cybernetics*, 36(4):193–202, 1980.

-
- Patxi Galán-García, José Gaviria de la Puerta, Carlos Laorden Gómez, Igor Santos, and Pablo García Bringas. Supervised Machine Learning for the Detection of Troll Profiles in Twitter Social Network: Application to a Real Case of Cyberbullying. *Logic Journal of the IGPL*, 24(1):42–53, 2016.
- Zhe Gan, Yen-Chun Chen, Linjie Li, Chen Zhu, Yu Cheng, and Jingjing Liu. Large-scale adversarial training for vision-and-language representation learning. In Hugo Larochelle, Marc’Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL <https://proceedings.neurips.cc/paper/2020/hash/49562478de4c54fafd4ec46fdb297de5-Abstract.html>.
- Spiros V. Georgakopoulos, Sotiris K. Tasoulis, Aristidis G. Vrahatis, and Vassilis P. Plagianakos. Convolutional Neural Networks for Toxic Comment Classification. In *Proceedings of the 10th Hellenic Conference on Artificial Intelligence*, Patras, Greece, 2018.
- Tarleton Gillespie. CHAPTER 3. Community Guidelines, or the Sound of No. In *CHAPTER 3. Community Guidelines, or the Sound of No*, pp. 45–73. 2018. ISBN 978-0-300-23502-9. doi: 10.12987/9780300235029-003.
- Goran Glavaš, Mladen Karan, and Ivan Vulić. XHate-999: Analyzing and detecting abusive language across domains and languages. In *Proceedings of the 28th International Conference on Computational Linguistics*, pp. 6350–6365, Barcelona, Spain (Online), 2020. International Committee on Computational Linguistics. doi: 10.18653/v1/2020.coling-main.559. URL <https://aclanthology.org/2020.coling-main.559>.
- Zhijiang Guo, Michael Schlichtkrull, and Andreas Vlachos. A survey on automated fact-checking. *Transactions of the Association for Computational Linguistics*, 10:178–206, 2022. doi: 10.1162/tacl.a.00454.
- Momchil Hardalov, Arnav Arora, Preslav Nakov, and Isabelle Augenstein. A survey on stance detection for mis- and disinformation identification. In *Findings of the Association for Computational Linguistics: NAACL 2022*, pp. 1259–1277, Seattle, United States, 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.findings-naacl.94. URL <https://aclanthology.org/2022.findings-naacl.94>.
- Susan Herring, Kirk Job-Sluder, Rebecca Scheckler, and Sasha Barab. Searching for Safety Online: Managing ”Trolling” in a Feminist Forum. *The Information Society*, 18(5):371–384, 2002.
- Minqing Hu and Bing Liu. Mining and Summarizing Customer Reviews. In *Proceedings of the Tenth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, KDD ’04*, pp. 168–177, Seattle, WA, USA, 2004. ISBN 1581138881.
- Jialun ’Aaron’ Jiang, Skyler Middler, Jed R. Brubaker, and Casey Fiesler. Characterizing community guidelines on social media platforms. In *Conference Companion Publication of the 2020 on Computer Supported Cooperative Work and Social Computing, CSCW ’20 Companion*, pp. 287–291, 2020. ISBN 9781450380591. doi: 10.1145/3406865.3418312.
- Jialun Aaron Jiang, Morgan Klaus Scheuerman, Casey Fiesler, and Jed R. Brubaker. Understanding international perceptions of the severity of harmful content online. *PLOS ONE*, 16(8):1–22, 2021. doi: 10.1371/journal.pone.0256762.
- Jigsaw. Toxic Comment Classification Challenge. <https://www.kaggle.com/c/jigsaw-toxic-comment-classification-challenge/>, 2018. Online; accessed 28 April 2021.
- Jigsaw Multilingual. Jigsaw Multilingual Toxic Comment Classification. <https://www.kaggle.com/c/jigsaw-multilingual-toxic-comment-classification/>, 2020. Online; accessed 28 April 2021.
- Mika Juuti, Tommi Gröndahl, Adrian Flanagan, and N. Asokan. A little goes a long way: Improving toxic language classification despite data scarcity. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 2991–3009, Online, 2020. Association for Computational

-
- Linguistics. doi: 10.18653/v1/2020.findings-emnlp.269. URL <https://aclanthology.org/2020.findings-emnlp.269>.
- Douwe Kiela, Hamed Firooz, Aravind Mohan, Vedanuj Goswami, Amanpreet Singh, Pratik Ringshia, and Davide Testuggine. The hateful memes challenge: Detecting hate speech in multi-modal memes. In Hugo Larochelle, Marc’Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL <https://proceedings.neurips.cc/paper/2020/hash/1b84c4cee2b8b3d823b30e2d604b1878-Abstract.html>.
- Gokul Karthik Kumar and Karthik Nandakumar. Hate-CLIPper: Multimodal hateful meme classification based on cross-modal interaction of CLIP features. In *Proceedings of the Second Workshop on NLP for Positive Impact (NLP4PI)*, pp. 171–183, Abu Dhabi, United Arab Emirates (Hybrid), 2022. Association for Computational Linguistics. URL <https://aclanthology.org/2022.nlp4pi-1.20>.
- Ritesh Kumar, Atul Kr. Ojha, Shervin Malmasi, and Marcos Zampieri. Benchmarking aggression identification in social media. In *Proceedings of the First Workshop on Trolling, Aggression and Cyberbullying (TRAC-2018)*, pp. 1–11, Santa Fe, New Mexico, USA, 2018. Association for Computational Linguistics. URL <https://aclanthology.org/W18-4401>.
- Ritesh Kumar, Atul Kr. Ojha, Shervin Malmasi, and Marcos Zampieri. Evaluating aggression identification in social media. In *Proceedings of the Second Workshop on Trolling, Aggression and Cyberbullying*, pp. 1–5, Marseille, France, 2020. European Language Resources Association (ELRA). ISBN 979-10-95546-56-6. URL <https://aclanthology.org/2020.trac-1.1>.
- Srijan Kumar, Francesca Spezzano, and V. S. Subrahmanian. Accurately detecting trolls in slashdot zoo via decluttering. In Xindong Wu, Martin Ester, and Guandong Xu (eds.), *2014 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining, ASONAM 2014, Beijing, China, August 17-20, 2014*, pp. 188–195. IEEE Computer Society, 2014. doi: 10.1109/ASONAM.2014.6921581. URL <https://doi.org/10.1109/ASONAM.2014.6921581>.
- Irene Kwok and Yuzhou Wang. Locate the hate: Detecting tweets against blacks. In Marie desJardins and Michael L. Littman (eds.), *Proceedings of the Twenty-Seventh AAAI Conference on Artificial Intelligence, July 14-18, 2013, Bellevue, Washington, USA*. AAAI Press, 2013. URL <http://www.aaai.org/ocs/index.php/AAAI/AAAI13/paper/view/6419>.
- Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. ALBERT: A lite BERT for self-supervised learning of language representations. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL <https://openreview.net/forum?id=H1eA7AEtvS>.
- Liunian Harold Li, Mark Yatskar, Da Yin, Cho-Jui Hsieh, and Kai-Wei Chang. VisualBERT: A Simple and Performant Baseline for Vision and Language. *ArXiv preprint*, abs/1908.03557, 2019. URL <https://arxiv.org/abs/1908.03557>.
- Wenbin Li, Ning Zhong, and Chunnian Liu. Combining multiple email filters based on multivariate statistical analysis. In *International symposium on methodologies for intelligent systems*, pp. 729–738, 2006.
- Xiujun Li, Xi Yin, Chunyuan Li, Pengchuan Zhang, Xiaowei Hu, Lei Zhang, Lijuan Wang, Houdong Hu, Li Dong, Furu Wei, et al. Oscar: Object-Semantics Aligned Pre-training for Vision-Language Tasks. In *European Conference on Computer Vision*, volume 12375, pp. 121–137, 2020.
- Phillip Lippe, Nithin Holla, Shantanu Chandra, Santhosh Rajamanickam, Georgios Antoniou, Ekaterina Shutova, and Helen Yannakoudakis. A Multimodal Framework for the Detection of Hateful Memes. *ArXiv preprint*, abs/2012.12871, 2020. URL <https://arxiv.org/abs/2012.12871>.

-
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. RoBERTa: A Robustly Optimized BERT Pre-training Approach. *ArXiv preprint*, abs/1907.11692, 2019. URL <https://arxiv.org/abs/1907.11692>.
- Thomas Mandl, Sandip Modha, Prasenjit Majumder, Daksh Patel, Mohana Dave, Chintak Mandlia, and Aditya Patel. Overview of the HASOC Track at FIRE 2019: Hate Speech and Offensive Content Identification in Indo-European Languages. In *Proceedings of the 11th Forum for Information Retrieval Evaluation*, FIRE '19, pp. 14–17, Kolkata, India, 2019. ISBN 9781450377508.
- M. McCord and M. Chuah. Spam Detection on Twitter Using Traditional Classifiers. In *Proceedings of the 8th International Conference on Autonomic and Trusted Computing*, ATC'11, pp. 175–186, Banff, Canada, 2011. ISBN 9783642234958.
- Todor Mihaylov and Preslav Nakov. Hunting for troll comments in news community forums. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 399–405, Berlin, Germany, 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-2065. URL <https://aclanthology.org/P16-2065>.
- Todor Mihaylov, Georgi Georgiev, and Preslav Nakov. Finding opinion manipulation trolls in news community forums. In *Proceedings of the Nineteenth Conference on Computational Natural Language Learning*, pp. 310–314, Beijing, China, 2015a. Association for Computational Linguistics. doi: 10.18653/v1/K15-1032. URL <https://aclanthology.org/K15-1032>.
- Todor Mihaylov, Ivan Koychev, Georgi Georgiev, and Preslav Nakov. Exposing paid opinion manipulation trolls. In *Proceedings of the International Conference Recent Advances in Natural Language Processing*, pp. 443–450, Hissar, Bulgaria, 2015b. INCOMA Ltd. Shoumen, BULGARIA. URL <https://aclanthology.org/R15-1058>.
- Todor Mihaylov, Tsvetomila Mihaylova, Preslav Nakov, Lluís Màrquez, Georgi Georgiev, and Ivan Koychev. The Dark Side of News Community Forums: Opinion Manipulation Trolls. *Internet Research*, 28(5):1292–1312, 2018.
- Alexandros Mittos, Savvas Zannettou, Jeremy Blackburn, and Emiliano De Cristofaro. "And We Will Fight for Our Race!" A Measurement Study of Genetic Testing Conversations on Reddit and 4chan. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 14, pp. 452–463, New York, New York, USA, 2020.
- Hamdy Mubarak, Ammar Rashed, Kareem Darwish, Younes Samih, and Ahmed Abdelali. Arabic offensive language on Twitter: Analysis and experiments. In *Proceedings of the Sixth Arabic Natural Language Processing Workshop*, pp. 126–135, Kyiv, Ukraine (Virtual), 2021. Association for Computational Linguistics. URL <https://aclanthology.org/2021.wanlp-1.13>.
- Niklas Muennighoff. Vilio: State-of-the-art Visio-Linguistic Models applied to Hateful Memes. *ArXiv preprint*, abs/2012.07788, 2020. URL <https://arxiv.org/abs/2012.07788>.
- Preslav Nakov, Tsvetomila Mihaylova, Lluís Màrquez, Yashkumar Shiroya, and Ivan Koychev. Do not trust the trolls: Predicting credibility in community question answering forums. In *Proceedings of the International Conference Recent Advances in Natural Language Processing, RANLP 2017*, pp. 551–560, Varna, Bulgaria, 2017. INCOMA Ltd. doi: 10.26615/978-954-452-049-6_072. URL https://doi.org/10.26615/978-954-452-049-6_072.
- Preslav Nakov, Alberto Barrón-Cedeño, Giovanni Da San Martino, Firoj Alam, Julia Maria Struß, Thomas Mandl, Rubén Míguez, Tommaso Caselli, Mucahid Kutlu, Wajdi Zaghouani, Chengkai Li, Shaden Shaar, Gautam Kishore Shahi, Hamdy Mubarak, Alex Nikolov, Nikolay Babulkov, Yavuz Selim Kartal, and Javier Beltrán. The CLEF-2022 CheckThat! lab on fighting the COVID-19 infodemic and fake news detection. In *Advances in Information Retrieval*, pp. 416–428, 2022. ISBN 978-3-030-99739-7.
- BBC News. TikTok and Twitch face fines under new Ofcom rules, 2021.
- F. Javier Ortega, José A. Troyano, Fermín L. Cruz, Carlos G. Vallejo, and Fernando Enríquez. Propagation of trust and distrust for the detection of trolls in a social network. *Computer Networks*, 56(12):2884–2895, 2012. ISSN 1389-1286.

-
- Nedjma Ousidhoum, Zizheng Lin, Hongming Zhang, Yangqiu Song, and Dit-Yan Yeung. Multilingual and multi-aspect hate speech analysis. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 4675–4684, Hong Kong, China, 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1474. URL <https://aclanthology.org/D19-1474>.
- Matthew E. Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep contextualized word representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 2227–2237, New Orleans, Louisiana, 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1202. URL <https://aclanthology.org/N18-1202>.
- Zesis Pitenis, Marcos Zampieri, and Tharindu Ranasinghe. Offensive language identification in Greek. In *Proceedings of the 12th Language Resources and Evaluation Conference*, pp. 5113–5119, Marseille, France, 2020. European Language Resources Association. ISBN 979-10-95546-34-4. URL <https://aclanthology.org/2020.lrec-1.629>.
- Shraman Pramanick, Dimitar Dimitrov, Rituparna Mukherjee, Shivam Sharma, Md. Shad Akhtar, Preslav Nakov, and Tanmoy Chakraborty. Detecting harmful memes and their targets. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 2783–2796, Online, 2021a. Association for Computational Linguistics. doi: 10.18653/v1/2021.findings-acl.246. URL <https://aclanthology.org/2021.findings-acl.246>.
- Shraman Pramanick, Shivam Sharma, Dimitar Dimitrov, Md. Shad Akhtar, Preslav Nakov, and Tanmoy Chakraborty. MOMENTA: A multimodal framework for detecting harmful memes and their targets. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pp. 4439–4455, Punta Cana, Dominican Republic, 2021b.
- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI Blog*, 2019.
- Tharindu Ranasinghe and Marcos Zampieri. Multilingual offensive language identification with cross-lingual embeddings. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 5838–5844, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.470. URL <https://aclanthology.org/2020.emnlp-main.470>.
- H. Rosa, N. Pereira, R. Ribeiro, P.C. Ferreira, J.P. Carvalho, S. Oliveira, L. Coheur, P. Paulino, A.M. Veiga Simão, and I. Trancoso. Automatic cyberbullying detection: A systematic review. *Computers in Human Behavior*, 93:333–345, 2019. ISSN 0747-5632.
- Sara Rosenthal, Pepa Atanasova, Georgi Karadzhev, Marcos Zampieri, and Preslav Nakov. SOLID: A large-scale semi-supervised dataset for offensive language identification. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 915–928, Online, 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.findings-acl.80. URL <https://aclanthology.org/2021.findings-acl.80>.
- David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning representations by back-propagating errors. *Nature*, 323(6088):533–536, 1986.
- Benet Oriol Sabat, Cristian Canton Ferrer, and Xavier Giro-i Nieto. Hate speech in pixels: Detection of offensive memes towards automatic moderation. *ArXiv preprint*, abs/1910.02334, 2019. URL <https://arxiv.org/abs/1910.02334>.
- Semiu Salawu, Yulan He, and Joanna Lumsden. Approaches to Automated Detection of Cyberbullying: A Survey. *IEEE Transactions on Affective Computing*, 11(1):3–24, 2017.
- Geetika Sarna and MPS Bhatia. Content based approach to find the credibility of user in social networks: an application of cyberbullying. *IJMLC*, 8(2):677–689, 2017.

-
- Sheikh Muhammad Sarwar and Vanessa Murdock. Unsupervised Domain Adaptation for Hate Speech Detection Using a Data Augmentation Approach. In *16th International Conference on Web and Social Media, ICWSM '22*, Atlanta, Georgia and Online, 2022.
- Sheikh Muhammad Sarwar, Dimitrina Zlatkova, Momchil Hardalov, Yoan Dinkov, Isabelle Augenstein, and Preslav Nakov. A neighborhood framework for resource-lean content flagging. *Transactions of the Association for Computational Linguistics*, 10:484–502, 2022. doi: 10.1162/tacl.a.00472. URL <https://aclanthology.org/2022.tacl-1.28>.
- Anna Schmidt and Michael Wiegand. A survey on hate speech detection using natural language processing. In *Proceedings of the Fifth International Workshop on Natural Language Processing for Social Media*, pp. 1–10, Valencia, Spain, 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-1101. URL <https://aclanthology.org/W17-1101>.
- Chun Wei Seah, Hai Leong Chieu, Kian Ming A. Chai, Loo-Nin Teow, and Lee Wei Yeong. Troll detection by domain-adapting sentiment analysis. In *2015 18th International Conference on Information Fusion (Fusion)*, FUSION '15, pp. 792–799, Washington, DC, USA, 2015.
- Fabrizio Sebastiani. Machine Learning in Automated Text Categorization. *ACM Comput. Surv.*, 34(1):1–47, 2002. ISSN 0360-0300.
- Baris Sezer, Ramazan Yilmaz, and Fatma Gizem Karaoglan Yilmaz. Cyber bullying and teachers' awareness. *Internet Research*, 25(4):674–687, 2015.
- Shivam Sharma, Md Shad Akhtar, Preslav Nakov, and Tanmoy Chakraborty. DISARM: Detecting the victims targeted by harmful memes. In *Findings of NAACL*, Seattle, Washington, 2022.
- Gudbjartur Ingi Sigurbergsson and Leon Derczynski. Offensive language and hate speech detection for Danish. In *Proceedings of the 12th Language Resources and Evaluation Conference*, pp. 3498–3508, Marseille, France, 2020. European Language Resources Association. ISBN 979-10-95546-34-4. URL <https://aclanthology.org/2020.lrec-1.430>.
- Weijie Su, Xizhou Zhu, Yue Cao, Bin Li, Lewei Lu, Furu Wei, and Jifeng Dai. VL-BERT: pre-training of generic visual-linguistic representations. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL <https://openreview.net/forum?id=SygXPaEYvH>.
- Hao Tan and Mohit Bansal. LXMERT: Learning cross-modality encoder representations from transformers. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 5100–5111, Hong Kong, China, 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1514. URL <https://aclanthology.org/D19-1514>.
- Sahana Udupa, Antonis Maronikolakis, Hinrich Schütze, and Axel Wisiolek. Ethical Scaling for Content Moderation: Extreme Speech and the (In)Significance of Artificial Intelligence, 2022.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5998–6008, 2017. URL <https://proceedings.neurips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html>.
- Munsif Vengattil and Elizabeth Culliford. Facebook allows war posts urging violence against Russian invaders, 2022.
- Bertie Vidgen and Leon Derczynski. Directions in abusive language training data, a systematic review: Garbage in, garbage out. *PLOS ONE*, 15(12):1–32, 2021.
- Zeerak Waseem and Dirk Hovy. Hateful symbols or hateful people? predictive features for hate speech detection on Twitter. In *Proceedings of the NAACL Student Research Workshop*, pp. 88–93, San Diego, California, 2016. Association for Computational Linguistics. doi: 10.18653/v1/N16-2013. URL <https://aclanthology.org/N16-2013>.

-
- Zeeraq Waseem, Thomas Davidson, Dana Warmusley, and Ingmar Weber. Understanding abuse: A typology of abusive language detection subtasks. In *Proceedings of the First Workshop on Abusive Language Online*, pp. 78–84, Vancouver, BC, Canada, 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-3012. URL <https://aclanthology.org/W17-3012>.
- Michael Wiegand, Melanie Siegel, and Josef Ruppenhofer. Overview of the GermEval 2018 Shared Task on the Identification of Offensive Language. In *14th Conference on Natural Language Processing KONVENS 2018*, Vienna, Austria, 2018.
- Randy YM Wong, Christy MK Cheung, and Bo Xiao. Does gender matter in cyberbullying perpetration? An empirical investigation. *Computers in Human Behavior*, 79:247–257, 2018. ISSN 0747-5632.
- Ellery Wulczyn, Nithum Thain, and Lucas Dixon. Ex machina: Personal attacks seen at scale. In Rick Barrett, Rick Cummings, Eugene Agichtein, and Evgeniy Gabrilovich (eds.), *Proceedings of the 26th International Conference on World Wide Web, WWW 2017, Perth, Australia, April 3-7, 2017*, pp. 1391–1399. ACM, 2017. doi: 10.1145/3038912.3052591. URL <https://doi.org/10.1145/3038912.3052591>.
- Jun-Ming Xu, Kwang-Sung Jun, Xiaojin Zhu, and Amy Bellmore. Learning from bullying traces in social media. In *Proceedings of the 2012 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 656–666, Montréal, Canada, 2012. Association for Computational Linguistics. URL <https://aclanthology.org/N12-1084>.
- Fei Yu, Jiji Tang, Weichong Yin, Yu Sun, Hao Tian, Hua Wu, and Haifeng Wang. ERNIE-ViL: Knowledge Enhanced Vision-Language Representations through Scene Graphs. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 3208–3216, Virtual, 2021.
- Marcos Zampieri, Shervin Malmasi, Preslav Nakov, Sara Rosenthal, Noura Farra, and Ritesh Kumar. Predicting the type and target of offensive posts in social media. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 1415–1420, Minneapolis, Minnesota, 2019a. Association for Computational Linguistics. doi: 10.18653/v1/N19-1144. URL <https://aclanthology.org/N19-1144>.
- Marcos Zampieri, Shervin Malmasi, Preslav Nakov, Sara Rosenthal, Noura Farra, and Ritesh Kumar. SemEval-2019 task 6: Identifying and categorizing offensive language in social media (OffensEval). In *Proceedings of the 13th International Workshop on Semantic Evaluation*, pp. 75–86, Minneapolis, Minnesota, USA, 2019b. Association for Computational Linguistics. doi: 10.18653/v1/S19-2010. URL <https://aclanthology.org/S19-2010>.
- Marcos Zampieri, Preslav Nakov, Sara Rosenthal, Pepa Atanasova, Georgi Karadzhov, Hamdy Mubarak, Leon Derczynski, Zeses Pitenis, and Çağrı Çöltekin. SemEval-2020 task 12: Multilingual offensive language identification in social media (OffensEval 2020). In *Proceedings of the Fourteenth Workshop on Semantic Evaluation*, pp. 1425–1447, Barcelona (online), 2020. International Committee for Computational Linguistics. URL <https://aclanthology.org/2020.semeval-1.188>.
- Weibo Zhang, Guihua Liu, Zhuohua Li, and Fuqing Zhu. Hateful Memes Detection via Complementary Visual and Linguistic Networks. *ArXiv preprint*, abs/2012.04977, 2020. URL <https://arxiv.org/abs/2012.04977>.
- Luowei Zhou, Hamid Palangi, Lei Zhang, Houdong Hu, Jason Corso, and Jianfeng Gao. Unified vision-language pre-training for image captioning and VQA. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 13041–13049, New York, New York, USA, 2020.
- Ron Zhu. Enhance Multimodal Transformer With External Label And In-Domain Pretrain: Hateful Meme Challenge Winning Solution. *ArXiv preprint*, abs/2012.08290, 2020. URL <https://arxiv.org/abs/2012.08290>.