# A Comparative Study on Language Models for Task-Oriented Dialogue Systems

Vinsen Marselino Andreas

SEEI

Institut Teknologi Bandung

U-CoE AI-VLB

Bandung, Indonesia
vinsenmarselino@gmail.com

Genta Indra Winata

ECE

HKUST

Clear Water Bay, Hong Kong
giwinata@connect.ust.hk

Ayu Purwarianti
SEEI
Institut Teknologi Bandung
U-CoE AI-VLB
Bandung, Indonesia
ayu@informatika.org

Abstract—The recent development of language models has shown promising results by achieving state-of-the-art performance on various natural language tasks by fine-tuning pretrained models. In task-oriented dialogue (ToD) systems, language models can be used for end-to-end training without relying on dialogue state tracking to track the dialogue history but allowing the language models to generate responses according to the context given as input. This paper conducts a comparative study to show the effectiveness and strength of using recent pretrained models for fine-tuning, such as BART and T5, on endto-end ToD systems. The experimental results show substantial performance improvements after language model fine-tuning. The models produce more fluent responses after adding knowledge to the context that guides the model to avoid hallucination and generate accurate entities in the generated responses. Furthermore, we found that BART and T5 outperform GPT-based models in BLEU and F1 scores and achieve state-of-the-art performance in a ToD system.

Index Terms—language model, end-to-end, task-oriented dialogue system

#### I. INTRODUCTION

Dialogue systems are developed to support human-to-human interactions in the natural language [1], and they are widely used in many applications, such as flight booking and hotel reservations. The task-oriented dialogue (ToD) systems commonly rely on modularized systems that use natural language understanding (NLU) to get input's meaning, separately with dialogue state tracking (DST) to track dialogue state and natural language generation (NLG) to generate suitable output. The benefit of applying this is the efficiency in training and inference during deployment. Recently, [2] show the possibility to utilize end-to-end models to replace the modularized systems, and they perform with decent performance. To implement end-to-end ToD dialogue systems, there are two main ideas: (1) put knowledge base (KB) as input directly into the model [3]. (2) develop a retrieval module to retrieve suitable knowledge from KB according to the input [4]. On the other line of work, [2], [5] utilized KB by augmenting samples using delexicalized templates. By applying this method, the trained model could learn the KB directly from the training dataset. By adding more datasets, the models can learn to utilize the knowledge in the context as input. <sup>1</sup> The previous work has been focused on GPT-2 models as the pre-trained language models. However, there is no study yet on other language models, such as BART [6] and T5 [7]. Both models are built with encoder-decoder architecture differently to GPT-2 that uses a decoder-only model. While, encoder-decoder models are utilized to develop end-to-end dialogue systems [8], [9]. The model accepts the input with the dialogue history and query and generates responses based on the context.

In this paper, we propose a comparative study to investigate the strength of language models for ToD systems. We also incorporate knowledge to the language models by two different methods: (1) applying Knowledge Embedded (KE) Dialogue [2] to leverage KB entities in delexicalized dialogue templates, and (2) adding KB in the input as context. Our experiment shows that some language models perform better than others for end-to-end ToD systems. We found that the models with pre-trained models produce more fluent responses after incorporating knowledge embedded. Furthermore, we found that BART and T5 outperform GPT-2-based models in both BLEU and F1 scores and achieve state-of-the-art performance in the CamRest dataset [9].

# II. METHODOLOGY

In this section, we would describe the task of an end-to-end task-oriented dialogue system and how we prepare the dataset.

# A. Notation and Task

We define a dialogue dataset  $\mathcal{D} = \{D_1, D_2, \cdots, D_n\}$  where each dialogue has user and system utterances or alternating dialogue turns  $D_i = \{U_1, S_1, U_2, S_2, \cdots, U_t, S_t\}$ . For each dialogue sample, we define a query Q and dialogue history H. In the end-to-end dialogue system, we define our generative model as  $\theta$ . The model  $\theta$  takes x = [H, Q] as a concatenation of the dialogue history H and query Q as input, and generates an output response y. The dialogue history H is taken from the previous turns of the query Q. We fine-tune  $\theta$  using the

<sup>1</sup>The code and dataset are available at https://github.com/sen33/end-to-end-dialogue-system

dialogue samples by the conditional generation objective. It trains the model by conditioning to the context. We define the loss as the following:

$$\mathcal{L}(\mathcal{D}) = -\sum_{i}^{n} \log p_{\theta}(s_i|s_{i<1}, x_i), \tag{1}$$

where  $p_{\theta}(s_i|s_{< i},x_i)$  is the conditional probability of generating token  $s_i$  given the previous tokens  $s_{< i}$  and the context  $x_i$ . On the inference time, greedy search are used to generate the response.

# B. Generative Language Models

In this section, we describe the models that are used in this work as the following:

- 1) Sequence-to-sequence: As our baseline model, we train vanilla encoder-decoder models using transformer with multihead attention [10] using OpenNMT toolkit [11]. This toolkit has been widely used for training sequence-to-sequence on NLP tasks [12].
  - 2) Fine-tuning using Pre-trained Models:
- a) Bidirectional and Auto-regressive Transformers (BART): BART [6] is a language model that is trained using the masked language modeling from BERT [13], and denoising objective to recover the perturbed input.
- b) Text-to-Text Transfer Transformer (T5): T5 is an encoder-decoder based language models [7]. This model is trained using BERT [13] training objective by applying the mask to the input tokens.
- 3) Embed Knowledge: To evaluate the effectiveness of adding KB information in the end-to-end ToD systems, we incorporate the knowledge in two ways: (1) the KE Dialogue data augmentation method, and (2) Adding the KB in the context as input, shown in Table I.

#### C. Dataset Preparation

Dataset is prepared by following the KE Dialogue [2]. Fig 1 shows the overall flow of the system. The dialogue template is extracted from each dialogue by delexicalization (KE-DELEX) using the entities from the dialogue ontology. Then, the templates are embedded with entities from knowledge bases to form knowledge embedded dialogue by relexicalization (KE-RELEX). For every question and answer, one dialogue history and target will be generated. To create the representation of dialogue history, each sentence is concatenated with a special token separator. (USR) token is concatenated before user's sentence, and (SYS) token is concatenated before system's sentence. These pairs of dialogue history and target will be the input and target of the trained models. To add KB directly into input, special token (DTA) is concatenated before every entity available from the intermediate API. The example of dialogue history with KB as input is shown in Table I.

#### III. EXPERIMENT

## A. Dataset

We use CamRest dataset [9], a human-to-human dialogues dataset for restaurant recommendation in Cambridge. We

TABLE I EXAMPLE OF DIALOGUE HISTORY WITH KB.

Input	(USR) i would like a moderately priced restaurant in
	the north part of town . (SYS) golden_wok is a mod-
	erately priced restaurant in the north side of town
	. (USR) what type of food does golden_wok serve
	? (DTA) the_nirala 7_milton_road_chesterton north in-
	dian 52.215157,0.125015 01223_360966 moderate cb41uy
	(DTA) golden_wok 191_histon_road_chesterton north chi-
	nese 52.220757,0.111564 01223_350688 moderate cb43hl
Target	the golden_wok serves chinese food . would you like more
	information ?




Fig. 1. The training and evaluation step of KE Dialogue [2].

use a dataset that is already preprocessed and use the code provided by [2] to extract 161 template dialogues and generate Knowledge Embedded Dialogues. 676 dialogues are provided by the CamRest dataset. It is split into 406, 135, and 135 as training data, validation data, and test data, respectively. The templates are generated from training data and augment 9,728 new dialogues to the training data.

#### B. Model Configuration

For each pre-trained model (BART and T5), there are four hyper-parameters configurations. Each configuration is a combination of batch sizes [8, 16] and learning rate [1e-5, 1e-4]. For BART, we use BART<sub>BASE</sub> that has 12 layers, attention heads of 16, 3,072 feed-forward, and 768-dimension embeddings with 139M parameters is used. For T5, we use T5<sub>BASE</sub> that has 24 layers, 12 attention heads, 3,072 feed-forward, and 768-dimension embeddings with 220M parameters is used. Every configuration use 30 epoch with the early stopping method. Early stopping evaluates the BLEU score from the validation dataset every epoch and picks the best one. For sequence-to-sequence with OpenNMT, there are two hyper-parameter configurations with two model sizes (small and large). All Seq2seq configurations use transformer encoder

and decoder. Table II shows the number of parameters of these Seq2seq models. All experiments were conducted on Tesla V100 GPU machines. Adam optimizer is used and learning rate is updated using a linear scheduler.

Parameter	Small model	Large model
Step	100k	50k
Batch size	8	16
Learning rate	6.25e-5	6.25e-5
Layer	12 (6 enc, 6 dec)	12 (6 enc, 6 dec)
Attention head	8	8
Feedforward	1024	3072
Embedding	512	768

#### IV. RESULTS AND ANALYSIS

In this section, we report the results, analyze our findings and ablation study, and conduct a human evaluation to measure the quality of our model's responses.

#### A. Results

TABLE III
RESULTS FOR PRE-TRAINED MODEL WITH DIFFERENT
HYPER-PARAMETERS.

Model	Batch size	Learning rate	BLEU	F1
BART <sub>BASE</sub>	8	1e-5	19.740	46.036
BARTBASE	16	1e-5	19.050	55.922
BART <sub>BASE</sub>	8	1e-4	18.240	56.202
BART <sub>BASE</sub>	16	1e-4	17.930	51.423
T5 <sub>BASE</sub>	8	1e-5	18.140	53.301
T5 <sub>BASE</sub>	16	1e-5	16.490	49.927
T5 <sub>BASE</sub>	8	1e-4	18.330	56.187
T5 <sub>BASE</sub>	16	1e-4	18.730	56.311

The result of the pre-trained model is shown in Table III. For sequence-to-sequence, the smaller model achieves a better BLEU and F1 score. For BART model, the best model was achieved by a model that use batch size of 16 with learning rate of 1e-5. However, the difference between the BLEU and F1 with the best model in each metrics is marginal. For T5 model, the best model is the model with batch size of 16 with learning rate of 1e-4. This model achieves the best score in both BLEU and T5 compared to other T5 models.

TABLE IV RESULT FOR BEST MODEL CONFIGURATION.

Model	Parameter	BLEU	F1
Seq2Seq <sub>SMALL</sub>	33M	17.870	49.304
Seq2Seq <sub>LARGE</sub>	101M	16.220	45.438
BART	139M	19.050	55.922
T5	220M	18.730	56.311

We show the performance of our best models for BART and T5 in Table IV. Both BART and T5 best model use batch size of 16. While BART achieves better BLEU, T5 achieves a better

F1 score. This is caused by how the model was pre-trained. BART is pre-trained by denoising sequence, so the model achieves better BLEU, a metric that shows how fluent the predictions are. Using BART and T5 models for initialization outperform the vanilla sequence-to-sequence model. It implies that pre-trained models have learned the knowledge that are useful for building ToD systems.

TABLE V
COMPARISON OF RESULTS WITH EXISTING WORKS.

Model	BLEU	F1
KB-Transformer [14]	14.80	45.30
MLMN [15]	13.61	54.85
BoSsNet [16]	15.20	43.10
KB-Retriever [4]	18.64	55.76
GPT-2 [2]	13.58	34.69
GPT-2+KB [2]	13.59	50.45
GPT-2+KE [2]	18.00	54.85
Seq2Seq+KE	17.870	49.304
BART+KE	19.050	55.922
T5+KE	18.730	56.311

We show the comparison of our models with the best hyper-parameters setting in Table V. Seq2Seq models achieve worse performance compared to some baselines, especially GPT-2+KE. Both BART and T5 achieve higher BLEU and F1 scores compared to all baselines.

TABLE VI
ABLATION STUDY WITHOUT KB, WITH KB, AND WITH KE.

Model	BLEU	F1
BART	19.100	41.580
BART+KB	20.240	56.704
BART+KE	19.050	55.922

#### B. Ablation Study

To compare the effectiveness of applying KE and KB to the language model, ablation study is conducted. Initially, the BART model is chosen as the base model in the experiment. Then, aside from using BART+KE, we also train a model without any augmentation (BART) and a model using KE (BART+KB). For BART+KB, every entity from intermediate API is concatenated to dialogue history with a special token (DTA). The result is shown in Table VI. BART achieves better BLEU than BART+KE by a slight margin but falls behind in the F1 score to BART+KB and BART+KE. It means that adding KB directly into input or with KE reduces hallucination, a condition where the generated sequence has good structure and meaning but the wrong entity.

#### C. Human Evaluation

Human evaluation is done for BART+KE and BART+KE to further measure the humanness of our generation results. A Likert scale [17] of 1, 3, and 5 are given to all test predictions by experts. Table VII shows the result of this evaluation. It shows that by using KE Dialogues as training data, the trained

model is more robust and more human-like, as demonstrated in Table VII.

TABLE VII Human evaluation for BART+KB and BART+KE.

Model	Likert Score
BART+KB	3.76
BART+KE	4.14

The example of input and output is shown in Table VIII. Each model could generate an answer that is understood by a human. Models tend to directly suggest a restaurant's name instead of asking for specific information.

TABLE VIII
THE EXAMPLES OF THE DIALOGUE INPUT AND OUTPUT ON DIFFERENT MODELS.

Input	(USR) i am looking for a restaurant that is in the	
Input	expensive price range and in the south part of town	
Target	there are results matching your query . would you like	
	mexican, italian, chinese, or indian?	
Seq2Seq	the_good_luck_chinese_food_takeaway serves expensive	
	food in the south part of town.	
BART	peking_restaurant serves <b>expensive food</b> in the <b>south part of</b>	
	town.	
T5	taj_tandoori serves <b>expensive food</b> in the <b>south part of town</b> .	
Input	(USR) i am looking for a restaurant that is in the	
	expensive price range and in the south part of town.	
	⟨SYS⟩ there are results matching your query . would you	
	like mexican, italian, chinese, or indian? (USR) let's	
	go with italian food .	
Target	frankie_and_bennys is an expensive italian eatery in the south	
	part of town . would you like any additional information about	
	this restaurant ?	
Seq2Seq	frankie_and_bennys is an expensive restaurant in the south	
	part of town .	
BART	frankie_and_bennys is an italian restaurant in the south	
	part of town.	
T5	frankie_and_bennys serves italian food in the south part of	
	town. is there anything else i can help you with?	

### V. RELATED WORK

The first task-oriented dialogue system is ELIZA [18], a dialogue system that utilize parsers and rule-based engines. Then, [19] explored developing dialogue systems by utilizing statistical-based methods using POMDP. Along with the development of machine learning, deep learning received a lot of attention from researchers to develop models on modularized dialogue systems, such as NLU [20]-[23], DST [24], [25], and NLG start to utilize deep learning approaches. The specificity of modularized dialogue systems leads to an idea where the DST module is bypassed, which is end-to-end dialogue systems. Handling new domains could be achieved by endto-end dialogue systems with retraining the model, unlike modularized dialogue systems that need to change the DST. To handle KB in the end-to-end dialogue systems, there are two main ideas, using KB directly as input [3] or using intermediate API to retrieve correct KB [4]. [2] propose

another idea where KBs are embedded into dialogue templates to form KE Dialogue and achieve promising results.

#### VI. CONCLUSION

This paper shows the effectiveness of applying pre-trained language models for fine-tuning end-to-end task-oriented dialogue systems and incorporating knowledge bases as context. Using pre-trained language models is essential for initialization to improve the generation results in terms of fluency. Moreover, adding KB to the context improves the correctness by reducing the hallucination. We found that BART and T5 models achieve state-of-the-art performance with higher BLEU and F1 scores compared to GPT-2 models with very similar sizes.

#### ACKNOWLEDGMENT

This research is partially funded by Center for Artificial Intelligence of Institut Teknologi Bandung.

#### REFERENCES

- D. Jurafsky and J. H. Martin, Speech and language processing: an introduction to natural language processing, computational linguistics, and speech recognition. Upper Saddle River, N.J.: Pearson Prentice Hall, 2009.
- [2] A. Madotto, S. Cahyawijaya, G. I. Winata, Y. Xu, Z. Liu, Z. Lin, and P. Fung, "Learning knowledge bases with parameters for task-oriented dialogue systems," in *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: Findings*, 2020, pp. 2372–2394.
- [3] A. Madotto, C.-S. Wu, and P. Fung, "Mem2seq: Effectively incorporating knowledge bases into end-to-end task-oriented dialog systems," in Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), 2018, pp. 1468–1478.
- [4] L. Qin, Y. Liu, W. Che, H. Wen, Y. Li, and T. Liu, "Entity-consistent end-to-end task-oriented dialogue system with kb retriever," in *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, 2019, pp. 133–142.
- [5] C.-S. Wu, A. Madotto, G. I. Winata, and P. Fung, "End-to-end dynamic query memory network for entity-value independent task-oriented dialog," in 2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2018, pp. 6154–6158.
- [6] M. Lewis, Y. Liu, N. Goyal, M. Ghazvininejad, A. Mohamed, O. Levy, V. Stoyanov, and L. Zettlemoyer, "Bart: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension," in *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, 2020, pp. 7871–7880.
- [7] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, "Exploring the limits of transfer learning with a unified text-to-text transformer," *Journal of Machine Learning Research*, vol. 21, no. 140, pp. 1–67, 2020.
- [8] I. Serban, A. Sordoni, Y. Bengio, A. Courville, and J. Pineau, "Building end-to-end dialogue systems using generative hierarchical neural network models," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 30, no. 1, 2016.
- [9] T. Wen, D. Vandyke, N. Mrkšíc, M. Gašíc, L. Rojas-Barahona, P. Su, S. Ultes, and S. Young, "A network-based end-to-end trainable task-oriented dialogue system," in 15th Conference of the European Chapter of the Association for Computational Linguistics, EACL 2017-Proceedings of Conference, vol. 1, 2017, pp. 438–449.
- [10] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," in *Advances in neural information processing systems*, 2017, pp. 5998–6008.
- [11] G. Klein, Y. Kim, Y. Deng, J. Senellart, and A. Rush, "OpenNMT: Open-source toolkit for neural machine translation," in *Proceedings of ACL 2017, System Demonstrations*. Vancouver, Canada: Association for Computational Linguistics, Jul. 2017, pp. 67–72. [Online]. Available: https://www.aclweb.org/anthology/P17-4012

- [12] F. J. Muis and A. Purwarianti, "Sequence-to-sequence learning for indonesian automatic question generator," in 2020 7th International Conference on Advance Informatics: Concepts, Theory and Applications (ICAICTA). IEEE, 2020, pp. 1–6.
- [13] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "Bert: Pre-training of deep bidirectional transformers for language understanding," in NAACL-HLT (1), 2019.
- [14] E. Haihong, W. Zhang, and M. Song, "Kb-transformer: Incorporating knowledge into end-to-end task-oriented dialog systems," in 2019 15th International Conference on Semantics, Knowledge and Grids (SKG). IEEE, 2019, pp. 44–48.
- [15] R. Reddy, D. Contractor, D. Raghu, and S. Joshi, "Multi-level memory for task oriented dialogs," in *Proceedings of NAACL-HLT*, 2019, pp. 3744–3754.
- [16] D. Raghu, N. Gupta et al., "Disentangling language and knowledge in task-oriented dialogs," in Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), 2019, pp. 1239–1255.
- [17] I. E. Allen and C. A. Seaman, "Likert scales and data analyses," *Quality progress*, vol. 40, no. 7, pp. 64–65, 2007.
- [18] J. Weizenbaum, "Eliza—a computer program for the study of natural language communication between man and machine," *Communications of the ACM*, vol. 9, no. 1, pp. 36–45, 1966.
- [19] S. Young, M. Gašić, B. Thomson, and J. D. Williams, "Pomdp-based statistical spoken dialog systems: A review," *Proceedings of the IEEE*, vol. 101, no. 5, pp. 1160–1179, 2013.
- [20] D. Hakkani-Tür, G. Tur, A. Celikyilmaz, Y.-N. Chen, J. Gao, L. Deng, and Y.-Y. Wang, "Multi-domain joint semantic frame parsing using bi-directional rnn-lstm," *Interspeech 2016*, pp. 715–719, 2016.
- [21] Y.-N. Chen, D. Hakkani-Tür, G. Tur, J. Gao, and L. Deng, "End-to-end memory networks with knowledge carryover for multi-turn spoken language understanding," *Interspeech* 2016, pp. 3245–3249, 2016.
- [22] C.-W. Goo, G. Gao, Y.-K. Hsu, C.-L. Huo, T.-C. Chen, K.-W. Hsu, and Y.-N. Chen, "Slot-gated modeling for joint slot filling and intent prediction," in *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers)*, 2018, pp. 753–757.
- [23] Z. Liu, G. I. Winata, Z. Lin, P. Xu, and P. Fung, "Attention-informed mixed-language training for zero-shot cross-lingual task-oriented dialogue systems," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 34, no. 05, 2020, pp. 8433–8440.
- [24] C.-S. Wu, A. Madotto, E. Hosseini-Asl, C. Xiong, R. Socher, and P. Fung, "Transferable multi-domain state generator for task-oriented dialogue systems," in *Proceedings of the 57th Annual Meeting of the* Association for Computational Linguistics, 2019, pp. 808–819.
- [25] Z. Lin, A. Madotto, G. I. Winata, and P. Fung, "Mintl: Minimalist transfer learning for task-oriented dialogue systems," in *Proceedings* of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2020, pp. 3391–3405.