Quantum Complexity of Weighted Diameter and Radius in CONGEST Networks

Xudong Wu^{*} Penghui Yao[†]

September 27, 2022

Abstract

This paper studies the round complexity of computing the weighted diameter and radius of a graph in the quantum CONGEST model. We present a quantum algorithm that (1 + o(1))-approximates the diameter and radius with round complexity \tilde{O} (min { $n^{9/10}D^{3/10},n$ }), where D denotes the unweighted diameter. This exhibits the advantages of quantum communication over classical communication since computing a $(3/2 - \varepsilon)$ -approximation of the diameter and radius in a classical CONGEST network takes $\tilde{\Omega}(n)$ rounds, even if D is constant [2]. We also prove a lower bound of $\tilde{\Omega}(n^{2/3})$ for $(3/2 - \varepsilon)$ -approximating the weighted diameter/radius in quantum CONGEST networks, even if D = $\Theta(\log n)$. Thus, in quantum CONGEST networks, computing weighted diameter and weighted radius of graphs with small D is strictly harder than unweighted ones due to Le Gall and Magniez's $\tilde{O}(\sqrt{nD})$ -round algorithm for unweighted diameter/radius [12].

1 Introduction

Quantum distributed computing has received great attention in the past decade [4, 24, 10, 12, 13, 18, 19, 7, 20, 14]. A large body of work has been devoted to investigating the quantum advantages in distributed computing. In this paper, we are concerned with the CONGEST networks, which are one of the most fundamental models in distributed computing. In a classical CONGEST network, the nodes synchronously exchange classical messages, and each channel has O(log n)-bit bandwidth, where n is the number of nodes in the network. Quantum CONGEST networks were first introduced by Elkin, Klauck, Nanongkai, and Pandurangan [10], where the only difference is that the nodes exchange quantum messages and the bandwidth of each channel is O(log n) qubits. The round complexity of diameter and radius of unweighted graphs in classical CONGEST networks has been extensively studied [2, 3, 17, 22, 11, 15]. Le Gall and Magniez [12] proved that quantum communication may save the round complexity in CONGEST networks if the graph has a low diameter.

In this paper, we further investigate the round complexity of computing the diameters and radius of weighted graphs in quantum CONGEST networks. We prove that quantum communication may also save the round complexity for both problems.

^{*}Nanjing University. Email: xdwu@smail.nju.edu.cn

[†]Nanjing University. Email: pyao@nju.edu.cn

1.1 Our Results

The following is one of our main results which asserts that quantum communication may save the round complexity for computing the weighted diameter and radius of a graph given that the graph has a low unweighted diameter.

Theorem 1.1. There exists a $\widetilde{O}(\min\{n^{9/10}D^{3/10},n\})$ -round distributed algorithm computing a (1 + o(1))-approximation of the weighted diameter/radius with probability at least 1-1/poly(n), in the quantum CONGEST model, where D denotes the unweighted diameter.

Holzer and Pinsker in [16] and Abboud, Censor-Hillel and Khoury in [2] proved that (2-o(1))-approximating the diameter and $(3/2-\varepsilon)$ -approximating the (even unweighted) radius in the classical CONGEST network require $\tilde{\Omega}(n)$ rounds, even when D is constant. Therefore, Theorem 1.1 exhibits the advantages of quantum communication over classical communication in approximating the weighted diameter/radius when D = $o(n^{1/3})$.

We prove Theorem 1.1 by applying the framework of distributed quantum optimization introduced by Le Gall and Magniez in [12]. Note that the diameter and radius are the maximum and minimum of eccentricities respectively. It will not give a sublinear-time algorithm if we simply apply a quantum search algorithm, because evaluating the eccentricity of one node takes $\tilde{\Theta}(\sqrt{n})$ rounds (the lower bound is due to [10]), and the searching process should require another $\tilde{\Theta}(\sqrt{n})$ times of evaluation (the number of nodes with maximum/minimum eccentricity maybe O(1)). Thus the number of rounds in total will be $\tilde{\Theta}(n)$.¹ Our algorithm is inspired by Nanongkai's algorithm [21] for approximating the weighted shortest paths in a classical network. The algorithm constructs several small vertex sets and searches the node achieving the maximum/minimum eccentricity within those sets, which turns out to be a good approximation of diameter/radius. Our algorithm quantizes Nanongkai's algorithm using the standard technique [5] and further combines with the framework of distributed quantum optimization in [12].

We also prove lower bounds for approximating weighted diameter and radius.

Theorem 1.2. Any algorithm computing a (3/2 - o(1))-approximation of the weighted diameter/radius requires $\widetilde{\Omega}(n^{2/3})$ rounds, in the quantum CONGEST model, even when $D = \Theta(\log n)$.

The hardness of both problems is proved via the communication complexity of quantum Server models. The Server model is a variant of two-party communication complexity models introduced in [10]. Combining with the graph gadget in [2], we get a reduction from the communication complexity of certain read-once functions to the round complexity of approximating the weighted diameter and radius. We further apply a lifting theorem of quantum communication complexity [10] to obtain the desired lower bounds.

Compared with Le Gall and Magniez's algorithm [12] for unweighted diameter/radius with $\tilde{O}(\sqrt{nD})$ rounds, Theorem 1.2 says that computing weighted diameter/radius is strictly harder than unweighted diameter/radius, when D is small. While in the classical setting, computing weighted and unweighted diameter/radius have the same round complexity $\Theta(n)$ [2, 6]².

1.2 Related Works

A series of works started with the distance computation in the classical CONGEST network. Earlier, Frischknecht, Holzer, and Wattenhofer [11] showed that computing the diameter of an un-

 $^{{}^{1}}O(\cdot)$, $\Omega(\cdot)$, and $\Theta(\cdot)$ hide polylogarithmic factors.

²The lower bound is proved in [2]. The upper bound is followed from the $\tilde{O}(n)$ -round algorithm for the exact weighted All-Pairs Shortest Paths (APSP) in [6].

Problem	Variant	Approx.	U	Supper bound $\widetilde{O}(\cdot)$	Lower bound $\widetilde{\Omega}(\cdot)$	
Tioblein			Classical	Quantum	Classical	Quantum
		exact	n [17, 22]	√ nD [12]	n [11]	$\sqrt[3]{nD^2} + \sqrt{n}$ [20]
diameter		$3/2 - \epsilon$	n	\sqrt{nD}	n [2]	$\sqrt{n} + D$ [12]
		3/2	$\sqrt{n} + D$ [15, 3]	$\sqrt[3]{nD} + D$ [12]	open	open
	weighted	exact	n [6]	n	n	n ^{2/3}
	weighted	(1,3/2)	n	$\min \left\{ n^{9/10} D^{3/10}, n \right\}$ (This work)	n	$n^{2/3}$ (This work)
	weighted	$2-\epsilon$	n	$\min \left\{ n^{9/10} D^{3/10}, n \right\}$	n [16]	$\sqrt{n} + D$
	weighted	2	$\sqrt{n}D^{1/4} + D$ [8]	$\sqrt{n}D^{1/4} + D$	open	open
radius		exact	n [17, 22]	\sqrt{nD}	n	$\sqrt[3]{nD^2} + \sqrt{n}$
		$3/2 - \epsilon$	n	\sqrt{nD}	n [2]	$\sqrt{n} + D$
		3/2	\sqrt{n} + D [3]	$\sqrt{n} + D$	open	open
	weighted	exact	n [6]	n	n	n ^{2/3}
	weighted	(1,3/2)	n	min $\left\{ n^{9/10} D^{3/10}, n \right\}$ (This work)	n	$n^{2/3}$ (This work)
	weighted	2	$\sqrt{n}D^{1/4} + D \ [8]$	$\sqrt{n}D^{1/4} + D$	open	open

Table 1: Complexity of computing diameter and radius in the CONGEST model.

weighted graph with constant diameter requires $\tilde{\Omega}(n)$ rounds, which is tight up to logarithmic factors since even computing All-Pairs Shortest Paths (ASAP) on an unweighted graph can be resolved in O(n) rounds [17, 22]. Abboud, Censor-Hillelet, and Khoury [2] later gave the same lower bound of $\tilde{\Omega}(n)$ for $(3/2 - \varepsilon)$ -approximating the diameter/radius in sparse networks. Bernstein and Nanongkai [6] provided a $\tilde{O}(n)$ -round algorithm computing the exact APSP on any weighted graph. As a result, computing unweighted diameter/radius and weighted diameter/radius (exactly or with a small approximation ratio) have an almost tight complexity of $\tilde{\Theta}(n)$ in the classical CONGEST network. If a larger approximation ratio is allowed, there are $\tilde{O}(\sqrt{n} + D)$ -round algorithms for 3/2-approximating the diameter/radius on any unweighted graph [15, 3]. Besides, Chechik and Mukhtar [8] showed a $\tilde{O}(\sqrt{n}D^{1/4} + D)$ -round algorithm computing Single-Source Shortest Paths (SSSP) exactly on any weighted graph, which also gives a 2-approximation of the diameter/radius.

As for the quantum setting, while quantum computation offers advantages over classical computation in various settings such as query complexity and two-party communication complexity, the power of quantum computation in distributed computing has not been fully explored. In the quantum CONGEST network, Elkin et al. [10] gave negative results for several problems such as minimum spanning tree, minimum cut, and SSSP, i.e., quantum communication does not speed up distributed algorithms for these problems. Le Gall and Magniez [12] presented a $\widetilde{O}(\sqrt{nD})$ -round algorithm computing the diameter/radius on any unweighted graph, along with a $\widetilde{O}(\sqrt[3]{nD} + D)$ -round algorithm 3/2-approximating the diameter. They also proved a $\widetilde{\Omega}(\sqrt{n} + D)$ -lower bound for computing the unweighted diameter, which was later improved to $\widetilde{\Omega}(\sqrt[3]{nD^2} + \sqrt{n})$ by Magniez and Nayak [20]. The above results are listed on Table 1.

2 Preliminaries

2.1 Graph Notations

Given a weighted graph (G, w) where G = (V, E) and $w : E \to \mathbb{N}^+$. The length of a path is defined to be the sum of weights of edges on it, and the distance between nodes u and v, denoted by $d_{G,w}(u,v)$, is the least length over all paths between them. The eccentricity of a node u is denoted by $e_{G,w}(u) = \max_{v \in V} d_{G,w}(u,v)$. The radius of weighted graph (G,w), denoted by $R_{G,w}$, is the minimum eccentricity over all nodes, i.e., $R_{G,w} = \min_{u \in V} e_{G,w}(u)$, while the diameter of (G,w), denoted by $D_{G,w}$, is the maximum eccentricity of nodes, or equally, the maximum distance between any two nodes, i.e., $D_{G,w} = \max_{u \in V} e_{G,w}(u) = \max_{u,v \in V} d_{G,w}(u,v)$. The unweighted diameter of graph G is denoted by $D_G = D_{G,w^*}$ where $w^*(e) = 1$ for all $e \in E$, which is an essential parameter when G represents the underlying graph of a distributed network.

2.2 CONGEST Model

In the classical CONGEST model, the communication network is a graph G = (V, E) with n nodes, and every node is assigned with a unique identifier. Each node represents a processor with unlimited computational power, i.e., the consumption of any local computation in a single processor is ignored. Each edge connecting two nodes represents a communication channel with $B = O(\log n)$ bits of bandwidth. In this article, we further consider the weighted graph (G, w) as underlying network, where the weight of each edge is initially known to both of its endpoints.

For quantum version of the CONGEST model defined in [10], adjacent nodes are allowed to exchange *qubits* (quantum bits), i.e., the classical channels are now quantum channels with the same bandwidth $B = O(\log n)$. Each node can locally do some quantum computation, and distinct nodes may own qubits with entanglement. In this paper, we assume that initially all nodes do not share any entanglement, but the nodes can, for example, locally create a pair of entangled qubits, and send one to others.

For both classical and quantum CONGEST models, the algorithm is implemented round by round in a synchronous manner. In each round, each node sends/receives a message of $O(\log n)$ (qu)bits to/from each neighbor, and then does local computation according to local knowledge. The algorithm halts when all nodes halt, and at the end of the algorithm, each node has its own output. We say an algorithm computes the diameter/radius if all nodes output the correct answer. The round complexity of an algorithm in this model is defined to be the number of communication rounds needed. And the round complexity of a distributed problem is the least round complexity of any algorithm solving it. Our focus here is the distance problems, mainly the computation of diameter and radius mentioned in Section 2.1.

2.3 Server Model

The Sever model is a variant of the two-party communication model, which was introduced by Elkin et al. [10] to prove lower bounds in the CONGEST model. There are three players in the Server model: Alice, Bob, and the server. Alice and Bob receive the inputs x and y respectively, and want to compute F(x, y) for some function F. The server receives no input. Alice and Bob can exchange messages with the server. The catch here is that the server can send messages for free. Thus, the communication complexity counts only messages sent by Alice and Bob. Note that Alice and Bob can talk to each other by considering the server as a communication channel, so any protocol in the traditional two-party communication model can be implemented in the Server model with the same complexity.

For a two-argument function F and $0 \le \varepsilon < 1$, we let $Q_{\varepsilon}^{sv}(F)$ denote the communication complexity (in the quantum setting) of computing F where for any inputs x, y, the algorithm must output F(x, y) with probability at least $1 - \varepsilon$. For Boolean function $f : \{0, 1\}^n \to \mathbb{R}$ and $0 \le \varepsilon < 1$, the ε -approximate degree of f, denoted by $\deg_{\varepsilon}(f)$, is the smallest degree of any polynomial p that ε -represents f, i.e., $|p(x) - f(x)| \le \varepsilon$ for any input $x \in \{0, 1\}^n$.

3 Algorithm

We first introduce the framework of distributed quantum optimization in [12]. Given function $f : X \to \mathbb{Z}$, where X is a finite set, let G = (V, E) be a network with a pre-defined node leader $\in V$. We write $|\phi\rangle_{v}$ to denote a state in the memory space of node v. A specific register $|\cdot\rangle_{I}$ called *internal* and the control of the algorithm are centralized by the node leader. Assume that the following three quantum procedures are given as black boxes.

- Initialization: Prepare an initial state $|0\rangle_1$ (init) with some pre-computed information (init).
- Setup: Produce a superposition from the initial state:

$$\left|0
ight
angle_{I}\left|\text{init}
ight
angle\mapsto\sum_{x\in X}lpha_{x}\left|x
ight
angle_{I}\left|\text{data}(x)
ight
angle\left| ext{init}
ight
angle$$
 ,

where the α_x 's are arbitrary amplitudes and data(x) are information depending on x.

• Evaluation: Perform the transformation

$$|x,0\rangle_{I} |data(x)\rangle |init\rangle \mapsto |x,f(x)\rangle_{I} |data(x)\rangle |init\rangle$$

The following lemma provides an algorithm to search $x \in X$ with high value f(x) given the three procedures above.

Lemma 3.1 (Theorem 2.4 in [12]³). Assume that Initialization can be implemented within T_0 rounds in the quantum CONGEST model, and that unitary operators Setup and Evaluation and their inverses can be implemented within T rounds. Let $\rho > 0$ be such that $\sum_{x \in X: f(x) \ge M} |\alpha_x|^2 \ge \rho$ where M is unknown to all nodes. Then, for any $\delta > 0$, the node leader can find, with probability at least $1 - \delta$, some element x such that $f(x) \ge M$, in $T_0 + O(\sqrt{\log(1/\delta)/\rho}) \times T$ rounds.

The three procedures will be described as deterministic or randomized procedures that combine the subroutines provided by Nanongkai [21] (also presented in Appendix A). They can be quantized using the standard technique [5], with potentially additional garbage whose size is of the same order as the initial memory space.

Given a weighted graph (G, w) where G = (V, E) is a network and $w : E \to \mathbb{N}^+$, we show a quantum algorithm approximating $D_{G,w}$ and $R_{G,w}$ by proving Theorem 1.1. We only show the algorithm approximating the diameter. The proof for radius is basically the same except that it finds the minimum (approximate) eccentricity instead of the maximum one.

We choose the parameters throughout this section.

$$\varepsilon = 1/\log n, r = n^{2/5} D_G^{-1/5}, \ell = n \log n/r, k = \sqrt{D_G}.$$
 (1)

³Although Le Gall and Magniez write a slightly weaker statement, the lemma we claim here can be proven by the same argument in [12].

As mentioned in Section 1.1, finding a node with maximum eccentricity among all nodes by directly applying a quantum search algorithm can hardly be done in o(n) rounds. We instead try to find a vertex set containing a node with maximum approximate eccentricity among n vertex sets S_1, \dots, S_n , and then search such a node in this vertex set. Each set S_i for $i \in [1, n]$ is sampled by having each node $v \in V$ join it independely with probability r/n. For such a random set and a node s in it, Nanongkai showed in [21] an efficient classical procedure to approximate its eccentricity (actually every node $v \in V$ can know an approximation of the distance from s to v).

3.1 Computation of Approximate Eccentricity

For convenience, we need to introduce several graph notations. Given a weighted graph (G, w), the hop distance between nodes u and v, denoted by $h_{G,w}(u, v)$, is the minimum number of edges over all shortest paths between them. The hop diameter of the weighted graph, denoted by $H_{G,w}$, is the maximum hop distance between any two nodes. For $\ell > 0$, the ℓ -hop distance between u and v, denoted by $d_{G,w}^{\ell}(u,v)$, is the least length over all paths between them containing at most ℓ edges. Note that $d_{G,w}^{\ell}(u,v) = d_{G,w}(u,v)$ when $h_{G,w}(u,v) \leq \ell$.

In general, Nanongkai [21] would approximate the bounded-hop distance, and sample a random set of key nodes as skeleton. Then it could approximate the distance from any key node s to any node v since, with high probability, any shortest path from s to v can be partitioned into bounded-hop shortest paths between key nodes, along with a tail path from some key node to v, as long as the number of key nodes is sufficiently large.

Here we only list the necessary definitions of approximate bounded-hop distance, approximate distance, and approximate eccentricity. We claim that these are good approximations. The algorithms evaluating these quantities are presented in Appendix A, and the detailed proof should be found in [21, arXiv version]. Note that we are given a weighted graph (G, w) where G = (V, E) and $w : E \to \mathbb{N}^+$.

Lemma 3.2 (Theorem 3.3 in [21]). *Given an integer* l > 0. *For integer* $i \ge 0$, *define* $w_i : E \to \mathbb{N}^+$ where $w_i(e) = \left\lceil \frac{2lw(e)}{\epsilon \cdot 2^i} \right\rceil$ for $e \in E$. For any $u, v \in V$, the approximate bounded-hop distance is defined as

$$\widetilde{d}_{G,w}^{\ell}(\mathfrak{u},\nu) = \min_{i} \left\{ d_{G,w_{i}}(\mathfrak{u},\nu) \cdot \frac{\epsilon \cdot 2^{i}}{2\ell} : d_{G,w_{i}}(\mathfrak{u},\nu) \leqslant \left(1 + \frac{2}{\epsilon}\right)\ell \right\}.$$

 $\textit{Then } d_{G,w}(u,\nu) \leqslant \widetilde{d}^{\ell}_{G,w}(u,\nu) \leqslant (1+\epsilon) d^{\ell}_{G,w}(u,\nu).$

Lemma 3.3 (Theorem 4.2 in [21]). Given a vertex set $S \subseteq V$. Let the weighted complete graph (G'_S, w'_S) be such that

$$G'_{S} = \left(S, {S \choose 2}\right), w'_{S} : {S \choose 2} \to \mathbb{N}^{+},$$
$$w'_{S}(\{u, v\}) = \widetilde{d}^{\ell}_{G, w}(u, v), \forall \{u, v\} \in {S \choose 2}.$$

For node $v \in S$, let $N_S^k(v)$ be the set of the k nodes with the least distance from v on (G'_S, w'_S) . And let the weighted complete graph (G''_S, w''_S) be such that

$$\begin{split} G_{S}^{\prime\prime} &= \left(S, \binom{S}{2}\right), w_{S}^{\prime\prime} : \binom{S}{2} \to \mathbb{N}^{+}, \\ w_{S}^{\prime\prime}(\{u, v\}) &= \begin{cases} d_{G_{S}^{\prime}, w_{S}^{\prime}}(u, v), & u \in \mathsf{N}_{S}^{k}(v) \text{ or } v \in \mathsf{N}_{S}^{k}(u) \\ w_{S}^{\prime}(\{u, v\}), & \text{otherwise} \end{cases}, \forall \{u, v\} \in \binom{S}{2}. \end{split}$$

For any $s \in S$ *and* $v \in V$ *, the approximate distance is defined as*

$$\widetilde{d}_{G,w,S}(s,\nu) = \min_{u \in S} \left\{ \widetilde{d}_{G''_{S},w''_{S}}^{4|S|/k}(s,u) + \widetilde{d}_{G,w}^{\ell}(u,\nu) \right\}.$$

If $\ell = n \log n/r$ and S is sampled by having each node $\nu \in V$ join it independently with probability r/n, then $d_{G,w}(s,\nu) \leq \tilde{d}_{G,w,S}(s,\nu) \leq (1+\varepsilon)^2 d_{G,w}(s,\nu)$ for all $s \in S$ and $\nu \in V$, with probability at least $1-2^{-cn}$, for some constant c > 0 and sufficiently large n.

Remark. We briefly explain why $\widetilde{d}_{G,w,S}(\cdot)$ is a good approximation. By the choice of ℓ and S, Lemma 4.3 in [21] says that, with high probability, any $s \in S, v \in V$ and shortest path $(s \rightsquigarrow v)$ on (G, w) is of the form $(s = s_1 \rightsquigarrow \cdots \rightsquigarrow s_m = u \rightsquigarrow v)$ such that $s_i \in S$ for $i \in [1, m]$, $h_{G,w}(s_{i-1}, s_i) \leq \ell$ for $i \in [2, m]$, and $h_{G,w}(u, v) \leq \ell$. Apparently $\widetilde{d}_{G,w,S} \geq d_{G,w}(s, v)$. On the other side,

$$\begin{split} \widetilde{d}_{G,w,S}(s,\nu) &= \widetilde{d}_{G_{s',w_{s}'}^{4|S|/k}}(s,u) + \widetilde{d}_{G,w}^{\ell}(u,\nu) \\ &\leqslant (1+\epsilon) d_{G_{s',w_{s}'}^{m''}}(s,u) + \widetilde{d}_{G,w}^{\ell}(u,\nu) \\ &= (1+\epsilon) d_{G_{s',w_{s}'}^{m''}}(s,u) + \widetilde{d}_{G,w}^{\ell}(u,\nu) \\ &\leqslant (1+\epsilon) \sum_{i=2}^{m} w_{S}'(\{s_{i-1},s_{i}\}) + \widetilde{d}_{G,w}^{\ell}(u,\nu) \\ &\leqslant (1+\epsilon) \sum_{i=2}^{m} \widetilde{d}_{G,w}^{\ell}(s_{i-1},s_{i}) + \widetilde{d}_{G,w}^{\ell}(u,\nu) \\ &\leqslant (1+\epsilon)^{2} \left(\sum_{i=2}^{m} d_{G,w}^{\ell}(s_{i-1},s_{i}) + d_{G,w}^{\ell}(u,\nu) \right) \\ &= (1+\epsilon)^{2} \left(\sum_{i=2}^{m} d_{G,w}(s_{i-1},s_{i}) + d_{G,w}(u,\nu) \right) \\ &= (1+\epsilon)^{2} d_{G,w}(s,\nu). \end{split}$$

The second and sixth lines are due to Lemma 3.2. The third line is due to Theorem 3.10 in [21], which says that $H_{G''_{s'},w''_{s'}} < 4|S|/k$ since $(G''_{s'},w''_{s'})$ is the *k*-shortcut graph of (G'_{s},w'_{s}) .

For $i \in [1, n]$, we rewrite $G_{S_i}'', w_{S_i}'', \tilde{d}_{G,w,S_i}(\cdot)$ as $G_i'', w_i'', \tilde{d}_{G,w,i}(\cdot)$ for short. For any $s \in S_i$, the approximate eccentricity is defined as $\tilde{e}_{G,w,i}(s) = \max_{v \in V} \tilde{d}_{G,w,i}(s,v)$. Define two good events:

- **Good-Scale:** For all $i \in [1, n]$, $|S_i| = \Theta(r)$. Besides, let $v^* \in V$ be a node with maximum eccentricity, i.e., $e_{G,w}(v^*) = D_{G,w}$, then v^* joins $\beta = \Theta(r)$ sets $S_{i_1}, \dots, S_{i_{\beta}}$.
- **Good-Approximation:** For all $i \in [1, n]$ and $s \in S_i, v \in V$, $d_{G,w}(s, v) \leq \tilde{d}_{G,w,i}(s, v) \leq (1 + \varepsilon)^2 d_{G,w}(s, v)$, thus $e_{G,w}(s) \leq \tilde{e}_{G,w,i}(s) \leq (1 + \varepsilon)^2 e_{G,w}(s)$.

By Chernoff inequality and a union bound, the event Good-Scale occurs with probability at least 1 - 1/poly(n). By Lemma 3.3 and a union bound, the event Good-Approximation occurs with probability at least 1 - 1/poly(n). Therefore, we can assume that the two events all happen in the following context.

3.2 Quantization

For each $i \in [1, n]$, we define $f_i : S_i \to \mathbb{Z}$ where $f_i(s) = \tilde{e}_{G,w,i}(s)$ for $s \in S_i$, and $f : [1, n] \to \mathbb{Z}$ where $f(i) = \max_{s \in S_i} f_i(s)$ for $i \in [1, n]$.

Lemma 3.4. The number of $i \in [1, n]$ satisfying $f(i) \ge D_{G, w}$ is $\Theta(r)$. Moreover, $f(i) \le (1 + \epsilon)^2 D_{G, w}$ for all $i \in [1, n]$.

Proof.

$$\begin{split} f(\mathfrak{i}_{\mathfrak{j}}) &= \max_{s \in S_{\mathfrak{i}_{\mathfrak{j}}}} \widetilde{e}_{G,w,\mathfrak{i}_{\mathfrak{j}}}(s) \geqslant \max_{s \in S_{\mathfrak{i}_{\mathfrak{j}}}} e_{G,w}(s) \geqslant e_{G,w}(v^{\star}) = \mathsf{D}_{G,w}, \quad \forall \mathfrak{j} \in [1,\beta]; \\ f(\mathfrak{i}) &= \max_{s \in S_{\mathfrak{i}}} \widetilde{e}_{G,w,\mathfrak{i}}(s) \leqslant \max_{s \in S_{\mathfrak{i}}} (1+\varepsilon)^2 e_{G,w}(s) \leqslant (1+\varepsilon)^2 \mathsf{D}_{G,w}, \quad \forall \mathfrak{i} \in [1,n]. \end{split}$$

Lemma 3.5. *Given* $i \in [1, n]$ *, there exists a quantum procedure performing the transformation*

$$\bigotimes_{\nu \in V} \left| i \right\rangle_{\nu} \left| 0 \right\rangle_{leader} \mapsto \bigotimes_{\nu \in V} \left| i \right\rangle_{\nu} \left| f(i) \right\rangle_{leader}$$

in the quantum CONGEST model, and taking $\widetilde{O}\left(D_G + \frac{n}{\epsilon \cdot r} + rk + \sqrt{r}\left(\frac{r}{\epsilon \cdot k} \cdot D_G + r\right)\right)$ rounds, with probability at least 1 - 1/poly(n).

Proof. We give the quantum procedure maximizing f_i (thus evaluating f(i)) by following the framework of distributed quantum optimization:

• **Initialization**_i: Perform the transformation

$$\bigotimes_{\nu \in V} \left| i \right\rangle_{\nu} \mapsto \bigotimes_{\nu \in V} \left| i \right\rangle_{\nu} \left| 0 \right\rangle_{I} \left| \text{init}_{i} \right\rangle,$$

where

$$|\text{init}_{i}\rangle = \bigotimes_{\nu \in V, u \in S_{i}} \left| \widetilde{d}_{G,w}^{\ell}(u,\nu) \right\rangle_{\nu} |G_{i}'',w_{i}''\rangle,$$

and $d_{G,w}^{\ell}(u,v)$ is given in Lemma 3.2, $G_{i}^{\prime\prime}$ and $w_{i}^{\prime\prime}$ are given in lemma 3.3.

• **Setup**_i: Perform the transformation

$$\bigotimes_{\nu \in V} |\mathfrak{i}\rangle_{\nu} |0\rangle_{I} |\text{init}_{\mathfrak{i}}\rangle \mapsto \bigotimes_{\nu \in V} |\mathfrak{i}\rangle_{\nu} \left(\sum_{s \in S_{\mathfrak{i}}} \frac{1}{|S_{\mathfrak{i}}|} |s\rangle_{I} |\text{data}_{\mathfrak{i}}(s)\rangle \right) |\text{init}_{\mathfrak{i}}\rangle,$$

where $|\text{data}_{\mathfrak{i}}(s)\rangle = \bigotimes_{v \in V} |s\rangle_{v} \bigotimes_{v \in V, u \in S_{\mathfrak{i}}} \left| \widetilde{d}_{G_{\mathfrak{i}}'', w_{\mathfrak{i}}''}(s, u) \right\rangle_{v}$.

• **Evaluation**_i: Perform the transformation

$$\bigotimes_{\nu \in V} |\mathfrak{i}\rangle_{\nu} \left(|\mathfrak{s}, 0\rangle_{\mathrm{I}} \left| \mathsf{data}_{\mathfrak{i}}(\mathfrak{s}) \right\rangle\right) |\mathsf{init}_{\mathfrak{i}}\rangle \mapsto \bigotimes_{\nu \in V} |\mathfrak{i}\rangle_{\nu} \left(|\mathfrak{s}, \mathsf{f}_{\mathfrak{i}}(\mathfrak{s})\rangle_{\mathrm{I}} \left| \mathsf{data}_{\mathfrak{i}}(\mathfrak{s}) \right\rangle\right) |\mathsf{init}_{\mathfrak{i}}\rangle.$$

We now analyze the round complexity:

- In Õ (D_G + n/ε·r + r) rounds, each ν ∈ V can know d̃^ℓ_{G,w}(u, ν) for each u ∈ S_i, with high probability, due to Lemma A.2. After that, the overlay network (G", w") can be embedded in O(D_G + rk) rounds due to Lemma A.3 (we say that the network G = (V, E) embeds an overlay network G' = (V', E') with a weight function w' : E' → N⁺ if V' ⊆ V and for each v ∈ V', it stores each e ∈ E' incident to v along with w'(e) in the local memory). Therefore, the procedure Initialization_i can be implemented in T₀ = Õ (D_G + n/ε·r + rk) rounds.
- The node leader can collect S_i in $O(D_G + r)$ rounds. It then prepares the quantum state $\sum_{s \in S_i} \frac{1}{|S_i|} |s\rangle_I$ and broadcasts to all nodes using CNOT copies, in $O(D_G)$ rounds. Thus, the transformation

$$\bigotimes_{\nu \in V} |i\rangle_{\nu} |0\rangle_{I} |init_{i}\rangle \mapsto \bigotimes_{\nu \in V} |i\rangle_{\nu} \left(\sum_{s \in S_{i}} \frac{1}{|S_{i}|} |s\rangle_{I} \bigotimes_{\nu \in V} |s\rangle_{\nu} \right) |init_{i}\rangle$$

can be implemented in $O(D_G + r)$ rounds. Besides, the transformation

$$\bigotimes_{\nu \in V} |i\rangle_{\nu} \bigotimes_{\nu \in V} |s\rangle_{\nu} |\text{init}_{i}\rangle \mapsto \bigotimes_{\nu \in V} |i\rangle_{\nu} \bigotimes_{\nu \in V} |s\rangle_{\nu} \bigotimes_{\nu \in V, u \in S_{i}} \left| \widetilde{d}_{G_{i}'', w_{i}''}^{4|S_{i}|/k}(s, u) \right\rangle_{\nu} |\text{init}_{i}\rangle$$

can be implemented in $T_1 = \widetilde{O}\left(\frac{r}{\epsilon \cdot k} \cdot D_G + r\right)$ rounds since Lemma A.4 implies that, after the overlay network (G''_i, w''_i) is embedded, each $v \in V$ can know $\widetilde{d}_{G''_i, w''_i}^{4|S_i|/k}(s, u)$ for each $u \in S_i$ within T_1 rounds. Therefore, the procedure Setup_i can be implemented in $T_1 = \widetilde{O}\left(\frac{r}{\epsilon \cdot k} \cdot D_G + r\right)$ rounds.

• For the procedure Evaluation_i, recall that $f_i(s) = \max_{v \in V} d_{G,w,i}(s,v)$ where

$$\widetilde{d}_{G,w,i}(s,\nu) = \min_{u \in S_i} \left\{ \widetilde{d}_{G_i'',w_i''}^{4|S_i|/k}(s,u) + \widetilde{d}_{G,w}^{\ell}(u,\nu) \right\}.$$

By definition, for any $v \in V$ and $u \in S_i$, $\tilde{d}_{G'',w''_i}^{4|S_i|/k}(s,u)$ and $\tilde{d}_{G,w}^{\ell}(u,v)$ have been stored in the local memory of v, i.e., $|\cdot\rangle_v$. Thus, each $v \in V$ can locally compute $\tilde{d}_{G,w,S_i}(s,v)$, and the node leader can compute the maximum by converge-casting in $O(D_G)$ rounds. So the procedure Evaluation_i can be implemented in $T_2 = O(D_G)$ rounds.

By Lemma 3.1, there exists a quantum procedure maximizing f_i in $\widetilde{O}(T_0 + \sqrt{r}(T_1 + T_2))$ rounds with high probability.

Proof of Theorem **1***.***1***.* We give a quantum procedure maximizing f also by following the framework of distributed quantum optimization:

- Initialization is a classical procedure which samples vertex sets S₁,..., S_n, and |init> represents the corresponding classical information.
- Setup: Perform the transformation

$$\left|0
ight
angle_{I}\left|\text{init}
ight
angle\mapsto\sum_{i=1}^{n}rac{1}{n}\left|i
ight
angle_{I}\left|\text{data}(i)
ight
angle\left|\text{init}
ight
angle$$

where $|\text{data}(i)\rangle = \bigotimes_{\nu \in V} |i\rangle_{\nu}$.

• Evaluation: Perform the transformation

 $\left| \mathfrak{i},0\right\rangle _{I}\left| data(\mathfrak{i})\right\rangle \left| \mathfrak{i}\mathfrak{n}\mathfrak{i}\right\rangle \mapsto \left| \mathfrak{i},\mathfrak{f}(\mathfrak{i})\right\rangle _{I}\left| data(\mathfrak{i})\right\rangle \left| \mathfrak{i}\mathfrak{n}\mathfrak{i}\mathfrak{t}\right\rangle .$

We now analyze the round complexity:

- S_1, \dots, S_n are sampled locally in parallel, and the procedure Initialization is free, i.e., $T_0 = 0$.
- The node leader prepares the quantum state $\sum_{i=1}^{n} \frac{1}{n} |i\rangle_{I}$ and broadcast using CNOT copies to all nodes. Therefore, the procedure Setup can be implemented in $T_{I} = O(D_{G})$ rounds.
- The procedure Evaluation can be of $T_2 = \widetilde{O}\left(D_G + \frac{n}{\epsilon \cdot r} + rk + \sqrt{r}\left(\frac{r}{\epsilon \cdot k} \cdot D_G + r\right)\right)$ rounds by Lemma 3.5.

By Lemma 3.1 and Lemma 3.4, there exists a quantum procedure that find, with high probability, some $i \in [1, n]$ such that $D_{G,w} \leq f(i) \leq (1 + \epsilon)^2 D_{G,w}$, in

$$\widetilde{O}(\mathsf{T}_0 + \sqrt{n/r}(\mathsf{T}_1 + \mathsf{T}_2)) = \widetilde{O}\left(\sqrt{n/r}\left(\mathsf{D}_G + \frac{n}{\epsilon \cdot r} + rk + \sqrt{r}\left(\frac{r}{\epsilon \cdot k} \cdot \mathsf{D}_G + r\right)\right)\right)$$

rounds. By the choice of the parameters in Eq. (1), Theorem 1.1 follows.

4 Lower Bound

To prove the lower bound on the round complexity of approximating (weighted) diameter in the quantum CONGEST model, we combine the reduction in [9, 23, 10] and the graph gadget in [2].

4.1 Reduction from Server Model

We briefly outline the reduction introduced by Elkin et al. [9, 23, 10] from the Server model to prove the hardness of certain graph problems such as diameter and radius. We will introduce a distributed network G = (V, E) and embed a certain two-argument function $F : \{0, 1\}^k \times \{0, 1\}^k \rightarrow \{0, 1\}$ into the network by showing that if the instance on the network G has a low round-complexity protocol in the quantum CONGEST model, then there exists a low communication complexity protocol for F in the quantum Server model. Thus, the hardness of diameters and radius in the quantum CONGEST model is reduced to proving the lower bounds the communication complexity in the quantum Server model.

The network G = (V, E) is depicted by Figure 1 where $V = V_S \uplus V_A \uplus V_B$ and $E = E_S \uplus E_A \uplus E_B \uplus E'$. We use G[U] to denote the subgraph induced by vertex set $U \subseteq V$, then E_S, E_A, E_B are the edges in $G[V_S], G[V_A], G[V_B]$ respectively. And E' denotes the edges between V_S and $V_A \uplus V_B$.

 $G[V_S]$ includes a full binary tree of height h and m disjoint paths of length $2^h - 1$. Each of the 2^h leaves of the binary tree is connected to the nodes on the paths as depicted in Figure 1. Suppose nodes of depth i on the tree are $t_{i,1}, \cdots, t_{i,2^i}$ and nodes on the i-th path are $p_{i,1}, \ldots, p_{i,2^h}$ from left to right. Then $t_{h,1}, \ldots, t_{h,2^h}$ are the leaves of the binary tree in $G[V_S]$. For each $i \in [1, m]$ and $j \in [1, 2^h]$, there is an edge between $t_{h,j}$ and $p_{i,j}$. Thus,



Figure 1: An example of constructed graph G.

 V_A contains at least m nodes, each of which is connected to $p_{i,1}$ for $1 \le i \le m$. V_B contains at least m nodes, each of which is connected to $p_{i,2^h}$ for $1 \le i \le m$. Those 2m edges are contained in E'. The subgraphs $G[V_A]$ and $G[V_B]$ are decided by Alice's input and Bob's input, respectively.

The following lemma gives an efficient simulation of algorithms on network G by the protocols in the quantum Server model.

Lemma 4.1 (Quantum Simulation Lemma). Suppose Alice and Bob are given (V_A, E_A) and (V_B, E_B) , respectively. For any T-round $(T < 2^h/2)$ distributed algorithm on network G described above, there exists a communication protocol for Alice and Bob in the quantum Server model to simulate the algorithm with communication complexity $O(T \cdot h \cdot B)$, where B denotes the bandwidth in the CONGEST model.

Proof. The proof of Lemma 4.1 follows closely with the proof in [10, Proof of Theorem 3.5]. The protocol we will construct simulates the distributed algorithm round by round. Thus, it also has $T < 2^{h}/2$ rounds of communication. In the beginning, the server simulates all the nodes in V_S which are independent of Alice and Bob's inputs. And in the end of the r-th round, the server simulates $p_{i,1+r}, \cdots, p_{i,2^{h}-r}$ on the i-th path and nodes $t_{h,1+r}, \cdots, t_{h,2^{h}-r}$ along with their ancestors on the binary tree, while Alice simulates the nodes on the left and Bob simulates on the right side. More formally, in the end of the r-th round, the server simulates

$$\left\{p_{i,j}: i \in [1,m], j \in [1+r,2^h-r]\right\} \cup \left\{t_{i,j}: i \in [0,h], j \in \left[\left\lceil (1+r)/2^{h-i}\right\rceil, \left\lceil (2^h-r)/2^{h-i}\right\rceil\right]\right\};$$

Alice simulates

$$V_{A} \cup \{p_{i,j} : i \in [1, m], j \in [1, 1+r)\} \cup \{t_{i,j} : i \in [0, h], j \in [1, \lceil (1+r)/2^{h-i}\rceil)\};$$

Bob simulates

$$V_{B} \cup \left\{ p_{i,j} : i \in [1, m], j \in (2^{h} - r, 2^{h}] \right\} \cup \left\{ t_{i,j} : i \in [0, h], j \in \left(\left\lceil (2^{h} - r)/2^{h-i} \right\rceil, 2^{i} \right\rceil \right\}.$$

We describe the simulation of the computation and communication of a processor v in the r-th round, and count the total communication complexity.

- If v is owned by Alice or the server in the (r-1)-th round and will be owned by Alice in the r-th round, Alice needs the local information of v in the (r-1)-th round and messages from $\Gamma(v)$ (neighbours of v) to v in the r-th round, which can be obtained by local computation and communication from the server to Alice since $T < 2^{h}/2$, which implies that each of v and nodes in $\Gamma(v)$ is owned by either Alice or the server in the (r-1)-th round for $r \leq T$. So in this case, we only need communication from the server to Alice in the Server model. This part will not be counted to complexity by definition.
- If v is owned by Bob or the server in the (r 1)-th round and will be owned by Bob in the r-th round, no communication will be counted to complexity by the same argument as mentioned above.
- If v is owned by the server in both the (r 1)-th round and the r-th round, the server needs the messages from $\Gamma(v)$ to v. For each node $u \in \Gamma(v)$ owned by Alice or Bob in the (r 1)-th round, Alice or Bob will simulates the local computation of u in the r-th round, and send the message to the server.
 - If v is on the paths on V_S, none of $\Gamma(v)$ is owned by Alice and Bob in the (r-1)-th round.
 - If v is on the binary tree, node $u \in \Gamma(v)$ is owned by Alice in the (r 1)-th round only if all nodes of the same depth with v, meanwhile on the left side of v, are not owned by the server in the r-th round, and u is the left-child of v. Similarly, node $u \in \Gamma(v)$ is owned by Bob in the (r 1)-th round only if all nodes of the same depth with v, meanwhile on the right side of v, are not owned by the server in the r-th round, and u is the round only if all nodes of the same depth with v, meanwhile on the right side of v, are not owned by the server in the r-th round, and u is the right-child of v. In the r-th round, there are at most 2h such (u, v) in total.

Hence, a total of $O(T \cdot h)$ messages, each of size O(B), are sent from Alice or Bob to the server. \Box

4.2 Hardness of Approximating Diameter

we will use G constructed above as a gadget to prove a lower bound on round complexity of approximating weighted diameter in the quantum CONGEST model. The specific graph depicted in Figure 2 will contain $n = (2^{h+1} - 1) + (2s + \ell) (2^h + 2) + 2 \cdot 2^s$ nodes, where parameters h, s, ℓ are chosen as follows throughout this section.

h is some even number,
$$s = 3h/2$$
, $\ell = 2^{s-h}$. (2)

This choice makes $2^h = \widetilde{\Theta}(n^{2/3})$, $2^s = \widetilde{\Theta}(n)$ and $\ell = \widetilde{\Theta}(n^{1/3})$.

Theorem 4.2 (Restated). For any constant $\varepsilon \in (0, \frac{1}{2}]$, any algorithm, with probability at least $\frac{11}{12}$, computing a $(\frac{3}{2} - \varepsilon)$ -approximation of the weighted diameter in the quantum CONGEST model requires $\Omega\left(\frac{n^{2/3}}{\log^2 n}\right)$ rounds, even when the unweighted diameter is $\Theta(\log n)$, where n denotes the number of nodes.

On network G = (V, E) described in Section 4.1, we specify $G[V_A]$ and $G[V_B]$. Let

$$\begin{split} V_A &= \{a_1, \cdots, a_{2^s}\} \uplus \left\{a_1^0, a_1^1, \cdots, a_s^0, a_s^1\right\} \uplus \{a_1^\star, \cdots, a_\ell^\star\}, \\ V_B &= \{b_1, \cdots, b_{2^s}\} \uplus \left\{b_1^0, b_1^1, \cdots, b_s^0, b_s^1\right\} \uplus \{b_1^\star, \cdots, b_\ell^\star\}. \end{split}$$



Figure 2: Graph G for approximating diameter. The black edges are of weight 1; the blue edges are of weight α ; and weights of red edges are determined by inputs x, y, i.e, $w(\{a_i, a_j^*\}) = \alpha$ if $x_{i,j} = 1$ and $w(\{a_i, a_j^*\}) = \beta$ if $x_{i,j} = 0$, and $w(\{b_i, b_j^*\}) = \alpha$ if $y_{i,j} = 1$ and $w(\{b_i, b_j^*\}) = \beta$ if $y_{i,j} = 0$, for $i \in [1, 2^s]$ and $j \in [1, \ell]$.

The edges E_A , E_B and E' are specified as follows.

where bin(i, j) denote the j-th bit in binary expression of integer i - 1. The node pairs $(a_i^0, p_{2i-1,1}), (a_i^1, p_{2i,1}), (b_i^0, p_{2i,2^h}), (b_i^1, p_{2i-1,2^h})$ for $1 \leq i \leq s$, and $(a_j^\star, p_{2s+j,1}), (a_i^\star, p_{2s+j,1})$

 $(b_j^{\star}, p_{2s+j,2^h})$ for $1 \leq j \leq \ell$ are connected. For each $i \in [1, 2^s]$, a_i is connected to $a_j^{bin(i,j)}$ for each $j \in [1, s]$, and a_i is connected to a_j^{\star} for each $j \in [1, \ell]$. Moreover, $G[\{a_1, \dots, a_{2^s}\}]$ is a clique. The edges in $G[V_B]$ are linked in the same way as the edges in $G[V_A]$.

The weights of the edges are specified as follows, which are also depicted in Figure 2.

- The edges on the binary tree and the edges on the 2s + l paths (including the endpoints in V_A and V_B) are of weight 1 (the black edges in Figure 2).
- Recall that Alice and Bob receive inputs $x, y \in \{0, 1\}^{2^{s,\ell}}$ respectively. x and y are indexed by $x_{i,j}$ and $y_{i,j}$ for $i \in [1, 2^s], j \in [1, \ell]$ where s and ℓ are given in Eq. (2). For each $i \in [1, 2^s], j \in [1, \ell]$, $w(\{a_i, a_j^*\}) = \alpha$ if $x_{i,j} = 1$ and $w(\{a_i, a_j^*\}) = \beta$ if $x_{i,j} = 0$ ($\alpha < \beta$); weights of edges between $\{b_1, \cdots, b_{2^s}\}$ and $\{b_1^*, \cdots, b_{\ell}^*\}$ are assigned according to y in the same way (the red edges in Figure 2).
- The edges between the binary tree and the $2s + \ell$ paths, those between $\{a_1, \dots, a_{2^s}\}$ and $\{a_1^0, a_1^1, \dots, a_s^0, a_s^1\}$, and those between $\{b_1, \dots, b_{2^s}\}$ and $\{b_1^0, b_1^1, \dots, b_s^0, b_s^1\}$ are of weight α ; weights of edges inside $G[\{a_1, \dots, a_{2^s}\}]$ and $G[\{b_1, \dots, b_{2^s}\}]$ are also α (the blue edges in Figure 2).

It is sufficient to analyze the diameter of graph after contracting all edges of weight 1 due to the following lemma. An edge is contracted if the two endpoints are merged to one node, and the adjacent edges of the two endpoints are incident to it. If there are parallel edges after contraction, we only keep the one with the lowest weight.

Lemma 4.3. Given a weighted graph (G, w) where G = (V, E) and $w : E \to \mathbb{N}^+$. Let G' be the graph after contracting all edges of weight 1. We have $D_{G',w} \leq D_{G,w} \leq D_{G',w} + n$ and $R_{G',w} \leq R_{G,w} \leq R_{G',w} + n$, where n = |V|.

Proof. For any path P in G, let P' be the path in G' obtained from P after contraction. Then

$$length(P') \leq length(P) \leq length(P') + n$$

as there are at most n - 1 1-weight edges. Thus we conclude the result.

For inputs $x, y \in \{0, 1\}^{2^s \cdot \ell}$ received by Alice and Bob, define

$$F(x,y) = \bigwedge_{i \in [1,2^s]} \left(\bigvee_{j \in [1,\ell]} (x_{i,j} \wedge y_{i,j}) \right),$$

i.e., $F = AND_{2^s} \circ (OR_\ell \circ AND_2^\ell)^{2^s}.$ We have the following lemma.

Lemma 4.4. $D_{G,w} \leq \max\{2\alpha, \beta\} + n$ if F(x, y) = 1, and $D_{G,w} \geq \min\{\alpha + \beta, 3\alpha\}$ otherwise.

Proof. The graph G' after contraction is given in Figure 3. The binary tree is contracted to node t. The $2s + \ell$ paths are contracted to nodes $a_1^0, a_1^1, \dots, a_s^0, a_s^1$ and a_1^*, \dots, a_{ℓ}^* respectively. Note that b_i is connected to $a_j^{bin(i,j)\oplus 1}$ for $i \in [1, 2^s], j \in [1, s]$. we list upper bounds of the distances between any two nodes u and v in G' on Table 2 with the corresponding paths, except for the distance between a_i and b_i with $i \in [1, 2^s]$.

Regarding the distance between a_i and b_i for $i \in [1, 2^s]$, if there exists $j \in [1, \ell]$ such that $x_{i,j} = y_{i,j} = 1$, then $w(\{a_i, a_j^*\}) = w(\{b_i, a_j^*\}) = \alpha$ and $d_{G',w}(a_i, b_i) \leq 2\alpha$ because of the path $(a_i \rightarrow a_j^* \rightarrow b_i)$ in G'. If there is no $j \in [1, \ell]$ such that $x_{i,j} = y_{i,j} = 1$, we claim that $d_{G',w}(a_i, b_i) \geq 2\alpha$



Figure 3: Graph G' after contraction. The distance between any pair of nodes, except a_i and b_i for $i \in [1, 2^s]$, is at most max{2 α , β }; and the distance between a_i and b_i is at most 2 α if there exists $j \in [1, \ell]$ such that $x_{i,j} = y_{i,j} = 1$, otherwise it is at least min{ $\alpha + \beta, 3\alpha$ }. Therefore, the diameter is at most max{2 α, β } if, for any $i \in [1, 2^s]$, there exists $j \in [1, \ell]$ such that $x_{i,j} = y_{i,j} = 1$, otherwise it is at least min{ $\alpha + \beta, 3\alpha$ }.

 $\min\{\alpha + \beta, 3\alpha\}$. For any path between a_i and b_i , if it contains exactly two edges, it is of the form $(a_i \rightarrow a_j^* \rightarrow b_i)$ for some $j \in [1, \ell]$ by the construction of G', and it is of length at least $\alpha + \beta$ by the assumption. If it contains at least three edges, it is of length at least 3α .

If F(x, y) = 1, then for any $i \in [1, 2^s]$, there exists $j \in [1, \ell]$ such that $x_{i,j} = y_{i,j} = 1$. Hence,

$$d_{G',w}(a_i, b_i) \leq 2\alpha, \forall i \in [1, 2^s],$$

$$D_{G',w} = \max_{u,v} d_{G',w}(u, v) \leq \max\{2\alpha, \beta\}.$$

Therefore, $D_{G,w} \leq D_{G',w} + n \leq \max\{2\alpha, \beta\} + n$ by Lemma 4.3.

If F(x, y) = 0, then there exists $i \in [1, 2^s]$ such that $x_{i,j} = 0$ or $y_{i,j} = 0$ for any $j \in [1, \ell]$. Hence,

$$d_{G',w}(a_{i}, b_{i}) = \min_{\text{path P from } a_{i} \text{ to } b_{i}} \text{length}(P) \ge \min\{\alpha + \beta, 3\alpha\},$$
$$D_{G',w} = \max_{u,v} d_{G',w}(u,v) \ge d_{G',w}(a_{i}, b_{i}) \ge \min\{\alpha + \beta, 3\alpha\}.$$

Therefore, $D_{G,w} \ge D_{G',w} \ge \min\{\alpha + \beta, 3\alpha\}$ by Lemma 4.3.

Combining Lemma 4.1 and Lemma 4.4, we have a reduction from computing F in the Server model to approximating diameter in the quantum CONGEST model. To prove the communication complexity of F in the Server model, we adopt the following lemma.

Lemma 4.5 (Lemma B.4 in [10], arXiv version). Function VER : $\{0, 1, 2, 3\} \times \{0, 1, 2, 3\} \rightarrow \{0, 1\}$ is defined by VER(x, y) = 1 if and only if x + y is equivalent to 0 or 1 modulo 4, where $x, y \in \{0, 1, 2, 3\}$. Let

u	ν	$d_{G',w}(u,v)$	Path
	router	$\leqslant \alpha$	(t ightarrow u)
t	$\mathfrak{a}_{\mathfrak{i}} \ (\mathfrak{i} \in [1, 2^s])$	$\leqslant 2\alpha$	$\left(\mathfrak{t} ightarrow \mathfrak{a}_{0}^{\mathrm{bin(i,0)}} ightarrow \mathfrak{a}_{i} ight)$
	$b_{\mathfrak{i}}\ (\mathfrak{i}\in[1,2^s])$	$\leqslant 2\alpha$	$\left(\mathbf{t} \to \mathbf{a}_0^{\mathrm{bin}(\mathbf{i},0)\oplus 1} \to \mathbf{b}_{\mathbf{i}}\right)$
	$a_j \ (j \neq i, j \in [1, 2^s])$	$\leqslant \alpha$	$(a_i \rightarrow a_j)$
	$\mathfrak{a}_{j}^{\mathrm{bin}(\mathfrak{i},\mathfrak{j})}$ $(\mathfrak{j} \in [1, \mathfrak{s}])$	$\leqslant \alpha$	$\left(a_{i} \rightarrow a_{j}^{\operatorname{bin}(i,j)}\right)$
$\mathfrak{a}_{\mathfrak{i}} \ (\mathfrak{i} \in [1, 2^s])$	$\mathfrak{a}_{j}^{\mathrm{bin}(\mathfrak{i},\mathfrak{j})\oplus 1}$ $(\mathfrak{j}\in[1,s])$	$\leqslant 2\alpha$	$\left(\mathfrak{a}_{i} \rightarrow \mathfrak{a}_{\mathrm{adj}(i,j)} \rightarrow \mathfrak{a}_{j}^{\mathrm{bin}(i,j)\oplus 1}\right)$
	$\texttt{b}_{j} \; (j \neq \texttt{i}, \texttt{j} \in [1, 2^s])$	$\leqslant 2\alpha$	$\left(a_{i} \rightarrow a_{ind(i,j)}^{bin(i,ind(i,j))} \rightarrow b_{j}\right)$
	$\mathfrak{a}_{\mathfrak{j}}^{\star}$ ($\mathfrak{j}\in [1,\ell]$)	$\leqslant \beta$	$\left(\mathfrak{a_i} ightarrow \mathfrak{a}_j^\star ight)$
	$b_j \ (j \neq i, j \in [1, 2^s])$	$\leqslant \alpha$	$(b_i \rightarrow b_j)$
1 (; - [1 08])	$a_j^{\mathrm{bin}(i,j)\oplus 1}$ ($j \in [1,s]$)	$\leqslant \alpha$	$\left(\mathfrak{b}_{\mathfrak{i}} \to \mathfrak{a}_{\mathfrak{j}}^{\operatorname{bin}(\mathfrak{i},\mathfrak{j})\oplus 1}\right)$
$\mathfrak{b}_{\mathfrak{i}} \ (\mathfrak{i} \in [1, 2^{\mathfrak{s}}])$	$a_j^{bin(i,j)}$ $(j \in [1,s])$	$\leqslant 2\alpha$	$\left(b_{i} \rightarrow b_{adj(i,j)} \rightarrow a_{j}^{bin(i,j)}\right)$
	\mathfrak{a}_j^\star $(j \in [1, \ell])$	<β	$\left(\mathfrak{b_i} ightarrow \mathfrak{a}_j^\star ight)$
router	router	$\leq 2\alpha$	$(\mathfrak{u} \to t \to \nu)$

Table 2: Distance between nodes in G'. Let router be any node in $\{a_1^0, a_1^1, \dots, a_s^0, a_s^1, a_1^*, \dots, a_\ell^*\}$. adj(i, j) denotes the integer after changing the j-th bit in binary expression of integer i - 1, and ind(i, j) is the smallest $z \in [1, s]$ satisfying $bin(i, z) \neq bin(j, z)$.

 $f:\{0,1\}^k \rightarrow \{0,1\}$ be an arbitrary function. Then

$$Q_{\epsilon}^{s\nu}(f \circ VER^{k}) \geqslant \frac{1}{2} deg_{4\epsilon}(f) - O(1)$$

for any $0 < \varepsilon < 1/4$ *.*

A read-once formula, which consists of AND gates, OR gates, and NOT gates, is a formula in which each variable appears exactly once. We will need the following conclusion for approximate degree of read-once formulas.

Lemma 4.6 (Theorem 6 in [1]). *For any read-once formula* $f : \{0, 1\}^k \to \{0, 1\}, deg_{1/3}(f) = \Theta\left(\sqrt{k}\right)$.

Lemma 4.7. Given s, ℓ defined in Eq. (2) where ℓ is a multiple of 4, $F = AND_{2^s} \circ (OR_{\ell} \circ AND_2^{\ell})^{2^s}$ with inputs x, $y \in \{0, 1\}^{2^s \cdot \ell}$, set

$$F(x,y) = \bigwedge_{i \in [1,2^s]} \left(\bigvee_{j \in [1,\ell]} \left(x_{i,j} \wedge y_{i,j} \right) \right).$$

It holds that

$$Q_{1/12}^{\mathfrak{sv}}(F) = \Omega\left(\sqrt{2^{\mathfrak{s}}\cdot \mathfrak{\ell}}\right).$$

Proof. The function F can be rewritten as $F = f \circ GDT^{2^s \cdot \ell/4}$, where $f = AND_{2^s} \circ OR_{\ell/4}^{2^s}$ and $GDT = OR_4 \circ AND_2^4$. Obviously the function f is a read-once formula. It can be seen that the function VER is actually a *promise version* of the function GDT where inputs $x, y \in \{0, 1\}^4$ satisfy

$$x \in \{0011, 1001, 1100, 0110\}, y \in \{0001, 0010, 0100, 1000\}.$$

Thus, the lower bound for $f \circ VER^{2^s \cdot \ell/4}$ clearly implies the lower bound for $f \circ GDT^{2^s \cdot \ell/4}$. Therefore,

$$Q_{1/12}^{s\nu}(f \circ GDT^{2^s \cdot \ell/4}) \geqslant Q_{1/12}^{s\nu}(f \circ VER^{2^s \cdot \ell/4}) \geqslant \frac{1}{2} deg_{1/3}(f) - O(1) = \Omega\left(\sqrt{2^s \cdot \ell}\right).$$

The second inequality is due to Lemma 4.5 and the last inequality is due to Lemma 4.6.

Proof of Theorem 4.2. Let \mathcal{A} be a T-round algorithm (T < 2^h/2) in the quantum CONGEST model which, for any weighted graph (G, w), computes a $(\frac{3}{2} - \varepsilon)$ -approximation of D_{G,w} (constant $\varepsilon \in (0, 1/2]$) with probability at least 11/12. Alice and Bob, who receive x, y $\in \{0, 1\}^{2^s \cdot \ell}$, respectively, construct the network G as described above with parameters h, s, ℓ given in Eq. (2). The number of nodes is

$$n = (2^{h+1} - 1) + (2s + \ell) (2^{h} + 2) + 2 \cdot 2^{s} = \Theta (2^{3h/2})$$

And the unweighted diameter is $D_G = \Theta(h) = \Theta(\log n)$. Let *w* be the weight function. Due to Lemma 4.1, they can simulate \mathcal{A} on (G, w) in the quantum Server model with communication complexity $O(T \cdot h \cdot B)$ where B denotes the bandwidth. With probability at least $\frac{11}{12}$, Alice and Bob output an approximation $\widetilde{D}_{G,w}$ satisfying $D_{G,w} \leq \widetilde{D}_{G,w} \leq (\frac{3}{2} - \epsilon)D_{G,w}$. We set $\alpha = n^2$ and $\beta = 2n^2$. By Lemma 4.4,

$$\begin{split} \text{if } \mathsf{F}(\mathsf{x},\mathsf{y}) &= 1, \widetilde{\mathsf{D}}_{\mathsf{G},w} \leqslant \left(\frac{3}{2} - \varepsilon\right) \mathsf{D}_{\mathsf{G},w} \leqslant \left(\frac{3}{2} - \varepsilon\right) (\max\{2\alpha,\beta\} + \mathfrak{n}) \\ &= 3\mathfrak{n}^2 - \left(2\varepsilon\mathfrak{n}^2 - \left(\frac{3}{2} - \varepsilon\right)\mathfrak{n}\right); \\ \text{if } \mathsf{F}(\mathsf{x},\mathsf{y}) &= 0, \widetilde{\mathsf{D}}_{\mathsf{G},w} \geqslant \mathsf{D}_{\mathsf{G},w} \geqslant \min\{\alpha + \beta, 3\alpha\} = 3\mathfrak{n}^2. \end{split}$$

For large enough n, Alice and Bob can distinguish whether F(x, y) = 1 or not with probability at least $\frac{11}{12}$ in the Server model, and thus $Q_{1/12}^{sv}(F) = O(T \cdot h \cdot B)$. Due to Lemma 4.7,

$$\mathsf{T} = \Omega\left(\frac{\sqrt{2^s \cdot \ell}}{\mathsf{h} \cdot \mathsf{B}}\right) = \Omega\left(\frac{2^{\mathsf{h}}}{\mathsf{h} \cdot \mathsf{B}}\right) = \Omega\left(\frac{\mathsf{n}^{2/3}}{\mathsf{log}^2 \,\mathsf{n}}\right),$$

where the last equality is by the choice of h and the the bandwidth $B = \Theta(\log n)$. Therefore, the round complexity of approximating diameter is $\Omega\left(\min\left\{2^{h}/2, \frac{n^{2/3}}{\log^2 n}\right\}\right) = \Omega\left(\frac{n^{2/3}}{\log^2 n}\right)$.

4.3 Hardness of Approximating Radius

We choose the same set of parameters h, s, l given in Eq. (2). The argument is very close to the one for diameter.

Theorem 4.8 (Restated). For any constant $\varepsilon \in (0, \frac{1}{2}]$, any algorithm, with probability at least $\frac{11}{12}$, computing a $(\frac{3}{2} - \varepsilon)$ -approximation of radius in the quantum CONGEST model requires $\Omega\left(\frac{n^{2/3}}{\log^2 n}\right)$ rounds, even when the unweighted diameter is $\Theta(\log n)$, where n denotes the number of nodes.

The weighted graph (G, w) that we construct for showing hardness of approximating radius is almost the same except that we add a node a_0 in V_A along with edges $\{a_0, a_1\}, \dots, \{a_0, a_{2^s}\}$ of weight 2α . Here we only show in Figure 4 the graph G' after contracting all edges of weight 1 (the green edges are the new-added edges).



Figure 4: Graph G' (after contraction) for approximating radius. The additional green edges are of weight 2 α . The eccentricity of any node, except a_i for $i \in [1, 2^s]$, is at least 3 α ; and the eccentricity of a_i is at most max{2 α , β } if there exists $j \in [1, \ell]$ such that $x_{i,j} = y_{i,j} = 1$, otherwise it is at least min{ $\alpha + \beta, 3\alpha$ }. Therefore, the radius is at most max{2 α, β } if there exist $i \in [1, 2^s], j \in [1, \ell]$ such that $x_{i,j} = y_{i,j} = 1$, otherwise it is at least min{ $\alpha + \beta, 3\alpha$ }.

For inputs $x, y \in \{0, 1\}^{2^s \cdot \ell}$ define

$$F'(x,y) = \bigvee_{i \in [1,2^s], j \in [1,\ell]} (x_{i,j} \wedge y_{i,j}).$$

We have the following lemma.

Lemma 4.9. $R_{G,w} \leq \max\{2\alpha, \beta\} + n$ if F'(x, y) = 1, and $R_{G,w} \geq \min\{\alpha + \beta, 3\alpha\}$ otherwise.

Proof. It suffices to estimate the radius of (G', w) by Lemma 4.3. For any node $v \notin \{a_0, a_1, \dots, a_{2^s}\}$, $d_{G',w}(a_0, v) \ge 3\alpha$. This is because that any path from a_0 to v is of the form $(a_0 \rightarrow a_i \rightsquigarrow v)$ for some $i \in [1, 2^s]$, where $w(\{a_0, a_i\}) = 2\alpha$, and the remaining edges on the path have total weight at least α . Therefore, $e_{G',w}(v) \ge 3\alpha$ for any $v \notin \{a_1, \dots, a_{2^s}\}$. To estimate the eccentricity of a_i for $i \in [1, 2^s]$, we have $d(a_i, v) \le \max\{2\alpha, \beta\}$ for any $v \ne b_i$ as shown on Table 2, and $d_{G',w}(a_i, b_i) \le 2\alpha$ if there exists $j \in [1, \ell]$ such that $x_{i,j} = y_{i,j} = 1$, and $d_{G',w}(a_i, b_i) \ge \min\{\alpha + \beta, 3\alpha\}$ otherwise.

If F'(x, y) = 1, then there are $i \in [1, 2^s]$ and $j \in [1, \ell]$ such that $x_{i,j} = y_{i,j} = 1$, and thus

$$\begin{split} & d_{G',w}(a_i,b_i) \leqslant 2\alpha, \\ & e_{G',w}(a_i) = \max_{\nu} d_{G',w}(a_i,\nu) \leqslant \max\{2\alpha,\beta\}, \\ & R_{G',w} = \min_{u} e_{G',w}(u) \leqslant e_{G',w}(a_i) \leqslant \max\{2\alpha,\beta\}. \end{split}$$

Therefore, $R_{G,w} \leq R_{G',w} + n \leq \max\{2\alpha, \beta\} + n$ by Lemma 4.3. If F'(x, y) = 0, then for any $i \in [1, 2^s]$ and $j \in [1, \ell]$, $x_{i,j} = 0$ or $y_{i,j} = 0$, and thus

$$\begin{split} d_{G',w}(a_i,b_i) &\geq \min\{\alpha+\beta,3\alpha\}, \forall i \in [1,2^s], \\ e_{G',w}(a_i) &= \max_{\nu} d_{G',w}(a_i,\nu) \geq d_{G',w}(a_i,b_i) \\ &\geq \min\{\alpha+\beta,3\alpha\}, \forall i \in [1,2^s], \\ R_{G',w} &= \min_{u} e_{G',w}(u) \geq \min\{\alpha+\beta,3\alpha\}. \end{split}$$

Therefore, $R_{G,w} \ge R_{G',w} \ge \min\{\alpha + \beta, 3\alpha\}$ by Lemma 4.3.

Similar to Lemma 4.7, one can prove a lower bound on communication complexity of F' in the quantum Server model.

Lemma 4.10. Given s, ℓ defined in Eq. (2) where $2^s \cdot \ell$ is a multiple of 4, $F' = OR_{2^s \cdot \ell} \circ AND_2^{2^s \cdot \ell}$ with inputs $x, y \in \{0, 1\}^{2^s \cdot \ell}$, set

$$F'(x,y) = \bigvee_{i \in [1,2^s], j \in [1,\ell]} (x_{i,j} \wedge y_{i,j}).$$

It holds that

$$Q_{1/12}^{\mathfrak{sv}}(F') = \Omega\left(\sqrt{2^{\mathfrak{s}}\cdot \mathfrak{\ell}}\right).$$

Proof. The function F' can be rewritten as $F' = f' \circ GDT^{2^s \cdot \ell/4}$, where $f' = OR_{2^s \cdot \ell/4}$. Note that f' is still a read-once formula. Thus the rest of proof is the same as the one in Lemma 4.7.

Proof of Theorem 4.8. Let \mathcal{A} be a T-round algorithm (T < 2^h/2) in the quantum CONGEST model which, for any weighted graph (G, w), computes a $(\frac{3}{2} - \epsilon)$ -approximation of $R_{G,w}$ (constant $\epsilon \in (0, \frac{1}{2}]$) with probability at least $\frac{11}{12}$. Alice and Bob, who receive $x, y \in \{0, 1\}^{2^{s} \cdot \ell}$ as input, construct the weighted graph (G, w) described above with the number of node $n = \Theta(2^{3h/2})$. The unweighted diameter $D_G = \Theta(\log n)$. Due to Lemma 4.1, Alice and Bob can simulate \mathcal{A} on (G, w) in the quantum Server model with communication complexity $O(T \cdot h \cdot B)$. Then with probability at least $\frac{11}{12}$, Alice and Bob compute $\widetilde{R}_{G,w}$ satisfying $R_{G,w} \leq \widetilde{R}_{G,w} \leq (\frac{3}{2} - \epsilon)R_{G,w}$. We set $\alpha = n^2$ and $\beta = 2n^2$. Due to Lemma 4.9,

$$\begin{split} \text{if } \mathsf{F}'(x,y) &= 1, \widetilde{\mathsf{R}}_{\mathsf{G},w} \leqslant 3n^2 - \left(2\epsilon n^2 - \left(\frac{3}{2} - \epsilon\right)n\right); \\ \text{if } \mathsf{F}'(x,y) &= 0, \widetilde{\mathsf{R}}_{\mathsf{G},w} \geqslant 3n^2. \end{split}$$

For large enough n, Alice and Bob can compute F' with probability at least $\frac{11}{12}$ in the Server model, and thus $Q_{1/12}^{\mathfrak{sv}}(\mathsf{F}') = O(\mathsf{T} \cdot \mathsf{h} \cdot \mathsf{B})$. Due to Lemma 4.10, $\mathsf{T} = \Omega\left(\frac{\mathfrak{n}^{2/3}}{\log^2 \mathfrak{n}}\right)$. Therefore, the round complexity of approximating radius is $\Omega\left(\min\left\{2^{\mathfrak{h}}/2, \frac{\mathfrak{n}^{2/3}}{\log^2 \mathfrak{n}}\right\}\right) = \Omega\left(\frac{\mathfrak{n}^{2/3}}{\log^2 \mathfrak{n}}\right)$.

Acknowledgements

We thank the anonymous reviewers' feedback. This work was supported in part by, the National Key R&D Program of China 2018YFB1003202, National Natural Science Foundation of China (Grant No. 61972191), the Program for Innovative Talents and Entrepreneur in Jiangsu, and Anhui Initiative in Quantum Information Technologies (Grant No. AHY150100).

References

- [1] AARONSON, S., BEN-DAVID, S., KOTHARI, R., RAO, S., AND TAL, A. Degree vs. approximate degree and quantum implications of huang's sensitivity theorem. In STOC '21: 53rd Annual ACM SIGACT Symposium on Theory of Computing, Virtual Event, Italy, June 21-25, 2021 (2021), S. Khuller and V. V. Williams, Eds., ACM, pp. 1330–1342.
- [2] ABBOUD, A., CENSOR-HILLEL, K., AND KHOURY, S. Near-linear lower bounds for distributed distance computations, even in sparse networks. In *Distributed Computing 30th International Symposium*, DISC 2016, Paris, France, September 27-29, 2016. Proceedings (2016), C. Gavoille and D. Ilcinkas, Eds., vol. 9888 of Lecture Notes in Computer Science, Springer, pp. 29–42.
- [3] ANCONA, B., CENSOR-HILLEL, K., DALIRROOYFARD, M., EFRON, Y., AND WILLIAMS, V. V. Distributed distance approximation. In 24th International Conference on Principles of Distributed Systems, OPODIS 2020, December 14-16, 2020, Strasbourg, France (Virtual Conference) (2020), Q. Bramas, R. Oshman, and P. Romano, Eds., vol. 184 of LIPIcs, Schloss Dagstuhl - Leibniz-Zentrum für Informatik, pp. 30:1–30:17.
- [4] BEN-OR, M., AND HASSIDIM, A. Fast quantum byzantine agreement. In Proceedings of the 37th Annual ACM Symposium on Theory of Computing, Baltimore, MD, USA, May 22-24, 2005 (2005), H. N. Gabow and R. Fagin, Eds., ACM, pp. 481–485.
- [5] BENNETT, C. H. Time/space trade-offs for reversible computation. *SIAM J. Comput. 18*, 4 (1989), 766–776.
- [6] BERNSTEIN, A., AND NANONGKAI, D. Distributed exact weighted all-pairs shortest paths in near-linear time. In *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing, STOC 2019, Phoenix, AZ, USA, June 23-26, 2019* (2019), M. Charikar and E. Cohen, Eds., ACM, pp. 334–342.
- [7] CENSOR-HILLEL, K., FISCHER, O., GALL, F. L., LEITERSDORF, D., AND OSHMAN, R. Quantum distributed algorithms for detection of cliques. In 13th Innovations in Theoretical Computer Science Conference, ITCS 2022, January 31 February 3, 2022, Berkeley, CA, USA (2022), M. Braverman, Ed., vol. 215 of LIPIcs, Schloss Dagstuhl Leibniz-Zentrum für Informatik, pp. 35:1–35:25.
- [8] CHECHIK, S., AND MUKHTAR, D. Single-source shortest paths in the CONGEST model with improved bound. In PODC '20: ACM Symposium on Principles of Distributed Computing, Virtual Event, Italy, August 3-7, 2020 (2020), Y. Emek and C. Cachin, Eds., ACM, pp. 464–473.
- [9] ELKIN, M. An unconditional lower bound on the time-approximation trade-off for the distributed minimum spanning tree problem. *SIAM J. Comput. 36*, 2 (2006), 433–456.

- [10] ELKIN, M., KLAUCK, H., NANONGKAI, D., AND PANDURANGAN, G. Can quantum communication speed up distributed computation? In ACM Symposium on Principles of Distributed Computing, PODC '14, Paris, France, July 15-18, 2014 (2014), M. M. Halldórsson and S. Dolev, Eds., ACM, pp. 166–175.
- [11] FRISCHKNECHT, S., HOLZER, S., AND WATTENHOFER, R. Networks cannot compute their diameter in sublinear time. In *Proceedings of the Twenty-Third Annual ACM-SIAM Symposium* on Discrete Algorithms, SODA 2012, Kyoto, Japan, January 17-19, 2012 (2012), Y. Rabani, Ed., SIAM, pp. 1150–1162.
- [12] GALL, F. L., AND MAGNIEZ, F. Sublinear-time quantum computation of the diameter in CONGEST networks. In *Proceedings of the 2018 ACM Symposium on Principles of Distributed Computing, PODC 2018, Egham, United Kingdom, July 23-27, 2018* (2018), C. Newport and I. Keidar, Eds., ACM, pp. 337–346.
- [13] GALL, F. L., NISHIMURA, H., AND ROSMANIS, A. Quantum advantage for the LOCAL model in distributed computing. In 36th International Symposium on Theoretical Aspects of Computer Science, STACS 2019, March 13-16, 2019, Berlin, Germany (2019), R. Niedermeier and C. Paul, Eds., vol. 126 of LIPIcs, Schloss Dagstuhl - Leibniz-Zentrum für Informatik, pp. 49:1– 49:14.
- [14] GAVOILLE, C., KOSOWSKI, A., AND MARKIEWICZ, M. What can be observed locally? In Distributed Computing, 23rd International Symposium, DISC 2009, Elche, Spain, September 23-25, 2009. Proceedings (2009), I. Keidar, Ed., vol. 5805 of Lecture Notes in Computer Science, Springer, pp. 243–257.
- [15] HOLZER, S., PELEG, D., RODITTY, L., AND WATTENHOFER, R. Distributed 3/2approximation of the diameter. In *Distributed Computing - 28th International Symposium*, DISC 2014, Austin, TX, USA, October 12-15, 2014. Proceedings (2014), F. Kuhn, Ed., vol. 8784 of Lecture Notes in Computer Science, Springer, pp. 562–564.
- [16] HOLZER, S., AND PINSKER, N. Approximation of distances and shortest paths in the broadcast congest clique. In 19th International Conference on Principles of Distributed Systems, OPODIS 2015, December 14-17, 2015, Rennes, France (2015), E. Anceaume, C. Cachin, and M. G. Potop-Butucaru, Eds., vol. 46 of LIPIcs, Schloss Dagstuhl - Leibniz-Zentrum für Informatik, pp. 6:1– 6:16.
- [17] HOLZER, S., AND WATTENHOFER, R. Optimal distributed all pairs shortest paths and applications. In ACM Symposium on Principles of Distributed Computing, PODC '12, Funchal, Madeira, Portugal, July 16-18, 2012 (2012), D. Kowalski and A. Panconesi, Eds., ACM, pp. 355–364.
- [18] IZUMI, T., AND GALL, F. L. Quantum distributed algorithm for the all-pairs shortest path problem in the CONGEST-CLIQUE model. In *Proceedings of the 2019 ACM Symposium on Principles of Distributed Computing, PODC 2019, Toronto, ON, Canada, July 29 - August 2, 2019* (2019), P. Robinson and F. Ellen, Eds., ACM, pp. 84–93.
- [19] IZUMI, T., GALL, F. L., AND MAGNIEZ, F. Quantum distributed algorithm for triangle finding in the CONGEST model. In 37th International Symposium on Theoretical Aspects of Computer Science, STACS 2020, March 10-13, 2020, Montpellier, France (2020), C. Paul and M. Bläser, Eds., vol. 154 of LIPIcs, Schloss Dagstuhl - Leibniz-Zentrum für Informatik, pp. 23:1–23:13.

- [20] MAGNIEZ, F., AND NAYAK, A. Quantum distributed complexity of set disjointness on a line. In 47th International Colloquium on Automata, Languages, and Programming, ICALP 2020, July 8-11, 2020, Saarbrücken, Germany (Virtual Conference) (2020), A. Czumaj, A. Dawar, and E. Merelli, Eds., vol. 168 of LIPIcs, Schloss Dagstuhl - Leibniz-Zentrum für Informatik, pp. 82:1–82:18.
- [21] NANONGKAI, D. Distributed approximation algorithms for weighted shortest paths. In Symposium on Theory of Computing, STOC 2014, New York, NY, USA, May 31 - June 03, 2014 (2014), D. B. Shmoys, Ed., ACM, pp. 565–573.
- [22] PELEG, D., RODITTY, L., AND TAL, E. Distributed algorithms for network diameter and girth. In Automata, Languages, and Programming - 39th International Colloquium, ICALP 2012, Warwick, UK, July 9-13, 2012, Proceedings, Part II (2012), A. Czumaj, K. Mehlhorn, A. M. Pitts, and R. Wattenhofer, Eds., vol. 7392 of Lecture Notes in Computer Science, Springer, pp. 660–672.
- [23] SARMA, A. D., HOLZER, S., KOR, L., KORMAN, A., NANONGKAI, D., PANDURANGAN, G., PELEG, D., AND WATTENHOFER, R. Distributed verification and hardness of distributed approximation. *SIAM J. Comput.* 41, 5 (2012), 1235–1265.
- [24] TANI, S., KOBAYASHI, H., AND MATSUMOTO, K. Exact quantum algorithms for the leader election problem. *ACM Trans. Comput. Theory* 4, 1 (2012), 1:1–1:24.

A Toolkits in Nanongkai's Algorithm

Let G = (V, E) be a distributed network with a weight function $w : E \to \mathbb{N}^+$ and a pre-defined node leader $\in V$. We assume that each node initially knows n = |V| and $W = \max_{e \in E} w(e)$. The parameters ε , r, ℓ , k are chosen the same as in Eq. (1). We follow the background of Section 3.1. Given a vertex set $S \subseteq V$, let $\tilde{d}_{G,w}^{\ell}(\cdot)$, (G'_S, w'_S) , $N_S^k(\cdot)$, (G''_S, w''_S) , $\tilde{d}_{G,w,S}(\cdot)$ be as defined in Lemma 3.2 and Lemma 3.3. The following lemmas and algorithms are summarized from [21, arXiv version].

Lemma A.1 (Theorem 3.2 in [21]). For $s \in V$ known to all nodes, there exists an algorithm (Algorithm 1) such that in $\widetilde{O}(\ell/\epsilon)$ rounds, each $v \in V$ knows $\widetilde{d}_{G,w}^{\ell}(s,v)$, and during the whole computation, each node broadcasts $O(\log n)$ messages of size $O(\log n)$ to its neighbors.

Algorithm 1 Bounded-Hop SSSP $(G, w, s, \ell, \varepsilon)$

Input: Network (G, *w*), source node s and parameters ℓ , $\varepsilon > 0$. **Output:** Each node v knows $\tilde{d}_{Gw}^{\ell}(s,v)$. 1: Initially, $\widetilde{d}_{G,w}^{\ell}(s,v) \leftarrow \infty$ for each $v \in V$. 2: for i = 0 to $\log \frac{2nW}{s}$ do Run bounded-distance SSSP with parameters $(G, w_i, s, (1 + 2/\epsilon)\ell)$ using Algorithm 2. 3: **for** each $v \in V$ **do** in parallel 4: if $d_{G,w_i}(s,v) \leq (1+2/\varepsilon)\ell$ then 5: $\widetilde{d}^{\ell}_{G,w}(s,v) \leftarrow \min \Big\{ \widetilde{d}^{\ell}_{G,w}(s,v), d_{G,w_{i}}(s,v) \Big\}.$ 6: end if 7: 8: end for 9: end for

Algorithm 2 Bounded-Distance SSSP (G, w, s, L)

Input: Network (G, w), source node s and parameter L > 0. **Output:** Each node v knows whether $d_{G,w}(s,v) \leq L$, and if so, it further knows $d_{G,w}(s,v)$. 1: Initially, $d_{G,w}(s,s) \leftarrow 0$ and $d_{G,w}(s,v) \leftarrow \infty$ for each $v \neq s$. 2: Let t be the time this algorithm starts. 3: **for** round r = t to t + L **do** 4: **for** each $v \in V$ **do** in parallel for each message $(u, d_{G,w}(s, u))$ received in the previous round **do** 5: if $d_{G,w}(s, u) + w(\{u, v\}) \leq L$ then 6: $\mathbf{d}_{\mathbf{G},w}(s,v) \leftarrow \min\{\mathbf{d}_{\mathbf{G},w}(s,v), \mathbf{d}_{\mathbf{G},w}(s,u) + w(\{u,v\})\}.$ 7: 8: end if end for 9: if $d_{G,w}(s,v) = r - t$ then 10: v broadcasts message ($v, d_{G,w}(s, v)$) to all neighbors. 11: 12: end if end for 13: 14: end for

Lemma A.2 (Theorem 3.6 and Lemma 3.7 in [21]). *There exist an algorithm (Algorithm 3) such that in* $\widetilde{O}(D_G + \ell/\epsilon + |S|)$ rounds, each node $v \in V$ knows $\widetilde{d}_{G,w}^{\ell}(s,v)$ for each $s \in S$, with probability of failure at most n^{-c} , for any constant c > 0 and sufficiently large n.

Algorithm 3	Bounded-Hop	Multi-Source	Shortest Paths	$(G, w, S, \ell, \varepsilon)$

Input: Network (G, *w*), set of source nodes S and parameters ℓ , $\varepsilon > 0$.

Output: With high probability, each node v knows $d_{G,w}^{\ell}(s,v)$ for each $s \in S$.

- 1: Assume that $S = \{s_1, \dots, s_b\}$. Let A_i be the Algorithm 1 with parameters $(G, w, s_i, \ell, \epsilon)$ for each $i \in [1, k]$ (each A_i is of $T = \widetilde{O}(\ell/\epsilon)$ rounds, and during the whole computation of A_i , each node broadcasts $O(\log n)$ messages to its neighbors due to Lemma A.1).
- 2: The node leader samples $\Delta_1, \dots, \Delta_b \in [0, b \log n]$ independently and uniformly at random for delaying algorithms A_1, \dots, A_k , and broadcasts them by pipelining in $O(D_G + b)$ rounds.

```
3: for r = 1 to T + b \log n do
```

4: **for** each $v \in V$ **do** in parallel

```
5: Let a = |\{i \in [1, b] : v \text{ broadcasts a message in the } (r - \Delta_i)\text{-th round of } A_i\}|.
```

6: **if** $a \leq \lceil \log n \rceil$ **then**

```
7: \nu broadcasts these a messages in the next \lceil \log n \rceil rounds.
```

- 8: else
- 9: The algorithm fails.
- 10: **end if**
- 11: **end for**
- 12: **end for**

Lemma A.3 (Theorem 4.5 in [21]). After the overlay network (G'_S, w'_S) is embedded, there exists an algorithm (Algorithm 4) which further embeds the overlay network (G''_S, w''_S) in $\widetilde{O}(D_G + |S|k)$ rounds.

Algorithm 4 Embedding Overlay Network (G, w, S, G'_S, w'_S, k)

Input: Network (G, w), set of source nodes S, overlay network (G'_S, w'_S) and parameter k > 0. **Output:** It embeds the overlay network (G''_S, w''_S) .

- 1: Each node $s \in S$ broadcasts the k shortest edges incident to it on (G'_S, w'_S) (this can be done in $O(D_G + |S|k)$ rounds).
- 2: for each $s \in S$ do locally
- 3: s computes $N_{S}^{k}(s)$, along with the weight $w_{S}''(\{s,\nu\}) = d_{G'_{S},w'_{S}}(s,\nu)$ for each $\nu \in N_{S}^{k}(s)$ (this can be done due to Observation 3.12 in [21]).
- 4: end for

Lemma A.4 (Lemma 4.6 in [21]). For node $s \in S$ known to all nodes, after the overlay network (G''_S, w''_S) is embedded, there exists an algorithm (Algorithm 5) such that in $\widetilde{O}\left(\frac{|S|}{\epsilon \cdot k} \cdot D_G + |S|\right)$ rounds, each node $v \in V$ knows for each $u \in S$ the value of $\widetilde{d}_{G''_S, w''_S}^{4|S|/k}(s, u)$.

Algorithm 5 SSSP on Overlay Network $(G, w, S, \varepsilon, k, G''_{S}, w''_{S}, s)$

Input: Network (G, w), set of source nodes S, parameters ε , k > 0, overlay network (G''_S, w''_S) and source node $s \in S$.

Output: Each node ν knows $\tilde{d}_{G'_{\nu},w'_{s}}^{4|S|/k}(s, u)$ for each $u \in S$.

- 1: Let \mathcal{A} be the Algorithm 1 with parameters $(G''_{S}, w''_{S}, s, 4|S|/k, \varepsilon)$ (\mathcal{A} is of $T = \widetilde{O}\left(\frac{|S|}{\varepsilon \cdot k}\right)$ rounds, and during the whole computation of \mathcal{A} , each node broadcasts $O(\log n)$ messages to its neighbors due to Lemma A.1).
- 2: **for** r = 1 to T **do**
- 3: Let a be the number of nodes in G''_S that want to broadcast a message to its neighbors in G''_S in the r-th round of A. Count a and make every nodes in G knows a in $O(D_G)$ rounds.
- 4: Each node in G''_S , which wants to send a message to each of its neighbors in G''_S , broadcasts such message to all nodes in G (this takes $O(D_G + a)$ rounds).
- 5: **end for**