# Identifying Mentions of Pain in Mental Health Records Text: A Natural Language Processing Approach

Jaya Chaturvedi (Institute of Psychiatry, Psychology and Neurosciences, King's College London),
Sumithra Velupillai (Institute of Psychiatry, Psychology and Neurosciences, King's College London),
Robert Stewart (Institute of Psychiatry, Psychology and Neurosciences, King's College London, Health Data
Research UK, South London and Maudsley Biomedical Research Centre, London, United Kingdom
Angus Roberts (Institute of Psychiatry, Psychology and Neurosciences, King's College London, Health Data
Research UK)

Pain is a common reason for accessing healthcare resources and is a growing area of research, especially in its overlap with mental health. Mental health electronic health records are a good data source to study this overlap. However, much information on pain is held in the free text of these records, where mentions of pain present a unique natural language processing problem due to its ambiguous nature. This project uses data from an anonymised mental health electronic health records database. The data are used to train a machine learning based classification algorithm to classify sentences as discussing patient pain or not. This will facilitate the extraction of relevant pain information from large databases, and the use of such outputs for further studies on pain and mental health. 1,985 documents were manually triple-annotated for creation of gold standard training data, which was used to train three commonly used classification algorithms. The best performing model achieved an F1-score of 0.98 (95% CI 0.98-0.99).

Keywords. Natural Language Processing, Electronic Health Records, Pain, Mental Health, Transformers.

## 1. Introduction

Pain is defined as an unpleasant sensory and emotional experience, and is influenced by a variety of biological, psychological, and social factors [1]. Pain is a common reason for people to access healthcare facilities, thereby making electronic health records (EHR) a potential source for information on pain [2].

EHRs are longitudinal compilations of electronic data pertaining to a person's medical history or healthcare [3]. They have been increasingly used in research as they provide the opportunity to explore patient symptoms and findings from structured and unstructured fields. Since pain is not well recorded in these structured fields, it may help to supplement this information with data from unstructured clinical text [4].

A commonly used machine learning based NLP approach is text classification, in which labels are assigned to units of text (sentences/paragraphs/documents) [5]. Commonly used classification algorithms include Support Vector Machines [6–8] and K-Nearest Neighbours [9–11]. Recent state of the art approaches use embedding models and transformer-based neural network architectures [12], such as the bi-directional encoder representations of BERT [13]. Many healthcare domain related models have emerged, such as PubMedBERT [14], BioBERT [15], ClinicalBERT [16], UmlsBERT [17] and SAPBERT [18] which were developed after recognition of the need for specialized models due to linguistic differences between general and biomedical text [19].

This paper describes the methods undertaken to develop an NLP application for a sentence-level classification of mentions of physical pain within clinical text. Two BERT models were trained - bert\_base and SAPBERT - and compared to two conventional models - support vector machines (SVM) and K-Nearest Neighbours (KNN). To the best of our knowledge, such extraction of information about pain from mental health clinical text using NLP has not been done.

# 2. Methods

# 2.1. Data Source

An anonymised version of EHR data from The South London and Maudsley NHS Foundation Trust (SLaM), one of the largest mental healthcare organizations in Europe, is stored in the Clinical Record Interactive Search

(CRIS) database [20]. The infrastructure of CRIS has been described in detail with an overview of the cohort profile [21]. CRIS contains over 30 million documents, averaging 90 documents per patient [22]. There are 23 different text sources (such as attachments, event notes, nurse assessment letters, etc.). Most of the text is contained within attachments and event notes, and so these were used as the data sources in this project.

### 2.2. Ethics and Data Access

Ethics approval for CRIS has been granted by (Oxford C Research Ethics Committee, reference 18/SC/0372). Research projects that use the CRIS database are reviewed and approved by a patient-led oversight committee (described in [23]). An opt-out model is in place for service users and is advertised in all publicity material and initiatives. Data are owned by a third party, Maudsley Biomedical Research Centre (BRC), who run the CRIS tool, providing access to anonymised data. These data can only be accessed by permitted individuals from within a secure firewall.

### 2.3. Data Extraction

Pain can be described in numerous ways, using a variety of terms. To help identify which documents in CRIS might be discussing pain, a lexicon of such pain terms was developed from a combination of pain-related terms extracted from the literature and biomedical ontologies, supplemented with additional similar terms from word embedding models. This lexicon and its development has been described in more detail in [24]. Terms from this pain lexicon were used to identify documents within CRIS that might be discussing pain. Documents containing pain terms were extracted for further processing using SQL. No time or diagnosis filter was applied to the extraction.

# 2.4. Annotation Task

Extracted documents were used to create a corpus of text discussing patient pain by labelling, i.e., annotating spans of text as being about pain or not. Each span consisted of 200 characters before and after a pain-related term. First, a set of annotation guidelines were developed to provide rules defining when a sentence should be considered as discussing pain. Next, terms from the pain lexicon were highlighted in the extracted documents. Three medical student annotators read through the extracted documents considering these spans of text containing the previously highlighted pain terms. Annotators labelled each span with one of three labels: relevant i.e., referring to physical pain experienced by the patient; not relevant i.e., mentions not related to pain, not related to the patient or hypothetical and metaphorical mentions; and negated i.e., absence of pain. Interannotator agreements were calculated after multiple rounds where 200 documents were annotated by all three annotators in each round. The annotation tool used for this was MedCAT [25]. Any disagreements were discussed, and the annotation guidelines updated. This iterative process was carried out until an inter-annotator agreement of over 0.80 was achieved, after which each annotator was then given a separate set of documents. The documents that were annotated by all three annotators during the iteration process were adjudicated following a set of adjudication guidelines in line with the most recent version of annotation guidelines. The annotation and adjudication guidelines can be accessed online.

# 2.5. NLP application

The annotations were split into train/test/validation sets at a proportion of 80/10/10 respectively. Four different models were trained, as detailed in Table 1. The parameters were chosen based on the recommendations made in (21) and models were checked for overfitting.

Table 1. Model specifications

Model	Tokenizer	Pre-processing	Other Parameters
1. Support Vector		Lowercase, stopword,	Tf-Idf vectorizer
Machine	NLTK	white space and	Default parameters from
<ol><li>K-Nearest</li></ol>		punctuation removal,	sklearn
Neighbour		lemmatize and tokenize	
3. BERT	bert_base_uncased	Tokenize	Epochs: 3
		Prepend sentence with	Batch size: 16
		special token [CLS] and	Optimizer: AdamW,
		append with special token	learning rate 3e-5
4. SAPBERT	cambridgeltl/SapBE	[SEP]	Epochs: 4

<sup>1</sup> https://github.com/jayachaturvedi/pain in mental health/blob/main/Annotation%20Guidelines%20-%20Pain%20-%20for%20github.pdf

RT-from-	Pad and truncate sentence
PubMedBERT-	to max length 105 (defar
fulltext	is 511)

Batch size: 16 Optimizer: AdamW, learning rate 2e-5

#### 3. Results

#### 3.1. Data Extraction

A total of 1,985 randomly selected documents from 723 patients were extracted that contained pain related keywords from the lexicon. The most common diagnosis codes for these extracted patients were Mood disorders (ICD10 chapters F30-39) (33% of patients). There was an average of 8 annotations per patient.

#### 3.2. Annotations

An inter-annotator agreement of 90% (Cohen's kappa 0.88) was achieved after four rounds (each round containing 200 documents) of triple annotations. A total of 5,644 annotations were obtained. 72% of these were marked as relevant, 15% as not-relevant, and 13% as negated. The relevant annotations were labelled as 1. The not-relevant and negated annotations were combined and labelled as 0.71% annotations were labelled as class 1 (relevant) for both training and testing data.

#### 3.3. Evaluation of NLP application

A single GPU (Tesla T4) was used for the training models. K-fold validation was carried out for evaluation of the models, and 95% confidence intervals were calculated. The result for each algorithm is outlined in Table 2. The BERT models performed better than Support Vector machine and K-Nearest Neighbour models.

Table 2. Evaluation Metrics, including 95% confidence intervals

Model	Precision	Recall	F1-score (average from 10- fold cross validation)
Support Vector Machine	0.86 (0.83-0.88)	0.98 (0.97-0.99)	0.91 (0.90-0.93)
K-Nearest Neighbour	0.84 (0.81-0.87)	0.91 (0.89-0.93)	0.87 (0.85-0.89)
BERT	0.96 (0.94-0.97)	0.98 (0.97-0.99)	0.97 (0.96-0.98)
SAPBERT	0.98 (0.97-0.99)	0.99 (0.98-0.99)	0.98 (0.98-0.99)

#### *3.4*. Error Analysis

During the annotation process, common disagreements included when an instance could be interpreted as physical or metaphorical, such as "...causing him pain", and hypothetical mentions such as "...she feared the pain" and "?migraine".

After training the models, some false positives spotted during error analysis on the test data. For the BERT\_base model, there were instances such as "...wishing to project his pain on others", "father's hip pain". Some false negatives such as "denying symptoms other than stomach ache", "...if pain increases" were also noted.

The SAPBERT model showed false negatives when there were undecipherable symbols incorporated in the text, which might have occurred during the anonymisation process of the text, as well as misspellings or conjoined words such as "dabdominal pain" and "achespainodd sensations". False positives were instances such as "risk of potential pressure sores".

#### 4. Discussion

The ambiguous nature of pain was highlighted during this project, especially during the annotation process where it took multiple rounds for three clinically trained annotators to agree on the meanings and interpretations of the pain mentions. Bearing this in mind, it is understandable that the classification models struggled with hypothetical and metaphorical instances. This highlights the importance of context and the necessity for the NLP models to incorporate and consider context during the classification task. This is a strength of transformer-based models such as BERT, which could be why they performed better than SVM/KNN.

Amongst the two BERT models that were trained, SAPBERT, which was pre-trained using a biomedical ontology, UMLS, performed slightly better than bert base. There were differences in how each of the BERT models used in this project tokenised words, where SAPBERT was able to tokenise clinical concepts more accurately. This improvement in tokenisation might have impacted and improved the overall performance of the model.

# 5. Conclusions

The objective of this project was to develop a machine learning based NLP application that can classify mentions of pain within clinical text as relevant or not. BERT models, which use a transformer-based machine learning technique and contextual embeddings, outperformed the other algorithms. This is a novel approach towards extracting information about pain from mental health records, leveraging the unstructured clinical notes to identify patients with relevant mentions of pain, and such cohorts of patients can then further be used in epidemiological and other pain related research with more confidence in the actual occurrence of pain when mentioned in the text.

# Acknowledgements

This work uses data provided by patients and collected by the NHS as part of their care and support. The authors are also grateful to Dr Aurelie Mascio for providing access to some of her Python scripts.

### References

- Terminology | International Association for the Study of Pain [Internet]. International Association for the Study of Pain (IASP). [cited 2022 Oct 31]. Available from: https://www.iasp-pain.org/resources/terminology/
- 2. Motov SM, Khan AN. Problems and barriers of pain management in the emergency department: Are we ever going to get better? J Pain Res [Internet]. 2008 Dec 9 [cited 2022 Oct 31];2:5–11. Available from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3004630/
- Safety I of M (US) C on DS for P, Aspden P, Corrigan JM, Wolcott J, Erickson SM. Key Capabilities of an Electronic Health Record System: Letter Report [Internet]. Patient Safety: Achieving a New Standard for Care. National Academies Press (US); 2004 [cited 2022 Oct 31]. Available from: https://www.ncbi.nlm.nih.gov/books/NBK216105/
- Carlson LA, Jeffery MM, Fu S, He H, McCoy RG, Wang Y, Hooten WM, Sauver JS, Liu H, Fan J. Characterizing Chronic Pain Episodes in Clinical Text at Two Health Care Systems: Comprehensive Annotation and Corpus Analysis. JMIR Medical Informatics [Internet]. 2020 Nov 16 [cited 2022 Aug 22];8(11):e18659. Available from: https://medinform.jmir.org/2020/11/e18659
- Minaee S, Kalchbrenner N, Cambria E, Nikzad N, Chenaghlu M, Gao J. Deep Learning Based Text Classification: A Comprehensive Review. arXiv:200403705 [cs, stat] [Internet]. 2021 Jan 4 [cited 2021 Sep 13]; Available from: http://arxiv.org/abs/2004.03705
- Wright A, McCoy AB, Henkin S, Kale A, Sittig DF. Use of a support vector machine for categorizing free-text notes: assessment of accuracy across two institutions. Journal of the American Medical Informatics Association [Internet]. 2013 Sep 1 [cited 2022 Nov 30];20(5):887–90. Available from: https://doi.org/10.1136/amiajnl-2012-001576
- Yao L, Mao C, Luo Y. Clinical text classification with rule-based features and knowledge-guided convolutional neural networks. BMC Medical Informatics and Decision Making [Internet]. 2019 Apr 4 [cited 2022 Nov 30];19(3):71. Available from: https://doi.org/10.1186/s12911-019-0781\_4
- 8. Garla V, Taylor C, Brandt C. Semi-supervised clinical text classification with Laplacian SVMs: an application to cancer case management. J Biomed Inform [Internet]. 2013 Oct [cited 2022 Nov 30];46(5):869–75. Available from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3806632/
- 9. Trstenjak B, Mikac S, Donko D. KNN with TF-IDF based Framework for Text Categorization. Procedia Engineering [Internet]. 2014 Jan 1 [cited 2022 Nov 30];69:1356–64. Available from: https://www.sciencedirect.com/science/article/pii/S1877705814003750
- Jindal R, Taneja S. A Lexical Approach for Text Categorization of Medical Documents. Procedia Computer Science [Internet]. 2015 Jan 1 [cited 2022 Nov 30];46:314–20. Available from: https://www.sciencedirect.com/science/article/pii/S1877050915000903
- 11. Xing W, Bei Y. Medical Health Big Data Classification Based on KNN Classification Algorithm. IEEE Access. 2020;8:28808–19.
- 12. Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, Kaiser L, Polosukhin I. Attention Is All You Need [Internet]. arXiv; 2017 [cited 2022 Oct 31]. Available from: http://arxiv.org/abs/1706.03762
- Devlin J, Chang MW, Lee K, Toutanova K. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In: Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers) [Internet]. Minneapolis, Minnesota: Association for Computational Linguistics; 2019 [cited 2021 Apr 21]. p. 4171–86. Available from: https://www.aclweb.org/anthology/N19-1423

- Gu Y, Tinn R, Cheng H, Lucas M, Usuyama N, Liu X, Naumann T, Gao J, Poon H. Domain-Specific Language Model Pretraining for Biomedical Natural Language Processing. ACM Trans Comput Healthcare [Internet]. 2022 Jan 31 [cited 2022 Oct 31];3(1):1–23. Available from: http://arxiv.org/abs/2007.15779
- 15. Lee J, Yoon W, Kim S, Kim D, Kim S, So CH, Kang J. BioBERT: a pre-trained biomedical language representation model for biomedical text mining. Bioinformatics [Internet]. 2019 Sep 10 [cited 2022 Oct 31];btz682. Available from: http://arxiv.org/abs/1901.08746
- Huang K, Altosaar J, Ranganath R. ClinicalBERT: Modeling Clinical Notes and Predicting Hospital Readmission [Internet]. arXiv; 2020 [cited 2022 Oct 31]. Available from: http://arxiv.org/abs/1904.05342
- 17. Michalopoulos G, Wang Y, Kaka H, Chen H, Wong A. UmlsBERT: Clinical Domain Knowledge Augmentation of Contextual Embeddings Using the Unified Medical Language System Metathesaurus. arXiv:201010391 [cs] [Internet]. 2021 Apr 12 [cited 2021 Apr 21]; Available from: http://arxiv.org/abs/2010.10391
- Liu F, Shareghi E, Meng Z, Basaldella M, Collier N. Self-Alignment Pretraining for Biomedical Entity Representations. arXiv:201011784 [cs] [Internet]. 2021 Apr 7 [cited 2021 May 21]; Available from: http://arxiv.org/abs/2010.11784
- Alsentzer E, Murphy J, Boag W, Weng WH, Jindi D, Naumann T, McDermott M. Publicly Available Clinical BERT Embeddings. In: Proceedings of the 2nd Clinical Natural Language Processing Workshop [Internet]. Minneapolis, Minnesota, USA: Association for Computational Linguistics; 2019 [cited 2021 Apr 21]. p. 72–8. Available from: https://www.aclweb.org/anthology/W19-1909
- 20. Stewart R, Soremekun M, Perera G, Broadbent M, Callard F, Denis M, Hotopf M, Thornicroft G, Lovestone S. The South London and Maudsley NHS Foundation Trust Biomedical Research Centre (SLAM BRC) case register: development and descriptive data. BMC Psychiatry. 2009 Aug 12;9:51.
- 21. Perera G, Broadbent M, Callard F, Chang CK, Downs J, Dutta R, Fernandes A, Hayes RD, Henderson M, Jackson R, Jewell A, Kadra G, Little R, Pritchard M, Shetty H, Tulloch A, Stewart R. Cohort profile of the South London and Maudsley NHS Foundation Trust Biomedical Research Centre (SLaM BRC) Case Register: current status and recent enhancement of an Electronic Mental Health Record-derived data resource. BMJ Open. 2016 Mar 1;6(3):e008721.
- 22. Velupillai S, Suominen H, Liakata M, Roberts A, Shah AD, Morley K, Osborn D, Hayes J, Stewart R, Downs J, Chapman W, Dutta R. Using clinical Natural Language Processing for health outcomes research: Overview and actionable suggestions for future advances. Journal of Biomedical Informatics [Internet]. 2018 Dec 1 [cited 2021 Mar 31];88:11–9. Available from: https://www.sciencedirect.com/science/article/pii/S1532046418302016
- 23. Fernandes AC, Cloete D, Broadbent MTM, Hayes RD, Chang CK, Jackson RG, Roberts A, Tsang J, Soncul M, Liebscher J, Stewart R, Callard F. Development and evaluation of a de-identification procedure for a case register sourced from mental health electronic records. BMC Med Inform Decis Mak. 2013 Jul 11:13:71.
- 24. Chaturvedi J, Mascio A, Velupillai SU, Roberts A. Development of a Lexicon for Pain. Frontiers in Digital Health [Internet]. 2021 [cited 2021 Dec 14];3:193. Available from: https://www.frontiersin.org/article/10.3389/fdgth.2021.778305
- Kraljevic Z, Searle T, Shek A, Roguski L, Noor K, Bean D, Mascio A, Zhu L, Folarin AA, Roberts A, Bendayan R, Richardson MP, Stewart R, Shah AD, Wong WK, Ibrahim Z, Teo JT, Dobson RJ. Multi-domain Clinical Natural Language Processing with MedCAT: the Medical Concept Annotation Toolkit. arXiv:201001165 [cs] [Internet]. 2021 Mar 25 [cited 2022 Feb 26]; Available from: http://arxiv.org/abs/2010.01165