PROCEEDINGS A

rspa.royalsocietypublishing.org





Cite this article: Müller A. 2023 Hamel's equations and geometric mechanics of constrained and floating multibody and space systems. 20220732. Proc R Soc A 479, 2023. http://dx.doi.org/10.1098/rspa.2022.0732

Article submitted to journal

Subject Areas:

Geometric mechanics, Lie groups, computational mechanics, robotics

Keywords:

Geometric mechanics, Hamel equations, Hamel coefficients, Euler-Poincaré equations, Lagrange reduction, mechanical connection, locked velocity, kinematic reconstruction, gauge fields, space systems

Author for correspondence: Andreas Müller e-mail: a.mueller@jku.at

THE ROYAL SOCIETY PUBLISHING

Hamel's Equations and Geometric Mechanics of Constrained and Floating Multibody and Space Systems

Andreas Müller¹

¹Johannes Kepler University, Linz, Austria

Modern geometric approaches to analytical mechanics rest on a bundle structure of the configuration space. The connection on this bundle allows for an intrinsic splitting of the reduced Euler-Lagrange equations. Hamel's equations, on the other hand, provide a universal approach to non-holonomic mechanics in local coordinates. The link between Hamel's formulation and geometric approaches in local coordinates has not been discussed sufficiently. The reduced Euler-Lagrange equations as well as the curvature of the connection, are derived with Hamel's original formalism. Intrinsic splitting into Euler-Lagrange and Euler-Poincaré equations, and inertial decoupling is achieved by means of the locked velocity. Various aspects of this method are discussed.

1. Introduction

Many dynamical systems and controlled multibody systems possess symmetry invariants, and can be modeled on a principle bundle. The bundle formulation (for Lagrangian systems) was developed in [1,2] as key concept in geometric mechanics, where the configuration space is regarded as principle bundle $Q = G \times Q/G$ with symmetry group *G*. Central is the notion of a connection as it allows encoding specific symmetries of the system [3–6]. The (*natural*) mechanical connection, deduced from the system momentum, was introduced in [7–9]. Given a *G*-invariant Lagrangian ℓ , in bundle coordinates ($\Omega^{\alpha}, \dot{r}^{I}$) of a (left) trivialization, where Ω^{α} is the locked velocity, the dynamics of unconstrained floating-base systems is governed by the Lagrange-Poincaré equations [3]

$$\frac{d}{dt}\frac{\partial\ell}{\partial\Omega^{\alpha}} = \frac{\partial\ell}{\partial\Omega^{\beta}} \left(-\mathcal{E}^{\beta}_{I\alpha}\dot{r}^{I} + c^{\beta}_{\alpha\lambda}\Omega^{\lambda} \right)$$
(1.1)

$$\frac{d}{dt}\frac{\partial\ell}{\partial\dot{r}^{I}} - \frac{\partial\ell}{\partial r^{I}} = \frac{\partial\ell}{\partial\Omega^{\beta}} \left(-\mathcal{B}^{\beta}_{IJ}\dot{r}^{J} + \mathcal{E}^{\beta}_{I\alpha}\Omega^{\alpha} \right)$$
(1.2)

with connection coefficients \mathcal{A}_{I}^{α} and its curvature $\mathcal{B}_{IJ}^{\alpha}$.

The Authors. Published by the Royal Society under the terms of the Creative Commons Attribution License http://creativecommons.org/licenses/ by/4.0/, which permits unrestricted use, provided the original author and source are credited. The coefficients $\mathcal{E}_{\beta I}^{\alpha} = c_{\beta \lambda}^{\alpha} \mathcal{A}_{I}^{\lambda}$, and the curvature coefficients

$$\mathcal{B}_{IJ}^{\alpha} = \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{J}} - \frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial r^{I}} \pm c_{\beta\lambda}^{\alpha} \mathcal{A}_{I}^{\beta} \mathcal{A}_{J}^{\lambda}$$
(1.3)

are determined by the structure constants $c^{\alpha}_{\beta\lambda}$ of the Lie algebra \mathfrak{g} of G. The symmetry group encodes invariances of the Lagrangian. Most prominent examples are floating-base multibody systems¹, where the motion g of a base body evolves in a subgroup G of the group of Euclidean motions SE(3), with body-velocity $\hat{\boldsymbol{\xi}} = g^{-1}\dot{g} \in \mathfrak{g}$, and Q/G is the 'joint space' (which will be identified with \mathbb{V}^n) with joint coordinates r^I . The kinetic energy is then G-invariant, and the locked velocity is defined in terms of the mechanical connection as $\Omega^{\alpha} := u^{\alpha}$ (see Sec. 5), with

$$u^{\alpha} = \xi^{\alpha} + \mathcal{A}^{\alpha}_{I}(r^{I})\dot{r}^{I}.$$
(1.4)

The curvature vanishes if and only if the constraints defined by momentum conservation, and thus the Pfaffian system (1.4), is integrable. Similarly for constrained systems, a *kinematic connection* was introduced, and the scleronomic constraints are expressed as $u^{\alpha} = 0$. Mechanical systems whose spatial motion is constrained are typical examples, where the constraints restrict the motion of a base body in *G*. Now the symmetry group accounts for the invariance of the constraints, and the curvature vanishes if and only if the constraints are integrable. The dynamics equations for constrained systems are obviously obtained from (1.2) by setting $\Omega^{\alpha} = 0$. Thus, in both cases, a kinematic relation of the form (1.4) applies, and the curvature appears in the equations of motion, and is a central object in motion planning and control.

Geometric mechanics provides an intrinsic and coordinate-free framework for modeling, analysis, and control of finite-dimensional (discrete) as well as infinite-dimensional (continua) systems. Local coordinate formulations, as the one above, are used for computations, where it may be necessary to switch between different local coordinate charts. In this context, the fact that (1.1,1.2) is a specific form of the Hamel equations [10,11] for finite-dimensional systems in local coordinates deserves recognition, which is the topic of this paper. In geometric mechanics, Hamel's equations are now introduced in an elegant modern form, e.g. [12], on the expense that the relation to the original Hamel equations is lost, however. Moreover, how the geometric framework and the Hamel formalism are related, and how connection and curvature of the literature. Without making explicit reference to the original formulation, (1.1,1.2) are referred to as Hamel equations [8]. Also in robotics and multibody system dynamics, the Euler-Poincaré equations (1.1) on *SE* (3) are often interchangeably referred to as Hamel equations or Euler-Poincaré equations, e.g. [13].

It is shown in this paper that the coefficients in (1.1,1.2) are naturally derived as the Hamel coefficients. This provides a link between the original Hamel formalism and the bundle formulation. The explicit derivation also admits consolidating the different coordinate expressions of local curvature found in the literature, which is crucial for applying the above equations (see Rem. 5.3). There are also various aspects that need to be taken into account when using the geometric formalism. One is the concept of locked velocity [3], and the related concept of average velocity [14,15] that proved to be powerful tools for control of floating-base systems. It is discussed that there is no frame which can be associated with this velocity whose motion is a function of $g \in G$ and $\mathbf{r} \in \mathbb{V}^n$, which has consequences for control of floating-base systems. Another aspect discussed in this paper is that the mechanical connection on Q induced by the locked velocity intrinsically splits the reduced Euler-Lagrange equations in horizontal and vertical. As an important consequence, the equations (1.1,1.2) are inertially decoupled, which is relevant for computational multibody dynamics. Throughout the paper, all constraints are assumed to be linear (i.e. catastatic) and scleronomic.

¹Throughout the paper, the term floating-base systems covers a large class of mechanical (control) systems characterized by a base body free to move in space to which further bodies (links) are geometrically connected, e.g. by joints.

rspa.royalsocietypublishing.org Proc R Soc A 0000000

The paper is organized as follows. In Sec. 2, the classical Hamel equations are summarized for unconstrained and constrained systems. Hamel's formulation is related to the formulation on a (locally) trivial bundle in Sec. 3. The obtained relations for the Hamel coefficients in local coordinates are the basis for the derivations in all subsequent sections. In Sec. 4, kinematically constrained systems with symmetries are treated, where the configuration space Q is a principal bundle, and the curvature coefficients $\mathcal{B}_{IJ}^{\alpha}$ are obtained as the Hamel coefficients in local bundle coordinates. This principle bundle approach is adopted in Sec. 5 for unconstrained systems with G-invariant Lagrangian, where the coefficients $\mathcal{E}^{\alpha}_{\beta I}$ are obtained immediately as the Hamel coefficients. A rolling sphere and a floating satellite are used to demonstrate application of the equations. Finally, unconstrained floating-base systems with conserved momentum are considered in Sec. 6 with a note on geometric phase and pseudo-holonomic motions. Numerical simulation results for a satellite and a space robot are reported in Sec. 6 and in the supplement [16]. For background material, an excellent introduction to geometric mechanics can be found in the text books [3,17] and the overview articles [4,9,18]. Relevant concepts from differential geometry and on bundles can be found in [3,19,20]. For all derivations, Hamel's original approach is the point of departure. This relies on coordinates on Q, and it is necessary to introduce local coordinates also on the symmetry group (yet the final formulation (1.1,1.2) only needs local coordinates on Q/G with parameter space \mathbb{V}^n). It applies to finite-dimensional systems for which always exist local coordinates on Q, and canonical coordinates on G such as multibody systems. This is in contrast to modern geometric mechanics, where globally valid equations are derived coordinate free, and local coordinates are introduced when needed. However, the coordinate formulations allow to relate the geometric approach to Hamel's formulation. It is assumed throughout the paper that G is a finite-dimensional Lie group possessing local coordinates. Let the Lie algebra \mathfrak{g} be isomorphic to the vector space \mathbb{R}^n . Then $\hat{\mathbf{x}} \in \mathfrak{g}$ denotes the Lie algebra element corresponding to the vector $\mathbf{x} \in \mathbb{R}^n \cong \mathfrak{g}$. Ricci's summation convention is used, e.g. $B_I^a u^I = \sum_I B_I^a u^I$ implies summation over index *I*. The notation is summarized in appendix A.

2. The Hamel Equations

(a) Boltzmann-Hamel Equations in Quasi-Velocities

The configuration is described in terms of n generalized coordinates $q^a, a = 1, ..., n$, with parameter manifold $Q = \mathbb{V}^n$, which serves as configuration space. In case of a multibody system with n_t translation and n_r revolute joints, for instance, $\mathbb{V}^n = T^{n_r} \times \mathbb{R}^{n_t}$, with n_r -torus T^{n_r} and $n = n_r + n_t$. For such systems, the generalized coordinates may only be locally valid. Quasivelocity coordinates $u^a, a = 1, ..., n$, are introduced that are related to the generalized speeds \dot{q}^a by

$$u^a = A^a_b \dot{q}^b, \quad \dot{q}^a = B^a_b u^b \tag{2.1}$$

where A_b^a and B_b^a are smooth functions of **q**. With vectors of generalized coordinates $\mathbf{q} \in \mathbb{V}^n$ and quasi-velocities $\mathbf{u} \in \mathbb{R}^n$, these relations are written in matrix form as

$$\mathbf{u} = \mathbf{A} (\mathbf{q}) \dot{\mathbf{q}}, \quad \dot{\mathbf{q}} = \mathbf{B} (\mathbf{q}) \mathbf{u}.$$
 (2.2)

It is assumed that q^a are valid local coordinates so that **A** is regular, and $\mathbf{B} = \mathbf{A}^{-1}$. The relation of u^a to the corresponding quasi-coordinates π^a , a = 1, ..., n is described by the differential forms $d\pi^a = A_b^a dq^b$, and the inverse relation by $dq^a = B_b^a d\pi^b$. The quasi-coordinates are generalized coordinates if and only if the differential forms are exact, otherwise u^a are called non-holonomic velocities [21,22], following [11, p. 473], [23, p. 218].

Denote with $L(q^a, u^a)$ a Lagrangian in terms of quasi-velocity coordinates u^a , which for mechanical systems is defined as kinetic energy $T(q^a, u^a)$ minus potential energy $U(q^a)$. Then the variational form of the Hamel equations [10,11,22,24] is

$$\left(\frac{d}{dt}\frac{\partial L}{\partial u^a} - \frac{\partial L}{\partial \pi^a} - Q_a\right)\delta\pi^a + \frac{\partial L}{\partial u^a}\left(\frac{d\delta\pi^a - \delta d\pi^a}{dt}\right) = 0$$
(2.3)

where Q_a are generalized forces dual to u^a . The explicit form of the Boltzmann-Hamel equations

$$\frac{d}{dt}\frac{\partial L}{\partial u^a} - \frac{\partial L}{\partial q^b}B^b_a + \frac{\partial L}{\partial u^b}\gamma^b_{ac}u^c = Q_a$$
(2.4)

is obtained after inserting the transitory relation

$$\frac{d\delta\pi^a - \delta d\pi^a}{dt} = \gamma^a_{cb} u^b \delta\pi^c \tag{2.5}$$

in which γ^a_{cb} are the *Hamel coefficients* defined as

$$\gamma_{ab}^{c} := \left(\frac{\partial A_{r}^{c}}{\partial q^{s}} - \frac{\partial A_{s}^{c}}{\partial q^{r}}\right) B_{a}^{r} B_{b}^{s}.$$
(2.6)

The Hamel coefficients vanish identically if and only if (2.1) are integrable, i.e. if u^a are holonomic velocities. The equations (2.4) along with the kinematic equations (2.1) govern the dynamics in the non-holonomic tangent bundle (i.e. tangent space defined by non-holonomic constraints). They are referred to as the Boltzmann-Hamel equations (e.g. in [25,26]) as they where (in a very similar form) presented by Boltzmann in [27,28] and by Hamel in [10,11,29]. It was Hamel, however, who generalized them to systems an a Lie group [24,29].

The motion of many mechanical systems can be described on a *n*-dimensional Lie-group G, so that quasi-velocities belong the corresponding Lie algebra \mathfrak{g} . If $g(t) \in G$, such quasi-velocities can be introduced as left- or right-invariant vector fields, $\hat{\mathbf{u}} = g^{-1}\dot{g}$ or $\hat{\mathbf{u}} = \dot{g}g^{-1}$, respectively. Let q^a be canonical coordinates on *G*, and let $\mathbf{u} \in \mathbb{R}^n$ be the vector representation of $\hat{\mathbf{u}} \in \mathfrak{g}$, then (2.2) is a map from \mathbb{R}^n to $\mathbb{R}^n \cong \mathfrak{g}$. When using the left-invariant definition of quasi-velocities, the Hamel coefficients (2.6) are identical to the structure constants c_{ab}^c of the Lie group. This was already shown by Hamel [24, p. 428] using the transitory relations $d\delta\pi^a - \delta d\pi^a = \gamma^a_{cb} d\pi^c \delta\pi^c$. Using right-invariant quasi-velocities leads to a change of sign: $\gamma_{ab}^c = -c_{ab}^c$. Typical example for such quasi-velocities are the angular velocity (where G = SO(3)) or rigid body twists (where G = SE(3)). Then left-invariance implies body-fixed representation of angular velocity or twists, and right-invariance implies spatial representation [30,31]. The explicit derivation of the Hamelcoefficients for SO(3) and SE(3) using the definition of Hamel coefficients can be found in [32]. Clearly, π^a are holonomic coordinates if and only if G is Abelian. It must be emphasized that canonical coordinates on G are only locally valid in general. This applies in particular to SO(3), and thus to SE(3), since it is not simply connected, which leads to the well-known parameterization singularity of rotations.

In summary, the Hamel equations on a Lie group are the forced Euler-Poincaré equations for Lagrangian $L(q^a, u^a)$

$$\frac{d}{dt}\frac{\partial L}{\partial u^a} \pm c^b_{ac}\frac{\partial L}{\partial u^b}u^c = \frac{\partial L}{\partial q^b}B^b_a + Q_a$$
(2.7)

where the positive sign applies to left-invariant, and the negative sign to right-invariant quasivelocities. These are the reduced Euler-Lagrange equations for systems whose Lagrangian is (left or right) invariant under action of a symmetry group G [9,33].

(b) Hamel Equations for Constrained Systems in Quasi-Velocities

The original Hamel equations for constrained systems where presented in [24]. The velocities $\dot{\mathbf{q}} \in \mathbb{R}^n$ are now subjected to \bar{m} Pfaffian constraints, written as $u^{\alpha} = 0, \alpha = 1, \dots, \bar{m}$, with

$$u^{\alpha} := A^{\alpha}_{a} \left(q^{a} \right) \dot{q}^{a}. \tag{2.8}$$

It is assumed that the system of Pfaffian constraints is regular, i.e. the \bar{m} constraints are independent. Then, $\bar{\delta} := n - \bar{m}$ independent quasi-velocity coordinates are introduced as

$$u^{I} = A_{a}^{I} \left(q^{a} \right) \dot{q}^{a}, \ I = \bar{m} + 1, \dots, n$$
 (2.9)

where $\bar{\delta}$ is the differential DOF of the system (also called instantaneous DOF) [34,35]. The overbar of $\bar{\delta}$ and \bar{m} indicate that the constraints are generally non-holonomic. If they are integrable, there

5

are $m = \bar{m}$ geometric constraints, and $\delta = n - m = \bar{\delta}$ is the finite DOF. The $n - \bar{m}$ independent coordinates are indexed with capital lattin letters I, J, K. The Pfaffian system (2.8) and the solution (2.9) are summarized as $u^a = A_b^a (q^a) \dot{q}^b$, as in (2.1) with index set $\{a\} = \{\alpha, I\}$. The independent coordinates are only locally valid. Moreover, the configuration space of a constrained system is in general not globally a manifold but possesses singularities. This strictly limits the global validity all coordinate formulations.

Denote with $\mathcal{L}(q^a, u^b) := L(q^a, B^a_b u^b)$ the Lagrangian in which \dot{q}^a is replaced by u^a , by means of (2.1). The Hamel equations for the constrained system, in terms of the independent velocities u^I , are then obtained from (2.4) as

$$\frac{d}{dt}\frac{\partial \mathcal{L}}{\partial u^{I}} - \frac{\partial \mathcal{L}}{\partial q^{a}}B_{I}^{a} + \frac{\partial \mathcal{L}}{\partial u^{a}}\gamma_{IJ}^{a}u^{J} = Q_{I}, \quad I = \bar{m} + 1, \dots, n$$
(2.10)

where u^{α} , $\alpha = 1, ..., \bar{m}$ are set to zero after taking the derivatives. The generalized forces are $Q_I = B_I^a Q_a$. The Hamel coefficients in (2.10) are obtained by restricting (2.6) to indices I, J as

$$\gamma_{IJ}^{a} = \left(\frac{\partial A_{b}^{a}}{\partial q^{c}} - \frac{\partial A_{c}^{a}}{\partial q^{b}}\right) B_{I}^{b} B_{J}^{c}.$$
(2.11)

The $n - \bar{m}$ equations (2.10) complemented with the *n* kinematic equations

$$\dot{q}^{a} = B_{I}^{a} \left(q^{a} \right) u^{I}, \ I = \bar{m} + 1, \dots, n$$
(2.12)

govern the system dynamics in terms of state variables (q^a, u^I) . Not all of the q^a may be independent if the constraints are not completely non-holonomic. Relation (2.12) is obtained from (2.2) assuming u^I are locally valid coordinates on the tangent space and constraints are regular.

Quasi-velocities u^{I} are integrable if and only if $\gamma_{IJ}^{K} \equiv 0$. The constraints (2.8), and thus the co-distribution $D^{*} \subset T_{\mathbf{q}}^{*}Q$ with $D_{\mathbf{q}}^{*} := \operatorname{span}(\mathbf{A}(\mathbf{q}))$ defined by the constraints, are integrable (in Pfaffian sense) if and only if $\gamma_{IJ}^{\alpha} \equiv 0$. The *constraint distribution* D on Q, defined as $D_{\mathbf{q}} := \operatorname{ker} \mathbf{A}(\mathbf{q}) \subset T_{\mathbf{q}}Q$, is thus integrable (in Cartan sense) if and only if the Hamel coefficients vanish and the constraints are regular (rank \mathbf{A} is constant). This may not apply to non-regular constraints.

3. Kinematically Constrained Systems on a Trivial Bundle

Many kinematic control problems can be formulated on a trivial bundle. Trivial because there is a global splitting into independent and dependent velocities. The independent velocities serve as control inputs. Moreover, many control system are in Chaplygin form, i.e. the kinematic relations only depend on the independent coordinates.

(a) Constrained Hamel Equations in Terms of Holonomic Velocities

Consider (mechanical) systems described by coordinates q^a and their time derivatives \dot{q}^a , rather then non-holonomic velocities u^I , subjected to scleronomic non-holonomic Pfaffian constraints (2.8). A set of (locally) independent velocity coordinates can be selected.

A particular choice of independent velocities is to use time derivatives of $\bar{\delta} := n - \bar{m}$ coordinates. To this end, the coordinates are partitioned as $\mathbf{q} = (s^{\alpha}, r^{I}) \in \mathbb{V}^{\bar{m}} \times \mathbb{V}^{\bar{\delta}} =: Q$, where $\dot{s}^{\alpha}, 1, \ldots, \bar{m}$ are the dependent, and the remaining $\dot{r}^{I}, I = \bar{m} + 1, \ldots, n$ are independent velocity coordinates, i.e. $u^{I} := \dot{r}^{I}$. This presumes that \dot{r}^{I} are valid local coordinates on Q. Notice that for non-holonomic constraints, this dependency does not hold true for the coordinates s^{α}, r^{I} , and Q serves as *n*-dimensional configuration space. The constraints (2.8) are then written as

$$u^{\alpha} := A^{\alpha}_{\beta} \left(q^{a}\right) \dot{s}^{\beta} + A^{\alpha}_{I} \left(q^{a}\right) \dot{r}^{I}, \alpha = 1, \dots, \bar{m}$$

$$(3.1)$$

$$\mathbf{u} = \mathbf{A} \left(\mathbf{q} \right) \dot{\mathbf{q}} = \begin{pmatrix} \mathbf{A}_1 & \mathbf{A}_2 \\ \mathbf{0} & \mathbf{I} \end{pmatrix} \begin{pmatrix} \dot{\mathbf{s}} \\ \dot{\mathbf{r}} \end{pmatrix}, \text{ with } \mathbf{A}_1 = \begin{pmatrix} A_{\beta}^{\alpha} \end{pmatrix}, \mathbf{A}_2 = \begin{pmatrix} A_I^{\alpha} \end{pmatrix}.$$
(3.2)

where (3.2) resembles the matrix form (2.2). The inverse relation of (3.1) and (3.2) are, respectively,

$$\dot{s}^{\alpha} = B^{\alpha}_{\beta} \left(q^{a} \right) u^{\beta} + B^{\alpha}_{I} \left(q^{a} \right) \dot{r}^{I}$$

$$(3.3)$$

$$\begin{pmatrix} \dot{\mathbf{s}} \\ \dot{\mathbf{r}} \end{pmatrix} = \mathbf{B}(\mathbf{q}) \mathbf{u}, \text{ with } \mathbf{B} = \begin{pmatrix} \mathbf{B}_1 & \mathbf{B}_2 \\ \mathbf{0} & \mathbf{I} \end{pmatrix}, \text{ with } \mathbf{B}_1 = \mathbf{A}_1^{-1}, \mathbf{B}_2 = -\mathbf{A}_1^{-1}\mathbf{A}_2.$$
(3.4)

With A in (3.2) and B in (3.4), the expression (2.11) gives rise to the Hamel coefficients

$$\begin{split} \gamma^{\alpha}_{\beta\lambda} &= \left(\frac{\partial A^{\alpha}_{\mu}}{\partial s^{\nu}} - \frac{\partial A^{\nu}_{\nu}}{\partial s^{\mu}}\right) B^{\mu}_{\beta} B^{\nu}_{\lambda} \\ \gamma^{\alpha}_{IJ} &= \left(\frac{\partial A^{\alpha}_{r}}{\partial q^{s}} - \frac{\partial A^{\alpha}_{s}}{\partial q^{r}}\right) B^{r}_{I} B^{s}_{J} \end{split} \tag{3.5}$$
$$&= \frac{\partial A^{\alpha}_{I}}{\partial r^{J}} - \frac{\partial A^{\alpha}_{J}}{\partial r^{I}} + \left(\frac{\partial A^{\alpha}_{\beta}}{\partial s^{\mu}} - \frac{\partial A^{\alpha}_{\mu}}{\partial s^{\beta}}\right) B^{\beta}_{I} B^{\mu}_{J} + \left(\frac{\partial A^{\alpha}_{I}}{\partial s^{\beta}} - \frac{\partial A^{\alpha}_{\beta}}{\partial r^{I}}\right) B^{\beta}_{J} + \left(\frac{\partial A^{\alpha}_{\beta}}{\partial r^{J}} - \frac{\partial A^{\alpha}_{J}}{\partial s^{\beta}}\right) B^{\beta}_{I} B^{\beta}_{J} \\ \gamma^{\alpha}_{\beta J} &= \left(\frac{\partial A^{\alpha}_{r}}{\partial q^{s}} - \frac{\partial A^{\alpha}_{s}}{\partial q^{r}}\right) B^{r}_{\beta} B^{s}_{J} = \left(\frac{\partial A^{\alpha}_{\nu}}{\partial s^{\mu}} - \frac{\partial A^{\alpha}_{\mu}}{\partial s^{\nu}}\right) B^{\nu}_{\beta} B^{\mu}_{J} + \left(\frac{\partial A^{\alpha}_{\mu}}{\partial r^{J}} - \frac{\partial A^{\alpha}_{J}}{\partial s^{\beta}}\right) B^{\mu}_{\beta}, \ \alpha = 1, \dots, \bar{m}. \end{split}$$

Since the velocities are integrable, it holds true that $\gamma_{ab}^K \equiv 0$. The Hamel coefficients vanish if and only if the constraints are holonomic. The expressions (3.5) will be central throughout the paper as the individual terms in (3.5) allow deriving the coordinate form of the reduced Euler-Lagrange equations for systems with symmetry directly from the Hamel formulation.

The Lagrangian is written as $L(s^{\alpha}, r^{I}, \dot{s}^{\alpha}, \dot{r}^{I})$ to indicate the coordinate partitioning. As in (2.10), denote with $\mathcal{L}(s^{\alpha}, r^{I}, u^{a}) := L(s^{\alpha}, r^{I}, B^{\alpha}_{\beta}u^{\beta} + B^{\alpha}_{I}u^{I}, u^{I})$ the Lagrangian with $\dot{r}^{I} = u^{I}$ and \dot{s}^{α} replaced by (3.3). The Hamel equations follow from (2.10). Noting that $\frac{\partial \mathcal{L}}{\partial u^{\alpha}} = \frac{\partial L}{\partial \dot{s}^{\beta}}B^{\beta}_{\alpha}$, and (with slight abuse of notation) identifying $u^{I} = \dot{r}^{I}$, yields the Hamel equations in independent holonomic velocities \dot{r}^{I}

$$\frac{d}{dt}\frac{\partial \mathcal{L}}{\partial \dot{r}^{I}} - \frac{\partial \mathcal{L}}{\partial r^{I}} + \frac{\partial L}{\partial \dot{s}^{\alpha}}\gamma^{\alpha}_{IJ}\dot{r}^{J} = Q_{I}, \quad I = \bar{m} + 1, \dots, n$$
(3.6)

where \boldsymbol{u}^{α} are set to zero, i.e. the solution

$$\dot{s}^{\alpha} = B_I^{\alpha} \left(q^a \right) \dot{r}^I \tag{3.7}$$

of the constraints is imposed, after taking the derivatives. The dynamic equations (3.6) along with the kinematic equations (3.7) govern the dynamics of the non-holonomically constrained system in terms of the state (q^a, \dot{q}^a) evolving on the non-holonomic tangent bundle.

(b) Kinematic Constraints in Terms of a Bundle Connection

The kinematic constraints $u^{\alpha} = 0$ are now formulated with

$$u^{\alpha} := \dot{s}^{\alpha} + \mathcal{A}_{I}^{\alpha} \left(q^{a} \right) \dot{r}^{I}, \alpha = 1, \dots, \bar{m}$$

$$(3.8)$$

where $(\mathcal{A}_{I}^{\alpha}) := \mathbf{A}_{1}^{-1}\mathbf{A}_{2} = -\mathbf{B}_{2}$, with $\mathbf{B}_{2} = (B_{I}^{\alpha})$ in (3.3). Combined with $u^{I} := \dot{r}^{I}$, this is written in matrix form as

$$\mathbf{u} = \bar{\mathbf{A}} (\mathbf{q}) \, \dot{\mathbf{q}} = \begin{pmatrix} \mathbf{I} & -\mathbf{B}_2 \\ \mathbf{0} & \mathbf{I} \end{pmatrix} \begin{pmatrix} \dot{\mathbf{s}} \\ \dot{\mathbf{r}} \end{pmatrix}.$$
(3.9)

which possesses the obvious inverse relation $\dot{s}^{\alpha} = u^{\alpha} - A_{I}^{\alpha}(q^{a}) u^{I}$, analogously to (3.7), and thus

$$\dot{\mathbf{q}} = \bar{\mathbf{B}}(\mathbf{q}) \mathbf{u} = \begin{pmatrix} \mathbf{I} & \mathbf{B}_2 \\ \mathbf{0} & \mathbf{I} \end{pmatrix} \mathbf{u}.$$
 (3.10)

Noting the specific structure of (3.9) and (3.10), and that only \mathcal{A}_{I}^{α} depends on \mathbf{q} , the corresponding Hamel coefficients are found from (2.11) as $\gamma_{\beta J}^{\alpha} = -\gamma_{J\beta}^{\alpha} = -\frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial s^{\beta}}$, and

$$\gamma_{IJ}^{\alpha} = \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{J}} - \frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial r^{I}} + \frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial s^{\beta}} \mathcal{A}_{I}^{\beta} - \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial s^{\beta}} \mathcal{A}_{J}^{\beta}, \quad \alpha = 1, \dots, \bar{m}; \quad I, J = \bar{m} + 1, \dots, n.$$
(3.11)

The configuration space $Q = \mathbb{V}^{\bar{m}} \times \mathbb{V}^{\bar{\delta}}$ is regarded as a trivial bundle² over the base manifold $\mathbb{V}^{\bar{\delta}}$ with fiber $\mathbb{V}^{\bar{m}}$, and bundle coordinates $(s^{\alpha}, r^{I}) \in \mathbb{V}^{\bar{m}} \times \mathbb{V}^{\bar{\delta}}$. The horizontal space of this trivial bundle is the constraint distribution, i.e. the vector space of velocities satisfying the constraints. The homogenous kinematic constraints (3.8) define a connection on this bundle. Writing the constraints in terms of the Pfaffian forms $\omega^{\alpha} := u^{\alpha} dt = ds^{\alpha} + \mathcal{A}_{I}^{\alpha} dr^{I}$, a connection is introduced as $\mathcal{A} = \omega^{\alpha} \frac{\partial}{\partial s^{\alpha}}$. This is referred to as an Ehresmann connection [3,18,33] with reference to the original publication [36], and \mathcal{A}_{I}^{α} are the local coordinates of the connection. Since it arises from the kinematic constraints, it is called the *kinematic connection* [18]. The connection relates (independent) motions in the base manifold $\mathbb{V}^{\bar{\delta}}$ to motions in the fiber. Whether this connection (i.e. the constraints) is holonomic is revealed by its curvature, denoted $\mathcal{B}_{IJ}^{\alpha}$. Moreover, the curvature of the kinematic connection plays a key role in the control of constrained mechanical systems [3,18,37] as well as in locomotion planning [38] as it encodes how motions in the base manifold generate motions in the fiber. On the trivial vector bundle, the Lie bracket in the curvature (1.3) is the Lie bracket $[\mathcal{A}_{J}, \mathcal{A}_{I}]^{\alpha} = \frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial s^{\beta}} \mathcal{A}_{I}^{\beta} - \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial s^{\beta}} \mathcal{A}_{J}^{\beta}$ of vector fields $\mathcal{A}_{I}, \mathcal{A}_{J}$ on Q, so that the local curvature is $\mathcal{B}_{IJ}^{\alpha} = \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{J}} - \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{\beta}} + [\mathcal{A}_{J}, \mathcal{A}_{I}]^{\alpha}$ [18, p. 32], [3, p. 108]. The Hamel coefficients (3.11) are thus clearly related to the coordinate form of the curvature as follows.

Proposition 3.1. The Hamel coefficients (3.11) are identical to the curvature components of the kinematic connection A, in bundle coordinates (s^{I}, r^{α}) , induced by the constraints with (3.8), i.e. $\mathcal{B}_{IJ}^{\alpha} = \gamma_{IJ}^{\alpha}$.

Although local coordinates are used in this paper, it should be mentioned that the curvature of a connection \mathcal{A} is its covariant derivative, written coordinate-free as $\mathcal{B}(X,Y) = d\mathcal{A}(X,Y) - [\mathcal{A}(X), \mathcal{A}(Y)]$, with horizontal vector fields X, Y, i.e. $\mathcal{B}^{\alpha}(X,Y) = \mathcal{B}_{IJ}^{\alpha}X^{I}Y^{J} = \gamma_{IJ}^{\alpha}X^{I}Y^{J}$.

Remark 3.1. The constraints are holonomic if and only if the kinematic connection is flat, i.e. the components $\mathcal{B}_{IJ}^{\alpha}$ of the curvature 2-form vanish identically. In this case, $\mathbb{V}^{\overline{\delta}}$ serves as configuration space. Constraints are said to be in Chaplygin form if $\mathcal{A} = \mathcal{A}(\mathbf{r})$, referring to Chaplygin's publications [39,40]. In this case, the Hamel-coefficients (2.10) reduce to $\gamma_{IJ}^{\alpha} = \frac{\partial A_{I}^{\alpha}}{\partial r^{J}} - \frac{\partial A_{I}^{\alpha}}{\partial r^{I}}$, which implies the obvious condition $\frac{\partial A_{I}^{\alpha}}{\partial r^{J}} \equiv \frac{\partial A_{I}^{\alpha}}{\partial r^{J}} = \frac{\partial A_{I}^{\alpha}}{\partial r^{I}}$ for integrability of $ds^{\alpha} + \mathcal{A}_{I}^{\alpha}(r^{J})dr^{I} = 0$.

(c) Hamel Equations on a Trivial Bundle, Lagrange-d'Alembert equations

The Hamel coefficients can now be identified with the components of the local curvature. Then the Hamel equations of the constrained system in holonomic bundle coordinates (r^{I}, s^{α}) follow from (3.6) as

$$\frac{d}{dt}\frac{\partial \mathcal{L}}{\partial \dot{r}^{I}} - \frac{\partial \mathcal{L}}{\partial r^{I}} + \frac{\partial L}{\partial \dot{s}^{\alpha}}\mathcal{B}_{IJ}^{\alpha}\dot{r}^{J} = Q_{I}, \quad I = \bar{m} + 1, \dots, n$$
(3.12)

with $Q_I = A_I^a Q_a$, in which u^{α} is set to zero, and u^I is replaced by \dot{r}^I . The dynamic equations are written in terms of the coordinates r^I on the base manifold of the bundle. The remaining coordinates, the fiber coordinates, are obtained as solution of

$$\dot{s}^{\alpha} = -\mathcal{A}_{I}^{\alpha} \left(q^{a}\right) \dot{r}^{I}. \tag{3.13}$$

The constrained dynamics is governed by the Hamel equations (3.12) along with the kinematic equations (3.13). The equations (3.12) are obtained as constrained Lagrange–d'Alembert ${}^{2}Q = M \times F$ is a trivial bundle if it can be written as Cartesian product of a manifold M and F, and if there is a projection $\pi : Q \to M$ [19]. F is called the standard fiber. For the considered systems, the base manifold is the coordinate subspace $\mathbb{V}^{\tilde{\Lambda}}$ corresponding to the independent velocities, and the fiber is the subspace $\mathbb{V}^{\tilde{m}}$ corresponding to dependent velocities.

rspa.royalsocietypublishing.org Proc R Soc A 0000000

equations with variations satisfying the constraints $0 = \delta s^{\alpha} + A_{I}^{\alpha}(r^{I})\delta r^{I}$ [3,8,18], which is a particular form of Hamel's equations when using a connection to introduce constraints.

Remark 3.2. Introduce the constrained Lagrangian $L_c(s^{\alpha}, r^I, \dot{r}^I) := L(s^{\alpha}, r^I, -\mathcal{A}_I^{\alpha} \dot{r}^I, \dot{r}^I) = \mathcal{L}(s^{\alpha}, r^I, u^{\alpha} := 0, u^I := \dot{r}^I)$, i.e. the Lagrangian with the constraints resolved. The Hamel equations (3.12) attain the instructive form

$$\frac{d}{dt}\frac{\partial L_{\rm c}}{\partial \dot{r}^{I}} - \frac{\partial L_{\rm c}}{\partial r^{I}} + \frac{\partial L_{\rm c}}{\partial s^{\alpha}}\mathcal{A}_{I}^{\alpha} + \frac{\partial L}{\partial \dot{s}^{\alpha}}\gamma_{IJ}^{\alpha}\dot{r}^{J} = Q_{I}, \quad I = \bar{m} + 1, \dots, n,$$
(3.14)

which reveals the consequence of non-holonomicity of the constraints. They were reported in [37, p. 326] (setting $\gamma_{IJ}^{\alpha} = \mathcal{B}_{IJ}^{\alpha}$), and in a similar form for constraints independent of s^{I} by Chaplygin [22,39]. The Hamel coefficients reveal the consequence of non-holonomic constraints. Clearly, if the constraints are completely holonomic, these are the classical Lagrange equations. A direct calculation shows that (3.14) can be written in the form

$$\frac{d}{dt}\frac{\partial L}{\partial \dot{r}^{I}} - \frac{\partial L}{\partial r^{I}} + \mathcal{A}_{I}^{a}\left(\frac{d}{dt}\frac{\partial L}{\partial \dot{s}^{\alpha}} - \frac{\partial L}{\partial s^{\alpha}}\right) = \mathcal{A}_{I}^{a}Q_{a}, \quad I = \bar{m} + 1, \dots, n$$
(3.15)

which have been reported by Voronets [41,42], and are referred to as Voronets equations [25,43].

4. Kinematically Constrained Mechanical Systems with Symmetry

Many kinematically constrained systems possess principal symmetries in the sense that the kinematic constraints are invariant under the action of a symmetry group *G*. The configuration space can then be regarded as a principal bundle³. Moreover, this is a trivial principal bundle when the kinematic constraints do not depend on group variables. Examples are mobile platforms and manipulators, or locomotion systems, where *G* is often a subgroup of *SE* (3), the group of rigid body (i.e. Euclidean) motions, and $g \in G$ describes the motion of a base body. The governing equations are the reduced Euler-Lagrange equations on the principle bundle.

(a) Constraints in Terms of a Connection on a Trivial Principal Bundle

The (non-holonomic) constraints are assumed to be invariant under the action of a Lie group G. Chaplygin systems are included as special case with Abelian symmetry group. The *configuration* space of the system is regarded as a trivial principal bundle $Q = G \times \mathbb{V}^{\overline{\delta}}$ over the base manifold $\mathbb{V}^{\overline{\delta}}$ with fiber G. The dimension of G is assumed to be equal to the number of constraints, and is denoted with \overline{m} (to be consistent with the preceding section). Typically, fiber elements $g \in G$ represent the overall configuration of the system in ambient space, and are often called 'body coordinates' (or 'rigid coordinates'). The coordinates $\mathbf{r} = (r^I) \in \mathbb{V}^{\overline{\delta}}$ represent the internal shape, and are called 'shape coordinates' (or 'internal variables'), and $\mathbb{V}^{\overline{\delta}}$ is called the *shape space*. For multibody systems, \mathbf{r} is the vector of joint variables. Notice that r^I are only locally valid coordinates in general. The case when the number of constraints is less then the dimension of the symmetry group G has been addressed for motion planning of non-holonomically constrained mechanical control systems in [44].

Kinematic constraints that are left-invariant under actions of *G* are expressed as Pfaffian system $u^{\alpha} = 0, \alpha = 1, ..., \bar{m}$, with

$$u^{\alpha} := \xi^{\alpha} + \mathcal{A}_{I}^{\alpha}(r^{I})\dot{r}^{I} \tag{4.1}$$

where $\hat{\boldsymbol{\xi}} = g^{-1}\dot{g} \in \mathfrak{g}$, and $\boldsymbol{\xi} = (\xi^{\alpha}) \in \mathbb{R}^n$ are the fiber coordinates in a left-trivialization. More precisely, for rigid body systems (where G = SE(3)), $\boldsymbol{\xi}$ is the velocity (also called twist) of

³A space $Q = G \times Q/G$ is a *principle bundle*, where *G* is a Lie group, with Lie algebra \mathfrak{g} , acting free and proper on *Q*, equipped with a projection $\pi : Q \to Q/G$ [20]. In a local trivialization, the *base space* Q/G can be identified with a manifold *B* so that $Q = G \times B$. If this splitting is globally valid, *Q* is a *trivial principle bundle*. In a local trivialization, with local coordinates $(\xi^{\alpha}, \dot{r}^{I})$, *B* will be identified with $\mathbb{V}^{\overline{\delta}}$. For a given $\mathbf{r} \in \mathbb{V}^{\overline{\delta}}$, π^{-1} (\mathbf{r}) is the fiber over \mathbf{r} . For mechanical systems, \mathbf{r} describes the internal configuration (shape) of the system, and fiber elements $g \in G$ represent the pose of a base body.

a reference body in 'body-fixed' representation. The constraints (4.1) give rise to a principal connection on the trivial principal bundle, denoting $\mathcal{A}d\mathbf{r} = (\mathcal{A}_{I}^{\alpha}dr^{I})$,

$$\mathcal{A}^{\mathrm{kin}} = Ad_g(g^{-1}dg + \mathcal{A}d\mathbf{r}) = dgg^{-1} + Ad_g(\mathcal{A}d\mathbf{r})$$
(4.2)

so that the horizontal subspace of the connection is the space of velocities satisfying the constraints, and \mathcal{A}^{kin} is a g-valued one-form (which may be considered as a special type of Ehresmann connection) called the *kinematic connection* as it arises from (4.1) by requiring it to be *G*-equivariant [3]. The name stems from the fact that it relates base and fiber motions according to the kinematic constraints. It is sufficient to use the local connection form \mathcal{A}_I^{α} in (4.1) as it encodes all relevant information. The symbol \mathcal{A}^{kin} is used to distinguish it from the coefficients of the local form \mathcal{A}_I^{α} . Next, the Hamel coefficients are derived and are identified as the coefficients of the curvature of the kinematic connection.

(b) The Hamel Coefficients and the Kinematic Connection

The dynamics of the constrained system is governed by the reduced Lagrange-d'Alembert-Poincaré equations, which have been derived from the variational principle [9,45]. To derive them as the constrained Hamel equations necessitates the corresponding Hamel coefficients.

Lemma 4.1. The non-vanishing Hamel coefficients in (2.10) for the system subjected to left *G*-invariant constraints are

$$\gamma_{IJ}^{\alpha} = \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{J}} - \frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial r^{I}} + c_{\lambda\mu}^{\alpha} \mathcal{A}_{I}^{\lambda} \mathcal{A}_{J}^{\mu}, \quad \alpha = 1, \dots, \bar{m}.$$
(4.3)

Proof. In order to apply the original definition (2.6) of the Hamel coefficients, local canonical coordinates $s^{\alpha}, \alpha = 1, ..., \bar{m}$ are introduced on *G*. The fiber coordinates are then expressed as $\xi^{\alpha} = A^{\alpha}_{\beta} (s^{\alpha}) \dot{s}^{\beta}$, with inverse relation $\dot{s}^{\alpha} = B^{\alpha}_{\beta} (s^{\alpha}) \xi^{\beta}$, and (4.1) is written as

$$u^{\alpha} = A^{\alpha}_{\beta} \left(s^{\alpha}\right) \dot{s}^{\beta} + \mathcal{A}^{\alpha}_{I}(r^{J}) \dot{r}^{I}.$$

$$(4.4)$$

This resembles the relation (3.1) with $A^{\alpha}_{\beta} = A^{\alpha}_{\beta}(s^{\alpha})$ and $A^{\alpha}_{I} = A^{\alpha}_{I}(r^{J})$. The inverse relation is

$$\dot{s}^{\alpha} = B^{\alpha}_{\beta} \left(s^{a}\right) u^{\beta} - B^{\alpha}_{\beta} \left(s^{a}\right) \mathcal{A}^{\beta}_{I} (r^{J}) u^{I}$$

$$\tag{4.5}$$

with B^{α}_{β} defined in (3.4). Noting that $A^{I}_{a} = \text{const}$, the only non-zero Hamel coefficients for the constrained system are γ^{α}_{IJ} . They are immediately found from (3.5), by replacing $A^{\alpha}_{I}(r^{J})$ with $\mathcal{A}^{\alpha}_{I}(r^{J})$, and B^{α}_{I} with $-B^{\alpha}_{\beta}(s^{a})\mathcal{A}^{\beta}_{I}(r^{J})$, as

$$\gamma_{IJ}^{\alpha} = \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{J}} - \frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial r^{I}} + \left(\frac{\partial A_{\delta}^{\alpha}}{\partial s^{\lambda}} - \frac{\partial A_{\lambda}^{\alpha}}{\partial s^{\delta}}\right) B_{\gamma}^{\delta} B_{\mu}^{\lambda} \mathcal{A}_{I}^{\gamma} \mathcal{A}_{J}^{\mu}.$$
(4.6)

It was already shown by Hamel [24, p. 428] that the terms $\gamma^{\alpha}_{\beta\lambda} = \left(\frac{\partial A^{\mu}_{\mu}}{\partial s^{\nu}} - \frac{\partial A^{\nu}_{\nu}}{\partial s^{\mu}}\right) B^{\mu}_{\beta} B^{\nu}_{\lambda} = c^{\alpha}_{\beta\lambda}$ are the structure constants of *G*. A more recent reference is [46, p. 301]. This was derived explicitly in [32] for *SO*(3) and *SE*(3) using the original definition of Hamel coefficients.

The expressions (4.3) are the coefficients of the local curvature of the connection \mathcal{A}^{kin} on the principal bundle possibly up to a change of sign [19,47] (for the sign convention see Rem. 5.3). In context of geometric mechanics, this can be stated as follows [18, notice the correction on p. 44].

Proposition 4.1. The Hamel coefficients (4.3) for left-invariant kinematic constraints (4.1) are the components of the curvature (1.3) of the kinematic connection defined in bundle coordinates $(\xi^{\alpha}, \dot{r}^{I})$ on the corresponding left-trivialized principal bundle: $\mathcal{B}_{IJ}^{\alpha} = \gamma_{IJ}^{\alpha}$. Noting that the curvature coefficients are identical to the Hamel coefficients, the connection is flat, if and only if the constraints are holonomic.

Also the curvature on the principle bundle can be defined coordinate-free as covariant derivative $\mathcal{B}(X,Y) = d\mathcal{A}(X,Y) - [\mathcal{A}(X), \mathcal{A}(Y)]$, with horizontal vector fields X, Y, now with Lie bracket on \mathfrak{g} . In local coordinates, it is $\mathcal{B}^{\alpha}(X,Y) = \gamma_{IJ}^{\alpha} X^{I} Y^{J}$.

Remark 4.1. If right trivialization is used, i.e. $\hat{\boldsymbol{\xi}} = \dot{g}g^{-1} \in \mathfrak{g}$ are right invariant vector fields (e.g. using spatial velocities), then $\gamma^{\alpha}_{\beta\lambda} = \left(\frac{\partial A^{\alpha}_{\mu}}{\partial s^{\nu}} - \frac{\partial A^{\alpha}_{\mu}}{\partial s^{\mu}}\right) B^{\mu}_{\beta} B^{\nu}_{\lambda} = -c^{\alpha}_{\beta\lambda}$, and the Hamel coefficients (4.3) are

$$\gamma_{IJ}^{\alpha} = \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{J}} - \frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial r^{I}} - c_{\lambda\mu}^{\alpha} \mathcal{A}_{I}^{\lambda} \mathcal{A}_{J}^{\mu}, \ \alpha = 1, \dots, \bar{m}.$$

$$(4.7)$$

Remark 4.2. The constraints (4.1) give rise to a kinematic control system on G that can be written as $\xi^{\alpha} = -\mathcal{A}_{I}^{\alpha}(r^{I})\dot{r}^{I}$. Such control systems with symmetry were addressed in various publications, e.g. [38, 44,48,49]. Controllability of this driftless control problem is encoded in the control vector fields \mathcal{A}_{I}^{α} and the distribution on the fiber defined by them. Written as $\dot{g} = -g\mathcal{A}d\dot{r}$ shows that the connection describes how a path in shape space is lifted to a path in the group (called the horizontal lift of the curve), which is the basis for kinematic control. The net change in the group variable as result of the horizontal lift of a closed curve in shape space is the holonomy (in this context called the geometric phase). The latter can be related to the curvature of the kinematic connection. Let ϕ be a closed path in $\mathbb{V}^{\overline{\delta}}$. The geometric phase is then found as

$$g(\phi) = -\oint_{\phi} g\mathcal{A}d\mathbf{r} = -\int_{\Phi} \mathcal{B} + \text{hot.}$$
(4.8)

using $\dot{g} = g\hat{\xi} = -g\mathcal{A}\dot{\mathbf{r}}$, where Φ is the area enclosed by the path in \mathbb{V}^{δ} , and $\mathcal{B} = (\mathcal{B}_{IJ}^{\alpha}dr^{I}dr^{J})$. If the constraints are holonomic, i.e. the curvature vanishes, the geometric phase is zero. This is an important relation for locomotion planning, where the closed path ϕ represents a gait, and the aim is to maximize the net motion in G generated by a gait [38]. The geometric phase further discussed in Sec. 6.

(c) The Hamel Equations, Lagrange-d'Alembert-Poincaré equations

The Lagrangian $L(g, r^I, \dot{g}, \dot{r}^I)$, defined on the configuration space Q, is assumed to be (left or right) *G*-invariant so that the reduced Lagrangian $l(r^I, \xi^{\alpha}, \dot{r}^I)$ can be introduced on the corresponding bundle trivialization. Assume that the motion in *G* is completely determined by the motion in the base manifold, i.e. the group orbits complement the constraints. This is called the 'principal kinematic case' [3,18] since then there is no momentum equation left on the fibre.

The Pfaffian equations (4.1) can be resolved as $\xi^{\alpha} = u^{\alpha} - \mathcal{A}_{I}^{\alpha}\dot{r}^{I}$. In the Hamel formalism, the u^{α} are regarded as intermediate coordinates, and setting $u^{\alpha} = 0$ yields the constraint solution. Denote with $\ell(r^{I}, u^{\alpha}, u^{I}) := l(r^{I}, \xi^{\alpha} := u^{\alpha} - \mathcal{A}_{I}^{\alpha}\dot{r}^{I}, \dot{r}^{I} := u^{I})$ the Lagrangian in terms of u^{α} in (4.1) and $\dot{r}^{I} := u^{I}$. The Hamel equations (2.10) for the constrained system are expressed using proposition 4.1 as

$$\frac{d}{dt}\frac{\partial\ell}{\partial\dot{r}^{I}} - \frac{\partial\ell}{\partial r^{I}} = \frac{\partial l}{\partial u^{\beta}}\mathcal{B}_{IJ}^{\beta}\dot{r}^{J} + Q_{I}, \quad I = \bar{m} + 1, \dots, n$$
(4.9)

where u^{α} is set to zero, and $u^{I} = \dot{r}^{I}$. These are indeed equations (1.2) when setting $\Omega^{\alpha} = u^{\alpha} = 0$. The velocities in the fiber are obtained with the kinematic connection as $\xi^{\alpha} = -\mathcal{A}_{I}^{\alpha}(\mathbf{r}) \dot{r}^{I}$, which is the principle bundle equivalent of (3.13). In geometric mechanics, equations (4.9) are obtained as Lagrange–d'Alembert–Poincaré equations with variations satisfying the constraints $u^{\alpha} = 0$ with (4.1). The motion g(t) in the fiber G is obtained by solving the *kinematic reconstruction equations*

$$\dot{g} = g \dot{\xi}$$
 (left trivialization) or $\dot{g} = \dot{\xi}g$ (right trivialization) (4.10)

where $\boldsymbol{\xi} = -\mathcal{A}\dot{\mathbf{r}}$. The Hamel equations (4.9) along with the reconstruction equations (4.10) govern the dynamics of the constrained system on the principle bundle Q. Chaplygin systems (Rem. 3.1) are special cases with Abelian symmetry group $G = \mathbb{R}^{\bar{m}}$, where $\mathcal{B}_{IJ}^{\alpha} = \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{I}} - \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{J}}$. rspa.royalsocietypublishing.org Proc R Soc A 0000000

Remark 4.3. Equations (4.10) are the Poisson equations on *G*. They are known in context of rigid body kinematics as the left- and right Poisson-Darboux equations, referring to [50], or as the generalized Poisson-Darboux equations [51]. In order to solve these differential equations on *G*, *g* is expressed as the exponential of a $\eta(t) \in \mathfrak{g}$, and (4.10) are replaced by the following differential equations on \mathfrak{g}

$$\begin{aligned} \dot{\hat{\boldsymbol{\eta}}} &= \operatorname{dexp}_{-\hat{\boldsymbol{\eta}}}^{-1}(\hat{\boldsymbol{\xi}}) = -\operatorname{dexp}_{-\hat{\boldsymbol{\eta}}}^{-1}(\mathcal{A}\dot{\mathbf{r}}), \text{ with } g = g_0 \exp(\hat{\boldsymbol{\eta}}) \text{ (left trivialization)} \end{aligned} \tag{4.11} \\ \dot{\hat{\boldsymbol{\eta}}} &= \operatorname{dexp}_{\hat{\boldsymbol{\eta}}}^{-1}(\hat{\boldsymbol{\xi}}) = -\operatorname{dexp}_{\hat{\boldsymbol{\eta}}}^{-1}(\mathcal{A}\dot{\mathbf{r}}), \text{ with } g = \exp(\hat{\boldsymbol{\eta}})g_0 \text{ (right trivialization)} \end{aligned}$$

with initial value $g_0 \in G$, where $\hat{\eta}(t) \in \mathfrak{g}$ represents a local canonical parameterization of G, and dexp is the right-trivialized differential of the exp map on G. The latter is defined by $\dot{g}g^{-1} = \operatorname{dexp}_{\hat{\eta}}(\hat{\eta})$ assuming $g = \exp(\hat{\eta})g_0$. This replacement is a key step in Lie group integration schemes [52–54]. For many Lie groups relevant to solid mechanics, there are closed from expressions for the dexp map, in particular for SO(3) and SE(3) [55]. The maps dexp and dexp⁻¹ can be evaluated using truncated series expansions.

(d) Example: Homogenous ball rolling without slipping or spinning

As a simple example, consider a ball on a horizontal plane that is subjected to pure rolling, i.e. in addition to the rolling-without-slipping constraint it is further constrained so that it cannot spin about its instantaneous vertical axis, which is parallel to the plane normal. Its configuration is described by its orientation and the location of its point of contact with the plane. The configuration space is the bundle $SO(3) \times \mathbb{R}^2$ over $M = \mathbb{R}^2$. The motion in the fiber G = SO(3)(the orientation) is completely determined by the motion of the contact point so that this example is a 'principal kinematic case'. Since the constraints and the potential energy (gravity) are right *G*-invariant, the kinetic energy is bi-invariant, the configuration space is regarded as a righttrivialized trivial principal bundle. It is assumed that the center of mass (COM) of the ball is at its geometric center. Denote with $\rho \in \mathbb{R}^3$ the vector from contact point to the COM of the ball, with $\mathbf{p} \in \mathbb{R}^3$ the position of contact point, and $\mathbf{R} \in SO(3)$ describes the rotation of the body-fixed frame $\mathcal{F}_{\rm b}$ relative to the inertial frame \mathcal{F}_0 . The angular velocity $\omega \in \mathbb{R}^3 \cong so(3)$ of the ball in spatial representation is defined by $\hat{\omega} = \dot{\mathbf{R}}\mathbf{R}^T \in so(3)$. All vectors are expressed in inertial frame \mathcal{F}_0 . This frame is introduced such that its 3-axis is parallel and directed along the plane normal, so that $\rho = (0, 0, R)^T$, where R is the ball radius.

The rolling condition is $\mathbf{0} = \dot{\mathbf{p}} + \tilde{\rho}\omega$, which can be transformed to $\mathbf{0} = \tilde{\rho}\dot{\mathbf{p}} + R^2\omega - (\rho\rho^T)\omega$. Here $\tilde{\rho}$ is the skew symmetric matrix so that the cross product of vector \mathbf{x} and \mathbf{y} is $\tilde{\mathbf{x}}\mathbf{y} = \mathbf{x} \times \mathbf{y}$ that is written in components as $\varepsilon_{ijk}x^jy^k$, with the Levi-Civita symbol ε_{ijk} . The non-spinning condition is $0 = \rho^T \omega$, which amounts to the constraint $\omega^3 = 0$, and the rolling condition simplifies to $\mathbf{0} = \omega + \frac{1}{R^2}\tilde{\rho}\dot{\mathbf{p}}$. Since ρ is along the plane normal, the rolling condition is $0 = \frac{1}{R^2}\varepsilon_{\alpha JI}\rho^J = \frac{1}{R}\varepsilon_{\alpha 3I}$. The 'shape coordinates' $\mathbf{r} = (r^4, r^5) = (p^1, p^2) \in \mathbb{R}^2$ are the coordinates of the contact



Figure 1. Ball rolling without spinning about the vertical axis.

location in the plane. For sake of compactness, denote $\bar{I} = I - 3$. Local bundle coordinates are ω^{α} , $\alpha = 1, 2, 3$ and $\dot{r}^{I} = \dot{p}^{\bar{I}}$, I = 4, 5. The $\bar{m} = 3$ kinematic constraints are $0 = u^{\alpha}$, $\alpha = 1, 2, 3$,

$$u^{\alpha} := \omega^{\alpha} + \mathcal{A}_{I}^{\alpha} \dot{r}^{I}, \quad \mathcal{A}_{I}^{\alpha} := \begin{cases} \frac{1}{R} \varepsilon_{\alpha 3 \bar{I}}, & \alpha = 1, 2\\ 0, & \alpha = 3 \end{cases}$$
(4.12)

The Hamel coefficients are $\gamma_{IJ}^{\alpha} = -c_{\beta\mu}^{\alpha} \mathcal{A}_{I}^{\beta} \mathcal{A}_{I}^{\mu}$, I, J = 4, 5 (negative sign is due to right-trivialization), which is only non-zero for $\alpha = 3$ as $\beta, \mu = 1, 2$. Evaluation yields $c_{\beta\mu}^{\alpha} \mathcal{A}_{I}^{\beta} \mathcal{A}_{J}^{\mu} = \frac{1}{R^{4}} \varepsilon_{\alpha\beta\mu} \varepsilon_{\beta r \bar{I}} \varepsilon_{\mu s \bar{J}} \rho^{r} \rho^{s} = \frac{1}{R^{4}} (\delta_{\mu r} \delta_{\alpha \bar{I}} - \delta_{\mu \bar{I}} \delta_{\alpha r}) \varepsilon_{\mu s \bar{J}} \rho^{r} \rho^{s} = -\frac{1}{R^{4}} \rho^{\alpha} \varepsilon_{\bar{I}} s_{\bar{J}} \rho^{s} = -\frac{1}{R^{2}} \rho^{\alpha} \mathcal{A}_{J}^{\beta} \delta_{\bar{J}}^{\bar{I}}$, thus

$$\gamma_{IJ}^{\alpha} = \begin{cases} 0, & \alpha = 1, 2\\ \frac{1}{R} \mathcal{A}_{J}^{\bar{I}}, & \alpha = 3 \end{cases}$$
(4.13)

In summary, the non-zero coefficients are $\mathcal{A}_4^2 = -\mathcal{A}_5^1 = \frac{1}{R}$ and $\mathcal{B}_{54}^3 = -\mathcal{B}_{45}^3 = \gamma_{54}^3 = \frac{1}{R^2}$.

The Lagrangian is identical to the kinetic energy (potential energy does not affect the motion of the ball). The right-reduced Lagrangian is $l(\omega^{\alpha}, \dot{r}^{I}) = \frac{m}{2} \delta_{IJ} \dot{r}^{I} \dot{r}^{J} + \frac{1}{2} \Theta_{\alpha\beta} \omega^{\alpha} \omega^{\beta}$, where $\Theta_{\alpha\beta}$ is the inertia tensor of the homogenous ball w.r.t. its COM expressed in the spatial inertial frame \mathcal{F}_{0} , and m is its mass. The Lagrangian in terms of $u^{I} = \dot{r}^{I}$ and u^{α} in (4.12) is

$$\ell(u^{\alpha}, u^{I}) = l(\omega^{\alpha} := u^{\alpha} - \mathcal{A}^{\alpha}_{J} u^{I}, \dot{r}^{I} := u^{I}) = \frac{m}{2} \delta_{IJ} u^{I} u^{J} + \frac{1}{2} \Theta_{\alpha\beta} (u^{\alpha} - \mathcal{A}^{\alpha}_{I} u^{I}) (u^{\beta} - \mathcal{A}^{\beta}_{J} u^{J}).$$

$$(4.14)$$

The Hamel equations (4.9), with $Q_I = 0$, are found as (with $r^I = p^I$)

$$(m\delta_{IJ} - \Theta_{\alpha\beta}\mathcal{A}_{I}^{\alpha}\mathcal{A}_{J}^{\beta})\ddot{r}^{J} - \frac{1}{R}\Theta_{3\beta}\mathcal{A}_{K}^{\beta}\dot{r}^{K}\mathcal{A}_{J}^{\bar{I}}\dot{r}^{J} = 0, \quad I = 4,5$$

$$(4.15)$$

where $\alpha, \beta \in \{1, 2\}$. The second term in (4.15) is the force due to the gyroscopic torque caused by the pure rolling. To see this, notice that $\pi_3 = \Theta_{3\beta} \mathcal{A}_K^\beta \dot{r}^K$ is the vertical component of the angular momentum $\pi_\alpha = \Theta_{\alpha\beta} \omega^\beta$ due to the rolling (note $\omega^3 = 0$), and the gyroscopic torque is $\varepsilon_{\alpha\beta\lambda} \omega^\beta \pi_\lambda$. The force is obtained as cross product of this torque with ρ , noting that $\pi_1 = \pi_3 = 0$ and $\omega_3 = 0$.

Remark 4.4. The principal kinematic case can be extended by allowing the Lagrangian to be invariant under actions of a subgroup of the symmetry group G of the constraints, i.e. infinitesimal generators of this subgroup lie in the constraint distribution. Then the system is said to possess horizontal symmetries (relative to the constraints) [3,4,18]. In this case, the kinematic connection along with a connection accounting for the horizontal symmetry can be introduced. As an example for mechanical systems with horizontal symmetries, a ball moving on a plane, i.e. a rolling ball that is free to spin about the plane normal, was used in [4,18]. The horizontal symmetry is then due to the momentum being invariant under the subgroup $SO(2) \subset SO(3)$ of rotations about the plane normal. The \bar{m} rolling constraints are the 1and 2-component of the condition $\mathbf{0} = \dot{\mathbf{r}} + \tilde{\boldsymbol{\rho}}\boldsymbol{\omega}$ above. The invariant momentum is the 3-component of $\boldsymbol{\Theta}\boldsymbol{\omega}$.

Floating-Base Mechanical Systems with Symmetries

If the Lagrangian $L: TQ \to \mathbb{R}$ is *G*-invariant and can be written as $L(g, r^I, \dot{g}, \dot{r}^I)$, the *n*-dimensional configuration space is regarded as a principal bundle, which admits the local trivialization $Q = G \times Q/G$. This parallels the formulation of constrained systems in Sec. 4, where *G* was the symmetry group of the constraints. The quotient space Q/G is again the *shape space*, which can locally be identified with $\mathbb{V}^{\overline{\delta}}$. This setting applies to many mechanical systems possessing symmetry invariants. Typical examples are floating multibody systems (humanoids, areal vehicles, space robots), where the fiber *G* is a subgroup of *SE*(3) representing the overall spatial motion, and $Q/G \cong \mathbb{V}^{\overline{\delta}}$ represents the internal shape. An early problem that was considered as a controlled floating-base system within this framework is the falling cat [56–61].

As an example, consider a human body (or humanoid robot) model. The spatial hip motion is described by $g \in G = SE(3)$, and the motion of body segments (body shape) relative to the hip is described by the joint variables (angles) $\mathbf{r} \in \mathbb{V}^{\overline{\delta}}$. The kinetic energy is invariant under left

13

G-actions, while the potential energy is invariant under rotations about the vector of gravity. Thus, with the obvious choice G = SE(3), and with the Lagrangian defined as kinetic minus potential energy, Q is not a principal bundle. This situation is referred to as symmetry breaking. However, for most mechanical systems, a *G*-invariant Lagrangian can be defined, e.g. restricting it to the kinetic energy and including potential forces separately. Moreover, for discrete mechanical systems, this bundle is often trivial, so that the configuration space is $Q = G \times M$, with shape space M, which will be identified with $\mathbb{V}^{\overline{\delta}}$ in the following, as in Sec. 4. This is naturally so for floating base multibody systems. It is assumed in the following, that Q is a principal bundle , and a local trivialization is assumed. In a local bundle trivialization, the Lagrangian is then written as $l(r^I, \xi^{\alpha}, \dot{r}^I) = T(r^I, \xi^{\alpha}, \dot{r}^I) - V(r^I)$ (Note that it is still possible to introduce a potential depending on shape variables r^I , e.g. accounting for compliant elements).

(a) Boltzmann-Hamel Equations Reduced Euler–Lagrange Equations

The Boltzmann-Hamel equations are expressed in terms of the velocity coordinates $(u^a) = (\xi^{\alpha}, \dot{r}^I)$, where $\xi^{\alpha} = A^{\alpha}_{\beta} (s^{\alpha}) \dot{s}^{\beta}$ are expressed in terms of canonical coordinates s^{β} on G (as in Sec. 4(b)). The Hamel coefficients $\gamma^I_{bc} \equiv 0$ follow immediately noting that \dot{r}^I are integrable, and $\gamma^{\alpha}_{bc} \equiv 0$ follows from (2.6) noting that ξ^{α} are independent of r^I . The remaining coefficients $\gamma^{\alpha}_{\beta\delta} = \pm c^{\alpha}_{\beta\delta}$ are the structure constants of G (lemma 4.1). The Boltzmann-Hamel equations (2.4) to the Lagrangian $l(r^I, \xi^{\alpha}, \dot{r}^I)$ are thus the well-known equations [9,33]

$$\frac{d}{dt}\frac{\partial l}{\partial \xi^{\alpha}} \pm \frac{\partial l}{\partial \xi^{\beta}} c^{\beta}_{\alpha\lambda} \xi^{\lambda} = 0$$
(5.1)

$$\frac{d}{dt}\frac{\partial l}{\partial \dot{r}^{I}} - \frac{\partial l}{\partial r^{I}} = 0$$
(5.2)

where in (5.1) the positive sign holds for a left-trivialization ($\hat{\xi} = g^{-1}\dot{g}$ body velocities), and the negative sign when right-trivialization is used ($\hat{\xi} = \dot{g}g^{-1}$ spatial velocities). The base motion is reconstructed with the respective kinematic equation in (4.10).

The above equations obviously split into the Euler-Poincaré equations (5.1) and Euler-Lagrange equations (5.2), where the first equation (5.1) can also be written as Lie-Poisson equations on *G* when expressed with momentum $\Pi_{\alpha} = \frac{\partial l}{\partial \xi^{\alpha}}$. While here they have been solely derived with the Hamel formalism, they were derived as reduced Euler-Lagrange equations [9,33] from a variational principle on *Q*. The involved variations are not intrinsic in the sense that they are not split into variations in the fiber and the base manifold, respectively. Such a splitting leads to a decoupling of the equations and to a block-diagonalization of the mass matrix defining the kinetic energy. This is achieved by variations of ξ^{α} with zero variations of \dot{r}^{I} , i.e. setting the shape velocity to zero, which in geometric terms is equivalent to variations in the vertical space of the principle bundle. This is formalized using a connection, as described next.

(b) The Mechanical Connection and Locked Velocity

Introducing a connection is not as obvious as in case of kinematic constraint. The starting point is the reduced Lagrangian $l(r^{I}, \xi^{\alpha}, \dot{r}^{I}) = T(r^{I}, \xi^{\alpha}, \dot{r}^{I}) - V(r^{I})$ with potential energy $V(r^{I})$, and kinetic energy

$$T(r^{I}, \xi^{\alpha}, \dot{r}^{I}) = \frac{1}{2} \begin{pmatrix} \boldsymbol{\xi}^{T} & \dot{\mathbf{r}}^{T} \end{pmatrix} \begin{pmatrix} \mathbf{L}(\mathbf{r}) & \mathbf{K}(\mathbf{r}) \\ \mathbf{K}^{T}(\mathbf{r}) & \mathbf{S}(\mathbf{r}) \end{pmatrix} \begin{pmatrix} \boldsymbol{\xi} \\ \dot{\mathbf{r}} \end{pmatrix}$$
(5.3)

expressed in terms of the mass matrix

$$\mathbf{M}(\mathbf{r}) = \begin{pmatrix} \mathbf{L}(\mathbf{r}) & \mathbf{K}(\mathbf{r}) \\ \mathbf{K}^{T}(\mathbf{r}) & \mathbf{S}(\mathbf{r}) \end{pmatrix}$$
(5.4)

rspa.royalsocietypublishing.org Proc R Soc A 0000000

which defines a *G*-invariant metric on *Q*. The momentum $\Pi_{\alpha} = \frac{\partial l}{\partial \xi^{\alpha}}$ associated to the fiber is thus $\Pi(\mathbf{r}, \boldsymbol{\xi}, \dot{\mathbf{r}}) = \mathbf{L}(\mathbf{r}) \boldsymbol{\xi} + \mathbf{K}(\mathbf{r}) \dot{\mathbf{r}}$. If this relation of $\boldsymbol{\xi}$ and $\dot{\mathbf{r}}$ cannot be integrated to define a relation of *g* and **r**, the momentum is said to be non-holonomic.

For a floating multibody system, for example, where ξ^{α} are twist coordinates of the floating base body, the momentum co-screw $\Pi \in \mathfrak{g}^* = se^*$ (3) comprises the angular and linear momentum. One can then introduce the *locked velocity* $\Omega = (\Omega^{\alpha}) \in \mathfrak{g}$ such that $\mathbf{L}(\mathbf{r}) \Omega = \mathbf{L}(\mathbf{r}) \boldsymbol{\xi} + \mathbf{K}(\mathbf{r}) \dot{\mathbf{r}}$. The name stems from the observation that Ω is the base body velocity which generates the same momentum Π when the system is regard as a rigid body, i.e. when $\dot{\mathbf{r}} = 0$. In the humanoid example, this is the velocity the hip would attain, when all joints are locked instantaneously. Accordingly, $\mathbf{L}(\mathbf{r}) : \mathfrak{g} \to \mathfrak{g}^*$ is called the *locked inertia tensor*, while \mathbf{S} is the inertia related to the shape coordinates, and \mathbf{K} is the cross coupling inertia. If ξ^{α} are coordinates of the base twist in body-fixed representation, i.e. left-invariant, then $\Omega \in \mathfrak{g}$ is usually called the locked body velocity.

This change of coordinates on g is formalized by means of a connection $\mathcal{A}^{\text{mech}} = Ad_g(g^{-1}dg + \mathcal{A}d\mathbf{r})$ on the principal bundle Q. The local connection one-form is defined with $(\mathcal{A}_I^{\alpha}) := \mathbf{L}^{-1}\mathbf{K}$ so that the velocity shift is

$$\Omega^{\alpha} = \xi^{\alpha} + \mathcal{A}^{\alpha}_{I}(r^{I})\dot{r}^{I}.$$
(5.5)

The so-defined connection, is called the *mechanical connection* [8,9] building upon a concept discussed in [62]. In contrast to the kinematic connection, it is defined via the momentum. The connection may be considered to be in Chaplygin form since it is independent of group variables. Notice that this strictly relies on a local bundle trivialization since Q may not be a trivial principal bundle. The locked velocity $\boldsymbol{\Omega}$ is the vertical part relative to the mechanical connection.

Remark 5.1. An important aspect of the locked velocity is that it cannot be associated to a frame whose motion is described by $h(g, \mathbf{r}) \in G$ depending on some g and \mathbf{r} , so that $\hat{\boldsymbol{\Omega}} = h^{-1}\dot{h}$. This is an immediate consequence of the fact that Ω is defined by the non-holonomic momentum $\boldsymbol{\Pi}(\mathbf{r}, \boldsymbol{\xi}, \dot{\mathbf{r}})$ (see Sec. 5(e)).

Remark 5.2. The principal bundle view on floating-base systems has an interesting connection to gauge theory. In gauge theory, the symmetry is related to gauge invariance, G is called the 'gauge group', and the connection one-form \mathcal{A} in (5.5) is the 'gauge potential' [47]. This was discussed for the falling cat and similar non-holonomic control systems in [60], and more generally, for 'deformable bodies' (mechanical structures that can change their shape) in [63,64], and for Maxwell or Yang-Mills fields in [1]. In gauge theory, the equivariance condition on the connection describes a gauge transformation from a local gauge \mathcal{A} to a new $\mathcal{A}' = Ad_g(g^{-1}dg + \mathcal{A}d\mathbf{r})$ [19,65]. In case of mechanical systems, it describes a transformation from one body-fixed frame to another in which velocities are measured. In [63,64], \mathcal{A}_I^β was called the master gauge, while its curvature is considered as field strength.

(c) Hamel Coefficients and the Mechanical Connection

Here again, the original definition (2.6) of the Hamel coefficients is employed to derive relations that are today obtained using the machinery of geometric mechanics.

Lemma 5.1. The Hamel coefficients in bundle coordinates $(\Omega^{\alpha}, \dot{r}^{I})$ are $\gamma_{ab}^{I} \equiv 0$, and

$$\gamma^{\alpha}_{\beta\delta} = \pm c^{\alpha}_{\beta\delta} \tag{5.6}$$

$$\gamma_{J\beta}^{\alpha} = -\gamma_{\beta J}^{\alpha} = \pm c_{\beta\delta}^{\alpha} \mathcal{A}_{J}^{\delta}$$
(5.7)

$$\gamma_{IJ}^{\alpha} = \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{J}} - \frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial r^{I}} + \gamma_{J\beta}^{\alpha} \mathcal{A}_{I}^{\beta} = \frac{\partial \mathcal{A}_{I}^{\alpha}}{\partial r^{J}} - \frac{\partial \mathcal{A}_{J}^{\alpha}}{\partial r^{I}} \pm c_{\beta\lambda}^{\alpha} \mathcal{A}_{I}^{\beta} \mathcal{A}_{J}^{\lambda}$$
(5.8)

where the positive sign of \pm applies to left-, and the negative sign to a right-trivialization of the G-bundle.

Proof. Canonical coordinates s^{α} are introduced on *G*, which are related to the fiber coordinates via $\xi^{\alpha} = A^{\alpha}_{\beta}(s^{\alpha}) \dot{s}^{\beta}$ and $\dot{s}^{\alpha} = B^{\alpha}_{\beta}(s^{\alpha}) \xi^{\beta}$, respectively (see Sec. 4(b)). Relation (5.5) and its inverse are then written as

$$\Omega^{\alpha} = A^{\alpha}_{\beta} \left(s^{\alpha} \right) \dot{s}^{\beta} + \mathcal{A}^{\alpha}_{I} (r^{J}) \dot{r}^{I}$$
(5.9)

$$\dot{s}^{\alpha} = B^{\alpha}_{\beta} \left(s^{a} \right) \Omega^{\beta} - B^{\alpha}_{\beta} \left(s^{a} \right) \mathcal{A}^{\beta}_{I} (r^{J}) u^{I}$$
(5.10)

With the locked velocity, the quasi-velocities are $(u^a) = (u^\alpha, u^I) = (\Omega^\alpha, \dot{r}^I)$, thus expressed in the form (2.1), with $B^I_J = \delta^I_J$ and $B^I_\beta \equiv 0$, or in matrix form

$$\mathbf{u} = \begin{pmatrix} \begin{pmatrix} A_{\beta}^{\alpha} \end{pmatrix} & (\mathcal{A}_{I}^{\alpha}) \\ \mathbf{0} & \mathbf{I} \end{pmatrix} \begin{pmatrix} \dot{\mathbf{s}} \\ \dot{\mathbf{r}} \end{pmatrix}, \quad \begin{pmatrix} \dot{\mathbf{s}} \\ \dot{\mathbf{r}} \end{pmatrix} = \begin{pmatrix} \begin{pmatrix} B_{\beta}^{\alpha} \end{pmatrix} & -\begin{pmatrix} B_{\beta}^{\alpha} \mathcal{A}_{I}^{\beta} \\ \mathbf{0} & \mathbf{I} \end{pmatrix} \mathbf{u}.$$
(5.11)

The relation (2.6) is separated for the coordinates Ω^{α} and \dot{r}^{I} . The coefficients $\gamma^{\alpha}_{\beta\delta} = \left(\frac{\partial A^{\alpha}_{\mu}}{\partial s^{\lambda}} - \frac{\partial A^{\alpha}_{\lambda}}{\partial s^{\mu}}\right) B^{\mu}_{\beta} B^{\lambda}_{\delta} = \pm c^{\alpha}_{\beta\delta}$ are again determined by the structure constants of *G*, and thus

$$\gamma^{\alpha}_{\beta J} = \left(\frac{\partial A^{\alpha}_{\delta}}{\partial s^{\lambda}} - \frac{\partial A^{\alpha}_{\lambda}}{\partial s^{\delta}}\right) B^{\lambda}_{\beta} B^{\delta}_{\gamma} \mathcal{A}^{\gamma}_{J} = \pm c^{\alpha}_{\beta \delta} \mathcal{A}^{\delta}_{J}.$$

The remaining coefficients γ_{IJ}^{α} are given in (4.3).

The Hamel coefficients (5.8) are identical to the components of the curvature (1.3), $\mathcal{B}_{IJ}^{\alpha} = \gamma_{IJ}^{\alpha}$, of the mechanical connection in bundle coordinates. They are indeed formally identical to the curvature coefficients (4.3) of the kinematic connection.

(d) Boltzmann-Hamel Equations as reduced Euler-Lagrange Equations in Bundle Coordinates

Denote with $\ell(r^I, \Omega^{\alpha}, \dot{r}^I) := l(r^I, \xi^{\alpha} := \Omega^{\alpha} - \mathcal{A}_I^{\alpha} \dot{r}^I, \dot{r}^I)$ the reduced Lagrangian in terms of the locked velocity Ω^{α} . The Hamel equations (2.4) are

$$\frac{d}{dt}\frac{\partial\ell}{\partial\Omega^{\alpha}} + \frac{\partial\ell}{\partial\Omega^{\beta}}\left(\gamma^{\beta}_{\alpha I}\dot{r}^{I} + \gamma^{\beta}_{\alpha\lambda}\Omega^{\lambda}\right) = Q_{\alpha}$$
(5.12)

$$\frac{d}{dt}\frac{\partial\ell}{\partial\dot{r}^{I}} - \frac{\partial\ell}{\partial r^{I}} + \frac{\partial\ell}{\partial\Omega^{\beta}}\left(\gamma^{\beta}_{IJ}\dot{r}^{J} + \gamma^{\beta}_{I\alpha}\Omega^{\alpha}\right) = Q_{I}.$$
(5.13)

The motion in *G* is obtained from the reconstruction equations (4.10), now with $\xi^{\alpha} = \Omega^{\alpha} - \mathcal{A}_{I}^{\alpha}(\mathbf{r}) \dot{r}^{I}$ defined by the mechanical connection. It is important that the motion is deduced from ξ^{α} , and not from Ω^{α} , as the latter can in general not be attributed to a frame motion (Rem. 5.1 and Sec. 5(e)). Equations (5.12,5.13), admit the following geometric interpretation.

Proposition 5.1. The Hamel equations (5.12,5.13) for a left *G*-invariant Lagrangian $\ell(r^I, \Omega^{\alpha}, \dot{r}^I)$ are the reduced Euler-Lagrange equations (1.1,1.2) in terms of bundle coordinates $(\Omega^{\alpha}, \dot{r}^I)$, with the coefficients $\mathcal{E}^{\alpha}_{\beta I} = \gamma^{\alpha}_{I\beta} = c^{\alpha}_{\beta\lambda} \mathcal{A}^{\lambda}_{I}, c^{\alpha}_{\beta\lambda} = \gamma^{\alpha}_{\beta\lambda}$, and curvature $\mathcal{B}^{\alpha}_{IJ} = \gamma^{\alpha}_{IJ}$ determined by the Hamel-coefficients.

The equations (1.1,1.2) have been derived in [9], and presented in [33, p. 397], by introducing the locked velocity (5.5) into the Lagrangian $\ell(r^I, \Omega^{\alpha}, \dot{r}^I)$ before taking the Euler-Lagrange derivative. Their derivation as Hamel equation in terms of the locked velocity has not been reported in the literature. The first equation (1.1), respectively (5.12), is indeed the Euler-Poincaré equation (5.1) with ξ^{α} replaced by the velocity Ω^{α} of the locked system, which is why (1.1,1.2) are also called Lagrange-Poincaré equations [45, p. 3395], [3, p. 146]. The terms with $\gamma^{\beta}_{\alpha I}$ in (5.12) and (5.13) can be regarded as interaction (or coupling) terms. Clearly, as remarked in [4, pp. 912, 913], the equations (5.12,5.13) reduce to the Hamel equations (5.1,5.2) if the coefficients of connection and curvature vanish, i.e. when expressed in local coordinates (ξ^{α}, \dot{r}^I). However, since the Hamel formalism applies to any choice of local coordinates, as shown in this paper, it should 15

not be said that (5.12,5.13) reduce to *the* Hamel equations when using local coordinates $(\xi^{\alpha}, \dot{r}^{I})$, as occasionally stated, e.g. [66, p. 226].

It follows from the definition of the Hamel coefficients that the mechanical connection is flat, i.e. the curvature $\mathcal{B}_{IJ}^{\alpha}$ vanishes, if and only if the momentum $\Pi_{\alpha} = \frac{\partial \ell}{\partial \Omega^{\alpha}}$ (equivalently $\Pi_{\alpha} = \frac{\partial l}{\partial \xi^{\alpha}}$) defines a non-integrable relation of ξ^{α} and \dot{r}^{I} .

Remark 5.3. A note on the sign convention for the curvature coefficients $\mathcal{B}_{IJ}^{\alpha}$ is in order. Given a connection, the local curvature is usually defined as $\mathcal{B}_{IJ}^{\alpha} = -\gamma_{IJ}^{\alpha}$ with γ_{IJ}^{α} in (4.3) (see [47] for right bundles), which agrees with the definition of curvature used in gauge theory [19, p. 247]. This convention is used in [9, p. 157] and [45, p. 3395], and thus $\mathcal{B}_{IJ}^{\alpha}$ appears with a positive sign in the reduced Euler-Lagrange equations (1.2). In [4, p. 910] and [18, notice the correction on p. 44], the local curvature is introduced as $\mathcal{B}_{IJ}^{\alpha} = \gamma_{IJ}^{\alpha}$, as in this paper, along with the reduced Euler-Lagrange equations (1.1,1.2). In [3, pp. 117,146], the curvature is derived as $\mathcal{B}_{IJ}^{\alpha} = -\gamma_{IJ}^{\alpha}$, but is then used with a negative sign in the reduced Euler-Lagrange equations. Similarly in [66], the curvature is introduced as $\mathcal{B}_{IJ}^{\alpha} = \gamma_{IJ}^{\alpha}$ but used with positive sign in (1.2). These inconsistencies deserve particular attention when applying equations (4.9) and (1.1,1.2).

(e) Inertial Decoupling of Poincaré and Lagrange Equations

The mechanical connection allows to intrinsically split variation into the vertical and horizontal parts⁴. As a consequence, the mass matrix \mathbf{M} of the equations in terms of the locked velocity, is diagonal [3, p. 147]. Inserting (5.5) into (5.3) yields the mass matrix

$$\mathbf{M}^{\Omega}(\mathbf{r}) = \begin{pmatrix} \mathbf{L}(\mathbf{r}) & \mathbf{0} \\ \mathbf{0} & \mathbf{S}(\mathbf{r}) - \mathcal{A}^{T}(\mathbf{r})\mathbf{L}(\mathbf{r})\mathcal{A}(\mathbf{r}) \end{pmatrix}$$
(5.14)

and the kinetic energy $\ell(r^I, \Omega^{\alpha}, \dot{r}^I) = \frac{1}{2} \Omega^T \mathbf{L}(\mathbf{r}) \Omega + \frac{1}{2} \dot{\mathbf{r}}^T \left(\mathbf{S}(\mathbf{r}) - \mathcal{A}^T(\mathbf{r}) \mathbf{L}(\mathbf{r}) \mathcal{A}(\mathbf{r}) \right) \dot{\mathbf{r}}$. Indeed, the momentum $\Pi_{\alpha} = \frac{\partial \ell}{\partial \Omega^{\alpha}}$ only depends on the fiber coordinates Ω^{α} , so that the equations (5.12) and (5.13) are inertially decoupled (not coupled on accelerations level). Coupling of the equations is via the velocity terms involving $\gamma^{\beta}_{\alpha I}$. Inertial decoupling using the locked velocity has been addressed for modeling of floating base robots [13,67] and space robots in [68,69].

A closely related concept for decoupling the equations is that of the *centroidal momentum* as introduced in [70], which is widely used for whole-body control of humanoid robots [15,71,72] for instance. In this context $\mathfrak{g} = se(3)$, and $\mathbf{V} \in se(3)$ is the velocity (twist) of the base body (using symbol \mathbf{V} instead of ξ), and $\dot{\mathbf{r}}$ are the joint velocities. A frame \mathcal{F}_G is introduced that is located at the total COM of the system and aligned with the inertial frame \mathcal{F}_0 . The configuration of \mathcal{F}_G relative to the frame \mathcal{F}_b attached at the base body is described by $g_{bG} \in SE(3) = G$. The centroidal momentum is defined as $\boldsymbol{\Pi}_G = \mathbf{Ad}_{g_{bG}}^T \boldsymbol{\Pi}$, with momentum co-screw $\boldsymbol{\Pi} \in se^*(3)$ defined in Sec. 5(b). This is also expressed as $\boldsymbol{\Pi}_G = \mathbf{M}_G \mathbf{V}_G$, where \mathbf{V}_G is referred to as the *average velocity*, and $\mathbf{M}_G = \mathbf{Ad}_{g_{bG}}^T \mathbf{M}_{bb} \mathbf{Ad}_{g_{bG}}$ is called the *centroidal composite inertia matrix*, and $\mathbf{Ad}_{g_{bG}}^T(\mathbf{L}, \mathbf{K})$ the *centroidal momentum matrix* [14,15]. Comparing this with the definition of the locked velocity $\mathbf{L}(\mathbf{r}) \mathbf{V}_{loc} = \boldsymbol{\Pi}$ shows that $\mathbf{V}_G = \mathbf{Ad}_{g_{bG}}^{-1} \mathbf{V}_{loc}$. Moreover, $\mathbf{V}_G = (\boldsymbol{\omega}_{ave}, \dot{\mathbf{p}}_{com})$, where $\boldsymbol{\omega}_{ave} = \boldsymbol{\omega}_{loc}$ is called the *average angular velocity* [70], and $\dot{\mathbf{p}}_{com}$ is the velocity of the total

COM of the system, both expressed in \mathcal{F}_0 . The important point is that $\mathbf{M}_{\mathrm{G}} = \begin{pmatrix} \boldsymbol{\Theta}_{\mathrm{G}} & \mathbf{0} \\ \mathbf{0} & \bar{m}\mathbf{I} \end{pmatrix}$ is a block diagonal matrix, where \bar{m} is the total mass, and $\boldsymbol{\Theta}_{\mathrm{G}}$ is the total inertia tensor w.r.t. to the

total COM expressed in \mathcal{F}_0 . This would replace the locked inertia L in (5.14) when the EOM are expressed with V_G .

The motivation for using the centroidal momentum $\boldsymbol{\Pi}_{G} = (\boldsymbol{\Theta}_{G}\boldsymbol{\omega}_{ave}, \bar{m}\dot{\mathbf{p}}_{com})$ is that the linear and angular momentum are decoupled (in addition to the inertial decoupling of (5.12) and

⁴The vertical space is the tangent space ker $T_q \pi$ to the group orbits, i.e. possible velocities of the base body for locked shape coordinates. The horizontal space is the space of velocities not producing a locked velocity.

(5.13)), and can be controlled independently. However, there is generally no frame associated to $\mathbf{V}_{\rm G}$ (Rem. 5.1) that could serve to represent the system orientation. This would imply that the motion of this frame is represented by a $g_{\rm bG}(g, \mathbf{r})$ such that $\hat{\mathbf{V}}_{\rm G} = \dot{g}_{\rm bG}g_{\rm bG}^{-1}$. It is clear from the definition of $\mathbf{V}_{\rm G}$ (and $\mathbf{V}_{\rm loc}$) by means of the momentum that such a frame exists if and only if the momentum defines integrable relation, i.e. if the curvature vanishes, which is generally not the case. This seemingly obvious fact was proven in [73]. In order to determine the base configuration $g \in SE$ (3) w.r.t. \mathcal{F}_0 , the reconstruction equations (4.10), which are now $\hat{\mathbf{V}}_{\rm b} = g^{-1}\dot{g}$, must be solved with $\mathbf{V}_{\rm b} = \mathbf{V}_{\rm loc} - \mathbf{L}^{-1}\mathbf{K}\dot{\mathbf{r}}$, as proposed in [71]. Finally it should be remarked that the centroidal kinematics and dynamics can be expressed in terms of barycentric vectors [74,75].

(f) Example: Satellite with three symmetric reaction wheels

The simplified model of a satellite equipped with three reaction wheels is considered. Fig. 2 shows a schematic drawing of the principle mechanical setup. In the following, the reaction wheels are called rotors, for simplicity. The axes of the three rotors are mutually orthogonal, the rotors are located arbitrarily at the satellite, and are assumed to be symmetric (so that the total COM of the satellite is constant). The satellite's main body is modeled as a rigid body. It is assumed that there are no gravity or other potential forces acting on the satellite, thus the Lagrangian is the kinetic energy. The motion of the main body is a rigid body motion evolving in a Lie group G, and represented by $g \in G$. The kinetic energy is invariant w.r.t. G-actions. The rotations of the three rotors are described by the rotation angles φ^i , i = 1, 2, 3. The configuration space of the satellite model is thus $Q = G \times T^3$, with configuration $q = (q, \varphi)$, with $\varphi = (\varphi^1, \varphi^2, \varphi^3)$. The latter serve as coordinates on the shape space, $r^I := \varphi^{\overline{I}}$. Different choices for G are used in the literature. Most of the original formulations in multibody system dynamics use the direct product group $G = SO(3) \times \mathbb{R}^3$, while recent research uses the proper rigid body motion group SE(3)(mainly triggered by development of Lie group integration methods [76], and geometrically exact modeling of Cosserat continua [77,78]). The particular choice of symmetry group, but also whether left- or right trivialization is used, leads to different definition of rigid body velocities and equations of motion. In the following, notation from multibody dynamics and robotics is adopted, where $\mathbf{V} \in \mathbb{R}^{6} \cong \mathfrak{g}$ denotes velocity of a frame (rigid body), and \mathfrak{g} is either $so(3) \times \mathbb{R}^{3}$ or se (3). A detailed description and numerical results can be found in the supplement [16].



Figure 2. Schematic drawing of a satellite model. The figure shows a self-stabilizing cube reported in [79].

(i) Mixed Representation of Rigid Body Velocity –Symmetry Group $G=SO\left(3\right)\times\mathbb{R}^{3}$

The configuration (pose) of the main body is represented as $(\mathbf{R}, \mathbf{p}) \in SO(3) \times \mathbb{R}^3$, where $\mathbf{R} \in$ SO(3) and $\mathbf{p} \in \mathbb{R}^3$ describes the rotation and translation of a body-fixed reference frame (RFR) $\mathcal{F}_{\rm b}$ relative to an inertial frame (IFR) $\mathcal{F}_{\rm 0}$. The group multiplication on the direct product group is $(\mathbf{R}_1, \mathbf{p}_1) \cdot (\mathbf{R}_2, \mathbf{p}_2) = (\mathbf{R}_1 \mathbf{R}_2, \mathbf{p}_1 + \mathbf{p}_2)$. Since rotations and translations are decoupled, this is clearly not a frame transformation (i.e. a rigid body motion). The corresponding velocity defined via left-trivialization is $\hat{\mathbf{V}}_{\mathrm{b}} = g^{-1}\dot{g} = (\mathbf{R}^{-1}\dot{\mathbf{R}}, \dot{\mathbf{p}}) = (\hat{\boldsymbol{\omega}}, \dot{\mathbf{p}}) \in \mathfrak{g} = so(3) \times \mathbb{R}^3$, and in vector representation $\mathbf{V}_{b} = (\boldsymbol{\omega}, \dot{\mathbf{p}}) \in \mathbb{R}^{6}$, where $\boldsymbol{\omega} \in \mathbb{R}^{3}$ is the angular velocity of the main body relative to \mathcal{F}_0 resolved in \mathcal{F}_b . This is referred to as the mixed representation of rigid body velocities since ω is resolved in the body frame, and $\dot{\mathbf{p}}$ in the inertia frame [30,31]. Regarding the dynamics, decoupling of rotation and translation is valid only if the body-fixed RFR is located at the COM, which is the main premise when using the direct product group G, since then the angular and linear momenta are decoupled. Therefore, the velocities of main body and rotors will be measured at the total COM of the satellite (main body including the rotors), thus **p** is the position vector of the total COM resolved in the IFR, and \mathcal{F}_{b} is located at the total COM. Denote with $\mathbf{V}_{i} = (\omega_{i}, \dot{\mathbf{p}})$ the hybrid velocity of rotor i = 1, 2, 3. W.l.o.g. the RFR is aligned with the rotor axes. Then $\omega_i = \omega + \mathbf{e}_i \dot{\varphi}^i$, where $\mathbf{e}_i \in \mathbb{R}^3$ is the *i*-th unit vector (e.g. $\mathbf{e}_1 = (1, 0, 0)$), and thus $\mathbf{V}_i = \mathbf{V}_b + \overline{\mathbf{V}}_i$, with $\overline{\mathbf{V}}_i = (\mathbf{e}_i \dot{\varphi}^i, \mathbf{0}).$

The momentum of the main body in mixed representation is $\boldsymbol{\Pi}^{\mathrm{b}} = \mathbf{M}^{\mathrm{b}} \mathbf{V}_{\mathrm{b}} \in \mathbb{R}^{6} \cong \mathfrak{g}^{*} = so^{*}(3) \times \mathbb{R}^{3}$, and of the *i*-th rotor $\boldsymbol{\Pi}^{i} = \mathbf{M}^{i} \mathbf{V}_{i}$, with the inertia matrix of the main body and the *i*-th rotor, respectively,

$$\mathbf{M}^{\mathrm{b}} = \begin{pmatrix} \boldsymbol{\Theta}^{\mathrm{b}} & \mathbf{0} \\ \mathbf{0} & m_{\mathrm{b}}\mathbf{I} \end{pmatrix}, \quad \mathbf{M}^{i} = \begin{pmatrix} \boldsymbol{\Theta}^{i} & \mathbf{0} \\ \mathbf{0} & m_{i}\mathbf{I} \end{pmatrix}$$
(5.15)

where Θ^{b} and Θ^{i} is the inertia tensor of the main body and the *i*-th rotor w.r.t. the total COM, and m_{b} and m_{i} is the mass of the main body and *i*-th rotor.

The velocity coordinates are $(\xi^{\alpha}, \dot{r}^{I}) = (\omega^{1}, \omega^{2}, \omega^{3}, \dot{p}^{1}, \dot{p}^{2}, \dot{p}^{3}, \dot{\varphi}^{1}, \dot{\varphi}^{2}, \dot{\varphi}^{3}) = (V_{\rm b}^{\alpha}, \dot{\varphi}^{i}) = (\mathbf{V}_{\rm b}, \dot{\varphi})$, with fiber coordinates $(\xi^{\alpha}) = (V_{\rm b}^{\alpha}) = (\omega^{1}, \omega^{2}, \omega^{3}, \dot{p}^{1}, \dot{p}^{2}, \dot{p}^{3}), \alpha = 1, \ldots, 6$ and $(\dot{r}^{I}) = (\dot{\varphi}^{1}, \dot{\varphi}^{2}, \dot{\varphi}^{3}), I = 7, 8, 9$. In the following, indexes i, j, k, l = 1, 2, 3 and the notation $\bar{I} = I - 6$ are used. The kinetic energy of the satellite is

$$T(\mathbf{V}_{\mathrm{b}}, \dot{\boldsymbol{\varphi}}) = \frac{1}{2} \mathbf{V}_{\mathrm{b}}^{T} \boldsymbol{\Pi}^{\mathrm{b}} + \frac{1}{2} \sum_{i=1}^{3} \mathbf{V}_{i}^{T} \boldsymbol{\Pi}^{i}$$
$$= \frac{1}{2} \Theta_{\alpha\beta}^{\mathrm{b}} \omega^{\alpha} \omega^{\beta} + \frac{1}{2} \sum_{i=1}^{3} \left[\Theta_{jk}^{i} (\omega^{j} + \delta_{i}^{j} \dot{\boldsymbol{\varphi}}^{i}) (\omega^{k} + \delta_{i}^{k} \dot{\boldsymbol{\varphi}}^{i}) + \bar{m} \dot{p}^{i} \dot{p}^{i} \right]$$
(5.16)

where $\bar{m} := m_{\rm b} + \sum_{i=1}^{3} m_i$ is the total mass of the satellite. The kinetic energy is invariant under left-action of *G* (due to the body-fixed angular velocity).

Hamel Equations The structure coefficients on the direct product group $SO(3) \times \mathbb{R}^3$ are $c_{\alpha\lambda}^{\beta} = \varepsilon_{\alpha\lambda\beta}$, for $\alpha, \beta, \lambda = 1, 2, 3$, and $c_{\alpha\lambda}^{\beta} = 0$ otherwise. The Euler-Poincaré equations (5.1) are found as

$$\frac{d}{dt}\frac{\partial T}{\partial\omega^{i}} + \frac{\partial T}{\partial\omega^{j}}c^{j}_{ik}\omega^{k} = \bar{\Theta}_{ij}\dot{\omega}^{j} + \varepsilon_{ikj}\omega^{k}\bar{\Theta}_{jl}\omega^{l} + \sum_{j=1}^{3}(\Theta^{j}_{ij}\ddot{\varphi}^{j} + \varepsilon_{ikl}\omega^{k}\Theta_{lj}\dot{\varphi}^{j})$$
$$\frac{d}{dt}\frac{\partial T}{\partial\dot{p}^{j}} = \bar{m}\ddot{p}^{j}$$
(5.17)

rspa.royalsocietypublishing.org Proc R Soc A 0000000

where $\bar{\boldsymbol{\Theta}} := \boldsymbol{\Theta}^{\mathrm{b}} + \sum_{i=1}^{3} \boldsymbol{\Theta}^{i}$ is the composite inertia tensor of the satellite including main body and rotors. They can also be written in vector form, with matrix $\mathbf{ad}_{\boldsymbol{\omega}} = \tilde{\boldsymbol{\omega}}$,

$$\frac{d}{dt}\frac{\partial T}{\partial \boldsymbol{\omega}} - \mathbf{a}\mathbf{d}_{\boldsymbol{\omega}}^{T}\frac{\partial T}{\partial \boldsymbol{\omega}} = \bar{\boldsymbol{\Theta}}\dot{\boldsymbol{\omega}} + \widetilde{\boldsymbol{\omega}}\bar{\boldsymbol{\Theta}}\boldsymbol{\omega} + \sum_{i=1}^{3} \left(\boldsymbol{\theta}^{i}\ddot{\boldsymbol{\varphi}}^{i} + \widetilde{\boldsymbol{\omega}}\boldsymbol{\theta}^{i}\dot{\boldsymbol{\varphi}}^{i}\right)$$
(5.18)

$$\frac{d}{dt}\frac{\partial T}{\partial \dot{\mathbf{p}}} = \bar{m}\ddot{\mathbf{p}}$$
(5.19)

where $\theta^i := \Theta^i \mathbf{e}_i$ is the *i*-th column of Θ^i .

The Euler-Lagrange equations (5.2) are, noting that *T* does not depend on $\varphi^i (= r^{\overline{I}})$,

$$\frac{d}{dt}\frac{\partial T}{\partial \dot{\varphi}^i} = \Theta^i_{ij}\dot{\omega}^j + \Theta^i_{ii}\ddot{\varphi}^i$$
(5.20)

where the diagonal element Θ_{ii}^i is the moment of inertia about the axis of rotator *i*. The above equations are summarized to the set of EOM for the satellite

$$\begin{pmatrix} \bar{\boldsymbol{\Theta}} & \mathbf{0} & \theta^{1} & \theta^{2} & \theta^{3} \\ \mathbf{0} & \bar{\boldsymbol{m}}\mathbf{I} & \mathbf{0} & \mathbf{0} & \mathbf{0} \\ \theta^{1^{T}} & \mathbf{0} & \Theta_{11}^{1} & \mathbf{0} & \mathbf{0} \\ \theta^{2^{T}} & \mathbf{0} & \mathbf{0} & \Theta_{22}^{2} & \mathbf{0} \\ \theta^{3^{T}} & \mathbf{0} & \mathbf{0} & \mathbf{0} & \Theta_{33}^{3} \end{pmatrix} \begin{pmatrix} \dot{\boldsymbol{\omega}} \\ \ddot{\boldsymbol{p}} \\ \ddot{\boldsymbol{\varphi}}^{1} \\ \ddot{\boldsymbol{\varphi}}^{2} \\ \ddot{\boldsymbol{\varphi}}^{3} \end{pmatrix} + \begin{pmatrix} \tilde{\boldsymbol{\omega}}\bar{\boldsymbol{\Theta}}\boldsymbol{\omega} + \sum_{i=1}^{3}\tilde{\boldsymbol{\omega}}\theta^{i}\dot{\boldsymbol{\varphi}}^{i} \\ \mathbf{0} \\ \mathbf{0} \\ \mathbf{0} \end{pmatrix} = \mathbf{0}.$$
 (5.21)

The mass matrix has the form (5.4) with non-zero submatrix **K**. It is constant due to the assumption of symmetric rotors and axes aligned with the RFR axes.

The pose of the satellite is obtained by solving the kinematic reconstruction equations (4.10). To this end, the equations $\dot{\mathbf{X}} = \mathbf{dexp}_{-\mathbf{X}}^{-1} \mathbf{V}_{\mathrm{b}} = \left(\mathbf{dexp}_{-\mathbf{x}}^{-1} \boldsymbol{\omega}_{\mathrm{b}}, \dot{\mathbf{p}}\right)$ are solved for the coordinate vector $\mathbf{X} = (\mathbf{x}, \mathbf{p}) \in \mathbb{R}^6 \cong so(3) \times \mathbb{R}^3$. Here $\mathbf{dexp}_{\mathbf{x}}$ is the matrix form of the right-trivialized differential of the exp map on SO(3) [55].

Euler-Lagrange Equations on a Trivial Principle Bundle With the partitioning (5.4) of the mass matrix, the connection coefficients A_I^{α} are defined by

$$\mathcal{A} = \mathbf{L}^{-1} \mathbf{K} = \begin{pmatrix} \bar{\boldsymbol{\theta}}^1 & \bar{\boldsymbol{\theta}}^2 & \bar{\boldsymbol{\theta}}^3 \\ \mathbf{0} & \mathbf{0} & \mathbf{0} \end{pmatrix}.$$
 (5.22)

The locked velocity (5.5) is $\mathbf{V}_{\text{loc}} = \mathbf{V}_{\text{b}} + \mathbf{L}^{-1}\mathbf{K}\dot{\boldsymbol{\varphi}}$, and thus with (5.22), $\omega_{\text{loc}}^{\alpha} = \omega^{\alpha} - \mathcal{A}_{I}^{\alpha}\dot{\boldsymbol{\varphi}}^{\bar{I}}$ and $\dot{p}_{\text{loc}}^{\alpha} = \dot{p}^{\alpha}$. In terms of the locked velocity, the kinetic energy is

$$T\left(\mathbf{V}_{\mathrm{loc}},\dot{\boldsymbol{\varphi}}\right) = \frac{1}{2}\Theta^{\mathrm{b}}_{\alpha\beta}\left(\omega^{\alpha}_{\mathrm{loc}} - \mathcal{A}^{\alpha}_{\bar{I}}\dot{\boldsymbol{\varphi}}^{\bar{I}}\right)\left(\omega^{\beta}_{\mathrm{loc}} - \mathcal{A}^{\beta}_{\bar{J}}\dot{\boldsymbol{\varphi}}^{\bar{J}}\right) + \frac{1}{2}\sum_{i=1}^{3}\Theta^{i}_{\alpha\beta}\left(\omega^{\alpha}_{\mathrm{loc}} + \left(\delta^{\alpha}_{\bar{I}} - \mathcal{A}^{\alpha}_{\bar{I}}\right)\dot{\boldsymbol{\varphi}}^{\bar{I}}\right)\left(\omega^{\beta}_{\mathrm{loc}} + \left(\delta^{\beta}_{\bar{J}} - \mathcal{A}^{\beta}_{\bar{J}}\right)\dot{\boldsymbol{\varphi}}^{\bar{J}}\right) + \frac{\bar{m}}{2}\dot{p}^{\alpha}\dot{p}^{\alpha}.$$
(5.23)

A straightforward calculation yields, with block matrices S, K, L deduced from (5.21),

$$\frac{\partial T}{\partial \mathbf{V}_{\text{loc}}} = \begin{pmatrix} \bar{\boldsymbol{\Theta}} & \mathbf{0} \\ \mathbf{0} & \bar{m}\mathbf{I} \end{pmatrix} \mathbf{V}_{\text{loc}}, \quad \frac{\partial T}{\partial \dot{\boldsymbol{\varphi}}} = \left(\mathbf{S} - \boldsymbol{\mathcal{A}}^T \mathbf{L} \boldsymbol{\mathcal{A}}\right) \dot{\boldsymbol{\varphi}} = \left(\mathbf{S} - \mathbf{K}^T \mathbf{L}^{-1} \mathbf{K}\right) \dot{\boldsymbol{\varphi}}$$
(5.24)

with

$$\mathbf{S} - \mathbf{K}^{T} \mathbf{L}^{-1} \mathbf{K} = \begin{pmatrix} \Theta_{11}^{1} - \boldsymbol{\theta}^{1^{T}} \bar{\boldsymbol{\theta}}^{1} & -\boldsymbol{\theta}^{1^{T}} \bar{\boldsymbol{\theta}}^{2} & -\boldsymbol{\theta}^{1^{T}} \bar{\boldsymbol{\theta}}^{3} \\ -\boldsymbol{\theta}^{2^{T}} \bar{\boldsymbol{\theta}}^{1} & \Theta_{22}^{2} - \boldsymbol{\theta}^{2^{T}} \bar{\boldsymbol{\theta}}^{2} & -\boldsymbol{\theta}^{2^{T}} \bar{\boldsymbol{\theta}}^{3} \\ -\boldsymbol{\theta}^{3^{T}} \bar{\boldsymbol{\theta}}^{1} & -\boldsymbol{\theta}^{3^{T}} \bar{\boldsymbol{\theta}}^{2} & \Theta_{33}^{3} - \boldsymbol{\theta}^{3^{T}} \bar{\boldsymbol{\theta}}^{3} \end{pmatrix}$$
(5.25)

Thus the mass matrix in the EOM in terms of the locked velocity has the block-diagonal form (5.14). The Hamel coefficients (5.6)-(5.8) are determined by the non-zero structure coefficients $c^{\beta}_{\alpha\lambda} = \varepsilon_{\alpha\lambda\beta}$, for $\alpha, \beta, \lambda = 1, 2, 3$. Since the connection coefficients are constant, the curvature

rspa.royalsocietypublishing.org Proc R Soc A 0000000

coefficients (5.8) are $\mathcal{B}_{IJ}^{\alpha} = [\mathcal{A}_I, \mathcal{A}_J]^{\alpha}$. In vector representation, \mathcal{A}_I is the \bar{I} -th column in (5.22), and $[\mathcal{A}_I, \mathcal{A}_J] = (\bar{\theta}^{\bar{I}} \times \bar{\theta}^{\bar{J}}, \mathbf{0})$. It is non-zero due the non-commutativity of vector fields \mathcal{A}_I w.r.t. the Lie bracket on $\mathfrak{g} = so(3) \times \mathbb{R}^3$ (non-parallel rotor axes). The non-zero $\mathcal{B}_{IJ}^{\alpha}$ (non-flat connection) implies that the momentum does not define an integrable relation of rotor and base motion.

(ii) Body-fixed Representation of Rigid Body Velocity — Symmetry Group G = SE(3)

The semi-direct product group $SE(3) = SO(3) \ltimes \mathbb{R}^3$ describes proper rigid body motions. The configuration of the main body is again represented as $(\mathbf{R}, \mathbf{p}) \in SE(3)$, but with group multiplication $(\mathbf{R}_1, \mathbf{p}_1) \cdot (\mathbf{R}_2, \mathbf{p}_2) = (\mathbf{R}_1 \mathbf{R}_2, \mathbf{p}_1 + \mathbf{R}_1 \mathbf{p}_2)$, which correctly accounts for coupling of rotations and translations. Thus, the body-fixed RFR can be located arbitrarily. The velocity (also called twists) of the main body, i.e. of \mathcal{F}_{b} , in body-fixed representation [30,31] is defined via left-trivialization as $\hat{\mathbf{V}}_{\mathrm{b}} = g^{-1}\dot{g} = (\mathbf{R}^{-1}\dot{\mathbf{R}}, \mathbf{R}^{-1}\dot{\mathbf{p}}) = (\hat{\boldsymbol{\omega}}, \mathbf{v}) \in \mathfrak{g} = se(3)$, and in vector representation $\mathbf{V}_{\mathrm{b}} = (\boldsymbol{\omega}, \mathbf{v}) \in \mathbb{R}^6$, where now $\mathbf{v} \in \mathbb{R}^3$ is the linear velocity of the main body relative to \mathcal{F}_0 resolved in \mathcal{F}_{b} . To simplify the derivation, the velocity of main body and rotors are expressed in the body-fixed RFR at the main body. The velocity of rotor i = 1, 2, 3 is $\mathbf{V}_i = (\boldsymbol{\omega}_i, \mathbf{v}_i)$. Assuming again that the RFR is aligned with the rotor axes, it holds true that $\mathbf{V}_i = \mathbf{V}_{\mathrm{b}} + \overline{\mathbf{V}}_i$.

The momentum of the main body in body-fixed representation is $\Pi^{b} = \mathbf{M}^{b}\mathbf{V}_{b} \in \mathbb{R}^{6} \cong \mathfrak{g}^{*} = se^{*}$ (3), and of the *i*-th rotor $\Pi^{i} = \mathbf{M}^{i}\mathbf{V}_{i}$, with the inertia matrix of the main body and of the *i*-th rotor w.r.t. an arbitrary RFR

$$\mathbf{M}^{\mathrm{b}} = \begin{pmatrix} \Theta^{\mathrm{b}} & m_{\mathrm{b}} \widetilde{\mathbf{d}}_{\mathrm{b}} \\ -m_{\mathrm{b}} \widetilde{\mathbf{d}}_{\mathrm{b}} & m_{\mathrm{b}} \mathbf{I} \end{pmatrix}, \quad \mathbf{M}^{i} = \begin{pmatrix} \Theta^{i} & m_{i} \widetilde{\mathbf{d}}_{i} \\ -m_{i} \widetilde{\mathbf{d}}_{i} & m_{i} \mathbf{I} \end{pmatrix}$$
(5.26)

where Θ^{b} and Θ^{i} are the inertia tensors of the main body and the *i*-th rotor w.r.t. the RFR, and \mathbf{d}_{b} , \mathbf{d}_{i} are the position vectors to the COM w.r.t. the RFR. The total kinetic energy of the satellite is

$$T\left(\mathbf{V}_{\mathrm{b}}, \dot{\boldsymbol{\varphi}}\right) = \frac{1}{2} \mathbf{V}_{\mathrm{b}}^{T} \mathbf{M}^{\mathrm{b}} \mathbf{V}_{\mathrm{b}} + \frac{1}{2} \sum_{i=1}^{3} \mathbf{V}_{i}^{T} \mathbf{M}^{i} \mathbf{V}_{i} = \frac{1}{2} \mathbf{V}_{\mathrm{b}}^{T} \mathbf{M}^{\mathrm{b}} \mathbf{V}_{\mathrm{b}} + \frac{1}{2} \sum_{i=1}^{3} \left(\mathbf{V}_{\mathrm{b}} + \overline{\mathbf{V}}_{i}\left(\dot{\boldsymbol{\varphi}}\right)\right)^{T} \mathbf{M}^{i} \left(\mathbf{V}_{\mathrm{b}} + \overline{\mathbf{V}}_{i}\left(\dot{\boldsymbol{\varphi}}\right)\right)$$

$$(5.27)$$

Hamel Equations In the following, the matrix form of the equations will be presented, for simplicity. The structure coefficients on the semi-direct product group SE(3) give rise to the matrix form of the adjoint operator [55,80]

$$\mathbf{ad}_{\mathbf{V}_{\mathrm{b}}} = \begin{pmatrix} \widetilde{\boldsymbol{\omega}}_{\mathrm{b}} & \mathbf{0} \\ \widetilde{\mathbf{v}}_{\mathrm{b}} & \widetilde{\boldsymbol{\omega}}_{\mathrm{b}} \end{pmatrix}$$
(5.28)

so that the Lie bracket is $ad_X Y = [X, Y]$. The Euler-Poincaré equations (5.1) are

$$\frac{d}{dt}\frac{\partial T}{\partial \mathbf{V}_{\mathrm{b}}} - \mathbf{a}\mathbf{d}_{\mathbf{V}_{\mathrm{b}}}^{T}\frac{\partial T}{\partial \mathbf{V}_{\mathrm{b}}} = \mathbf{L}\dot{\mathbf{V}}_{\mathrm{b}} + \sum_{i=1}^{3}\mathbf{M}^{i}\dot{\overline{\mathbf{V}}}_{i} - \mathbf{a}\mathbf{d}_{\mathbf{V}_{\mathrm{b}}}^{T}\left(\mathbf{L}\mathbf{V}_{\mathrm{b}} + \sum_{i=1}^{3}\mathbf{M}^{i}\overline{\mathbf{V}}_{i}\right)$$
(5.29)

with locked mass matrix $\mathbf{L} = \mathbf{M}^{\mathrm{b}} + \sum_{i=1}^{3} \mathbf{M}^{i}$. Written explicitly yields the instructive form

$$\bar{\boldsymbol{\Theta}}\dot{\boldsymbol{\omega}} + \tilde{\boldsymbol{\omega}}\bar{\boldsymbol{\Theta}}\boldsymbol{\omega} - \bar{m}(\dot{\tilde{\mathbf{v}}} + \tilde{\boldsymbol{\omega}}\tilde{\mathbf{v}})\mathbf{d} + \sum_{i=1}^{3} \left(\boldsymbol{\theta}^{i}\ddot{\varphi}^{i} + \left(\tilde{\boldsymbol{\omega}}\theta^{i} - m_{i}\tilde{\mathbf{v}}\mathbf{a}_{i}\right)\dot{\varphi}^{i}\right) = \mathbf{0}$$
$$\bar{m}\left(\dot{\mathbf{v}} + \tilde{\boldsymbol{\omega}}\mathbf{v} + (\dot{\tilde{\boldsymbol{\omega}}} + \tilde{\boldsymbol{\omega}}\tilde{\boldsymbol{\omega}})\mathbf{d}\right) - \sum_{i=1}^{3} m_{i}\left(\mathbf{a}_{i}\ddot{\varphi}^{i} + \tilde{\boldsymbol{\omega}}\mathbf{a}_{i}\dot{\varphi}^{i}\right) = \mathbf{0}$$
(5.30)

with $\bar{\boldsymbol{\Theta}} := \boldsymbol{\Theta}^{\mathrm{b}} + \sum_{i=1}^{3} \boldsymbol{\Theta}^{i}$ and $\boldsymbol{\theta}^{i} := \boldsymbol{\Theta}^{i} \mathbf{e}_{i}$ as above, and $\mathbf{a}_{i} := \tilde{\mathbf{d}}_{i} \mathbf{e}_{i}$, where $\mathbf{d} := (m_{\mathrm{b}} \mathbf{d}_{\mathrm{b}} + \sum_{i=1}^{3} \mathbf{d}_{i} m_{i})/\bar{m}$ is the position vector of the total COM measured in the RFR.

The Euler-Lagrange equations (5.2) are found immediately as

$$\frac{d}{dt}\frac{\partial T}{\partial \dot{\varphi}^{i}} = \Theta_{ii}^{i} \ddot{\varphi}^{i} + \dot{\omega}^{T} \boldsymbol{\theta}^{i} - m_{i} \mathbf{a}_{i}^{T} \dot{\mathbf{v}} \quad (\text{no summation over } i).$$
(5.31)

Clearly, if $\mathbf{d} = \mathbf{0}$, i.e. the RFR \mathcal{F}_{b} is located at the total COM, these equations are equivalent to those in (5.18-5.20) when modeling the system on $G = SO(3) \times \mathbb{R}^{3}$.

In matrix form, the motion equations are

$$\begin{pmatrix} \bar{\boldsymbol{\Theta}} & \bar{m}\tilde{\mathbf{d}} & \boldsymbol{\theta}^{1} & \boldsymbol{\theta}^{2} & \boldsymbol{\theta}^{3} \\ -\bar{m}\tilde{\mathbf{d}} & \bar{m}\mathbf{I} & -m_{1}\mathbf{a}_{1} & -m_{2}\mathbf{a}_{2} & -m_{3}\mathbf{a}_{3} \\ \boldsymbol{\theta}^{1^{T}} & -m_{1}\mathbf{a}_{1}^{T} & \boldsymbol{\Theta}_{11}^{1} & \mathbf{0} & \mathbf{0} \\ \boldsymbol{\theta}^{2^{T}} & -m_{2}\mathbf{a}_{2}^{T} & \mathbf{0} & \boldsymbol{\Theta}_{22}^{2} & \mathbf{0} \\ \boldsymbol{\theta}^{3^{T}} & -m_{3}\mathbf{a}_{3}^{T} & \mathbf{0} & \mathbf{0} & \boldsymbol{\Theta}_{33}^{3} \end{pmatrix} \begin{pmatrix} \dot{\boldsymbol{\omega}} \\ \dot{\mathbf{v}} \\ \ddot{\boldsymbol{\varphi}}^{1} \\ \ddot{\boldsymbol{\varphi}}^{2} \\ \ddot{\boldsymbol{\varphi}}^{3} \end{pmatrix} + \begin{pmatrix} * \\ ** \\ \mathbf{0} \\ \mathbf{0} \\ \mathbf{0} \end{pmatrix} = \mathbf{0} \qquad (5.32)$$

with $* := \widetilde{\boldsymbol{\omega}} \overline{\boldsymbol{\Theta}} \boldsymbol{\omega} - \overline{m} \widetilde{\boldsymbol{\omega}} \widetilde{\mathbf{v}} \mathbf{d} + \sum_{i=1}^{3} (\widetilde{\boldsymbol{\omega}} \boldsymbol{\theta}^{i} - m_{i} \widetilde{\mathbf{v}} \mathbf{a}_{i}) \dot{\varphi}^{i}$ and $** := \overline{m} (\widetilde{\boldsymbol{\omega}} \mathbf{v} + \widetilde{\boldsymbol{\omega}} \widetilde{\boldsymbol{\omega}} \mathbf{d}) - \sum_{i=1}^{3} m_{i} \widetilde{\boldsymbol{\omega}} \mathbf{a}_{i} \dot{\varphi}^{i}$.

Eule-Lagrange Equations on a Trivial Principle Bundle The mass matrix in (5.32) is block-partitioned, according to (5.4), with

$$\mathbf{L} = \begin{pmatrix} \bar{\boldsymbol{\Theta}} & \bar{m}\tilde{\mathbf{d}} \\ -\bar{m}\tilde{\mathbf{d}} & \bar{m}\mathbf{I} \end{pmatrix}, \ \mathbf{K} = \begin{pmatrix} \boldsymbol{\theta}^1 & \boldsymbol{\theta}^2 & \boldsymbol{\theta}^3 \\ -m_1\mathbf{a}_1 & -m_2\mathbf{a}_2 & -m_3\mathbf{a}_3 \end{pmatrix}, \ \mathbf{S} = \begin{pmatrix} \Theta_{11}^1 & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & \Theta_{22}^2 & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & \Theta_{33}^3 \end{pmatrix}.$$

Therewith, the local connection, defining the locked velocity $V_{\rm loc} = V_{\rm b} + A\dot{\phi}$ in (5.5), is

$$\mathcal{A} = \mathbf{L}^{-1} \mathbf{K} = \begin{pmatrix} \bar{\mathbf{m}}^1 & \bar{\mathbf{m}}^2 & \bar{\mathbf{m}}^3 \end{pmatrix}$$
(5.33)

with column vectors $\bar{\mathbf{m}}^i := \mathbf{L}^{-1} \mathbf{M}^i \begin{pmatrix} \mathbf{e}_i \\ \mathbf{0} \end{pmatrix}$. Explicit expressions for $\mathbf{L}, \mathbf{K}, \mathcal{A}$ are given in the supplement [16]. The kinetic energy expressed with the locked velocity is

$$T\left(\mathbf{V}_{\text{loc}}, \dot{\boldsymbol{\varphi}}\right) = \frac{1}{2} \left(\mathbf{V}_{\text{loc}} - \mathcal{A}\dot{\boldsymbol{\varphi}}\right)^{T} \mathbf{M}^{\text{b}} \left(\mathbf{V}_{\text{loc}} - \mathcal{A}\dot{\boldsymbol{\varphi}}\right) + \frac{1}{2} \sum_{i=1}^{3} \left(\mathbf{V}_{\text{loc}} + \overline{\mathbf{V}}_{i}\left(\dot{\boldsymbol{\varphi}}\right) - \mathcal{A}\dot{\boldsymbol{\varphi}}\right)^{T} \mathbf{M}^{i} \left(\mathbf{V}_{\text{loc}} + \overline{\mathbf{V}}_{i}\left(\dot{\boldsymbol{\varphi}}\right) - \mathcal{A}\dot{\boldsymbol{\varphi}}\right)$$
(5.34)

The partial derivatives in (5.12) and (5.13) are found (replacing Ω^{α} with V_{loc}^{α} and \dot{r}^{I} with $\dot{\varphi}^{i}$, $i = \overline{I}$) as

$$\frac{\partial T}{\partial \mathbf{V}_{\text{loc}}} = \mathbf{L} \left(\mathbf{V}_{\text{loc}} - \mathcal{A} \dot{\boldsymbol{\varphi}} \right) + \sum_{i=1}^{3} \mathbf{M}^{i} \overline{\mathbf{V}}_{i} = \mathbf{L} \mathbf{V}_{\text{loc}}$$
(5.35)

and $\frac{\partial T}{\partial \varphi}$ as in (5.24). Consequently, the mass matrix becomes block diagonal is in (5.14). The Hamel coefficients (5.6-5.8) are determined by the structure constants $c^{\alpha}_{\beta\delta}$ on SE (3). Again, the curvature $\mathcal{B}^{\alpha}_{IJ} = [\mathcal{A}_I, \mathcal{A}_J]^{\alpha}$ does not vanishing because of the non-commutativity of G = SE (3), where $[\mathcal{A}_I, \mathcal{A}_J] = [\mathbf{m}^{\bar{I}}, \mathbf{m}^{\bar{J}}] = \mathbf{ad}_{\mathbf{m}^{\bar{I}}} \mathbf{m}^{\bar{J}}$ is the Lie bracket on se (3) in (5.28), i.e. screw product [80]. The Euler-Lagrange equations (5.12),(5.13) are thus determined explicitly. Finally, the inverse of the locked mass matrix attains the closed form

$$\mathbf{L}^{-1} = \begin{pmatrix} \mathbf{U} & -\mathbf{U}\widetilde{\mathbf{d}} \\ \widetilde{\mathbf{d}}\mathbf{U} & \frac{1}{\bar{m}}\mathbf{I} - \widetilde{\mathbf{d}}\mathbf{U}\widetilde{\mathbf{d}} \end{pmatrix}, \text{ with } \mathbf{U} = (\bar{\boldsymbol{\Theta}} + \bar{m}\widetilde{\mathbf{d}}\widetilde{\mathbf{d}})^{-1}.$$
(5.36)

The satellite pose is obtained by solving the local kinematic reconstruction equations $\dot{\mathbf{X}} = \mathbf{dexp}_{-\mathbf{X}}^{-1} \mathbf{V}_{b}$ for the instantaneous screw coordinate vector $\mathbf{X} = (\mathbf{x}, \mathbf{y}) \in \mathbb{R}^{6} \cong se(3)$, see supplement [16]. The matrix form of the dexp map on SE(3) also possesses a closed form [55].

Floating-Base Mechanical Systems with Symmetry and Conserved Momentum

21

spa.royalsocietypublishing.org Proc R Soc A 0000000

(a) Hamel Equations, Lagrange–d'Alembert–Poincaré equations

Conservation laws can be used to introduce a connection. For floating systems with *G*-invariant Lagrangian $l(r^{I}, \xi^{\alpha}, \dot{r}^{I})$, the momentum $\boldsymbol{\Pi} \in \mathfrak{g}^{*}$, in local bundle coordinates, is

$$\Pi_{\alpha} = \frac{\partial l}{\partial \xi^{\alpha}} = L_{\alpha\beta} \xi^{\beta} + K_{\alpha J} \dot{r}^{J}.$$
(6.1)

Assuming that the initial momentum is zero, the momentum conservation $\Pi_{\alpha} = 0$ imposes non-holonomic *dynamic constraints* $u^{\alpha} = 0, \alpha = 1, \dots, \overline{m}$, which are expressed in terms of the mechanical connection with

$$u^{\alpha} = \xi^{\alpha} + \mathcal{A}_{I}^{\alpha}(r^{I})\dot{r}^{I}.$$
(6.2)

The Hamel equations are the Lagrange–d'Alembert–Poincaré equations (4.9), now with the curvature of the mechanical connection in (5.5). The connection encodes dynamic constraints due to the momentum conservation. If the initial momentum is zero, then the locked velocity is also zero. Comparing $\xi^{\alpha} = u^{\alpha} - A_{I}^{\alpha}\dot{r}^{I}$, obtained from (6.2), with $\xi^{\alpha} = \Omega^{\alpha} - A_{I}^{\alpha}\dot{r}^{I}$, obtained from (5.5), shows that the equations (4.9) are obtained from the equations (5.13), in terms of the locked velocity, when Ω^{α} is set to zero and the mechanical connection is used:

$$\frac{d}{dt}\frac{\partial\ell}{\partial\dot{r}^{I}} - \frac{\partial\ell}{\partial r^{I}} + \frac{\partial\ell}{\partial\Omega^{\beta}}\mathcal{B}_{IJ}^{\beta}\dot{r}^{J} = Q_{I}$$
(6.3)

with $\ell(r^I, \Omega^{\alpha}, \dot{r}^I) := l(r^I, \xi^{\alpha} := \Omega^{\alpha} - \mathcal{A}_I^{\alpha} \dot{r}^I, \dot{r}^I)$, and curvature $\mathcal{B}_{IJ}^{\beta} = \gamma_{IJ}^{\beta}$ given by the Hamel coefficients in (5.8), where Ω^{α} is set to zero after taking the derivatives. The system dynamics is thus described in terms of coordinates r^I on the base manifold (shape space). The motion in *G* is determined as solution of the kinematic reconstruction equations (4.10) with $\xi^{\alpha} = -\mathcal{A}_I^{\alpha}(\mathbf{r}) \dot{r}^I$ defined by the dynamic constraints $\Pi_{\alpha} = 0$.

As example, consider the satellite in Sec. 5.(f), with Lagrangian ℓ equal to the kinetic energy *T*. According to (6.3), the Hamel equations in terms of the rotor angles φ^i , $i = \overline{I}$ are given with

$$\frac{d}{dt}\frac{\partial T}{\partial \dot{\varphi}^{\bar{I}}} - \frac{\partial T}{\partial V_{\rm loc}^{\beta}} \mathcal{B}_{IJ}^{\beta} \dot{\varphi}^{\bar{J}} = Q_I \tag{6.4}$$

with $\frac{\partial T}{\partial \dot{\varphi}^i}$, and $\frac{\partial T}{\partial V_{\text{loc}}^{\alpha}}$ in (5.24) if $G = SO(3) \times \mathbb{R}^3$, and with $\frac{\partial T}{\partial V_{\text{loc}}^{\alpha}}$ in (5.35) if G = SE(3). The components of the curvature are the Hamel coefficients γ_{IJ}^{α} in (5.8) given with the structure constants of the respective symmetry group G.

(b) Geometric Phase and Pseudo-Holonomic Motion

The significance of the mechanical connection on the principal bundle is that it reveals the geometric phase shift (holonomy) $dg = -g\mathcal{A}d\mathbf{r}$, i.e. the motion in the fiber, as a result of the motion along a closed curve in shape space (Rem. 4.2), which is proportional to the curvature (here written for left-trivialization). This is due to non-integrable condition imposed by the momentum conservation (while for constrained systems this is due to non-holonomic kinematic constraints, Rem. 4.2). Whether a closed path in shape space $\mathbb{V}^{\overline{\delta}}$ leads to a closed path in G is a question arising in context of motion planning of space robots. Although for non-holonomic systems, this is not possible globally, there may be trajectories that show such cyclicity. This phenomenon was given the attribute *pseudo-holonomic*, and necessary conditions were reported in [81,82] for planar space robots. This aspect was not treated in the literature for general space robots performing spatial motions. In view of (4.8), it follows from the mean value theorem that a necessary condition is the existence of a point $\mathbf{r}_0 \in \mathbb{V}^{\overline{\delta}}$ within the area enclosed by the closed path in shape space such that the curvature of the mechanical connection vanishes, i.e. $\mathcal{B}(\mathbf{r}_0) = \mathbf{0}$. How this can be translated into cyclic 'pseudo-holomic' path planning is topic of current research. As a simple example, a floating base robot equipped with an arm comprising two revolute joints with parallel axes is discusses in the supplement [16]. For this space robot, a simple cyclic motion of the two joints leads to a pseudo-holonomic behavior so that the base motion is also cyclic (zero geometric rspa.royalsocietypublishing.org Proc R Soc A 0000000

phase). That is, along this path the base motion is a function of the arm motion, despite the momentum conservation imposing a non-holonomic constraint.

(c) Non-Zero Momentum and the Dynamic Phase

Equations (6.3) apply also when the total momentum is non-zero. The centroidal momentum $\Pi_{\rm G}^0 = \text{const}$ is the conserved quantity, which is related to its body-fixed representation by $\Pi^0(g) = \operatorname{Ad}_{g_{\rm bG}}^{-T} \Pi_{\rm G}^0$ (Sec. 5(e)). The net change of group variables is determined by the extended reconstruction equations

$$dg = g\mathbf{L}^{-1}\boldsymbol{\Pi}^0 dt - g\widehat{\mathcal{A}}d\mathbf{\hat{r}}$$
(6.5)

that replace equations (4.10). Solving the reconstruction equations for a full cycle along a closed path in \mathbb{V}^{δ} yields the total phase shift as in (4.8), but now with the additional term $q\mathbf{L}^{-1}\boldsymbol{\Pi}^{0}$. The latter delivers the dynamic phase which is intrinsically due to the (initial) momentum, and leads to a symmetry breaking from G to the symmetry group that preserves the initial momentum. If (6.5) is regarded as a control problem, this term is the drift vector field. As an example, consider the satellite in Sec. 5(f) with specific parameters. The rotation of the wheels is prescribed as $\mathbf{r}(t) =$ $(\pi (\cos (2\pi t) - 1), \pi \sin (2\pi t), \pi/2 \sin (4\pi t))$, which is periodic with cycle time 1 s. The geometric and dynamic parameters, and animations can be found in the supplementary material [16]. First assume zero total momentum. The motion of the base (i.e. of base frame \mathcal{F}_{b} located at geometric center of the base body, as shown in Fig. 2) is found from the reconstruction equations (4.11). Fig. 3a) shows the translation of \mathcal{F}_{b} in the *x-y*-plane of \mathcal{F}_{0} over 6s time duration, i.e. for six cycles of the rotor motion, starting at the origin. Indicated is the position after each cycle, which corresponds to the translation component of the geometric phase. The translation of $\mathcal{F}_{\rm b}$ is caused by the rotation about the total COM, which is not the origin of \mathcal{F}_{b} . Fig. 3b) shows the translation when the initial momentum is not zero. As an example, the momentum is set to $\Pi^0 = \mathbf{K}\dot{\mathbf{r}}(0)$, which is the momentum injected by the rotors when the base is at rest. This resembles the situation where a satellite is released with spinning fly-wheels. The base motion is caused by the turning rotors via the non-holonomic kinematics as well as the dynamics due to the momentum, which determine the total phase. For completeness, the translation that is generated by the conserved momentum only when the rotors are rest, is shown as dashed line, which yields the dynamic phase.



Figure 3. a) Translation of base frame \mathcal{F}_{b} projected onto the *x*-*y*-plane of \mathcal{F}_{0} (Fig. 2), when the total momentum is zero, and \mathcal{F}_{b} and \mathcal{F}_{0} initially coincide. Positions after full cycles (with 1 s) of the rotor motion (geometric phase) are indicated. b) Base motion for non-zero initial momentum (solid line), with positions after a full cycle of rotor motions indicated. Shown separately (dashed line) is the motion only due to the initial momentum, and the corresponding dynamic phase.

rspa.royalsocietypublishing.org Proc R Soc A 0000000

7. Remark on Classical Riemannian Geometry Formulations

It should be recalled that geometric approaches to analytical dynamics of discrete mechanical systems have a long history. They were originally developed in the setting of Riemannian geometry for unconstrained systems with Lagrangian that is quadratic in \dot{q}^a [21,83,84], where the configuration space \mathbb{V}^n is treated as a Riemannian space with metric induced by the Lagrangian. This was later extended to systems in non-holonomic quasi-velocities and non-holonomically constrained systems, and Hamel's equations are viewed as the Lagrange-d'Alembert equations on a configuration manifold whose tangent space is defined by non-holonomic constraints (which are in classical literature called non-holonomic tangent bundles). An overview of classical coordinate formulations can be found in [22,25], and using modern notations of differential geometry in [85]. Only a few publications deal with rheonomic systems and with systems where the Lagrangian is non-quadratic in \dot{q}^a . Such systems are modeled in the n + 1-dimensional event space $\mathbb{V}^n \times \mathbb{R}_+$, which is treated as a Finsler space. Thus the corresponding model-based control schemes are developed in event space [86]. Also in this classical setting, the connection and its curvature play a key roll. For example, consider an unconstrained holonomic system with Lagrangian $L(q^a, \dot{q}^a) :=$ $\frac{1}{2}g_{ab}(q)\dot{q}^{a}\dot{q}^{b}$ defined by the kinetic energy. The mass matrix defines a Riemannian metric with coefficients g_{ab} on the configuration space \mathbb{V}^n . The system dynamics, on the holonomic tangent bundle $T\mathbb{V}^n$, is governed by the equations

$$\frac{D}{dt}\dot{q}^a = Q^a \tag{7.1}$$

where $D\xi^a = d\xi^a + \Gamma^a_{bc}\xi^b dq^c$ is the absolute differential of a contravariant vector field ξ^a , and the generalized forces $Q^a = g^{ab}Q_b$. The Christoffel symbols of second kind Γ^a_{bc} define a natural affine connection, which is metric and symmetric ($\Gamma^a_{bc} = \Gamma^a_{cb}$), thus the configuration space \mathbb{V}^n is torsion free. While this is a classical result, there is a beautiful relation for the linearized equations, which is less known. Denote with $(x^a) \in \mathbb{R}^n$ small perturbations superposed to the nominal trajectory q^a , so that $q^a(t) + x^a(t)$ is the perturbed trajectory. The linearized equations along the nominal trajectory q^a are, in covariant form, with the *Riemann-Christoffel curvature* tensor R_{cbda} ,

$$g_{ab}\frac{D^2x^b}{dt^2} + \left(R_{cbda}\dot{q}^c\dot{q}^d - \nabla_b Q_a\right)x^b = \Phi_a \tag{7.2}$$

the covariant derivative $\nabla_b Q_a = \frac{\partial Q_a}{\partial q^b} - \Gamma_{ba}^c Q_c$, and small generalized forces Φ_a dual to x^a . The curvature is hence a *measure of stability* of the perturbed dynamics.

8. Conclusion

The classical Hamel formulation is a generally applicable approach in analytical mechanics for describing the dynamics of finite-dimensional systems in terms of local coordinates, which can be extended to continua [87]. Frequently, the coordinate form of equations that can be derived coordinate-free in the framework of geometric mechanics are referred to as Hamel equations. The link between these conceptually very different approaches has not been sufficiently addressed, however. This link was established in this paper, where the key is to identify the Hamel coefficients as the coefficients appearing in the coordinate form of the reduced Euler-Lagrange equations, respectively the Lagrange-Poincaré equations. Of particular significance are the local curvature coefficients that are central in many aspects of control and computational treatment of mechanical systems whose configuration space is a non-linear manifold or a Lie-group. Therewith, a clear connection between the equations governing the dynamics on a principle bundle, defined by a connection originating from certain symmetries, and the original Hamel formulation is established. In this context the choice of bundle coordinates is crucial. As such the locked velocity, and the related concept of average velocity, were discussed. The locked velocity leads to inertial decoupling, which is important for control and computational investigations. This should motivate further research into their use for deriving formulations with improved

efficiency. A problem that is increasingly receiving attention is that the average velocity cannot be used for kinematic reconstruction [67,71,73,88,89]. This could, for instance, be addressed by means of holonomy minimizing gauge transformations, i.e. introducing a frame that is not body-fixed nor aligned with the inertia frame. As a geometric aspect of the motion of non-holomic systems, it was discussed how the geometric phase leads to attitude change of floating systems for instance, and that there may be pseudo-holonomic motions. Since this is naturally covered by the geometric approach, it shall motivate treating Hamel's formalism in a geometric setting. It remains to be explored how Hamel's formulation can be extended to the general case when constraints and Lagrangian possess (possibly complementary) symmetries, as treated in [9,18], where a non-holonomic connection is introduced generalizing the kinematic and mechanical connection. As a side-contribution, some differences and inconsistencies of the definition of local curvature found in the literature were identified, which is crucial when applying equations (1.1,1.2).

A. List of Symbols

n	_	number of (generalized) coordinates
$ar{m}$	_	i) number of Pfaffian constraints, ii) dimension of the symmetry group G
$\bar{\delta} = n - \bar{m}$	-	differential (instantaneous) DOF defined by the \bar{m} Pfaffian constraints
a, b, c, \ldots	_	indices running over all coordinates: $a = 1, \ldots, n$
I, K, L, \ldots	_	indices $I = \overline{m} + 1, \dots, n$ of i) independent velocity, ii) shape coordinates
		(i.e. coordinates of the base manifold of the principle bundle) of a
		constrained or unconstrained system
$\alpha, \beta, \gamma, \ldots$	_	indices $\alpha = 1, \dots, \bar{m}$ of i) constraint equations, ii) dependent velocity
		coordinates, iii) canonical coordinates on the symmetry group G
i, j, k, l, \ldots	_	indices $i, j, k, l = 1, 2, 3$ of Cartesian vectors, e.g. $\mathbf{x} = (x^i) \in \mathbb{R}^3$
$q^a, \mathbf{q} = (q^a)$	_	local coordinates, generalized coordinates of unconstrained system
$r^I, \mathbf{r} = (r^I)$	-	independent (local) coordinates, $I = \bar{m} + 1, \dots, n$
$s^{\alpha}, \mathbf{s} = (s^{\alpha})$	-	dependent (local) coordinates, $\alpha = 1, \ldots, \bar{m}$
$\gamma^a_{bc}, \gamma^\alpha_{IJ}, \gamma^\alpha_{\beta J}$	_	Hamel coefficients
u^{lpha}	_	i) quasi-velocities, ii) bundle coordinates, iii) Pfaffian constraints
Ω^{lpha}	_	local coordinates of the locked velocity
${\cal A}^lpha_I, {\cal B}^lpha_{IJ}$	_	coefficients of the local connection and of the local curvature
ε_{ijk}	_	Levi-Civita symbol
δ_{ij}	_	Kronecker delta symbol
ĩ	-	skew symmetric matrix $\widetilde{\mathbf{x}} = (\varepsilon_{ikj} x^k)$ associated to vector $\mathbf{x} = (x^k) \in \mathbb{R}^3$
$\mathbf{x} imes \mathbf{y}$	_	cross product of $\mathbf{x}, \mathbf{y} \in \mathbb{R}^3$, can be written as $\widetilde{\mathbf{x}}\mathbf{y}$
$\hat{oldsymbol{\eta}}\in\mathfrak{g}$	-	element of Lie algebra \mathfrak{g} , corresponding to vector $oldsymbol{\eta} \in \mathbb{R}^n \cong \mathfrak{g}$
$c^{lpha}_{eta\lambda}$	-	structure coefficients of the Lie algebra \mathfrak{g}
[X, Y]	_	Lie bracket $[X, Y] = c^{\alpha}_{\beta\lambda} X^{\beta} Y^{\lambda}$ of $X, Y \in \mathfrak{g}$
$\mathcal{F}_0, \mathcal{F}_{\mathrm{b}}$	_	Inertial frame (IFR) \mathcal{F}_0 , body-fixed frame \mathcal{F}_b
$SE\left(3 ight)$	-	special Euclidean group (rigid body motion group) $SE(3) = SO(3) \ltimes \mathbb{R}^3$
$SO\left(3 ight)$	-	special orthogonal group (rotation group)
D		$r = pa I = pa I = a r \beta r \lambda = p = a r \beta r \lambda$

Ricci's summation convention: e.g. $B_I^a u^I = \sum_I B_I^a u^I$, $c^{\alpha}_{\beta\lambda} X^{\beta} Y^{\lambda} = \sum_{\beta} \sum_{\lambda} c^{\alpha}_{\beta\lambda} X^{\beta} Y^{\lambda}$

References

- R. Montgomery, J. E. Marsden, and T. S. Ratiu, "Gauged Lie-Poisson structures," Contemp. Math, vol. 28, pp. 101–114, 1984.
- 2. R. W. Montgomery, The bundle picture in mechanics. University of California, Berkeley, 1986.
- 3. A. M. Bloch, Nonholonomic mechanics and control. Springer, 2003.
- 4. W.-S. Koon and J. E. Marsden, "Optimal control for holonomic and nonholonomic mechanical systems with symmetry and Lagrangian reduction," *SIAM Journal on Control and Optimization*, vol. 35, no. 3, pp. 901–929, 1997.

- 5. N. Sreenath, "Nonlinear control of planar multibody systems in shape space," *Mathematics of Control, Signals and Systems*, vol. 5, no. 4, pp. 343–363, 1992.
- 6. E. A. Shammas, H. Choset, and A. A. Rizzi, "Towards a unified approach to motion planning for dynamic underactuated mechanical systems with non-holonomic constraints," *The International Journal of Robotics Research*, vol. 26, no. 10, pp. 1075–1124, 2007.
- 7. A. Guichardet, "On rotation and vibration motions of molecules," in *Annales de l'IHP Physique théorique*, vol. 40, no. 3, 1984, pp. 329–342.
- 8. J. E. Marsden, Lectures on Mechanics. Cambridge, 1992.
- 9. J. Marsden and J. Scheurle, "The reduced Euler-Lagrange equations," *Fields Institute Comm.*, vol. 1, pp. 139–164, 1993.
- 10. G. Hamel, "Über nichtholonome Systeme," Math. Annalen, vol. 92, no. 1, pp. 33-41, 1924.
- 11. —, Theoretische Mechanik: Eine einheitliche Einführung in die gesamte Mechanik. Springer-Verlag Berlin Heidelberg, 1949.
- 12. D. V. Zenkov, "On Hamel's equations," *Theoretical and Applied Mechanics*, vol. 43, no. 2, pp. 191–220, 2016.
- H. Mishra, M. De Stefano, A. M. Giordano, R. Lampariello, and C. Ott, "A geometric controller for fully-actuated robotic capture of a tumbling target," in 2020 American Control Conference (ACC). IEEE, 2020, pp. 2150–2157.
- 14. D. E. Orin and A. Goswami, "Centroidal momentum matrix of a humanoid robot: Structure and properties," in 2008 IEEE/RSJ Int. Conf. on Intel. Rob. and Sys., 2008, pp. 653–659.
- 15. D. E. Orin, A. Goswami, and S.-H. Lee, "Centroidal dynamics of a humanoid robot," *Autonomous robots*, vol. 35, no. 2, pp. 161–176, 2013.
- 16. A. Müller, "Supplement to "Hamel's Equations and Geometric Mechanics of Constrained and Floating Multibody and Space Systems"," *Figshare*, DOI: 10.6084/m9.figshare.c.6607449.
- 17. D. D. Holm, Geometric mechanics-Part I: Dynamics and symmetry. World Scientific, 2011.
- 18. A. M. Bloch, P. Krishnaprasad, J. E. Marsden, and R. M. Murray, "Nonholonomic mechanical systems with symmetry," *Archive for Rational Mech. and Anal.*, vol. 136, no. 1, pp. 21–99, 1996.
- 19. J. C. Baez and J. P. Muniain, *Gauge fields, knots and gravity*. World Scientific, 1994, vol. 4.
- 20. T. Frankel, *The Geometry of Physics*. Cambridge, 2004.
- 21. E. T. Whittaker, A treatise on the analytical dynamics of particles and rigid bodies (4th ed.). Cambridge, 1988.
- 22. J. Papastavridis, Analytical Mechanics: A Comprehensive Treatise on the Dynamics of Constrained Systems for Engineers, Physicists, and Mathematicians. Oxford University Press, 2002.
- 23. A. Sommerfeld, Vorlesungen über theoretische Physik, Band 1: Mechanik,. Akademische Verlagsgesellschaft, Leipzig, 1948.
- 24. G. Hamel, "Über die virtuellen Verschiebungen in der Mechanik," *Math. Ann.*, vol. LIX, pp. 416–434, 1904.
- 25. P. Maisser, "Differential-geometric methods in multibody dynamics," *Nonlinear Analysis: Theory, Methods & Applications*, vol. 30, no. 8, pp. 5127–5133, 1997.
- 26. J. M. Maruskin and A. M. Bloch, "The boltzmann-hamel equations for optimal control," in 2007 46th IEEE Conference on Decision and Control. IEEE, 2007, pp. 554–559.
- 27. L. Boltzmann, "Über die Form der Lagrange'schen Gleichungen für nicht holonome generalisierte Coordinaten," Sitzungsberichte der Mathematisch-Naturwissenchaftlichen Klasse der Kaiserlichen Akademie der Wissenchaften in Wien, vol. 111, pp. 1603–1614, 18. December 1902.
- 28. —, Vorlesungen über die Principe der Mechanik: II Teil. Verlag von Johann Ambrosius Barth, Leipzig, 1904.
- 29. G. Hamel, "Die Lagrange-Eulersche Gleichungen der Mechanik," Z. Math. Phys., vol. 50, no. 1, pp. 1–57, 1904.
- R. Murray, Z. Li, and S. Sastry, A Mathematical Introduction to Robotic Manipulation. CRC Press, 1994.
- 31. A. Müller, "Screw and Lie group theory in multibody kinematics," *Multibody System Dynamics*, vol. 43, no. 1, pp. 37–70, 2018.
- , "On the Hamel Coefficients and the Boltzmann–Hamel Equations for the Rigid Body," *Journal of Nonlinear Science*, vol. 31, no. 2, pp. 1–39, 2021.
- 33. J. E. Marsden and T. S. Ratiu, "Introduction to mechanics and symmetry," *Physics Today*, vol. 48, no. 12, p. 65, 1995.
- 34. T. G. Ionescu, P. Antonescu, I. Biro, G. Bögelsack, and A. K. Breteler, "Terminology for the mechanism and machine science," *Mech. Mach. Theory*, vol. 38, pp. 767–901, 2003.

- 35. A. Müller and D. Zlatanov, *Singular Configurations of Mechanisms and Manipulators*. Springer, 2019.
- 36. C. Ehresmann, "Les connexions infinitésimales dans un espace fibré différentiable," in *Colloque de topologie, Bruxelles*, vol. 29, 1950, pp. 55–75.
- 37. A. M. Bloch, J. E. Marsden, and D. V. Zenkov, "Nonholonomic dynamics," *Notices of the AMS*, vol. 52, no. 3, pp. 324–333, 2005.
- 38. R. L. Hatton and H. Choset, "Geometric motion planning: The local connection, stokes theorem, and the importance of coordinate choice," *The International Journal of Robotics Research*, vol. 30, no. 8, pp. 988–1014, 2011.
- 39. S. A. Chaplygin, "On a motion of a heavy body of revolution on a horizontal plane," *Regular and Chaotic Dynamics [English translation]*, vol. 7, no. 2, pp. 119–130, 2002.
- 40. ——, "On some generalization of the area theorem with applications to the problem of rolling balls (matematicheskii sbornik, vol. 20, 1897, pp. (in russian))," *English translation: Regular and Chaotic Dynamics*, vol. 17, no. 2, pp. 199–217, 2012.
- 41. P. Voronets, "Equations of motion for nonholonomic systems," *Matematicheskii Sbornik*, vol. 22, no. 4, pp. 659–686., 1901.
- 42. P. Woronetz, "Über die Bewegung eines starren Körpers, der ohne Gleitung auf einer beliebigen Fläche rollt," *Mathematische Annalen*, vol. 70, no. 3, pp. 410–453, 1911.
- 43. S. Soltakhanov, M. Yushkov, and S. Zegzhda, *Mechanics of non-holonomic systems A New Class of control systems*. Springer, 2009.
- 44. E. A. Shammas, H. Choset, and A. A. Rizzi, "Towards a unified approach to motion planning for dynamic underactuated mechanical systems with non-holonomic constraints," *The International Journal of Robotics Research*, vol. 26, no. 10, pp. 1075–1124, 2007.
- 45. J. E. Marsden, T. S. Ratiu, and J. Scheurle, "Reduction theory and the lagrange-routh equations," *Journal of mathematical physics*, vol. 41, no. 6, pp. 3379–3429, 2000.
- 46. J. McCauley, Classical Mechanics. Cambridge, 1997.
- 47. Y. Choquet-Bruhat, C. DeWitt-Morette, and M. Dillard-Bleick, *Analysis, Manifolds and Physics* - *Part I.* North-Holland, 1996.
- 48. S. D. Kelly and R. M. Murray, "Geometric phases and robotic locomotion," *Journal of Robotic Systems*, vol. 12, no. 6, pp. 417–431, 1995.
- 49. J. Ostrowski and J. Burdick, "Geometric perspectives on the mechanics and control of robotic locomotion," pp. 536–547, 1996.
- 50. G. Darboux, "Leçons sur la théorie généles applications géométriques du calcul infinitesimal," *Gautiers-Villars, Paris*, vol. 4, 1887.
- 51. D. Condurache, "Poisson-Darboux problems's extended in dual Lie algebra," in AAS/AIAA Astrodynamics Specialist Conference, Stevenson, WA, USA, 2017.
- 52. H. Munthe-Kaas, "Runge-Kutta methods on Lie groups," *BIT Numerical Mathematics*, vol. 38, no. 1, pp. 92–111, 1998.
- 53. —, "High order Runge-Kutta methods on manifolds," Applied Numerical Mathematics, vol. 29, no. 1, pp. 115–127, 1999.
- 54. A. Iserles, H. Z. Munthe-Kaas, S. P. Nørsett, and A. Zanna, "Lie-group methods," Acta Numerica, vol. 9, p. 215â€"365, 2000.
- 55. A. Müller, "Review of the exponential and Cayley map on SE (3) as relevant for Lie group integration of the generalized Poisson equation and flexible multibody systems," *Proceedings* of the Royal Society A, vol. 477, no. 2253, 2021.
- 56. D. McDonald, "How does a man twist in the air?" *New Scientist*, vol. 10, no. 237, pp. 501–503, 1961.
- 57. T. Kane and M. Scher, "A dynamical explanation of the falling cat phenomenon," *International journal of solids and structures*, vol. 5, no. 7, pp. 663–670, 1969.
- H. Essén, "The cat landing on its feet revisited or angular momentum conservation and torque-free rotations of non-rigid mechanical systems," *American Journal of Physics*, vol. 49, no. 8, pp. 756–758, 1981.
- 59. M. Enos, "On an optimal control problem on SO(3)xSO(3) and the falling cat," American Mathematical Society (Ed.): Dynamics and Control of Mechanical Systems, 1993.
- R. Montgomery, "Gauge Theory of the Falling Cat," *Fields Inst. Commun*, vol. 1, pp. 193–218, 1993.
- 61. D. Gerritsen and M. Kuipers, "On the angular motion of a freely falling human or animal body," *Journal of Engineering Mathematics*, vol. 13, no. 4, pp. 347–353, 1979.

- 62. S. Smale, "Topology and mechanics. ii," Inventiones mathematicae, vol. 11, no. 1, pp. 45-64, 1970.
- 63. A. Shapere and F. Wilczek, "Self-propulsion at low reynolds number," *Physical Review Letters*, vol. 58, no. 20, p. 2051, 1987.
- 64. —, "Gauge kinematics of deformable bodies," *American Journal of Physics*, vol. 57, no. 6, pp. 514–518, 1989.
- 65. C. J. Isham, *Modern differential geometry for physicists*, 2nd ed. World Scientific Publishing Company, 1999, vol. 61.
- 66. H. Cendra, J. E. Marsden, and T. S. Ratiu, "Geometric mechanics, Lagrangian reduction, and nonholonomic systems," in *Math. unlimited*—2001 and beyond. Springer, 2001, pp. 221–273.
- 67. G. Garofalo, B. Henze, J. Englsberger, and C. Ott, "On the inertially decoupled structure of the floating base robot dynamics," *IFAC-PapersOnLine*, vol. 48, no. 1, pp. 322–327, 2015.
- A. M. Giordano, D. Calzolari, and A. Albu-Schäffer, "Workspace fixation for free-floating space robot operations," in 2018 IEEE International Conference on Robotics and Automation (ICRA). IEEE, 2018, pp. 889–896.
- 69. A. M. Giordano, C. Ott, and A. Albu-Schäffer, "Coordinated control of spacecraft's attitude and end-effector for space robots," *IEEE Rob. and Aut. Let.*, vol. 4, no. 2, pp. 2108–2115, 2019.
- 70. H. Essén, "Average angular velocity," European journal of physics, vol. 14, no. 5, p. 201, 1993.
- G. Nava, L. Fiorio, S. Traversaro, and D. Pucci, "Position and attitude control of an underactuated flying humanoid robot," in 2018 IEEE-RAS 18th International Conference on Humanoid Robots (Humanoids). IEEE, 2018, pp. 1–9.
- 72. S.-H. Lee and A. Goswami, "Reaction mass pendulum (rmp): An explicit model for centroidal angular momentum of humanoid robots," in *Proceedings* 2007 *IEEE International Conference on Robotics and Automation*. IEEE, 2007, pp. 4667–4672.
- 73. A. Saccon, S. Traversaro, F. Nori, and H. Nijmeijer, "On centroidal dynamics and integrability of average angular velocity," *IEEE Rob. Automat. Letters*, vol. 2, no. 2, pp. 943–950, 2017.
- 74. S. Dubowsky and E. Papadopoulos, "The kinematics, dynamics, and control of free-flying and free-floating space robotic systems," *IEEE Tran. Rob. Automat.*, vol. 9, no. 5, pp. 531–543, 1993.
- 75. E. G. Papadopoulos, "Nonholonomic behavior in free-floating space manipulators and its utilization," in *Nonholonomic Motion Planning*. Springer, 1993, pp. 423–445.
- F. Celledoni and B. Owren, "Lie group methods for rigid body dynamics and time integration on manifolds," *Computer Methods in Appl. Mech. and Eng.*, vol. 192, no. 3, pp. 421 – 438, 2003.
 M. Borri and C. Bottasso, "An intrinsic beam model based on a helicoidal approximation-Part
- 77. M. Borri and C. Bottasso, "An intrinsic beam model based on a helicoidal approximation-Part I: Formulation," *Int. J. for Num. Methods in Eng.*, vol. 37, no. 13, pp. 2267–2289, 1994.
- V. Sonneville, A. Cardona, and O. Brüls, "Geometrically exact beam finite element formulated on the special Euclidean group SE(3)," *Computer Methods in Applied Mechanics and Engineering*, vol. 268, pp. 451–474, 2014.
- 79. H. Gattringer, A. Reiter, C. Stöger, M. Jörgl, P. Hörmandinger, and A. Müller, "Dynamical modeling and swing-up control of a self-balancing cube," in *International Conference on Robotics in Alpe-Adria Danube Region*. Springer, 2016, pp. 144–151.
- 80. J. M. Selig, Geometric fundamentals of robotics. Springer Science & Business Media, 2004.
- 81. R. Mukherjee and M. Zurowski, "Pseudo-holonomic behavior of planar space robots," in 1994 IEEE Int. Conf. on Rob. and Automat. IEEE, 1994, pp. 2405–2410.
- R. Mukherjee, "Pseudoholomorphic behavior of planar space robots," Journal of Guidance, Control, and Dynamics, vol. 19, no. 1, pp. 251–253, 1996.
- 83. J. L. Synge and A. Schild, Tensor calculus. University of Toronto Press, 1949.
- 84. A. I. Lurie, Analytical Mechanics (in Russian). State Publishing House, Physical And Mathematical Literature, Moscow, 1961; Published as English translation: A.I. Lurie, Analytical Mechanics, Springer, 2002.
- 85. F. Bullo and A. D. Lewis, *Geometric control of mechanical systems: modeling, analysis, and design for simple mechanical control systems.* Springer, 2004, vol. 49.
- U. Jungnickel, G. Kielau, P. Maisser, and A. Müller, "A passivity-based control of eulerlagrange systems with a non-quadratic lagrangian," ZAMM-Journal of Applied Mathematics and Mechanics, pp. 982–992, 2008.
- 87. D. Shi, D. V. Zenkov, and A. M. Bloch, "Hamel's formalism for classical field theories," *Journal* of Nonlinear Science, vol. 30, no. 4, pp. 1307–1353, 2020.
- 88. J. I. Mulero-Martínez, "A new factorization of the coriolis/centripetal matrix," *Robotica*, vol. 27, no. 5, pp. 689–700, 2009.
- 89. W. Du, Z. Wang, E. Moullet, and F. Benamar, "Meaningful centroidal frame orientation of multi-body floating locomotion systems," in *IEEE Int. Conf. Rob. Automat*, 2021, pp. 3061–3067.

Proc R Soc A 0000000