Experts' cognition-driven ensemble deep learning for external validation of predicting pathological complete response to neoadjuvant chemotherapy from histological images in breast cancer

Yongquan Yang¹, Fengling Li¹², Yani Wei¹², Yuanyuan Zhao³, Jing Fu⁴, Xiuli Xiao⁵, Hong Bu¹²

1. Institute of Clinical Pathology, West China Hospital, Sichuan University, Chengdu, China

2. Department of Pathology, West China Hospital, Sichuan University, Chengdu, China

3. Department of Pathology, Shanxi Province Cancer Hospital/Shanxi Hospital Affifiliated to Cancer Hospital, Chinese Academy of Medical Sciences/Cancer Hospital Affifiliated to Shanxi Medical University, Taiyuan, China.

4. Department of Pathology, Sichuan Provincial People's Hospital, Chengdu, China.

5. Department of Pathology, The Affiliated Hospital of Southwest Medical University, Luzhou, China.

Abstract

Purpose: In breast cancer imaging, there has been a trend to directly predict pathological complete response (pCR) to neoadjuvant chemotherapy (NAC) from histological images based on deep learning (DL). Existing studies, which follow the paradigm of constructing DL-based models for medical prediction, have provided alternative solutions for predicting pCR from histological images in breast cancer. However, it has been a commonly known problem that the constructed DL-based models numerically have better performances in internal validation than in external validation. The primary reason for this situation lies in that the distribution of the external data for validation is different from the distribution of the training data for the construction of the predictive model. In this paper, we aim to alleviate this situation with a more intrinsic approach.

Methods: We propose an experts' cognition-driven ensemble deep learning (ECDEDL) approach for external validation of predicting pCR to NAC from histological images in breast cancer. The proposed ECDEDL, which takes the cognition of both pathology and artificial intelligence experts into consideration to improve the generalization of the predictive model to the external validation, more intrinsically approximates the working paradigm of a human being which will refer to his various working experiences to make decisions. The proposed ECDEDL approach was validated with 695 WSIs collected from the same center as the primary dataset to develop the predictive model and perform the internal validation, and 340 WSIs collected from other three centers as the external dataset to perform the external validation.

Results: In external validation, the proposed ECDEDL approach improves the AUCs of pCR prediction from 61.52(59.80-63.26) to 67.75(66.74-68.80) and the Accuracies of pCR

prediction from 56.09(49.39-62.79) to 71.01(69.44-72.58).

Conclusion: The proposed ECDEDL was quite effective for external validation, numerically more approximating the internal validation.

Key words

Ensemble deep learning; External validation; Pathological complete response; Neoadjuvant chemotherapy; Breast cancer

Email addresses: Yongquan Yang (<u>remy_yang@foxmail.com</u>), Fengling Li (<u>lifengling_scu@foxmail.com</u>), Yani Wei (<u>yani_wei@foxmail.com</u>), Yuanyuan Zhao(82894392@qq.com), Jing Fu (<u>bailangefly@163.com</u>), Xiuli Xiao (<u>xiaoxiulily@sina.com</u>), Hong Bu (<u>hongbu@scu.edu.cn</u>).

1. Introduction

With the advances of deep learning (DL) [1], mostly deep neural networks [2–4] which are the state-of-the-art machine learning techniques, various studies have shown that DL-based artificial intelligence (AI) models have significant effectiveness and potentials in medical diagnostic or prognostic prediction [5–8]. There has been an increasingly standardized paradigm of constructing DL-based AI models for medical diagnostic or prognostic results are collected as a training dataset; Subsequently, a deep learning architecture is selected and optimized on the collected training dataset to produce a DL-based AI model that can predict the diagnostic or prognostic results corresponding to the clinical data; Finally, the produced DL-based AI model is validated on some new data that contain clinical data and corresponding diagnostic and prognostic.

Particularly, the validation procedure is an essential part in the constructing paradigm, for it can reflect the expected predictive performance and generalization of the produced DLbased AI model in practical usage. The data required by the validation procedure can be internal or external. Specifically, the internal data is assumed to have the same distribution while the external data is assumed to have a different distribution, compared with the training data collected for producing the DL-based Al model. Usually, we say that the data for the validation procedure is internal and have the same distribution compared with the training data when the data for the validation procedure and the training data are collected from the same centers, since they share common data production in the same centers. On the contrary, we say that the data for the validation procedure is external and have a different distribution compared with the training data when the data for the validation procedure and the training data are collected from different centers, since they probably have uncommon data production in different centers. The validation procedure is called internal validation when provided with internal data, or external validation when provided with external data. Both internal validation and external validation are essential [9-13], since internal validation can reflect the feasibility of constructing a DL-based AI model for a medical diagnostic or prognostic prediction task while external validation can reflect the potentials of the constructed DL-based AI model for a wider usage in practice.

In breast cancer, neoadjuvant chemotherapy (NAC) [14, 15] provides a standard treatment option for patients who have locally advanced cancer and some large operable tumors. In clinical trials, it has been shown that a patient will have better prognosis when he has achieved a pathological complete response (pCR) with the treatment of NAC to reduce the tumor burden and promote breast-conserving surgery [16]. In breast cancer imaging, there has been a trend to directly predict pCR to NAC from histological images using DL [17]. Following the paradigm of constructing DL-based AI models for medical prediction, which has been described in the first paragraph of this section, existing studies [18–22] have provided alternative solutions for predicting pCR from histological images in breast cancer. The application of these alternative solutions can be summarized as directly build the predictive model from the histological images via DL.

However, it has been a commonly known problem that the AI models constructed for medical prediction numerically have better performances in internal validation than in external validation, which significantly affects the clinical safety of using AI models [23]. The primary reason for this situation lies in that the distribution of the external data for validation is different from the distribution of the training data for the construction of the predictive model, due to the significant variance of slide preparation and microscope scanning. This issue is also known as sample selection bias [24, 25] in statistics with small data, or out-of-distribution validation [26] and domain adaption/generalization [27–30] in machine learning with big data. According to a recent survey [31], the out-of-distribution problem of external validation, i.e., the problem of domain generalization is the primary challenge for deep learning in breast cancer imaging. Therefore, it is important and necessary to investigate advanced approaches for the out-of-distribution problem of external validation in breast cancer imaging.

The usual methods for alleviating this issue in breast pathology analysis can be divided into three categories [31], including data augmentation via color distortion on the RGB channels and the HSI channels [32, 33], mapping from source domain to target domain via adversarial learning [34, 35], and generalizing AI models to unseen domain via feature alignment and domain-invariant feature learning [36–38]. Having shown promising potentials to provide alternative solutions for external validation of predicting pCR to NAC in breast cancer from histological images, these existing methods as well have some limitations. Data augmentation solutions via color distortion, which have been standard processes in the evolvement of a deep predictive model, usually can only imitate certain aspects of variance due to the complex situation of the slide preparation and microscope scanning. Domain adaption via adversarial learning, which maps source domain to target domain, requires some image samples of the target domain in advance. As a result, domain adaption is not suitable for the situation where the target domain is unseen. Domain generalization overcomes the defect of domain adaption without requiring some image samples of the target domain in advance, however, only a very few methods have been particularly proposed for medical prediction [39-42]. In addition, two recent works [43, 44] have proposed to employ federated learning [45–47] to improve performance in multicenter deep learning without data sharing, which have shown that federated learning can help to provide alternative solutions relevant to the out-of-distribution problem of external validation in medical prediction. However, a federated learning solution requires each of the multiple centers constructs a predictive model, and it also needs a central system to manage communications between the predictive models of the multiple centers for testing in practical usage. As a result, federate leaning is a technique that is more appropriate to solve the problem of data privacy among multiple centers and requires high expenses at the meantime.

More importantly, we observe that these existing alternative methods have the paradigm that is different from the working paradigm of a medical expert. Usually, a pathological expert commonly will refer to his cognition, that has been accumulated via different working experiences, about the medical data at hand to make decisions. Moreover, the out-ofdistribution problem of the external data commonly will not affect a well-trained expert that much to make usual decisions, since a first-class expert is unlikely to become a third-class expert in practice because of the distribution change of data. Due to these insights, we argue that a more intrinsic approach is required to address the out-of-distribution problem in external validation of predicting pCR to NAC in breast cancer from histological images.

In this paper, we propose an experts' cognition-driven ensemble deep learning (ECDEDL) approach for external validation of predicting pCR to NAC from histological images in breast cancer. The proposed ECDEDL, which takes the cognition of both pathology and Al experts into consideration to improve the generalization of the predictive model to the external validation, has three innovations: 1) Proposing a data preparation strategy that takes into account the cognition of pathology experts about viewing a histological image in breast cancer, which results in a Tumor dataset and a Stroma dataset respectively extracted from histological images; 2) Proposing a learning paradigm that takes into account the cognition of AI experts about exploiting complementary information among the pathologically variant contents of histological images to improve the generalization of the predictive model, which results in an Ensemble Deep Learning [48] framework; 3) Constructing a new approach for the external validation of predicting pCR to NAC from histological images in breast cancer, by integrating the proposed pathology experts' cognition-driven data preparation strategy and the proposed AI experts' cognition-driven learning paradigm. Regarding to these three innovations, the proposed ECDEDL approach is different from the alternative solutions [18– 21] for predicting pCR to NAC from histological images in breast cancer and the existing approaches [39-44] for the out-of-distribution problem of external validation in medical prediction.

Since the cognition of both pathology and AI experts have been taken to construct the predictive model, the proposed ECDEDL approach, to some extent, approximates the working paradigm of a human being which will refer to his various working experiences to make decisions. As the cognition of experts is less likely to be affected by data distribution shift in practice, the proposed ECDEDL approach for external validation is more likely to be invariant to the significant variance of slide preparation and microscope scanning of the external data. As far as we know, this paper is the first to particularly address the out-of-distribution problem in external validation of predicting pCR to NAC in breast cancer from histological images. Besides, this paper also has contributions including: 1) Proposing an ECDEDL approach for external validation; 2) Implementing and evaluating the proposed ECDEDL approach for external validation; 3) The proposed ECDEDL approach shows significant effectiveness in improving the performance for external validation.

2. Materials and Method

2.1 Data basis and preprocessing

2.1.1 Data basis

The histological images used in this study to evaluate ECDEDL for external validation are the same as our previous paper [49], in which more details are provided. The used histological images were 1035 whole slide images (WSIs) collected from four centers. Among the 1035 WSIs, 695 WSIs collected from the same center are used as the primary dataset to develop the predictive model and perform the internal validation, and the rest 340 WSIs collected from other three centers are used as the external dataset to perform the external validation. More details are available at [49]. Among the primary dataset, 555 WSIs are used as the training dataset to develop the predictive model and the rest 140 WSIs are used as the internal dataset to perform the internal validation.

2.1.2 Data preprocessing

As a WSI usually contains many repetitive and less informative regions, pathological experts were invited to annotate representative regions containing tumor and stroma on each of the collected WSIs. The annotated representative region is called region of interest (ROI), which ensures that the stroma inside the ROI was near the tumor and surrounded by tumor cells. Small images from the ROIs annotated on each of the collected WSIs were cropped at $233 \times 233 \ \mu\text{m}$ squares (256 × 256 pixels at 10 × magnification), which are called "tiles". More details about how the ROIs were annotated, readers can refer to [49].

2.1.3 Summary

The data basis and preprocessing can be summarized as Table. 1.

Total 1035 WSIs						
Primary dataset			External dataset			
(695 WSIs from the same center)			(340WSIs from three centers)			
Training dataset		Internal dataset	Total			
(555WSIs)		(140 WSIs)	(18304 tiles)			
Total		Total				
(32556 tiles)		(6981 tiles)				
Training	Validation					
(26045 tiles)	(6511 tiles)					
Per WSI		Per WSI	Per WSI			
(59 tiles on average)		(50 tiles on average)	(54 tiles on average)			
Model development		Internal validation	External validation			

Table 1. summarization of data basis and preprocessing.

2.2 Methodology of ECDEDL

ECDEDL constitutes of a pathology experts' cognition-driven data preparation strategy, an AI experts' cognition-driven learning paradigm and the feeding relation between them. The outline of ECDEDL for external validation of predicting pCR to NAC from histological images in breast cancer is shown as Fig. 1. More details of ECDEDL for external validation of predicting pCR to NAC from histological images in breast cancer are provided in the rest of this subsection.

2.2.1 Pathology experts' cognition-driven data preparation strategy

We propose a data preparation strategy which respectively extracts a Tumor dataset and a Stroma dataset from the collected histological images. This data preparation strategy is established by referring to the cognition of pathology experts about viewing a histological image in breast cancer, which is that tumor and stroma are likely to be paid more attention than the whole content of the histological image and can probably possess potential predictive ability for predicting pCR to NAC from histological images in breast cancer. Moreover, two recent studies [49, 50] have shown that tumor and stroma areas of histological images in breast cancer can both be predictive for pCR to NAC. Proving that the cognition of pathology experts indeed can have effectiveness in constructing appropriate DL-based AI models for medical prediction, these two studies [49, 50] just can explain the rationality of the proposed pathology experts' cognition-driven data preparation strategy for the external validation of predicting pCR to NAC from histological images in breast cancer.



Fig. 1. Outline of the proposed ECDEDL approach for external validation of predicting pCR to NAC from histological images in breast cancer.

2.2.2 Artificial intelligence experts' cognition-driven learning paradigm

We propose an artificial intelligence (AI) experts' cognition-driven learning paradigm which is an Ensemble Deep Learning framework. This learning paradigm is established by referring to the cognition of AI experts about exploiting complementary information among the pathologically variant contents of histological images to improve the generalization of the predictive model, which can be realized via ensemble learning [48, 51, 52] based on data manipulation, which is an effective basis for the realization of ensemble learning []. Moreover, some researches [27, 28, 53–55] have shown that ensemble deep learning have the potentials in addressing the out-of-distribution problem of external validation. Proving that the cognition of AI experts can also have effectiveness in constructing better DL-based AI models, these researches [27, 28, 53–55] just can explain the rationality of the proposed AI experts' cognition-driven learning paradigm for the external validation of predicting pCR to NAC from histological images in breast cancer.

2.2.3 Construction of ECDEDL

Based on the pathology experts' cognition driven data preparation strategy proposed in section 2.1.1 and the AI experts' cognition driven learning paradigm proposed in section 2.1.2, we constructed ECDEDL by feeding the Tumor and Stroma datasets of the data preparation strategy to Ensemble Deep Learning framework of the learning paradigm as the data manipulation basis, as the Tumor and Stroma datasets of the data preparation strategy naturally fit the data manipulation basis for the ensemble deep learning framework of the learning paradigm.

2.3 Implementation of ECDEDL

For the preparation of the Tumor and Stroma datasets, we used a previously developed image segmentation tool to extract the Tumor and the Stroma contents from the collected histological images tiles. Readers can refer to [56] for the technical details of the used image segmentation tool. Some examples of the Tumor and Stroma datasets extracted from the

original histological image tiles are shown as Fig. 2.



Fig. 2. Examples of original histological image tiles and extracted Tumor and Stroma tiles. Top: original histological image tiles; Middle: extracted Tumor tiles; Bottom: extracted Stroma tiles.

For the implementation of the Ensemble Deep Learning framework, two key points need to be considered: 1) the settings of DNN architecture and learning strategy for generating base models; and 2) the ensembling criterion for forming the final predictive model. For point 1), we employ existing state-of-the-art deep convolutional neural networks (DNNs) [57] and corresponding learning strategy to generate base models. More specifically, we respectively employed MobileNetV2 [58], ResNet101V2 [59] and NASNetLarge [60] as the DNN architecture from light weight to complex, which will be further discussed in the next section of evaluating ECDEDL for external validation. The details of the learning strategy include, optimizer: SGD [61] with learning rate=0.001, momentum=0.9; batch size: 16; epochs: 256; online augmentation: horizontal flip=True, vertical flip=True, rotation range=10, zoom range=[0.8, 1.2], width shift range=0.2, height shift range=0.2, brightness range=[0.7, 1.3]; and weighted cross-entropy loss []. For point 2) we employ weighted average strategy to integrate the predictions of the base models for forming the final predictive model. More specifically, we weighted the base models according to their individual predictive performance (default is fifty-fifty).

For the evolvement of ECDEDL, we firstly used the corresponding learning strategy to optimize the DNN architecture to produce two base models, respectively feeding the prepared Tumor and Stroma datasets to the DNN architecture. Then, based on the produced two base models, we weighted and averaged their predictions to form the final prediction.

2.4 Evaluating ECDEDL for external validation

We respectively trained four series of predictive models for predicting pathological complete response to neoadjuvant chemotherapy from histological images in breast cancer. The trained two series of predictive models include: 1) the predictive model produced by training the given DNN architecture based on the original prepared data, examples of which

are shown as the top row of Fig. 2; 2) the predictive model produced by training the same DNN architecture based on the Tumor dataset, examples of which are shown as the middle row of Fig. 2; 3) the predictive model produced by training the same DNN architecture based on the Stroma dataset, examples of which are shown as the bottom row of Fig. 2; 4) the ensemble model of the predictive models respectively produced based on the Tumor and Stroma dataset, which represents the ECDEDL approach.

The four series of predictive models were trained with the same learning strategy described in section 2.3. We respectively denote the four series of predictive model as Direct model, Tumor model, Stroma model and TS-Ensemble model. We validate and compare their performances using different metrics, to show the effectiveness of the ECDEDL approach for external validation. More specifically, we first compare the Tumor and Stroma models with the Direct model to show the effectiveness of the pathology experts' cognition in ECDEDL. Second, we compare TS-Ensemble model respectively with Tumor model and Stroma model to assess the effectiveness of the AI experts' cognition in ECDEDL. Then, we compare TS-Ensemble model to show the effectiveness of the ECDEDL approach for external validation, since the Direct model can be regarded as the usual model constructed without experts' cognition. To avoid the effects of possible experimental errors, we repeated the training and validation metrics for a fair comparison.

We respectively employed MobileNetV2 [58], ResNet101V2 [59] and NASNetLarge [60] (from light weight to complex) as the DNN architecture in the procedures of the training and validation of the two series of predictive models, to show the stability of the effectiveness of the ECDEDL approach for external validation with different DNN architectures. We employed ROC and PR curves to evaluate the overall performances of predictive models, and metrics of Precision, Recall, F1 and Accuracy calculated at the threshold of probability 0.5 to evaluate the practical performances of predictive models.

3. Results and Discussion

3.1 Effectiveness of pathology experts' cognition in ECDEDL

The ROC and PR curves of the Tumor model, the Stroma model and the Direct model on external data are shown as Fig. 3. In Fig. 3, the curves were drawn with different DNN architectures and repeated experiments.

From Fig. 3, we can summarize that the Tumor model and the Stroma model perform better than both the Direct model on external data. These results reflect that pathology experts' cognition in ECDEDL is effective, leading to better performances in external validation.

3.2 Effectiveness of AI experts' cognition in ECDEDL

The ROC and PR curves of the TS-Ensemble model (ensemble of the Tumor and Stroma models), the single Tumor model and the single Stroma model on external data are shown as Fig. 4. In Fig. 4 the curves were drawn with different DNN architectures and repeated experiments.

From Fig. 4, we can summarize that the TS-Ensemble model performs better than both the Tumor model and the Stroma model on external data. These results reflect that AI experts'

cognition in ECDEDL is effective, leading to even better performances in external validation.



Fig. 3. ROC and PR curves of the Tumor model and the Stroma model compared with the Direct model on external data



Fig. 4. ROC and PR curves of the TS-Ensemble model compared with the Tumor model and the Stroma model on external data.

3.3 Overall performance of ECDEDL

The ROC curves of the TS-Ensemble model on external data and the Direct model respectively on Internal data and external are shown as Fig. 5. In Fig. 5, the curves were drawn regarding to different DNN architectures with repeated experiments, and their union results. Corresponding PR curves are shown as Fig. 6. The 95% confident intervals (CI) of the AUC for ROC curves corresponding to Fig. 5 and the AP for PR curves corresponding to Fig. 6 are shown as Table 2.

Form Fig. 5, Fig. 6 and Table 2, we can summarize that the TS-Ensemble model performs much better than the Direct model on external data, and the performances of the TS-Ensemble model on external data are close to the performances of the Direct model on internal data. These results indicate that the overall performances of the ECDEDL approach



for external validation are quite good, approximating the internal validation.

Fig. 5. ROC curves of the TS-Ensemble model on external data and the Direct model respectively on Internal data and external. Internal: Direct model on internal data; External: Direct model on external data; ECDEDL-External: TS-Ensemble model on external data.

Metrics-Architecture		Internal(CI)	External(CI)	ECDEDL-External(CI)
AUC	MobileNetV2	70.62(66.12-75.07)	60.55(58.57-62.53)	68.76(66.90-70.67)
	ResNet101V2	74.02(70.87-77.11)	63.95(62.30-65.59)	65.99(65.15-66.88)
	NASNetLarge	70.42(68.69-72.16)	60.07(56.06-64.12)	68.48(66.97-70.07)
	Union	71.12(69.71-73.64)	61.52(59.80-63.26)	67.75(66.74-68.80)
AP	MobileNetV2	47.56(38.95-53.76)	34.81(32.71-36.13)	42.51(40.31-43.72)
	ResNet101V2	48.63(42.00-52.39)	36.08(34.14-37.23)	39.07(37.39-39.96)
	NASNetLarge	45.24(40.70-48.12)	32.99(28.73-36.22)	43.79(41.94-44.55)
	Union	45.15(42.95-49.21)	34.63(32.67-35.72)	41.79(40.04-42.58)

Tabel 2. 95% confident intervals (CI) of the AUC for ROC curves corresponding to Fig. 4 and the AP for PR curves corresponding to Fig. 5.



Fig. 6. PR curves of the TS-Ensemble model on external data and the Direct model respectively on Internal data and external. Internal: Direct model on internal data; External: Direct model on external data; ECDEDL-External: TS-Ensemble model on external data.

3.4 Practical performance of ECDEDL

The 95% confident intervals (CI) for the metrics of Precision, Recall, F1 and Accuracy of the TS-Ensemble model on external data and the Direct model respectively on internal data and external data are shown as Table 3. Form Table 3, we can summarize that the TS-Ensemble model performs much better than the Direct model on external data, and the performances of the TS-Ensemble model on external data are close to the performances of the Direct model on internal data. These results indicate that the practical use of the ECDEDL approach for external validation are also quite good, approximating the internal validation.

4. Conclusions and Future Work

Directly predicting pCR to NAC in breast cancer from histological images using deep learning has been shown to be a new trend recently [17]. However, it has been a commonly known problem that the AI models constructed for medical prediction have better performances in internal validation than in external validation, which significantly affects the clinical safety of using AI models [23]. Moreover, a recent study [31] indicates that the poor

performances in external validation is the primary challenge for deep learning applied to breast cancer imaging. Therefore, it is very meaningful and necessary to investigate advanced approaches for the out-of-distribution problem of external validation in predicting pCR to NAC in breast cancer from histological images.

Table 3. 95% confident intervals (CI) for the metrics of Precision, Recall, F1 and Accuracy of the TS-Ensemble model on external data and the Direct model respectively on internal data and external data. Internal: Direct model on internal data; External: Direct model on external data; ECDEDL-External: TS-Ensemble model on external data.

Metrics-Architecture		Internal(CI)	External(CI)	ECDEDL-External(CI)
Precision	MobileNetV2	61.07(46.28-75.87)	40.32(37.59-43.05)	45.98(41.18-50.78)
	ResNet101V2	47.24(43.24-51.25)	32.40(29.18-35.62)	40.87(37.66-44.08)
	NASNetLarge	41.88(40.64-43.12)	29.05(26.60-31.50)	45.14(42.11-48.18)
	Union	50.07(43.70-56.43)	33.92(31.03-36.82)	44.00(41.67-46.33)
Recall	MobileNetV2	30.74(26.41-35.07)	29.43(16.18-42.67)	33.10(20.06-46.15)
	ResNet101V2	45.48(34.13-56.82)	70.80(56.69-84.92)	51.72(42.25-61.20)
	NASNetLarge	50.82(44.02-57.62)	78.62(65.47-91.77)	42.30(34.75-49.85)
	Union	42.34(36.16-48.53)	59.62(46.20-73.03)	42.38(35.59-49.16)
F1	MobileNetV2	40.36(35.34-45.38)	31.55(20.96-42.14)	37.04(28.82-45.25)
	ResNet101V2	45.77(38.03-53.50)	43.40(41.99-44.82)	45.10(41.51-48.70)
	NASNetLarge	45.64(43.29-47.99)	41.92(40.35-43.49)	43.12(39.50-46.74)
	Union	43.92(40.70-47.14)	38.96(34.63-43.29)	41.75(38.27-45.24)
Accuracy	MobileNetV2	77.85(75.10-80.60)	70.44(67.97-72.91)	72.84(70.99-74.70)
	ResNet101V2	74.55(72.55-76.54)	53.37(45.96-60.78)	68.27(65.47-71.07)
	NASNetLarge	70.79(69.35-72.24)	44.46(35.74-53.18)	71.91(70.08-73.74)
	Union	74.40(72.51-76.29)	56.09(49.39-62.79)	71.01(69.44-72.58)

Approaches like data augmentation via color distortion on the RGB channels and the HSI channels [32, 33], mapping from source domain to target domain via adversarial learning [34, 35], and generalizing AI models to unseen domain via feature alignment and domaininvariant feature learning [36–38] have shown promising potentials to provide alternative solutions for external validation of predicting pCR to NAC in breast cancer from histological images. However, these existing methods as well have respective limitations. In addition, two recent works [43, 44] have proposed to employ federated learning [45–47] to improve performance in multicenter deep learning without data sharing, which have shown relevance to the problem of external validation in medical prediction. However, federate leaning is a technique that is more appropriate to solve the problem of data privacy among multiple centers and requires high expenses at the meantime. More importantly, these existing alternative methods have the paradigm that is different from the working paradigm of a medical expert, who will refer to his cognition about the medical data at hand to make decisions. Moreover, the problem of external validation commonly will not come along with a well-trained expert in usual decision making.

In this paper, we propose the experts' cognition-driven ensemble deep learning (ECDEDL) approach for external validation of predicting pCR to NAC from histological images in breast cancer. Since the cognition of both pathology and AI experts have been taken to construct the predictive model, the proposed ECDEDL approach, to some extent, approximates the working paradigm of a human being which will refer to his various working experiences to make decisions. Extensive experimental results indicate: 1) The experts' cognition in ECDEDL is effective with external validation; 2) The overall and practical performances of the ECDEDL approach for external validation are quite effective, numerically approximating the internal validation. These indications have shown the promising potentials of ECDEDL for external validation. In future works, we will investigate the effectiveness of the ECDEDL approach with more other cancer imaging tasks.

Reference

- 1. Lecun Y, Bengio Y, Hinton G (2015) Deep learning. Nature
- 2. Dong S, Wang P, Abbas K (2021) A survey on deep learning and its applications. Comput. Sci. Rev.
- 3. Khan S, Naseer M, Hayat M, et al (2022) Transformers in Vision: A Survey. ACM Comput Surv. https://doi.org/10.1145/3505244
- 4. Han K, Wang Y, Chen H, et al (2023) A Survey on Vision Transformer. IEEE Trans Pattern Anal Mach Intell 45:87–110. https://doi.org/10.1109/TPAMI.2022.3152247
- 5. Aggarwal R, Sounderajah V, Martin G, et al (2021) Diagnostic accuracy of deep learning in medical imaging: a systematic review and meta-analysis. npj Digit. Med.
- 6. Kleppe A, Skrede OJ, De Raedt S, et al (2021) Designing deep learning studies in cancer diagnostics. Nat. Rev. Cancer
- Nam D, Chapiro J, Paradis V, et al (2022) Artificial intelligence in liver diseases: Improving diagnostics, prognostics and response prediction. JHEP Reports 4:100443. https://doi.org/10.1016/j.jhepr.2022.100443
- Kuntz S, Krieghoff-Henning E, Kather JN, et al (2021) Gastrointestinal cancer classification and prognostication from histology using deep learning: Systematic review. Eur J Cancer 155:200–215. https://doi.org/10.1016/j.ejca.2021.07.012
- 9. Ramspek CL, Jager KJ, Dekker FW, et al (2021) External validation of prognostic models: What, why, how, when and where? Clin. Kidney J.
- 10. Steyerberg EW, Harrell FE (2016) Prediction models need appropriate internal, internal– external, and external validation. J Clin Epidemiol 69:245–247. https://doi.org/10.1016/j.jclinepi.2015.04.005
- 11. Steyerberg EW, Bleeker SE, Moll HA, et al (2003) Internal and external validation of predictive models: A simulation study of bias and precision in small samples. J Clin Epidemiol. https://doi.org/10.1016/S0895-4356(03)00047-7
- 12. Consonni V, Ballabio D, Todeschini R (2010) Evaluation of model predictive ability by external validation techniques. J Chemom. https://doi.org/10.1002/cem.1290
- 13. Bleeker SE, Moll HA, Steyerberg EW, et al (2003) External validation is necessary in prediction research: A clinical example. J Clin Epidemiol. https://doi.org/10.1016/S0895-

4356(03)00207-5

- 14. Derks MGM, van de Velde CJH (2018) Neoadjuvant chemotherapy in breast cancer: more than just downsizing. Lancet Oncol.
- 15. Von Minckwitz G, Blohmer JU, Costa SD, et al (2013) Response-guided neoadjuvant chemotherapy for breast cancer. In: Journal of Clinical Oncology
- 16. Cortazar P, Zhang L, Untch M, et al (2014) Pathological complete response and long-term clinical benefit in breast cancer: the CTNeoBC pooled analysis. Lancet 384:164–172. https://doi.org/10.1016/S0140-6736(13)62422-8
- 17. Echle A, Rindtorff NT, Brinker TJ, et al (2021) Deep learning in cancer pathology: a new generation of clinical biomarkers. Br J Cancer 124:686–696. https://doi.org/10.1038/s41416-020-01122-x
- 18. Zhang F, Yao S, Li Z, et al (2020) Predicting treatment response to neoadjuvant chemoradiotherapy in local advanced rectal cancer by biopsy digital pathology image features. Clin Transl Med 10:. https://doi.org/10.1002/ctm2.110
- 19. Kather JN, Krisam J, Charoentong P, et al (2019) Predicting survival from colorectal cancer histology slides using deep learning: A retrospective multicenter study. PLoS Med. https://doi.org/10.1371/journal.pmed.1002730
- 20. Beck AH, Sangoi AR, Leung S, et al (2011) Systematic Analysis of Breast Cancer Morphology Uncovers Stromal Features Associated with Survival. Sci Transl Med 3:. https://doi.org/10.1126/scitranslmed.3002564
- Bhargava HK, Leo P, Elliott R, et al (2020) Computationally derived image signature of stromal morphology is prognostic of prostate cancer recurrence following prostatectomy in African American patients. Clin Cancer Res. https://doi.org/10.1158/1078-0432.CCR-19-2659
- Li B, Li F, Liu Z, et al (2022) Deep learning with biopsy whole slide images for pretreatment prediction of pathological complete response to neoadjuvant chemotherapy in breast cancer
 A multicenter study. The Breast 66:183–190. https://doi.org/10.1016/j.breast.2022.10.004
- 23. Challen R, Denny J, Pitt M, et al (2019) Artificial intelligence, bias and clinical safety. BMJ Qual Saf 28:231–237. https://doi.org/10.1136/bmjqs-2018-008370
- Cortes C, Mohri M, Riley M, Rostamizadeh A (2008) Sample selection bias correction theory.
 In: Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)
- 25. Huang J, Smola AJ, Gretton A, et al (2007) Correcting sample selection bias by unlabeled data. In: Advances in Neural Information Processing Systems
- 26. Teney D, Kafle K, Shrestha R, et al (2020) On the Value of Out-of-Distribution Testing: An Example of Goodhart's Law. Adv Neural Inf Process Syst
- 27. Wang J, Lan C, Liu C, et al (2021) Generalizing to Unseen Domains: A Survey on Domain Generalization. In: IJCAI International Joint Conference on Artificial Intelligence
- 28. Zhou K, Liu Z, Qiao Y, et al (2022) Domain Generalization: A Survey. IEEE Trans Pattern Anal Mach Intell 1–20. https://doi.org/10.1109/TPAMI.2022.3195549
- 29. Patel VM, Gopalan R, Li R, Chellappa R (2015) Visual Domain Adaptation: A survey of recent advances. IEEE Signal Process Mag. https://doi.org/10.1109/MSP.2014.2347059
- 30. Guan H, Liu M (2022) Domain Adaptation for Medical Image Analysis: A Survey. IEEE Trans

Biomed Eng 69:1173-1185. https://doi.org/10.1109/TBME.2021.3117407

- 31. Luo L, Wang X, Lin Y, et al (2023) Deep Learning in Breast Cancer Imaging: A Decade of Progress and Future Directions. https://doi.org/https://doi.org/10.48550/arXiv.2304.06662
- 32. Faryna K, Van Der Laak J, Litjens G (2021) Tailoring automated data augmentation to H&Estained histopathology. Proc Mach Learn Res
- Tellez D, Balkenhol M, Otte-Holler I, et al (2018) Whole-Slide Mitosis Detection in H&E
 Breast Histology Using PHH3 as a Reference to Train Distilled Stain-Invariant Convolutional
 Networks. IEEE Trans Med Imaging 37:2126–2136.
 https://doi.org/10.1109/TMI.2018.2820199
- 34. Mahmood F, Borders D, Chen RJ, et al (2020) Deep Adversarial Training for Multi-Organ Nuclei Segmentation in Histopathology Images. IEEE Trans Med Imaging 39:3257–3267. https://doi.org/10.1109/TMI.2019.2927182
- 35. de Haan K, Zhang Y, Zuckerman JE, et al (2021) Deep learning-based transformation of H&E stained tissues into special stains. Nat Commun. https://doi.org/10.1038/s41467-021-25221-2
- 36. Alirezazadeh P, Hejrati B, Monsef-Esfahani A, Fathi A (2018) Representation learningbased unsupervised domain adaptation for classification of breast cancer histopathology images. Biocybern Biomed Eng 38:671–683. https://doi.org/10.1016/j.bbe.2018.04.008
- 37. Lafarge MW, Pluim JPW, Eppenhof KAJ, et al (2017) Domain-Adversarial Neural Networks to Address the Appearance Variability of Histopathology Images. In: Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics). pp 83–91
- 38. Zhang Y, Chen H, Wei Y, et al (2019) From Whole Slide Imaging to Microscopy: Deep Microscopy Adaptation Network for Histopathology Cancer Image Classification. In: Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics). pp 360–368
- 39. Li H, Wang Y, Wan R, et al (2020) Domain Generalization for Medical Imaging Classification with Linear-Dependency Regularization. Adv Neural Inf Process Syst
- 40. Liu Q, Chen C, Qin J, et al (2021) FEDDG: Federated Domain Generalization On Medical Image Segmentation via Episodic Learning in Continuous Frequency Space. In: Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition
- 41. Ouyang C, Chen C, Li S, et al (2023) Causality-Inspired Single-Source Domain Generalization for Medical Image Segmentation. IEEE Trans Med Imaging 42:1095–1106. https://doi.org/10.1109/TMI.2022.3224067
- 42. Li C, Lin X, Mao Y, et al (2022) Domain generalization on medical imaging classification using episodic training with task augmentation. Comput Biol Med. https://doi.org/10.1016/j.compbiomed.2021.105144
- 43. Sarma K V., Harmon S, Sanford T, et al (2021) Federated learning improves site performance in multicenter deep learning without data sharing. J Am Med Informatics Assoc 28:1259–1264. https://doi.org/10.1093/jamia/ocaa341
- 44. Ogier du Terrail J, Leopold A, Joly C, et al (2023) Federated learning for predicting histological response to neoadjuvant chemotherapy in triple-negative breast cancer. Nat Med. https://doi.org/10.1038/s41591-022-02155-w

- 45. Nguyen DC, Pham Q-V, Pathirana PN, et al (2023) Federated Learning for Smart Healthcare: A Survey. ACM Comput Surv. https://doi.org/10.1145/3501296
- 46. Zhang C, Xie Y, Bai H, et al (2021) A survey on federated learning. Knowledge-Based Syst. https://doi.org/10.1016/j.knosys.2021.106775
- 47. Banabilah S, Aloqaily M, Alsayed E, et al (2022) Federated learning review: Fundamentals, enabling technologies, and future applications. Inf Process Manag 59:103061. https://doi.org/10.1016/j.ipm.2022.103061
- 48. Yang Y, Lv H, Chen N (2023) A Survey on ensemble learning under the era of deep learning. Artif Intell Rev 56:5545–5589. https://doi.org/10.1007/s10462-022-10283-5
- 49. Li F, Yang Y, Wei Y, et al (2022) Predicting neoadjuvant chemotherapy benefit using deep learning from stromal histology in breast cancer. npj Breast Cancer 8:124. https://doi.org/10.1038/s41523-022-00491-1
- 50. Li F, Yang Y, Wei Y, et al (2021) Deep learning-based predictive biomarker of pathological complete response to neoadjuvant chemotherapy from histological images in breast cancer. J Transl Med. https://doi.org/10.1186/s12967-021-03020-z
- Dietterich TG (2000) Ensemble methods in machine learning. In: Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)
- 52. Zhou ZH (2012) Ensemble methods: Foundations and algorithms
- 53. Zhou K, Yang Y, Qiao Y, Xiang T (2021) Domain Adaptive Ensemble Learning. IEEE Trans Image Process 30:8008–8018. https://doi.org/10.1109/TIP.2021.3112012
- 54. Wu G, Gong S (2021) Collaborative Optimization and Aggregation for Decentralized Domain Generalization and Adaptation. In: 2021 IEEE/CVF International Conference on Computer Vision (ICCV). IEEE, pp 6464–6473
- 55. Dubey A, Ramanathan V, Pentland A, Mahajan D (2021) Adaptive Methods for Real-World Domain Generalization. In: 2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). IEEE, pp 14335–14344
- 56. Yang Y, Li F, Wei Y, et al (2021) One-Step Abductive Multi-Target Learning with Diverse Noisy Samples and Its Application to Tumour Segmentation for Breast Cancer
- 57. Khan A, Sohail A, Zahoora U, Qureshi AS (2020) A survey of the recent architectures of deep convolutional neural networks. Artif Intell Rev 53:5455–5516. https://doi.org/10.1007/s10462-020-09825-6
- 58. Sandler M, Howard A, Zhu M, et al (2018) MobileNetV2: Inverted Residuals and Linear Bottlenecks. In: Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition
- 59. He K, Zhang X, Ren S, Sun J (2016) Identity Mappings in Deep Residual Networks. In: Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics). pp 630–645
- Zoph B, Vasudevan V, Shlens J, Le Q V. (2018) Learning Transferable Architectures for Scalable Image Recognition. In: 2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition. IEEE, pp 8697–8710
- 61. Theodoridis S (2015) Stochastic Gradient Descent. In: Machine Learning. Elsevier, pp 161– 231