# A Comprehensive Survey of Forgetting in Deep Learning Beyond Continual Learning

Zhenyi Wang, Enneng Yang, Li Shen, Heng Huang

**Abstract**—Forgetting refers to the loss or deterioration of previously acquired information or knowledge. While the existing surveys on forgetting have primarily focused on continual learning, forgetting is a prevalent phenomenon observed in various other research domains within deep learning. Forgetting manifests in research fields such as generative models due to generator shifts, and federated learning due to heterogeneous data distributions across clients. Addressing forgetting encompasses several challenges, including balancing the retention of old task knowledge with fast learning of new tasks, managing task interference with conflicting goals, and preventing privacy leakage, etc. Moreover, most existing surveys on continual learning implicitly assume that forgetting is always harmful. In contrast, our survey argues that forgetting is a double-edged sword and can be beneficial and desirable in certain cases, such as privacy-preserving scenarios. By exploring forgetting in a broader context, we aim to present a more nuanced understanding of this phenomenon and highlight its potential advantages. Through this comprehensive survey, we aspire to uncover potential solutions by drawing upon ideas and approaches from various fields that have dealt with forgetting. By examining forgetting beyond its conventional boundaries, in future work, we hope to encourage the development of novel strategies for mitigating, harnessing, or even embracing forgetting in real applications. A comprehensive list of papers about forgetting in various research fields is available at https://github.com/EnnengYang/Awesome-Forgetting-in-Deep-Learning.

Index Terms—Beneficial Forgetting, Harmful Forgetting, Memorization, Distribution Shift, Cross-Disciplinary Research

#### **1** INTRODUCTION

Forgetting [1] refers to the phenomenon where previously acquired information or knowledge in a machine learning system degrades over time. In the early days of neural networks, the focus was primarily on training models on static datasets. Forgetting was not a significant concern in these settings since the models were trained and evaluated on fixed datasets. The concept of catastrophic forgetting was first formally introduced by McCloskey and Cohen [1]. They demonstrated that neural networks when trained sequentially on different tasks, tend to forget previously learned tasks when new tasks are learned. This observation highlighted the need for addressing forgetting in sequential learning scenarios. Later, addressing the issue of forgetting was formalized as continual learning (CL). Nowadays, forgetting has garnered significant attention not only within the CL domain but also in the broader machine learning community, which has evolved into a fundamental problem in the field of machine learning as a whole.

Existing surveys on forgetting have primarily focused on CL [2], [3], [4], [5], [6], [7], [8], [9]. However, these surveys tend to concentrate solely on the harmful effects of forgetting and lack a comprehensive discussion on the topic. In contrast, our survey aims to provide a more holistic understanding of forgetting. We highlight its dual nature

Manuscript received July 15, 2023; revised July 15, 2023.

as a double-edged sword, emphasizing both its benefits and harms. Additionally, our survey extends beyond the scope of CL and covers the forgetting issue in various other domains, including foundation models, domain adaptation, meta-learning, test-time adaptation, generative models, reinforcement learning and federated learning. By doing so, we offer a comprehensive examination of forgetting that encompasses a broader range of contexts and applications.

In this survey, we classify forgetting in machine learning into two categories: harmful forgetting and beneficial forgetting, based on the specific application scenarios. Harmful forgetting occurs when we desire the machine learning model to retain previously learned knowledge while adapting to new tasks, domains, or environments. In such scenarios, it is crucial to prevent and mitigate knowledge forgetting. Conversely, there are many cases where beneficial forgetting becomes necessary. For example: (1) Overfitting to the training data hinders generalization. (2) Irrelevant and noisy information impedes the model's ability to effectively learn new tasks and knowledge. (3) Pre-trained model contains private information that could potentially lead to privacy leakage. In these situations, forgetting becomes desirable as it serves several important purposes. Firstly, forgetting can mitigate overfitting, as it allows the model to forget irrelevant details and focus on the most pertinent patterns in the training data. Additionally, by discarding unnecessary information, forgetting facilitates the learning of new knowledge, as the model can make better use of its capacity to acquire and adapt to novel information. Lastly, forgetting helps protect privacy by discarding sensitive user information, ensuring that such data is not retained in the model's memory.

Zhenyi Wang and Heng Huang are with the Department of Computer Science, University of Maryland, College Park, MD 20742, USA. E-mail: wangzhenyineu@gmail.com; heng@umd.edu

<sup>•</sup> Enneng Yang is with Northeastern University, China. E-mail: en-

nengyang@stumail.neu.edu.cn • Li Shen is with JD Explore Academy, China. E-mail: mathshenli@gmail.com.

TABLE 1 Harmful Forgetting: Comparisons among different problem settings.

Problem Setting	Goal	Source of Forgetting		
Continual Learning Foundation Model Domain Adaptation Test-time Adaptation Meta Learning Generative Model Reinforcement Learning Federated Learning	learn non-stationary data distribution without forgetting previous knowledge unsupervised learning on large-scale unlabeled data adapt to target domain while maintaining performance on source domain mitigate the distribution gap between training and testing learn adaptable knowledge to new tasks learn a generator to approximate real data distribution maximize accumulate rewards decentralized training without sharing data	data-distribution shift during training data-distribution shift in pre-training, fine-tuning target domain sequentially shift over time adaptation to the test data distribution during testing incrementally meta-learn new classes / task-distribution shift generator shift / data-distribution shift state, action, reward and state transition dynamics shift model average; non-i.i.d data; data-distribution shift		
TABLE 2           Beneficial Forgetting: Comparisons among different problem settings.				
Prol	olem Setting	Goal		
Mitig	ate Overfitting mitigate memorization of train	ing data through selective forgetting		

1.1 Harmful Forgetting

Debias and Forget Irrelevant Information

Machine Unlearning

Harmful forgetting has been observed not only in CL but also in various other research areas, including foundation model, domain adaptation, meta-learning, test-time adaptation, generative model, reinforcement learning and federated learning. While existing surveys have predominantly focused on forgetting in the context of CL, they often overlook a comprehensive examination of these other related research areas. This survey aims to fill this gap by offering an overview of forgetting in different learning scenarios, encompassing the aforementioned research areas.

Forgetting in these research fields can be attributed to various factors. In the context of continual learning, forgetting occurs due to the shift in data distribution across different tasks. In meta-learning, forgetting is a consequence of the shift in task distribution. In federated learning, forgetting is caused by the heterogeneity of data distribution among different clients, commonly known as client drift. In domain adaptation, forgetting happens because of domain shift. In test-time adaptation, forgetting is a result of adapting to the test data distribution during testing. In generative models, forgetting occurs due to the shift in the generator over time or when learning non-stationary data distribution. In reinforcement learning, forgetting can occur as a result of shifts in state, action, reward, and state transition dynamics over time. These changes in the underlying factors of the environment can lead to the loss or alteration of previously learned knowledge in the reinforcement learning process. In the case of foundation models, forgetting can be attributed to three different reasons: fine-tuning forgetting, incremental streaming data pre-training, and the utilization of foundation models for downstream CL tasks.

To facilitate clarity and comparison of various settings related to forgetting, we present a comprehensive analysis of harmful forgetting in Table 1, highlighting the distinctions among different settings.

#### 1.2 Beneficial Forgetting

While the prevailing belief in most existing works is that forgetting is harmful, we have come to recognize that forgetting is a double-edged sword. There are many instances where it is advantageous to forget certain knowledge within learned neural networks. Intentional forgetting proves beneficial in several scenarios: (1) selective forgetting could help mitigate overfitting; (2) to enhance model generalization or facilitate learning of new tasks/knowledge, it is imperative to eliminate biased or irrelevant information from previously learned knowledge; and (3) machine unlearning, which prevents data privacy leakage.

forget biased information to achieve better performance or remove irrelevant information to learn new tasks

forget some specified training data to protect user privacy

First, overfitting has remained a fundamental challenge in machine learning, as it arises when a model excessively memorizes the training data but struggles to generalize effectively to new, unseen test data. To improve generalization, it is crucial for the model to avoid the mere memorization of training data and instead should prioritize learning the true underlying relationship between the input data and corresponding labels. One important technique to enhance generalization is selective forgetting, which plays a significant role in removing irrelevant or noisy information learned from the training data. By selectively discarding such irrelevant details, the model can focus on the most pertinent patterns and features, leading to improved generalization performance on unseen data.

Second, when the goal is to learn new tasks or knowledge, the previously acquired knowledge may not always be relevant or beneficial for improving future learning on new information. When the model holds on to outdated or unrelated knowledge, it can hinder its ability to effectively learn and generalize from new data. In such situations, it becomes necessary to discard irrelevant information that is still retained in the model's memory. By freeing up capacity within the model, it becomes more receptive and adaptive to acquiring new knowledge. The process of discarding irrelevant information is crucial for preventing interference between old and new knowledge.

Lastly, machine learning model users may request the removal of not only their training data from the database but also any traces within the pre-trained model itself, exercising their Right to Be Forgotten [10]. To address this concern, researchers have explored the concept of machine unlearning, which allows for the intentional forgetting of undesirable private training data. Furthermore, certain privacy attacks exploit the memorization effect of machine learning models to extract private information from pre-trained models. Membership inference attacks [11], for example, can determine whether a data point belongs to the training data associated with a pre-trained model. These privacy attacks can be successful in practice due to the memorization effect of neural networks. In such cases, intentional forgetting of private knowledge becomes beneficial in protecting privacy and preventing information leakage.

To facilitate comparisons, we also provide a comparative analysis in Table 2 for beneficial forgetting, encompassing the above mentioned diverse settings for reference.

#### 1.3 Challenges in Addressing Forgetting

Addressing forgetting faces numerous challenges that vary across different research fields. These challenges include:

Data Availability: Data availability is a significant challenge in various scenarios and greatly complicates the task of addressing forgetting. On one hand, the availability of previous task data may be limited due to storage constraints or data privacy concerns when learning new tasks. This challenge is prevalent in continual learning, meta-learning, domain adaptation, generative model and reinforcement learning, where access to past task data is crucial for mitigating forgetting and leveraging prior knowledge. On the other hand, some scenarios prohibit the use of raw data. For instance, in federated learning, only the parameters of a pretrained model are transmitted to a central server, without sharing the underlying training data.

*Resource Constraints*: Resource-limited environments, such as those with constraints on memory and computation, present challenges in effectively addressing forgetting. In online continual learning and meta-learning, where data or tasks are typically processed only once, these challenges are particularly pronounced. In addition, the learning agent has limited access to past data and experiences, which restricts the opportunities to reinforce previously learned tasks. This limited exposure to past data makes it difficult to retain knowledge and effectively mitigate forgetting. Furthermore, online learning often operates in resource-constrained environments with limited memory or computation capabilities. These constraints pose additional hurdles for addressing forgetting in an online setting.

Adaption to New Environments/Distribution: In various domains such as continual learning, foundation model, reinforcement learning, domain adaptation, test-time adaptation, meta-learning, and generative model, the target environment or data distribution can change over time. It becomes necessary for the learning agent to adapt to these new environments or scenarios. This adaptation can occur either during the training phase or during the testing phase. However, the forgetting challenge arises when the learning agent adapts to new scenarios and environments. The agent tends to lose previously acquired knowledge or performance on earlier tasks due to the shift in data distribution.

Task Interference/Inconsistency: Conflicting and incompatible goals among different tasks can lead to task interference, posing challenges in preventing forgetting. This issue is observed in various contexts, including continual learning and federated learning. In continual learning, sequentially observed tasks may have conflicting goals, making it difficult for the network to balance its performance across multiple tasks. As the network learns new tasks, the interference from these conflicting goals can exacerbate the forgetting problem. Similarly, in federated learning, models trained on different clients can exhibit inconsistencies [12] due to the heterogeneous data distribution across clients. These inconsistencies can lead to task or client interference, further aggravating the forgetting issue. *Privacy-Leakage Prevention*: In certain scenarios, retaining old knowledge can raise privacy concerns as it may inadvertently expose private information. Consequently, it is essential to address these privacy risks and prevent the unintended disclosure of sensitive data. In this context, the objective shifts towards forgetting or erasing the traces of training data rather than memorizing them, thereby safeguarding user privacy. This specific challenge is encountered in the field of machine unlearning [13], which focuses on developing techniques to effectively forget or remove the training data traces from machine learning models.

#### 1.4 Survey Scope, Contributions and Organization

**Survey Scope** Our primary objective is to provide a comprehensive overview of forgetting in the main research directions within the aforementioned fields. These fields have been chosen as representative research directions where forgetting plays a significant role. By covering these areas, we aim to shed light on the existence and impact of forgetting in these research domains.

Our contributions can be summarized into three fold:

- We provide a more systematic survey on CL compared to existing surveys. Our survey includes a more systematic categorization of CL problem settings and methods, offering a more thorough overview of the field.
- In addition to CL, our survey extends its scope to encompass forgetting in other research fields such as foundation model, meta-learning, domain adaptation, test time adaptation, generative model, federated learning, reinforcement learning and machine unlearning. This broader coverage provides a comprehensive understanding of forgetting across various research fields.
- Our survey, in contrast to existing surveys on CL and forgetting, reveals that forgetting can be viewed as a double-edged sword. While it is often seen as a challenge, we highlight that forgetting also has desirable implications in privacy-preserving scenarios.

**Organization** The structure of this paper is as follows. In Sections 2-9, we provide a comprehensive survey on the phenomenon of harmful forgetting in various machine learning domains. These include continual learning, foundation model, domain adaptation, test-time adaptation, meta-learning, generative model, reinforcement learning, and federated learning. Each section explores the occurrence and impact of forgetting within these specific fields. In Section 10, we delve into the concept of beneficial forgetting and its role in enhancing model generalization performance and facilitating machine unlearning. This section highlights the positive aspects of forgetting in specific learning scenarios. In Section 11, we present the current research trends and offer insights into the potential future developments in the field.

#### 2 FORGETTING IN CONTINUAL LEARNING

The goal of continual learning (CL) is to learn on a sequence of tasks  $T_1, T_2, \dots, T_N$  without forgetting the knowledge on previous tasks. It can be formulated with the following

TABLE 3

Content outline in CL. Based on different problem setting categorization criteria, the CL setting can be classified into various scenarios, as presented in the following table:

Section	Problem Setting	Categorization Criterion
Section 2.1	Task-aware and Task-free CL	whether explicit task splits/information are available or not during training
Section 2.2	Online CL	the model processes the data in a single pass or multiple passes
Section 2.3	Semi-supervised, Few-shot and Unsupervised CL	the amount of labeled data used in CL

optimization objective. Suppose when learning task t, the goal is to minimize the risk on all the seen tasks so far, i.e.,

$$\mathcal{L}(\boldsymbol{\theta}_t) = \sum_{t=1}^{N} \mathbb{E}_{(\boldsymbol{x}, y) \sim \mathcal{D}_{\mathcal{T}_t}} \mathcal{L}_{\boldsymbol{\theta}_t}(\boldsymbol{x}, y),$$
(1)

where  $\theta_t$  are the parameters when learning task t, and  $\mathcal{D}_{\mathcal{T}_t}$  represents the training data associated with task t.

The CL problem can be categorized in several different ways. Firstly, according to whether explicit task splits/information are available or not during training, CL can be divided into task-aware and task-free scenarios. Taskaware can be further classified into task/domain/class incremental learning. Addressing forgetting in task-aware CL is relatively straightforward due to the availability of task information. This task information can be leveraged to design and implement various strategies to mitigate forgetting. With knowledge of the specific tasks involved, CL learner can utilize task-specific cues or labels to guide its learning process and manage forgetting. However, addressing forgetting in task-free CL is more challenging. In task-free CL, there are no explicit task splits or task-specific information available to the learning system. As a result, the learning system must autonomously identify and adapt to changes or shifts in the data distribution without any task-specific cues or labels. This requires the development of robust and adaptive mechanisms that can detect and respond to changes in the data distribution, effectively managing forgetting in the absence of explicit task information.

Secondly, depending on whether the model processes the data in a single pass or multiple passes, CL can be categorized as online and offline CL. Offline CL has been extensively studied due to its availability of abundant computing and storage resources. However, online CL presents unique challenges. In online CL, the agent has limited access to past data and experiences, which restricts the opportunities to revisit and reinforce previously learned tasks. This limited exposure to past data makes it challenging to retain knowledge and effectively mitigate forgetting. Furthermore, online learning often operates in resource-constrained environments with limited memory or processing capabilities. These resource limitations pose additional hurdles for addressing forgetting in online CL. Storing and processing large amounts of data becomes more difficult due to the restricted resources, impeding the development and implementation of effective strategies to mitigate forgetting.

Lastly, according to the amount of labeled data used in CL, they could be categorized into *supervised, semisupervised, few-shot, and unsupervised CL*. Supervised CL is generally considered the easiest case since the availability of labeled data provides clear task boundaries and evaluation signals. However, challenges arise in other forms of CL. For semi-supervised CL: the challenge lies in selecting useful knowledge from unlabeled data to mitigate forgetting. Not all unlabeled data may be beneficial for addressing forgetting, making the selection process challenging. In few-shot CL: with only a limited number of labeled data points available for learning, few-shot CL poses additional challenges. The scarcity of labeled data requires the learning agent to effectively utilize the available information to minimize forgetting and adapt to new tasks. In the case of unsupervised CL: unsupervised CL is the most challenging due to the absence of explicit task boundaries. Defining when a new task begins and differentiating it from previous tasks becomes difficult. The lack of task boundaries complicates the identification and management of forgetting, as the learning agent needs to adapt to new data streams without clear task transitions. Furthermore, the absence of labeled data in unsupervised CL results in a scarcity of feedback and evaluation signals for measuring forgetting. This absence of explicit task labels or ground truth information makes it challenging to quantify the extent of forgetting and evaluate the performance of unsupervised CL algorithms.

Below, we present the details of each problem setting and its corresponding related works. To make content organization clear, we provide a Table 3 to summarize the problem setting categorization in the following sections.

#### 2.1 Task-Aware and Task-Free CL

#### 2.1.1 Task-aware CL

Task-aware CL focuses on addressing scenarios where explicit task definitions, such as task IDs or labels, are available during the CL process. The three most common CL scenarios within task-aware settings are task-incremental learning, domain-incremental learning, and class-incremental learning [3]. In domain-incremental learning, tasks sequentially arrive with the same label space but different input data distributions. This means that the tasks share a common set of labels or categories, but the distribution of the input data may vary across tasks. Task-incremental learning refers to the scenario where tasks arrive sequentially, and each task has its own disjoint label space. During testing, the presence of explicit task identification is considered, allowing the model to identify the specific task at hand. Classincremental learning is similar to task-incremental learning but without explicit task identification during testing. Instead, the model needs to incrementally learn new classes without forgetting previously learned classes

Problem Setup: We consider the standard CL problem of learning a sequence of N tasks denoted as  $\mathcal{D}^{tr} = \{\mathcal{D}_1^{tr}, \mathcal{D}_2^{tr}, \cdots, \mathcal{D}_N^{tr}\}$ . The training data of k-th task  $\mathcal{D}_k^{tr}$ consists of a set of triplets  $\{(\boldsymbol{x}_k^k, \boldsymbol{y}_k^k, \mathcal{T}_k)_{i=1}^{n_k}\}$ , where  $\boldsymbol{x}_i^k$  is the *i*-th task data example,  $\boldsymbol{y}_i^k$  is the data label associated with  $\boldsymbol{x}_i^k$ , and  $\mathcal{T}_k$  is the task identifier. The goal is to learn a neural network with parameters  $\boldsymbol{\theta}$ , i.e.,  $f_{\boldsymbol{\theta}}$ , on the training task sequence  $\mathcal{D}^{tr}$  so that it performs well on the test set of all the learned tasks  $\mathcal{D}^{te} = \{\mathcal{D}_1^{te}, \mathcal{D}_2^{te}, \cdots, \mathcal{D}_N^{te}\}$  without forgetting the knowledge of previous tasks.

Existing methods on task-aware CL have explored five main branches: memory-based, architecture-based, regularization-based, subspace-based, and Bayesian-based methods. An overall framework depicting these branches is provided in Figure 1. For a more comprehensive understanding of the methods within each category, please refer to Appendix A.1, where we provide detailed descriptions. Below, we provide a brief overview of each class method.

2.1.1.1 Memory-based Method: Memory-based method keeps a *memory buffer* that stores the data examples from previous tasks and replays those examples during learning new tasks. It can be further categorized into: raw memory replay; memory sample selection; generative replay; and compressed memory replay. Next, we discuss each direction in detail. (1) Raw Sample Replay: These methods randomly save a small amount of raw data from previous tasks and train the model together with the new task data. When the new task updates the model, the old task data is used as a constraint [14], [15] or directly mixed with the new data to form a batch [16] to update the model, thereby alleviating forgetting. (2) Memory Sample Selection: Randomly selecting samples for replay ignores the amount of information in each sample, which can lead to suboptimal performance [17], [18]. Therefore, *heuristic selection* selects samples to be stored according to certain rules. For example, select the representative sample closest to the cluster center [19], the samples with higher diversity [20], [21], or the difficult sample closer to the decision boundary [22], [23]. (3) Generative Replay: When privacy concerns restrict the storage of raw memory data, generative replay provides an alternative approach in CL to replay previous task data. The main concept behind generative replay is to train a generative model capable of capturing and remembering the data distribution from previous tasks. The representative works in this line involve using different generative models, including GAN-based [24], [25], AutoEncoder-based [26], Diffusion-based [27], and Model-inversion [28]. (4) Compressed Memory Replay: In scenarios with strict storage constraints on edge devices, memory efficiency becomes a critical consideration. Different strategies have been proposed to improve memory efficiency in CL learning. For example, storing feature representations [29], [30] or low-fidelity images [31], [32] instead of original images, or learning a set of condensed images [33], [34] using dataset distillation [35].

2.1.1.2 Architecture-based Method: Architecturebased methods in CL [36], [37], [38] involve updating the network architecture during the learning process to retain previously acquired knowledge. These methods aim to adapt the model's architecture to acquire new tasks while preserving the knowledge from previous tasks. Based on whether the model parameters expand with the number of tasks, architecture-based methods can be categorized into two types: fixed-capacity and capacity-increasing methods. (1) *Fixed-Capacity*: In these methods, the amount of CL model's parameters does not increase with the number of tasks, and each task selects a sub-network from the CL model to achieve knowledge transfer and reduce the forgetting caused by sub-network updates. Common subnetwork selection techniques include masking [39], [40], [41], and pruning [42], [43], [44]. (2) *Capacity-Increasing*: As the number of tasks increases, fixed-capacity CL models may face limitations in accommodating new tasks. To overcome this challenge, dynamic capacity methods are proposed [36], [38], [45], [46]. These methods ensure that old tasks are not forgotten and adapt to new tasks by introducing new task-specific parameters for each new task, while freezing parameters related to old tasks.

2.1.1.3 Regularization-based Method: These methods in CL involve the addition of regularization loss terms to the training objective to prevent forgetting previously learned knowledge [47], [48], [49]. It can be further divided into two subcategories: penalizing important parameter updates and knowledge distillation using a previous model as a teacher. (1) Penalize Parameter Updates: These methods use the Fisher information matrix [47], the cumulative update amount of parameters [50], etc. as a measure of the importance of old task parameters. On the one hand, when new tasks update important parameters, a large penalty is imposed in order to keep the knowledge of old tasks from being forgotten. On the other hand, imposing a small penalty on unimportant parameter updates can learn new task's knowledge [22], [48], [51]. (2) Knowledge-Distillation-Based: Inspired by knowledge distillation [52], several methods in CL incorporate a distillation loss between the network of the previous task (referred to as the teacher) and the network of the current task (referred to as the student) to mitigate forgetting [53], [54], [55]. It should be mentioned that the ideal scenario would involve using raw data from old tasks to extract the knowledge of the teacher model and refine it into a student model. However, accessing raw data of old tasks is often not feasible due to data privacy concerns. Therefore, existing methods utilize proxy data, such as new task data [53] or large-scale unlabeled data [56], as a substitute for distillation.

2.1.1.4 **Subspace-based Method**: Subspace-based methods in CL aim to address the issue of interference between multiple tasks by conducting learning in separate and disjoint subspaces, thus reducing old task forgetting. Subspace-based methods can be categorized into two types based on how the subspaces are constructed: orthogonal gradient subspace and orthogonal feature subspace methods. (1) *Orthogonal Gradient Subspace*: These methods require that the parameter update direction of the new task is orthogonal to the gradient subspace of the old tasks [57], [58], [59], ensuring minimal interference between tasks. (2) *Orthogonal Feature Subspace*: Similarly, these require that the parameter update direction of the new task is orthogonal to the subspace spanned by the input (feature) of the old tasks [60], [61], [62], [63].

2.1.1.5 **Bayesian Method**: These Bayesian approaches offer effective strategies to mitigate forgetting by incorporating uncertainty estimation and regularization techniques, thereby enhancing the adaptability of the learning process. Bayesian methods can be classified into three categories: methods that constrain the update of weight parameter distributions, methods that constrain the update in function space, and methods that dynamically grow the CL model architecture in an adaptive and Bayesian manner. Specifically, (1) *Weight Space Regularization:* These methods model the parameter update uncertainty and enforce the



Fig. 1. Categorization of existing continual learning approach.

model parameter (weight space) distribution when learning the new task is close to that of all the previously learned tasks, including [64], [65], [66], [67], [68], [69]. (2) Function Space Regularization: Different from weight space regularization which constrains the weight update, the function space regularization regulates the CL function update in the function space. They achieve this goal by enforcing the posterior distribution over the function space [70], constraining neural network predictions [71], modeling the cross-task covariances [72] or sequential function-space variational inference [73]. (3) Bayesian Architecture Expansion: Bayesian architecture growing methods employ a probabilistic and Bayesian approach to dynamically expand the CL model. By leveraging Bayesian principles, these methods enable the CL model to incrementally grow and adapt to new tasks or data while preserving previously learned knowledge. This probabilistic framework facilitates the flexible and principled expansion of the model's architecture, allowing it to accommodate increasing complexity and variability in the learning process, including [74], [75].

#### 2.1.2 Task-free CL

Task-free CL refers to a specific scenario that the learning system does not have access to any explicit task information. Unlike the task-aware CL setting, where a sequence of tasks is defined, task-free CL aims to perform adaptation without explicit task boundaries or labels. The system needs to adapt and generalize its knowledge over time, continually updating its model or representation to accommodate new information while retaining previously learned knowledge. The absence of explicit task information in task-free CL poses significantly more challenges, as the learning system must autonomously identify and adapt to changes or shifts in the data distribution without any task-specific cues or labels. Existing approaches for task-free CL can be categorized into two classes: memory-based methods and network expansion-based methods.

2.1.2.1 *Memory-based method*: Memory-based methods [15], [20], [23], [76] involve storing a small subset of previous data and replaying them alongside new minibatch data. MIR [23] selects and replays samples that are most prone to interference. This selective replay aims to prioritize samples that are most relevant for retaining previously learned knowledge. Building upon MIR, GEN-MIR [23] incorporates generative models to synthesize memory examples during replay. GSS [20] focuses on storing diverse examples. GMED [77], proposes a method for editing the memory examples to promote forgetting and discourage memorization. While GMED focuses on editing memory examples, Wang et al. [78] propose a Distributionally Robust Optimization framework that considers population- and distribution-level evolution to address memory overfitting.

2.1.2.2 Expansion-based method: In the context of architecture expansion-based methods, several approaches have been proposed to address the forgetting issue and facilitate continual adaptation. CN-DPM [79] introduces a method that expands the network structure based on the Dirichlet process mixture model. This approach allows for the automatic expansion of the network to accommodate new data distributions or concepts while preserving previously learned knowledge. VariGrow [80] proposes a variational architecture growing method based on Bayesian novelty to mitigate forgetting. This method leverages Bayesian techniques to identify novel information and dynamically expand the network architecture to accommodate new knowledge. ODDL [81] proposes a dynamical architecture expansion method based on estimating the discrepancy between the probabilistic representation of the memory buffer data and the accumulated knowledge.

#### 2.2 Online CL

#### 2.2.1 Approaches for Online CL

The online CL setting presents additional challenges compared to offline CL. In online CL, the learner is only allowed to process the data for each task once [5]. Existing works addressing forgetting in online CL are mainly based on rehearsal replay [20], [23], [82], [83]. MIR [23] suggests replaying the samples that exhibit the maximum increase in loss. OCS [84] proposes to select samples with high affinity for old tasks. DVC [85] introduces a technique that involves selecting samples whose gradients are most interfered with new incoming samples to store in memory buffer. ASER [82] introduces an adversarial Shapley value scoring method that assigns scores to memory data samples. These scores are used to evaluate the contribution of memory samples to the performance of forgetting. La-MAML [86] utilizes a meta-learning algorithm to tackle online CL by leveraging a small episodic memory. GPS [87] formulates the memory construction problem in experience replay as a combinatorial optimization problem, and simulates the forgetting mode of the current task by creating future pseudotasks. However, in cases where memory constraints are stringent, replay-based online CL approaches have limited effectiveness. Some studies have proposed the utilization of regularization-based strategies to prevent forgetting [88], [89].

#### 2.2.2 Imbalanced Class Issue in Online CL

The presence of imbalanced data streams in online CL has drawn significant attention, primarily due to its prevalence in real-world application scenarios [90], [91], [92], [93]. Addressing the issue of class imbalance can be approached through two main strategies: (1) learning a model that effectively balances the learning of both old and new classes

during the training phase, or (2) employing post-processing techniques to calibrate the biases inherent in the model.

2.2.2.1 Balance Learning Between New and Old Classes: Balancing in the training phase involves heuristically selecting a balanced memory to tune the model [90], [91], [94], [95]. Chrysakis et al. [94] propose class-balancing reservoir sampling (CBRS) to tackle this issue. PRS [95] suggests a partitioning reservoir sampling strategy to address this issue. Kim et al. [96] introduces a stochastic informationtheoretic reservoir sampler to select memory points from the imbalanced data stream. E2E [90] proposes to alleviate the imbalance problem by adopting a balanced fine-tuning strategy at the end of each incremental stage. GDumb [91] found that the downsampling strategy can well solve the problem of imbalance between old and new classes.

2.2.2. Post-Processing Calibration Techniques: Postprocessing calibration methods perform bias calibration on the classifier of the model during the inference phase [92], [97], [98]. BiC [92] introduces a two-stage training where they perform the main training in the first stage, followed by a linear transformation to mitigate bias in the second stage. WA [98] reduces the imbalance between old and new classes by aligning the logits output from the model on the old and new classes. OBC [99] provides both theoretical and empirical explanations of how replay can introduce a bias towards the most recently observed data stream. They address this issue by modifying the model's output layer, aiming to mitigate the effects of this online bias.

#### 2.3 Semi-supervised, Few-shot and Unsupervised CL

#### 2.3.1 Semi-supervised CL

Semi-supervised CL is an extension of traditional CL that allows each task to incorporate unlabeled data as well.

Existing works on semi-supervised CL, mainly include generative replay [100], [101] and distillation [56], [102] to avoid forgetting. Specifically, ORDisCo [101] maintains a relatively constant-sized network, and it simultaneously trains a classifier and a conditional GAN, and learns the classifier by replaying data sampled from the GAN in an online fashion. SDSL [100] is also based on the generation-replay framework. GD [56] and DistillMatch [102] are distillationbased approaches. DistillMatch performs knowledge distillation by assigning pseudo-labels and data augmentation to the unlabeled data to reduce forgetting.

#### 2.3.2 Few-shot CL

Few-shot CL refers to the scenario where a model needs to learn new tasks with only a limited number of labeled examples per task while retaining knowledge from previously encountered tasks. The challenge lies in effectively leveraging the limited labeled data and previously learned knowledge to adapt to new tasks while avoiding forgetting.

Compared to traditional CL, few-shot CL faces the challenge of overfitting due to the limited number of examples available per task [103], [104]. To tackle the forgetting problem in few-shot CL, existing approaches employ various techniques, including metric learning, meta-learning, and parameter regularization. Due to limited pages, we provide details of these methods in Appendix. A.2. Below, we briefly explain each method: (1) *Metric Learning-Based:*  These methods perform classification by class prototypes. To avoid forgetting, the prototype of the new class should be separable from the old class [105], [106], [107], and the prototype of the old class should not change drastically during the adjustment process of the new class [103], [107]. (2) Meta-Learning-Based: These methods simulate the inference phase during training so that CL models can quickly adapt to unseen new classes to solve few-shot CL. For example, LIMIT [108] and MetaFSCIL [109] split the base task into multiple 'fake'-incremental tasks, so that the model has the learning ability of few-shot CL tasks. By reducing the loss associated with the meta-objective, they minimize forgetting of the old tasks. (3) Parameter Regularization-Based: These methods employ various strategies to address the forgetting problem by penalizing parameter updates that are important for old tasks [110], [111].

#### 2.3.3 Unsupervised CL

Unsupervised CL [112], [113] is a rapidly growing research area that emphasizes learning from unlabeled data alone. Unlike traditional supervised CL relying on labeled data, unsupervised CL explores techniques that enable learning and adaptation using only unlabeled data.

Existing unsupervised CL methods mainly rely on *representation-based contrastive learning* techniques [112], [113], [114], [115]. CURL [112] is the first offline continual unsupervised representation learning framework with unknown task labels and boundaries. Co2l [114] finds that self-supervised loss is generally more robust to forgetting than cross-entropy loss in CL. LUMP [113] observes that unsupervised CL models have a flatter loss landscape than supervised CL models, and additionally, it performs Mixup [116] between old task samples and new task samples to reduce forgetting. Prob [115] revisits the phenomenon of representational forgetting in both supervised and unsupervised CL settings, and shows that using observed accuracy to measure forgetting is a misleading metric.

#### 2.4 Theoretical Analysis

The *theoretical* analysis of CL is quite a few. Pentina et al. [117] provide a generalization bound in the PAC-Bayesian framework for CL. Karakida et al. [118] conduct a theoretical analysis of the generalization performance within a solvable case of CL. They utilized a statistical mechanical analysis of kernel ridge-less regression to provide insights into the understanding of the generalization capabilities in CL scenarios. Kim et al. [119] study class-incremental learning and provides a theoretical justification for decomposing the problem into task-id prediction and within-task prediction. Evron et al. [120] theoretically study the CL on a sequence of separable linear classification tasks with binary classes. Peng et al. [121] propose Ideal Continual Learner (ICL), which unifies multiple existing well-established CL solutions, and gives the generalization boundary of ICL.

#### **3** FORGETTING IN FOUNDATION MODEL

The forgetting in foundation models manifests in several distinct directions. Firstly, when fine-tuning a foundation model, there is a tendency to forget the pre-trained knowl-edge, resulting in sub-optimal performance on downstream

tasks. This implies that the model may not effectively leverage the general knowledge it acquired during pre-training, leading to a decrease in overall performance.

Secondly, foundation models are typically trained on a dataset for a single pass [122], [123], resulting in two types of forgetting. Firstly, in the case of streaming data, the challenge lies in retaining previous pre-trained knowledge as unlabeled data arrives sequentially [124]. This type of forgetting is undesirable as it can hinder the model's ability to leverage prior knowledge effectively. Conversely, the earlier examples encountered during pre-training may be overwritten or forgotten more quickly than the later examples. While this characteristic of forgetting can be seen as a disadvantage in some contexts, it can be advantageous in privacy-preserving scenarios. By discarding or attenuating sensitive information from the initial training examples, the model can enhance privacy protection. Therefore, foundation models exhibit both challenges and potential benefits associated with forgetting.

Lastly, foundation models have the ability to extract features with a strong feature extractor, which makes foundation models increasingly popular for CL approaches, aiming to achieve excellent performance across multiple tasks without forgetting previously learned knowledge. By leveraging the powerful feature extraction capabilities of foundation models, researchers have explored new avenues for advancing CL techniques.

Below, we will delve into each research direction in more detail, examining the challenges and opportunities they present in the context of foundation models.

#### 3.1 Forgetting in Fine-Tuning Foundation Models

Fine-tuning the foundation model could achieve impressive performance on downstream tasks. However, fine-tuning a foundation model can result in the forgetting of pre-trained knowledge, which may lead to sub-optimal performance on downstream tasks. Forgetting occurs when the target model deviates significantly from the pre-trained model during the fine-tuning process [125]. This deviation increases the likelihood of overfitting to a small fine-tuning set [126], which can contribute to forgetting.

There are several simple and effective strategies to mitigate forgetting during the fine-tuning process. These include techniques such as learning rate decreasing [126], weight decay [127], [128], and Mixout regularization [125]. Furthermore, Fatemi et al. [129] find that in the study of mitigating the gender bias of the pre-trained language model, the pre-trained knowledge will be forgotten when the small neutral data is fine-tuned, which will hurt the downstream task performance. Dong et al. [130] observe that adversarial fine-tuning of pre-trained language models is prone to severe catastrophic forgetting, causing the loss of previously captured general and robust linguistic features. To address these issues, they propose a Robust Informative Fine-Tuning method from an information-theoretical perspective. In addition, an approach called Recall and Learn, proposed in Chen et al. [131], addresses the forgetting issue by utilizing Pretraining Simulation and Objective Shifting. This approach enables multi-task fine-tuning without relying on the data from the pretraining tasks.

#### 3.2 Forgetting in One-Epoch Pre-training

#### 3.2.1 Forgetting Previous Knowledge in Pre-training

Foundation model is typically trained using self-supervised learning, and self-supervised learning with streaming data has become a significant research area due to the storage and time costs associated with storing and training on large amounts of unlabeled data. In this context, Hu et al. [132] propose a sequential training method for self-supervised learning, demonstrating that self-supervised learning exhibits less forgetting compared to its supervised learning counterpart. Similarly, Purushwalkam et al. [133] perform self-supervised learning on a continuous non-iid data stream and introduce a minimum redundancy (MinRed) buffer approach to mitigate catastrophic forgetting. Furthermore, Lin et al. [134] develop a rehearsal-based framework that incorporates their proposed sampling strategies and self-supervised knowledge distillation to address the forgetting problem in streaming self-supervised learning.

#### 3.2.2 Beneficial Forgetting in Pre-training

The memorization and forgetting of large foundation model have attracted much attention, some emerging work [124] studies the connection between the memorization of training data and different types of forgetting. Foundation models display two seemingly conflicting occurrences: the memorization of training data and different types of forgetting. Memorization refers to models excessively fitting to specific training examples, making them vulnerable to privacy leakage, e.g., inferring whether a data point belong to the training data associated with the pre-trained model. Some researches have shown that this phenomenon of leakage personally identifiable information in language model [135], [136], which is undesible in practice. On the other hand, forgetting involves the gradual loss of information about examples encountered early in training. The study in [124] establishes a connection between these phenomena and introduce a method to quantify the degree to which models "forget" specific details of training examples. This leads to reduced susceptibility to privacy attacks on examples that have not been recently encountered. Different from CL, which measures the forgetting as apposed to retain the knowledge from previously learned knowledge. In contrast, the study conducted by [124] examines a task-specific model and investigates the degree of forgetting exhibited towards specific training examples.

#### 3.3 CL in Foundation Model

Recently, researchers have explored the use of foundation models to tackle continual learning (CL) problems. CL based on foundation or pre-trained models has shown promise, particularly in the domain of natural language processing (NLP). Studies such as [137], [138] delve into the effective application of pre-trained models in CL for NLP tasks. Furthermore, [139] demonstrates the capability of fine-tuned pre-trained language models to act as continual learners.

Given the remarkable success of the Transformer model [140] in computer vision tasks [141], many studies in the field have started exploring the application of CL using foundational model. Ostapenko et al. [142] study the efficacy

of pre-trained vision models as a foundation for downstream CL tasks. Mehta et al. [143] explain why pretrained models are more helpful in mitigating forgetting from a loss landscape perspective. They find that pretrained models drive weights to converge to wider minima, which usually indicates better generalization. Ramasesh et al. [144] observe that pretrained models are more resistant to forgetting than randomly initialized models, and this capability increases with the size of pretrained model and data.

In addition to the aforementioned studies, many researchers have explored the fine-tuning of pre-trained models to enhance their adaptation to downstream tasks in CL. These efforts primarily revolve around parameterefficient fine-tuning techniques, such as Adapters [145], [146] and Prompts [147], [148], [149], [150]. (1) Adapterbased methods: ADAM [145] demonstrates that utilizing a frozen base model to generate generalizable embeddings and setting classifier weights as prototype features can outperform state-of-the-art CL methods. Additionally, performing model adaptation on downstream tasks further enhances performance. ADA [146], on the other hand, adopts a different approach by learning a single adapter for each new task instead of adjusting the entire CL model. The new adapter is then fused with the existing adapter to maintain a fixed capacity. (2) Prompts-based methods: L2P [147] introduces a dynamic instance-level learning approach to determine the matched expert-prompt for each new task, while freezing the pre-trained model. DualPrompt [148] builds upon L2P by appending complementary prompts (shared general-prompt and matched expert-prompt) on a pre-trained backbone. S-Prompt [149] focuses on exemplarfree domain-incremental learning. It independently learns prompts for each domain and stores them in a pool to prevent forgetting. Progressive Prompts [150] also learns a prompt for each new task, but it freezes the prompts of old tasks and incorporates them into the new task to encourage the transfer of knowledge in a forward manner.

#### 4 FORGETTING IN DOMAIN ADAPTATION

The objective of domain adaptation is to transfer knowledge from a source domain to a target domain. A domain represents the joint distribution of the input space  $\mathcal{X}$  and the output space  $\mathcal{Y}$ . Specifically, the source domain is defined as  $\mathcal{P}^{S}(\boldsymbol{x}, y)$ , where  $\boldsymbol{x}$  belongs to the input space  $\mathcal{X}^{S}$  and ybelongs to the output space  $\mathcal{Y}^{S}$ . Similarly, the target domain is defined as  $\mathcal{P}^{T}(\boldsymbol{x}, y)$ , where  $\boldsymbol{x}$  belongs to the input space  $\mathcal{X}^{T}$  and y belongs to the output space  $\mathcal{Y}^{T}$ .

In the context of continual domain adaptation (CDA) [151], the focus is primarily on the covariate shift setting. Covariate shift refers to a situation where the distribution of input data,  $\mathcal{X}$ , differs between the source and target domains, while the conditional distribution of the output,  $\mathcal{Y}$ , remains the same. This setting assumes that the relationship between inputs and outputs remains consistent across domains, but the distributions of the input data vary. This is formally defined as the following:

$$\mathcal{P}^{S}(X = \boldsymbol{x}) \neq \mathcal{P}^{T}(X = \boldsymbol{x}), \mathcal{P}^{S}(y|X = \boldsymbol{x}) = \mathcal{P}^{T}(y|X = \boldsymbol{x}).$$
(2)

CDA and traditional CL have distinct characteristics and goals. On the one hand, CDA differs from traditional CL in

terms of the availability of source domain data for transferring knowledge across the target domain sequence. In CDA, the source domain data is accessible, and the objective is to adapt the model from the source domain to the target domain, leveraging the available source domain data. However, the target domain may only provide unlabeled data, requiring the model to adapt to the new domain without explicit supervision. On the other hand, traditional CL aims to learn and adapt the model to a sequence of tasks without accessing previous task-specific labeled data. Labeled data is typically provided for each task in traditional CL.

Problem Setup: Suppose we have a pre-trained model  $f_{\theta}$  that has been trained on a set of source domain data  $\mathcal{P}^{S}(x, y)$ , where x belongs to the source domain input space  $\mathcal{X}^{S}$  and y belongs to the source domain label space  $\mathcal{Y}^{S}$ . Additionally, we have a sequence of evolving target distributions  $\mathcal{P}_{t}^{T}(x, y)$ , where x belongs to the input space  $\mathcal{X}_{t}^{T}$  of the target domain t. y belongs to the label space  $\mathcal{Y}_{t}^{T}$  of the target domain t. t represents the domain index ranging from 1 to N. The objective of CDA, as proposed in [151], is to train  $f_{\theta}$  in such a way that it performs well on all the domains  $\mathcal{P}_{t}^{T}(x, y)$  in the evolving target domain sequence, defined as follows:

$$\min_{\boldsymbol{\theta}} \mathbb{E}_{t \in [1,...,N]} \mathbb{E}_{\boldsymbol{x}^T \sim P_t^T, \boldsymbol{x}^S \sim P^S} \mathcal{L}\left(f_{\boldsymbol{\theta}}(\boldsymbol{x}^T), f_{\boldsymbol{\theta}}(\boldsymbol{x}^S)\right).$$
(3)

When dealing with new target domains, it is important to note that their data distributions differ from that of the source domain. As a result, adapting the model to these new domains can inadvertently result in forgetting the knowledge acquired from the previous domains. To mitigate this issue, various approaches have been developed to tackle the problem of catastrophic forgetting in domain adaptation.

When the source domain data is available, most of the works avoid forgetting by replaying the source domain data [152], [153], [154], and a few works are based on regularization [155], or meta-learning [156]. First, Replaybased methods are effective in preventing forgetting by incorporating data or knowledge from previous domains. One approach, CUA [152], addresses the issue by randomly selecting samples from previous domains and storing them in a memory buffer. Another method called UCL-GV [157] utilizes a First-In, First-Out (FIFO) buffer to replay episodic memory. AuCID [153] tackles the problem of continual unsupervised domain adaptation by consolidating the learned internal distribution. It achieves this by storing a fixed number of confident samples for each class per domain, which are later replayed during the adaptation process. Then, GRCL [155] utilizes the gradient direction of samples from the previous domain as a *regularization* term. This constraint ensures that the model can be updated with new target domain data without negatively affecting the performance of the previous domain. Finally, Meta-DR [156] proposes a meta-learning and domain randomization approach to mitigate forgetting and retain knowledge from previous domains during CDA.

Recently, few works have focused on *source-free* approaches [158] that aim to protect the privacy of the source domain data, which is often inaccessible in many scenarios [159], [160]. CoSDA [159] introduces a knowledge distillation method that employs a dual-speed teacher-student structure. The slow-updating teacher preserves the

long-term knowledge of previous domains, while the fastupdating student quickly adapts to the target domain. C-SUDA [160] achieves continual adaptation by synthesizing source-style images to avoid forgetting the source domain.

#### 5 FORGETTING IN TEST TIME ADAPTATION

Test time adaptation (TTA) refers to the process of adapting a pre-trained model on-the-fly to unlabeled test data during inference or testing [161], [162], [163], [164], [165]. Unlike domain adaptation, test time adaptation occurs during the deployment phase rather than during the training phase. This approach allows the model to adapt to specific instances or conditions encountered at test time to improve the model generalization performance. TTA can involve updating certain parameters or features of the model based on additional information or feedback obtained during inference.

In traditional machine learning scenarios, during testing, it is typically assumed that the test data  $\mathcal{D}_{test}$  follows the same distribution as the training data. However, in real-world applications, it is common for the test data distribution to deviate from the training data distribution. To address the distribution shift between the training and testing phases, TTA is employed. TTA involves adapting the pre-trained model on the unlabeled testing data x using an unsupervised adaptation loss function. This adaptation aims to minimize the loss function  $\mathcal{L}(\boldsymbol{x}, \boldsymbol{\theta})$  with respect to the parameters  $\theta$ . It is important to note that x is sampled from the testing dataset,  $\mathcal{D}_{test}$ . Subsequently, the adapted model utilizes the updated parameters to make predictions for the test input *x*. This allows the model to account for the distribution shift between the training and testing phases, and hopefully improve its performance on the test data.

*Existing Works:* The Tent method [161] presents a testtime entropy minimization approach to enhance model generalization. This method focuses on minimizing the entropy of model predictions on test data, thereby improving the model's ability to generalize to unseen examples. Another approach, known as MECTA [166], aims to improve the memory efficiency of test time adaptation. MECTA proposes techniques to adapt the model during testing while optimizing memory usage, ensuring efficient and effective adaptation to the test data distribution. In a different vein, MEMO [167] proposes a method that applies various data augmentations to a test data point. Subsequently, all model parameters are adapted by minimizing the entropy of the model's output distribution across the augmented samples.

When a pre-trained model is adapted to new unlabeled test data, the model shifts to the new data, potentially causing it to forget crucial information previously learned from the source domain data. This phenomenon can result in a substantial loss of knowledge and adversely affect the model's overall performance [162], [168]. To address this issue, existing approaches primarily adopt two strategies.

Firstly, one intuitive approach to prevent the model from forgetting the knowledge acquired from the source domain is to employ a two-step process. Initially, the model trained on the source data is frozen. Subsequently, new learnable parameters are introduced to adapt the model to the testtime data [169], [170]. For instance, VDP [169] prevents

Secondly, another common approach to prevent forgetting in TTA is by constraining the update of important parameters, thereby avoiding the introduction of new parameters. Tent [161] specifically focuses on preserving the previous knowledge by updating only the BatchNorm layer in the network. On the other hand, CoTTA [168] proposes a different strategy. In each iteration of the adaptation process, CoTTA randomly restores the weights of certain neurons to the weights that were originally trained in the source domain. This restoration mechanism helps in retaining the knowledge acquired from the source domain, preventing it from being forgotten during the adaptation to the target domain. Other approaches in TTA employ techniques similar to regularization-based approaches commonly used in traditional CL. These methods penalize the updating of parameters that are deemed important to the source data during the adaptation process [162], [171], [172]. For instance, EATA [162] calculates the importance using the Fisher information matrix and utilizes this measure as a penalty when updating parameters during adaptation.

#### 6 FORGETTING IN META-LEARNING

Meta-learning, also known as learning to learn, focuses on developing algorithms and models that can learn from previous learning experiences to improve their ability to learn new tasks or adapt to new domains more efficiently and effectively. In meta-learning, the goal is to enable a learning system, often referred to as the meta-learner or the meta-model, to acquire general knowledge or "metaknowledge" from a set of related learning tasks or domains. This meta-knowledge is then leveraged to facilitate faster learning, better generalization, and improved adaptation to new, unseen tasks or domains.

Formally, let's consider a distribution of tasks, denoted as  $P(\mathcal{T})$ . For a specific task  $\mathcal{T}_t$ , which consists of a training dataset  $\mathcal{D}_{\text{train}}$  and a validation dataset  $\mathcal{D}_{\text{val}}$ , sampled from the task distribution  $P(\mathcal{T})$ . The loss function for task  $\mathcal{T}_t$  with meta-parameters  $\boldsymbol{\theta}$  is defined as:

$$\mathcal{L}(\mathcal{T}_t) = \log P(\mathcal{D}_{\text{val}} | \mathcal{D}_{\text{train}}; \boldsymbol{\theta}).$$
(4)

The objective of meta-learning is to optimize the meta loss function, given by:

$$\min_{\mathbf{C}} \mathbb{E}_{\mathcal{T}_t \sim P(\mathcal{T})} \mathcal{L}(\mathcal{T}_t).$$
(5)

In other words, the aim is to find the optimal metaparameters  $\theta$  that minimize the expected loss across tasks, where tasks are sampled from the task distribution  $P(\mathcal{T})$ .

However, forgetting can still occur in the context of meta-learning, and it can be classified into two distinct research directions. The first research direction focuses on Incremental Few-Shot Learning (IFSL), where the objective is to meta-learn new classes in addition to the pre-trained base classes. In this scenario, forgetting arises from the loss of information related to the pre-trained base classes. The challenge lies in retaining the knowledge of both the base classes and the newly introduced classes during the learning process. The second research direction deals with Continual Meta-Learning, where the agent encounters nonstationary task distributions over time while learning new tasks. Unlike IFSL, the goal here is not to remember the specific base classes. Instead, the objective is to retain the meta-knowledge acquired from previous task distributions. We will present the details of each direction in the following.

#### 6.1 Incremental Few-Shot Learning

Incremental few-shot learning (IFSL) [173], [174] focuses on the challenge of learning new categories with limited labeled data while retaining knowledge about previously learned categories. In this scenario, a standard classification network has previously undergone training to recognize a predefined set of base classes. After that, the focus is on incorporating additional novel classes, each accompanied by only a small number of labeled examples. Subsequently, the model is tested on its classification performance, considering both the base and novel classes.

Existing Works: Gidaris et al. [173] propose the IFSL problem and an attention-based solution to mitigate the forgetting in IFSL. The Attention Attractor Network, proposed by Ren et al. [174], is an alternative approach where the per-episode training objective during the incremental metalearning stage is regulated using an attention mechanism to attend the set of base classes. In contrast to previous approaches that extract a fixed representation for each task, XtarNet [175] emphasizes the extraction of task-adaptive representations by combining novel and base features to enhance the adaptability of the representations. Shi et al. [176] suggest putting more effort into the base classifier pretraining stage rather than the later few-shot learning stage. As a result, they propose to seek flat local minima of the base classifier training objective function and subsequently fine-tune the model parameters within that flat region when faced with new tasks. In addition, C-FSCIL [106] incorporates a trainable fixed-size fully connected layer and a rewritable dynamically growing memory buffer to mitigate forgetting. This memory buffer can store a vector for each class encountered up to that point in the learning process.

#### 6.2 Continual Meta-Learning

The goal of continual meta-learning (CML) is to address the challenge of forgetting in non-stationary task distributions. Traditional meta-learning approaches typically focus on a single task distribution. However, CML extends this concept to handle a sequence of task distributions, denoted as  $P_1(\mathcal{T}), P_2(\mathcal{T}), \cdots, P_N(\mathcal{T})$ . In CML, the objective is to develop meta-learning algorithms that can effectively adapt and generalize to new task distributions as they arise over time. These task distributions can represent different environments, domains, or contexts. It aims to mitigate the forgetting of previously learned task distributions while efficiently adapting to new tasks.

*Existing Works:* Online meta-learning (OML) [177] is a framework that assumes tasks arrive sequentially and

aims to improve performance on future tasks. Jerfel et al. [178] extended the Model-Agnostic Meta-Learning [179] approach and utilized Dirichlet process mixtures to group similar training tasks together. However, this method is not scalable to large-scale non-stationary distributions due to the requirement of independent parameters for each component. Yap et al. [180] proposed an approach to model the posterior distribution of meta-parameters using Laplace approximation [64]. Zhang et al. [181] further extended this framework by employing a dynamical mixture model to learn the distribution of meta-parameters instead of a single distribution. Additionally, they used structural variational inference techniques to infer latent variables in the model. Wang et al. [182], [183], [184] introduced a largescale benchmark for sequential domain meta-learning. They proposed different settings, including supervised learning, imbalanced domains, and semi-supervised settings, to evaluate the performance of various methods in sequential domain meta-learning.

#### 7 FORGETTING IN GENERATIVE MODEL

The goal of a generative model is to learn a generator that can generate samples from a target distribution. In the context of generative models, research related to forgetting can be categorized into two main categories: (1) GAN training itself can be viewed as CL; (2) lifelong learning generative model on non-stationary distributions.

#### 7.1 GAN Training is a Continual Learning Problem

Thanh-Tung et al. [185] approach GAN training as a CL problem. They consider the discriminator as learning a sequence of tasks, with each task representing the data distribution generated by a specific generator. To address the issue of catastrophic forgetting, they propose the use of momentum or gradient penalties on the discriminator. By incorporating these techniques, they aim to prevent forgetting of previously learned tasks, leading to improved convergence and reduced mode collapse in GAN training. Similarly, Liang et al. [186] adopt Elastic Weight Consolidation (EWC) [47] or Synaptic Intelligence (SI) [48] to mitigate forgetting in the discriminator during GAN training.

One application of viewing GAN training as CL is in the context of data-free knowledge distillation (DFKD) [187]. DFKD aims to extract a compact student model from a pretrained teacher model when the original training data of the teacher model is unavailable. The basic approach in DFKD involves using a generative model to reconstruct or generate hard examples as input to the pretrained model, thereby distilling knowledge from the teacher model. However, forgetting poses a significant challenge in DFKD. Forgetting occurs in DFKD due to the non-stationary distribution of pseudo-samples generated by the pseudo-data generator, as the generator evolves over time. To mitigate this forgetting issue, Binici et al. [188] propose the use of a memory buffer that dynamically collects generated samples over time. By preserving past samples, the memory buffer helps to alleviate forgetting in DFKD. Binici et al. [189] utilize generative replay, which involves remembering previous data distributions, to further mitigate forgetting in DFKD.

Another approach to address forgetting in DFKD is MAD [190] proposed by Do et al, which maintains an exponential moving average of the generator, preventing drastic changes in the generated data distribution and preserving previous knowledge. Patel et al. [191] propose a meta-learning-inspired framework to tackle the forgetting issue in DFKD.

#### 7.2 Lifelong Learning of Generative Models

Lifelong learning of generative models seeks to enable generative models to generate data for new tasks while preserving the ability to generate data for previously learned tasks without forgetting. The goal is to develop generative models that can continually generate high-quality samples for both new and previously encountered tasks. The proposed approaches in lifelong learning of generative models encompass both Generative Adversarial Networks (GAN)based and Variational Autoencoders (VAE)-based methods.

In the realm of GAN-based approaches, Zhai et al. [192], [193] have proposed lifelong GAN, which allows for conditioned image generation while avoiding the problem of forgetting previously acquired knowledge. In the context of VAE-based approaches, Ramapuram et al. [194] introduce a teacher-student architecture. Furthermore, Ye et al. propose network expansion [195] and dynamic optimal transport formulation [196] to address the continual VAE.

Intentional Forgetting in Diffusion Model: The advancement of text-to-image diffusion models [197], [198] has sparked significant concerns regarding data privacy, copyright infringement, and safety related to generative models, primarily because of the memorization effect observed in large generative models. This effect leads to the learning and generation of unauthorized and potentially harmful content, contributing to the creation and dissemination of unregulated material. To address these concerns, the Forget-Me-Not approach [199] and Selective Amnesia (SA) [200] have emerged, aiming to mitigate the presence of potentially harmful or unauthorized content. These approaches achieve this by leveraging forgetting mechanisms to eliminate unwanted information, thereby promoting diversity in generated outputs and protecting data privacy.

#### 8 FORGETTING IN REINFORCEMENT LEARNING

While most existing CL methods primarily tackle the issue of forgetting in image classification, it is important to note that forgetting also widely occurs in reinforcement learning (RL), known as continual RL. Addressing catastrophic forgetting in RL is vital for the advancement of intelligent agents that can continuously learn and adapt to new tasks and environments [201].

Standard RL formulation could be defined as the following. We denote S as the state space, A as the action space, and a reward function is  $r : S \times A \rightarrow R$ . At each time step t, the agent sample action from a policy function which output the optimal action or the distributions over the action space. The deterministic policy takes the current state s as input, and outputs the action according to  $a_t = \mu(s_t)$ . A stochastic policy takes the state  $s_t$  as input, outputs the optimal action distribution according to  $a_t \sim \pi(\cdot|s_t)$ . Then, the state transition function takes the state  $s_t$  and  $a_t$  as input and outputs the next action either deterministically  $s_{t+1} = f(s_t, a_t)$  or stochastically  $s_{t+1} \sim p(\cdot|s_t, a_t)$ . The goal of RL agent is to accumulate as much reward as possible.

Following [201], the general continual RL can be formulated as the following:

**Definition 8.1.** (General Continual RL): Given a state space S, action space A and observation space O. A reward function is  $r : S \times A \rightarrow R$ ; A transition function is  $p : S \times A \rightarrow S$ ; An observation function is  $x : S \rightarrow O$ . The general continual RL can be formulated as

$$\mathcal{M} \stackrel{def}{=} \langle \mathcal{S}(t), \mathcal{A}(t), r(t), p(t), x(t), \mathcal{O}(t) \rangle.$$
(6)

Definition 8.1 highlights that in continual RL, various components such as the state, action, reward, observation, and more, undergo changes over time. This emphasizes the dynamic nature of the RL process in continual settings.

**Continual RL approach**. The existing continual RL methods can be categorized into four main groups: (1) regularization-based methods. These approaches employ techniques such as knowledge distillation to alleviate forgetting [202], (2) rehearsal-based methods. These methods utilize rehearsal or experience replay to mitigate forgetting [203], (3) architecture-based methods. These approaches focus on learning a shared structure, such as network modularity or composition, to facilitate continual learning [204] and (4) meta-learning-based methods [179].

#### 9 FORGETTING IN FEDERATED LEARNING

Federated learning (FL) is a decentralized machine learning approach where the training process takes place on local devices or edge servers instead of a centralized server. In federated learning, instead of sending raw data to a central server, the model is distributed to multiple client devices or servers. Each client device performs training on its local data, and only the model updates are sent back to the central server. The central server aggregates these updates from multiple clients to update the global model. This collaborative learning process enables privacy preservation as the raw data remains on the local devices, reducing the risks associated with data sharing.

We can classify the forgetting issue in federated learning (FL) into two branches. The first branch pertains to the forgetting problem caused by the inherent non-IID (not identically and independently distributed) data among different clients participating in FL. In this scenario, each client's data distribution may vary significantly, leading to challenges in preserving previously learned knowledge when aggregating model updates from multiple clients. The second branch addresses the issue of continual learning within each individual client in the federated learning process, which results in forgetting at the overall FL level. This branch is referred to as federated continual learning (FCL) [205]. FCL involves the continual learning and adaptation of models on each client while participating in federated learning, potentially leading to forgetting of previously learned knowledge at the global FL level. We will provide a detailed explanation for each research direction in the following.

#### 9.1 Forgetting Due to Non-IID Data in FL

The problem of *client drift* [206] in federated learning pertains to the scenario where there is a substantial variation in the data distribution across individual clients. In federated learning, each client conducts local training using its own data, and subsequently, the model updates are aggregated to construct a global model. However, when there are significant variations in the data distribution among clients, it leads to each client updating its model in different directions, ultimately resulting in a drift among the client models. This drift can lead to performance degradation or instability in the global model. In other words, forgetting in federated learning occurs during the model averaging process on the server side and is primarily driven by the inconsistency of models among clients [12]. This inconsistency arises due to the presence of heterogeneous data distributions across clients.

Shoham et al. [207] provide an interpretation of the client drift issue in FL by relating it to the concept of forgetting in continual learning. They propose a regularization-based approach specifically designed to address client drift in federated learning settings, particularly in the non-IID data setting. Their method aims to mitigate the effects of forgetting and preserve previously learned knowledge during the training process in federated learning. Subsequently, multiple methods have been proposed to alleviate the issue of forgetting by integrating penalty or regularization terms that account for client model shifts [208], [209], [210]. FCCL [208] utilizes two teachers, the optimal model pretrained on the client's private data and the model after the server's collaborative update, and applies knowledge distillation to constrain the client model update, thereby alleviating forgetting. FedReg [209] addresses forgetting by using generated pseudo data to regularize the parameter update during client training, noting that solving forgetting in federated learning can enhance the convergence speed of the algorithm. FedNTD [210] employs knowledge distillation to mitigate knowledge forgetting, but focuses only on distilling mispredicted classes while disregarding wellpredicted ones. Additionally, inspired by the GEM [14] and OGD [57], GradMA [211] employs gradient information from the previous local model and the centralized model to restrict the gradient direction of the local model update. By rethinking the design of the models used in federated learning, Qu et al. [212] propose architectural strategies to mitigate forgetting and improve the overall performance and stability of federated learning systems.

#### 9.2 Federated Continual Learning

In traditional federated learning, the focus is primarily on aggregating model updates from different clients without considering the long-term retention of knowledge across multiple training rounds. However, in scenarios where clients encounter non-stationary distribution, it becomes necessary to incorporate continual learning techniques to avoid catastrophic forgetting and retain knowledge from previous training rounds. In standard CL, an agent learns a sequence of tasks, denoted as  $\mathcal{T}_1, \dots, \mathcal{T}_N$ . However, in federated continual learning (FCL), each client learns its own private task sequence.

FCL is more complicated than traditional FL or CL because non-iid and catastrophic forgetting problems need to be solved simultaneously. FedWeIT [205] first formally introduced the FCL setting from the perspective of CL. Solving forgetting in FCL is very challenging due to two reasons: (1) non-stationary data distribution in each client; and (2) model average in the server. Existing methods of addressing forgetting can be divided into three classes. (1) Parameter Isolation Method [205]: FedWeIT [205] decomposes the parameters of each client into global and sparse local task adaptation parameters to reduce inter-client interference and thus alleviate forgetting. (2) Replay-based Method [213], [214]: inspired by traditional memory-based CL, some methods address the forgetting problem by replaying the client's old data. (3) Knowledge Distillation Method [215]: CFeD [215] assumes that there is an unlabeled wild dataset in the clients and server. It proposes a distillation-based method that utilizes an unlabeled surrogate dataset to aggregate clients and avoids forgetting by rehearsing old data.

### **10 BENEFICIAL FORGETTING**

Forgetting is not always harmful; in fact, intentional forgetting can prove beneficial in many cases. In this section, we explore the concept of beneficial forgetting within various learning scenarios. We begin by discussing selective forgetting and its positive impact on mitigating overfitting, as outlined in Section 10.1. Next, we highlight the importance of discarding old, irrelevant knowledge when acquiring new knowledge, which we explore in Section 10.2. Additionally, we delve into the field of *machine unlearning* in Section 10.3, which specifically focuses on the task of erasing private user data from pre-trained models. This area of research aims to address privacy concerns by effectively removing sensitive information from models that have been trained on user data. By discussing machine unlearning, we shed light on the techniques and strategies employed to achieve secure and privacy-preserving machine learning models.

#### 10.1 Combat Overfitting Through Forgetting

Overfitting in neural networks occurs when the model excessively memorizes the training data, leading to poor generalization. To address overfitting, it is necessary to selectively forget irrelevant or noisy information [216]. One strategy to mitigate overfitting is selective forgetting, as proposed by Shibata et al. [217]. This approach involves identifying and discarding less relevant or noisy information from the training data, enabling the model to focus on the most important patterns and improve its ability to generalize to unseen data. Current methodologies, including techniques such as  $l_1$  normalization, feature selection, and early stopping, can be considered as forms of selective forgetting. These methods play an important role in removing less informative components from the model's memory. By applying  $l_1$  normalization, the model's parameters are encouraged to become sparse, effectively forgetting less relevant features. Feature selection techniques focus on identifying and retaining only the most informative features while discarding the rest. Additionally, early stopping halts the

training process when the model's performance on a validation set starts to deteriorate, preventing further memorization of noise or irrelevant patterns. Furthermore, Nikishin et al. [218] overcome the overfitting to early experiences in reinforcement learning by resetting the last few layers of the RL agent. All of these methods contribute to selective forgetting by discarding less informative components and promoting the retention of more relevant information in the model's memory.

In the context of learning from noisy labeled data, the memorization and overfitting to noisy labeled data can detrimentally impact the model's generalization performance. SIGUA [219] proposes a method to selectively forget the undesired memorization of noisy labeled data, reinforcing the desired memorization and improving the model's overall performance.

Adversarial forgetting, as described in the work by Jaiswal et al. [220], offers a mechanism to mitigate overfitting to unwanted and nuisance factors present in the training data. This approach involves selectively forgetting irrelevant information to promote the learning of invariant representations, thus reducing the impact of irrelevant factors on the model's performance.

#### 10.2 Learning New Knowledge Through Forgetting Previous Knowledge

Numerous studies in psychology and neuroscience have revealed the interconnected nature of forgetting and learning [221]. In the field of machine learning, the Learn to Forget approach proposed by Baik et al. [222] highlights that not all prior knowledge acquired through meta-learning is beneficial for learning new tasks. They propose selectively forgetting certain aspects of prior knowledge to facilitate faster learning of new tasks. In a different line of research, Zhou et al. [223] introduce a forget-and-relearn paradigm. They show that adding a forgetting step can improve the generalization and effectiveness of model relearning. Another approach, Learning Not to Learn (LNL) [224], focuses on forgetting biased information. LNL aims to minimize the mutual information between feature embeddings and bias, thereby enhancing performance during test time by reducing the influence of biased or irrelevant information. Bevan et al. [225] leverage the concept of forgetting biased information for Melanoma Classification. They explore the idea of selectively forgetting certain biased information that might be present in the dataset to improve the accuracy and effectiveness of melanoma classification models. Chen et al. [226] delve into the learn-forget paradigm in the context of optimal task selection for meta-learning. Their research investigates how the selective learning and forgetting of tasks can contribute to achieving optimal task selection in metalearning scenarios. Moreover, in the context of continual learning, Wang et al. [227] identify that when old knowledge interferes with the learning of new tasks, accurate preservation of the old knowledge can exacerbate the interference. To address this issue, they propose an active forgetting mechanism that selectively discards old knowledge that hinders the learning of new tasks. By doing so, they demonstrate the potential benefits of active forgetting in CL.

#### 10.3 Machine Unlearning

#### 10.3.1 Problem Overview

Machine unlearning [13], [228], [229], a recent area of research, addresses the need to forget previously learned training data in order to protect user data privacy and aligns with privacy regulations such as the European Union's General Data Protection Regulation [230] and the Right to Be Forgotten [10]. These regulations require companies and organizations to provide users with the ability to remove their data under specific circumstances.

Interestingly, machine unlearning demonstrates two distinct phenomena related to forgetting. On one hand, it involves forgetting specific training data memorized by the pre-trained model. The problem of machine unlearning can be categorized into two main types: exact unlearning and approximate unlearning. In Section 10.3.2, we will delve into the details of *exact unlearning*, while in Section 10.3.3, we will focus on the concept of *approximate unlearning*. On the other hand, machine unlearning can lead to catastrophic forgetting of knowledge on data other than the targeted forgotten training set. The gradual updating of the pretrained model to achieve unlearning is responsible for this second type of forgetting. In Section 10.3.4, we will provide a comprehensive exploration of catastrophic forgetting in machine unlearning and its implications.

#### 10.3.2 Exact Unlearning

Exact unlearning refers to the scenario where the distribution of the model obtained by training on the remaining dataset is identical to the distribution of the unlearned model. Let  $P(\mathbb{A}(\mathcal{D}))$  denote the model distribution trained on dataset  $\mathcal{D}$  with algorithm  $\mathbb{A}$ . Let  $\mathcal{F}$  denote the dataset to be removed in the pre-trained model.  $P(\mathbb{A}(\mathcal{D}\setminus\mathcal{F}))$  denote the model distribution by training on the remaining dataset  $\mathcal{D}\setminus\mathcal{F}$ .  $P(\mathcal{U}(\mathcal{D},\mathcal{F},\mathbb{A}(\mathcal{D})))$  denote the unlearned model distribution. This concept can be defined as follows.

**Definition 10.1 (exact unlearning).** For a learning algorithm  $\mathbb{A}$ , a dataset  $\mathcal{D}$  and a dataset  $\mathcal{F}$  to be forgotten, the exact unlearning  $\mathcal{U}$  can be defined as following:

$$P(\mathbb{A}(\mathcal{D}\backslash\mathcal{F})) = P(\mathcal{U}(\mathcal{D},\mathcal{F},\mathbb{A}(\mathcal{D}))).$$
(7)

One straightforward approach to achieve exact unlearning of targeted training data from a machine learning model is to retrain the model using the remaining dataset as defined earlier. This method effectively removes all information associated with the deletion set. However, this approach can be computationally expensive, especially in the case of large-scale pre-trained models and datasets.

*Existing works.* To address the above challenges, DeltaGrad [231] cache the model parameters and gradients at each training iteration during the learning process to speed up the retraining on the remaining dataset. SISA [228] involves partitioning the dataset into distinct shards or subsets and maintaining multiple independent models by training the model on each subset. During inference, the predictions of these individual models are combined or aggregated. Upon receiving deletion requests, SISA approach retraining process focuses solely on the constituent model that originally trained on the subset containing this data point. This methodology ensures the elimination of all information associated with the removed data points. Sekhari et al. [232] explores on machine unlearning with a focus on population risk minimization instead of previous work focus on empirical risk minimization. Ullah et al. [233] further propose an exact unlearning method based on the notion of total variation (TV) stability. ARCANE [234] is an approach that leverages ensemble learning to address the retraining cost associated with unlearning. Instead of performing a full retraining process, ARCANE transforms it into multiple one-class classification tasks. By doing so, it reduces the computational and resource requirements while still maintaining the desired model performance.

#### 10.3.3 Approximate Unlearning

As discussed above, exact unlearning can be computationally and memory intensive, especially in the case of largescale pre-trained models and datasets. Additionally, it poses a challenge to validate whether the distribution of the model after unlearning matches that of a fully retrained model using the remaining dataset. As a result, recent research has embraced the concept of approximate unlearning [235]. This concept allows for a more efficient and feasible approach to unlearning, offering a balance between computational resources and the desired level of forgetting. The concept of "approximate unlearning" is defined in the following:

**Definition 10.2 (approximate unlearning** [235]). Given a  $\epsilon$ , for a learning algorithm  $\mathbb{A}$ , a dataset  $\mathcal{D}$  and a dataset  $\mathcal{F}$  to be forgotten, the unlearning algorithm  $\mathcal{U}$  performs  $\epsilon$  certified removal to remove the influence of z defined as the following:

$$\log ||P(\mathbb{A}(\mathcal{D} \setminus \boldsymbol{z})) - P(\mathcal{U}(\mathcal{D}, \boldsymbol{z}, \mathbb{A}(\mathcal{D})))|| \le \epsilon.$$
(8)

Intuitively, the definition of approximate unlearning strives to minimize the disparity between the parameter distribution of the unlearned model and the model obtained through full retraining on the remaining dataset. Instead of enforcing an exact match, approximate unlearning relaxes the requirement by focusing on bringing their distributions closer together. This relaxation allows for a more practical approach to unlearning, acknowledging that achieving an exact replication of the fully trained model on the remaining dataset may not always be feasible or necessary.

Existing works. Certified Removal [235] introduces a theoretical framework for approximate unlearning. It offers a compelling assurance that a model, from which specific data has been removed, is indistinguishable from a model that has never encountered that data in the first place. This theoretical guarantee provides a strong foundation for the effectiveness of the unlearning process. By ensuring that the model's behavior remains consistent with a model that lacks knowledge of the removed data, Certified Removal offers a high level of confidence in the privacy and security of the unlearning procedure. The scrubbing procedure [236] offers an alternative framework for machine unlearning by leveraging a generalized and weaker form of Differential Privacy. It modifies neural network weights to eliminate or "scrub" information related to specific training data. Variational Bayesian Unlearning (VBU) [237] is a probabilistic framework for approximate unlearning. It aims to minimize the KL-divergence between the approximate posterior of

model parameters obtained through direct unlearning and the exact posterior from retraining the model with full data. VBU strikes a balance between completely forgetting the erased data and retaining essential knowledge captured by the model's posterior belief when trained on the full data. In a subsequent study, L-CODEC [238] is an approximate unlearning method that identifies a specific subset of model parameters with the highest semantic overlap on an individual sample level. This subset of parameters is then utilized in the context of machine unlearning to achieve more efficient and targeted unlearning.

#### 10.3.4 Catastrophic Forgetting Other Normal Examples

Catastrophic forgetting in machine unlearning refers to the unintended decrease in the log posterior probability of the remaining dataset, denoted as  $P(\boldsymbol{\theta} \mid \mathcal{D} \setminus \mathcal{F})$ , as a result of unlearning [239]. This phenomenon leads to a degradation in the performance of the unlearned model on data other than the targeted samples, which is undesirable. The significance of catastrophic forgetting increases as more data is unlearned. It is important to note that this concept differs from the objective of machine unlearning, which focuses solely on forgetting specific samples. In the UNLEARN method proposed by [239], the update magnitude of new parameter values to the old values is constrained, and a memory buffer is maintained to store previous examples. The Forsaken method [240] introduces a dynamic gradient penalty term to restrict parameter changes on normal data, effectively mitigating the issue of catastrophic forgetting. A Bayesian unlearning framework proposed by [237] provides a natural trade-off interpretation between fully unlearning from erased data and retaining posterior beliefs by learning on the entire dataset. Additionally, scrubbing procedure [236] minimizes loss on the remaining data while maximizing forgetting on the target forgetting dataset by introducing random noise to the model weights, allowing for forgetting on the specified dataset while retaining knowledge on the remaining data. Furthermore, PUMA [241], aims to mitigate the potential negative impact caused by the removal of targeted training data. PUMA achieves this by optimally reweighting the remaining data, ensuring that the model's performance is not excessively affected when unlearning specific samples.

Finally, it is evident that we cannot simply erase an excessive number of data points, as doing so would eventually lead to a decrease in performance on the test set. In a study by Sekhari et al. [232], the authors conduct a theoretical analysis to determine the maximum number of samples that can be deleted from a pre-trained model without compromising the performance on the test set. This analysis provides insights into the trade-off between machine unlearning on a specific subset of training set and maintaining the generalization performance on test set.

#### 10.3.5 Application of Machine Unlearning

Machine unlearning techniques find application in various domains, including backdoor attack defense and defending against membership inference attacks. In the context of backdoor attack defense [242], machine unlearning can be used to erase the backdoor trigger that has been injected into a trained model. By selectively unlearning the specific information related to the backdoor trigger, the model can be cleansed of its malicious behavior. Similarly, machine unlearning can also serve as a defense mechanism [235], [241] against membership inference attacks. By removing the specific training data from a pre-trained model, the traces or characteristics of these data are eliminated, making it harder for attackers to infer membership or extract sensitive information.

#### 11 **DISCUSSION AND FUTURE PROSPECT**

#### 11.1 Summary and Research Trends

*Cross Discipline Research About Forgetting:* Cross-disciplinary research is vital for advancing machine learning disciplines. Various fields offer valuable insights and innovations through cross-disciplinary research. This exploration encompasses both the application of techniques from CL to address challenges in other research domains and applications of techniques from various fields to solve problems in CL. These interdisciplinary research efforts pave the way for the advancements in different research areas. In future work, we anticipate that actively promoting collaboration and facilitating idea exchange across diverse research areas will be crucial in overcoming disciplinary barriers.

Intentional Forgetting in Machine Learning: Intentional forgetting has emerged as a promising approach to enhance model performance and address data privacy concerns in recent studies. On one hand, intentional forgetting proves valuable in eliminating biased and irrelevant information during model training, thereby mitigating overfitting and improving generalization. On the other hand, in the context of machine unlearning, forgetting plays a crucial role in removing private data to safeguard data privacy.

Growing Trend for Theoretical Analysis: Recently, there is an emerging trend towards conducting theoretical analyses to delve deeper into the understanding and analysis of forgetting across diverse research fields. These theoretical analyses aim to provide more valuable insights and uncover fundamental principles that govern forgetting.

Addressing Forgetting with Foundation Models: The foundation model has demonstrated promising potential in tackling forgetting across various research fields, making it an active and promising area of research.

#### 11.2 Open Research Questions and Future Prospect

In the following, we prospect several potential research directions for future study.

In-depth Theoretical Analysis of Forgetting: The majority of existing methods are empirical in nature, lacking theoretical guarantees and comprehensive analysis. Therefore, there is a pressing need for more thorough theoretical analysis across different learning domains. Future research efforts should aim to bridge this gap by incorporating rigorous theoretical analysis of forgetting.

Trustworthiness of Forgetting: Most existing studies on forgetting primarily concentrate on its impact on model performance while overlooking other crucial aspects such as robustness, fairness, transparency, etc. To bridge this research gap, future investigations should dedicate more efforts to analyze and understand the effects of forgetting on these trustworthiness properties.

Proper Trade-off Between Memorization and Forgetting: Striking a balance between remembering previous knowledge and protecting privacy poses a critical research problem. Remembering more previous knowledge can increase the risk of memorizing private information, potentially compromising privacy. Conversely, prioritizing privacy protection may result in sacrificing performance on previous tasks. Achieving an appropriate equilibrium between memorization and forgetting is crucial to address this challenge effectively. Future research should focus on developing methodologies and techniques that enable effective management of knowledge retention while ensuring privacy preservation, thereby striking the optimal balance between the two.

#### 12 CONCLUSION

Forgetting is a prevalent phenomenon across various machine learning fields, driven by different factors. This survey aims to offer a comprehensive examination of the forgetting issue in diverse machine learning domains, such as continual learning, foundation model, meta-learning, domain adaptation, test time adaptation, generative model, federated learning, reinforcement learning and machine unlearning. Our survey aims to provide a thorough overview and understanding of the research progress on forgetting, with the intention of inspiring future investigations into intriguing and innovative research directions and methods. While existing surveys on continual learning often emphasize the harmful aspects of forgetting, our survey argues that forgetting can also be beneficial. We present application scenarios where selective forgetting improves generalization performance and learns new tasks, and intentional forgetting of memorized examples helps safeguard the privacy of machine learning systems.

#### REFERENCES

- M. McCloskey and N. J. Cohen, "Catastrophic interference in [1] connectionist networks: The sequential learning problem," Psychology of learning and motivation, 1989.
- [2] G. I. Parisi, R. Kemker, J. L. Part, C. Kanan, and S. Wermter, "Continual lifelong learning with neural networks: A review," Neural Networks, 2019.
- G. M. van de Ven and A. S. Tolias, "Three scenarios for continual [3] learning," 2019.
- M. De Lange, R. Aljundi, M. Masana, S. Parisot, X. Jia, [4] A. Leonardis, G. Slabaugh, and T. Tuytelaars, "A continual learning survey: Defying forgetting in classification tasks," TPAMI, 2022.
- Z. Mai, R. Li, J. Jeong, D. Quispe, H. Kim, and S. Sanner, "Online [5] continual learning in image classification: An empirical survey," Neurocomputing, 2022.
- M. Masana, X. Liu, B. Twardowski, M. Menta, A. D. Bagdanov, [6] and J. van de Weijer, "Class-incremental learning: survey and performance evaluation on image classification," TPAMI, 2022.
- [7] D.-W. Zhou, Q.-W. Wang, Z.-H. Qi, H.-J. Ye, D.-C. Zhan, and Z. Liu, "Deep class-incremental learning: A survey," 2023
- [8] J. A. Mendez and E. Eaton, "How to reuse and compose knowledge for a lifetime of tasks: A survey on continual learning and functional composition," Transactions on Machine Learning Research, 2023.
- [9] L. Wang, X. Zhang, H. Su, and J. Zhu, "A comprehensive survey of continual learning: Theory, method and application," 2023.
- A. Ginart, M. Guan, G. Valiant, and J. Y. Zou, "Making ai forget [10] you: Data deletion in machine learning," *NeurIPS*, 2019. R. Shokri, M. Stronati, C. Song, and V. Shmatikov, "Membership
- [11] inference attacks against machine learning models," in SP, 2017.

- [12] Y. Shi, L. Shen, K. Wei, Y. Sun, B. Yuan, X. Wang, and D. Tao, "Improving the model consistency of decentralized federated learning," *ICML*, 2023.
- [13] Y. Cao and J. Yang, "Towards making systems forget with machine unlearning," in 2015 IEEE symposium on security and privacy, 2015.
- [14] D. Lopez-Paz and M. Ranzato, "Gradient episodic memory for continual learning," *NeurIPS*, 2017.
- [15] A. Chaudhry, M. Ranzato, M. Rohrbach, and M. Elhoseiny, "Efficient lifelong learning with a-gem," *ICLR*, 2019.
- [16] P. Buzzega, M. Boschini, A. Porrello, D. Abati, and S. Calderara, "Dark experience for general continual learning: a strong, simple baseline," *NeurIPS*, 2020.
- [17] R. Tiwari, K. Killamsetty, R. Iyer, and P. Shenoy, "Gcr: Gradient coreset based replay buffer selection for continual learning," in *CVPR*, 2022.
- [18] Z. Sun, Y. Mu, and G. Hua, "Regularizing second-order influences for continual learning," in CVPR, 2023.
- [19] S.-A. Rebuffi, A. Kolesnikov, G. Sperl, and C. H. Lampert, "icarl: Incremental classifier and representation learning," in CVPR, 2017.
- [20] R. Aljundi, M. Lin, B. Goujaud, and Y. Bengio, "Gradient based sample selection for online continual learning," in *NeurIPS*, 2019.
- [21] J. Bang, H. Kim, Y. Yoo, J.-W. Ha, and J. Choi, "Rainbow memory: Continual learning with a memory of diverse samples," in CVPR, 2021.
- [22] A. Chaudhry, P. K. Dokania, T. Ajanthan, and P. H. Torr, "Riemannian walk for incremental learning: Understanding forgetting and intransigence," in ECCV, 2018.
- [23] R. Aljundi, E. Belilovsky, T. Tuytelaars, L. Charlin, M. Caccia, M. Lin, and L. Page-Caccia, "Online continual learning with maximal interfered retrieval," *NeurIPS*, 2019.
- [24] W. Chenshen, L. Herranz, L. Xialei *et al.*, "Memory replay gans: Learning to generate images from new categories without forgetting," in *NeurIPS*, 2018.
- [25] Y. Xiang, Y. Fu, P. Ji, and H. Huang, "Incremental learning using conditional adversarial networks," in *ICCV*, 2019.
- [26] R. Kemker and C. Kanan, "Fearnet: Brain-inspired model for incremental learning," in *ICLR*, 2018.
  [27] Q. Jodelet, X. Liu, Y. J. Phua, and T. Murata, "Class-incremental
- [27] Q. Jodelet, X. Liu, Y. J. Phua, and T. Murata, "Class-incremental learning using diffusion model for distillation and replay," *CoRR*, 2023.
- [28] J. Smith, Y.-C. Hsu, J. Balloch, Y. Shen, H. Jin, and Z. Kira, "Always be dreaming: A new approach for data-free classincremental learning," in *ICCV*, 2021.
- [29] G. M. Van de Ven, H. T. Siegelmann, and A. S. Tolias, "Braininspired replay for continual learning with artificial neural networks," *Nature communications*, 2020.
- [30] K. Jeeveswaran, P. Bhat, B. Zonooz, and E. Arani, "Birt: Bioinspired replay in vision transformers for continual learning," *ICML*, 2023.
- [31] L. Wang, X. Zhang, K. Yang, L. Yu, C. Li, L. HONG, S. Zhang, Z. Li, Y. Zhong, and J. Zhu, "Memory replay with data compression for continual learning," in *ICLR*, 2022.
- [32] Z. Luo, Y. Liu, B. Schiele, and Q. Sun, "Class-incremental exemplar compression for class-incremental learning," in CVPR, 2023.
- [33] Y. Liu, Y. Su, A. Liu, B. Schiele, and Q. Sun, "Mnemonics training: Multi-class incremental learning without forgetting," in CVPR, 2020.
- [34] Z. Deng and O. Russakovsky, "Remember the past: Distilling datasets into addressable memories for neural networks," in *NeurIPS*, 2022.
- [35] G. Cazenavette, T. Wang, A. Torralba, A. A. Efros, and J.-Y. Zhu, "Dataset distillation by matching training trajectories," in CVPR, 2022.
- [36] A. A. Rusu, N. C. Rabinowitz, G. Desjardins, H. Soyer, J. Kirkpatrick, K. Kavukcuoglu, R. Pascanu, and R. Hadsell, "Progressive neural networks," 2016.
- [37] C. Fernando, D. Banarse, C. Blundell, Y. Zwols, D. Ha, A. A. Rusu, A. Pritzel, and D. Wierstra, "Pathnet: Evolution channels gradient descent in super neural networks," arXiv preprint arXiv:1701.08734, 2017.
- [38] J. Yoon, E. Yang, J. Lee, and S. J. Hwang, "Lifelong learning with dynamically expandable networks," *ICLR*, 2018.
- [39] J. Serrá, D. Surís, M. Miron, and A. Karatzoglou, "Overcoming catastrophic forgetting with hard attention to the task," in *ICML*, 2018.

- [40] G. Bellec, D. Kappel, W. Maass, and R. Legenstein, "Deep rewiring: Training very sparse deep networks," in *ICLR*, 2018.
- [41] Z. Wang, Z. Zhan, Y. Gong, G. Yuan, W. Niu, T. Jian, B. Ren, S. Ioannidis, Y. Wang, and J. Dy, "Sparcl: Sparse continual learning on the edge," in *NeurIPS*, 2022.
- [42] A. Mallya, D. Davis, and S. Lazebnik, "Piggyback: Adapting a single network to multiple tasks by learning to mask weights," in ECCV, 2018.
- [43] A. Mallya and S. Lazebnik, "Packnet: Adding multiple tasks to a single network by iterative pruning," in *CVPR*, 2018.
  [44] C.-Y. Hung, C.-H. Tu, C.-E. Wu, C.-H. Chen, Y.-M. Chan, and
- [44] C.-Y. Hung, C.-H. Tu, C.-E. Wu, C.-H. Chen, Y.-M. Chan, and C.-S. Chen, "Compacting, picking and growing for unforgetting continual learning," *NeurIPS*, 2019.
  [45] X. Li, Y. Zhou, T. Wu, R. Socher, and C. Xiong, "Learn to
- [45] X. Li, Y. Zhou, T. Wu, R. Socher, and C. Xiong, "Learn to grow: A continual structure learning framework for overcoming catastrophic forgetting," in *ICML*, 2019.
- [46] S. Yan, J. Xie, and X. He, "Der: Dynamically expandable representation for class incremental learning," in CVPR, 2021.
- [47] J. Kirkpatrick, R. Pascanu, N. Rabinowitz, J. Veness, G. Desjardins, A. A. Rusu, K. Milan, J. Quan, T. Ramalho, A. Grabska-Barwinska, D. Hassabis, C. Clopath, D. Kumaran, and R. Hadsell, "Overcoming catastrophic forgetting in neural networks," *Proceedings of the national academy of sciences*, 2017.
  [48] F. Zenke, B. Poole, and S. Ganguli, "Continual learning through
- [48] F. Zenke, B. Poole, and S. Ganguli, "Continual learning through synaptic intelligence," in *ICML*, 2017.
- [49] J. von Oswald, C. Henning, J. Sacramento, and B. F. Grewe, "Continual learning with hypernetworks," 2019.
- [50] R. Aljundi, F. Babiloni, M. Elhoseiny, M. Rohrbach, and T. Tuytelaars, "Memory aware synapses: Learning what (not) to forget," in ECCV, 2018.
- [51] H. Ahn, S. Cha, D. Lee, and T. Moon, "Uncertainty-based continual learning with adaptive regularization," *NeurIPS*, 2019.
- [52] G. Hinton, O. Vinyals, and J. Dean, "Distilling the knowledge in a neural network," arXiv preprint arXiv:1503.02531, 2015.
- [53] Z. Li and D. Hoiem, "Learning without forgetting," *TPAMI*, 2018.
  [54] P. Dhar, R. V. Singh, K.-C. Peng, Z. Wu, and R. Chellappa,
- "Learning without memorizing," in *CVPR*, 2019. [55] I. Fostiropoulos, J. Zhu, and L. Itti, "Batch model consolidation:
- A multi-task model consolidation framework," in *CVPR*, 2023. [56] K. Lee, K. Lee, J. Shin, and H. Lee, "Overcoming catastrophic
- forgetting with unlabeled data in the wild," in *ICCV*, 2019.[57] M. Farajtabar, N. Azizan, A. Mott, and A. Li, "Orthogonal gradient descent for continual learning," 2020.
- [58] T. Doan, M. A. Bennani, B. Mazoure, G. Rabusseau, and P. Alquier, "A theoretical analysis of catastrophic forgetting
- through the NTK overlap matrix," in *AISTATS*, 2021.
  [59] A. Chaudhry, N. Khan, P. K. Dokania, and P. H. Torr, "Continual learning in low-rank orthogonal subspaces," in *NeurIPS*, 2020.
- [60] G. Zeng, Y. Chen, B. Cui, and S. Yu, "Continual learning of context-dependent processing in neural networks," *Nature Machine Intelligence*, 2019.
- [61] G. Saha, I. Garg, and K. Roy, "Gradient projection memory for continual learning," *ICLR*, 2021.
- [62] D. DENG, G. Chen, J. HAO, Q. Wang, and P.-A. Heng, "Flattening sharpness for dynamic gradient projection memory benefits continual learning," in *NeurIPS*, 2021.
- [63] S. Lin, L. Yang, D. Fan, and J. Zhang, "TRGP: Trust region gradient projection for continual learning," in *ICLR*, 2022.
- [64] C. V. Nguyen, Y. Li, T. D. Bui, and R. E. Turner, "Variational continual learning," ICLR, 2018.
- [65] S.-W. Lee, J.-H. Kim, J. Jun, J.-W. Ha, and B.-T. Zhang, "Overcoming catastrophic forgetting by incremental moment matching," *NeurIPS*, 2017.
- [66] T. Adel, H. Zhao, and R. E. Turner, "Continual learning with adaptive weights (claw)," in *ICLR*, 2020.
- [67] R. Kurle, B. Čseke, A. Klushyn, P. van der Smagt, and S. Günnemann, "Continual learning with bayesian neural networks for non-stationary data," in *ICLR*, 2020.
- [68] C. Henning, M. Cervera, F. D'Angelo, J. V. Oswald, R. Traber, B. Ehret, S. Kobayashi, B. F. Grewe, and J. Sacramento, "Posterior meta-replay for continual learning," in *NeurIPS*, 2021.
- [69] T.-C. Kao, K. Jensen, G. van de Ven, A. Bernacchia, and G. Hennequin, "Natural continual learning: success is a journey, not (just) a destination," *NeurIPS*, 2021.
- [70] P. Pan, S. Swaroop, A. Immer, R. Eschenhagen, R. Turner, and M. E. E. Khan, "Continual deep learning by functional regularisation of memorable past," *NeurIPS*, 2020.

- [71] M. K. Titsias, J. Schwarz, A. G. d. G. Matthews, R. Pascanu, and Y. W. Teh, "Functional regularisation for continual learning with gaussian processes," in ICLR, 2020.
- [72] S. Kapoor, T. Karaletsos, and T. D. Bui, "Variational autoregressive gaussian processes for continual learning," in ICML, 2021.
- [73] T. G. Rudner, F. B. Smith, Q. Feng, Y. W. Teh, and Y. Gal, "Continual learning via sequential function-space variational inference," in ICML, 2022
- A. Kumar, S. Chatterjee, and P. Rai, "Bayesian structural adapta-[74] tion for continual learning," in ICML, 2021.
- N. Mehta, K. Liang, V. K. Verma, and L. Carin, "Continual [75] learning using a bayesian nonparametric dictionary of weight factors," in AISTATS, 2021.
- A. Chaudhry, M. Rohrbach, M. Elhoseiny, T. Ajanthan, P. K. [76] Dokania, P. H. S. Torr, and M. Ranzato, "Continual learning with tiny episodic memories," 2019.
- X. Jin, A. Sadhu, J. Du, and X. Ren, "Gradient-based editing [77] of memory examples for online task-free continual learning, NeurIPS, 2021.
- Z. Wang, L. Shen, L. Fang, Q. Suo, T. Duan, and M. Gao, "Im-[78] proving task-free continual learning by distributionally robust memory evolution," in ICML, 2022.
- S. Lee, J. Ha, D. Zhang, and G. Kim, "A neural dirichlet process [79] mixture model for task-free continual learning," in ICLR, 2020.
- R. Ardywibowo, Z. Huo, Z. Wang, B. J. Mortazavi, S. Huang, and [80] X. Qian, "VariGrow: Variational architecture growing for taskagnostic continual learning based on Bayesian novelty," in ICML, 2022.
- [81] F. Ye and A. G. Bors, "Task-free continual learning via online discrepancy distance learning," in NeurIPS, 2022.
- [82] D. Shim, Z. Mai, J. Jeong, S. Sanner, H. Kim, and J. Jang, "Online class-incremental continual learning with adversarial shapley value," in AAAI, 2021.
- [83] Y. Guo, B. Liu, and D. Zhao, "Online continual learning through mutual information maximization," in ICML, 2022.
- J. Yoon, D. Madaan, E. Yang, and S. J. Hwang, "Online coreset selection for rehearsal-based continual learning," in *ICLR*, 2022. [84]
- Y. Gu, X. Yang, K. Wei, and C. Deng, "Not just selection, but [85] exploration: Online class-incremental continual learning via dual view consistency," in CVPR, 2022.
- [86] G. Gupta, K. Yadav, and L. Paull, "La-maml: Look-ahead meta learning for continual learning," in *NeurIPS*, 2020. Y. Liu, W. Zhu, and S. Ren, "Navigating memory construction
- [87] by global pseudo-task simulation for continual learning," in NeurIPS, 2022.
- E. Fini, S. Lathuiliere, E. Sangineto, M. Nabi, and E. Ricci, "Online [88] continual learning under extreme memory constraints," in ECCV, 2020.
- J. Schwarz, J. Luketina, W. M. Czarnecki, A. Grabska-Barwinska, [89] Y. W. Teh, R. Pascanu, and R. Hadsell, "Progress and compress: A scalable framework for continual learning," in ICML, 2018.
- F. M. Castro, M. J. Marín-Jiménez, N. Guil, C. Schmid, and [90] K. Alahari, "End-to-end incremental learning," in ECCV, 2018.
- [91] A. Prabhu, P. H. Torr, and P. K. Dokania, "Gdumb: A simple approach that questions our progress in continual learning," in ÉCCV, 2020.
- Y. Wu, Y. Chen, L. Wang, Y. Ye, Z. Liu, Y. Guo, and Y. Fu, "Large [92] scale incremental learning," in CVPR, 2019.
- [93] H. Ahn, J. Kwak, S. Lim, H. Bang, H. Kim, and T. Moon, "Ss-il: Separated softmax for incremental learning," in ICCV, 2021.
- A. Chrysakis and M.-F. Moens, "Online continual learning from [94] imbalanced data," in ICML, 2020.
- C. D. Kim, J. Jeong, and G. Kim, "Imbalanced continual learning [95] with partitioning reservoir sampling," in ECCV, 2020.
- [96] S. Sun, D. Calandriello, H. Hu, A. Li, and M. Titsias, "Information-theoretic online memory selection for continual learning," in ICLR, 2022.
- E. Belouadah and A. Popescu, "Il2m: Class incremental learning [97] with dual memory," in ICCV, 2019.
- [98] B. Zhao, X. Xiao, G. Gan, B. Zhang, and S.-T. Xia, "Maintaining discrimination and fairness in class incremental learning," in CVPR, 2020.
- A. Chrysakis and M.-F. Moens, "Online bias correction for task-[99] free continual learning," in *ICLR*, 2023. W. Ren, P. Wang, X. Li, C. E. Hughes, and Y. Fu, "Semi-supervised
- [100] drifted stream learning with short lookback," in SIGKDD, 2022.

- [101] L. Wang, K. Yang, C. Li, L. Hong, Z. Li, and J. Zhu, "Ordisco: Effective and efficient usage of incremental unlabeled data for semi-supervised continual learning," in CVPR, 2021.
- [102] J. Smith, J. Balloch, Y.-C. Hsu, and Z. Kira, "Memory-efficient semi-supervised continual learning: The world is its own replay buffer," in IJCNN, 2021.
- [103] B. Yang, M. Lin, Y. Zhang, B. Liu, X. Liang, R. Ji, and Q. Ye, "Dynamic support network for few-shot class incremental learning," TPAMI, 2022.
- [104] X. Tao, X. Hong, X. Chang, S. Dong, X. Wei, and Y. Gong, "Fewshot class-incremental learning," in CVPR, 2020.
- [105] K. Zhu, Y. Cao, W. Zhai, J. Cheng, and Z.-J. Zha, "Self-promoted prototype refinement for few-shot class-incremental learning," in CVPR, 2021.
- [106] M. Hersche, G. Karunaratne, G. Cherubini, L. Benini, A. Sebastian, and A. Rahimi, "Constrained few-shot class-incremental learning," in CVPR, 2022.
- [107] Y. Yang, H. Yuan, X. Li, Z. Lin, P. Torr, and D. Tao, "Neural collapse inspired feature-classifier alignment for few-shot classincremental learning," in *ICLR*, 2023. [108] D.-W. Zhou, H.-J. Ye, L. Ma, D. Xie, S. Pu, and D.-C. Zhan, "Few-
- shot class-incremental learning by sampling multi-phase tasks," TPAMI, 2022.
- [109] Z. Chi, L. Gu, H. Liu, Y. Wang, Y. Yu, and J. Tang, "Metafscil: a meta-learning approach for few-shot class incremental learning, in CVPR, 2022
- [110] P. Mazumder, P. Singh, and P. Rai, "Few-shot lifelong learning," in AAAI, 2021.
- [111] D.-Y. Kim, D.-J. Han, J. Seo, and J. Moon, "Warping the space: Weight space rotation for class-incremental few-shot learning," in ICLR, 2023.
- [112] D. Rao, F. Visin, A. A. Rusu, Y. W. Teh, R. Pascanu, and R. Hadsell, "Continual unsupervised representation learning," in NeurIPS, 2019.
- [113] D. Madaan, J. Yoon, Y. Li, Y. Liu, and S. J. Hwang, "Representational continuity for unsupervised continual learning," in ICLR, 2022.
- [114] H. Cha, J. Lee, and J. Shin, "Co2l: Contrastive continual learning," in ICCV, 2021.
- [115] M. Davari, N. Asadi, S. Mudur, R. Aljundi, and E. Belilovsky, "Probing representation forgetting in supervised and unsupervised continual learning," in *CVPR*, 2022. [116] H. Zhang, M. Cissé, Y. N. Dauphin, and D. Lopez-Paz, "mixup:
- Beyond empirical risk minimization," in ICLR, 2018.
- [117] A. Pentina and C. Lampert, "A pac-bayesian bound for lifelong learning," in ICML, 2014.
- [118] R. Karakida and S. Akaho, "Learning curves for continual learning in neural networks: Self-knowledge transfer and forgetting," in ICLR, 2022.
- [119] G. Kim, C. Xiao, T. Konishi, Z. Ke, and B. Liu, "A theoretical study on solving continual learning," in NeurIPS, 2022.
- [120] I. Evron, E. Moroshko, G. Buzaglo, M. Khriesh, B. Marjieh, N. Srebro, and D. Soudry, "Continual learning in linear classification on separable data," in ICML, 2023.
- [121] L. Peng, P. V. Giampouras, and R. Vidal, "The ideal continual learner: An agent that never forgets," in ICML, 2023.
- A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann [122] et al., "Palm: Scaling language modeling with pathways," arXiv preprint arXiv:2204.02311, 2022
- [123] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar et al., "Llama: Open and efficient foundation language models," arXiv preprint arXiv:2302.13971, 2023.
- [124] M. Jagielski, O. Thakkar, F. Tramer, D. Ippolito, K. Lee, N. Carlini, E. Wallace, S. Song, A. G. Thakurta, N. Papernot, and C. Zhang, "Measuring forgetting of memorized training examples," in ICLR, 2023
- [125] C. Lee, K. Cho, and W. Kang, "Mixout: Effective regularization to finetune large-scale pretrained language models," in ICLR, 2020.
- J. Howard and S. Ruder, "Universal language model fine-tuning [126] for text classification," in ACL, 2018.
- [127] C. Chelba and A. Acero, "Adaptation of maximum entropy capitalizer: Little data can help a lot," Computer Speech & Language, 2006
- [128] T. Zhang, F. Wu, A. Katiyar, K. Q. Weinberger, and Y. Artzi, "Revisiting few-sample bert fine-tuning," in ICLR, 2020.

- [129] Z. Fatemi, C. Xing, W. Liu, and C. Xiong, "Improving gender fairness of pre-trained language models without catastrophic forgetting," in ACL, 2023.
- [130] X. Dong, A. T. Luu, M. Lin, S. Yan, and H. Zhang, "How should pre-trained language models be fine-tuned towards adversarial robustness?" *NeurIPS*, 2021.
- [131] S. Chen, Y. Hou, Y. Cui, W. Che, T. Liu, and X. Yu, "Recall and learn: Fine-tuning deep pretrained language models with less forgetting," in *EMNLP*, 2020.
- [132] D. Hu, S. Yan, Q. Lu, L. HONG, H. Hu, Y. Zhang, Z. Li, X. Wang, and J. Feng, "How well does self-supervised pre-training perform with streaming data?" in *ICLR*, 2022.
- [133] S. Purushwalkam, P. Morgado, and A. Gupta, "The challenges of continuous self-supervised learning," in ECCV, 2022.
- [134] Z. Lin, Y. Wang, and H. Lin, "Continual contrastive learning for image classification," in *ICME*, 2022.
- [135] N. Lukas, A. Salem, R. Sim, S. Tople, L. Wutschitz, and S. Zanella-Béguelin, "Analyzing leakage of personally identifiable information in language models," S&P, 2023.
- [136] N. Carlini, D. Ippolito, M. Jagielski, K. Lee, F. Tramer, and C. Zhang, "Quantifying memorization across neural language models," in *ICLR*, 2023.
- [137] Z. Ke, B. Liu, N. Ma, H. Xu, and L. Shu, "Achieving forgetting prevention and knowledge transfer in continual learning," *NeurIPS*, 2021.
- [138] T. Wu, M. Caccia, Z. Li, Y.-F. Li, G. Qi, and G. Haffari, "Pretrained language model in continual learning: A comparative study," in *ICLR*, 2022.
- [139] T. Scialom, T. Chakrabarty, and S. Muresan, "Fine-tuned language models are continual learners," in *EMNLP*, 2022.
- [140] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," *NeurIPS*, 2017.
- [141] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly *et al.*, "An image is worth 16x16 words: Transformers for image recognition at scale," in *ICLR*, 2021.
- [142] O. Ostapenko, T. Lesort, P. Rodríguez, M. R. Arefin, A. Douillard, I. Rish, and L. Charlin, "Continual learning with foundation models: An empirical study of latent replay," in *Conference on Lifelong Learning Agents*, 2022.
- [143] S. V. Mehta, D. Patil, S. Chandar, and E. Strubell, "An empirical investigation of the role of pre-training in lifelong learning," *ICML*, 2021.
- [144] V. V. Ramasesh, A. Lewkowycz, and E. Dyer, "Effect of scale on catastrophic forgetting in neural networks," in *ICLR*, 2022.
- [145] D.-W. Zhou, H.-J. Ye, D.-C. Zhan, and Z. Liu, "Revisiting classincremental learning with pre-trained models: Generalizability and adaptivity are all you need," arXiv preprint arXiv:2303.07338, 2023.
- [146] B. Ermis, G. Zappella, M. Wistuba, A. Rawal, and C. Archambeau, "Memory efficient continual learning with transformers," in *NeurIPS*, 2022.
- [147] Z. Wang, Z. Zhang, C.-Y. Lee, H. Zhang, R. Sun, X. Ren, G. Su, V. Perot, J. Dy, and T. Pfister, "Learning to prompt for continual learning," in *CVPR*, 2022.
- [148] Z. Wang, Z. Zhang, S. Ebrahimi, R. Sun, H. Zhang, C. Lee, X. Ren, G. Su, V. Perot, J. G. Dy, and T. Pfister, "Dualprompt: Complementary prompting for rehearsal-free continual learning," in ECCV, 2022.
- [149] Y. Wang, Z. Huang, and X. Hong, "S-prompts learning with pretrained transformers: An occam's razor for domain incremental learning," in *NeurIPS*, 2022.
- [150] A. Razdaibiedina, Y. Mao, R. Hou, M. Khabsa, M. Lewis, and A. Almahairi, "Progressive prompts: Continual learning for language models," in *ICLR*, 2023.
- [151] H. Liu, M. Long, J. Wang, and Y. Wang, "Learning to adapt to evolving domains," *NeurIPS*, 2020.
- [152] A. Bobu, E. Tzeng, J. Hoffman, and T. Darrell, "Adapting to continuously shifting domains," 2018.
- [153] M. Rostami, "Lifelong domain adaptation via consolidated internal distribution," in *NeurIPS*, 2021.
- [154] T. Panagiotakopoulos, P. L. Dovesi, L. Härenstam-Nielsen, and M. Poggi, "Online domain adaptation for semantic segmentation in ever-changing conditions," in ECCV, 2022.

- [155] S. Tang, P. Su, D. Chen, and W. Ouyang, "Gradient regularized contrastive learning for continual domain adaptation," in AAAI, 2021.
- [156] R. Volpi, D. Larlus, and G. Rogez, "Continual adaptation of visual representations via domain randomization and meta-learning," in CVPR, 2021.
- [157] A. M. N. Taufique, C. S. Jahan, and A. Savakis, "Unsupervised continual learning for gradually varying domains," in CVPR Workshops, 2022.
- [158] S. Yang, Y. Wang, J. Van De Weijer, L. Herranz, and S. Jui, "Generalized source-free domain adaptation," in *ICCV*, 2021.
- [159] H. Feng, Z. Yang, H. Chen, T. Pang, C. Du, M. Zhu, W. Chen, and S. Yan, "Cosda: Continual source-free domain adaptation," arXiv preprint arXiv:2304.06627, 2023.
- [160] W. Ahmed, P. Morerio, and V. Murino, "Continual source-free unsupervised domain adaptation," arXiv preprint arXiv:2304.07374, 2023.
- [161] D. Wang, E. Shelhamer, S. Liu, B. Olshausen, and T. Darrell, "Tent: Fully test-time adaptation by entropy minimization," in *ICLR*, 2021.
- [162] S. Niu, J. Wu, Y. Zhang, Y. Chen, S. Zheng, P. Zhao, and M. Tan, "Efficient test-time model adaptation without forgetting," in *ICML*, 2022.
- [163] T. Gong, J. Jeong, T. Kim, Y. Kim, J. Shin, and S.-J. Lee, "Note: Robust continual test-time adaptation against temporal correlation," *NeurIPS*, 2022.
- [164] S. Niu, J. Wu, Y. Zhang, Z. Wen, Y. Chen, P. Zhao, and M. Tan, "Towards stable test-time adaptation in dynamic wild world," in *ICLR*, 2023.
- [165] J. Liang, R. He, and T. Tan, "A comprehensive survey on test-time adaptation under distribution shifts," 2023.
- [166] J. Hong, L. Lyu, J. Zhou, and M. Spranger, "MECTA: Memoryeconomic continual test-time model adaptation," in *ICLR*, 2023.
- [167] M. M. Zhang, S. Levine, and C. Finn, "MEMO: Test time robustness via adaptation and augmentation," in *NeurIPS*, 2022.
- [168] Q. Wang, O. Fink, L. Van Gool, and D. Dai, "Continual test-time domain adaptation," in CVPR, 2022.
- [169] Y. Gan, X. Ma, Y. Lou, Y. Bai, R. Zhang, N. Shi, and L. Luo, "Decorate the newcomers: Visual domain prompt for continual test time adaptation," AAAI, 2023.
- [170] J. Song, J. Lee, I. S. Kweon, and S. Choi, "Ecotta: Memory-efficient continual test-time adaptation via self-distilled regularization," in *CVPR*, 2023, pp. 11920–11929.
- [171] S. Choi, S. Yang, S. Choi, and S. Yun, "Improving test-time adaptation via shift-agnostic weight regularization and nearest source prototypes," in ECCV, 2022.
- [172] D. Brahma and P. Rai, "A probabilistic framework for lifelong test-time adaptation," in CVPR, 2023.
- [173] S. Gidaris and N. Komodakis, "Dynamic few-shot visual learning without forgetting," CVPR, 2018.
- [174] M. Ren, R. Liao, E. Fetaya, and R. S. Zemel, "Incremental fewshot learning with attention attractor networks," *NeurIPS*, 2019.
- [175] S. W. Yoon, D.-Y. Kim, J. Seo, and J. Moon, "Xtarnet: Learning to extract task-adaptive representation for incremental few-shot learning," *ICML*, 2020.
- [176] G. SHI, J. Chen, W. Zhang, L.-M. Zhan, and X.-M. Wu, "Overcoming catastrophic forgetting in incremental few-shot learning by finding flat minima," in *NeurIPS*, 2021.
- [177] C. Finn, A. Rajeswaran, S. Kakade, and S. Levine, "Online metalearning," in *ICML*, 2019.
- [178] G. Jerfel, E. Grant, T. L. Griffiths, and K. Heller, "Reconciling meta-learning and continual learning with online mixtures of tasks," *NeurIPS*, 2019.
- [179] C. Finn, P. Abbeel, and S. Levine, "Model-agnostic meta-learning for fast adaptation of deep networks," *ICML*, 2017.
- [180] P. Yap, H. Ritter, and D. Barber, "Addressing catastrophic forgetting in few-shot problems," in *ICML*, 2020.
- [181] Q. Zhang, J. Fang, Z. Meng, S. Liang, and E. Yilmaz, "Variational continual bayesian meta-learning," in *NeurIPS*, 2021.
  [182] Z. Wang, L. Shen, T. Duan, D. Zhan, L. Fang, and M. Gao,
- [182] Z. Wang, L. Shen, T. Duan, D. Zhan, L. Fang, and M. Gao, "Learning to learn and remember super long multi-domain task sequence," in CVPR, 2022.
- [183] Z. Wang, T. Duan, L. Fang, Q. Suo, and M. Gao, "Meta learning on a sequence of imbalanced domains with difficulty awareness," in *ICCV*, 2021.

- [184] Z. Wang, L. Shen, L. Fang, Q. Suo, D. Zhan, T. Duan, and M. Gao, "Meta-learning with less forgetting on large-scale non-stationary task distributions," in ECCV, 2022.
- [185] H. Thanh-Tung and T. Tran, "On catastrophic forgetting and mode collapse in generative adversarial networks," in IJCNN, 2020.
- [186] K. J. Liang, C. Li, G. Wang, and L. Carin, "Generative adversarial network training is a continual learning problem," arXiv preprint arXiv:1811.11083, 2018.
- [187] H. Chen, Y. Wang, C. Xu, Z. Yang, C. Liu, B. Shi, C. Xu, C. Xu, and Q. Tian, "Data-free learning of student networks," in ICCV, 2019
- [188] K. Binici, N. T. Pham, T. Mitra, and K. Leman, "Preventing catastrophic forgetting and distribution mismatch in knowledge distillation via synthetic data," in WACV, 2022.
- [189] K. Binici, S. Aggarwal, N. T. Pham, K. Leman, and T. Mitra, "Robust and resource-efficient data-free knowledge distillation by generative pseudo replay," in AAAI, 2022
- [190] K. Do, T. H. Le, D. Nguyen, D. Nguyen, H. Harikumar, T. Tran, S. Rana, and S. Venkatesh, "Momentum adversarial distillation: Handling large distribution shifts in data-free knowledge distillation," NeurIPS, 2022.
- [191] G. Patel, K. R. Mopuri, and Q. Qiu, "Learning to retain while acquiring: Combating distribution-shift in adversarial data-free knowledge distillation," in CVPR, 2023.
- [192] M. Zhai, L. Chen, F. Tung, J. He, M. Nawhal, and G. Mori, "Lifelong gan: Continual learning for conditional image generation," in ICCV, 2019.
- [193] M. Zhai, L. Chen, and G. Mori, "Hyper-lifelonggan: Scalable lifelong learning for image conditioned generation," in CVPR, 2021.
- [194] J. Ramapuram, M. Gregorova, and A. Kalousis, "Lifelong gener-ative modeling," *Neurocomputing*, 2020.
- [195] F. Ye and A. G. Bors, "Lifelong mixture of variational autoencoders," TNNLS, 2021.
- [196] -, "Continual variational autoencoder learning via online cooperative memorization," in ECCV, 2022.
- [197] J. Ho, A. Jain, and P. Abbeel, "Denoising diffusion probabilistic models," NeurIPS, 2020.
- [198] C. Saharia, W. Chan, S. Saxena, L. Li, J. Whang, E. L. Denton, K. Ghasemipour, R. Gontijo Lopes, B. Karagol Ayan, T. Salimans et al., "Photorealistic text-to-image diffusion models with deep language understanding," NeurIPS, 2022.
- [199] E. Zhang, K. Wang, X. Xu, Z. Wang, and H. Shi, "Forget-menot: Learning to forget in text-to-image diffusion models," arXiv preprint arXiv:2303.17591, 2023.
- [200] A. Heng and H. Soh, "Selective amnesia: A continual learning approach to forgetting in deep generative models," arXiv preprint arXiv:2305.10120, 2023.
- [201] K. Khetarpal, M. Riemer, I. Rish, and D. Precup, "Towards continual reinforcement learning: A review and perspectives,' Journal of Artificial Intelligence Research, vol. 75, 2022.
- [202] M. Igl, G. Farquhar, J. Luketina, W. Boehmer, and S. Whiteson, "Transient non-stationarity and generalisation in deep reinforcement learning," in ICLR, 2021.
- [203] Z. Daniels, A. Raghavan, J. Hostetler, A. Rahman, I. Sur, M. Piacentino, and A. Divakaran, "Model-free generative replay for lifelong reinforcement learning: Application to starcraft-2," 2022.
- [204] J.-B. Gaya, T. Doan, L. Caccia, L. Soulier, L. Denoyer, and R. Raileanu, "Building a subspace of policies for scalable continual learning," in ICLR, 2023.
- [205] J. Yoon, W. Jeong, G. Lee, E. Yang, and S. J. Hwang, "Federated continual learning with weighted inter-client transfer," in ICML, 2021.
- [206] S. P. Karimireddy, S. Kale, M. Mohri, S. Reddi, S. Stich, and A. T. Suresh, "Scaffold: Stochastic controlled averaging for federated learning," in ICML, 2020.
- N. Shoham, T. Avidor, A. Keren, N. Israel, D. Benditkis, L. Mor-[207] Yosef, and I. Zeitak, "Overcoming forgetting in federated learn-ing on non-iid data," *NeurIPS Workshop*, 2019.
- [208] W. Huang, M. Ye, and B. Du, "Learn from others and be yourself in heterogeneous federated learning," in CVPR, 2022.
- [209] C. Xu, Z. Hong, M. Huang, and T. Jiang, "Acceleration of federated learning with alleviated forgetting in local training," in ICLR, 2022.

- [210] G. Lee, M. Jeong, Y. Shin, S. Bae, and S.-Y. Yun, "Preservation of the global knowledge by not-true distillation in federated learning," NeurIPS, 2022.
- [211] K. Luo, X. Li, Y. Lan, and M. Gao, "Gradma: A gradient-memorybased accelerated federated learning with alleviated catastrophic forgetting," in CVPR, 2023. [212] L. Qu, Y. Zhou, P. P. Liang, Y. Xia, F. Wang, E. Adeli, L. Fei-Fei,
- and D. Rubin, "Rethinking architecture design for tackling data heterogeneity in federated learning," in CVPR, 2022. [213] J. Dong, L. Wang, Z. Fang, G. Sun, S. Xu, X. Wang, and Q. Zhu,
- "Federated class-incremental learning," in CVPR, 2022.
- [214] D. Qi, H. Zhao, and S. Li, "Better generative replay for continual federated learning," in ICLR, 2023
- [215] Y. Ma, Z. Xie, J. Wang, K. Chen, and L. Shou, "Continual federated learning based on knowledge distillation," in IJCAI, 2022.
- [216] K. Audhkhasi, G. Saon, Z. Tüske, B. Kingsbury, and M. Picheny, "Forget a bit to learn better: Soft forgetting for ctc-based automatic speech recognition." in Interspeech, 2019.
- [217] T. Shibata, G. Irie, D. Ikami, and Y. Mitsuzumi, "Learning with
- selective forgetting," in *IJCAI*, 2021.
  [218] E. Nikishin, M. Schwarzer, P. D'Oro, P.-L. Bacon, and A. Courville, "The primacy bias in deep reinforcement learning," in ICML, 2022
- [219] B. Han, G. Niu, X. Yu, Q. Yao, M. Xu, I. Tsang, and M. Sugiyama, "Sigua: Forgetting may make learning with noisy labels more robust," in ICML, 2020.
- [220] A. Jaiswal, D. Moyer, G. Ver Steeg, W. AbdAlmageed, and P. Natarajan, "Invariant representations through adversarial forgetting," in AAAI, 2020.
- [221] L. Gravitz, "The importance of forgetting," Nature, 2019.
- [222] S. Baik, S. Hong, and K. M. Lee, "Learning to forget for metalearning," in CVPR, 2020.
- [223] H. Zhou, A. Vani, H. Larochelle, and A. Courville, "Fortuitous forgetting in connectionist networks," in ICLR, 2022.
- B. Kim, H. Kim, K. Kim, S. Kim, and J. Kim, "Learning not to [224] learn: Training deep neural networks with biased data," in CVPR, 2019
- [225] P. J. Bevan and A. Atapour-Abarghouei, "Skin deep unlearning: Artefact and instrument debiasing in the context of melanoma classification," in ICML, 2022.
- [226] Y. Chen, S. Zhang, and B. K. H. Low, "Near-optimal task selection for meta-learning with mutual information and online variational bayesian unlearning," in AISTATS, 2022.
- [227] L. Wang, M. Zhang, Z. Jia, Q. Li, C. Bao, K. Ma, J. Zhu, and Y. Zhong, "Afec: Active forgetting of negative transfer in continual learning," NeurIPS, 2021. [228] L. Bourtoule, V. Chandrasekaran, C. A. Choquette-Choo, H. Jia,
- A. Travers, B. Zhang, D. Lie, and N. Papernot, "Machine unlearning," in SSP, 2021.
- [229] T. T. Nguyen, T. T. Huynh, P. L. Nguyen, A. W.-C. Liew, H. Yin, and Q. V. H. Nguyen, "A survey of machine unlearning," 2022.
- [230] A. Mantelero, "The eu proposal for a general data protection regulation and the roots of the 'right to be forgotten'," Computer Law & Security Review, 2013.
- [231] Y. Wu, E. Dobriban, and S. Davidson, "DeltaGrad: Rapid retraining of machine learning models," in ICML, 2020.
- [232] A. Sekhari, J. Acharya, G. Kamath, and A. T. Suresh, "Remember what you want to forget: Algorithms for machine unlearning,' NeurIPS, 2021.
- [233] E. Ullah, T. Mai, A. Rao, R. A. Rossi, and R. Arora, "Machine unlearning via algorithmic stability," in COLT, 2021.
- [234] H. Yan, X. Li, Z. Guo, H. Li, F. Li, and X. Lin, "Arcane: An efficient architecture for exact machine unlearning," in IJCAI, 2022.
- [235] C. Guo, T. Goldstein, A. Hannun, and L. van der Maaten, "Certified data removal from machine learning models," in ICML, 2020.
- [236] A. Golatkar, A. Achille, and S. Soatto, "Eternal sunshine of the spotless net: Selective forgetting in deep networks," in CVPR, 2020.
- [237] Q. P. Nguyen, B. K. H. Low, and P. Jaillet, "Variational bayesian unlearning," NeurIPS, 2020.
- [238] R. Mehta, S. Pal, V. Singh, and S. N. Ravi, "Deep unlearning via randomized conditionally independent hessians," in CVPR, 2022.
- [239] M. Du, Z. Chen, C. Liu, R. Oak, and D. Song, "Lifelong anomaly detection through unlearning," in SIGSAC, 2019.
- Z. Ma, Y. Liu, X. Liu, J. Liu, J. Ma, and K. Ren, "Learn to forget: [240] Machine unlearning via neuron masking," IEEE Transactions on Dependable and Secure Computing, 2022.

- [241] G. Wu, M. Hashemi, and C. Srinivasa, "Puma: Performance unchanged model augmentation for training data removal," in AAAI, 2022.
- [242] Y. Liu, M. Fan, C. Chen, X. Liu, Z. Ma, L. Wang, and J. Ma, "Backdoor defense with machine unlearning," in *IEEE INFOCOM* 2022, 2022.
- [243] H. Shin, J. K. Lee, J. Kim, and J. Kim, "Continual learning with deep generative replay," *NeurIPS*, vol. 30, 2017.
- [244] M. Riemer, I. Cases, R. Ajemian, M. Liu, I. Rish, Y. Tu, and G. Tesauro, "Learning to learn without forgetting by maximizing transfer and minimizing interference," *ICLR*, 2019.
- [245] Y. Liu, B. Schiele, and Q. Sun, "Rmm: Reinforced memory management for class-incremental learning," *NeurIPS*, 2021.
- [246] F.-K. Sun, C.-H. Ho, and H.-Y. Lee, "Lamol: Language modeling for lifelong language learning," in *ICLR*, 2020.
- [247] A. Iscen, J. Zhang, S. Lazebnik, and C. Schmid, "Memory-efficient incremental learning through feature adaptation," in ECCV, 2020.
- [248] F. Zhu, X.-Y. Zhang, C. Wang, F. Yin, and C.-L. Liu, "Prototype augmentation and self-supervision for incremental learning," in *CVPR*, 2021.
- [249] K. Zhu, W. Zhai, Y. Cao, J. Luo, and Z. Zha, "Self-sustaining representation expansion for non-exemplar class-incremental learning," in CVPR, 2022.
- [250] B. Zhao, K. R. Mopuri, and H. Bilen, "Dataset condensation with gradient matching," in *ICLR*, 2021.
- [251] M. Wortsman, V. Ramanujan, R. Liu, A. Kembhavi, M. Rastegari, J. Yosinski, and A. Farhadi, "Supermasks in superposition," *NeurIPS*, 2020.
- [252] T. Konishi, M. Kurokawa, C. Ono, Z. Ke, G. Kim, and B. Liu, "Parameter-level soft-masking for continual learning," *ICML*, 2023.
- [253] H. Kang, R. J. L. Mina, S. R. H. Madjid, J. Yoon, M. Hasegawa-Johnson, S. J. Hwang, and C. D. Yoo, "Forget-free continual learning with winning subnetworks," in *ICML*, 2022.
- [254] J. Frankle and M. Carbin, "The lottery ticket hypothesis: Finding sparse, trainable neural networks," in *ICLR*, 2019.
- [255] M. B. Gurbuz and C. Dovrolis, "Nispa: Neuro-inspired stabilityplasticity adaptation for continual learning in sparse networks," in *ICML*, 2022.
- [256] R. Aljundi, P. Chakravarty, and T. Tuytelaars, "Expert gate: Lifelong learning with a network of experts," in CVPR, 2017.
- [257] D.-W. Zhou, Q.-W. Wang, H.-J. Ye, and D.-C. Zhan, "A model or 603 exemplars: Towards memory-efficient class-incremental learning," in *ICLR*, 2023.
- [258] Z. Hu, Y. Li, J. Lyu, D. Gao, and N. Vasconcelos, "Dense network expansion for class incremental learning," in CVPR, 2023, pp. 11858–11867.
- [259] Y. Wen, D. Tran, and J. Ba, "Batchensemble: an alternative approach to efficient ensemble and lifelong learning," in *ICLR*, 2023.
  [260] S. Jung, H. Ahn, S. Cha, and T. Moon, "Continual learning with
- [260] S. Jung, H. Ahn, S. Cha, and T. Moon, "Continual learning with node-importance based adaptive group sparse regularization," *NeurIPS*, 2020.
- [261] Y. Guo, W. Hu, D. Zhao, and B. Liu, "Adaptive orthogonal projection for batch and online continual learning," in AAAI, 2022.
- [262] A. F. Akyürek, E. Akyürek, D. Wijaya, and J. Andreas, "Subspace regularizers for few-shot class incremental learning," in *ICLR*, 2022.

## APPENDIX A CONTINUAL LEARNING

#### A.1 Task-aware CL

Existing works proposed for solving task-aware CL have five major research branches: memory-based, architecturebased, regularization-based, subspace-based, and Bayesianbased CL methods. We give an overall framework in Fig. 1. We present the details of each class method in the following.

A.1.0.1 **Memory-based Method**: Memory-based method keeps a *memory buffer* that stores the data examples from previous tasks and replay those examples during learning new tasks, representative works include [15], [23], [76], [243], [244]. It can be further categorized into: (1) raw memory replay; (2) memory sample selection; (3) generative replay; (4) compressed memory replay. Next, we discuss each direction in detail.

*Raw Sample Replay:* These methods save a small amount of data from previous tasks and trains the model with the new task. A key issue in this type of approach is how to select raw samples to store in the memory buffer. Current research works contain random selection [76] and selection based on heuristic rules [22], [23]. The random selection method randomly saves some raw samples into the memory, and performs replay [76] or constraints [14], [15] when learning a new task. For example, GEM [14] and A-GEM [15] use the memory buffer data losses as inequality constraints to constrain their increase but allow their decrease to mitigate forgetting. Meta Experience Replay (MER) [244] uses meta-learning to encourage information transfer from previous tasks and minimize interference. DER++ [16] found that replaying old data with soft labels is significantly better than one-hot labels.

Memory Sample Selection: These simplest methods to mitigate forgetting is to randomly store some examples for replay. However, this may lead to sub-optimal performance since random selection overlooks the informativeness of each sample. The heuristic selection selects samples for storage based on certain rules. e.g., iCaRL [19] selects the samples closest to each category cluster center. Some works choose the samples closest to the decision boundary of each class [22], [23] or make the sample diversity in memory the highest [20], [21]. GCR [17] selects the corset that best represents the gradients produced by past data. Sun et al. [18] model and regularize the influence of each selected example on the future. In addition, the above schemes of static memory allocation (fixed total capacity or storing a specific number of samples per class) may also lead to suboptimal performance. RMM [245] proposes a reinforcement learning based strategy to automatically allocate capacity for old and new classes.

*Generative Replay:* When privacy concerns restrict the storage of raw memory data, generative replay provides an alternative approach in CL to replay previous task data. The main concept behind generative replay is to train a generative model capable of capturing and remembering the data distribution from previous tasks. Instead of storing raw samples, the generative model is used to generate synthetic samples representative of the old tasks [246]. The representative works in this line involve using different generative models, include GAN-based meth-

ods [24], [25], AutoEncoder-based methods [26], Diffusion-based model [27], and Model-inversion [28].

*Compressed Memory Replay:* In scenarios where storage constraints are stringent on edge devices, memory efficiency becomes a crucial consideration. Several research efforts have aimed to improve memory efficiency in CL by employing different strategies. For example, instead of directly storing high-resolution images, one approach is to store *feature representations* [29], [30], [247] or *feature prototype* extracted from the image [248], [249], or compress the high-fidelity image into a low-fidelity image (JPEG) for storage [31], [32]. Recently, dataset condensation has emerged as a promising approach for compressing and condensing datasets, as demonstrated by works such as [35], [250]. Drawing inspiration from data distillation techniques, many CL methods adopt the strategy of storing *condensed samples* from old tasks in memory for replay [33], [34].

A.1.0.2 **Architecture-based Method**: Architecturebased methods in CL [36], [37], [38] involve updating the network architecture during the learning process to retain previously acquired knowledge. These methods aim to adapt the model's architecture to accommodate new tasks while preserving the knowledge from previous tasks. Based on whether the model parameters expand with the number of tasks, architecture-based methods can be categorized into two types: fixed-capacity and capacity-increasing methods.

Fixed-Capacity: In these methods, the amount of CL model's parameters does not increase with the number of tasks, and each task selects a sub-network from the CL model to achieve knowledge transfer and reduce the forgetting caused by sub-network updates. Common subnetwork selection techniques include masking [39], [40], [41], and pruning [42], [43], [44]. On the one hand, the maskbased method isolates the update of important neurons or parameters of old tasks during the backpropagation of the new task, thereby alleviating the forgetting of old tasks. A representative method, HAT [39] proposes a task-based binary/hard attention mask mechanism on neurons instead of parameters. Unlike HAT, which requires task identification during testing, SupSup [251] proposes a gradientbased optimization strategy, which can automatically infer tasks and find the learned optimal mask during testing. In addition, different from the above-mentioned hard mask methods that monopolize the sub-network, which hinders knowledge transfer and has the problem of excessive consumption of network capacity by old tasks, SPG [252] proposes a soft mask mechanism that uses the importance of old task parameters as a mask to constrain the backpropagation gradient flow updates to important parameters. On the other hand, similar to the mask mechanism, the pruning-based method freezes important parameters to avoid forgetting after the old tasks are learned, and reinitializes unimportant parameters to learn new tasks. PackNet [43] iteration performs pruning of a well-trained base network and maintains the binary sparse mask. Similarly, WSN [253] selects an optimal sub-network (winning ticket) for each task based on the Lottery Ticket Hypothesis [254]. Finally, unlike all the above methods that start masking or pruning from a densely connected network, although NISPA [255] also fixes the total number of neurons, it only starts learning tasks from a sparsely connected network, and then continuously increases the connections between neurons to learn new tasks.

Capacity-Increasing: a fixed capacity CL model may face limitations in accommodating new tasks as the number of tasks increases. This can restrict the plasticity of new tasks due to insufficient remaining network capacity. To overcome this challenge, dynamic capacity methods have been proposed. These methods augment the CL model by introducing task-specific new parameters for each new task while freezing the parameters associated with old tasks. By doing so, dynamic capacity methods aim to prevent forgetting while allowing the model to adapt and learn new tasks effectively [36], [38], [45], [46]. For example, PNN [36] employs an independent network branch for each task, where the input of the new task branch is the output from the old task branch, enabling knowledge transfer between tasks. ExpertGate [256], MEMO [257], and DNE [258] also add task-specialized experts/blocks/layers for each new task, respectively. BatchEnsemble [259] freezes the backbone network after learning the first task, and learns two independent rank-one matrices for each new task. However, it also limits knowledge transfer between tasks starting from the second task.

A.1.0.3 **Regularization-based Method**: Regularization-based methods in CL involve the addition of regularization loss terms to the training objective to prevent forgetting of previously learned knowledge [47], [48], [49]. These methods aim to constrain the model's parameter updates during the learning process to ensure that valuable information from past tasks is retained. Regularization-based methods can be further divided into two subcategories: penalizing important parameter updates and knowledge distillation using a previous model as a teacher.

*Penalize Parameter Updates:* Some works alleviate forgetting by penalizing parameter updates that are important for old tasks. For example, EWC [47] calculates regularization terms by approximating Fisher information matrix (FIM). MAS [50] takes the cumulative update of the parameters as a penalty term. SI [48] computes parameter importance using the path integral of gradient vector fields during parameter updating. Rwalk [22] can be seen as a generalized version of SI and EWC++. UCL [51] proposes an uncertain regularization based on the Bayesian online learning framework. AGS-CL [260] proposes two group sparsity penalties based on node importance as regularization terms.

*Knowledge-Distillation-Based:* Inspired by knowledge distillation [52], several methods in CL incorporate a distillation loss between the network of the previous task (referred to as the teacher) and the network of the current task (referred to as the student) to mitigate forgetting. One method that follows this approach is Learning without Forgetting (LwF) [53], which considers the soft targets generated by the teacher network as additional learning objectives for the student model. By treating the soft targets as valuable information, LwF enables the current model to learn from the knowledge of the previous model, reducing the risk of forgetting. Building upon LwF, LwM [54] leverages the attention mechanism of the previous network to guide the training of the current network. The attention of the teacher network helps the student model focus on relevant features and retain important knowledge from past tasks. Another method, BMC [55], takes a different approach by training multiple expert models simultaneously on disjoint sets of tasks. These expert models are then aggregated through knowledge distillation, which involves transferring knowledge from the expert models to a single student model. On the other hand, in distillation-based CL methods, the ideal scenario would involve using the raw data of old tasks to extract the knowledge of the teacher model and distill it to the student model. However, accessing the raw data of old tasks is often not feasible due to data privacy concerns. Consequently, existing approaches utilize proxy data as a substitute for distillation. One such method is LwF [53], which uses the current task data as a proxy for distillation. Another approach, GD [56], utilizes large-scale unlabeled data from the wild as a proxy for distillation.

A.1.0.4 **Subspace-based Method**: Subspace-based methods in CL aim to address the issue of interference between multiple tasks by conducting learning in separate and disjoint subspaces. Subspace-based methods can be categorized into two types based on how the subspaces are constructed: orthogonal gradient subspace and orthogonal feature subspace methods.

Orthogonal Gradient Subspace: These methods require that the parameter update direction of the new task is orthogonal to the gradient subspace of the old tasks, ensuring minimal interference between tasks. OGD [57] proposes updating the CL model in a gradient subspace orthogonal to the subspace of the old tasks. PCAOGD [58] is an extension of OGD that only stores the top principal components of gradients for each task. ORTHOG-SUBSPACE [59] learns different tasks in different orthogonal (low-rank) subspaces to minimize interference.

Orthogonal Feature Subspace: These require that the parameter update direction of the new task is orthogonal to the subspace crossed by the input (feature) of the old task. OWM [60] proposes that when learning a new task, network parameters are only updated in a direction orthogonal to the subspace spanned by the inputs of all previous tasks. AOP [261] solves the problem of inaccurate input space estimation in OWM. GPM [61] proposes to construct subspace for past tasks, the network updates the network parameters taking gradient steps in the orthogonal direction to the gradient subspaces that are important for the past learned tasks. Deng et al. [62] propose a Flattening Sharpness for Dynamic Gradient Projection Memory (FS-DGPM) with soft weight on the basis of GPM to improve new task learning. TRGP [63] introduces a trust-region variant of GPM to tackle the challenge of balancing the learning of new tasks with preserving the knowledge of old tasks.

A.1.0.5 **Bayesian Method**: Bayesian methods provide a principled probabilistic framework for addressing CF and can be classified into three categories: (1) methods that constrain the update of weight parameter distributions, (2) methods that constrain the update in function space, and (3) methods that dynamically grow the CL model architecture in an adaptive and Bayesian manner. These Bayesian approaches offer effective strategies to mitigate CF by incorporating uncertainty estimation and regularization techniques, thereby enhancing the adaptability of the learning process. In the following paragraphs, we provide a

detailed discussion of each research direction.

Weight Space Regularization: Weight space regularization based methods model the parameter update uncertainty and enforce the model parameter (weight space) distribution when learning the new task is close to that of all the previously learned tasks, including [64], [65], [66]. Gaussian Residual Scoring (GRS) [67] extends Bayesian neural network to the non-stationary streaming data. Different from previous work, which updates the parameter posterior distribution recursively over the task sequence, posteriors via a single shared meta-model, improving the flexibility in representing the current task and previous tasks. Natural Continual Learning (NCL) [69] combines Bayesian inference with gradient projection methods.

Function Space Regularization: Different from weight space regularization which constrains the weight update, the function space regularization regulates the CL function update in the function space. Functional Regularisation of Memorable Past (FROMP) [70] enforce the posterior distribution over function space (instead of weight space) of the new task to be close to that of the all the previously learned task with Gaussian process. In contrast to previous works that primarily emphasize either parameter or function space regularization, Functional Regularized Continual Learning (FRCL) [71] takes a different approach by focusing on constraining neural network predictions to prevent significant deviations from solutions to previous tasks. Variational Auto-Regressive Gaussian Processes (VAR-GPs) [72] further proposes a framework through a principled posterior updating mechanism to naturally model the cross-task covariances. Sequential function-space variational inference (S-FSVI) [73] presents a framework for addressing CL by formulating it as sequential function-space variational inference. This approach offers several advantages, including the ability to employ more flexible variational distributions and more effective regularization techniques.

Bayesian Architecture Expansion: Bayesian architecture growing methods employ a probabilistic and Bayesian approach to dynamically expand the CL model. By leveraging Bayesian principles, these methods enable the CL model to incrementally grow and adapt to new tasks or data while preserving previously learned knowledge. This probabilistic framework facilitates the flexible and principled expansion of the model's architecture, allowing it to accommodate increasing complexity and variability in the learning process. Kumar et al. [74] introduce a principled framework for CL that incorporates both variational Bayes and a nonparametric Bayesian modeling paradigm. Their approach enables the continual learning of neural network structures, offering a systematic methodology for adapting and expanding the network architecture over time. Moreover, the work by Mehta et al. [75] introduces IBP-WF, a method that leverages a principled Bayesian nonparametric approach, to dynamically expand the network architecture based on the task complexity. This approach allows the model to scale and accommodate increasing demands and intricacies of the learning tasks, ensuring efficient and effective adaptation throughout the CL process.

#### A.2 Few-shot CL

In order to tackle the forgetting problem within the context of few-shot CL, existing approaches employ various techniques, including metric learning, meta-learning, and parameter regularization. These techniques will be elaborated upon in the following.

A.2.0.1 Metric Learning-Based: These methods perform classification by class prototypes. To avoid forgetting, the prototype of the new class should be separable from the old class [105], and the prototype of the old class should not change drastically during the adjustment process of the new class [107]. TOPIC [104] first defines the benchmark-setting of few-shot class-incremental learning (FSCIL), which represents the topological structure of different classes in the feature space, and alleviates the forgetting of old classes by keeping the topology stable. To alleviate forgetting, DSN [103] estimates the distribution of classes in the current task. In a new task, feature vectors are sampled from old class distributions for replay. Another two approaches, C-FSCIL [106] and FSCIL [107] try to reduce interference between prototypes. C-FSCIL maps input images to quasiorthogonal prototypes to minimize task interference. Also, FSCIL pre-assigns and fixes the feature prototype classifier, and trains a projection layer to project the sample features of each class onto the assigned prototype, thereby avoiding the interference between classes and the problem of forgetting.

A.2.0.2 *Meta-Learning-Based*: These methods simulate the inference phase during training so that CL models can quickly adapt to unseen new classes to solve few-shot CL. LIMIT [108] and MetaFSCIL [109] split the base task into multiple 'fake'-incremental tasks, so that the model has the learning ability of FSCIL tasks. Specifically, MetaFSCIL directly considers the adaptability of new tasks and the stability of old tasks as its primary objectives for meta-learning. When MetaFSCIL trains on a new class, it evaluates the performance on all encountered classes as a meta-objective. By reducing the loss associated with the meta-objective, MetaFSCIL minimizes forgetting of the old tasks.

A.2.0.3 *Parameter Regularization-Based*: These methods employ various strategies to address the forgetting problem by penalizing parameter updates that are important for old tasks. For example, FSLL [110] and WaRP [111] adopt an approach where certain crucial parameters are frozen during training, while the remaining parameters are fine-tuned specifically for the few-shot task. Another approach, Subspace Regularization [262], introduces a subspace regularization that encourages the weights of new classes to be close to the subspace spanned by the weights of existing classes.