Improving Zero-Shot Text Matching for Financial Auditing with Large Language Models

Lars Hillebrand* Armin Berger* Tobias Deußer[†] lars.patrick.hillebrand@iais.fraunhofer.de Fraunhofer IAIS Sankt Augustin, Germany Tim Dilmaghani Mohamed Khaled Bernd Kliem Rüdiger Loitz PricewaterhouseCoopers GmbH Düsseldorf, Germany Maren Pielka David Leonhard Christian Bauckhage[†] Rafet Sifa[†] Fraunhofer IAIS Sankt Augustin, Germany

ABSTRACT

Auditing financial documents is a very tedious and time-consuming process. As of today, it can already be simplified by employing AI-based solutions to recommend relevant text passages from a report for each legal requirement of rigorous accounting standards. However, these methods need to be fine-tuned regularly, and they require abundant annotated data, which is often lacking in industrial environments. Hence, we present ZeroShotALI, a novel recommender system that leverages a state-of-the-art large language model (LLM) in conjunction with a domain-specifically optimized transformer-based text-matching solution. We find that a two-step approach of first retrieving a number of best matching document sections per legal requirement with a custom BERT-based model and second filtering these selections using an LLM yields significant performance improvements over existing approaches.

CCS CONCEPTS

Information systems → Recommender systems; Information extraction; Language models.

KEYWORDS

Large Language Models, Recommender System, Text Matching

ACM Reference Format:

Lars Hillebrand, Armin Berger, Tobias Deußer, Tim Dilmaghani, Mohamed Khaled, Bernd Kliem, Rüdiger Loitz, Maren Pielka, David Leonhard, Christian Bauckhage, and Rafet Sifa. 2023. Improving Zero-Shot Text Matching for Financial Auditing with Large Language Models. In ACM Symposium on Document Engineering 2023 (DocEng '23), August 22–25, 2023, Limerick, Ireland. ACM, New York, NY, USA, 4 pages. https://doi.org/10.1145/3573128.3609344

1 INTRODUCTION

The annual disclosure of corporate financial statements plays a vital role in informing the public about a company's financial situation and future prospects. The published documents contain detailed

DocEng '23, August 22-25, 2023, Limerick, Ireland

© 2023 Copyright held by the owner/author(s).

ACM ISBN 979-8-4007-0027-9/23/08.

https://doi.org/10.1145/3573128.3609344

information about its financial stability, productivity, and profitability and thus influence external investor's decisions. Due to their economic significance, these documents are highly regulated. On an annual basis, trained auditors thoroughly introspect and proofread the mandatory disclosures and ensure their compliance according to the legal requirements of the applicable accounting standard, e.g. IFRS (International Financial Reporting Standards). This manual examination process requires high-grade expert knowledge and experience and proves to be inherently time-consuming and prone to human error. The regulatory requirements of IFRS and other accounting standards are generally presented as a large collection of individual checklist items. For each item, the assigned auditor has to identify the relevant text segments in the financial report before answering the completeness and correctness questions raised by the requirement. The first retrieval task is particularly tedious, considering the report size and the number of items in the standard.

To alleviate this tedious process, we have previously introduced a tool called Automated List Inspection (ALI) [15], a recommender system linking paragraphs in a financial document to their corresponding requirements. In light of the recent advances of LLMs , we aim to examine whether domain-specific solutions are still required or can be augmented by LLMs in such a recommender context. Therefore, we compare different architectures that leverage GPT-4 [12], a state-of-the-art LLM, for the task of auditing financial documents. Considering the heterogeneous performance gains of GPT-4 reported in OpenAI's technical report, we investigate the potential and limitations of LLMs in the domain of financial auditing. In this work, we focus on the task of matching relevant text segments from financial statements to concrete legal requirements from an accounting standard.

Therefore, our contributions are introducing a novel method, called ZeroShotALI, which enables zero-shot text matching between new financial reports and unseen legal requirements based on a pretrained SentenceBERT [14] model from [3] and GPT-4 [12], and we evaluate multiple strong baselines, e.g. combining a vector store-based architecture utilizing OpenAI's Ada embeddings with GPT-4.

2 RELATED WORK

To capture the field of related work, we briefly look at two areas of research: The use of natural language processing (NLP) in the financial domain and the use of OpenAI's GPT models in particular.

The large field of financial NLP and the subfield of automated auditing have been of interest to researchers for several years. In 2019 we introduced the Automated List Inspection (ALI) tool [15], a

^{*}Both authors contributed equally to this research.

[†]The authors are also affiliated with the University of Bonn in Germany.

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

supervised recommender system that ranks textual components of financial documents according to the requirements of established regulatory frameworks, such as IFRS. Subsequently, in [13], we enhanced ALI by utilizing a pre-trained BERT language model developed by [7] to encode text segments. With [3], we introduced a more general framework for this task. Regarding a more detailed method for extracting information pertaining to automatic consistency checks of financial disclosures, in [9], we introduced KPI-Check. This BERT-based system utilizes a customized model for named entity and relation extraction, as presented in our previous work, [8], to automatically identify and validate semantically equivalent key performance indicators in financial reports. Similarly, in [5], we studied the KPI extraction task on an English dataset which was released together with the results. Within [1] we investigated how a plethora of pre-trained tabular models can check the table and text consistency in financial reports. Another important aspect of financial auditing is the detection of contradictions in annual reports. In [6] we studied how such a task can be automated with a transformer-based model. As for the implementation of entire LLMs specialized in financial language, [17] introduced BLOOMBERGGPT, employing Bloomberg's extensive data sources and evaluating the model's performance on financial tasks and general LLM benchmarks.

As the GPT line of OpenAI is still relatively novel, research exploring its capabilities and limitations is still conducted. However some results have already been found in various domains. When it comes to finance, [4] demonstrated GPT-4's effectiveness in sentiment analysis, ESG analysis, corporate culture analysis, and Federal Reserve opinion analysis qualitatively using practical examples. Quantitative analysis was carried out by [11] who used ChatGPT to create financial recommendations for the Australian financial sector, finding, that ChatGPT failed to operate effectively with complex financial advise, requiring additional professional guidance.

3 METHODOLOGY

Formally, the task of assigning relevant text segments from a financial report to concrete requirements from an accounting standard can be defined as a text matching problem: For each legal requirement $r_j \in \mathcal{R}$, a list of relevant text segments from the report $s_i \in S$ (where S is the set of all paragraphs and \mathcal{R} is the set of all requirements) has to be predicted. The recommendation system has to assign relevance scores $n_{i,j} \in (0, 1)$ to every segment-requirement pair (s_i, r_j) . To obtain a classification from those scores, the top Ktext segments for each requirement are being selected as relevant.

Previous work has mostly approached this task as a multi-label classification problem, where a sigmoidal output layer predicts individual relevance scores for each pre-defined legal requirement. This problem formulation is inflexible with respect to unseen requirements, i.e. a full model re-training is required. Also, the semantic information contained in the actual requirement texts is neglected, since the requirements have been translated to numeric class ids.

To overcome these architectural shortcomings, we introduce ZeroShotALI. Following [3], we employ a text similarity based matching model that individually encodes text segments from the financial report as well as legal requirements from the accounting



Figure 1: Schematic visualization of the ZeroShotALI recommender system. A domain-adapted SentenceBERT model matches relevant financial report segments s to concrete legal requirements r based on cosine similarity before GPT-4 further enhances the final matching outcome.

standard before predicting matches based on semantic text similarity. Specifically, we leverage a domain-adapted SentenceBERT model as our initial text retrieval solution. It is a modification of the BERT language model [7] that encodes both the requirement text and the financial report text segment, using two BERT models with shared weights, and applies mean-pooling to obtain paragraph level embeddings s_i for text segment *i* and r_i for requirement *j*, respectively. Subsequently, the cosine similarity between these embeddings is computed to measure how well the report segment and legal requirement semantically match, resulting in a normalized similarity score between 0 and 1. For full architectural details and training procedures, we refer to [3]. To further improve the final matching performance, we augment the described SentenceBERT model with the state-of-the-art generative language model, GPT-4. In a first pre-filtering step, SentenceBERT retrieves the top 15 most relevant financial report segments for each requirement query *j*. Then, we prompt GPT-4 with these 15 segments and the requirement text as input to further narrow down the recommendations to the five best matching segments. The complete architecture is illustrated in Figure 1. We evaluate and compare the two-stage approach of ZeroShotALI with multiple baselines in the next section.

4 EXPERIMENTS

In the following, we introduce our custom data set, describe competing baseline methods and different LLM prompt designs, as well as evaluation metrics. Finally, we also discuss the results we obtained from our approaches.

4.1 Data

We obtained 10 IFRS-compliant reports from PwC as the data source for this paper, containing a total of 7097 text segments. The reports are labeled by auditors, who map the text segments in each report to one of the corresponding 1214 IFRS requirements. This process was done in multiple iterations by different domain experts, in order to assure a high annotation quality. Since, except for the SentenceBERT model, none of the four architectures require additional training, we only employ a test set to compare the different architectures. The fine-tuned SentenceBERT model has not been trained or evaluated on the employed test set to prevent data leakage. For more information on the domain data utilized to fine-tune the SentenceBERT model, we direct the reader to [3].

4.2 Baselines

We compare ZeroShotALI with (1) a plain SentenceBERT model as described in Section 3 without the GPT-4 filtering, (2) a vector database retrieval model employing OpenAI's Ada V1 or V2 embeddings, and (3) the same vector database approach combined with GPT-3.5 Turbo or GPT-4 as filtering models.

The vector database we use is Chroma DB. This open-source vector database combines a k-means clustering algorithm with the ClickHouse database management system to retrieve semantically similar text passages given an input query. For more details on the concept and an overview of similar applications, we refer to [2]. We embedded each of the 10 IFRS reports using either the lower dimensional Ada V1 or Ada V2 embeddings and stored them in the database separately so that each report could be accessed by its name, and we could query the system based on a specific report. For each query, we retrieved the top five most semantically similar text segments using their cosine similarity score.

The third set of systems consists of a vector database, Chroma DB, using V2 Embeddings and frozen LLMs, GPT-3.5 Turbo or GPT-4. These systems follow the idea of retrieval-augmented generation, which aims to provide LLMs with relevant information for a specific task instead of relying solely on the language model's parametric knowledge. As before, we retrieved the top 15 most relevant text segments for each query using Chroma DB. Then, we used these 15 segments as prompt input for the LLM, which was then tasked to return the five most relevant text segments for each requirement.

4.3 Effects of prompt design

For all architectures leveraging GPT-4 we evaluate the impact of prompt design on model performance. Prompt design refers to the format and phrasing of the task presented to the GPT-style LLMs. Building upon the findings of [10] regarding the effects of prompt phrasing on LLM performance, we conduct our evaluations by primarily investigating two factors: (1) the phrasing of the task and (2) the structure of the output allowed for the model's responses.

Our evaluation is as follows: We formulate a specific task for GPT-4, which involves the retrieval of the five most relevant text segments from a provided set of 15 segments, based on a given requirement. We then randomly sample 20 requirements from one of the 10 IFRS-compliant reports. Regarding the phrasing of the task, we find no significant impact on the quality of the model's

Table 1: Quantitative comparison of 4 different prompt setups for the text segment to requirement matching task. Reported metrics are defined in Section 4.4. The (bracketed blue) text shows the respective differences between prompts B and A as well as D and C.

Prompt \setminus in %	Sensitivity	MAP	F_1
А	36.92	26.38	23.75
В	35.54	26.00	23.75
C & D	23.57	22.62	17.05

A & (B): "(System: You are an expert auditor with perfect knowledge of the IFRS accounting standard.) Out of all document segments provided below which ones are the 5 most relevant for fulfiling the IFRS requirement? (Think step by step.) IFRS requirement: {requirement} document segments: {document} Your answer should only contain the ids of the relevant document segments. Example: ['1129', '1139', '1161', '829']. Your answer needs to be machine readable. Do not add any additional text."

C & (D): "System: You are an expert auditor with perfect knowledge of the IFRS accounting standard. Out of all document segments provided below which ones are the 5 most relevant for fulfilling the IFRS requirement? Explain for each requirement why you selected the 5 most relevant requirements. (Each should only be a sentence long.) Think step by step: IFRS requirement: {requirement} document segments: {document} Format your output complying to the following json schema: {explanation': The most relevant document segments ..., 'answer': ['1129', '1139', '1159', '1161', '829']}. Ensure that 'answer' is its own key in the json schema. Your answer needs to be machine readable."

responses, implying that variations in the way the task was presented did not substantially influence the model's performance. However, when examining the structure of the output allowed for the model's responses, we observe a notable effect. We categorize the types of outputs into two broad formats: "open-ended" and "closed." In the "open-ended" format, the model is permitted to provide explanations for its answers, while in the "closed" format, the model is restricted to returning the IDs of the five most relevant text segments. Interestingly, we find that the "closed" format yields improved performance compared to the "open-ended" format. Table 1 shows the four best performing prompts and their respective performance.¹ For all GPT-based experiments we leverage the best performing prompt design A.

4.4 Evaluation Metrics

To more accurately evaluate the performance of the four architectures, we employ the "mean-average-precision" (MAP) to comprehensively assess the performance of the recommender system across multiple queries. The average precision (AP) is calculated as

$$AP = \frac{1}{\min(\{K, A(r)\})} \sum_{i=1}^{K} (Precision(i) \cdot relevance(i))$$
(1)

where relevance(i) is 1 if requirement i is relevant and 0 if it is not, r is a given requirement, and A(r) are the annotated text segments for requirement r. In addition, we deploy the custom performance metric sensitivity, which is a slightly modified version of recall and considers whether the relevant segments are contained in the set of recommendations (see [15]). Precision and sensitivity are defined as

$$\operatorname{Precision}(r) = \frac{|P(r,K) \cap A(r)|}{K}, \text{ Sensitivity}(r) = \frac{|P(r,K) \cap A(r)|}{\min(\{K,A(r)\})}$$

¹Due to the stochastic nature of GPT-4 it is impossible to exactly reproduce results. We set the temperature parameter to 0, which reduces but does not remove stochasticity in the generation process.

Table 2: Test set results for the top 5 recommendation of relevant financial report segments for legal requirements of the IFRS accounting standard. ZeroShotALI outperforms all competing methods in mean sensitivity, mean average precision (MAP) and F₁ score.

Model \setminus in %	Sensitivity	MAP	F_1
Chroma (Ada V1)	14.00	7.12	9.12
Chroma (Ada V2)	25.73	17.33	13.15
Chroma (Ada V2) + GPT-3.5 Turbo	29.95	21.32	15.74
Chroma (Ada V2) + GPT-4	35.30	24.72	18.53
SentenceBERT (from [3])	52.12	39.00	27.69
ZeroShotALI (this work)	57.62	44.65	30.57

with P(r, K) being the top *K* recommended text segments for *r*. For our experiments, we choose K = 5, as this proves to deliver optimal results with respect to user experience. Finally, the conventional F_1 -score (with respect to the top-*K* predictions) is defined as the harmonic mean over precision and recall for a given requirement. All scores are averaged across the dataset to determine the overall performance.

4.5 Evaluation and Results

As depicted in Table 2, the performance analysis reveals that the two architectures based on SentenceBERT surpass the vector storebased architectures. Notably, ZeroSHotALI, combining Sentence-BERT with GPT-4, demonstrates the highest performance which can be attributed to several factors.

Firstly, the vector store-based architectures rely on embeddings from generically pre-trained language models that exhibit no domain specific fine-tuning and leverage approximate nearest-neighbor calculations to return text matches. In contrast, the SentenceBERT model was fine-tuned specifically for the task of retrieving semantically similar text passages within an auditing context. This custom training process enables SentenceBERT to capture the intricacies and nuances of the auditing domain, leading to more accurate and contextually relevant retrievals. The observed subpar performance of vector store-based architectures in our use cases raises an important question regarding the suitability of such systems in various applications. Currently, many applications leverage retrievalaugmented generation using vector databases, assuming that these systems can provide reliable results. However, our findings suggest that incorporating domain-specific, fine-tuned retrieval systems like SentenceBERT could significantly enhance the performance of such applications.

5 CONCLUSION AND FUTURE WORK

In this study, we conducted an extensive evaluation to explore the viability of employing a "frozen" LLM for auditing financial documents. Our assessment focused on implementing various architectures tailored to match the text of IFRS-compliant annual reports with legal requirements. The results of our analysis revealed that our proposed system, ZeroShotAli, which combines a domain-tuned SentenceBERT model with OpenAI's GPT4, outperforms other systems significantly. This finding underscores the advantage of deploying domain-specific solutions when indomain data is available, surpassing generic systems such as vector databases with general purpose embeddings. Our study accentuates the potential for substantial performance gains through the utilization of domain-specific approaches in the context of retrievalaugmented generation. This study identifies three key areas for future research: (1) deploying domain-specific fine-tuned LLMs for auditing purposes using open-source models like LLaMA, (2) exploring advanced prompt tuning methodologies such as Chain-of-Thought [16] or Tree-of-Thoughts [18] approaches, and (3) expanding the ZeroShotAli system to assess requirement completeness based on relevant text passages.

ACKNOWLEDGMENTS

This research has been partially funded by the Federal Ministry of Education and Research of Germany and the state of North-Rhine Westphalia as part of the Lamarr-Institute for Machine Learning and Artificial Intelligence.

REFERENCES

- Syed Musharraf Ali, Tobias Deußer, Sebastian Houben, Lars Hillebrand, Tim Metzler, and Rafet Sifa. 2023. Automatic Consistency Checking of Table and Text in Financial Documents. In Proc. NLDL.
- [2] Martin Aumüller, Erik Bernhardsson, and Alexander Faithfull. 2020. ANN-Benchmarks: A Benchmarking Tool for Approximate Nearest Neighbor Algorithms. *Information Systems* (2020).
- [3] David Biesner, Maren Pielka, Rajkumar Ramamurthy, Tim Dilmaghani, Bernd Kliem, Rüdiger Loitz, and Rafet Sifa. 2022. Zero-Shot Text Matching for Automated Auditing using Sentence Transformers. In Proc. ICML-A.
- [4] Yi Cao and Jia Zhai. 2023. Bridging the gap-the impact of ChatGPT on financial research. Journal of Chinese Economic and Business Studies (2023).
- [5] Tobias Deußer, Syed Musharraf Ali, Lars Hillebrand, Desiana Nurchalifah, Basil Jacob, Christian Bauckhage, and Rafet Sifa. 2022. KPI-EDGAR: A Novel Dataset and Accompanying Metric for Relation Extraction from Financial Documents. In Proc. ICMLA.
- [6] Tobias Deußer, Maren Pielka, Lisa Pucknat, Basil Jacob, Tim Dilmaghani, Mahdis Nourimand, Bernd Kliem, Rüdiger Loitz, Christian Bauckhage, and Rafet Sifa. 2023. Contradiction Detection in Financial Reports. In Proc. NLDL.
- [7] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In Proc. NAACL.
- [8] Lars Hillebrand, Tobias Deußer, Tim Dilmaghani, Bernd Kliem, Rüdiger Loitz, Christian Bauckhage, and Rafet Sifa. 2022. KPI-BERT: A joint Named Entity Recognition and Relation Extraction Model for Financial Reports. In Proc. ICPR.
- [9] Lars Hillebrand, Tobias Deußer, Tim Dilmaghani, Bernd Kliem, Rüdiger Loitz, Christian Bauckhage, and Rafet Sifa. 2022. Towards automating Numerical Consistency Checks in Financial Reports. In Proc. BigData.
- [10] Xiao Liu, Yuxuan He, Jianfeng Chen, Jianfeng Gao, and Li Deng. 2021. GPT Understands, Too. arXiv:2103.10385 (2021).
- [11] Ben Neilson. 2023. Artificial Intelligence Authoring Financial Recommendations: Comparative Australian Evidence. Journal of Financial Regulation (2023).
- [12] OpenAI. 2023. GPT-4 Technical Report. arXiv:2303.08774 (2023).
- [13] Rajkumar Ramamurthy, Maren Pielka, Robin Stenzel, Christian Bauckhage, Rafet Sifa, Tim Khameneh, Ulrich Warning, Bernd Kliem, and Rüdiger Loitz. 2021. ALiBERT: improved automated list inspection (ALI) with BERT. In *Proc. DocEng.*
- [14] Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks. In Proc. EMNLP-IJCNLP.
- [15] Rafet Sifa, Anna Ladi, Maren Pielka, Rajkumar Ramamurthy, Lars Hillebrand, Birgit Kirsch, David Biesner, Robin Stenzel, Thiago Bell, Max Lübbering, et al. 2019. Towards automated auditing with machine learning. In Proc. DocEng.
- [16] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. Advances in Neural Information Processing Systems 35 (2022), 24824–24837.
- [17] Shijie Wu, Ozan Irsoy, Steven Lu, Vadim Dabravolski, Mark Dredze, Sebastian Gehrmann, Prabhanjan Kambadur, David Rosenberg, and Gideon Mann. 2023. Bloomberggpt: A large language model for finance. arXiv:2303.17564 (2023).
- [18] Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L Griffiths, Yuan Cao, and Karthik Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. arXiv preprint arXiv:2305.10601 (2023).