PRE: Vision-Language Prompt Learning with Reparameterization Encoder

Anh Pham Thi Minh¹, An Duc Nguyen², Georgios Tzimiropoulos¹ ¹Queen Mary University of London, ²University of Oxford

t.pham@se22.qmul.ac.uk, an.nguyen@cs.ox.ac.uk, g.tzimiropoulos@qmul.ac.uk

Abstract-Large pre-trained vision-language models such as CLIP have demonstrated great potential in zero-shot transferability to downstream tasks. However, to attain optimal performance, the manual selection of prompts is necessary to improve alignment between the downstream image distribution and the textual class descriptions. This manual prompt engineering is the major challenge for deploying such models in practice since it requires domain expertise and is extremely time-consuming. To avoid non-trivial prompt engineering, recent work Context Optimization (CoOp) introduced the concept of prompt learning to the vision domain using learnable textual tokens. While CoOp can achieve substantial improvements over manual prompts, its learned context is worse generalizable to wider unseen classes within the same dataset. In this work, we present Prompt Learning with Reparameterization Encoder (PRE) - a simple and efficient method that enhances the generalization ability of the learnable prompt to unseen classes while maintaining the capacity to learn Base classes. Instead of directly optimizing the prompts, PRE employs a prompt encoder to reparameterize the input prompt embeddings, enhancing the exploration of task-specific knowledge from few-shot samples. Experiments and extensive ablation studies on 8 benchmarks demonstrate that our approach is an efficient method for prompt learning. Specifically, PRE achieves a notable enhancement of 5.60% in average accuracy on New classes and 3% in Harmonic mean [1] compared to CoOp in the 16-shot setting, all achieved within a good training time. Index Terms-prompt learning; vision-language models; CLIP.

I. INTRODUCTION

State-of-the-art visual recognition systems are typically built by extensive training on large-scale discrete labeled datasets to predict a predefined set of object categories. This process involves extracting relevant visual features utilizing advanced architectures such as ResNet [2] or ViT [3] and mapping them to discrete labels. Such a learning strategy concentrates on closed-set visual concepts, limiting the model's ability to recognize new categories unseen during training.

In recent years, large-scale vision-language models (VLMs) have brought new light on leveraging natural language supervision in visual recognition systems, enabling a wide exploration of open-set visual concepts [4]–[7]. Pretrained vision-language models with contrastive learning [5] [8] [9], exemplified by Contrastive Language-Image Pretraining (CLIP) models [9], have revolutionized the field by aligning images and their associated textual descriptions in the feature space via contrastive loss. By pre-training on large-scale image-text association datasets, CLIP gains diverse visual concepts and rich cross-modal representations that hold great potential to

TABLE I: Compared to existing methods on 8 datasets with 16-shot settings, PRE obtains a higher performance within good training time.

Methods	Prompts	Ac	curacy (Training Time	
	110111.011	Base	New	Н	
CLIP	hand-crafted	68.81	74.43	71.42	-
CoOp	textual	83.32	66.92	73.34	6ms/image
CoCoOp	textual+visual	80.89	70.99	74.47	160ms/image
ProGrad	textual	82.96	70.30	75.58	22ms/image
PRE	textual	82.14	71.90	76.22	6.2ms/image

be transferred to various tasks. As these VLMs evolve, a pivotal question arises: How can the valuable knowledge from pretraining be effectively adapted to downstream tasks?

In the initial study [9], prompt engineering has been utilized to bridge the gap between the pre-trained and downstream tasks without the need for additional fine-tuning adaptation. Typically, prompt engineering adds more meaningful context in textual class descriptions by using a set of manually selected prompts for the given task. For example, on the Oxford Pets dataset [10], employing a tuning prompt such as "a photo of a class, a type of pet." helps improve the accuracy performance [9] [11] [12] [13]. In this case, the prompt word "pet" indicates the context of the current task, thus providing a more precise description. However, prompt engineering relies on trial and error, demanding significant human effort for word tuning a slight change in wording could make a huge difference in performance, and does not guarantee the optimal prompts.

Following research in Natural Language Processing (NLP) [14], [15], many recent works, beginning with Context Optimization(CoOp) [16] have introduced the concept of prompt learning (soft prompts) to replace the hand-crafted prompts with a sequence of prompt embedding tokens. Then, these prompt tokens are learned by minimizing the distance between the visual features and prompt-based language features using a few training examples to provide more flexibility in the text encoding process. Despite significant improvements on fewshot classifications over zero-shot CLIP, a noticeable problem with CoOp-based methods is the poor generalization to the unseen (*New*) classes within the same dataset, *e.g.*, obtaining a worse performance in *New* classes than CLIP using handengineered prompts, as demonstrated in Table 1.

The soft prompt optimization in CoOp attempts to learn separate prompt tokens solely through the pre-trained knowledge embedded in the fixed parameters of CLIP's text encoder. Because of the fixed over-parameterization of CLIP and lack of training examples, naive prompt tuning would lead to overfitting the seen (Base) classes on specific datasets. Intuitively, we believe the values of prompt embeddings should be dependent on each other rather than independent, and their interdependence varies according to different downstream tasks. We need a trainable mechanism that jointly processes prompt embeddings. It could flexibly capture task-relevant dependencies within prompt tokens beyond the constraints of the frozen text encoder. Incorporating these associate-learned prompt tokens into the text encoder would make the optimization easier to find a more contextually generalizable prompt specific to the particular domain. This idea partly aligns with the reparameterizing method in the language domain where prefix embeddings undergo a shallow neural network and combine with the input embeddings through concatenation [14] [17]. Based on our hypothesis and inspired by the effectiveness of the reparameterizing method for language models, we introduce Prompt Learning with a Reparameterization Encoder (PRE). Our main contributions are as follows:

- We propose a more adaptable parameterization method for soft prompts. Instead of directly learning the prompts, PRE reparameterizes the original prompt embeddings utilizing a prompt encoder before feeding them into the Text Encoder. Different from the reparameterizing method in NLP which solely uses a bottle-neck Multilayer Perceptron (MLP), our prompt encoder incorporates a Bidirectional long shortterm memory network (BiLSTM). This BiLSTM not only serves as a parameterizing network as MLP but also exploits the domain-specific long-range dependencies in the prompt sequence. We further adopt a residual connection for the prompt encoder to avoid forgetting the original knowledge encoded by the pre-trained CLIP. This integration leads to improved generalization in *New* classes while retaining the capacity to effectively learn *Base* classes.
- We perform extensive ablation studies of PRE on eight classification datasets to analyze its characteristics. Specifically, several network architectures have been implemented in the prompt encoder, thus offering distinct benefits for different recognition tasks. The code is available at https://github.com/minhanh151/ResPro.

Main results: We assess the performance of PRE through extensive experimentation on the base-to-new generalization setting across eight image classification datasets. The evaluation results in Table 1 highlight the efficiency and effective-ness of PRE. Our method demonstrated substantial accuracy improvement for the *New* class compared to other methods while maintaining good training time.

II. RELATED WORK

A. Vision-language Models

The field of Vision-Language Models (VLM) has experienced significant progress in forming robust representations that can be effectively transferred to various downstream tasks [5]–[9], [18]–[22]. A typical vision-language model comprises three crucial components: an image encoder, a text encoder, and a loss function. In the past, researchers relied on manual image descriptors [23] [24] and pre-trained word vectors [25] with independently operated encoders for each modality. The pivotal transformation in vision-language models emerged with the widespread adoption of transformer architectures [26] [3] [27], contrastive representation learning [28]–[31], and web-scale training datasets [6] [9]. Transformer-based encoders revolutionize the field by allowing models to process visual and textual information in parallel while effectively capturing long-range dependencies. Contrastive representation learning has also shown its effectiveness in enhancing the discriminative capabilities of VLMs. Recent works such as CLIP [9], ALIGN [6], and DeCLIP [5] bridge the visionlanguage modalities by learning text encoder and image encoder jointly with a contrastive loss, using large imagecaption pairs datasets. Notably, CLIP showcases an impressive ability for zero-shot image recognition. Similar to the previous work CoOp and CoCoOp, we apply the pre-trained CLIP for knowledge transfer, aiming to facilitate the adaptation and deployment of such models in downstream datasets.

B. Prompt Learning

Prompt learning has emerged as a novel paradigm in NLP for exploiting pre-trained language models, gradually replacing the traditional fine-tuning transfer approach. The main idea of prompt learning is to formulate various NLP tasks as masked language modeling problems, adopting different templates (or prompts). Initially, prompt engineering involved manually designing prompts [32]-[36], but later works focused on automatically generating discrete [14], [15] or soft (continuous) prompts [37]-[40] in the natural language space. Although prompt learning has received considerable attention in NLP, its application in computer vision remains underexplored. In the context of Vision-Language Models like CLIP, human-crafted prompts based on class names are utilized to enable zero-shot visual recognition. Context Optimization (CoOp) [16] extended soft prompt optimization to VLMs, where a set of prompts is learned and used as input to the text encoder alongside the class name. However, CoOp suffers from weak generalization, as the learned prompts tend to overfit the seen classes and perform poorly in novel classes. To address CoOp's generalization limitations, later work Conditional Context Optimization (CoCoOp) [41] proposes a dynamic approach. It employs a small neural network to produce a visual feature from each input image, which is then combined with the learned prompts, making them input-specific and enhancing their adaptability. Furthermore, ProGrad [42] updates the prompts whose gradient is aligned to the "general knowledge" generated by the original prompts to improve prompt learning's robustness. Other approaches have tried to boost the generality of the unseen class by reducing the discrepancy between the learnable prompt and the manuallydefined prompt, such as KgCoOp [43], and LASP [43]. Our method, otherwise, does not use hand-crafted prompts in the learning process to obtain better generalization on novel classes.

Among the existing approaches, CoOp and CoCoOp are the most relevant methods to our proposed PRE and they can serve as the baseline models for PRE. Instead of directly learning the prompts like CoOp, the proposed PRE first passes the prompt tokens through a trainable encoder with a residual connection, enabling a flexible combination of the original prompt embeddings and embeddings projections. This approach leads PRE to outperform CoOp, particularly in handling unseen classes. Meanwhile, CoCoOp uses a lightweight neural network known as Meta-Net to improve its generalization. However, CoCoOp's Meta-Net takes the input image and generates input-conditional context tokens specific to each image. This process demands additional computation, which can be limiting, especially when dealing with large datasets or resource-constrained environments. Differently, PRE uses static prompts and does not add any inference cost since the prompts are pre-computed. The comprehensive evaluation demonstrates the effectiveness of PRE, which achieves better performance with a relatively short training period.

C. Reparameterization Methods

Recent studies in NLP [14], [38] explored the reparameterization of embeddings as a way to enhance the performance of prefix tuning and full model tuning for pre-trained Language Models. In these approaches, prefix embeddings undergo a shallow neural network and are combined with the input embeddings through concatenation. Most related to our work is Residual Prompt Tuning [17] which reparameterizes soft prompt embeddings using a Multilayer Perceptron (MLP) network with a residual connection to improve the performance and stability of prompt tuning for pre-trained Large-Language models. It significantly outperforms manually picked prompt engineering on the SuperGLUE benchmark [44] across T5-Large [45] and BERT-Base [46] language models. Motivated by the effectiveness of prompt tuning with learnable parameterizing networks for large language models, we exploit the impact of adding a lightweight encoder to learn context tokens with different network architectures and settings for better generalization in vision-language CLIP-like models. We found that MLP-based reparameterization leads to performance improvement in New classes, albeit at the cost of decreased performance in Base classes. In the PRE method, we propose a Bidirectional LSTM as the prompt encoder which demonstrates enhanced efficacy in maintaining performance stability across both Base and New classes.

III. METHODOLGY

A. Preliminaries

Our proposed method builds upon the Contrastive Language-Image Pre-training (CLIP) model [9], which is a well-known visual-language model trained on an extensive dataset of 400 million image-text pairs. CLIP contains two types of encoders: a visual encoder (ϕ) responsible for mapping images to visual embeddings and a textual encoder (θ) used for embedding corresponding textual information. During pretraining, CLIP trains the image and text encoders on enormous image-text pairs by contrastive loss, which tries to maximize the similarity between matching pairs while minimizing the similarity with mismatching pairs.

Prompt Engineering: For downstream recognition tasks, CLIP performs the zero-shot inference by employing handengineered prompts to generate textual class embeddings. Given set \mathcal{V} of \mathcal{C} class names, the class descriptions $\{\mathbf{t}_c\}_{c=1}^C$ are generated with the manually designed prompt template, such as "a class of a {class_name}". Then the class descriptions are passed through the text encoder $\theta(\cdot)$ to compute the class-specific textual embeddings (weight): \mathbf{w}_i^C = $\theta(\mathbf{t}_i^C)$. Given an image \mathbf{x} along with its label y, the image features are extracted with the visual encoder $\phi(\cdot)$: $\mathbf{f} = \phi(\mathbf{x})$. Then the prediction probability of the sample \mathbf{x} over the class labels is:

$$P(y = i \mid \mathbf{x}) = \frac{\exp(\cos(\mathbf{w}_i, \mathbf{f})/\tau)}{\sum_{j=1}^{C} \exp(\cos(\mathbf{w}_j, \mathbf{f})/\tau)}$$
(1)

where $cos(\cdot)$ denotes the cosine similarity and τ is a learnable temperature parameter in CLIP. Finally, the class label predicted for image **x** is given by $\tilde{y} = arg_{max} P(y|\mathbf{x})$.

Soft prompt learning: While calculating \mathbf{w}_i^C does not involve training with class-specific image data, enabling zeroshot recognition with any given class name, CLIP's reliance on fixed human-crafted prompt templates for generating textual embeddings results in limited adaptability to downstream tasks. An alternative way to generate the weight \mathbf{w}_i^C is soft prompt learning [14]-[16], which automatically learns a suitable prompt from a few samples on the target task. Recently, Context Optimization (CoOp) has utilized this soft prompt learning approach to learn prompts as a set of continuous context vectors for CLIP-like models. Specifically, CoOp introduces M context vectors $V = \{v_1, v_2, ..., v_M\}$ as the learnable prompt. The class token embedding c_i of the *i*-th class is then concatenated with the learnable context vector Vfor generating the prompts $\mathbf{p}_i = \{\mathbf{v}_1, \mathbf{v}_2, ..., \mathbf{v}_M, \mathbf{c}_i\}$. Let $\theta(\cdot)$ denote the text encoder and the prediction probability over the class labels of image x is computed as follows:

$$P(y = i \mid \mathbf{x}) = \frac{\exp(\cos(\theta(\mathbf{p}_i), \mathbf{f})/\tau)}{\sum_{j=1}^{C} \exp(\cos(\theta(\mathbf{p}_j), \mathbf{f})/\tau)}$$
(2)

The prompts can be learned by minimizing the cross-entropy loss:

$$\mathcal{L}_{VL} = -\sum_{c=1}^{C} \log P(c|\mathbf{x}) y_c \tag{3}$$

B. Prompt Learning with Reparameterization Encoder

While excelling in *Base* classes, conventional soft prompt learning (Section III.A) exhibits suboptimal results in novel classes. Specifically, CoOp achieves a significant improvement in *Base* accuracy compared to CLIP, e.g., 68.81% (CLIP)



Fig. 1: Prompt Learning with Reparameterization Encoder (PRE) is depicted in the following illustration: The original prompt embeddings V undergo projection using a trainable prompt encoder $\mathcal{F}(\cdot)$ (e.g. BiLSTM) equipped with a residual connection. This process enables the modeling of domain-specific sequential dependencies within the input prompt embeddings and acquires a new mapping for the soft prompts. The optimization process involves jointly tuning the prompt embeddings V and the parameters of the encoder $\mathcal{F}(\cdot)$.

vs 83.32% (CoOp). However, it performs worse on the New accuracy for unseen classes, e.g., 74.43% (CLIP) vs 66.92% (CoOp) (see Table 1).

In this work, we propose a more adaptable parameterization of soft prompts, achieved through the utilization of a prompt encoder (Fig. 1). This encoder can be trained on the downstream task to enable domain-specific modifications to the prompt embeddings before forwarding them into the fixed text encoder. Specifically, we project the original prompt embeddings V consisting of M prompt tokens $\{v_1, v_2, ..., v_M\}$ through the prompt encoder into a reparameterized sequence \tilde{V} as follows:

$$ilde{oldsymbol{V}} = [ilde{oldsymbol{v}}_1, ilde{oldsymbol{v}}_2, ..., ilde{oldsymbol{v}}_M] = [\mathcal{F}(oldsymbol{v}_1), \mathcal{F}(oldsymbol{v}_2), ..., \mathcal{F}(oldsymbol{v}_M)]$$
 (4)

where $\mathcal{F}(\cdot)$ represents the reparameterization function of the prompt encoder, which consists of a network $\varphi(\cdot)$ with a residual connection. $\mathcal{F}(\cdot)$ is applied to each prompt token:

$$\mathcal{F}(\boldsymbol{v}_i) = \varphi(\boldsymbol{v}_i) + \boldsymbol{v}_i, i \in \{1...M\}$$
(5)

Network $\varphi(\cdot)$ acts as an adaptable mechanism that establishes associations between prompt embeddings and processes the input prompt sequences to enable task-relevant reparameterization in the prompt embeddings. Different encoder network architectures exhibit varying effects on the model's adaptability. The comprehensive evaluation and the impacts of different types of encoder networks in model adaptation are presented in the Ablation Studies section. In PRE, we propose a one-layer Bidirectional Long Short-Term Memory architecture, as shown in Fig. 2. BiLSTM processes the input prompt sequence in both forward and backward directions simultaneously. By considering both backward and forward context, it enhances the modeling of the domain-specific sequential dependencies in the projected prompt tokens. The



Fig. 2: Illustration of one-layer Bidirectional LSTM architecture used in Prompt Encoder.

encoder itself has a skip connection internally. It enables the model to be more flexible in combining the original embedding of each prompt token with the mapping representation derived from the network $\varphi(\cdot)$, as in Equation (5). By employing this residual-style blending, PRE can flexibly combine the original knowledge encoded in the parameters from the original CLIP and the newly learned knowledge acquired from the few-shot training examples through the BiLSTM network. Ablation Studies provide a detailed examination of the implications and effects of the residual connection in PRE.

Once the projected context sequence V is obtained from the prompt encoder, it is merged with the class token embedding c_i corresponding to the *i*-th class. This combined input is then fed into the text encoder $\theta(\cdot)$, resulting in the generation of a class-specific encoded adaptable prompt $\mathbf{t}_i^r = \theta(\mathbf{r}_i)$. The

prediction probability over the class labels of image \mathbf{x} is:

$$P(y = i \mid \mathbf{x}) = \frac{\exp(\cos(\mathbf{t}_i^r, \mathbf{f})/\tau)}{\sum_{j=1}^C \exp(\cos(\mathbf{t}_j^r, \mathbf{f})/\tau)}$$
(6)

Training: We train the prompt embeddings V and the encoder parameters $\mathcal{F}(\cdot)$ on the downstream task, while preserving all other parameters fixed. The training objective is to maximize the log-likelihood of correct output y given the encoded learnable prompt \mathbf{t}_c^r of the c-th class:

$$\mathcal{L} = -\sum_{c=1}^{C} \log p(c|\mathbf{x}; \mathbf{t}_{c}^{r}) y_{c}$$
(7)

The gradients can be back-propagated through the text encoder $\theta(\cdot)$ and the prompt encoder $\mathcal{F}(\cdot)$. This differential optimization not only utilizes the pre-trained knowledge stored in the fixed text encoder's parameters but also takes advantage of the prompt embeddings projected by the reparameterizing encoder. This combination guides the gradient towards convergence on more generalizable prompts to downstream tasks.

IV. EXPERIMENTS

Following [33], CoOp [16] and CoCoOp [41], we mainly evaluate the accuracy of our proposed method based on generalization from base-to-new classes within a dataset. The experiments are extensively conducted on 8 image recognition datasets in total. All experiments are conducted based on the pre-trained CLIP [9] model. More detailed settings and results will be given in the Supplementary materials.

Datasets: The base-to-new generalization is conducted on 8 image classification datasets, namely: Caltech101 [47] for generic object classification; Oxford-Pets [10], Stanford Cars [48], Flowers102 [49], Food101 [50], FGVC Aircraft [51] for fine-grained visual categorization; DTD [52] for texture classification; and EuroSAT [53] for satellite image classification.

Models: Our implementation is based on CoOp's code [16] with the CLIP model. The experiments were conducted based on the vision backbone ViT-B/16 image encoder [3]. Similar to CoOp, we set the prompt tokens to 4 and initialize the context vectors using the template "a photo of a []". The class names are inserted at the end of these random templates. To ensure a fair comparison, the final performance is averaged over three random seeds.

Training Details: We maintain consistency with CoOp [16] and CoCoOp [41] in terms of training epochs and training procedures which adopted the SGD optimizer with 0.002 initial learning rate, CosineAnnealingLR schedule. We conducted all training and testing on two NVIDIA GeForce RTX 3080 Ti GPUs. The implementation was done using PyTorch. [54].

Baselines: We present the results of the PRE method to compare its performance with four methods:

• CLIP [9]: This method uses hand-crafted templates to generate prompts for knowledge transfer. It is noteworthy that the manual prompts for each dataset were intensively tuned using all classes present in the test data [9].

- CoOp [16]: It replaces manually-picked prompts with a set of learnable prompts inferred from downstream datasets, serving as our direct baseline.
- CoCoOp [41]: This approach generates image-conditional prompts by combining the image context of each image with the learnable prompts from CoOp.
- ProGrad [42] leverages the zero-shot CLIP predictions as the general knowledge and compares the fine-tuned predictions with the general knowledge to regularize the gradient direction.

A. Generalization From Base-to-New Classes

Similar to previous works CoOp and CoCoop, we partition each dataset into two distinct groups: base classes (*Base*) and new classes (*New*), where the new classes are completely separate from the *Base* classes. To assess the generalization capabilities, all compared methods and the proposed PRE utilize the *Base* classes for prompt tuning and evaluate the performance of the *New* classes. Table 2 presents a detailed comparison of the performance across all 8 datasets, specifically focusing on 16-shot settings, M = 4 learnable prompts on the backbone architecture ViT-B/16.

Limitations of CoOp in handling unseen classes: As shown in Table 2, CoOp significantly improves the *Base* classes accuracy compared to CLIP on all 8 datasets. Particularly, CoOp obtains the highest *Base* performance on 6 in total 8 datasets, resulting in the best average *Base* performance among five methods. While CoOp achieves remarkable improvements in the *Base* classes, it fails to generalize effectively to the *New* classes, with a substantial performance gap of 7.5% on average (74.43% vs. 66.92%). This discrepancy arises because CoOp focuses solely on inferring a learnable prompt by leveraging pre-trained knowledge from CLIP. The fixed over-parameterization of CLIP and lack of enough training examples result in discriminative prompts for the *Base* class.

CoCoOp improves performance on *New* **classes with a loss in** *Base* **Accuracy:** Unlike CoOp, CoCoOp takes into account the instance-conditional token in combination with the learnable context vectors. Incorporating the instanceconditional token can enhance generability in the *New* class, but it also reduces discrimination in the *Base* class. Notably, CoCoOp improves the accuracy in unseen classes from 63.22% to 70.99% while experiencing a decline in performance on the seen classes across most datasets. Nevertheless, in most cases, CoOp and CoCoOp demonstrate inferior performance in the unseen classes compared to CLIP. The observed generalization gap highlights the necessity to enhance the generalizability of learning-based prompts.

PRE Significantly Narrows Generalization Gap Compared with existing methods, our proposed PRE method achieves the highest *New* performance on three out of eight datasets, including OxfordPets, Food101, and EuroSAT. In direct comparison with CoOp, PRE demonstrates significant improvements in accuracy for unseen classes. Specifically, the accuracy increases more than 5% from 67.14% to 71.90%, substantially narrowing the gap between soft prompt learning

TABLE II: Comparison with existing methods in the base-to-new generalization setting with ViT-B/16 as the backbone. The context length M is 4 for prompt-based methods with the 16-shot samples from the base classes. H: Harmonic mean (to highlight the generalization trade-off [1]).

(a) Av	erage ove	er 8 datas	ets.		(b) Calte	ch101.			(c) OxfordPets.		
	Base	New	H		Base	New	Н		Base	New	Н
CLIP	68.81	74.43	71.42	CLIP	96.84	94.00	95.40	CLIP	91.17	97.26	94.12
CoOp	83.32	66.92	73.34	CoOp	98.11	93.02	95.50	CoOp	94.24	96.66	95.43
CoCoOp	80.89	70.99	74.47	CoCoOp	97.96	93.81	95.84	CoCoOp	95.20	97.69	96.43
ProGrad	82.96	70.30	75.58	ProGrad	98.02	93.89	95.91	ProGrad	95.07	97.63	96.33
PRE	82.02	71.90	76.22	PRE	98.00	93.50	95.70	PRE	95.27	97.61	96.43
(d) Stanfo	rdCars.			(e) Flowe	ers102.			(f) Food	1101.	
	Base	New	H		Base	New	Н		Base	New	Н
CLIP	63.37	74.89	68.85	CLIP	72.08	77.80	74.83	CLIP	90.10	91.22	90.66
CoOp	76.20	67.14	71.38	CoOp	97.63	66.55	79.15	CoOp	89.44	86.50	87.95
CoCoOp	70.49	73.59	72.01	CoCoOp	94.87	71.75	81.71	CoCoOp	90.70	91.29	90.99
ProGrad	76.68	68.63	72.43	ProGrad	95.54	71.87	82.03	ProGrad	90.37	89.59	89.98
PRE	75.83	69.90	72.74	PRE	96.04	70.80	81.64	PRE	90.96	91.46	91.21
(g	g) FGVCA	Aircraft.			(h) DTD.				(i) EuroSAT.		
	Base	New	H		Base	New	Н		Base	New	Н
CLIP	27.19	36.29	31.09	CLIP	53.24	59.90	56.37	CLIP	56.48	64.05	60.03
CoOp	39.24	23.49	29.39	CoOp	80.17	47.54	59.69	CoOp	91.54	54.44	68.28
CoCoOp	33.41	23.71	27.74	CoCoOp	77.01	56.00	64.85	CoCoOp	87.49	60.04	71.21
ProGrad	40.54	27.57	32.82	ProGrad	77.35	52.35	62.44	ProGrad	90.11	60.89	72.67
PRE	35.63	32.43	34.53	PRE	77.84	53.93	63.70	PRE	86.23	64.47	73.78

with manual prompts. The results confirm that our reparameterizing encoder $\mathcal{F}(\cdot)$ coupled with a residual connection, proficiently captures task-relevant dependencies within the initial prompt embeddings. This associate-learned projected prompt sequence navigates a more efficient optimization process to find a contextually generalizable prompt specific to the downstream domain, thereby enhancing the model's generalization capability. Furthermore, when compared to both CoCoOp and ProGrad, PRE showcases a relatively improved performance in novel classes - averaging 71.90% against CoCoOp's 70.99% and ProGrad's 70.30%. This consistent enhancement in novel classes' performance across various classes demonstrates PRE's remarkable ability to balance performance across a wide spectrum of categories, reinforcing its potential for broad applicability in real-world scenarios.

Regarding the Harmonic mean (represents the generalization trade-off [1]), PRE outperforms all other methods. Our proposed method consistently achieves the highest Harmonic mean across five out of eight datasets. On average, it surpasses CLIP by 5%, CoOp by 3%, CoCoOp by nearly 2%, and ProGrad by 1%. Besides the performance improvements in novel classes, this is partly attributed to the fact that PRE maintains a good *Base* classes' performance. Specifically, PRE achieves a remarkable 6.7% higher Base accuracy than CLIP and surpasses CoCoOp on six out of eight datasets with an average accuracy of 82.02% compared to 80.89%. This performance improvement in seen classes comes from the efficacy of the residual connection, which dynamically balances and blends knowledge from both the original CLIP model and the newly acquired insights from the prompt encoder based on few-shot training examples. These outcomes underscore how PRE enhances the generalizability of *New* classes without compromising the model's robust learning potential for *Base* classes.

Various K-shot samples: Table 3 summarizes the average performance across all 8 datasets, considering various K-shot samples on the backbone architecture ViT-B/16. Similar to the observations in the 16-shot settings, PRE consistently achieves a higher average Harmonic mean than existing methods, demonstrating their superiority in generalizing to base-to-new classes. Among the existing methods, CoOp still achieves the best performance regarding *Base* classes while obtaining the

		Κ – Λ		K - 8			<i>K</i> – 16			
Methods	Prompts				$A = \delta$			<i>N</i> = 10		
		Base	New	Н	Base	New	Н	Base	New	Н
CoOp	textual	79.33	66.02	71.47	81.67	66.29	71.89	83.32	66.92	73.34
CoCoOp	textual+visual	76.51	71.48	73.68	78.67	70.78	74.14	80.89	70.99	74.47
ProGrad	textual	79.15	70.40	74.11	80.55	70.84	75.00	80.96	70.30	75.58
PRE	textual	78.62	71.31	74.46	79.84	71.49	75.07	82.02	71.90	76.22

TABLE III: Comparison in the base-to-new setting with different K-shot samples in terms of the average performance among all 8 datasets with backbones ViT-B/16.

worst *New* class performance in all K-shot samples. Compared with ProGrad, PRE leads to slight enhancements in *New* accuracy across all settings. Meanwhile, CoCoOp achieves a marginally higher *Base* class performance than PRE for the 4-shot case. The performance gap between our proposed methods and others is most significant when K = 16 shots and tends to diminish as K decreases. This phenomenon is because the reparameterizing encoder $\mathcal{F}(\cdot)$ in PRE requires a certain number of data samples to fully explore its potential in learning the optimal prompt embeddings.

B. Ablation Studies

In this subsection, we conducted ablation studies to investigate the effectiveness of different components in PRE.

Parameter-efficiency of PRE: The total number of trainable parameters in PRE consists of 1) trainable prompt embeddings, and 2) reparameterizing encoder network. Our encoder network $\mathcal{F}(\cdot)$ contains a one-layer Bidirectional LSTM. Let M be the number of prompt tokens and d be the dimensionality of model embeddings, the BiLSTM network has an input size of d and a hidden size of d/2, and it incorporates two separate LSTM units: one for processing the input sequence in the forward direction and another for processing it in the backward direction. For each LSTM unit, the weight matrix for input-to-hidden connections has a shape of $4 \times d \times d/2$, and the weight matrix for hidden-to-hidden connections has a shape of $4 \times d/2 \times d/2$. Taking into account both the forward and backward LSTM units, the total number of parameters in the BiLSTM network is $3 \times d \times d$. In total, we have $d \times M$ soft prompt parameters, and $3 \times d \times d$ parameters of the reparameterizing encoder network. As the number of prompt tokens M varies from 1 to 16, the number of trainable parameters in PRE remains relatively low, resulting in efficient training compared to CoOp.

Training efficiency: We evaluated the prompt-based methods' training time on 8 datasets using a 16-shot setting. The batch size used for CoOp, ProGrad, and PRE is 32, while CoCoOp uses a batch size of 1. The training time represents the average time taken to process one image, measured in milliseconds per image. The training process in PRE is straightforward and does not require additional inference time. The running time added by the lightweight reparameterizing encoder network for prompt tokens in PRE is negligible compared to the training time of the most time-efficient method -

TABLE IV: Training Time Comparison. The training time is the average time to process one image, i.e., ms/image.

Method	CoOp	CoCoOp	ProGrad	PRE
Time (ms/image)	6	160	22	6.3
H Accuracy (%)	73.34	74.47	75.58	76.22



Fig. 3: The impact of different reparameterizing encoder network architectures on average Accuracy on *Base*, *New* and *H* over 8 datasets on the 16-shot setting.

CoOp. In our experiments (as shown in Table 4), PRE exhibits slightly higher training times compared to CoOp, with values of 6.3 milliseconds per image for PRE and 6 milliseconds per image for CoOp. This marginal difference in training times is well justified by the significant performance enhancement achieved by PRE. Compared to CoCoOp (160 milliseconds per image) and ProGrad (22 milliseconds per image), PRE's training efficiency remains notably superior. This substantial difference in speed is because CoCoOp adopts an instanceconditional design, requiring an independent forward pass of instance-specific prompts through the text encoder for each image, resulting in a more computationally intensive process. Overall, PRE's efficiency in training makes it an attractive choice for practitioners seeking to efficiently adapt Vision-Language Models (VLMs) to actual image recognition tasks.

Effects of different reparameterization encoder net-

TABLE V: Comparison in different encoder network architectures with vs. without Residual connection in terms of the average *Base*, *New*, and *H* performance in the 16-shot setting.

Encoder Network	Residual	Accuracy (%)			
	connection	Base	New	Н	
BiLSTM	Yes	82.02	71.90	76.22	
BiLSTM	No	80.51	70.57	74.67	
		-1.64	-1.31	-1.61	
Transformer Encoders	Yes	82.05	71.55	75.98	
Transformer Encoders	No	82.01	69.34	74.54	
		-0.04	-2.21	-1.44	
Bottleneck MLP	Yes	78.77	72.04	75.00	
Bottleneck MLP	No	74.54	68.88	71.16	
		-4.23	-3.16	-3.84	

work architectures: To gain a deeper understanding of the reparameterizing mechanism and how its choice of network architecture impacts the model's performance, we have implemented a range of network architectures in the prompt encoder including a bottle-neck MLP, Transformer Encoder network, and BiLSTM, all equipped with a residual connection. The detailed architecture and implementations are presented in Appendix B3. Fig. 3 shows the effects of these three networks on the average accuracy on *Base*, *New*, and *H* over 8 datasets. All three networks lead to improvements in novel classes and the Harmonic mean compared to the CoOp method (detailed results in Table 5). These results underscore the efficacy of the prompt reparameterization technique for adapting Vision-Language Models (VLMs), although the outcomes vary based on the chosen network architecture. We observe that the Transformer Encoder network follows a similar trend to the BiLSTM, albeit with slightly lower performance. While MLPbased reparameterization demonstrates an improvement in New class accuracy, but at the cost of a substantial decrease in Base class performance. This phenomenon can be attributed to the inherent limitations of bottleneck MLPs in capturing long-range sequential dependencies and contextual information within prompt embeddings. As MLPs are feedforward networks, they process each token independently without considering the relationships between them. Consequently, this lack of contextual understanding could lead to the loss of valuable contextual information, leading to less contextually rich prompt embeddings. Comparatively, the BiLSTM network showcases promising benefits due to its ability to capture both forward and backward contextual information within prompt sequences. Furthermore, BiLSTMs have fewer parameters than Transformer Encoder networks, making them easier to train and less prone to overfitting in few-shot training examples.

Residual connection is an important component in PRE: We assess the effect of the residual connection in the PRE architecture by conducting an ablation study on different encoder networks. Specifically, we examine the performance of these variants when each prompt is projected through the reparameterization encoder $\mathcal{F}(\cdot)$ without a residual connection. According to Table 5, the performance of both the Base, New, and H decreases when the skip connection is removed from the prompt encoder in all network architectures. Notably, MLP exhibits a significant drop of up to 4.23% in accuracy for Base classes and 3.16% in the New class performance, demonstrating a significant vulnerability in handling input prompt embeddings. This is because the MLPs are inherently shallow networks without inherent memory mechanisms to capture sequential dependencies. As a result, when the residual connection is removed, without the complementary from the original prompt embeddings, the MLP lacks the ability to effectively propagate contextual information through the layers, leading to a more significant performance degradation.

Limitations and Future Works: Owing to time and computational constraints, our evaluation of PRE was limited to only 8 out of the 11 datasets typically used for assessing prompt learning methods. We are confident that PRE's true effectiveness will be fully and strongly demonstrated when evaluated on the complete set of 11 classification datasets on both base-to-new generalization and distribution shift settings. In terms of New class performance, PRE's performance lags behind that of CLIP in 5 out of the 8 datasets (as seen in Table 2). This result indicates that more efforts are required and we hope the information presented in this research can help the community tackle the generalizability issue in prompt learning. In terms of future work, one direction is to further develop the reparameterizing prompt encoder network with potentially a more efficient architecture that can enhance the model's generalizability. Furthermore, a promising avenue is to investigate the influence of our reparameterizing encoder within the context of other VLMs tuning methods such as adapter-based. We believe that with targeted modifications, our approach could potentially be integrated to accelerate certain aspects of these models, and this will be explored in future research.

V. CONCLUSIONS

In this paper, we presented PRE - a soft prompt learning method for Vision Language adaptation. The proposed approach involves a simple yet effective prompt projection technique that employs a reparameterizing encoder. Our method demonstrates its efficiency in achieving improved generalization performance over prior works while maintaining performance on the seen classes. We hope that our approach could be explored in collaboration with other well-established methods in the future, thereby contributing to the overall enhancement of adaptability within the realm of Vision Language models.

ETHICS STATEMENT

The primary objective of this research paper is to improve the parameter-efficient prompt tuning of large pre-trained vision-language models, which enables research groups and practitioners with limited computational and data-labeling resources to leverage the capabilities of these state-of-the-art models. We conducted all our experiments using public data that the research community widely recognizes and utilizes. Therefore, we believe our work does not involve any private or sensitive components, guaranteeing the safety and transparency of our contributions.

ACKNOWLEDGMENT

We would like to thank Professor Georgios (Yorgos) Tzimiropoulos - Queen Mary University of London for his support and helpful input throughout the project. We also thank Dr. Andrew Nguyen - PhD at Oxford University for our discussions on the prompt tuning methodologies.

REFERENCES

- Y. Xian, B. Schiele, and Z. Akata, "Zero-shot learning-the good, the bad and the ugly," in *Proceedings of the IEEE conference on computer* vision and pattern recognition, 2017, pp. 4582–4591.
- [2] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proceedings of the IEEE conference on computer vision* and pattern recognition, 2016, pp. 770–778.
- [3] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly *et al.*, "An image is worth 16x16 words: Transformers for image recognition at scale," *arXiv preprint arXiv:2010.11929*, 2020.
- [4] A. Fürst, E. Rumetshofer, J. Lehner, V. T. Tran, F. Tang, H. Ramsauer, D. Kreil, M. Kopp, G. Klambauer, A. Bitto *et al.*, "Cloob: Modern hopfield networks with infoloob outperform clip," *Advances in neural information processing systems*, vol. 35, pp. 20450–20468, 2022.
- [5] Y. Li, F. Liang, L. Zhao, Y. Cui, W. Ouyang, J. Shao, F. Yu, and J. Yan, "Supervision exists everywhere: A data efficient contrastive languageimage pre-training paradigm," arXiv preprint arXiv:2110.05208, 2021.
- [6] C. Jia, Y. Yang, Y. Xia, Y.-T. Chen, Z. Parekh, H. Pham, Q. Le, Y.-H. Sung, Z. Li, and T. Duerig, "Scaling up visual and vision-language representation learning with noisy text supervision," in *International conference on machine learning*. PMLR, 2021, pp. 4904–4916.
- [7] L. Yao, R. Huang, L. Hou, G. Lu, M. Niu, H. Xu, X. Liang, Z. Li, X. Jiang, and C. Xu, "Filip: Fine-grained interactive language-image pre-training," arXiv preprint arXiv:2111.07783, 2021.
- [8] J. Yu, Z. Wang, V. Vasudevan, L. Yeung, M. Seyedhosseini, and Y. Wu, "Coca: Contrastive captioners are image-text foundation models," *arXiv* preprint arXiv:2205.01917, 2022.
- [9] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark *et al.*, "Learning transferable visual models from natural language supervision," in *International conference on machine learning*. PMLR, 2021, pp. 8748–8763.
- [10] O. M. Parkhi, A. Vedaldi, A. Zisserman, and C. Jawahar, "Cats and dogs," in 2012 IEEE conference on computer vision and pattern recognition. IEEE, 2012, pp. 3498–3505.
- [11] J. Lu, D. Batra, D. Parikh, and S. Lee, "Vilbert: Pretraining task-agnostic visiolinguistic representations for vision-and-language tasks," *Advances* in neural information processing systems, vol. 32, 2019.
- [12] Y. Yao, A. Zhang, Z. Zhang, Z. Liu, T.-S. Chua, and M. Sun, "Cpt: Colorful prompt tuning for pre-trained vision-language models," *arXiv* preprint arXiv:2109.11797, 2021.
- [13] W. Jin, Y. Cheng, Y. Shen, W. Chen, and X. Ren, "A good prompt is worth millions of parameters: Low-resource prompt-based learning for vision-language models," *arXiv preprint arXiv:2110.08484*, 2021.
- [14] X. L. Li and P. Liang, "Prefix-tuning: Optimizing continuous prompts for generation," arXiv preprint arXiv:2101.00190, 2021.

- [15] B. Lester, R. Al-Rfou, and N. Constant, "The power of scale for parameter-efficient prompt tuning," arXiv preprint arXiv:2104.08691, 2021.
- [16] K. Zhou, J. Yang, C. C. Loy, and Z. Liu, "Learning to prompt for visionlanguage models," *International Journal of Computer Vision*, vol. 130, no. 9, pp. 2337–2348, 2022.
- [17] A. Razdaibiedina, Y. Mao, R. Hou, M. Khabsa, M. Lewis, J. Ba, and A. Almahairi, "Residual prompt tuning: Improving prompt tuning with residual reparameterization," *arXiv preprint arXiv:2305.03937*, 2023.
- [18] A. Kamath, M. Singh, Y. LeCun, G. Synnaeve, I. Misra, and N. Carion, "Mdetr-modulated detection for end-to-end multi-modal understanding," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021, pp. 1780–1790.
- [19] L. Li, M. Yatskar, D. Yin, C. Hsieh, and K. Chang, "A simple and performant baseline for vision and language," *arXiv preprint* arXiv:1908.03557, 2019.
- [20] Y. Hong, Q. Wu, Y. Qi, C. Rodriguez-Opazo, and S. Gould, "A recurrent vision-and-language bert for navigation," arXiv preprint arXiv:2011.13922, 2020.
- [21] W. Kim, B. Son, and I. Kim, "Vilt: Vision-and-language transformer without convolution or region supervision," in *International Conference* on Machine Learning. PMLR, 2021, pp. 5583–5594.
- [22] H. Bao, W. Wang, L. Dong, Q. Liu, O. K. Mohammed, K. Aggarwal, S. Som, S. Piao, and F. Wei, "Vlmo: Unified vision-language pre-training with mixture-of-modality-experts," *Advances in Neural Information Processing Systems*, vol. 35, pp. 32 897–32 912, 2022.
- [23] M. Elhoseiny, B. Saleh, and A. Elgammal, "Write a classifier: Zero-shot learning using purely textual descriptions," in *Proceedings of the IEEE International Conference on Computer Vision*, 2013, pp. 2584–2591.
- [24] R. Socher, M. Ganjoo, C. D. Manning, and A. Ng, "Zero-shot learning through cross-modal transfer," *Advances in neural information processing systems*, vol. 26, 2013.
- [25] A. Frome, G. S. Corrado, J. Shlens, S. Bengio, J. Dean, M. Ranzato, and T. Mikolov, "Devise: A deep visual-semantic embedding model," *Advances in neural information processing systems*, vol. 26, 2013.
- [26] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," *Advances in neural information processing systems*, vol. 30, 2017.
- [27] Z.-Y. Dou, Y. Xu, Z. Gan, J. Wang, S. Wang, L. Wang, C. Zhu, P. Zhang, L. Yuan, N. Peng *et al.*, "An empirical study of training end-to-end vision-and-language transformers," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 18166–18176.
- [28] K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick, "Momentum contrast for unsupervised visual representation learning," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2020, pp. 9729–9738.
- [29] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton, "A simple framework for contrastive learning of visual representations," in *International conference on machine learning*. PMLR, 2020, pp. 1597–1607.
- [30] O. Henaff, "Data-efficient image recognition with contrastive predictive coding," in *International conference on machine learning*. PMLR, 2020, pp. 4182–4192.
- [31] A. Jain, M. Guo, K. Srinivasan, T. Chen, S. Kudugunta, C. Jia, Y. Yang, and J. Baldridge, "Mural: multimodal, multitask retrieval across languages," arXiv preprint arXiv:2109.05125, 2021.
- [32] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell *et al.*, "Language models are few-shot learners," *Advances in neural information processing systems*, vol. 33, pp. 1877–1901, 2020.

- [33] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, I. Sutskever *et al.*, "Language models are unsupervised multitask learners," *OpenAI blog*, vol. 1, no. 8, p. 9, 2019.
- [34] T. Schick and H. Schütze, "Exploiting cloze questions for few shot text classification and natural language inference," *arXiv preprint* arXiv:2001.07676, 2020.
- [35] F. Petroni, T. Rocktäschel, P. Lewis, A. Bakhtin, Y. Wu, A. H. Miller, and S. Riedel, "Language models as knowledge bases?" arXiv preprint arXiv:1909.01066, 2019.
- [36] N. Poerner, U. Waltinger, and H. Schütze, "E-bert: Efficient-yet-effective entity embeddings for bert," arXiv preprint arXiv:1911.03681, 2019.
- [37] M. Tsimpoukelli, J. L. Menick, S. Cabi, S. Eslami, O. Vinyals, and F. Hill, "Multimodal few-shot learning with frozen language models," *Advances in Neural Information Processing Systems*, vol. 34, pp. 200– 212, 2021.
- [38] X. Liu, Y. Zheng, Z. Du, M. Ding, Y. Qian, Z. Yang, and J. Tang, "Gpt understands, too," arXiv preprint arXiv:2103.10385, 2021.
- [39] Z. Jiang, F. F. Xu, J. Araki, and G. Neubig, "How can we know what language models know?" *Transactions of the Association for Computational Linguistics*, vol. 8, pp. 423–438, 2020.
- [40] T. Shin, Y. Razeghi, R. L. Logan IV, E. Wallace, and S. Singh, "Autoprompt: Eliciting knowledge from language models with automatically generated prompts," *arXiv preprint arXiv:2010.15980*, 2020.
- [41] K. Zhou, J. Yang, C. C. Loy, and Z. Liu, "Conditional prompt learning for vision-language models," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 16816– 16825.
- [42] B. Zhu, Y. Niu, Y. Han, Y. Wu, and H. Zhang, "Prompt-aligned gradient for prompt tuning," *arXiv preprint arXiv:2205.14865*, 2022.
- [43] H. Yao, R. Zhang, and C. Xu, "Visual-language prompt tuning with knowledge-guided context optimization," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023, pp. 6757–6767.
- [44] A. Wang, Y. Pruksachatkun, N. Nangia, A. Singh, J. Michael, F. Hill, O. Levy, and S. Bowman, "Superglue: A stickier benchmark for generalpurpose language understanding systems," *Advances in neural information processing systems*, vol. 32, 2019.
- [45] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, "Exploring the limits of transfer learning with a unified text-to-text transformer," *The Journal of Machine Learning Research*, vol. 21, no. 1, pp. 5485–5551, 2020.
- [46] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "Bert: Pre-training of deep bidirectional transformers for language understanding," *arXiv* preprint arXiv:1810.04805, 2018.
- [47] L. Fei-Fei, R. Fergus, and P. Perona, "Learning generative visual models from few training examples: An incremental bayesian approach tested on 101 object categories," in 2004 conference on computer vision and pattern recognition workshop. IEEE, 2004, pp. 178–178.
- [48] J. Krause, M. Stark, J. Deng, and L. Fei-Fei, "3d object representations for fine-grained categorization," in *Proceedings of the IEEE international conference on computer vision workshops*, 2013, pp. 554–561.
- [49] M.-E. Nilsback and A. Zisserman, "Automated flower classification over a large number of classes," in 2008 Sixth Indian conference on computer vision, graphics & image processing. IEEE, 2008, pp. 722–729.
- [50] L. Bossard, M. Guillaumin, and L. Van Gool, "Food-101-mining discriminative components with random forests," in *Computer Vision– ECCV 2014: 13th European Conference, Zurich, Switzerland, September* 6-12, 2014, Proceedings, Part VI 13. Springer, 2014, pp. 446–461.
- [51] S. Maji, E. Rahtu, J. Kannala, M. Blaschko, and A. Vedaldi, "Finegrained visual classification of aircraft," *arXiv preprint arXiv:1306.5151*, 2013.

- [52] M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, and A. Vedaldi, "Describing textures in the wild," in *Proceedings of the IEEE conference* on computer vision and pattern recognition, 2014, pp. 3606–3613.
- [53] P. Helber, B. Bischke, A. Dengel, and D. Borth, "Eurosat: A novel dataset and deep learning benchmark for land use and land cover classification," *IEEE Journal of Selected Topics in Applied Earth Observations* and Remote Sensing, vol. 12, no. 7, pp. 2217–2226, 2019.
- [54] A. Paszke, S. Gross, S. Chintala, G. Chanan, E. Yang, Z. DeVito, Z. Lin, A. Desmaison, L. Antiga, and A. Lerer, "Automatic differentiation in pytorch," 2017.

APPENDIX

This appendix is organized as follows:

- Section A provides the experimental and dataset details for PRE.
- Section B provides extended Ablation studies about the effect of the context length, prompt initialization, and parameter sharing on PRE of the base-to-new generalization experiments. It also studies different residual network architectures in PRE.
- Section C provides the interpretation of the learned textual prompts using the nearest words in the embedding space.
- Section D gives additional detailed results for each dataset of the base-to-new generalization experiments in different K-shot settings and the detailed experiment results to see the impact of the residual network as well as parameter sharing settings on PRE.

A. EXPERIMENTAL DETAILS

1) Datasets Details: The datasets utilized in our experiments align with the ones employed in the CoOp [16]. These datasets encompass 8 different benchmarks designed for fewshot visual recognition. For comprehensive reference, Table A1 provides detailed information about each dataset, such as the number of classes, sizes of the training and testing sets, and the original image recognition tasks associated with each dataset.

2) **Training Details:** Adopting the training settings from CoOp [16], we maintain a consistent training epoch of 50 for all the experiments conducted with various shots. For promptbased models, we employ a batch size of 32, except in the case of CoCoOp. As reported by (Zhou et al., 2022) [41], CoCoOp exhibits a considerable GPU memory consumption when the batch size is set larger than one. Hence, we follow their original configuration and set the batch size to 1 for CoCoOp in our experiments. We conducted our experiments with two NVIDIA GeForce RTX 3080 Ti GPUs, with 8 GB of memory each. On each task, training took between 4 minutes and 2 hours.

3) Hyperparameters: The original CoOp method has different versions with different class token positions and parameter initialization strategies. To maintain consistency, we selected a specific configuration for our baseline, where the token position is "end," the parameter initialization strategy is "a photo of a," and the length of learnable context tokens is 4, similar to the CoOp and CoCoOp settings.

B. EXTENDED ABLATION STUDIES

1) Effect of context length: In this study, we examine the significance of the context length for the learnable prompts. To analyze its impact on base-to-new generalization, we conduct experiments using the ViT-16/B backbone with PRE models. Following a similar approach to CoOp [16], we investigate three context lengths: 4, 8, and 16 context tokens. For context lengths of 8 and 16, the prompt is initialized as "X X ... X a photo of a [Class]". The performance using PRE across 8



Fig. A1: The impact of different context length on average Accuracy on *Base*, *New* and *H* over 8 datasets using PRE model.



Fig. A2: Comparison with vs without prompt initialization on PRE on average Accuracy on *Base*, *New* and *H* over 8 datasets using PRE model.

datasets is then averaged and summarized in Fig. A1. Notably, we observe that setting the context length to 8 consistently yields superior performance compared to the other two settings across all three evaluation metrics. Learning prompts with context lengths of 4 and 16 exhibit similar performance levels on PRE. To ensure a fair comparison with CoOp and CoCoOp, we ultimately opt to set the context length to 4 in our final model. This decision ensures consistency in the experimental setup and facilitates a proper evaluation against the previous state-of-the-art methods.

2) *Effect of prompt initialization:* Lester et al. (2021) [15] find that the initialization of prompt parameters plays a major role in the final performance. To assess the influence of prompt initialization on prompt tuning, we carry out a comparative analysis employing two different methods: word embeddings-based initialization ('w/ init') and random initialization ('w/o init') on PRE. For random initialization, we utilize a zero-mean Gaussian distribution with a standard deviation of 0.02 to initialize the prompt tokens. On the other hand,

Dataset	Classes	Training Size	Testing Size	Task
Caltech101 (Fei-Fei et al., 2004)	100	4,128	2,465	Object Recognition
DTD (Cimpoi et al., 2014)	47	2,820	1,692	Texture Recognition
EuroSAT (Helber et al., 2019)	10	13,500	8,100	Satellite Image Recognition
FGVCAircraft (Maji et al., 2013)	100	3,334	3,333	Fine-Grained Aircraft Recognition
Flowers102 (Nilsback & Zisserman, 2008)	102	4,093	2,463	Fine-Grained Flowers Recognition
Food101 (Bossard et al., 2014)	101	50,500	30,300	Fine-Grained Food Recognition
OxfordPets (Parkhi et al., 2012)	37	2,944	3,669	Fine-Grained Pets Recognition
StanfordCars (Krause et al., 2013)	196	6,509	8,041	Fine-Grained Car Recognition

TABLE A1: Details of 8 Datasets for Few-Shot Visual Recognition and Base-to-New Generalization Image Recognition Evaluation.





(a) A shared bottleneck MLP for every prompt token (b) A shared Transformer Encoder network for every prompt token

Fig. A3: Two other network architectures for the prompt encoder in PRE.

word embeddings-based initialization involves initializing the prompt tokens with the phrase "a photo of a." with a context length of 4. After conducting our experiments and evaluating the performance across 8 datasets, we have summarized the results in Fig. A2. Notably, we have observed that employing word embeddings-based initialization yields slightly higher performance in all three evaluation metrics when compared to random initialization in PRE. This finding highlights the significance of the initialization strategy in prompt tuning and its substantial impact on the overall performance of the model.

3) Studies of different network architectures for Prompt Encoder: In this study, we examine other different network architectures for reparameterizing soft prompt embeddings in PRE. Following Anastasia et al. (2023) [17], we use a bottleneck MLP network (as shown in Fig. A3a). Specifically, this MLP network consists of a down-projection linear layer followed by a ReLU layer, and an up-projection linear

layer, with a dropout layer at the end. The bottleneck size hyperparameter has been thoroughly studied to get the optimal performance. We also explored a Transformer Encoder network consisting of two Transformer encoder layers followed by a dropout layer, each layer equipped with two attention heads (as in Fig. A3b). The residual connection is used in all three network architectures (BiLSTM, MLP, and Transformer Encoders network) to combine the input prompt embeddings and the output of the reparameterization network. The reparameterizing network can be shared among every prompt token or separately process each prompt token using separate parameters. Table A2 shows the results of these networks on the base-to-new generalization setting. These results have been discussed in the Ablation Studies section. Following that, we expand the ablation study to investigate the impact of parameter sharing on these networks in the next part.

Encoder Network	Parameter Sharing	Accuracy (%)			
	C	Base	New	Н	
BiLSTM	Share	82.02	71.90	76.22	
BiLSTM	Separate	82.72	69.02	74.60	
Bottle-neck MLP	Share	78.77	72.04	75.00	
Bottle-neck MLP	Separate	80.26	72.07	75.54	
Transformer Encoders	Share	82.05	71.55	75.66	
Transformer Encoders	Separate	81.49	70.21	74.97	

TABLE A2: Comparison in PRE using different reparameterizing network architectures in terms of the average *Base*, New, and *H* performance in the base-to-new generalization setting.



Fig. A4: Performance of PRE with shared and separate BiL-STM networks on average Accuracy on *Base*, *New* and *H* over 8 datasets.

4) Effect of processing prompt tokens independently by separate networks vs. jointly by a shared network in Prompt Encode: Fig. A3 illustrates the performance comparison of PRE when employing a shared BiLSTM network for every prompt token versus separate BiLSTM networks for each prompt token while Fig. A4 shows the impact of a shared MLP network vs. separate MLP networks on the prompt encoder. The detailed results of parameter sharing on three kinds of network architecture BiLSTM, Transformer Encoders, and MLP are shown in Table 2. We can see that the shared network exhibits significantly better performance on the Base classes, while still maintaining strong generalization capabilities. This performance improvement indicates that parameter sharing in the BiLSTM Encoder network of PRE is highly beneficial, as it allows for the effective learning of dependencies between prompt tokens, outperforming the separate network setting.

Table A3 shows the detailed results on all three network architectures. The downward trend is observed in the case of the Transformer Encoder network as well. This trend is consistent across both network architectures because they both utilize the benefits of processing prompt tokens collectively,



Fig. A5: Performance of PRE with shared and separate MLP networks on average Accuracy on *Base*, *New* and *H* over 8 datasets.

which allows them to capture the extended dependencies present within the sequence of prompts.

In contrast, for the MLP network, the separate network configuration yields relatively higher performance on the *Base* classes while maintaining the performance in novel classes. MLP is not affected by the absence of parameter sharing as it does not primarily aim to capture interactions between prompt tokens. In contrast, separate MLP networks with increased parameters can enhance the encoder's adaptability in exploring various mappings of prompt embeddings.

C. INTERPRETATION OF PROMPTS

The prompts learned through optimization in the continuous space, as highlighted in CoOp [16], are difficult for humans to understand. To address this issue, CoOp introduces a method that utilizes the nearest words in the embedding space to represent and visualize the learned prompts. In line with this approach, we present the nearest words corresponding to our learned prompts across 8 datasets in Table A3 for the PRE with BiLSTM network and Table A4 for PRE with the Transformer Encoder network as the reparameterizing encoder. Like CoOp's findings, most of these words remain difficult

#	Word 1	Word 2	Word 3	Word 4
Caltech101	borderlands (0.6706)	oth (0.6446)	pose (0.6732)	mark (0.7446)
OxfordPets	ol (0.5578)	moves (0.6612)	wild (0.6559)	mountain (0.5700)
Flowers102	screen (1.1097)	photoo (1.1657)	battles (1.4090)	sey (1.2732)
FGVC Aircraft	can (1.4438)	independent (1.8402)	tail (1.7982)	campaigner (1.0018)
DTD	aster (0.9711)	consecutive (0.8758)	line (1.0512)	stones (1.0743)
EuroSAT	three (0.4983)	report (0.5567)	rain (0.4577)	pose (0.5220)
Stanford Cars	salt (0.9016)	riot (1.1503)	N/A (0.9737)	toby (1.1054)
Food101	tur (1.1864)	color (0.7646)	lh (1.0958)	water (0.9743)

TABLE A3: The nearest words for each of the 4 context vectors learned by PRE with BiLSTM network as prompt encoder, with their distances shown in parentheses. N/A means non-Latin characters.

TABLE A4: The nearest words for each of the 4 context vectors learned by PRE with Transformer Encoder network as prompt encoder, with their distances shown in parentheses. N/A means non-Latin characters.

#	Word 1	Word 2	Word 3	Word 4
Caltech101	draws (0.5176)	ability (0.4955)	mirrors (0.6053)	pre (0.4966)
OxfordPets	sep (0.5221)	line (0.6307)	living (0.4938)	marked (0.5395)
Flowers102	bag (0.7056)	paint (0.5929)	pup (0.5806)	pray (0.8519)
FGVC Aircraft	nail (0.7897)	cranl (1.2032)	mor (0.7339)	wound (0.8062)
DTD	aster (0.9711)	consecutive (0.8758)	line (1.0512)	stones (1.0743)
EuroSAT	ma (0.4567)	kt (0.5447)	wong (0.4650)	N/A (0.4693)
Stanford Cars	mines (0.4830)	line (0.4581)	heights (0.4842)	sheet (0.4345)
Food101	buddies (0.4452)	losing (0.7646)	voter (0.5958)	marching (0.4493)

to interpret directly through human logic. However, we can still see some connections between these prompts and the corresponding images in certain datasets. For instance, in the OxfordPets dataset, the prompts learned by PRE seem to emphasize elements related to "wild" and "mountain" environments in each image. In the FGVC Aircraft dataset, the learned prompts from PRE show a preference for the tail region to distinguish between different types of airplanes. Moreover, in the DTD dataset, PRE with both types of encoder network focuses on prompts associated with "consecutive" and "line", which appear to be indicative of specific image texture characteristics. It demonstrates that the learned multiple prompts focus on particular attributes of categories.

D. DETAILED RESULTS

This section presents a detailed comparison of the proposed PRE approach with existing methods in various aspects. Table A5 shows the results in the base-to-new generalization setting of PRE using a shared network and separate network as the reparameterizing mechanism for input prompt embeddings. To explore the effect of residual connection in the reparameterization network on PRE, we compare the performance in the base-to-new generalization setting of the prompt encoder with and without the presence of residual connection. The summarized averaged results are shown in Table 5. The detailed results on 8 datasets are shown in Table A6.

TABLE A5: Detailed results on 8 datasets to see the impact of residual connection on different encoder architectures of PRE in the base-to-new generalization setting with ViT-B/16 as the backbone. The context length M is 4 for prompt-based methods with the 16-shot samples from the base classes.

Dataset	Set	CoOp	BiLSTM		Transform	mer Encoders	MLP		
			Residual	W/o Residual	Residual	W/o Residual	Residual	W/o Residual	
	Base	83.32	82.02	80.51	82.05	82.01	78.77	74.54	
Average	New	66.92	71.90	70.57	71.55	69.34	72.04	68.88	
	Н	73.34	76.22	74.67	75.98	74.54	75.00	71.16	
	Base	98.11	98.00	97.77	98.00	98.00	97.63	97.10	
Caltech101	New	93.02	93.50	93.90	93.40	92.10	94.17	94.200	
	Н	95.50	95.70	95.80	95.64	94.96	95.87	95.63	
	Base	94.24	95.27	94.90	95.37	96.50	95.37	95.30	
OxfordPets	New	96.66	97.60	97.13	97.00	95.30	97.59	97.50	
	Н	95.43	96.42	96.00	96.18	95.90	96.47	96.39	
	Base	97.63	96.40	96.73	96.00	96.62	89.23	86.60	
Flowers102	New	66.55	70.80	68.43	70.90	67.93	72.53	74.60	
	Н	79.15	81.64	80.16	81.56	79.77	80.02	80.15	
ECVC	Base	39.24	35.63	34.40	36.70	37.10	33.82	23.66	
Aircraft	New	23.49	32.43	33.30	31.40	30.33	32.03	11.24	
	Н	29.39	34.53	33.84	33.84	33.38	32.90	15.24	
	Base	80.17	77.80	74.70	78.60	79.20	72.37	50.87	
DTD	New	47.54	53.93	54.50	52.75	51.30	54.60	52.10	
	Н	59.69	63.70	63.02	63.13	62.27	62.24	51.48	
	Base	91.54	86.23	85.10	87.40	87.00	81.60	82.33	
EuroSAT	New	54.44	64.47	56.50	63.73	57.10	62.00	60.20	
	Н	68.28	73.78	67.91	73.71	68.95	70.46	69.55	
Ctaufaul	Base	76.20	75.83	71.47	73.34	72.74	70.20	71.50	
Cars	New	67.14	69.90	72.77	71.87	72.53	72.93	72.20	
	Н	71.38	72.74	72.11	72.60	72.86	71.54	71.85	
	Base	71.38	73.20	72.11	72.60	72.86	71.54	71.85	
Food101	New	86.5	91.46	88.02	91.36	88.12	91.02	89.02	
	Н	87.95	91.21	88.52	91.16	88.27	90.47	88.97	