

1st Place in ICCV 2023 Workshop Challenge Track 1 on Resource Efficient Deep Learning for Computer Vision: Budgeted Model Training Challenge

Youngjun Kwak^{1,2}, Seonghun Jeong¹, Yunseung Lee¹, and Changick Kim^{*2}

¹KakaoBank Corp., South Korea

²Department of Electrical Engineering, KAIST, South Korea

{vivaan.yjkwak, bentley.j, yun.lee}@lab.kakaobank.com, {yjk.kwak, changick}@kaist.ac.kr

Abstract

The budgeted model training challenge aims to train an efficient classification model under resource limitations. To tackle this task in ImageNet-100, we describe a simple yet effective resource-aware backbone search framework composed of profile and instantiation phases. In addition, we employ multi-resolution ensembles to boost inference accuracy on limited resources. The profile phase obeys time and memory constraints to determine the models' optimal batch-size, max epochs, and automatic mixed precision (AMP). And the instantiation phase trains models with the determined parameters from the profile phase. For improving intra-domain generalizations, the multi-resolution ensembles are formed by two-resolution images with randomly applied flips. We present a comprehensive analysis with expensive experiments. Based on our approach, we win first place in International Conference on Computer Vision (ICCV) 2023 Workshop Challenge Track 1 on Resource Efficient Deep Learning for Computer Vision (RCV).

1. Our Approach

We provide a detailed account of our two victorious approaches: 1) the resource-aware backbone search comprises profile and instantiation phases with the aim of identifying the optimal models that utilize either automatic mixed precision (AMP) or single precision floating point format (FP32), and 2) the proposed ensemble consists of multi-inferences with randomly flipped multi-resolution images to improve accuracy on the time and memory constraints.

1.1. Problem Description

ImageNet-100 is a subset of ImageNet-1K by choosing 100 classes and splitting them into training, validation, and test sets [2]. With the benchmark, our model is trained to maximize accuracy on the test set with a constraint of GPU memory (6 GB) and training time (9 GPU hours).

*Corresponding author

Algorithm 1 Procedure of our resource-aware backbone search

Profile phase: Profile candidate models.

Let denote available models $F = \{f_{\theta,q}^i \in \{\text{AMP,FP32}\}\}_{i=0}^N$ of PyTorch's timm. Tune parameters such as batch-size $b \in \mathbb{Z}^+$, input-size $s^{HW} \in \{160, 224\}$, and max-epochs m by pre-estimated training time $t \in \mathbb{R}^+$.

Candidates $C = \text{list}()$

```
for  $f_{\theta,q}^i \leftarrow F$  do
  for  $s^{hw} \leftarrow s^{HW}$  do
     $b^i, m^i \leftarrow \text{PROFILE\_MODEL}(f_{\theta,q}^i, s^{hw})$ 
     $C.\text{push\_back}((f_{\theta,q}^i, s^{hw}, b^i, m^i))$ 
  end for
```

end for

function PROFILE_MODEL($f_{\theta,q}^i, s^{hw}$)

Calculate the number of learnable-parameters $|f_{\theta,q}^i|$ with given i^{th} model.

Find maximum batch-size b with given $|f_{\theta,q}^i|$, s^{hw} , and 6GB memory by ϕ :

$\text{argmax}_{b \in \mathbb{Z}^+} \phi(b) := \{b \in \mathbb{Z}^+ : \phi(\hat{b}) < \phi(b), \forall \hat{b} \in \mathbb{Z}^+\}$.

$t \leftarrow \text{ESTIMATE_ONE_EPOCH_TIME}(f_{\theta,q}^i, b, s^{hw})$

Calculate max epochs m with estimated t and given 9 GPU hours.

return b, m

end function

function ESTIMATE_ONE_EPOCH_TIME($f_{\theta,q}^i, b, s^{hw}$)

Define dummy dataloader $D \in \{d_j\}_{j=0}^J$ with b and s^{hw} .

Measure training time t of one epoch.

for $d_j \leftarrow D$ do

$\mathcal{L} = f_{\theta,q}^i(d)$

if D is train set then

$\theta_{j+1,q} \leftarrow \theta_{j,q} - \eta \nabla \mathcal{L}(\theta_{j,q})$

end if

end for

return t

end function

Instantiation phase: Estimate and sort out the given candidates C through the order of validation accuracy on ImageNet-100 benchmark.

for $f_{\theta,q}^i, s^{hw}, b^i, m^i \leftarrow C$ do

for $e \leftarrow m^i$ do

$\text{train_acc} \leftarrow \text{TRAIN_MODEL}(f_{\theta,q}^i, s^{hw}, b^i)$

if $m^i - e < 3$ then

$\text{val_acc} \leftarrow \text{VAL_MODEL}(f_{\theta,q}^i, s^{hw}, b^i)$

end if

end for

end for

1.2. Implementation Details

We adjust the time-limitation for training models from 9 to 3 hours on RTX 3090 [1], adopt ResNest50d_1s4x24d [8] as our backbone, and set batch-size and max-epochs 65 and 46 in each. In addition, we employ the AdamW optimizer [6] and cosine scheduler [5].

Methods	Train image-size	Test image-size	Ensemble (En)	AMP	Val Acc.	Phase 1 Test Acc.	Phase 2 Test Acc.
Symmetric-sizes (SS)	160	160			87.08	84.62	86.28
Asymmetric-sizes (AS)	160	224			88.70	86.40	87.60
AS w/ En	160	224	✓		90.80	-	90.34
AS w/ AMP	160	224		✓	91.20	-	-
Ours (AS w/ En and AMP)	160	224	✓	✓	91.60	89.16	91.38

Table 1. Quantitative results on our method and ablation studies of key components at training and inference stages. The usage of input images with higher resolution at the inference stage improves 1.4%p validation accuracy (Val Acc.), and ensemble with the results from image-sizes 160 and 224 helps Val Acc. to rise an extra 2.1%p from the methods with asymmetric-sizes (AS). Moreover, adopting mixed precision training helps to improve training speed and enlarge batch-size so that the score of methods with AMP goes up about 2.5%p.

Models	# of params.	Batch-size	Image-size	Max-epochs	Val Acc.
EfficientNet_B0 [7]	4.1M	110	160	112	86.51
MobileNetV3 [4]	4.3M	200	160	110	84.12
EfficientNet_B1 [7]	6.6M	80	160	62	85.22
ResNet18 [3]	11.2M	256	160	110	83.24
ResNet26d [8]	15.2M	110	160	51	85.71
ResNet50 [3]	23.7M	100	160	60	86.92
ResNest50d¹ [8]	23.8M	<u>56</u>	160	<u>46</u>	87.08
ResNest50d [8]	25.6M	74	160	46	87.02
ResNest50d ² [8]	28.5M	58	160	36	87.01
ResNet101 [3]	42.7M	64	160	38	84.71

Table 2. Accuracy of candidate models trained with varying batch-sizes, image-sizes, and max-epochs. Val Acc. represents the accuracy of the validation dataset. ResNest50d¹ and ResNest50d² denote ResNest50d_1s4x24d and ResNest50d_4s2x40d, respectively.

1.3. Enlargement of batch-size using AMP

Our model is trained with mixed precision for less memory usage. As the required memory budget decreased by using AMP, it is possible to *increase the batch-size 56 to 96*. In addition, this leads to acceleration of the training speed so that *maximum epochs stretch 46 to 72*. As shown in Table 1, our method with mixed precision exceeds the model with no-AMP by 3%p higher validation accuracy. When the learnable-parameters of our model are calculated in a half-precision floating point format, the throughput becomes higher. Mixing FP16 and FP32 is automatically calculated by PyTorch in this challenge.

1.4. Asymmetric training and deploying image-sizes

To enforce the GPU memory constraint, we utilize the asymmetric image-sizes 160 and 224 for training and deploying individually. Moreover, our multi-inference ensembles combine the outputs of our model according to the test images and arbitrarily flipped test images. As indicated in Table 1, our approaches demonstrate consistently improved performance because the high-resolution images contain abundant information and the flipped images enable the randomness of our trained model.

1.5. Resource-aware backbone exploration

As illustrated in Table 2, we present candidate models with maximize batch-size and training epochs by our Algorithm 1. Those confirmed-parameters lead to an adaptive learning-rate for learning our models with a cosine annealing scheduler [5]. Consequently, we evaluate that

ResNest50d¹(radix 1, cardinality 4, and base-width 24) [8] serves as the most suitable backbone to adapt our methods: 1) increasing batch-size using AMP and 2) employing asymmetric training and deploying image-sizes. Finally, we validate that each of the two components contributed to performance improvement because larger batch-size, image-size, and epochs affect intra-domain performance in general as shown in Table 1.

2. Conclusion

We draw our approaches for International Conference on Computer Vision (ICCV) 2023 Workshop Challenge Track 1 on Resource Efficient Deep Learning for Computer Vision (RCV): Budgeted Model Training Challenge. Based on our approaches, we achieved first place in the challenge as indicated (our team named helloimjyk) on the final leader-board ¹.

Acknowledgements

This work was supported by KakaoBank Corporation.

References

- [1] <https://lambdalabs.com/gpu-benchmarks>.
- [2] <https://sites.google.com/view/rcv2023/workshop-challenges>.
- [3] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *CoRR*, abs/1512.03385, 2015.
- [4] Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, Quoc V. Le, and Hartwig Adam. Searching for mobilenetv3. *CoRR*, abs/1905.02244, 2019.
- [5] Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts, 2017.
- [6] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization, 2019.
- [7] Mingxing Tan and Quoc V. Le. Efficientnet: Rethinking model scaling for convolutional neural networks, 2020.
- [8] Hang Zhang, Chongruo Wu, Zhongyue Zhang, Yi Zhu, Haibin Lin, Zhi Zhang, Yue Sun, Tong He, Jonas Mueller, R. Manmatha, Mu Li, and Alexander Smola. Resnet: Split-attention networks, 2020.

¹<https://sites.google.com/view/rcv2023/leaderboard-workshop-challenges>.