

A-JEPA: Joint-Embedding Predictive Architecture Can Listen

Zhengcong Fei, Mingyuan Fan, Junshi Huang*

Kunlun Inc.

feizhengcong@gmail.com

Abstract

This paper presents that the masked-modeling principle driving the success of large foundational vision models can be effectively applied to audio by making predictions in a latent space. We introduce Audio-based Joint-Embedding Predictive Architecture (A-JEPA), a simple extension method for self-supervised learning from the audio spectrum. Following the design of I-JEPA, our A-JEPA encodes visible audio spectrogram patches with a curriculum masking strategy via context encoder, and predicts the representations of regions sampled at well-designed locations. The target representations of those regions are extracted by the exponential moving average of context encoder, *i.e.*, target encoder, on the whole spectrogram. We find it beneficial to transfer random block masking into time-frequency aware masking in a curriculum manner, considering the complexity of highly correlated in local time and frequency in audio spectrograms. To enhance contextual semantic understanding and robustness, we fine-tune the encoder with a regularized masking on target datasets, instead of input dropping or zero. Empirically, when built with Vision Transformers structure, we find A-JEPA to be highly scalable and sets new state-of-the-art performance on multiple audio and speech classification tasks, outperforming other recent models that use externally supervised pre-training.

1 Introduction

Numerous cognitive theories state that the process of adapting an internal model to predict the absence of input information is a crucial mechanism for learning in biological systems [Rao and Ballard, 1999]. The recent accomplishments of substantial foundational language models have been propelled by the utilization of the self-supervised mask-denosing paradigm, which involves learning through the process of filling in missing information [Devlin *et al.*, 2018; Brown *et al.*, 2020; Touvron *et al.*, 2023]. Moreover, masked




Figure 1: **Overview of A-JEPA.** The audio-based joint-embedding predictive architecture uses a context encoder to predict and align the representations of various target blocks in a latent space, originating from the same audio spectrogram.

pretraining tasks also dominate the performance of representation learning in computer vision [Bao *et al.*, 2021; He *et al.*, 2022; Zhou *et al.*, 2021; Fei *et al.*, 2023a].

The recently proposed image-based Joint-Embedding Predictive Architecture (JEPA) [LeCun, 2022; Assran *et al.*, 2023] demonstrates that one could learn well-performed image representations by predicting the masked image regions in a latent space. Compared to other methods for masked image modeling [He *et al.*, 2022; Fei, 2019; Tong *et al.*, 2022; Fei *et al.*, 2022; Fei, 2020; Yan *et al.*, 2021; Feichtenhofer *et al.*, 2022], which predict low-level visual tokens or pixels, JEPAs make predictions in a high-level representation space, where unnecessary pixel-level details can be eliminated, thereby leading the model to concentrate on more semantic features [Assran *et al.*, 2023]. However, the implementation of this learning principle on sensory data, *e.g.*, audio, continues to be a promising endeavor.

In this work, we study the problem of self-supervised rep-

*The corresponding author.

resentation learning on audio data and extend the JEPA-based learning principle to the audio spectrogram, which we refer to as A-JEPA: Audio-based Joint-Embedding Predictive Architecture. Different from JEPA for images, it is believed that the random block masking of audio spectrogram may be easy due to the correlation of information along the time and frequency axis [Tong *et al.*, 2022]. Therefore, the region masking strategy of A-JEPA is designed in a curriculum manner for the spectrogram of audio signal, *i.e.*, gradually from random block to time-frequency aware masking in a schedule. After that, we train the context-encoder by restoring the missing regions of masked spectrogram with the guidance from exponential moving averaged target-encoder in learned representation space. We minimize the patch-normalized mean square error to optimize the networks. At the fine-tuning stage, we discard the decoder and fine-tune the context encoder with regularized patch-masking, where the attention weights for the masked token are solely reliant on others rather than directly dropped patches or set to zero. We target to manipulate the connections between audio patches via masking, where the networks are forced to exploit partial neighbors’ information to produce a meaningful representation.

Empirically, the A-JEPA model exhibits exceptional performance in multiple audio and speech classification tasks, thereby establishing a new state-of-the-art benchmark. Notably, as a self-supervised audio-only model, it surpasses other contemporary competitors focused on masking and reconstruction by a significant margin of +1.3 points in terms of mAP on the AudioSet-2M dataset. We further provide the visualization and audible examples to qualitatively ascertain the efficacy of the A-JEPA. More encouragingly, our findings indicate that increasing the pre-training audio dataset size yields continued performance enhancements, even under fixed computational constraints. This observation suggests a promising avenue for further advancements in audio foundation models. Through an extensive empirical evaluation, we demonstrate that:

- This paper delves into a simple extension of JEPA to audio data, presenting a unified and scalable framework for learning self-supervised audio representations. To the best of our knowledge, it is the initial endeavor to apply JEPA to the audio area, yielding remarkably favorable outcomes.
- To cover the unique challenges of the audio domain, we introduce a curriculum masking strategy for gradually time-frequency aware pattern during pre-training, and regularized patch masking for robust information flow during fine-tuning.
- Experimental results substantiate the scalability and efficiency of the A-JEPA framework. Moreover, A-JEPA exhibits superior performance compared to pixel-reconstruction techniques like AudioMAE in AS-2M classification and other downstream tasks. Finally, the code and models will be publicly available.

2 Related Works

Joint-embedding architectures for masked pre-training. Masked and denoising autoencoders [Vincent *et al.*, 2008;

Vincent *et al.*, 2010; Devlin *et al.*, 2019] have emerged as versatile methods for learning representations by reconstructing the original source from masked or corrupted inputs [Fei and Huang, 2023; Fei *et al.*, 2023b]. In CV, a set of approaches attempt to integrate joint-embedding architectures with reconstruction-based approaches, wherein they employ an invariance pretraining loss with a patch-level reconstruction loss [Zhou *et al.*, 2021; Pathak *et al.*, 2016; Chen *et al.*, 2020a; He *et al.*, 2021; Wei *et al.*, 2021]. However, it is noteworthy that view-invariance-based methods often exhibit a bias towards learning global image representations. Adding local loss terms is proposed to improve performance on other popular tasks in computer vision [Bardes *et al.*, 2022; Chen *et al.*, 2022b; Gidaris *et al.*, 2020]. The concept of contrastive predictive coding [Oord *et al.*, 2018] is also closely connected to this research direction on local loss terms. In the context of images [Henaff, 2020], it uses a contrastive objective combined with a convolutional network to discriminate between overlapping image patch representations. Furthermore, I-JEPA [Assran *et al.*, 2023] aims to predict the representations of different target blocks from a single context block, thereby constructing semantic information. Our work extends the JEPA framework with unique designs for representation learning with audio spectrograms.

Out-of-domain and in-domain pre-training for audio.

Pre-training for audio representation can generally be divided into two main categories: (i) Transferring natural image supervised pre-trained ViT [Dosovitskiy *et al.*, 2020] or ResNet [He *et al.*, 2015], *e.g.*, ImageNet [Gong *et al.*, 2021a; Koutini *et al.*, 2021; Nagrani *et al.*, 2021; Chen *et al.*, 2022a; Gong *et al.*, 2021b; Gong *et al.*, 2022a]. In this approach, the models operate over audio spectrograms by deflating from three channels (RGB) into one channel (spectrogram) in the pre-trained patch embedding in ViT and employing the rest of the transformer blocks [Gong *et al.*, 2021a; Koutini *et al.*, 2021]. [Chen *et al.*, 2022a] encodes spectrograms initialized from the Swin Transformer [Liu *et al.*, 2021] and [Nagrani *et al.*, 2021] uses ImageNet-21K pre-trained ViT. Instead, our A-JEPA focuses on audio-only self-supervised pre-training from scratch. (ii) Audio-only self-supervised methods, which can be further split by the input signal type, *e.g.*, raw waveform [Schneider *et al.*, 2019; Baevski *et al.*, 2020; Baevski *et al.*, 2022], frame-level features [Hsu *et al.*, 2021; Shi *et al.*, 2022; Srivastava *et al.*, 2021], or spectrogram patches [Gong *et al.*, 2021c; Baade *et al.*, 2022]; and the objective used for self-supervision, *e.g.*, contrastive [van den Oord *et al.*, 2018; Baevski *et al.*, 2020; Arandjelovic and Zisserman, 2018; Patrick *et al.*, 2021; Hsu *et al.*, 2021] or prediction and reconstruction [Gong *et al.*, 2021c; Baevski *et al.*, 2022; Srivastava *et al.*, 2021; Shi *et al.*, 2022]. [Baevski *et al.*, 2020] takes raw waveform as inputs and exploits contrastive learning to differentiate contextualized representations across different time segments. [Liu *et al.*, 2020] introduces a pretext task of masked acoustic model, aiming to reconstruct frame-level Mel-features from masked time frames. [Gong *et al.*, 2021c; Baade *et al.*, 2022; Chong *et al.*, 2022; Niizumi *et al.*, 2022; Huang *et al.*, 2022] operates over spectrogram patches and

employs joint contrastive and reconstructive objectives on masked patches. Compared with prediction at a low level, we build in a latent space and showcase its superiority.

3 Approach

In this section, we review the standard joint-embedding predictive architecture (JEPA) and describe how we instantiate it for the audio domain as A-JEPA.

3.1 Joint-Embedding Predictive Architecture

The main idea of JEPA is to learn an encoder by predicting parts of input, *i.e.*, target regions, based on the visible context in the latent space. The basic architecture is made up of three networks: a context encoder $E_\theta(\cdot)$ and target encoder $E_{\tilde{\theta}}(\cdot)$ extract the representations of context and target regions, respectively. The predictor $P_\phi(\cdot, \cdot)$ is used to predict the target representation condition on the context representation from $E_\theta(\cdot)$. The parameters of target encoder $E_{\tilde{\theta}}(\cdot)$ are updated via the exponential moving average of context encoder weights at each iteration. The parameters of context encoder and predictor are optimized jointly by minimizing the distance of representations of target regions from predictor and target encoder.

3.2 Application to Audio

We instantiate the A-JEPA for audio by using a curriculum masking strategy in pre-training and regularized masking in fine-tuning. Generally, the context encoder extracts the representation of visible audio spectrogram pre-processed by our masking strategy, based on which the predictor outputs the representation of target regions in latent space. See Figure 1 for an overview.

Input spectrogram. In line with [Gong *et al.*, 2021a; Gong *et al.*, 2022b; Huang *et al.*, 2022], we transform audio signals into Mel-spectrograms and segment them into non-overlapped grid patches. These patches are then flattened and embedded by a linear projection. We also add fixed sinusoidal positional encoding to the patch embedding.

Curriculum masking strategy. Vanilla JEPA randomly masks out a block of spectrogram patches for the selection of context and target regions [Assran *et al.*, 2023]. As the spectrogram can be viewed as a 2D representation of audio along time and frequency with implicit entangles, it is reasonable to explore treating time and frequency differently during masking. Following [Huang *et al.*, 2022], we consider both random block masking without any prior and masking a portion of time and frequency of a spectrogram. It is believed that random block masking is comparably easier than time-frequency aware masking, as the model can guess the missing component by extrapolating nearby context, *e.g.*, formants in vowels and frictional sounds in consonants around. That is, directly applying block masking will retain enough information in the time domain and frequency domain. It would be more difficult to completely obscure information from a certain paradigm. To this end, we carefully design two masking strategies with adjustable scale factors for specific masking ratios, as shown in Figure 2.




Figure 2: **Examples of our context and target-masking strategy on Mel-spectrograms.** Given an audio spectrogram, (i) random block: we randomly sample 4 target blocks with scale in the range (0.15, 0.2) and aspect ratio in the range (0.75, 1.5); (ii) time and frequency: we randomly sample 3 target blocks with scale in the range (0.05, 0.075) and *remove all the related time or frequency* in the total Mel-spectrograms. Next, we randomly sample a context block with a scale in the range (0.85, 1.0) and *remove any overlapping target blocks*. **green** patches are selected while **gray** patches are removed.

Based on the above two masking strategies, we further propose an annealing dividing strategy with curriculum learning [Bengio *et al.*, 2009; Hachohen and Weinshall, 2019; Fei, 2021]. To be specific, we randomly decide whether to use random block or time-frequency aware masking at each training step and gradually anneal to the time-frequency aware masking method at the end of the training. Figure 3 illustrate several popular progressive functions. Formally, given the image I and the mask scale factor r , we define block masking set \mathcal{M} as follows:

$$p \sim \text{Bernoulli}(f(s)) \quad (1)$$

$$\mathcal{M} = \begin{cases} \text{Time-frequency}(I, r) & p = 1, \\ \text{Block}(I, r) & p = 0 \end{cases} \quad (2)$$

where $f(s)$ is the progressing function [Platanios *et al.*, 2019], and s denotes the training step. We set $f(s) = \min(1, \sqrt{s \frac{1-c_0^2}{S} + c_0^2})$, $c_0 > 0$ is set to 0.01 by default, as prior experiments shown a slight advantage compared with other schedule. $\text{Bernoulli}(\cdot)$ is the Bernoulli distribution with input $f(s)$. The entire process can be seen in Algorithm 1. Intuitively, a smaller value of $f(s)$ leads to easier reconstruction prediction. In this grade, $f(s)$ gradually increases from 0 to 1 automatically during pre-training, which results in a better representation performance.

Architecture. The employed architecture is reminiscent of the setting in [Huang *et al.*, 2022; He *et al.*, 2021; Assran *et al.*, 2023] and encompasses key components as: (i) *Context-encoder and target-encoder*. A-JEPA uses a stack of standard vision Transformers [Dosovitskiy *et al.*, 2020] as its encoder.




Figure 3: **Different curriculum function.** With the increase of the pre-training step, progressive function approx to hard (1) from easy (0) in different trends.

The encoder exclusively processes non-masked patches. Target encoder, shares an identical structure and its weights are updated iteratively via an exponential moving average of the context encoder weights. (ii) *Decoder* is also composed of standard Transformer blocks. The encoded patches from the encoder are padded with trainable masked tokens. After restoring the original time-frequency order in the audio spectrogram, we add fixed sinusoidal positional embeddings and feed the restored sequence into the decoder. At the topmost of the decoder, we add a linear head to predict and reconstruct the latent features.

Multi-mask objective. The objective is also simply to average the L2 distance between the output features of the predictor and the target encoder. To increase the efficiency of A-JEPA, we utilize a multi-masking strategy [Caron *et al.*, 2020; Baeviski *et al.*, 2023], which facilitates the amortization of the target computation expenses.

Fine-tuning with regularized masking. In the fine-tuning stage, we only keep and fine-tune the encoder and discard the decoder. An average pooling layer is applied followed by a linear layer on top in downstream tasks. On the other hand, certain works have attempted to integrate masking operations into the fine-tuning stage [Oneata and Cucu, 2022; Chen *et al.*, 2020b]. For example, SpecAug [Park *et al.*, 2019] takes full-length input with the masked portion set to zero as data augmentation; AudioMAE [Huang *et al.*, 2022] selectively encounters a subset of real-valued input patches without the nullified ones with low masking ration. However, these methods may still lead to a discrepancy between actual conditions.

In this study, we present regularized masking (RM), illustrated in Figure 4. In a nutshell, we modify the computing of self-attention to control the connections between different audio patch tokens, thereby influencing the attention scores and contextual semantic representation. Specifically, in the l -th layer, a certain percentage of audio patch tokens is first randomly selected. These tokens are excluded from the calculation of attention weights among the tokens, but entirely




Figure 4: **Regularize patch masking during fine-tuning.** Masked patch is forbidden to attend to attention computation where its attention score is entirely contributed by others. It manipulates the connections between patch tokens in self-attention via masking, where the networks are forced to exploit partial neighbors’ information to produce a meaningful representation.

Algorithm 1: Curriculum Masking Strategy

Input: Image size (w, h) , target scale s_t and aspect ratio r_t , context scale s_c and aspect ratio r_c , target mask number N_t , training step s , curriculum $f(\cdot)$;

- 1: Context size $\mathcal{S}_c = \text{Sample block Size}(w, h, s_c, r_c)$;
 - 2: Target size $\mathcal{S}_t = \text{Sample block Size}(w, h, s_t, r_t)$;
 - 3: $p \sim \text{Bernoulli}(f(s))$;
 - 4: Target mask list M_t , compliment target mask list C_t ;
 - 5: **for** i in range(N_t) **do**
 - 6: **if** $p=1$ **then**
 - 7: $m, c = \text{Sample time-frequency mask}(\mathcal{S}_t)$;
 - 8: **else**
 - 9: $m, c = \text{Sample block mask}(\mathcal{S}_t)$;
 - 10: **end if**
 - 11: M_t append m , C_t append c ;
 - 12: **end for**
 - 13: Acceptable region $\mathcal{R} = C_t$;
 - 14: Context mask $M_c = \text{Sample context mask}(\mathcal{S}_c, \mathcal{R})$;
 - 15: **return** M_t and M_c
-

contributed by remaining others. In this manner, the networks are required to utilize partial neighbors’ attention information, and robust to acquire meaningful information. We utilize RM in the fine-tuning phase while maintaining the attention calculation as the vanilla during testing.

4 Experiments

We perform an extensive evaluation on six tasks, including audio classification on AudioSet (AS-2M, AS-20K), Environmental Sound Classification (ESC-50), and speech classification on Speech Commands (SPC-1 and SPC-2) and VoxCeleb (SID). We use AudioSet for ablation studies. The implementation details can be seen in Appendix A.

4.1 Experimental settings.

For a comparable comparison, similar to [Huang *et al.*, 2022], we utilize the following tasks with datasets:

- (i) AudioSet [Gemmeke *et al.*, 2017] (AS-2M, AS-20K) comprises approximately 2 million 10 seconds that are utilized for audio classification purposes. Each clip in the dataset is weakly annotated for 527 types of audio events [Li *et al.*, 2022; Hershey *et al.*, 2017; Hershey *et al.*, 2021],

Model	Backbone	PT-Data	AS-20K	AS-2M	ESC-50	SPC-2	SPC-1	SID
<i>No pre-training</i>								
ERANN [Verbitskiy <i>et al.</i> , 2021]	CNN	-	-	45.0	89.2	-	-	-
PANN [Kong <i>et al.</i> , 2020]	CNN	-	27.8	43.1	83.3	61.8	-	-
<i>In-domain self-supervised pre-training</i>								
wav2vec 2.0 [Baevski <i>et al.</i> , 2020]	Transformer	LS	-	-	-	-	96.2*	75.2*
HuBERT [Hsu <i>et al.</i> , 2021]	Transformer	LS	-	-	-	-	96.3*	81.4*
Conformer [Srivastava <i>et al.</i> , 2021]	Conformer	AS	-	41.1	88.0	-	-	-
SS-AST [Gong <i>et al.</i> , 2021c]	ViT-B	AS+LS	31.0	-	88.8	98.0	96.0	64.3
<i>Mask and reconstruction works</i>								
MaskSpec [Chong <i>et al.</i> , 2022]	ViT-B	AS	32.3	47.1	89.6	97.7	-	-
MAE-AST [Baade <i>et al.</i> , 2022]	ViT-B	AS+LS	30.6	-	90.0	97.9	95.8	63.3
Audio-MAE [Huang <i>et al.</i> , 2022]	ViT-B	AS	37.0	47.3	94.1	98.3	96.9	94.8
A-JEPA	ViT-B	AS	38.4	48.6	96.3	98.5	97.7	95.8
<i>Out-of-domain supervised pre-training</i>								
PSLA [Gong <i>et al.</i> , 2021b]	EfficientNet	IN	31.9	44.4	-	96.3	-	-
AST [Gong <i>et al.</i> , 2021a]	DeiT-B	IN	34.7	45.9	88.7	98.1	95.5	41.1
MBT [Nagrani <i>et al.</i> , 2021]	ViT-B	IN-21K	31.3	44.3	-	-	-	-
HTS-AT [Chen <i>et al.</i> , 2022a]	Swin-B	IN	-	47.1	97.0	98.0	-	-
PaSST [Koutini <i>et al.</i> , 2021]	DeiT-B	IN	-	47.1	96.8	-	-	-

Table 1: **Comparison with other state-of-the-art audio representation models** on audio and speech classification tasks. We use the mAP (%) metric for AS and the accuracy metric for ESC/SPC/SID tasks. For pre-training (PT) dataset, we simplify as AudioSet (AS), LibriSpeech (LS), and ImageNet (IN). [†] denotes Fine-tuning results with additional supervised training on AS-2M. We gray-out models pre-trained with external non-audio datasets, e.g., ImageNet. The best single models in AS-2M are compared in no ensembles. * represents linear evaluation results from corresponding papers.

with the possibility of multiple events occurring within a single clip. The dataset consists of a full training set, which is further divided into two subsets: a class-wise balanced set containing 22,176 clips, and an unbalanced set containing 2,042,985 clips. Additionally, an evaluation set with 20,383 clips is provided for testing purposes. To conduct our experiments, we obtained and processed a subset of the dataset, comprising 1.96M clips from the unbalanced training set, 21k clips from the balanced training set, and 19k clips from the evaluation set. We use the union of unbalanced and balanced training audio for pre-training and fine-tuning for AS-2M; We use AS-2M for pre-training and the 20K balanced set for fine-tuning in the AS-20K experiment. We report the testing mAP on the 19K eval set following AST [Gong *et al.*, 2021a].

(ii) Environmental Sound Classification (ESC-50) [Piczak, 2015] is a collection of 2,000 environmental sound recordings for audio classification. Each lasts 5 seconds and there are 50 classes in ESC. We report accuracy under 5-fold cross-validation with the same split used by [Gong *et al.*, 2021a].

(iii) Speech Commands (SPC-2, SPC-1) [Warden, 2018] pertain two keyword spotting tasks. SPC-2 encompasses a set of 35 speech commands. The training set is 84,843 and the testing and validation sets are with sizes 11,005, and 9,981 respectively. Each with a duration of 1 second. SPC-1 encompasses 10 classes of keywords, 1 silence class, and 1 unknown class that includes all remaining 20 common speech commands. We employ the data and partitioning from SUPERB [wen Yang *et al.*, 2021] benchmark to report the testing accuracy.

Backbone	#Params	AS-20K	AS-2M
ViT-S	22M	33.7	46.1
ViT-B	86M	38.4	48.6
ViT-L	304M	38.8	48.8

Table 2: **Ablating model size.** Evaluating the impact of model size on downstream tasks. A-JEPA benefits from larger models.

(iv) VoxCeleb (SID) [Nagrani *et al.*, 2020] comprises 150K utterances attributed to 1,251 distinct speakers. The speaker identification task (SID) involves to classify the utterances to identify their original speaker. We use the V1 version for training, validation, and testing sets with 128k, 6k, and 8k, and report the testing accuracy metric.

4.2 Comparison with the State-of-the-art

Table 1 presents a comprehensive comparison of A-JEPA against previous state-of-the-art models for audio representation learning. The analysis is divided into three distinct groups. To ensure a fair evaluation, our primary focus lies on models within the middle group, which have undergone self-supervised pre-training using in-domain audio-only datasets. In addition, we include other models without any pre-training at the top group and models with supervised pre-training on out-of-domain ImageNet at the bottom group, where the latter comprises the previous leading systems on the respective datasets. Among the models with in-domain self-supervised pre-training, A-JEPA, pre-trained on AudioSet, exhibits the highest performance across all tasks. Notably, its mAP score of 38.4 on the AudioSet-20K dataset surpasses all alterna-

Mask	Backbone	Mask Ratio	mAP
Curriculum	ViT-B	0.75	48.6
Random	ViT-B	0.75	47.8
Inverse	ViT-B	0.75	46.3

Table 3: **Ablating masking strategy in pre-training.** The proposed curriculum masking strategy is preferred.

Model	Backbone	Masking Ratio	mAP
A-JEPA	ViT-B	0.1	48.6
w/o RM	ViT-B	0.1	48.1

Table 4: **Ablating regularized masking (RM) in fine-tuning.** The proposed regularized masking strategy in fine-tuning is helpful for guiding A-JEPA to learn more robust audio representations.

tive approaches, including previous masking-reconstruction works Conformer [Srivastava *et al.*, 2021], SS-AST [Gong *et al.*, 2021c] and AudioMAE [Huang *et al.*, 2022]. In the low-most group of Table 1, A-JEPA also demonstrates superior performance compared to previous state-of-the-art models that employed ImageNet supervised pre-training. It is worth noting that A-JEPA, the proposed approach, does not rely on external data or labels from unrelated domains. More encouragingly, as indicated in the experiments conducted in [Kong *et al.*, 2020], there is a potential for further mAP enhancement for A-JEPA if audio data with a sampling rate of 32K becomes available. The advantage is still maintained for the speech tasks, including SPC-1, SPC-2, and SID. In summary, A-JEPA, which leverages audio-only pre-training from scratch using AudioSet, achieves commendable performance in both audio and speech classification tasks through the incorporation of feature alignment.

4.3 Model Analysis

Model scalability. We study the various design choices pertaining to encoder architectures in the A-JEPA. Table 2 illustrates the trade-off between encoder model size and its performance. It is observed that larger encoder models tend to exhibit superior performance, albeit at the expense of increased computational requirements and memory utilization. Moreover, it is noted that the accuracy improvement of ViT-L over ViT-B/S is particularly pronounced when applied to the smaller and more balanced AS-20K dataset. Additionally, the performance disparity between ViT-S and ViT-B can be considerably diminished, e.g., from 4.7 to 2.5 mAP, by employing fine-tuning techniques with a greater volume of in-domain data, e.g., from AS-20K to AS-2M, as observed in [Huang *et al.*, 2022].

Masking strategies in pre-training and fine-tuning. We also present a comparison of different pre-training masking strategies for A-JEPA in In Table 3. The results obtained from our experiments reveal that curriculum masking outperforms random block masking. This finding suggests that a guided approach to time-frequency aware masking, yields superior performance. Moreover, inverse strategy denotes that first time and frequency and then random masking, which results in a more significant performance drop, demonstrate the

Depth	Backbone	Epoch	mAP
8	ViT-B	24	48.3
16	ViT-B	24	48.6

Table 5: **Ablating the predictor depth.** Increasing the predictor depth leads to a prominent performance improvement of the pre-trained audio representations.

Width	Backbone	Epoch	mAP
256	ViT-B	24	48.0
512	ViT-B	24	48.6
768	ViT-B	24	48.5

Table 6: **Ablating the predictor width.** Having a width bottleneck in the predictor improves the downstream performances.

effectiveness of our method again. In general, we observe that for task-agnostic pre-training, curriculum masking from easy to hard with a high ratio is preferred. On the other hand, when it comes to fine-tuning, as illustrated in Table 4, employing regularized patch masking with lower ratios achieves better performance in downstream tasks.

Predictor depth and width. The impact of decoder depth on mean average precision (mAP) is evaluated in Table 5. A 16-layer decoder, being deeper than its shallower counterparts, exhibits superior performance. Furthermore, Table 6 presents a comparison of decoder widths, specifically the embedding dimension. The results indicate that a 512-dimension decoder strikes a favorable balance between computational requirements and performance, as increasing the width beyond this threshold does not yield significant improvements.

Pre-training data size and epochs. Figure 5 depicted the influence of pre-training dataset size. A subset of data is randomly sampled from originals for pre-training. It is observed that the performance of the model consistently improves with an increase in the amount of data used for pre-training. Meanwhile, as shown in Figure 7, we also plot the mAP score at different training epochs. It is evident that prolonging the training duration yields favorable outcomes; however, the performance reaches a plateau after the 24th epoch.

4.4 Predictor Visualizations

The purpose of the predictor component in I-JEPA is to utilize the output of the context-encoder and provide predictions for the representations of a target object at a specific location, as specified by the positional mask tokens. In this section, we aim to analyze whether the predictor conditioned on the positional mask tokens is learning to correctly capture positional uncertainty in the target in the audio spectrogram. Specifically, we qualitatively visualize the outputs of the predictor referring to [Assran *et al.*, 2023]. After pretraining, we freeze the context-encoder and predictor weights, and train a decoder following the RCDM framework [Bordes *et al.*, 2021] to map the average pool of the predictor outputs back to pixel space. The outputs of the decoder for different random seeds are illustrated in Figure 5. Shared characteristics observed across multiple samples indicate information that is conveyed




Figure 5: **Visualization of A-JEPA predictor representations.** The first column presents the original audio spectrogram, while the second column displays the context audio spectrogram, which is processed with a pre-trained A-JEPA ViT-B encoder. **red** bounding boxes, in subsequent columns, showcase samples created from a generative model. It decoded the output of the pre-trained A-JEPA predictor, conditioned on positional mask tokens corresponding to the location of the bounding box. It is worth noting that qualities shared among these samples indicate the information contained in the A-JEPA prediction.




Figure 6: **Ablating pre-training data size.** When increasing the size of the pre-training dataset, we see a significant performance improvement in audio representation for the ViT-B model.

within the average-pooled predictor representation. It is noteworthy that the A-JEPA predictor successfully captures positional uncertainty and generates high-level audio components with an accurate pose.

5 Conclusion

We have conducted an investigation into an extension of JEPA to audio data. Our A-JEPA is designed to reconstruct masked spectrogram patches from audio recordings within a latent space and achieves superior performance on multiple audio and speech classification tasks. We have made three noteworthy observations: First, a straightforward application of JEPA




Figure 7: **Ablating pre-training epochs on ViT-B backbone in AudioSet.** Training for longer is beneficial for downstream task performance.

yields remarkable outcomes for audio spectrograms. Second, we find that it is possible to enhance the quality of learned representations with a time-frequency aware masking strategy progressing from easy to hard. Third, we show that regularized masking, instead of directly dropping or setting to zero, can be applied to fine-tuning, contributing to accuracy improvement. In the future, we intend to explore multi-modal self-supervised learning with a joint latent embedding, *e.g.*, video and text modals, to provide a better formulation of audio representation guidance.

References

- [Arandjelovic and Zisserman, 2018] Relja Arandjelovic and Andrew Zisserman. Objects that sound. In Vittorio Ferrari, Martial Hebert, Cristian Sminchisescu, and Yair Weiss, editors, *Computer Vision - ECCV 2018 - 15th European Conference, Munich, Germany, September 8-14, 2018, Proceedings, Part I*, volume 11205 of *Lecture Notes in Computer Science*, pages 451–466. Springer, 2018.
- [Assran et al., 2023] Mahmoud Assran, Quentin Duval, Ishan Misra, Piotr Bojanowski, Pascal Vincent, Michael Rabbat, Yann LeCun, and Nicolas Ballas. Self-supervised learning from images with a joint-embedding predictive architecture. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15619–15629, 2023.
- [Baade et al., 2022] Alan Baade, Puyuan Peng, and David Harwath. Mae-ast: Masked autoencoding audio spectrogram transformer. *arXiv preprint arXiv:2203.16691*, 2022.
- [Baevski et al., 2020] Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. wav2vec 2.0: A framework for self-supervised learning of speech representations. In Hugo Larochelle, Marc’Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.
- [Baevski et al., 2022] Alexei Baevski, Wei-Ning Hsu, Qiantong Xu, Arun Babu, Jiatao Gu, and Michael Auli. data2vec: A general framework for self-supervised learning in speech, vision and language. *CoRR*, abs/2202.03555, 2022.
- [Baevski et al., 2023] Alexei Baevski, Arun Babu, Wei-Ning Hsu, and Michael Auli. Efficient self-supervised learning with contextualized target representations for vision, speech and language. In *International Conference on Machine Learning*, pages 1416–1429. PMLR, 2023.
- [Bao et al., 2021] Hangbo Bao, Li Dong, Songhao Piao, and Furu Wei. Beit: Bert pre-training of image transformers. *arXiv preprint arXiv:2106.08254*, 2021.
- [Bardes et al., 2022] Adrien Bardes, Jean Ponce, and Yann LeCun. Vicregl: Self-supervised learning of local visual features. *Advances in Neural Information Processing Systems*, 35:8799–8810, 2022.
- [Bengio et al., 2009] Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th annual international conference on machine learning*, pages 41–48, 2009.
- [Bordes et al., 2021] Florian Bordes, Randall Balestriero, and Pascal Vincent. High fidelity visualization of what your self-supervised representation knows about. *arXiv preprint arXiv:2112.09164*, 2021.
- [Brown et al., 2020] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.
- [Caron et al., 2020] Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. *Advances in neural information processing systems*, 33:9912–9924, 2020.
- [Chen et al., 2020a] Mark Chen, Alec Radford, Rewon Child, Jeffrey Wu, Heewoo Jun, David Luan, and Ilya Sutskever. Generative pretraining from pixels. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 1691–1703. PMLR, 2020.
- [Chen et al., 2020b] Pengguang Chen, Shu Liu, Hengshuang Zhao, and Jiaya Jia. Gridmask data augmentation. *arXiv preprint arXiv:2001.04086*, 2020.
- [Chen et al., 2022a] Ke Chen, Xingjian Du, Bilei Zhu, Zhenjun Ma, Taylor Berg-Kirkpatrick, and Shlomo Dubnov. Hts-at: A hierarchical token-semantic audio transformer for sound classification and detection. *arXiv preprint arXiv:2202.00874*, 2022.
- [Chen et al., 2022b] Yubei Chen, Adrien Bardes, ZENGYI LI, and Yann LeCun. Intra-instance vicreg: Bag of self-supervised image patch embedding explains the performance. 2022.
- [Chong et al., 2022] Dading Chong, Helin Wang, Peilin Zhou, and Qingcheng Zeng. Masked spectrogram prediction for self-supervised audio pre-training, 2022.
- [Devlin et al., 2018] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.
- [Devlin et al., 2019] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In Jill Burstein, Christy Doran, and Thamar Solorio, editors, *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, pages 4171–4186. Association for Computational Linguistics, 2019.
- [Dosovitskiy et al., 2020] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.
- [Fei and Huang, 2023] Zhengcong Fei and Junshi Huang. Incorporating unlikely negative cues for distinctive image captioning. 2023.
- [Fei et al., 2022] Zhengcong Fei, Xu Yan, Shuhui Wang, and Qi Tian. Deccap: Dynamic early exiting for efficient im-

- age captioning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12216–12226, 2022.
- [Fei *et al.*, 2023a] Zhengcong Fei, Mingyuan Fan, Li Zhu, Junshi Huang, Xiaoming Wei, and Xiaolin Wei. Masked auto-encoders meet generative adversarial networks and beyond. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 24449–24459, 2023.
- [Fei *et al.*, 2023b] Zhengcong Fei, Mingyuan Fan, Li Zhu, Junshi Huang, Xiaoming Wei, and Xiaolin Wei. Uncertainty-aware image captioning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pages 614–622, 2023.
- [Fei, 2019] Zheng-cong Fei. Fast image caption generation with position alignment. *arXiv preprint arXiv:1912.06365*, 2019.
- [Fei, 2020] Zhengcong Fei. Iterative back modification for faster image captioning. In *Proceedings of the 28th ACM International Conference on Multimedia*, pages 3182–3190, 2020.
- [Fei, 2021] Zhengcong Fei. Partially non-autoregressive image captioning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 1309–1316, 2021.
- [Feichtenhofer *et al.*, 2022] Christoph Feichtenhofer, Yanghao Li, Kaiming He, et al. Masked autoencoders as spatiotemporal learners. *Advances in neural information processing systems*, 35:35946–35958, 2022.
- [Gemmeke *et al.*, 2017] Jort F Gemmeke, Daniel PW Ellis, Dylan Freedman, Aren Jansen, Wade Lawrence, R Channing Moore, Manoj Plakal, and Marvin Ritter. Audio set: An ontology and human-labeled dataset for audio events. In *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 776–780. IEEE, 2017.
- [Gidaris *et al.*, 2020] Spyros Gidaris, Andrei Bursuc, Nikos Komodakis, Patrick Pérez, and Matthieu Cord. Learning representations by predicting bags of visual words. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6928–6938, 2020.
- [Gong *et al.*, 2021a] Yuan Gong, Yu-An Chung, and James R. Glass. AST: audio spectrogram transformer. In Hynek Hermansky, Honza Cernocký, Lukás Burget, Lori Lamel, Odette Scharenborg, and Petr Motlíček, editors, *Interspeech 2021, 22nd Annual Conference of the International Speech Communication Association, Brno, Czechia, 30 August - 3 September 2021*, pages 571–575. ISCA, 2021.
- [Gong *et al.*, 2021b] Yuan Gong, YuAn Chung, and James Glass. Psla: Improving audio tagging with pretraining, sampling, labeling, and aggregation. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 2021.
- [Gong *et al.*, 2021c] Yuan Gong, Cheng-I Lai, Yu-An Chung, and James R. Glass. Ssast: Self-supervised audio spectrogram transformer. *ArXiv*, abs/2110.09784, 2021.
- [Gong *et al.*, 2022a] Yuan Gong, Sameer Khurana, Andrew Rouditchenko, and James Glass. Cmkd: Cnn/transformer-based cross-model knowledge distillation for audio classification, 2022.
- [Gong *et al.*, 2022b] Yuan Gong, Cheng-I Lai, Yu-An Chung, and James Glass. Ssast: Self-supervised audio spectrogram transformer. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 10699–10709, 2022.
- [Hacohen and Weinshall, 2019] Guy Hacohen and Daphna Weinshall. On the power of curriculum learning in training deep networks. In *International conference on machine learning*, pages 2535–2544. PMLR, 2019.
- [He *et al.*, 2015] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2015.
- [He *et al.*, 2021] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. *arXiv preprint arXiv:2111.06377*, 2021.
- [He *et al.*, 2022] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 16000–16009, 2022.
- [Henaff, 2020] Olivier Henaff. Data-efficient image recognition with contrastive predictive coding. In *International conference on machine learning*, pages 4182–4192. PMLR, 2020.
- [Hershey *et al.*, 2017] Shawn Hershey, Sourish Chaudhuri, Daniel P. W. Ellis, Jort F. Gemmeke, Aren Jansen, Channing Moore, Manoj Plakal, Devin Platt, Rif A. Saurous, Bryan Seybold, Malcolm Slaney, Ron Weiss, and Kevin Wilson. Cnn architectures for large-scale audio classification. In *International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. 2017.
- [Hershey *et al.*, 2021] Shawn Hershey, Daniel PW Ellis, Eduardo Fonseca, Aren Jansen, Caroline Liu, R Channing Moore, and Manoj Plakal. The benefit of temporally-strong labels in audio event classification. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 366–370. IEEE, 2021.
- [Hsu *et al.*, 2021] Wei-Ning Hsu, Benjamin Bolte, Yao-Hung Hubert Tsai, Kushal Lakhota, Ruslan Salakhutdinov, and Abdelrahman Mohamed. Hubert: Self-supervised speech representation learning by masked prediction of hidden units. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 29:3451–3460, 2021.
- [Huang *et al.*, 2022] Po-Yao Huang, Hu Xu, Juncheng Li, Alexei Baevski, Michael Auli, Wojciech Galuba, Florian Metze, and Christoph Feichtenhofer. Masked autoencoders that listen. *Advances in Neural Information Processing Systems*, 35:28708–28720, 2022.

- [Kong *et al.*, 2020] Qiuqiang Kong, Yin Cao, Turab Iqbal, Yuxuan Wang, Wenwu Wang, and Mark D. Plumbley. Panns: Large-scale pretrained audio neural networks for audio pattern recognition. *IEEE ACM Trans. Audio Speech Lang. Process.*, 28:2880–2894, 2020.
- [Koutini *et al.*, 2021] Khaled Koutini, Jan Schlüter, Hamid Eghbal-zadeh, and Gerhard Widmer. Efficient training of audio transformers with patchout. *CoRR*, abs/2110.05069, 2021.
- [LeCun, 2022] Yann LeCun. A path towards autonomous machine intelligence version 0.9. 2, 2022-06-27. *Open Review*, 62, 2022.
- [Li *et al.*, 2022] Juncheng B. Li, Shuhui Qu, Po-Yao Huang, and Florian Metze. Audiotagging done right: 2nd comparison of deep learning methods for environmental sound classification. *CoRR*, abs/2203.13448, 2022.
- [Liu *et al.*, 2020] Andy T. Liu, Shu-Wen Yang, Po-Han Chi, Po-chun Hsu, and Hung-yi Lee. Mockingjay: Unsupervised speech representation learning with deep bidirectional transformer encoders. In *2020 IEEE International Conference on Acoustics, Speech and Signal Processing, ICASSP 2020, Barcelona, Spain, May 4-8, 2020*, pages 6419–6423. IEEE, 2020.
- [Liu *et al.*, 2021] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *2021 IEEE/CVF International Conference on Computer Vision, ICCV 2021, Montreal, QC, Canada, October 10-17, 2021*, pages 9992–10002. IEEE, 2021.
- [Nagrani *et al.*, 2020] Arsha Nagrani, Joon Son Chung, Weidi Xie, and Andrew Senior. Voxceleb: Large-scale speaker verification in the wild. *Comput. Speech Lang.*, 60, 2020.
- [Nagrani *et al.*, 2021] Arsha Nagrani, Shan Yang, Anurag Arnab, Aren Jansen, Cordelia Schmid, and Chen Sun. Attention bottlenecks for multimodal fusion. In Marc’Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan, editors, *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pages 14200–14213, 2021.
- [Niizumi *et al.*, 2022] Daisuke Niizumi, Daiki Takeuchi, Yasunori Ohishi, Noboru Harada, and Kunio Kashino. Masked spectrogram modeling using masked autoencoders for learning general-purpose audio representation. *arXiv:2204.12260*, 2022.
- [Oneata and Cucu, 2022] Dan Oneata and Horia Cucu. Improving multimodal speech recognition by data augmentation and speech representations. *arXiv preprint arXiv:2204.13206*, 2022.
- [Oord *et al.*, 2018] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.
- [Park *et al.*, 2019] Daniel S Park, William Chan, Yu Zhang, Chung-Cheng Chiu, Barret Zoph, Ekin D Cubuk, and Quoc V Le. SpecAugment: A simple data augmentation method for automatic speech recognition. *arXiv preprint arXiv:1904.08779*, 2019.
- [Pathak *et al.*, 2016] Deepak Pathak, Philipp Krähenbühl, Jeff Donahue, Trevor Darrell, and Alexei A. Efros. Context encoders: Feature learning by inpainting. In *2016 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2016, Las Vegas, NV, USA, June 27-30, 2016*, pages 2536–2544. IEEE Computer Society, 2016.
- [Patrick *et al.*, 2021] Mandela Patrick, Po-Yao Huang, Ishan Misra, Florian Metze, Andrea Vedaldi, Yuki M. Asano, and João F. Henriques. Space-time crop & attend: Improving cross-modal video representation learning. In *2021 IEEE/CVF International Conference on Computer Vision, ICCV 2021, Montreal, QC, Canada, October 10-17, 2021*, pages 10540–10552. IEEE, 2021.
- [Piczak, 2015] Karol J. Piczak. ESC: Dataset for Environmental Sound Classification. In *Proceedings of the 23rd Annual ACM Conference on Multimedia*, pages 1015–1018. ACM Press, 2015.
- [Platanios *et al.*, 2019] Emmanouil Antonios Platanios, Otilia Stretcu, Graham Neubig, Barnabas Poczos, and Tom M Mitchell. Competence-based curriculum learning for neural machine translation. *arXiv preprint arXiv:1903.09848*, 2019.
- [Povey *et al.*, 2011] Daniel Povey, Arnab Ghoshal, Gilles Boulianne, Lukas Burget, Ondrej Glembek, Nagendra Goel, Mirko Hannemann, Petr Motlicek, Yanmin Qian, Petr Schwarz, et al. The kaldi speech recognition toolkit. In *IEEE 2011 workshop on automatic speech recognition and understanding*, number CONF. IEEE Signal Processing Society, 2011.
- [Rao and Ballard, 1999] Rajesh PN Rao and Dana H Ballard. Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. *Nature neuroscience*, 2(1):79–87, 1999.
- [Schneider *et al.*, 2019] Steffen Schneider, Alexei Baevski, Ronan Collobert, and Michael Auli. wav2vec: Unsupervised pre-training for speech recognition. In Gernot Kubin and Zdravko Kacic, editors, *Interspeech 2019, 20th Annual Conference of the International Speech Communication Association, Graz, Austria, 15-19 September 2019*, pages 3465–3469. ISCA, 2019.
- [Shi *et al.*, 2022] Bowen Shi, Wei-Ning Hsu, and Abdelrahman Mohamed. Robust self-supervised audio-visual speech recognition. *CoRR*, abs/2201.01763, 2022.
- [Srivastava *et al.*, 2021] Sangeeta Srivastava, Yun Wang, Andros Tjandra, Anurag Kumar, Chunxi Liu, Kritika Singh, and Yatharth Saraf. Conformer-based self-supervised learning for non-speech audio tasks. *arXiv preprint arXiv:2110.07313*, 2021.
- [Tong *et al.*, 2022] Zhan Tong, Yibing Song, Jue Wang, and Limin Wang. Videomae: Masked autoencoders

- are data-efficient learners for self-supervised video pre-training. *Advances in neural information processing systems*, 35:10078–10093, 2022.
- [Touvron *et al.*, 2023] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.
- [van den Oord *et al.*, 2018] Aäron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *CoRR*, abs/1807.03748, 2018.
- [Verbitskiy *et al.*, 2021] Sergey Verbitskiy, Vladimir Berikov, and Viacheslav Vyshegorodtsev. Eranns: Efficient residual audio neural networks for audio pattern recognition. *arXiv preprint arXiv:2106.01621*, 2021.
- [Vincent *et al.*, 2008] Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. Extracting and composing robust features with denoising autoencoders. In William W. Cohen, Andrew McCallum, and Sam T. Roweis, editors, *Machine Learning, Proceedings of the Twenty-Fifth International Conference (ICML 2008), Helsinki, Finland, June 5-9, 2008*, volume 307 of *ACM International Conference Proceeding Series*, pages 1096–1103. ACM, 2008.
- [Vincent *et al.*, 2010] Pascal Vincent, Hugo Larochelle, Isabelle Lajoie, Yoshua Bengio, and Pierre-Antoine Manzagol. Stacked denoising autoencoders: Learning useful representations in a deep network with a local denoising criterion. *J. Mach. Learn. Res.*, 11:3371–3408, 2010.
- [Warden, 2018] P. Warden. Speech Commands: A Dataset for Limited-Vocabulary Speech Recognition. *ArXiv e-prints*, April 2018.
- [Wei *et al.*, 2021] Chen Wei, Haoqi Fan, Saining Xie, Chao-Yuan Wu, Alan L. Yuille, and Christoph Feichtenhofer. Masked feature prediction for self-supervised visual pre-training. *CoRR*, abs/2112.09133, 2021.
- [wen Yang *et al.*, 2021] Shu wen Yang, Po-Han Chi, Yung-Sung Chuang, Cheng-I Jeff Lai, Kushal Lakhotia, Yist Y. Lin, Andy T. Liu, Jiatong Shi, Xuankai Chang, Guanting Lin, Tzu-Hsien Huang, Wei-Cheng Tseng, Ko tik Lee, Da-Rong Liu, Zili Huang, Shuyan Dong, Shang-Wen Li, Shinji Watanabe, Abdelrahman Mohamed, and Hung yi Lee. SUPERB: Speech Processing Universal Performance Benchmark. In *Proc. Interspeech 2021*, pages 1194–1198, 2021.
- [Yan *et al.*, 2021] Xu Yan, Zhengcong Fei, Zekang Li, Shuhui Wang, Qingming Huang, and Qi Tian. Semi-autoregressive image captioning. In *Proceedings of the 29th ACM International Conference on Multimedia*, pages 2708–2716, 2021.
- [Zhou *et al.*, 2021] Jinghao Zhou, Chen Wei, Huiyu Wang, Wei Shen, Cihang Xie, Alan Yuille, and Tao Kong. ibot: Image bert pre-training with online tokenizer. *arXiv preprint arXiv:2111.07832*, 2021.

A Implementation Details

For model structure, we use a vanilla 12-layer ViT-B by default as the Transformer encoder and use a 16-layer vanilla Transformer as the decoder. The design of other ViT model sizes is identical to [Huang *et al.*, 2022]. Following [Gong *et al.*, 2021a; Nagrani *et al.*, 2021], we convert raw waveform, pre-processed as mono channel under 16,000 sampling rate, into 128 Kaldi-compatible Mel-frequency bands [Povey *et al.*, 2011] with a 25ms Hanning window that shifts every 10 ms. In the case of a 10-second recording in AudioSet, the resulting spectrogram is of $1 \times 1024 \times 128$ dimension. For patch embedding, we employ convolutional kernels with a size of (16, 16) and apply a stride in both time and frequency, ensuring that the resulting patches are non-overlapping. We sample 4 possibly overlapping target random blocks with a scale in the range (0.15, 0.2) and aspect ratio in the range (0.75, 1.5); sample time-frequency aware 3 target blocks with scale in the range (0.05, 0.075). We sample 1 context block mask with a random scale in the range (0.85, 1.0) and unit aspect ratio. We subsequently eliminate specific regions, different for random and time-frequency, in the context block mask that overlaps with any of the target block masks. These hyperparameters are tested in prior experiments to balance a patch available number. The context-block mask and target-block masks are sampled independently for each image in the mini-batch.

The pre-training phase involves the utilization of AudioSet-2M, wherein we conduct a random iteration over all audio recordings. We train for 24 epochs with a batch size of 512, coupled with a learning rate of $2e-4$. For each audio, we randomly sample the starting time, cyclically extract a 10-second audio segment, and randomly jitter its magnitude by up to ± 6 dB. During fine-tuning, we employ a 10% regularized patch masking ratio by default. For the supervised fine-tuning on AudioSet-2M, to address the issue of imbalanced training sample sizes across classes, we follow the common practice of using a weighted sampling to balance the classes during training [Huang *et al.*, 2022]. In each epoch, we sample 200K instances, approximately 10% of AudioSet-2M, without replacement. We fine-tune for 100 epochs, which aggregate to 10 full epochs of AudioSet-2M. This sampling procedure ensures that the probability of selecting an instance is inversely proportional to the occurrences of its corresponding class within the dataset. For the smaller balanced AudioSet-20K, we fine-tune for 60 epochs without weighted sampling. We use the Sqrt progressive function based on prior observations.

B Pytorch Code for Time-frequency Aware Masking

We provide the pytorch implementation for time-frequency aware masking.

Listing 1: Pytorch code for time-frequency aware masking

```
1 def sampe_time_frequency_mask(b_size,
2   acceptable_regions=None, min_ratio
3   =0.35):
4   """b_size: sampled block size."""
5   h, w = b_size
6   def constrain_mask(mask, tries=0):
7       """ Helper to restrict given mask
8         to acceptable regions """
9       N = max(int(len(
10          acceptable_regions)-tries), 0)
11       for k in range(N):
12           mask *= acceptable_regions[k]
13
14   valid_mask = False
15   while not valid_mask:
16       # Sample block top-left corner
17       top = torch.randint(0, height - h
18         , (1,))
19       left = torch.randint(0, width - w
20         , (1,))
21       mask = torch.zeros((height, width
22         ), dtype=torch.int32)
23       mask[top:top+h, left:left+w] = 1
24       # Constrain mask to a set of
25       acceptable regions
26       if acceptable_regions is not None
27         :
28           constrain_mask(mask, tries)
29       mask = torch.nonzero(mask.flatten
30         ())
31       # If mask too small try again
32       valid_mask = len(mask) >
33         min_ratio * h * w
34
35   mask_complement = torch.ones((height,
36     width), dtype=torch.int32)
37   mask_complement[top:top+h, left:left+
38     w] = 0
39
40   # Remove the time and frequency part
41   mask_complement_tf = torch.ones((
42     height, width), dtype=torch.int32)
43   mask_complement_tf[top:top+h, :] = 0
44   mask_complement_tf[:, left:left+w] =
45     0
46   return mask, mask_complement,
47     mask_complement_tf
```