# ProLLaMA: A Protein Language Model for Multi-Task Protein Language Processing

Liuzhenghao Lv<sup>1</sup>, Zongying Lin<sup>1</sup>, Hao Li<sup>1,2</sup>, Yuyang Liu<sup>1</sup>, Jiaxi Cui<sup>1</sup>, Calvin Yu-Chian Chen<sup>1</sup>, Li Yuan<sup>1,2</sup>, Yonghong Tian<sup>1,2\*</sup>

<sup>1</sup>Peking University, China <sup>2</sup>Peng Cheng Laboratory, China

### Abstract

Large Language Models (LLMs) have achieved remarkable performance in multiple Natural Language Processing (NLP) tasks. Under the premise that protein sequences constitute the protein language, Protein Language Models(PLMs) have advanced the field of protein engineering. However, as of now, unlike LLMs in NLP, PLMs cannot handle the protein understanding task and the protein generation task simultaneously in the Protein Language Processing (PLP) field. This prompts us to delineate the inherent limitations in current PLMs: (i) the lack of natural language capabilities, (ii) insufficient instruction understanding, and (iii) high training resource demands. To address these challenges, we introduce a training framework to transform any general LLM into a PLM capable of handling multiple PLP tasks. To improve training efficiency, we propose Protein Vocabulary Pruning (PVP) for general LLMs. We construct a multi-task instruction dataset containing 13 million samples with superfamily information, facilitating better modeling of protein sequence-function landscapes. Through these methods, we develop the ProLLaMA model, the first known PLM to handle multiple PLP tasks simultaneously. Experiments show that ProLLaMA achieves state-of-the-art results in the unconditional protein sequence generation task. In the controllable protein sequence generation task, ProLLaMA can design novel proteins with desired functionalities. As for the protein understanding task, ProLLaMA achieves a 62% exact match rate in superfamily prediction. Codes, model weights, and datasets are available at https://github.com/PKU-YuanGroup/ProLLaMA and https://huggingface.co/GreatCaptainNemo.

### 1 Introduction

Large Language Models (LLMs), like GPT-x and LLaMA2 [1, 2], have achieved outstanding performance in handling a wide range of Natural Language Processing (NLP) tasks [3–9], including both Natural Language Generation (NLG) and Natural Language Understanding (NLU) tasks, in a generative manner. This surge in LLMs has extended their applications beyond traditional contexts, including their adoption in the challenging field of protein engineering [10–14].

Taking protein sequences as the protein language, researchers train Protein Language Models (PLMs) on vast protein corpora [6, 11, 12]. PLMs have the potential to significantly advance protein engineering, holding immense promise for biomedical and biotechnological innovations [10]. However, this progress is challenged, particularly in extending their capabilities to multi-task Protein Language Processing (PLP).

<sup>\*</sup>Correspondence to: yuanli-ece@pku.edu.cn and yhtian@pku.edu.cn



Figure 1: **Left**: LLMs can handle both generation and understanding tasks, whereas PLMs cannot. This highlights the disparity in capabilities between the two. **Right**: Our ProLLaMA can handle generation tasks (unconditional protein generation, controllable protein generation) and understanding tasks (protein superfamily prediction), surpassing current PLMs.

Analogous to NLP, tasks related to protein language can be viewed as PLP [15, 16]. Consequently, PLP tasks can also be divided into two categories: Protein Language Generation (PLG), such as protein sequence generation, and Protein Language Understanding (PLU), such as protein property prediction. However, current PLMs tend to focus either exclusively on PLG [17–19] or PLU [20–24], rather than being proficient in both aspects simultaneously, as LLMs in NLP.

These limitations prompt the need for innovative solutions to unleash the full potential of PLMs. Developing a multi-task PLM would be highly beneficial for protein engineering and protein fitness landscape modeling [25–28], but three main challenges must be considered:

(i) **Necessity of Natural Language:** Protein language is not fully sufficient for PLP tasks, meaning it cannot fully represent all components of a task (the task instruction, the input, and the expected output) [29, 30]. It requires a language beyond protein language (typically, natural language) for representation, which current PLMs lack.

(ii) Instruction Following: To possess multi-task capabilities, models must execute tasks following user instructions [31–33]. However, current PLMs are unable to follow instructions.

(iii) **Training Resource Consumption:** Substantial training resources are needed for models to learn natural language, protein language, and user instructions [34], which can sometimes be unaffordable.

To address the challenges, we construct an instruction dataset that contains approximately 13 million samples and encompasses both PLG and PLU tasks. We propose a two-stage training framework to achieve a PLM for multi-task PLP. In the first stage, we leverage a pre-trained general LLM like LLaMA2 to continually learn the protein language while maintaining the natural language knowledge. In the second stage, the model is further trained on the multi-task instruction dataset. Additionally, we propose Protein Vocabulary Pruning (PVP) for general LLMs to significantly improve training efficiency. Furthermore, during both stages, we adopt Low-Rank Adaptation (LoRA) [35], which prevents catastrophic forgetting in the first stage and reduces training costs in both stages.

Using these methods, we develop ProLLaMA, a model capable of multi-tasks for PLP, distinguishing it from all other PLMs. Through a series of experiments, we demonstrate the multi-task capabilities of our ProLLaMA. Specifically, as for PLG, in unconditional protein generation, ProLLaMA outperforms current PLMs on common metrics such as pLDDT and TM-score. In controllable protein generation, based on a user-provided textual description, ProLLaMA generates novel proteins from scratch with desired functionalities, such as the SAM-MT superfamily. As for PLU, in protein superfamily prediction, ProLLaMA achieved a 62% exact match rate on the test dataset and obtained an F1-score above 0.9 in many specific categories. In summary, the contributions of our research are as follows:

• We propose a training framework that enables any general LLM to be trained as a proficient model for multi-task PLP, including both PLG and PLU tasks.

• We propose Protein Vocabulary Pruning and are the first to apply Low-Rank Adaptation in the training of large PLMs, which improves the efficiency of protein learning.

• We construct an instruction dataset that contains 13 million samples and over 11,000 kinds of superfamily annotations, potentially facilitating a better modeling of sequence-function landscapes.

• Experiments show that our ProLLaMA not only handles multiple PLP tasks but also achieves state-of-the-art results in protein generation tasks.

# 2 Preliminaries



Figure 2: (A) **Overview of the dataset construction.** The protein language dataset contains 53 million samples, which is used for training in Stage 1. The instruction dataset contains 13 million instances with 11,268 unique superfamily annotations, which is used for training in Stage 2. (B) **Overview of the training framework.** Stage 1: The pre-trained LLaMA2 learns the protein language, resulting in ProLLaMA. Stage 2: ProLLaMA learns to perform multiple tasks by instruction tuning. (C) **Overview of protein vocabulary pruning.** The vocabulary, *Embed* layer and *Head* layer are pruned based on characteristics of protein datasets, aiming for higher training efficiency.

**Necessity of Natural Language.** As aforementioned, given the similarities between protein sequences and natural language, tasks related to protein sequences can be considered as PLP, analogous to NLP. However, we observe a fundamental difference between protein language and natural language: natural language is complete for NLP tasks, whereas protein language is not complete for PLP tasks.

For example, in the sentiment analysis task, instructions, inputs, and outputs are straightforwardly expressed in natural language, such as "Analyze the sentiment: I am happy" yielding "The sentiment is positive." However, in PLP tasks like protein property prediction, instructions like "Predict this protein's property: MAFCF...FEV" cannot be fully conveyed in protein language alone, necessitating assistance from a language beyond protein language, in this case, natural language, for representation. Therefore, multi-task PLMs must possess a certain level of natural language ability, especially as more textual descriptions of proteins become available [29].

**Low-Rank Adaptation (LoRA)** [35] is a parameter-efficient technique for fine-tuning LLMs. Due to the immense parameter size of LLMs, full-parameter fine-tuning could be impractical sometimes. LoRA circumvents this by freezing the original parameters of LLMs and introducing additional trainable low-rank adapters. It achieves fine-tuning with a significantly smaller number of trainable parameters, yielding results comparable to full-parameter fine-tuning. LoRA prevents catastrophic forgetting of the original knowledge, as the newly learned knowledge has a lower rank than the original knowledge. The theoretical details of LoRA are provided in Appendix A.2.

# 3 Methods

In Section 3.1 and Figure 2(A), we show how to construct the protein language dataset and the instruction dataset. In Section 3.2 and Figure 2(C), we show how Protein Vocabulary Pruning (PVP) works. In Section 3.3, we show how the LLaMA2 model learns protein language on the protein language dataset through continued pre-training, resulting in ProLLaMA. In Section 3.4, we show the integration of various tasks into ProLLaMA through instruction tuning on the instruction dataset. The overview of the training framework is shown in Figure 2(B). The overview of the ProLLaMA model is shown in Figure 3.

### 3.1 Dataset Construction

**The protein language dataset** is utilized in the first training stage to enable LLaMA2 to grasp the language of proteins. Specifically, the dataset is sourced from UniRef50\_2023\_03 [36] on the UniProt website. We eliminate the descriptive parts of UniRef50, retaining only the pure protein sequences. Furthermore, We filter UniRef50 to ensure that the protein sequences consisted only of the 20 standard amino acids. We also retain sequences with a length of less than 512, aligning



Figure 3: **The overview of the ProLLaMA model.** We add low-rank adapters (LoRA) to certain weights and apply protein vocabulary pruning (PVP). We freeze original parameters, focusing solely on training LoRA (*Embed* and *Head* are also involved in the first training stage).

with ProGen [18]. Given that the lengths of protein sequences follow a long-tail distribution, the sequences that are deleted constitute only a small portion of the total dataset. To preprocess the protein sequences, we employ a specific prefix "Seq=<" and suffix ">". This standardized format aids LLaMA2 in distinguishing the new protein language from its existing natural language knowledge, thereby reducing confusion. The original Uniref50 contains 60,952,894 sequences, while after the above series of processing, our dataset comprises 52,807,283 protein sequences, with 90% for training and 10% reserved for testing.

**The instruction dataset** is utilized in the second training stage to enable ProLLaMA to perform various tasks. We first obtain the protein2ipr database from InterPro [37], which includes all proteins from UniProtKB along with their corresponding InterPro annotation information. Subsequently, we iterate through each protein's rep\_id in UniRef50 to retrieve the corresponding annotation information from protein2ipr. This retrieval process is implemented using a distributed Redis database, and only proteins with lengths less than 256 participate in the retrieval to enhance efficiency. We utilize regular expressions to filter out superfamily annotation from the whole annotation. In the end, we obtain 6,350,106 data instances, each of which contains one protein sequence and its superfamily annotation. And the number of unique superfamily annotations is 11,268.

Then, we process the obtained data into a multi-task instruction dataset following the Alpaca format [38], where each instance comprises three parts: instruction, input, and output. The instruction specifies the task type. We design two tasks: generating proteins based on superfamily and determining the superfamily of the given protein. For the former task, the input is the superfamily annotation, and the output is the expected protein. The latter task is the opposite. We selected these two tasks because they represent PLG and PLU, respectively. Additionally, modeling the relationships between sequences and superfamilies is crucial for uncovering protein functions and evolutionary insights [39]. In the end, the instruction dataset comprises 12,700,212 (6,350,106 \* 2) instances, with 90% for training and the rest reserved for testing.

### 3.2 Protein Vocabulary Pruning

It is known that LLMs are equipped with large vocabularies in tokenizers, which is beneficial to cover multi-lingual corpora and shorten the length of the input token sequence. However, a larger

vocabulary also implies slower tokenization of raw text, along with increased parameters in the model's *Embed* layer and *Head* layer, as discussed in detail in Appendix A.9. When considering only the protein language, such large vocabularies are clearly unnecessary. Therefore, we propose a method called Protein Vocabulary Pruning (PVP). PVP helps ProLLaMA achieve almost the same performance with higher training efficiency, whose proof is in Appendix A.3.

PVP is rule-based. Specifically, we iterate through each token in the original vocabulary and retain it if it meets our predefined grammatical rules (e.g., consisting only of the 20 uppercase English letters representing standard amino acids). We save these tokens and their indices. Using the saved tokens, we construct a smaller vocabulary. We then use the indices to extract the corresponding vectors from *Embed* and *Head* layers to construct smaller ones. Thus, we can train LLMs using reduced vocabulary and parameters.

Table 1: Effects of PVP. The vocabulary size, parameter numbers in *Embed* and *Head* layers, parameter numbers involved in training are listed.

Training Stage	Vocab	Embed and Head	Training
I (w/o PVP)	32,000	262M	582M
I (w/ PVP)	1,045	8.56M	328M
II (w/o PVP)	32,000	262M	160M
II (w/ PVP)	25,466	209M	160M

PVP is employed before training. After training, the vocabulary can be recovered back to its original size by incorporating the entries from the original vocabulary. This process is also applicable to the *Embed* and *Head* layers, restoring them to their original dimensions. This ensures that the architecture of LLMs remains entirely consistent both before and after training, facilitating potential training on broader corpora in the future. Naturally, if subsequent training is not a consideration, omitting the recovery operation is permissible.

We use PVP in both the first and second training stages of ProLLaMA, and its effects are shown in Table 1. It is evident that we achieve a significant compression rate in the first stage, primarily because the dataset in the first stage contains only protein sequences, which can be summarized by a simple rule. In contrast, the dataset in the second stage also includes English. More details about PVP is shown in Appendix A.3.

#### 3.3 Learning Protein Language

As mentioned in Section 1, current PLMs lack natural language abilities, which hinders multi-task capabilities. To solve this problem, we propose leveraging LLaMA2 to perform continued pre-training on protein language. This approach is analogous to humans learning a foreign language, where the model learns protein language while retaining its original natural language abilities.

We add Low-Rank Adapters (LoRA) into LLaMA2. To be specific, in each decoder block, we add LoRA to certain weights including  $W_q$ ,  $W_k$ ,  $W_v$ ,  $W_o$ ,  $W_{up}$ ,  $W_{gate}$  and  $W_{down}$ . The original parameters are frozen, enabling only LoRA to be trained. Due to the significant differences between protein language and natural language, we choose a relatively high rank for LoRA, which helps the model learn protein sequences better and prevents under-fitting. We also include both the *Embed* and *Head* layers in training. This is based on the premise that a token may have different meanings in protein sequences and natural languages, requiring distinct embeddings for the same token.

We trained the model using causal language modeling on the protein language dataset, resulting in ProLLaMA. Details on causal language modeling are provided in Appendix A.1. Benefiting from PVP and LoRA, as shown in Table 7, we train only about 5% of the parameters, in contrast to full-parameter training, which significantly reduces training costs. Additionally, as the remaining parameters are not involved in training, the inherent natural language abilities are preserved.

In summary, we have developed ProLLaMA, a model that comprehends both protein language and natural language, with reduced training costs. Consequently, we have addressed two problems mentioned in Section 1: the lack of natural language abilities and excessive training costs.

#### 3.4 Performing Multiple Tasks

As aforementioned, current PLMs are unable to perform multiple tasks based on user instructions. To solve this problem, we perform instruction tuning on ProLLaMA obtained from the previous section.

We train ProLLaMA on the instruction dataset mentioned in Section 3.1:

$$\mathcal{L}(\Theta) = \mathbb{E}_{\boldsymbol{x}, \boldsymbol{u} \sim \mathcal{D}} \left[ -\log p(\boldsymbol{x} | \boldsymbol{u}; \Theta) \right]$$
(1)

Table 2: **Comparison of proteins generated by different models.** Our ProLLaMA achieves the best performance on pLDDT, TM-score, and RMSD metrics, and is second-best in SC-Perp, demonstrating ProLLaMA excels in de novo protein design. \*: We list ProGen2 and ProGen as the same item, referring to Appendix A.6 for explanation. AE: Auto-Encoder. AR: Auto-Regressive.

Туре	Method	 pLDDT↑	SC-Perp↓	AFDB		PDB	
			1.	TM-score↑ RMSD↓		TM-score↑ RMSD↓	
CNN	CARP [40]	34.40±14.43	4.05±0.52	0.28	19.38	0.38	8.95
CININ	LRAR [40]	49.13±15.50	$3.59 \pm 0.54$	0.40	14.47	0.43	9.47
DIM (AE)	ESM-1b [22]	59.57±15.36	3.47±0.68	0.34	20.88	0.44	8.59
r LM (AL)	ESM-2 [24]	51.16±15.52	$3.58 \pm 0.69$	0.20	35.70	0.41	9.57
Diffusion	EvoDiff [40]	44.29±14.51	3.71±0.52	0.32	21.02	0.41	10.11
	ProtGPT2 [17]	56.32±16.05	3.27±0.59	0.44	12.60	0.43	9.19
PLM (AR)	ProGen2/ProGen* [19, 18]	61.07±18.45	$2.90 \pm 0.71$	0.43	15.52	0.44	11.02
	ProLLaMA (ours)	66.49±12.61	3.10±0.65	0.49	9.50	0.48	7.63

Table 3: **Controllable generation of ProLLaMA.** SAM-MT, TPHD, Trx, and CheY are four supefamiles. High values of TM-score and H-Prob indicate the generated proteins meet the desired superfamily. "xx% seen" denotes that xx% residues of one protein sequence belonging to the related superfamily are provided to ESM-1b for further generation. Even so, ProLLaMA performs best.

Method	SAM	-MT TPHD		ID	Tr	CheY		
	TM-score <sup>↑</sup>	H-Prob†	TM-score <sup>↑</sup>	H-Prob†	TM-score	H-Prob†	TM-score <sup>↑</sup>	H-Prob^
ESM-1b	0.58	0.37%	0.55	0.48%	0.61	0.37%	0.63	0.27%
ESM-2	0.52	0.26%	0.51	0.25%	0.53	0.30%	0.57	0.18%
EvoDiff	0.46	1.17%	0.42	1.80%	0.42	1.10%	0.46	1.43%
ProtGPT2	0.45	3.86%	0.43	4.62%	0.44	2.53%	0.45	4.86%
ProGen2/ProGen*	0.44	1.90%	0.45	2.49%	0.43	2.44%	0.44	2.13%
ESM-1b (25% seen)	0.43	0.64%	0.40	4.13%	0.42	1.01%	0.49	4.47%
ESM-1b (50% seen)	0.59	61.08%	0.63	66.21%	0.64	62.75%	0.73	78.00%
ESM-1b (75% seen)	0.67	88.51%	0.73	90.23%	0.75	93.92%	0.78	96.93%
ProLLaMA (ours)	0.71	98.13%	0.82	100.00%	0.81	99.96%	0.93	100.00%

Here,  $\Theta$  denotes the parameters to be optimized,  $\mathcal{L}$  the loss function, and  $\mathcal{D}$  the dataset. u denotes the instruction and the input of one instance. For brevity, when we refer to the instruction in the following text, it includes the input as well.  $x = \{x_0, x_1, \dots, x_{n-1}\}$  denotes the output, where  $x_i$  is the *i*-th token of the output.

Since causal language modeling is employed, we need to combine Equation 1 with Equation 3:

$$\mathcal{L}(\Theta) = \mathbb{E}_{\boldsymbol{x} \sim \mathcal{D}}\left[-\sum_{i} \log p(x_i | \boldsymbol{u}, x_0, x_1, \dots, x_{i-1}; \Theta)\right]$$
(2)

Equation 2 is the optimization objective for instruction tuning of ProLLaMA. u is not involved in the loss calculation, whereas x is. This is because the latter is the output part, where ensuring its quality of generation is crucial. The former, u, only needs to be understood by the model. In the instruction tuning stage, we exclusively train LoRA at a lower rank than specified in Section 3.3.

In summary, through instruction tuning, we have made ProLLaMA capable of following instructions and performing multiple tasks. Consequently, we have addressed the problems mentioned in Section 1: the lack of instruction following and the lack of multi-task capabilities.

In addition, the tasks that ProLLaMA can perform depend on the tasks included in the instruction dataset. Appendix A.7 shows that by training on an additional instruction dataset, ProLLaMA also performs well in predicting protein solubility.

## **4** Experiments

We introduce the experiment setup in Section 4.1. And we evaluate the unconditional protein generation task in Section 4.2, the controllable protein generation task in Section 4.3, the protein property prediction task in Section 4.4.

### 4.1 Experiment Setup

**Training Settings:** For continued pre-training, the LoRA rank is set to 128, employing the AdamW optimizer alongside a cosine annealing scheduler with warm-up. The peak learning rate stands at 5e-5, with a total of one training epoch. It takes six days on eight A6000 GPUs using FlashAttention-2 [41]. For instruction tuning, the LoRA rank is set to 64 with two training epochs, and all other settings remain consistent with the continued pre-training setup. It takes 5 days on eight A6000 GPUs. More training details can be found in Appendix A.4.

**Evaluation Settings:** Unconditional protein generation involves generating protein sequences without specific instructions. Controllable protein generation involves generating desired protein sequences based on instructions that specify the required superfamily. Property prediction involves predicting protein superfamily based on instructions, which include the protein sequences to be predicted. All evaluations are conducted on one GPU with 24GB of VRAM, with model inference occupying approximately 13GB of VRAM.

**Evaluation Metrics:** We use the following metrics to evaluate the generated protein sequences. The pLDDT [42] is used to measure whether sequences are structurally plausible. Self-Consistency Perplexity (SC-Perp) [40] serves as an additional metric of plausible structures since pLDDT falls short in dealing with intrinsically disordered regions (IDRs) [43]. TM-score [44] reflects the structural similarity between generated sequences and known ones in AFDB [45] and PDB [46]. RMSD also reflects the structural similarity from the perspective of atomic distance. Homologous probability (H-Prob) reflects the probability that the generated protein is homologous to a known one. Seq-Ident reflects the sequence similarity between generated sequences and known ones. More details are shown in Appendix A.5.

### 4.2 Unconditional Protein Generation

We compare our model with other models in protein sequence generation. These models cover a variety of types, with parameter numbers shown in Table 7. Table 2 shows the results. Our ProLLaMA is optimal on pLDDT, TM-score, and RMSD and is suboptimal on SC-Perp. This indicates that ProLLaMA, through its training on protein sequence data, can generate structurally plausible proteins. Notably, ProLLaMA-generated proteins exhibit a mean and standard deviation for pLDDT and SC-Perp of 66.49±12.61 and 3.10±0.65, respectively. These values are comparable to those of natural proteins as reported in [40], which are 68.25±17.85 and 3.09±0.63, respectively. It is noted that we list ProGen2 and ProGen as the same item in the table, referring to Appendix A.6 for explanation.

De novo design of long and structurally plausible protein sequences is highly challenging [17], yet our ProLLaMA performs well. As shown in Figure 4(A)(B)(C), when the length is more than 300, ProLLaMA performs the best in all the three metrics. Although ProGen2's performance is better in short sequences (length $\leq$ 200), it decreases as the length increases. This indicates that ProLLaMA is able to capture long-range dependencies between amino acids while other models struggle.

### 4.3 Controllable Protein Generation

We utilize four superfamily descriptions as instructions respectively: the S-adenosyl-L-methioninedependent methyltransferase superfamily (SAM-MT), the Tetratricopeptide-like helical domain superfamily (TPHD), the Thioredoxin-like superfamily (Trx), and the CheY-like superfamily (CheY). For each superfamily, ProLLaMA generates 100 protein sequences. We randomly select 100 natural proteins from each of the four superfamilies as benchmarks for comparison. We employ Foldseek[47] to compare generated proteins with natural ones.

The results shown in Table 3 demonstrate that ProLLaMA can generate desired protein sequences based on instructions that specify the required functionalities, confirming the capability for control-lable generation. For SAM-MT, the TM-scores of our generated sequences exceed 0.7; for TPHD



Figure 4: **Contrast experiments of ProLLaMA.** (A-C): Compared to other models, ProLLaMA maintains a high quality of generated proteins as their length increases. (D-F): According to the three indicators normalized by percentage, proteins generated by ProLLaMA are roughly comparable to natural proteins in the four superfamilies of CheY, TPHD, Trx, and SAM-MT (SAM).

and CheY, they are over 0.8; and for Trx, they surpass 0.9. The high TM-score indicates that the structures of the generated proteins closely resemble those of natural proteins in the same superfamily, implying functional similarity. For SAM-MT, TPHD, Trx, and CheY, all of the H-prob values are close to or even equal to 100%, indicating that the generated proteins are homologous to natural proteins and belong to the same superfamily. In summary, these provide strong evidence that the protein generation of ProLLaMA is controllable under instructions. In contrast, other models exhibit low TM-score and very low H-Prob due to their uncontrollable generation.

We also conduct another experiment. We provide residues of natural proteins belonging to the superfamily to ESM-1b, allowing ESM-1b to complete these sequences, rather than generating them from scratch as done previously. As seen in Table 3, with more residues provided, the proteins generated by ESM-1b increasingly exhibit the characteristics of the corresponding superfamily. Even so, it still does not surpass ProLLaMA. Higher TM-score and H-prob indicate that, under instruction control, ProLLaMA's de novo protein generation even outperforms the non-de novo generation by ESM-1b, which is provided with 75% of the residues. These results indicate that ProLLaMA can effectively capture structural and evolutionary relationships (as reflected by TM-score and H-prob) solely through learning from text and sequences.

Additionally, using natural proteins as a benchmark, we assess pLDDT, SC-Perp, and TM-score of proteins generated by ProLLaMA. Figure 4(D) shows that for CheY, TPHD, Trx, and SAM-MT, the average pLDDT of generated proteins is only 19.0%, 1.41%, 10.9%, and 10.3% lower than that of natural proteins, respectively. Figure 4(E) shows that for TPHD and SAM-MT, the average SC-Perp is 5.66% and 5.06% lower; for Trx and CheY, the average SC-Perp is 7.58% and 14.92% higher. Figure 4(F) visualizes the TM-score, with scores near the maximum indicating a high degree of structural similarity. These findings indicate that proteins generated by ProLLaMA are roughly comparable to their natural counterparts in the same superfamily.

In Figure 5, we visualize four examples of proteins generated by ProLLaMA (colored in blue) alongside the most structurally similar natural proteins from PDB (colored in yellow). The significant overlap in 3D structures and the high TM-score confirm structural similarity. Low Seq-ident indicates sequence diversity. In summary, through controllable protein generation, ProLLaMA is capable of generating desired proteins with structures similar to natural proteins, yet with novel sequences.

#### 4.4 Property Prediction

We use the test dataset to evaluate whether ProLLaMA can predict the superfamily to which a given protein belongs. The test dataset consists of 10,000 samples. Although ProLLaMA performs a classification task here, it is more complex than typical ones. The key difference is that typical classification tasks require models to output a fixed label, often in one-hot encoding. In contrast,

Table 4: Protein property prediction. The results of ten certain superfamilies in the test dataset.

	OBFD	UPF0145	NACD	U3S	CCHC	Kazal	SAM-MT	TPHD	Trx	CheY
Precision	0.33	1.00	1.00	1.00	0.75	1.00	0.77	0.94	0.86	0.93
Recall	1.00	1.00	1.00	1.00	0.95	1.00	0.94	0.91	0.94	1.00
F1-score	0.50	1.00	1.00	1.00	0.86	0.98	0.84	0.93	0.90	0.96
	Seq-iden TM-score H-prob 9 to PDB 30	t 16.2% 0.775 6% Jho_A		Seq-ident TM-score H-prob 98 to PDB 2vo	21.2% 0.833 % g2_A		Geq-ident 21.0% IM-score 0.782 H-prob 94% to PDB 3gnj_A		Seq-i TM-s H-pro	dent 33.0% core 0.922 ob 100% B <b>2a9p_A</b>
SAN	И-МТ		TPHD	)		Tr	(		CheY	

Figure 5: **Protein visualization.** Four proteins of controllable generation by ProLLaMA using SAM-MT, TPHD, Trx, and CheY as instructions. Blue is generated proteins, and yellow is natural. They are similar in structure but different in sequence.

ProLLaMA outputs the text. The advantage of the latter lies in its flexibility, such as the ability to easily handle situations where a sample belongs to multiple categories simultaneously. However, this increases task difficulty due to the much larger number of potential classification categories.

Even so, as shown in Table 5, ProLLaMA generates superfamily descriptions that exactly match the real descriptions in 62% of the test dataset. In addition, Table 4 illustrates ProLLaMA's performance on ten specific superfamilies. The recall value exceeds 0.9 in all the ten superfamilies and the F1-score exceeds 0.8 in nine superfamilies. The calculation formulas for these metrics can be found in Appendix A.5. Additional experiments on protein solubility prediction using ProLLaMA can be found in Appendix A.7.

Table	5:	Protein	property
predi	ctio	n. Results	s of all su-
perfan	nilie	s in the te	st dataset.

Metric	Value
Exact Match	0.62
Jaccard Similarity	0.67
Precision	0.63
Recall	0.72
F1-score	0.67

### 5 Related Work

**Protein Language Models.** Recognizing the similarity between natural language sequences and protein sequences, many methods from NLP have been applied to protein sequence data [48–51]. This has led to the development of PLMs, which are broadly categorized into two types [12, 52]: Auto-Regressive (AR) PLMs and Auto-Encoder (AE) PLMs. AR PLMs adopt the decoder-only architecture and Causal Language Modeling (CLM) [53, 54]. They primarily concentrate on PLG [55, 17–19], with a minority also focusing on fitness prediction [10]. AE PLMs adopt the encoder-only architecture and Masked Language Modeling (MLM) [20–24]. They excel in PLU, with the learned protein representations being applied to downstream predictive tasks [29]. However, they face challenges in de novo protein generation. Our ProLLaMA is capable of multitasking, excelling in tasks that both of the above types specialize in, surpassing existing PLMs. This multitasking capability is achieved through instruction following, making it user-friendly. We have also noticed the recent emergence of scientific LLMs [13, 14, 56–58]. In Appendix A.10, we discuss the differences between these models and ProLLaMA.

**Training LLMs.** There is a general training framework for LLMs [4], where LLMs are first pretrained on large-scale corpora [59] and then undergo instruction tuning to follow user instructions [60]. However, we believe that our proposed two-stage training framework differs in motivation and insights, as discussed in Appendix A.11. Considering the vast number of parameters in LLMs, various parameter-efficient techniques have been proposed to accelerate training and conserve memory [61, 62, 35, 63, 64], including LoRA. For the same reason, some vocabulary pruning methods have been studied [65], which rely on statistics specific to a provided dataset. This results in them being more time-consuming and failing to leverage the prior patterns of the dataset. In contrast, our PVP, derived from the prior data patterns, achieves excellent compression rates.

### 6 Conclusion

Existing PLMs excel in either protein generation tasks or protein understanding tasks. In this work, we introduce an efficient training framework to transform any general LLM into a multi-task PLM.

We construct an instruction dataset containing both generation tasks and understanding tasks. We propose PVP to improve training efficiency. We develop ProLLaMA, a versatile PLM for multiple tasks like controllable protein generation and protein property prediction. Experiments indicate that ProLLaMA performs exceptionally well. We are confident that our work will have a significant impact on the AI4Science community.

### References

- Sébastien Bubeck, Varun Chandrasekaran, Ronen Eldan, Johannes Gehrke, Eric Horvitz, Ece Kamar, Peter Lee, Yin Tat Lee, Yuanzhi Li, Scott Lundberg, et al. Sparks of artificial general intelligence: Early experiments with gpt-4. arXiv preprint arXiv:2303.12712, 2023.
- [2] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. arXiv preprint arXiv:2307.09288, 2023.
- [3] Alex Tamkin, Miles Brundage, Jack Clark, and Deep Ganguli. Understanding the capabilities, limitations, and societal impact of large language models. *arXiv preprint arXiv:2102.02503*, 2021.
- [4] Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, et al. A survey of large language models. arXiv preprint arXiv:2303.18223, 2023.
- [5] Jan Kocoń, Igor Cichecki, Oliwier Kaszyca, Mateusz Kochanek, Dominika Szydło, Joanna Baran, Julita Bielaniewicz, Marcin Gruza, Arkadiusz Janz, Kamil Kanclerz, et al. Chatgpt: Jack of all trades, master of none. *Information Fusion*, page 101861, 2023.
- [6] Chengwei Qin, Aston Zhang, Zhuosheng Zhang, Jiaao Chen, Michihiro Yasunaga, and Diyi Yang. Is chatgpt a general-purpose natural language processing task solver? arXiv preprint arXiv:2302.06476, 2023.
- [7] Fan Huang, Haewoon Kwak, and Jisun An. Is chatgpt better than human annotators? potential and limitations of chatgpt in explaining implicit hate speech. *arXiv preprint arXiv:2302.07736*, 2023.
- [8] Qihuang Zhong, Liang Ding, Juhua Liu, Bo Du, and Dacheng Tao. Can chatgpt understand too? a comparative study on chatgpt and fine-tuned bert. *arXiv preprint arXiv:2302.10198*, 2023.
- [9] Yejin Bang, Samuel Cahyawijaya, Nayeon Lee, Wenliang Dai, Dan Su, Bryan Wilie, Holy Lovenia, Ziwei Ji, Tiezheng Yu, Willy Chung, et al. A multitask, multilingual, multimodal evaluation of chatgpt on reasoning, hallucination, and interactivity. *arXiv preprint arXiv:2302.04023*, 2023.
- [10] Pascal Notin, Mafalda Dias, Jonathan Frazer, Javier Marchena Hurtado, Aidan N Gomez, Debora Marks, and Yarin Gal. Tranception: Protein fitness prediction with autoregressive transformers and inference-time retrieval. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato, editors, *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 16990–17017. PMLR, 17–23 Jul 2022.
- [11] Alexey Strokach and Philip M Kim. Deep generative modeling for protein design. *Current opinion in structural biology*, 72:226–236, 2022.
- [12] Noelia Ferruz and Birte Höcker. Controllable protein design with language models. *Nature Machine Intelligence*, 4(6):521–532, 2022.
- [13] Yin Fang, Xiaozhuan Liang, Ningyu Zhang, Kangwei Liu, Rui Huang, Zhuo Chen, Xiaohui Fan, and Huajun Chen. Mol-instructions-a large-scale biomolecular instruction dataset for large language models. In *The Twelfth International Conference on Learning Representations*, 2023.
- [14] Qizhi Pei, Lijun Wu, Kaiyuan Gao, Xiaozhuan Liang, Yin Fang, Jinhua Zhu, Shufang Xie, Tao Qin, and Rui Yan. Biot5+: Towards generalized biological understanding with iupac integration and multi-task tuning. arXiv preprint arXiv:2402.17810, 2024.
- [15] Tristan Bepler and Bonnie Berger. Learning the protein language: Evolution, structure, and function. *Cell* systems, 12(6):654–669, 2021.
- [16] Dan Ofer, Nadav Brandes, and Michal Linial. The language of proteins: Nlp, machine learning & protein sequences. *Computational and Structural Biotechnology Journal*, 19:1750–1758, 2021.

- [17] Noelia Ferruz, Steffen Schmidt, and Birte Höcker. Protgpt2 is a deep unsupervised language model for protein design. *Nature communications*, 13(1):4348, 2022.
- [18] Ali Madani, Ben Krause, Eric R Greene, Subu Subramanian, Benjamin P Mohr, James M Holton, Jose Luis Olmos Jr, Caiming Xiong, Zachary Z Sun, Richard Socher, et al. Large language models generate functional protein sequences across diverse families. *Nature Biotechnology*, pages 1–8, 2023.
- [19] Erik Nijkamp, Jeffrey A Ruffolo, Eli N Weinstein, Nikhil Naik, and Ali Madani. Progen2: exploring the boundaries of protein language models. *Cell Systems*, 14(11):968–978, 2023.
- [20] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. arXiv preprint arXiv:1810.04805, 2018.
- [21] Joshua Meier, Roshan Rao, Robert Verkuil, Jason Liu, Tom Sercu, and Alex Rives. Language models enable zero-shot prediction of the effects of mutations on protein function. *Advances in Neural Information Processing Systems*, 34:29287–29303, 2021.
- [22] Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Jason Liu, Demi Guo, Myle Ott, C Lawrence Zitnick, Jerry Ma, et al. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences*, 118(15):e2016239118, 2021.
- [23] Nadav Brandes, Dan Ofer, Yam Peleg, Nadav Rappoport, and Michal Linial. Proteinbert: a universal deep-learning model of protein sequence and function. *Bioinformatics*, 38(8):2102–2110, 2022.
- [24] Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, Robert Verkuil, Ori Kabeli, Yaniv Shmueli, et al. Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science*, 379(6637):1123–1130, 2023.
- [25] Sewall Wright et al. The roles of mutation, inbreeding, crossbreeding, and selection in evolution. 1932.
- [26] Xingjie Pan and Tanja Kortemme. Recent advances in de novo protein design: Principles, methods, and applications. *Journal of Biological Chemistry*, 296, 2021.
- [27] Zhizhou Ren, Jiahan Li, Fan Ding, Yuan Zhou, Jianzhu Ma, and Jian Peng. Proximal exploration for modelguided protein sequence design. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvari, Gang Niu, and Sivan Sabato, editors, *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 18520–18536. PMLR, 17–23 Jul 2022.
- [28] Zhenqiao Song and Lei Li. Importance weighted expectation-maximization for protein sequence design. arXiv preprint arXiv:2305.00386, 2023.
- [29] Minghao Xu, Xinyu Yuan, Santiago Miret, and Jian Tang. Protst: Multi-modality learning of protein sequences and biomedical texts. arXiv preprint arXiv:2301.12040, 2023.
- [30] Zeyuan Wang, Qiang Zhang, Keyan Ding, Ming Qin, Xiang Zhuang, Xiaotong Li, and Huajun Chen. Instructprotein: Aligning human and protein language via knowledge instruction. arXiv preprint arXiv:2310.03269, 2023.
- [31] Zhiyuan Zeng, Jiatong Yu, Tianyu Gao, Yu Meng, Tanya Goyal, and Danqi Chen. Evaluating large language models at evaluating instruction following. In *NeurIPS 2023 Workshop on Instruction Tuning* and Instruction Following, 2023.
- [32] Yilun Liu, Shimin Tao, Xiaofeng Zhao, Ming Zhu, Wenbing Ma, Junhao Zhu, Chang Su, Yutai Hou, Miao Zhang, Min Zhang, et al. Automatic instruction optimization for open-source llm instruction tuning. arXiv preprint arXiv:2311.13246, 2023.
- [33] Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. Instruction-following evaluation for large language models. arXiv preprint arXiv:2311.07911, 2023.
- [34] Yiming Cui, Ziqing Yang, and Xin Yao. Efficient and effective text encoding for chinese llama and alpaca. arXiv preprint arXiv:2304.08177, 2023.
- [35] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. arXiv preprint arXiv:2106.09685, 2021.

- [36] Baris E Suzek, Yuqi Wang, Hongzhan Huang, Peter B McGarvey, Cathy H Wu, and UniProt Consortium. Uniref clusters: a comprehensive and scalable alternative for improving sequence similarity searches. *Bioinformatics*, 31(6):926–932, 2015.
- [37] Typhaine Paysan-Lafosse, Matthias Blum, Sara Chuguransky, Tiago Grego, Beatriz Lázaro Pinto, Gustavo A Salazar, Maxwell L Bileschi, Peer Bork, Alan Bridge, Lucy Colwell, et al. Interpro in 2022. Nucleic acids research, 51(D1):D418–D427, 2023.
- [38] Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford alpaca: An instruction-following llama model. https://github. com/tatsu-lab/stanford\_alpaca, 2023.
- [39] Tyler N Starr and Joseph W Thornton. Exploring protein sequence–function landscapes. Nature biotechnology, 35(2):125–126, 2017.
- [40] Sarah Alamdari, Nitya Thakkar, Rianne van den Berg, Alex Xijie Lu, Nicolo Fusi, Ava Pardis Amini, and Kevin K Yang. Protein generation with evolutionary diffusion: sequence is all you need. *bioRxiv*, pages 2023–09, 2023.
- [41] Tri Dao. Flashattention-2: Faster attention with better parallelism and work partitioning. *arXiv preprint arXiv:2307.08691*, 2023.
- [42] John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, 596(7873):583–589, 2021.
- [43] Norman E Davey. The functional importance of structure in unstructured protein regions. *Current opinion in structural biology*, 56:155–163, 2019.
- [44] Yang Zhang and Jeffrey Skolnick. Scoring function for automated assessment of protein structure template quality. *Proteins: Structure, Function, and Bioinformatics*, 57(4):702–710, 2004.
- [45] Mihaly Varadi, Stephen Anyango, Mandar Deshpande, Sreenath Nair, Cindy Natassia, Galabina Yordanova, David Yuan, Oana Stroe, Gemma Wood, Agata Laydon, et al. Alphafold protein structure database: massively expanding the structural coverage of protein-sequence space with high-accuracy models. *Nucleic acids research*, 50(D1):D439–D444, 2022.
- [46] Helen M Berman, Tammy Battistuz, Talapady N Bhat, Wolfgang F Bluhm, Philip E Bourne, Kyle Burkhardt, Zukang Feng, Gary L Gilliland, Lisa Iype, Shri Jain, et al. The protein data bank. Acta Crystallographica Section D: Biological Crystallography, 58(6):899–907, 2002.
- [47] Michel Van Kempen, Stephanie S Kim, Charlotte Tumescheit, Milot Mirdita, Jeongjae Lee, Cameron LM Gilchrist, Johannes Söding, and Martin Steinegger. Fast and accurate protein structure search with foldseek. *Nature Biotechnology*, 42(2):243–246, 2024.
- [48] Kevin K Yang, Zachary Wu, Claire N Bedbrook, and Frances H Arnold. Learned protein embeddings for machine learning. *Bioinformatics*, 34(15):2642–2648, 2018.
- [49] Ethan C Alley, Grigory Khimulya, Surojit Biswas, Mohammed AlQuraishi, and George M Church. Unified rational protein engineering with sequence-based deep representation learning. *Nature methods*, 16(12):1315–1322, 2019.
- [50] Roshan M Rao, Jason Liu, Robert Verkuil, Joshua Meier, John Canny, Pieter Abbeel, Tom Sercu, and Alexander Rives. Msa transformer. In *International Conference on Machine Learning*, pages 8844–8856. PMLR, 2021.
- [51] Ahmed Elnaggar, Michael Heinzinger, Christian Dallago, Ghalia Rehawi, Yu Wang, Llion Jones, Tom Gibbs, Tamas Feher, Christoph Angerer, Martin Steinegger, et al. Prottrans: Toward understanding the language of life through self-supervised learning. *IEEE transactions on pattern analysis and machine intelligence*, 44(10):7112–7127, 2021.
- [52] Zaixiang Zheng, Yifan Deng, Dongyu Xue, Yi Zhou, Fei Ye, and Quanquan Gu. Structure-informed language models are protein designers. *bioRxiv*, pages 2023–02, 2023.
- [53] Yoshua Bengio, Réjean Ducharme, and Pascal Vincent. A neural probabilistic language model. Advances in neural information processing systems, 13, 2000.

- [54] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.
- [55] Lewis Moffat, Shaun M Kandathil, and David T Jones. Design in the dark: learning deep generative models for de novo protein design. *bioRxiv*, pages 2022–01, 2022.
- [56] Songhua Yang, Hanjie Zhao, Senbin Zhu, Guangyu Zhou, Hongfei Xu, Yuxiang Jia, and Hongying Zan. Zhongjing: Enhancing the chinese medical capabilities of large language model through expert feedback and real-world multi-turn dialogue. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19368–19376, 2024.
- [57] Ross Taylor, Marcin Kardas, Guillem Cucurull, Thomas Scialom, Anthony Hartshorn, Elvis Saravia, Andrew Poulton, Viktor Kerkez, and Robert Stojnic. Galactica: A large language model for science. arXiv preprint arXiv:2211.09085, 2022.
- [58] Qizhi Pei, Lijun Wu, Kaiyuan Gao, Jinhua Zhu, Yue Wang, Zun Wang, Tao Qin, and Rui Yan. Leveraging biomolecule and natural language through multi-modal learning: A survey. *arXiv preprint arXiv:2403.01528*, 2024.
- [59] Bonan Min, Hayley Ross, Elior Sulem, Amir Pouran Ben Veyseh, Thien Huu Nguyen, Oscar Sainz, Eneko Agirre, Ilana Heintz, and Dan Roth. Recent advances in natural language processing via large pre-trained language models: A survey. ACM Computing Surveys, 56(2):1–40, 2023.
- [60] Shengyu Zhang, Linfeng Dong, Xiaoya Li, Sen Zhang, Xiaofei Sun, Shuhe Wang, Jiwei Li, Runyi Hu, Tianwei Zhang, Fei Wu, et al. Instruction tuning for large language models: A survey. arXiv preprint arXiv:2308.10792, 2023.
- [61] Junxian He, Chunting Zhou, Xuezhe Ma, Taylor Berg-Kirkpatrick, and Graham Neubig. Towards a unified view of parameter-efficient transfer learning. *arXiv preprint arXiv:2110.04366*, 2021.
- [62] Xiang Lisa Li and Percy Liang. Prefix-tuning: Optimizing continuous prompts for generation. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 4582– 4597, 2021.
- [63] Xiao Liu, Kaixuan Ji, Yicheng Fu, Weng Tam, Zhengxiao Du, Zhilin Yang, and Jie Tang. P-tuning: Prompt tuning can be comparable to fine-tuning across scales and tasks. In *Proceedings of the 60th Annual Meeting* of the Association for Computational Linguistics (Volume 2: Short Papers), pages 61–68, 2022.
- [64] Zhiqiang Hu, Yihuai Lan, Lei Wang, Wanyu Xu, Ee-Peng Lim, Roy Ka-Wei Lee, Lidong Bing, and Soujanya Poria. Llm-adapters: An adapter family for parameter-efficient fine-tuning of large language models. arXiv preprint arXiv:2304.01933, 2023.
- [65] Yehui Tang, Fangcheng Liu, Yunsheng Ni, Yuchuan Tian, Zheyuan Bai, Yi-Qi Hu, Sichao Liu, Shangling Jui, Kai Han, and Yunhe Wang. Rethinking optimization and architecture for tiny language models. arXiv preprint arXiv:2402.02791, 2024.
- [66] Ning Ding, Yujia Qin, Guang Yang, Fuchao Wei, Zonghan Yang, Yusheng Su, Shengding Hu, Yulin Chen, Chi-Min Chan, Weize Chen, et al. Parameter-efficient fine-tuning of large-scale pre-trained language models. *Nature Machine Intelligence*, 5(3):220–235, 2023.
- [67] Armen Aghajanyan, Sonal Gupta, and Luke Zettlemoyer. Intrinsic dimensionality explains the effectiveness of language model fine-tuning. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 7319–7328, 2021.
- [68] Tatsuya Niwa, Bei-Wen Ying, Katsuyo Saito, WenZhen Jin, Shoji Takada, Takuya Ueda, and Hideki Taguchi. Bimodal protein solubility distribution revealed by an aggregation analysis of the entire ensemble of escherichia coli proteins. *Proceedings of the National Academy of Sciences*, 106(11):4201–4206, 2009.
- [69] Jack Hanson, Kuldip Paliwal, Thomas Litfin, Yuedong Yang, and Yaoqi Zhou. Accurate prediction of protein contact maps by coupling residual two-dimensional bidirectional long short-term memory with convolutional neural networks. *Bioinformatics*, 34(23):4039–4045, 2018.
- [70] Jianwen Chen, Shuangjia Zheng, Huiying Zhao, and Yuedong Yang. Structure-aware protein solubility prediction from sequence through graph convolutional network and predicted contact map. *Journal of cheminformatics*, 13:1–10, 2021.

- [71] Max Hebditch, M Alejandro Carballo-Amador, Spyros Charonis, Robin Curtis, and Jim Warwicker. Protein–sol: a web tool for predicting protein solubility from sequence. *Bioinformatics*, 33(19):3098–3100, 2017.
- [72] Sameer Khurana, Reda Rawi, Khalid Kunji, Gwo-Yu Chuang, Halima Bensmail, and Raghvendra Mall. Deepsol: a deep learning framework for sequence-based protein solubility prediction. *Bioinformatics*, 34(15):2605–2613, 2018.

### A Appendix

#### A.1 Causal Language Modeling

Causal Language Modeling (CLM) is a common objective of training LLMs. Given a token sequence  $x = \{x_0, x_1, \ldots, x_{n-1}\}$  that is subject to training. CLM can be conceptualized as predicting the *i*-th token based on the preceding i - 1 tokens [53]. Therefore, the optimization objective when training LLM using CLM is formulated as:

$$\mathcal{L}(\Theta) = \mathbb{E}_{\boldsymbol{x} \sim \mathcal{D}}\left[-\sum_{i} \log p(x_i | x_0, x_1, \dots, x_{i-1}; \Theta)\right]$$
(3)

where  $\mathcal{L}$  denotes the loss function,  $\Theta$  denotes the trainable parameters of the model, and  $\mathcal{D}$  is the training dataset.

#### A.2 Low-Rank Adaptation

LoRA yields results comparable to full-parameter fine-tuning. Theoretically, fine-tuning can be conceptualized as a process of finding the change in parameters [66]. Let the original parameters of the model be denoted as  $W_0$ , and the parameters after fine-tuning as W. The objective of fine-tuning is to find  $\Delta W = W - W_0$ . Hypothesizing  $\Delta W$  is of low rank [67], denoted as r, it can be decomposed into two low-rank matrices,  $\Delta W = AB$ . This leads to the following equation:

$$W = W_0 + AB \tag{4}$$

where  $W, W_0 \in \mathbb{R}^{d \times h}$ ,  $A \in \mathbb{R}^{d \times r}$ , and  $B \in \mathbb{R}^{r \times h}$ . And the fine-tuning objective is transformed from finding  $\Delta W$  to finding A and B:

$$\min_{\Delta W} \mathcal{L}(\Delta W) \to \min_{A,B} \mathcal{L}(A,B)$$
(5)

Consequently, the quantity of parameters involved in training is reduced from dh to r(d + h). Given the low-rank hypothesis, where  $r \ll d$  and  $r \ll h$ , this reduction in the number of trainable parameters is quite significant. Additionally, low-rank adapters can be integrated into the original model using Equation 4, which ensures that the architecture of the post-training model remains consistent with that of the original model.

### A.3 Protein Vocabulary Pruning

**Details**. In the first training stage of ProLLaMA, the rule used by PVP is that the retained tokens consist only of uppercase letters representing the 20 standard amino acids, along with a few special tokens (e.g., <bos> token). In the second training stage, the rule used by PVP is that the retained tokens consist only of English letters, punctuation marks, and numbers, along with a few special tokens. After completion of the first stage training, the recovery operation is necessary to facilitate subsequent second stage training. The data reported in the experimental section are from models that do not use PVP.

**Proof of Concept.** Casual language modeling is essentially a classification problem, with the classification space being identical to the input space, meaning the number of classes to classify is the size of the vocabulary, V. Suppose we know that the number of unique tokens present in the training set is V' (with V' being less than V). Thus, classes outside of V' are always negative classes during training for the model. In fact, PVP effectively incorporates this prior knowledge as an inductive bias into the model. This naturally does not harm the model's training results on this training dataset.

Therefore, for the first stage of training, the use of PVP does not affect the model's performance. However, if we perform the PVP recovery operation and proceed to the subsequent second stage of training, the performance of the second stage training may be slightly inferior to that of the model trained without using PVP under the same settings. The following can compensate for this:

During recovery, use the mean of the *Embed* layer obtained from the first stage model to fill the expanded *Embed* layer, and apply the same to the *Head* layer. In the second stage of training, add LoRA adapters to the *Embed* and *Head* layers and train them.

#### A.4 Training Details

For continued pre-training, the block size is set to 2048, with a gradient accumulation step count of 8. The warm-up ratio is 0.05, and the weight decay is set to 0.01. The data type is bfloat16. The batch size per GPU is 4. DeepSpeed Zero Redundancy Optimizer stage 2 (ZeRO-2) is employed without using offload. FlashAttention-2 is also employed. For instruction tuning, the max sequence length is set to 256, with a gradient accumulation step count of 4. The warm-up ratio is 0.03. The batch size per GPU is 144. Other settings are the same as continued pre-training.

#### A.5 Detailed Evaluation Metrics

#### A.5.1 Protein Generation

We use OmegaFold to calculate the values of the predicted Local Distance Difference Test (pLDDT) of protein sequences. Omegafold performs structure prediction without the need for homologous sequences or evolutionary information, relying solely on a single sequence for prediction. To calculate Self-Consistency Perplexity (SC-Perp), following the process mentioned in EvoDiff, we fold the sequence into a 3D structure using OmegaFold, then unfold it back into the sequence using ProteinMPNN. The self-consistency perplexity between the resulting sequence and the original sequence is referred to as SC-Perp.

We calculate TM-score, RMSD, H-Prob, and Seq-Ident using Foldseek. Foldseek facilitates the pairing of the queried protein  $p^{query}$  with structurally similar proteins from an existing protein database (AFDB or PDB), yielding pairs represented as  $(p^{query}, p^{target})$ . Here,  $p^{target}$  denotes the protein in the database with a significant structural similarity to  $p^{query}$ . The magnitude of the average Template Modeling score (TM-score) value and Root-Mean-Square Deviation (RMSD) reflects the degree of structural similarity. TM-score takes into account the overall topological structure of proteins, focusing more on the overall structure. RMSD calculates the square root of the average position deviation of corresponding atoms between two protein structures, being highly sensitive to the size of the protein structure and local variations. Additionally, Foldseek also calculates the Sequence Identity (Seq-Ident) between  $p^{query}$  and  $p^{target}$ , reflecting their sequence-level similarity. Homologous probability (H-Prob) reflects the probability that  $p^{query}$  and  $p^{target}$  is homologous.

#### A.5.2 Superfamily Prediction

For the i-th protein in the test dataset, we denote its true superfamily text description as the set  $F_i$  and the prediction by ProLLaMA as the set  $F'_i$ . We calculate the prediction accuracy using:

$$\begin{aligned} \operatorname{Recall} &= \frac{\sum_{i=1}^{N} |F_i \cap F'_i|}{\sum_{i=1}^{N} |F_i|} \\ \operatorname{Precision} &= \frac{\sum_{i=1}^{N} |F_i \cap F'_i|}{\sum_{i=1}^{N} |F_i|} \\ \operatorname{Jaccard-Similarity} &= \frac{\sum_{i=1}^{N} |F_i \cap F'_i|}{\sum_{i=1}^{N} |F_i \cup F'_i|} \\ \operatorname{Exact-Match} &= \frac{\sum_{i=1}^{N} \delta(F_i, F'_i)}{N} \end{aligned}$$

where |X| denotes the number of elements in set X,  $\cap$  denotes the intersection of two sets, and N denotes the number of samples in the test dataset. The symbol  $\delta(F_i, F'_i)$  denotes the indicator function, which equals 1 when the sets  $F_i$  and  $F'_i$  are exactly the same, and 0 otherwise.

#### A.6 About ProGen2 and ProGen

Following ProGen [18] and ProGen2 [19], it is known that ProGen enables controllable protein generation based on control tags, such as protein family, location, function, etc. And ProGen2 is limited to unconditional protein generation. Nevertheless, our attempts to find open-source model weights and executable code for ProGen were unsuccessful. In fact, the provided open-source repository link in the paper of ProGen is the same as that in the paper of ProGen2. However, the models provided by this repository cannot perform controllable protein generation.

In addition, ProLLaMA can perform various tasks based on user instructions, including the protein understanding task, which ProGen cannot accomplish.

#### A.7 Protein Solubility Prediction

We transform the eSol dataset [68, 69] into an additional instruction dataset, which includes two tasks: generating proteins based on solubility and determining the solubility of proteins. We binarize the solubility, with "Solubility=<False>" indicating insoluble and "Solubility=<True>" indicating soluble.

We train ProLLaMA (the one after the first training stage) on this additional instruction dataset. The LoRA rank is 64, the learning rate is 5e-5, and the number of training steps is 370. We compare our ProLLaMA with other methods in predicting protein solubility. The results are shown in Table 6. Our ProLLaMA outperforms models specifically designed for solubility prediction in terms of precision and F1-score. And its accuracy is almost the same as that of GraphSol. Notably, ProLLaMA utilizes only protein sequences, whereas other models incorporate additional features.

Table 6: Protein Solubility Prediction. \*: Values are sourced from GraphSol [70].

Method	Accuracy	Precision	Recall	F1-score
Protein-Sol* [71]	0.714	0.689	0.688	0.693
DeepSol* [72]	0.763	0.771	0.738	0.695
GraphSol* [70]	0.779	0.775	0.693	0.732
ProLLaMA (ours)	0.775	0.788	0.685	0.733

### A.8 Comparison of Model Parameters

Table 7 shows the comparison. As ProLLaMA takes a two-stage training procedure, 328M and 160M denote the parameters involved in Stage 1 and Stage 2, respectively. Due to the use of PVP and LoRA, ProLLaMA's training parameters are significantly fewer than the inference parameters (which are also the total number of model parameters). In contrast, other models require full-parameter training, so their training parameters are equal to their inference parameters. ProGen2 has versions of different sizes; in this work, we compare against ProGen2-large.

Table 7: Comparison of Model Parameters.

	CARP	LRAR	ESM-1b	ESM-2	EvoDiff	ProtGPT2	ProGen2	ProLLaMA
Training parameters	640M	640M	650M	650M	640M	738M	2.7B	(328+160)M
Inference parameters	640M	640M	650M	650M	640M	738M	2.7B	7B

#### A.9 Details about Embed layer and Head layer

In fact, both layers can be viewed as "single-layer linear projection" layers. *Embed* layer projects tokens of the raw data to the embedding. The shape of it is 32000\*4096, where 32000 is the size of the vocabulary, and 4096 is the feature size of the embedding. *Head* layer projects the embedding back to the language tokens space (probability distribution). By sampling from the probability distribution, the model can generate proteins and natural language. The shape of it is 4096\*32000. Therefore, pruning the vocabulary can reduce the size of these two layers.

### A.10 Comparison with Scientific LLMs

Recently, many scientific LLMs have emerged, addressing the deficiencies of conventional LLMs in specialized knowledge such as chemistry and biology, and also handling some protein-related tasks. However, we cannot classify them as PLMs because they have not been trained on large-scale protein corpora and have a limited understanding of the highly complex protein sequences. Additionally, their motivation is to supplement the shortcomings of LLMs in specific scientific domains. Therefore, they often use general LLMs, rather than PLMs, as baselines in experiment comparisons. Compared to PLMs, they perform poorly in protein-related tasks, especially in protein generation tasks. In contrast, the motivation behind ProLLaMA is to develop a more powerful PLM.

As shown in Table 8, Mol-Instructions [13] performs worse than ProLLaMA and other PLMs in Table 2 on unconditional protein generation, which indicates that it struggles to generate structurally plausible proteins. As for controllable protein generation, Table 8 indicates that the control conditions in Mol-Instructions do not take effect. In summary, although scientific LLMs perform well in knowledge question answering tasks in fields such as medicine, biology, and chemistry, they do not master the protein language.

Table 8: Comparison with scientific LLMs on unconditional protein generation.

Туре	Method	pLDDT ↑	TM-score ↑	$\mathbf{RMSD}\downarrow$
Scientific LLM	Mol-Instructions	37.07±8.60	0.17	36.99
PLM	ProLLaMA	66.49±12.61	0.49	9.50

Table 9: Comparison	n with scientific LLMs on	controllable protein generation.
---------------------	---------------------------	----------------------------------

Method	hod SAM-MT		TPHD		Trx		CheY	
	TM-score↑	H-Prob↑	TM-score↑	<b>H-Prob</b> ↑	TM-score↑	H-Prob^	TM-score↑	<b>H-Prob</b> ↑
Mol-Instructions ProLLaMA	0.39 0.71	6.55% 98.13%	0.38 0.82	0.78% 100.00%	0.39 0.81	1.29% 99.96%	0.45 0.93	6.62% 100.00%

### A.11 Comparison with General Training Framework

The general training framework of LLMs involves pre-training and instruction tuning. In fact, after pre-training, LLMs are already capable of performing multiple tasks due to the comprehensiveness of natural language as discussed in Section 2; instruction tuning is primarily for enhancing the quality of the output.

In contrast, it is not feasible for LLMs to acquire multi-task PLP capability in the first stage due to the following factors: 1. Protein language is not complete for PLP tasks. 2. Annotated protein sequences are significantly fewer than unannotated ones. 3. The patterns within protein sequences are extremely complex, and LLMs do not have inherent knowledge of them. Therefore, we believe that the model should first learn the protein language in the initial stage, and in the second stage, learn to use both the protein language and natural language to perform PLP tasks.

Additionally, our approach appears to have a certain biological plausibility. Specifically, our training framework can be viewed as modeling the patterns of protein sequences in the first stage and modeling the sequence-function landscape in the second stage. Compared to directly modeling the sequence-function landscape, our decoupled strategy significantly reduces the modeling difficulty.

### A.12 Impact Statements and Limitations

Our work holds the potential to revolutionize the field of computational biology and biotechnology. With multi-task capabilities in the protein field, our ProLLaMA could significantly accelerate the pace of research and innovation in areas such as drug discovery, synthetic biology, and the development of novel biomaterials.

Moreover, our work can enable a wider range of researchers and institutions, particularly those with limited resources, to participate in cutting-edge research, fostering a more inclusive AI4Science community.

However, our work may raise concerns regarding model reliability and the potential for misuse. The uncertainty in model outputs could lead to misinformed decisions in critical research areas like drug discovery, necessitating cautious reliance and thorough validation by human experts to mitigate risks. Moreover, the powerful capabilities of ProLLaMA could be exploited for harmful purposes, posing bio-security challenges and ethical challenges.

A collaborative effort among researchers, policymakers, and the broader community is crucial to harness the benefits of our work while addressing the potential risks and ethical considerations.

#### A.13 Licenses and Guidelines

As LLaMA2 is used in our work, all potential users of our ProLLaMA should respect the original license of Meta-LLaMA. Our datasets are based on UniProt and InterPro. UniProt applies CC BY 4.0 License. InterPro applies CC0 1.0 Public Domain Dedication. All potential users of our datasets should respect the licenses of UniProt and InterPro.

We strongly advise all users to adhere to the highest ethical standards when using our model and datasets. This includes ensuring fairness, transparency, and responsibility in all aspects of their research and applications. Users should be vigilant in avoiding any forms of bias, discrimination, or unfair treatment that could arise from the use of our tools. It is crucial to maintain a commitment to accuracy and integrity, rigorously validating results and being transparent about methodologies. Any use of our model and datasets that could cause harm to individuals or society, whether through misinformation, invasion of privacy, or other unethical practices, is strictly prohibited. Users should contribute to a more responsible and beneficial use of AI technologies, promoting trust and positive impact in their respective fields.