ERBENCH: AN ENTITY-RELATIONSHIP BASED AUTOMATICALLY VERIFIABLE HALLUCINATION BENCHMARK FOR LARGE LANGUAGE MODELS

PREPRINT

Jio Oh^{*1} Soyeon Kim^{*1} Junseok Seo¹ Jindong Wang² Ruochen Xu² Xing Xie² Steven E. Whang^{†1}

¹KAIST ²Microsoft Research Asia

ABSTRACT

Large language models (LLMs) have achieved unprecedented performance in various applications, yet their evaluation remains a critical issue. Existing hallucination benchmarks are either static or lack adjustable complexity for thorough analysis. We contend that utilizing existing relational databases is a promising approach for constructing benchmarks due to their accurate knowledge description via functional dependencies. We propose ERBench to automatically convert any relational database into a benchmark based on the entity-relationship (ER) model. Our key idea is to construct questions using the database schema, records, and functional dependencies such that they can be automatically verified. In addition, we use foreign key constraints to join relations and construct multi-hop questions, which can be arbitrarily complex and used to debug the intermediate answers of LLMs. Finally, ERBench supports continuous evaluation, multimodal questions, and various prompt engineering techniques. In our experiments, we construct an LLM benchmark using databases of multiple domains and make an extensive comparison of contemporary LLMs. We observe that better LLMs like GPT-4 can handle a larger variety of question types, but are by no means perfect. Also, correct answers do not necessarily imply correct rationales, which is an important evaluation that ERBench does better than other benchmarks for various question types. Code is available at https: //github.com/DILAB-KAIST/ERBench.

*Equal contribution.

1 Introduction

Large Language Models (LLMs) [1, 2] have become prevalent and are increasingly popular in a wide range of applications, including natural language processing, chatbots, content generation, and information retrieval, to name a few. However, a fundamental issue of LLMs is hallucination [3–6], which refers to the phenomenon that LLMs generate fake, unverified, or non-existent information especially for knowledge-related and safety-critical applications. Hallucination remains one of the most severe issues that should be addressed.

To address the issue of hallucination, it is necessary to develop benchmarks that are comprehensive, intricate, automatically verifiable, and can be scaled efficiently. One approach is to construct manual benchmarks by human annotators [7–10], which are expensive and not scalable. Another approach is to automatically construct evaluation samples using knowledge bases [11] by converting triples to simple factual questions or use existing QA datasets [12]. Although these benchmarks may scale as the answers can be verified automatically and updated with more knowledge, their questions are still simplistic or unmodifiable, thus lacking the ability to evaluate on intricate tasks.

We contend that utilizing existing relational databases is a promising approach to construct a benchmark that has both merits. Until now, many LLM benchmarks have been constructed based on knowledge bases. Although these benchmarks can scale, the main limitation is that the questions tend to be simplistic as they are based on triples. In comparison, relational databases contain structured data where they have schema information and follow the entity-relationship (ER) model, which supports various integrity constraints that make sure the data is well formed. A schema can be designed using traditional ER diagrams or more recent notions like UMLs. By using a database's schema, records, and integrity constraints, it is possible to construct arbitrarily-long multi-hop questions based on multiple relations that also have clear automatically-verifiable answers based on the integrity constraints. Using databases thus opens up opportunities to extensively evaluate LLMs on a vast amount of knowledge in a principled fashion.

[†]Corresponding author (swhang@kaist.ac.kr).

	ERD	Jiagram	Questio	on Templates	
E	(name) (birth year) (title)		FD of <i>Movie</i> : <i>title</i> , <i>year</i> \rightarrow <i>director</i> , <i>length</i>		
Design	<u>name</u> birth year <u>title</u>	<u>year</u> length <u>name</u> age	Binary (BN)	Multiple-Choice (MC)	
Database I	Director Directed-by	Movie Stars-in Star	<i>Q</i> : Is there a director who directed movie $\langle title \rangle$ released in $\langle vear \rangle$?	<i>Q</i> : What is false option about the movie $\langle title \rangle$ released in $\langle year \rangle$?	
	Schema	Functional Dependencies	v .		
Relational	Movie(<u>title</u> , <u>vear</u> , director, length)	FD of <i>Movie</i> : <i>title</i> , <i>year</i> \rightarrow <i>director</i> , <i>length</i>		<i>A</i> : Directed by 〈false director〉 <i>B</i> : Has length 〈length〉	
Rel	Director(<u>name</u> , birth year) Foreign Key Constraint	FD of <i>Director</i> : <i>name</i> \rightarrow <i>birth year</i>	Answer: Yes	Answer: A	
	StarsIn(<u>title, year, name</u> , age)	FD of <i>Movie</i> \bowtie <i>Director</i> : <i>title</i> , <i>year</i> \rightarrow <i>birth year</i>	Rationale : (director)	<i>Rationale</i> : <i>(true director)</i>	
n	① Prompt Construction	② QA Task	③ Auton	natic Verification	
LLM Evaluation	Question Templates (BN, MC) Joined DB + Multi-hop	Q: Is there a director who directed movie Star Wars released in 1977?	A: Yes . The director na Steven Spielberg direct movie Star Wars in 19	ted the	

Figure 1: The ERBench workflow. Starting from an ER diagram, database schema, functional dependencies, and foreign key constraints, we construct questions and evaluate the answers and rationales of LLMs.

In this paper, we propose **ERBench**, an LLM benchmark based on the ER model. ERBench supports complex questions and are automatically verifiable (see Figure 1). The questions can be automatically constructed using ER diagrams. For example, if a movie's length is determined by its *title* and *year*, and the ER diagram shows the entity movie with three attributes *title*, *year*, and *length*, then one can ask LLM *Does the movie* titled "Star Wars" produced in 1977 run for more than an hour?. We use two popular integrity constraints - functional dependencies (FDs) and foreign key constraints to make the questions verifiable. FDs are used to infer an attribute's value based on other attribute values. In our example, if the FD title, *year* \rightarrow *director, length* holds for movies, then the director and length of Star Wars are determined (George Lucas and 121 minutes, respectively). We can construct both binary and multiple-choice questions asking for the inferred values. A foreign key is a set of attributes in one relation that refers to the primary key of another relation, and a foreign key constraint (FK) ensures that the foreign key values actually exist in the other relation. Using FKs, ERBench can support questions with increasing complexity by generating multi-hop questions via joining multiple relations that have foreign key constraints and inferring longer FDs that span them.

ERBench is also extensible in terms of data, modality, and prompting. First, ERBench can be easily updated as its underlying database changes and thus support continuous evaluation. Second, ERBench supports multimodal questions where one can replace attribute text values with other data types like images. Third, we can further diversify the questions using recent techniques like chain-of-thought, few-shot QA, and knowledge augmentation.

We conducted extensive experiments using 5 public databases and evaluated several popular LLMs, namely, GPT-3.5 [13], GPT-4 [1], Llama2-70B-Chat [14], Gemini-Pro [2], and Mistral-7B-Instruct [15]. We perform comprehensive analyses in terms of answer and rationale accuracies and hallucination rates using single, multi-hop, and multimodal questions and also perform prompt engineering and fine-tuning. Overall, GPT-4 performs the best, but all LLMs can be improved significantly, and the point is that ERBench is effective in showing which aspects need improvements comprehensively.

Summary of Contributions. (1) We propose ERBench, an LLM benchmark that utilizes relational databases to construct complex questions where the model reasoning can be automatically verified. (2) We show how any database can be converted to a benchmark using its schema, records, and integrity constraints. (3) We extensively evaluate contemporary LLMs using ERBench and demonstrate how ERBench itself can be extended and remain relevant over time.

2 Preliminaries

2.1 LLM Hallucination

We would like to evaluate LLMs in terms of their hallucination levels. We define hallucination as generated content that is nonsensical or unfaithful to the provided source content [16]. Hallucination may occur because the data sources are flawed in various ways or the data is utilized imperfectly and cannot be recalled properly [16]. In any case, we are interested in whether an LLM not only gives correct answers, but also has the correct thought process and thus consider hallucination on two levels: (1) The LLM gives a wrong answer. For example, if the question asks whether Firenze and Florence are the same city, the answer is *Yes* (Firenze is the Italian name of Florence), and *No* is considered as hallucination. (2) The LLM gives a correct answer, but with a wrong rationale. In the above example, if the answer is *Yes*, but the reasoning is that both cities are in

Table 1: Sample questions constructed with FDs.

#	Question
q_1	For the movie with the title \langle Harry Potter and the Philosopher's Stone \rangle produced in \langle 2001 \rangle , is the length larger than \langle 100 \rangle minutes?
q_2	Is there a movie, released in $\langle 2001 \rangle$, starring $\langle Emma Watson \rangle$ where $\langle Chris Columbus \rangle$ is the director?
q_3	Was the director who directed the movie \langle Harry Potter and the Philosopher's Stone \rangle that was released in $\langle 2001 \rangle$ born in the $\langle 1950s \rangle$?

the United States, then this is considered as hallucination as well. We note that recent hallucination benchmarks like Head-to-Tail [11] are good at evaluating (1), but are not designed to evaluate (2). Our key idea is to utilize relational databases to generate questions that can be used to evaluate both (1) and (2).

2.2 Relational Databases

We utilize relational databases, which are based on the ER model. A relation consists of a schema containing attributes and records containing the attribute values. The relation may also have integrity constraints including functional dependencies and foreign key constraints. When designing a schema, a typical approach is to start with an intuitive ER diagram or UML to determine which entities and relationships are needed and how they are connected with each other. These are well known notions in databases, which we would like to utilize for question generation.

An *ER diagram* represents relationships among entities in a database. For example, the movie ER diagram in Fig. 1 has three entity sets *Movie*, *Star*, and *Director*. In addition, there could be relationships, e.g., *Stars-in* between *Movie* and *Star* and *Directed-by* between *Movie* and *Director*. The resulting schema of the database could then be *Movie*(*title*, *year*, *director*, *length*), *StarsIn*(*name*, *age*), and *Director*(*name*, *birth year*). ER diagrams can be used to post natural language questions.

A *functional dependency* (FD) is a relationship between two sets of attributes X and Y where the X values determine the Y values. For example, Fig. 1 shows the FD *title, year* \rightarrow *director, length* because a movie's title and year can be used to identify the movie, which in turn determines its director and length. Likewise, there is another FD *name* \rightarrow *birth year* where the director name determines his or her birth year. We denote an FD as $X \rightarrow Y$ and use it to evaluate the LLM's reasoning as we explain later.

A *foreign key constraint* (FK) is a set of attributes in one relation that refers to the key attributes in another relation, which can be used to identify records. For example, Fig. 1 shows that the *director* attribute of *Movie* is a foreign key to the *name* attribute of *Director*. Using a foreign key, we can also join two relations and construct FDs that span them. In Fig. 1, the FD *title, year* \rightarrow *birth year* is a result of joining the *Movie* and *Director* relations and combining the first two *Movie* and *Director* FDs. This multi-relation FD construction enables us to construct questions with arbitrary complexity as we explain later.

The integrity constraints thus determine the correctness of records, and our idea is to utilize them to verify the LLM responses as well. A natural question to ask is whether the integrity constraints themselves are always correct. Since the integrity constraints are determined by the database owner, it is the owner's responsibility to determine if they should hold in general. In addition, we are not aiming to ensure that LLMs get perfect scores in their evaluations, but to make a relative comparison among LLMs.

3 ERBench

We first explain how we utilize functional dependencies to construct questions (Sec. 3.1). We then design two types of questions: binary and multiple-choice questions (Sec. 3.2), and discuss how to verify the questions automatically (Sec. 3.3). We also show how to increase the complexity of questions by joining relations with foreign key constraints together and expanding the functional dependencies to construct multi-hop questions (Sec. 3.4). Finally, we explain how to extend ER-Bench with diverse data types, modalities, and prompting techniques (Sec. 3.5).

3.1 Question Construction using FDs

We first explain how to utilize an FD to construct a question. Given a relation R and an FD $X \rightarrow Y$, we can specify the R.X values and ask a question involving the R.Y values, e.g., q_1 in Table 1. One can also use an LLM to generate a question from the ER diagram where the attribute values are left as place holders. In order to fill in the question templates with values, we obtain records by either accessing existing databases or constructing ones ourselves. For example, we can either use a public movie database like IMDb or crawl the IMDb website. We then use the ER diagram to generate a question that involves the attributes of the database.

3.2 Binary and Multiple-choice QA

We construct two types of questions in a binary and multiplechoice answer format for a comprehensive evaluation.

For binary QA, we generate questions whose answers are within { *Yes*, *No*, *Unsure* }. The *Unsure* option is necessary as it can significantly reduce hallucination rates [11] when LLM is not confident about its answers. Hence, similar to Head-to-Tail [11], we prompt the LLM with *Answer the following question in yes or no, and then explain why. Say unsure if you don't know and then explain why.* Note that we ask for further explanation to proceed with the automatic reasoning verification step.

Example. We can generate the binary question q_1 in Table 1. Here, the answer is *Yes*, as the movie is 152 minutes.

We can naturally extend the binary QA to multiple-choice QA where we provide several correct options and one incorrect option, which the LLM should figure out. The correct options can be generated using any FD. The incorrect option can be generated by choosing one FD $X \rightarrow Y$ where we know the correct Y value and choosing any other Y value from the relation, which we know is incorrect. To evaluate whether the LLM is not just guessing, we can also add the option *None of the above* and make it the correct answer for a certain portion of questions.

Example. Continuing from above, suppose we now ask a multiple-choice question of *Harry Potter and the Philosopher's Stone*. Some correct options include *The director is Chris Columbus* and *The movie length is 152 minutes*. For incorrect options, we can replace *Chris Columbus* with *David Yates* (a director for a different *Harry Potter* film) or *152 minutes* with another number in the same relation.

3.3 Verifying LLM Responses

We verify LLM responses by automatically checking their answers and reasonings. The answer checking is straightforward where for binary questions, we look for Yes and No answers, and for multiple-choice questions, we check whether the model has successfully found the incorrect option among the correct options. When checking the reasoning, we look for the inferred values of the FD applied on the current record. For example, let us assume the FD star, director \rightarrow title. If we ask the binary question (e.g., q_2 in Table 1), we not only look for the answer Yes, but also the movie title Harry Potter within the reasoning. Similarly, if we ask the multiple-choice question where the previous FD is used to generate the incorrect option (e.g., the option includes Star Wars for the false value), we look for the true value Harry Potter within the model reasoning. We can thus use FDs in both question types to check whether the LLM has the correct internal knowledge to answer the question.

We may run into an entity resolution problem where the LLM mentions an entity that is essentially the same as the inferred one, but is written differently. In the above example, we may be looking for *Harry Potter*, but the LLM mentions *Harry J. Potter*, which contains the middle initial of *Harry Potter*. We perform entity resolution based on heuristics including conventional string matching. Another possible solution is to use an LLM itself for the matching. While ChatGPT has indeed been used to replace human judgement [11], we also believe this may give an unfair advantage to GPT compared to other LLMs and choose not to use this method.

3.4 Multi-hop Question Construction using FKs

We can increase the complexity of a question by making it a multi-hop question [17, 18], which can be used to test whether an LLM can think in multiple steps. We use the straightforward extension of joining multiple relations to implement the multiple hops. The relations must have foreign key relationships so that the FDs can span the relations. Given two relations R(X, Y) and S(Y, Z) where R's key is X, suppose there is a foreign key constraint from R.Y to S.Y. For any tuple e representing an entity in R, we can ask a question only using its X and Z values to see if the LLM knows the hidden Y value.

Example. If the relations are movies and directors, we can ask the 2-hop question q_3 in Table 1. Here *e* is the original *Harry Potter and the Philosopher's Stone* movie, and the hidden *Y* value is *Chris Columbus*. If the LLM knows *Chris Columbus*, then it should be able to confirm that his birth year is 1958, while giving *Yes* as an answer.

Notice that the verification of multi-hop questions is exactly the same as for single-hop questions. Thus, we can construct arbitrarily-complex, but automatically verifiable questions.

3.5 Extensions

We explain how ERBench is extensible in terms of data, modality, and prompting. In Sec. 4, we perform experiments on modality and prompting extensions.

Data. ERBench supports continuous evaluation in the sense that if the underlying databases change, ERBench can be updated automatically by simply reflecting the record updates to the questions as well. For any domain, we expect that new databases will continuously be introduced to evaluate LLMs over time, so being able to incrementally update the benchmark is crucial. ERBench overcomes the limitations of LLM by incorporating continuous evaluation, leveraging the benefits of databases for easy updates.

Modality. We can make ERBench multimodal by making the underlying database itself multimodal. For example, we can replace a text attribute in a relation with an image and then pose the same question to the LLM.

Prompt Engineering. There are many other prompt engineering techniques that can be used in ERBench, but are also orthogonal to the relative comparison of LLMs. We highlight the ones we use in our experiments: (1) Chain-of-thought [19] is a step-by-step approach of prompting and is more likely to give an LLM better context for answering the question; (2) Few-shot prompting [20] provides demonstrations to the LLM to give it more context before answering questions; and (3) Knowledge augmentation [21–23] utilizes a search engine to augment the generated answer with search results.

4 Experiments

We test the performances of LLMs on questions based on databases that are constructed from public data. We would like to evaluate LLMs based on whether their answers and rationales are both correct.

LLMs Compared. We compare Mistral-7B-Instruct [15], Llama2-70B-Chat [14], GPT-3.5 [13], Gemini-Pro [2], and GPT-4 [1]. For multimodal LLMs, we evaluate Gemini-Pro-Vision [2]. All these LLMs are accessible from Hugging Face or can be called through Microsoft Azure AI Studio APIs or Google Gemini API.

Datasets and Functional Dependencies. We perform experiments on 5 datasets representing different domains and call them *Movie* [24], *Soccer* [25], *Airport* [26], *Music* [27], and *Book* [28] (see Sec. A.1 for details). We also use separate *Di*-

Dataset	FD	Basic Question
Movie	director, star, released year \rightarrow movie title	Is there a movie, released in $\langle year \rangle$, starring $\langle star \rangle$ where $\langle dir \rangle$ is the director?
Soccer	club, jersey number, nationality \rightarrow player name (2019 year only)	Is there a soccer player from $\langle country \rangle$ who played for $\langle club \rangle$ with uniform number $\langle no \rangle$ in $\langle club \rangle$ in 2019?
Airport	latitude, longitude \rightarrow airport name	Is there an airport located at latitude $\langle latitude \rangle$ and longitude $\langle longitude \rangle$?
Music	music title, released year \rightarrow artist name	Is there an artist or group who sang a song titled $\langle title \rangle$ in $\langle year \rangle$?
Book	author, published date $ ightarrow$ book title	Is there a book written by $\langle author \rangle$ that was published in $\langle year \rangle$?

Table 2: Functional dependencies (FD) and basic questions of the 5 datasets for binary QA. See Sec. A.2 for multiple-choice QA.

rector and *Olympic* relations that are joined with the *Movie* and *Soccer* relations for multi-hop questioning. All data are available on Kaggle or public Github repositories. Table 2 and Table 7 (in Sec. A.2) show the FDs for each dataset, which are used to verify the LLM responses for binary QA and multiple-choice QA, respectively.

Performance Measures. We utilize existing hallucination measures [11] and newly introduce two measures involving rationale evaluation.

- Answer Accuracy (A) [11]: The portion of LLM answers that are correct (binary).
- *Rationale Accuracy* (**R**): The portion of LLM answers whose rationale contains the FD's inferred value.
- Answer-Rationale Accuracy (**AR**): The portion of LLM answers that are not only correct (binary), but also contain the FD's inferred value in the rationale.
- *Hallucination Rate* (**H**) [11]: The portion of LLM answers that are at least partially incorrect. Specifically, $\mathbf{H} = 1 \mathbf{A} \mathbf{M}$, where **M** denotes the percentage of LLM answers that admit they cannot answer the given question (i.e., *missing rate*). A lower **H** value is better.

Measuring Performance based on Internal Knowledge. When measuring LLM performances, we also take into account their internal knowledge of the entities within the questions. That is, if an LLM is hallucinating on a question because it simply does not know the entity mentioned (e.g., the entity may not exist in its training data) we may want to skip that question for evaluation. We can assess an LLM's knowledge by directly prompting if it knows an entity (e.g., Do you know about the movie "Harry Potter"?; see more details in Sec. B.1). For our datasets, the numbers of known entities per LLM are shown in Sec. B.2. For a fair evaluation, we perform three types of evaluations: (1) each LLM is evaluated only with questions with entities that it has knowledge of: (2) all LLMs are evaluated with questions that all the LLMs have knowledge of; and (3) all LLMs are evaluated with all questions, regardless of their knowledge. Due to space constraints, we only present results using (1), and the (2) and (3) results can be found in Sec. B.3.

4.1 Results for Single-hop Questions

We evaluate the LLM performances using single-hop binary and multiple-choice questions on the 5 datasets. We first explain




Figure 2: GPT-3.5 answer accuracy across domains with varying portions of the *None of the above* option in multiple-choice QA.

how we construct the questions and then analyze the LLM performances.

Binary Questions. We use the basic questions in Table 2 and expect a Yes answer. In addition, we construct negated versions of these questions and expect a No answer. For example, we can negate the basic question for the Movie dataset as Is it true that there are no movies released in $\langle year \rangle$, starring $\langle star \rangle$ where $\langle dir \rangle$ is the director?. The reason we always negate a basic question instead of say changing one of its attribute values into an incorrect one is to still perform the FD-based verification. If the question cannot utilize FDs anymore, we can no longer just look for inferred values, but need to understand the entire LLM response to see if the rationale is correct. Table 3 shows that GPT-4 and GPT-3.5 tend to have superior performances, especially in terms of answer and rationale accuracies. Gemini-Pro has lower answer and rationale accuracies, but also low hallucination rates. All three LLMs have worse performances for the negated questions. Llama2 and Mistral, on the other hand, tend to give trivial No answers for most questions, which results in high performances on the negated questions, but low performances on the basic ones.

Multiple-choice Questions. For the multiple-choice questions, we generate 2–4 choices using the attributes on the right-hand side of the functional dependencies, with one incorrect choice using the construction in Sec. 3.2. For each question, we generate three versions with rephrased choices (e.g., "born in US" can be rephrased to "birthplace is US" and "nationality is US") and report the averaged LLM performance to account for prompt sensitivity (see Sec. A.2 for more details). Table 3 shows that most LLMs demonstrate improved performances in multiple-choice questions compared to binary questions. GPT-4 and Gemini-Pro are comparable in answer and rationale accuracies, while GPT-4 has better hallucination rates. Llama2 and Mistral

Table 3: LLM performances using the binary (BN) basic and negated and multiple-choice (MC) questions on the 5 datasets. For each LLM, we specify their parameter count (**UNK** means unknown) and only evaluate with questions with known entities; see Sec. B.3 for more evaluation results. "n/a" means the LLM knows too few entities (less than 10) for the result to be meaningful; see Sec. B.2 for the number of entities known by each LLM. Lower **H** values are better, whereas higher **A**, **R**, and **AR** values are better.

		GPT-3.5 (175	B) GPT-4 (t	JNK)	Llama2 (7	0B)	Gemini-Pro (UNK)	Mistral (7B)
Dataset	Question Type	A R AR H	(\downarrow) A R AR	$\mathbf{H}\left(\downarrow ight)$	A R AR	$\mathbf{H}\left(\downarrow ight)$	A R AR H (\downarrow)	A R AR H (\downarrow)
Movie	BN (basic) BN (negated) MC	.06 .11 .05 .9	15 .65 .81 .64 .94 .51 .76 .50 .93 .97 .97 .97	.35 .47 .03	.05 .53 05 1.0 .92 .92 .93 .97 .91	.95 .00 .07	.28 .66 .26.40.00 .27 .001.0.92 .97 .92.08	.48 .54 .31 .52 1.0 .66 .66 .00 .72 .75 .64 .28
Soccer	BN (basic) BN (negated) MC	.00 .02 .00 1	64.47.70.41.0.19.49.17.17.91.69.69	.38 .04 .02	.02 .18 .02 1.0 .62 .62 n/a n/a n/a	.98 .00 n/a	.01 .06 .00 .17 .00 .05 .00 .29 .89 .55 .51 .11	.54 .10 .06 .46 .99 .18 .18 .01 .44 .21 .19 .56
Airport	BN (basic) BN (negated) MC	.00.00.00.	67.68.23.2097.1116.0329.96.90.90	.32 .80 .04	.00 .00 .00 1.0 .02 .02 n/a n/a n/a	1.0 .00 n/a	.00.00.00.00.00.00.42.76.33.33.24	.71 .00 .00 .29 1.0 .00 .00 .00 .13 .09 .05 .87
Music	BN (basic) BN (negated) MC	.20 .18 .14 .7	27.83.74.6876.63.56.5409.97.87.86	.15 .01 .01	.76 .31 .29 1.0 .29 .29 .91 .71 .67	.24 .00 .09	.51 .14 .11 .02 .02 .05 .01 .10 .89 .55 .54 .11	.41 .03 .03 .54 .96 .04 .04 .00 .56 .37 .14 .44
Book	BN (basic) BN (negated) MC	.01 .01 .00 .9	05.41 .21 .1904.02 .02 .0145.48 .34 .34	.08 .01 .01	.02 .02 .00 1.0 .05 .05 n/a n/a n/a	.98 .00 n/a	.00.00.01.00.00.01.47.13.11	.16 .01 .00.83.98 .01 .01.02.40 .04 .03.60

Table 4: LLM performances using the binary basic and negated multi-hop questions w/wo CoT prompting on 2 datasets. We exclude Mistral as it knows too few entities (less than 10), resulting in mostly "n/a" values; see Sec. B.2 for the # of entities known by each LLM.

		G	GPT-3.5 (1751	B)	(GPT-4 (UNK)		L	lama2 (70B)		Gen	nini-Pro (UN	NK)
Dataset	Question Type	A R-ext	AR-ext	$H\left(\downarrow \right)$	A R-ex	t AR -ext	$H\left(\downarrow \right)$	A R-ext	AR-ext	$H\left(\downarrow \right)$	A R-ext	AR-ext	$H\left(\downarrow \right)$
Movie	BN (basic) BN (negated)	.74 .92 .00 .92	.73/.70 .00/.00	.21 .96	.59 .98 .40 .98		.41 .60	.02 .95 1.0 .95	.02/.02 .98/.92	.98 .00	.19 .42 .01 .60	.19/.19 .01/.01	.02 .33
w/ Director	BN (basic) + CoT BN (negated) + CoT	.36 .95 .54 .79	.35/.34 .53/.50	.62 .27	.80 .98 .66 .98		.20 .34	.79 .97 .06 .95	.78/.77 .06/.05	.21 .94	.31 .40 .02 .28	.31/.30 .02/.01	.00 .20
Soccer	BN (basic) BN (negated)		.00/.05/.03 .00/.00/.00	.17 .18		.28/.42/.41 .15/.19/.19	.25 .13	.00 .22	.00/.00/.00 .25/.55/.44	.12 .88		.00/.00/.00 .00/.00/.00	.00. .00
w/ Olympic	BN (basic) + CoT BN (negated) + CoT		.36/.54/.54 .19/.31/.31	.33 .21	.79 .73 .70 .73	.40/.55/.55 .55/.73/.73	.20 .29		.09/.14/.13 .32/.62/.62	.15 .65		.57/.73/.75 .09/.09/.09	.60 .15

show good performances for the Movie and Music datasets. We also extend the multiple-choice questions with a *None of the above* option and evaluate with GPT-3.5 and GPT-4. Fig. 2 and Fig. 3 (in Sec. B.4) show that the LLM performances tend to decrease when the proportion of this option increases among the questions.

Instead of trying to rank LLMs by performance, we would like to make observations from a benchmark perspective: (1) rationale accuracy tends to be worse than answer accuracy and (2) the LLM performances vary significantly across question types, even when using the same entities. We thus conclude that there is much room for improvement for LLM rationale and that LLM benchmarking should always involve diverse questions for a comprehensive analysis.

4.2 **Results for Multi-hop Questions**

For the multi-hop questions, we construct 2 and 3-hop questions for the Movie and Soccer dataset respectively using the

construction in Sec. 3.4. In the Movie dataset, we employed two relations, movies and director, following the prompt outlined in Sec. 3.4. The director's name serves as the foreign key for joining the two relations. More details on the multi-hop question construction are in Sec. B.5. Since we are evaluating multiple steps of the LLM's reasoning, we also extend the **R** and **AR** measures as follows:

PREPRINT

- **R**-ext: We compute the portion of rationales that occur in the *i*th hop that are correct, for each *i* ∈ [1, . . ., total # hops]. We then take the average of these portions.
- **AR**-ext: We compute the **AR** value of answers and rationales that occur in the i^{th} hop, for each $i \in [1, ..., \text{total } \# \text{ hops}]$, in order to analyze any "snowball effect" [29] on how early hop reasoning errors affect the final accuracy.

Table 4 shows the LLM performances on the two datasets. Compared to the single-hop question results, most LLMs naturally have worse answer and rationale accuracies. Even if the answer accuracies are high, the rationale accuracies are

Table 5: LLM performances using multimodal questions on 2 datasets. See Sec. B.2 for # entities known by Gemini-Pro-Vision.

			Gemini-Pro			Gemini-Pro-V			
Dataset	Question Type	А	R AR	$\mathbf{H}\left(\downarrow\right)$	A	R AR	$H\left(\downarrow \right)$		
Movie	BN (basic) BN (negated) MC	.00	.66 .26 .27 .00 .97 .92	.40 1.0 .08	.17	.95 .78 .94 .16 .73 .58	.18 .83 .41		
Soccer	BN (basic) BN (negated) MC	.00	.06 .00 .05 .00 .55 .51	.17 .29 .11	.01	.38 .34 .20 .01 .56 .43	.31 .97 .32		

low, underscoring the need to evaluate LLM rationales. Using Chain-of-Thought prompting [19] (denoted as "+ CoT") has mixed results where the demonstrations sometimes guide the LLMs to retrieve better knowledge about entities, but may also add unintended biases. Finally, the **AR**-ext results show that the **AR** performance does not decrease for more hops, which means that answering the early hops correctly is important.

4.3 Results for Multimodal Questions

We evaluate the Gemini-Pro-Vision LLM with multimodal questions using the construction in Sec. 3.5. We unfortunately do not have access to the GPT-4V LLM, which also supports multimodal questions. Thus instead of making a relative comparison of LLMs, we explore how introducing multimodality in questions can change LLM performance by using Geminifamily LLMs: Gemini-Pro, which supports text-only inputs and Gemini-Pro-Vision, which supports multimodal-only inputs (i.e., it does not support text-only inputs). Using the singlehop questions in Sec. 4.1, we introduce multimodality in two datasets - Movie and Soccer - by replacing the values of one text attribute to corresponding image values. For the Movie dataset, we replace each movie title attribute value with a movie poster image, and for the Soccer dataset, we replace each *club* attribute value with a soccer club logo (see actual prompts in Sec C.1). As a result, Table 5 shows that introducing multimodality improves the relative performances on binary questions compared to multiple-choice questions. This comparison is by itself interesting and demonstrates how ERBench can be used to perform analyses across different modalities using the same question generation techniques.

4.4 Results on Prompt Engineering Methods

We further diversify our questions using prompt engineering techniques for a more extensive evaluation of LLMs. First, we use chain-of-thought (CoT) techniques [19] in multi-hop questions to encourage step-by-step LLM reasoning and observe improved LLM performances (Table 4). Second, we use few-shot QA when evaluating LLMs where we provide 8 (2–4) demonstrations before asking each binary (multiple-choice) question. Table 14 (in Sec. B.6) shows that the demonstrations indeed improve LLM performances for both types of questions for most domains. For binary questions, we generate demonstrations with both *Yes* and *No* answers to avoid introducing answer bias (more details are in Sec. C.2). Finally, we imple-

Table 6: GPT-3.5 performances on 5 datasets after fine-tuning with Soccer dataset entities. Lower **H** values are better, whereas higher **A**, **R**, and **AR** values are better.

		w/o F	Т	w/ FT (Soccer)		
Dataset	Question Type	A R AR	$\mathbf{H}(\downarrow)$	A R AR	$\mathbf{H}(\downarrow)$	
Movie	BN (basic)	.85 .81 .80	.15	.88 .93 .84	.12	
	BN (negated)	.06 .11 .05	.94	.89 .95 .86	.11	
Soccer	BN (basic)	.35 .28 .24	.64	.92 .75 .70	.08	
	BN (negated)	.00 .02 .00	1.0	.92 .71 .66	.08	
Airport	BN (basic)	.13 .01 .01	.67	.94 .09 .09	.06	
	BN (negated)	.00 .00 .00	.97	.91 .08 .08	.09	
Music	BN (basic)	.58 .36 .34	.27	.93 .61 .60	.07	
	BN (negated)	.20 .18 .14	.76	.93 .55 .54	.07	
Book	BN (basic)	.77 .13 .12	.05	.94 .09 .09	.06	
	BN (negated)	.01 .01 .00	.94	.68 .10 .09	.32	

ment a simple version of knowledge augmentation [21] using the LangChain API [30], which adds a background knowledge passage of entities from data sources like Wikipedia before each QA prompt. Surprisingly, we often observe a degradation in LLM performance as the passage may actually mislead the LLM instead of help it; see Table 15 with a more detailed analysis in Sec. B.7.

4.5 **Results for Fine-tuning**

We analyze how fine-tuning affects LLM performance using ERBench. We use GPT-3.5 [13] and fine-tune it on 3,000 entities of the Soccer dataset for 2 epochs and then observe how its performances on the 5 datasets change. We use similar questions as in Sec. 4.4. As a result, Table 6 shows that fine-tuning is mostly helpful across all datasets, even if the Soccer dataset does not have the same distribution, but there is still room for improvement (see more detailed results in Sec. B.2).

5 Related Work

While there are many LLM benchmarks nowadays, we focus on categorizing them according to what they evaluate and whether they can ask complex questions about entities. We emphasize that ERBench is the first work to tap the vast knowledge in relational databases and uses the ER model to generate complex and automatically-verifiable questions.

Many hallucination benchmarks evaluate factual knowledge of LLMs, which can be (1) general [7, 31, 10, 32–39, 8, 9, 40] or (2) specialized, where the questions are about medicine and healthcare [41, 42], facts in certain languages [43, 44], financial tasks [45], or domain-specific knowledge [46]. In comparison, ERBench can be applied to any domain as long as its underlying database reflects the knowledge of that domain.

Another line of benchmarks evaluates certain functionalities or qualities of LLMs. The functionalities include long text generation, [47, 48], semantic role identification [49], knowl-edge location [50], report or knowledge generation [51–53], text summarization [54, 55], attributing answers [56], and fact

checking [57]. The qualities include consistency [58], reliability [59, 12], trustworthiness [60], and hallucination accumulation [61]. In comparison, ERBench evaluates whether an LLM knows certain facts in relational databases and also its reasoning and thus complements the above works.

There are also entity-centric benchmarks that focus on information retrieval for an entity [62], entity resolution [63], and evaluating fact checking on head, torso, and tail entities [11]. In comparison, ERBench is also entity-centric as it is based on the ER model, but provides a general mechanism for converting any relational database into an LLM benchmark.

Recent scalable LLM benchmarks utilize existing QA datasets [12, 10] or knowledge bases [11] to automatically generate questions at scale. For example, one can easily convert subject-predicate-object triples in a knowledge base into a question that asks for the object. However, these approaches fail to verify the thought process of LLMs as they only check whether the final answers are correct. In comparison, ERBench also focuses on evaluating the thought process using database integrity constraints.

Finally, there are now LLM benchmarks that are multimodal [64] or cross-lingual [65]. ERBench also supports multimodal questions and can easily be extended to be cross-lingual as well.

6 Conclusion

We proposed ERBench, which converts relational databases based on the ER model to LLM benchmarks. ERBench starts from a schema and generates questions using an ER diagram and ensures that the LLM responses can be automatically verified using functional dependencies in a principled fashion. In addition, ERBench uses foreign key constraints to join relations and construct multi-hop questions, which can be arbitrarily complex and used to evaluate the intermediate answers of LLMs. Finally, ERBench is extensible in terms of data, modality, and prompt engineering. We generated our own LLM benchmark in 5 domains and performed comprehensive analyses in terms of answer and rationale accuracies and hallucination rates using single, multi-hop, and multimodal questions and also performed prompt engineering and fine-tuning. Overall, GPT-4 performed the best, but we also see many new opportunities to improve all the LLMs using the comprehensive evaluations of ERBench.

Acknowledgement

This project was supported by Microsoft Research Asia, by the Microsoft Accelerating Foundation Models Research (AFMR) program, and by the National Research Foundation of Korea(NRF) grant funded by the Korea government(MSIT) (No. NRF-2022R1A2C2004382).

Broader Impact Statement

This paper proposes an LLM benchmark that is intended to perform an objective evaluation of LLM performance. Although there may be a concern that the underlying database may somehow be biased, this is an issue for any benchmark. The fact that ERBench can use any database implies that it less likely to be biased than other fixed benchmarks.

References

- [1] OpenAI. Gpt-4 technical report, 2023.
- [2] Gemini Team and Rohan Anil. Gemini: A family of highly capable multimodal models. 11 2023.
- [3] Yue Zhang, Yafu Li, Leyang Cui, Deng Cai, Lemao Liu, Tingchen Fu, Xinting Huang, Enbo Zhao, Yu Zhang, Yulong Chen, et al. Siren's song in the ai ocean: A survey on hallucination in large language models. arXiv preprint arXiv:2309.01219, 2023.
- [4] Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, et al. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. arXiv preprint arXiv:2311.05232, 2023.
- [5] Hongbin Ye, Tong Liu, Aijia Zhang, Wei Hua, and Weiqiang Jia. Cognitive mirage: A review of hallucinations in large language models. *arXiv preprint arXiv*:2309.06794, 2023.
- [6] Vipula Rawte, Amit Sheth, and Amitava Das. A survey of hallucination in large foundation models. arXiv preprint arXiv:2309.05922, 2023.
- [7] Stephanie Lin, Jacob Hilton, and Owain Evans. Truthfulqa: Measuring how models mimic human falsehoods. In ACL, pages 3214–3252, 2022.
- [8] Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R. Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, Agnieszka Kluska, Aitor Lewkowycz, Akshat Agarwal, Alethea Power, Alex Ray, Alex Warstadt, Alexander W. Kocurek, Ali Safaya, Ali Tazarv, Alice Xiang, Alicia Parrish, Allen Nie, Aman Hussain, Amanda Askell, Amanda Dsouza, Ameet Rahane, Anantharaman S. Iver, Anders Andreassen, Andrea Santilli, Andreas Stuhlmüller, Andrew M. Dai, Andrew La, Andrew K. Lampinen, Andy Zou, Angela Jiang, Angelica Chen, Anh Vuong, Animesh Gupta, Anna Gottardi, Antonio Norelli, Anu Venkatesh, Arash Gholamidavoodi, Arfa Tabassum, Arul Menezes, Arun Kirubarajan, Asher Mullokandov, Ashish Sabharwal, Austin Herrick, Avia Efrat, Aykut Erdem, Ayla Karakas, and et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. CoRR, abs/2206.04615, 2022.
- [9] Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc V. Le, Ed Chi, Denny Zhou, and Jason Wei. Challenging big-bench tasks and whether chain-ofthought can solve them. In ACL, pages 13003–13051, 2023.
- [10] Junyi Li, Xiaoxue Cheng, Xin Zhao, Jian-Yun Nie, and Ji-Rong Wen. Halueval: A large-scale hallucination evaluation benchmark for large language models. In *EMNLP*, pages 6449–6464, 2023.
- [11] Kai Sun, Yifan Ethan Xu, Hanwen Zha, Yue Liu, and Xin Luna Dong. Head-to-tail: How knowledgeable are

large language models (llm)? A.K.A. will llms replace knowledge graphs? *CoRR*, abs/2308.10168, 2023.

- [12] Xiaodong Yu, Hao Cheng, Xiaodong Liu, Dan Roth, and Jianfeng Gao. Automatic hallucination assessment for aligned large language models via transferable adversarial attacks. *CoRR*, abs/2310.12516, 2023.
- [13] OpenAI. Chatgpt. https://chat.openai.com, 2022.
- [14] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihavlov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stoinic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023.
- [15] Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mistral 7b, 2023.
- [16] Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *CoRR*, abs/2311.05232, 2023.
- [17] Alon Talmor and Jonathan Berant. The web as a knowledge-base for answering complex questions. *arXiv* preprint arXiv:1803.06643, 2018.
- [18] Johannes Welbl, Pontus Stenetorp, and Sebastian Riedel. Constructing datasets for multi-hop reading comprehension across documents. *Transactions of the Association for Computational Linguistics*, 6:287–302, 2018.
- [19] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *NeurIPS*, 2022.
- [20] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances*

2020.

- [21] Grégoire Mialon, Roberto Dessì, Maria Lomeli, Christoforos Nalmpantis, Ramakanth Pasunuru, Roberta Raileanu, Baptiste Rozière, Timo Schick, Jane Dwivedi-Yu, Asli Celikyilmaz, Edouard Grave, Yann LeCun, and Thomas Scialom. Augmented language models: a survey. CoRR, abs/2302.07842, 2023.
- [22] Yuchen Zhuang, Yue Yu, Kuan Wang, Haotian Sun, and Chao Zhang. Toolqa: A dataset for LLM question answering with external tools. CoRR, abs/2306.13304, 2023.
- [23] Tu Vu, Mohit Iyyer, Xuezhi Wang, Noah Constant, Jerry W. Wei, Jason Wei, Chris Tar, Yun-Hsuan Sung, Denny Zhou, Quoc V. Le, and Thang Luong. Freshllms: Refreshing large language models with search engine augmentation. CoRR, abs/2310.03214, 2023.
- [24] Himanshu Sekhar Paul. Imdb movie ratings dataset. https://www.kaggle.com/datasets/ thedevastator/imdb-movie-ratings-dataset, 2018.
- [25] Stefano Leone. Fifa 20 complete player dataset. https: //www.kaggle.com/datasets/stefanoleone992/ fifa-20-complete-player-dataset, 2019.
- [26] Mike Borsetti. Flights and airports data. https://www. https://github.com/mwgg/Airports, 2020.
- [27] Luan Moura. Music dataset : 1950 to 2019. https: //www.kaggle.com/datasets/saurabhshahane/ music-dataset-1950-to-2019, 2021.
- [28] Elvin Rustamov. Books dataset. https://www.kaggle. com/datasets/elvinrustam/books-dataset, 2023.
- [29] Muru Zhang, Ofir Press, William Merrill, Alisa Liu, and Noah A Smith. How language model hallucinations can snowball. arXiv preprint arXiv:2305.13534, 2023.
- [30] Harrison Chase. LangChain, October 2022. URL https: //github.com/langchain-ai/langchain.
- [31] Tianyu Liu, Yizhe Zhang, Chris Brockett, Yi Mao, Zhifang Sui, Weizhu Chen, and Bill Dolan. A token-level reference-free hallucination detection benchmark for freeform text generation. In ACL, pages 6723-6737, 2022.
- [32] Xiang Yue, Boshi Wang, Ziru Chen, Kai Zhang, Yu Su, and Huan Sun. Automatic evaluation of attribution by large language models. In EMNLP, pages 4615-4635, 2023.
- [33] Peter Hase, Mona T. Diab, Asli Celikyilmaz, Xian Li, Zornitsa Kozareva, Veselin Stoyanov, Mohit Bansal, and Srinivasan Iyer. Methods for measuring, updating, and visualizing factual beliefs in language models. In EACL, [45] Haoqiang Kang and Xiao-Yang Liu. Deficiency of large pages 2706-2723, 2023.
- [34] Pouya Pezeshkpour. Measuring and modifying factual knowledge in large language models. CoRR, abs/2306.06264, 2023.

- in neural information processing systems, 33:1877–1901, [35] Jifan Yu, Xiaozhi Wang, Shangqing Tu, Shulin Cao, Daniel Zhang-li, Xin Lv, Hao Peng, Zijun Yao, Xiaohan Zhang, Hanming Li, Chunyang Li, Zheyuan Zhang, Yushi Bai, Yantao Liu, Amy Xin, Nianyi Lin, Kaifeng Yun, Linlu Gong, Jianhui Chen, Zhili Wu, Yunjia Qi, Weikai Li, Yong Guan, Kaisheng Zeng, Ji Qi, Hailong Jin, Jinxin Liu, Yu Gu, Yuan Yao, Ning Ding, Lei Hou, Zhiyuan Liu, Bin Xu, Jie Tang, and Juanzi Li. Kola: Carefully benchmarking world knowledge of large language models. CoRR, abs/2306.09296, 2023.
 - [36] Dor Muhlgay, Ori Ram, Inbal Magar, Yoav Levine, Nir Ratner, Yonatan Belinkov, Omri Abend, Kevin Leyton-Brown, Amnon Shashua, and Yoav Shoham. Generating benchmarks for factuality evaluation of language models. CoRR, abs/2307.06908, 2023.
 - [37] Shiqi Chen, Yiran Zhao, Jinghan Zhang, I-Chun Chern, Siyang Gao, Pengfei Liu, and Junxian He. FELM: benchmarking factuality evaluation of large language models. CoRR, abs/2310.00741, 2023.
 - [38] Shiping Yang, Renliang Sun, and Xiaojun Wan. A new benchmark and reverse validation method for passagelevel hallucination detection. In EMNLP, pages 3898-3908, 2023.
 - [39] Xuming Hu, Junzhe Chen, Xiaochuan Li, Yufei Guo, Lijie Wen, Philip S. Yu, and Zhijiang Guo. Do large language models know about facts? CoRR, abs/2310.05177, 2023.
 - [40] Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. Hotpotqa: A dataset for diverse, explainable multi-hop question answering. In EMNLP, pages 2369-2380, 2018.
 - [41] Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. Med-halt: Medical domain hallucination test for large language models. In CoNLL, pages 314-334, 2023.
 - [42] Muhammad Aurangzeb Ahmad, Ilker Yaramis, and Taposh Dutta Roy. Creating trustworthy llms: Dealing with hallucinations in healthcare AI. CoRR. abs/2311.01463, 2023.
 - [43] Qinyuan Cheng, Tianxiang Sun, Wenwei Zhang, Siyin Wang, Xiangyang Liu, Mozhi Zhang, Junliang He, Mianqiu Huang, Zhangyue Yin, Kai Chen, and Xipeng Qiu. Evaluating hallucinations in chinese large language models. CoRR, abs/2310.03368, 2023.
 - [44] Xun Liang, Shichao Song, Simin Niu, Zhiyu Li, Feiyu Xiong, Bo Tang, Zhaohui Wy, Dawei He, Peng Cheng, Zhonghao Wang, and Haiying Deng. Uhgeval: Benchmarking the hallucination of chinese large language models via unconstrained generation. CoRR, abs/2311.15296, 2023.
 - language models in finance: An empirical examination of hallucination. CoRR, abs/2311.15548, 2023.
 - [46] Mobashir Sadat, Zhengyu Zhou, Lukas Lange, Jun Araki, Arsalan Gundroo, Bingqing Wang, Rakesh Menon,

Md. Rizwan Parvez, and Zhe Feng. Delucionqa: Detecting hallucinations in domain-specific question answering. In *EMNLP*, pages 822–835, 2023.

- [47] Sewon Min, Kalpesh Krishna, Xinxi Lyu, Mike Lewis, Wen-tau Yih, Pang Wei Koh, Mohit Iyyer, Luke Zettlemoyer, and Hannaneh Hajishirzi. Factscore: Fine-grained atomic evaluation of factual precision in long form text generation. In *EMNLP*, pages 12076–12100, 2023.
- [48] Zican Dong, Tianyi Tang, Junyi Li, Wayne Xin Zhao, and Ji-Rong Wen. BAMBOO: A comprehensive benchmark for evaluating long text modeling capacities of large language models. *CoRR*, abs/2309.13345, 2023.
- [49] Jing Fan, Dennis Aumiller, and Michael Gertz. Evaluating factual consistency of texts with semantic role labeling. In *SEM@ACL, pages 89–100, 2023.
- [50] Yiming Ju and Zheng Zhang. Klob: a benchmark for assessing knowledge locating methods in language models. *CoRR*, abs/2309.16535, 2023.
- [51] Razi Mahmood, Ge Wang, Mannudeep K. Kalra, and Pingkun Yan. Fact-checking of ai-generated reports. In Machine Learning in Medical Imaging - 14th International Workshop, MLMI 2023, Held in Conjunction with MICCAI 2023, Vancouver, BC, Canada, October 8, 2023, Proceedings, Part II, volume 14349 of Lecture Notes in Computer Science, pages 214–223, 2023.
- [52] Fan Gao, Hang Jiang, Moritz Blum, Jinghui Lu, Yuang Jiang, and Irene Li. Large language models on wikipediastyle survey generation: an evaluation in NLP concepts. *CoRR*, abs/2308.10410, 2023.
- [53] Liang Chen, Yang Deng, Yatao Bian, Zeyu Qin, Bingzhe Wu, Tat-Seng Chua, and Kam-Fai Wong. Beyond factuality: A comprehensive evaluation of large language models as knowledge generators. In *EMNLP*, pages 6325–6341, 2023.
- [54] Philippe Laban, Wojciech Kryscinski, Divyansh Agarwal, Alexander R. Fabbri, Caiming Xiong, Shafiq Joty, and Chien-Sheng Wu. Llms as factual reasoners: Insights from existing benchmarks and beyond. *CoRR*, abs/2305.14540, 2023.
- [55] Derek Tam, Anisha Mascarenhas, Shiyue Zhang, Sarah Kwan, Mohit Bansal, and Colin Raffel. Evaluating the factual consistency of large language models through news summarization. In *ACL*, pages 5220–5255, 2023.
- [56] Guido Zuccon, Bevan Koopman, and Razia Shaik. Chatgpt hallucinates when attributing answers. In *SIGIR*, pages 46–51, 2023.
- [57] Han Cao, Lingwei Wei, Mengyang Chen, Wei Zhou, and Songlin Hu. Are large language models good fact checkers: A preliminary study. *CoRR*, abs/2311.17355, 2023.
- [58] Jian Xie, Kai Zhang, Jiangjie Chen, Renze Lou, and Yu Su. Adaptive chameleon or stubborn sloth: Unraveling the behavior of large language models in knowledge clashes. *CoRR*, abs/2305.13300, 2023.
- [59] Xiang Chen, Duanzheng Song, Honghao Gui, Chengxi Wang, Ningyu Zhang, Fei Huang, Chengfei Lv, Dan

Zhang, and Huajun Chen. Unveiling the siren's song: Towards reliable fact-conflicting hallucination detection. *CoRR*, abs/2310.12086, 2023.

- [60] Lingbo Mo, Boshi Wang, Muhao Chen, and Huan Sun. How trustworthy are open-source llms? an assessment under malicious demonstrations shows their vulnerabilities. *CoRR*, abs/2311.09447, 2023.
- [61] Muru Zhang, Ofir Press, William Merrill, Alisa Liu, and Noah A. Smith. How language model hallucinations can snowball. *CoRR*, abs/2305.13534, 2023.
- [62] Christopher Sciavolino, Zexuan Zhong, Jinhyuk Lee, and Danqi Chen. Simple entity-centric questions challenge dense retrievers. In *EMNLP*, pages 6138–6148, 2021.
- [63] Meihao Fan, Xiaoyue Han, Ju Fan, Chengliang Chai, Nan Tang, Guoliang Li, and Xiaoyong Du. Cost-effective in-context learning for entity resolution: A design space exploration, 2023.
- [64] Yejin Bang, Samuel Cahyawijaya, Nayeon Lee, Wenliang Dai, Dan Su, Bryan Wilie, Holy Lovenia, Ziwei Ji, Tiezheng Yu, Willy Chung, Quyet V. Do, Yan Xu, and Pascale Fung. A multitask, multilingual, multimodal evaluation of chatgpt on reasoning, hallucination, and interactivity. *CoRR*, abs/2302.04023, 2023.
- [65] Jirui Qi, Raquel Fernández, and Arianna Bisazza. Crosslingual consistency of factual knowledge in multilingual language models. In *EMNLP*, pages 10650–10666, 2023.

A Appendix – More Details on Datasets and Functional Dependencies

A.1 More Details on Datasets

Continuing from Sec. 4, we provide more details on the 5 datasets utilized in our experiments.

- *Movie* [24]: We use a relation with the attributes *movie title*, *released year*, *director*, *country of origin*, *genre* and *4 main stars*. For multi-hop questioning, we join this relation with a separate *Director* relation with the attributes *director name* and *birth year*. We generate the *Director* relation using the crawled data from Wikipedia.
- Soccer [25]: We use a relation with the attributes *player name*, *club*, *jersey number*, *nationality*, and *league*. For multi-hop questioning, we join this relation with a separate *Club* relation with the attributes *club name* and *located city*, and *Olympic* relation with the attributes *city name* and *hosted years*. We generate the *Club* and *Olympic* relation using the crawled data from Wikipedia.
- *Airport* [26]: We use a relation with the attributes *airport name*, *shortcode*, *latitude*, *longitude*, *located city*, and *country code*.
- *Music* [27]: We use a relation with the attributes *music title*, *artist name*, *released year*, and *genre*.
- Book [28]: We use a relation with the attributes book title, author, published date, and publisher name.

A.2 Functional Dependencies and Example Questions for Multiple-choice QA

Continuing from Sec. 4, we provide the functional dependencies and example questions used in our multiple-choice QA in Table 7. As noted in the main text, our main focus is to transform existing relational databases into QA prompts, and the performance of an LLM on these QA prompts may vary depending on the data fidelity of a given database.

B Appendix – More Details on Experiments

B.1 Assessing Internal Knowledge of LLMs

Continuing from Sec. 4, we provide more details on our approach to assess an LLM's internal knowledge. We directly ask the LLM if it knows about an entity and its attributes in a given relation. The input prompts for these questions are different for binary and multiple-choice questions, as we explain below. For simplicity, let us assume that we have a *Movie* relation with an FD *title*, *year* \rightarrow *director*, *length*.

Binary Questions. For the binary questions, we use one input prompt per entity that concatenates the following questions:

- one question that asks the left hand side (LSH) attributes of the FD
- multiple questions that ask each right hand side (RSH) attribute of the FD

For example, with the *Movie* relation, we use one input prompt "*Do you know about the movie* $\langle title \rangle$ released in $\langle year \rangle$? If yes, is the movie directed by $\langle director \rangle$? If yes, does the movie have the length $\langle length \rangle$?". Due to the concatenation, we can check whether the LLM knows all attribute values of an entity in the given FD via a single API call. We additionally use a system prompt "*Answer the following question in yes or no. Be concise.*" to get *Yes* or *No* answers from the LLM. An entity is considered to be known by the LLM iff it answers with only *Yes* to this input prompt.

Multiple-choice Questions. For the multiple-choice questions, we use multiple input prompts per entity that ask the following questions:

- one question that asks the LSH attributes of the FD
- multiple questions that ask each RSH attribute of the FD along with LSH attributes

For example, with the *Movie* relation, we use 3 input prompts: (1) "*Do you know about the movie* $\langle title \rangle$ released in $\langle year \rangle$?"; (2) "*Is the movie* $\langle title \rangle$ released in $\langle year \rangle$ directed by $\langle director \rangle$?"; and (3) "*Does the movie* $\langle title \rangle$ released in $\langle year \rangle$ have the length $\langle length \rangle$?". The reason we do not use one concatenated input prompt as in the binary questions is that the concatenated prompt itself can be similar to the multiple-choice questions – which is our main QA task – and may thus affect the main QA results. For example, if we use the above example input prompt in the binary questions, an LLM may consider this prompt as a 2-choice question that asks about director and length of a particular movie. As we filter out the unknown entities of LLM *before* performing the main QA task, filtering with these prompts, which are similar to the main task, may boost the resulting LLM performance, thereby leading to unreliable results. We thus use separate prompts rather than one concatenated prompt in multiple-choice questions, whereas the system prompt and the answer evaluation are identical to those of binary questions.

Table 7: Functional dependencies (FD) and examples questions of the 5 datasets for multiple-choice QA. We generate three versions of questions with rephrased choices to measure the average performance of LLMs. The term "false", "inaccurate", or "wrong" is used when asking for the incorrect option, which is preceded by "Q:". Each attribute of an entity is described in a short phrase that follows "Option n: ", where n represents the respective option number.

Dataset	FD	Example Question
Movie	movie title, released year \rightarrow director, country of origin, genre (animation, non-animation)	Q: What is the false option about the movie (Avatar) released in year (2009)? Provide an explanation. Option 1: It was directed by (James Cameron). Option 2: It was produced in the country (USA). Option 3: It is an (animation) movie.
		<i>A</i> :
Soccer	player name (2019 year only) $ ightarrow$ club, jersey number, nationality, league	Q: What is the false option about soccer player named (E. Hazard)? Provide an explanation. Option 1: He played for (Real Madrid CF) in 2019. Option 2: His uniform number was (10) in 2019. Option 3: He was born in (Belgium). Option 4: He played in (Spain Primera Division) during the year 2019.
		<i>A</i> :
Airport	airport name \rightarrow ICAO shortcode, latitude, longitude, country code	Q: What's the inaccurate option about the airport (Torca)? Provide an explanation. Option 1: ICAO Shortcode of the airport is (SCLI). Option 2: Latitude of the airport is (-34.7833). Option 3: Longitude of the airport is (-72.0508). Option 4: Country code of the airport is (US).
		<i>A</i> :
Music	music title, artist name ightarrow released year, genre (pop/rock, hip hop/raggae, country/folk, blues/jazz)	Q: What is the wrong option regarding the song ("Day After Day") of the artist (Badfinger)? Provide an explanation. Option 1: The released year of the song is (1971). Option 2: The song is categorized as (country/folk) genre.
		<i>A</i> :
Book	book title, author \rightarrow published month, published year, publisher name	Q: What's the false option about the book titled (Speak to My Heart) written by an author named (Adams, Stacy Hawkins)? Provide an explanation. Option 1: Published month of the book is (October). Option 2: Published year of the book is (1979). Option 3: Published by the publisher named (Revell).
		<i>A</i> :

B.2 Number of Known Entities

Continuing from Sec. 4, we provide the number of entities known by LLMs for various tasks. Table 8–11 show the number of the known entities when evaluating single-hop questions, multi-hop questions, multi-modal questions, and single-hop questions with fine-tuning, respectively.

Table 8: Number of entities of 5 datasets known by each LLM using the binary (BN) and multiple-choice (MC) single-hop questions. If the LLM knows too few entities (less than 10), we exclude it when computing the number of commonly known entities (Common #).

Dataset (Total #)	Question Type	GPT-3.5	GPT-4	Llama2	Gemini-Pro	Mistral	Common #
Movie (1,485)	BN	1,352	1,266	390	1,020	426	223
100010 (1,403)	MC	1,338	1,358	642	1,203	1,284	605
Second (1.500)	BN	1,006	1,280	128	859	459	69
Soccer (1,500)	MC	721	662	1	636	840	210
Airmort (1.500)	BN	1,293	636	1,011	1,208	1,496	330
Airport (1,500)	MC	844	91	1	472	1,390	62
Music (1 500)	BN	1,068	625	238	1,359	1,186	85
Music (1,500)	MC	571	327	43	602	678	22
Pools (1 500)	BN	1,211	636	650	1,465	855	206
Book (1,500)	MC	989	60	0	846	649	20

Table 9: Number of entities of 2 datasets known by each LLM using the binary multi-hop questions.

Dataset (Total #)	GPT-3.5	GPT-4	Llama2	Gemini-Pro	Mistral
Movie w/ Director (1,267)	1,191	1,049	443	1,214	2
Soccer w/ Olympic (1,500)	1,470	1,453	1,164	1,471	198

Table 10: Number of entities of 2 datasets known by Gemini-Pro-Vision using the binary (BN) and multiple-choice (MC) multimodal questions.

Dataset (Total #)	Question Type	Gemini-Pro-V
Marrie (1 495)	BN	1,243
Movie (1,485)	MC	1,143
Saaar (1,500)	BN	1,408
Soccer (1,500)	MC	577

Table 11: Number of entities of 5 datasets known by GPT-3.5 after fine-tuning with (1) only the Soccer dataset and (2) the combined dataset of Movie, Soccer, Music, and Book.

PREPRINT

Dataset (Total #)	FT w/ Soccer	FT w/4 Datasets
Movie (1,485)	1,006	682
Soccer (1,500)	1,308	314
Airport (1,500)	930	971
Music (1,500)	313	137
Book (1,500)	670	109

PREPRINT

Continuing from Sec. 4.1, we perform the other two types of evaluations. First, all the LLMs are evaluated with questions that all the LLMs have knowledge of in Table 12. As a result, most of the LLMs show improved performances, which is likely due to the exclusion of long-tail entities that are typically challenging to answer or reason correctly. Second, all the LLMs are evaluated with all questions, regardless of their knowledge in Table 13. As a result, the LLMs show a notable degradation in performance. The results from other two types of evaluations are consistent with the observations highlighted in the main text: (1) rationale accuracy is lower than answer accuracy, and (2) the performances of LLMs varies depending on the question type. These results again underscore the importance of benchmarks that focus more on LLM's rationale and provide diverse question types.

Table 12: LLM performances using the binary (BN) basic and negated and multiple-choice (MC) questions on the 5 datasets. For each LLM, we specify their parameter count (UNK means unknown) and evaluate with the questions whose entities are commonly known by all the LLMs. "n/a" means the LLM knows too few entities (less than 10) for the result to be meaningful; see Sec. B.2 for the number of entities known by each LLM. Lower **H** values are better, whereas higher **A**, **R**, and **AR** values are better.

		GPT-3.5 (175B)	GPT-4 (UNK)	Llama2 (70B)	Gemini-Pro (UNK)	Mistral (7B)
Dataset	Question Type	A R AR H (\downarrow)	$\begin{array}{c c} A & R & AR & H(\downarrow) \end{array}$	A R AR $H(\downarrow)$	A R AR $H(\downarrow)$	A R AR H (\downarrow)
Movie	BN (basic) BN (negated) MC	.95 .95 .94.05.19 .29 .16.81.98 .98 .98.02	.91 .96 .90 .09 .85 .96 .83 .15 .99 .99 .99 .01	.09 .63 .09 .91 1.0 .95 .95 .00 .93 .97 .91 .07	.57 .87 .55 .34 .00 .40 .00 1.0 .95 .98 .95 .05	.56.58.39.441.0.72.72.00.78.80.71.22
Soccer	BN (basic) BN (negated) MC	.39 .45 .36 .61 .00 .07 .00 1.0 .86 .69 .63 .14	.68 .96 .67 .29 .54 .90 .52 .03 .92 .75 .75 .02	.03 .22 .03 .97 1.0 .67 .67 .00 n/a n/a n/a n/a	.03 .17 .03 .22 .00 .17 .00 .38 .94 .55 .53 .06	.46 .32 .19 .54 1.0 .46 .46 .00 .45 .25 .21 .55
Airport	BN (basic) BN (negated) MC	.16 .02 .02.72.00 .00 .00.99.90 .85 .85.10	.63 .13 .12 .37 .11 .10 .02 .82 .95 .91 .91 .05	.00 .00 .00 1.0 1.0 .03 .03 .00 n/a n/a n/a n/a	.00.00.00.00.00.00.82.41.18	.87 .00 .00 .13 1.0 .00 .00 .00 .20 .12 .11 .80
Music	BN (basic) BN (negated) MC	.69 .44 .41 .20 .33 .34 .25 .65 1.0 .97 .97 .00	.73.53.47.25.55.44.42.001.0.97.97.00	.76 .33 .32 .24 1.0 .32 .32 .00 .94 .86 .83 .06	.75.34.33.00.07.18.06.09.95.89.86.05	.58.11.40.89.09.09.48.50.14.52
Book	BN (basic) BN (negated) MC	.83 .13 .13 .03 .01 .00 .00 .94 .73 .28 .22 .27	.45 .20 .19 .06 .03 .03 .02 .00 .48 .28 .28 .02	.03 .04 .00 .97 1.0 .08 .08 .00 n/a n/a n/a n/a	.01 .01 .01 .00 .00 .00 .00 .01 .62 .20 .20 .38	.23 .01 .01 .76 .97 .01 .01 .03 .43 .07 .07 .57

Table 13: LLM performances using the binary (BN) basic and negated and multiple-choice (MC) questions on the 5 datasets. For each LLM, we specify their parameter count (UNK means unknown) and evaluate with all questions regardless of the LLM knowledge of entities. Lower **H** values are better, whereas higher **A**, **R**, and **AR** values are better.

		GPT-3.5 (175	B) GPT-4 (UNK)	Llama2 (70)B)	Gemini-Pro	(UNK)	Mistral	(7B)
Dataset	Question Type	A R AR H	(\downarrow) A R AR	$\mathbf{H}\left(\downarrow ight)$	A R AR I	H (↓)	A R AR	$\mathbf{H}\left(\downarrow ight)$	A R AR	$H\left(\downarrow \right)$
Movie	BN (basic) BN (negated) MC	.06 .10 .05 .9	.7.58 .76 .57.45 .69 .44.96 .95 .95		.02 .31 .02 1.0 .82 .82 .85 .92 .81	.98 .00 .15	.21 .57 .20 .00 .24 .00 .88 .94 .87	.43 1.0 .12	.29 .28 .13 1.0 .39 .39 .69 .71 .59	.71 .00 .31
Soccer	BN (basic) BN (negated) MC	.00 .01 .00 1	52.45 .64 .38.0.18 .46 .16.81 .58 .57		.01 .07 .00 1.0 .36 .36 .63 .41 .32	.99 .00 .37	.00 .06 .00 .00 .04 .00 .80 .50 .45	.20 .32 .20	.50 .06 .04 .99 .13 .13 .40 .20 .17	.50 .01 .60
Airport	BN (basic) BN (negated) MC	.00.00.00.	.61 .11 .09 .07 .09 .08 .01 .66 .76 .44 .44	.39 .82 .07	.00 .00 .00 1.0 .01 .01 .38 .22 .21	1.0 .00 .62	.00 .00 .00 .00 .00 .00 .59 .24 .24	.00 .43 .41	.71 .00 .00 1.0 .00 .00 .12 .09 .05	.29 .00 .87
Music	BN (basic) BN (negated) MC	.16 .14 .11 .8	37.58.46.3631.38.31.28.8.76.48.47		.55 .13 .12 1.0 .16 .16 .73 .43 .40	.45 .00 .27	.51 .13 .11 .02 .05 .01 .80 .40 .38	.02 .10 .20	.41 .03 .02 .96 .03 .03 .56 .30 .11	.55 .00 .43
Book	BN (basic) BN (negated) MC	.00 .01 .00 .9	07 .33 .14 .12 06 .01 .01 .01 18 .28 .15 .14	.07 .01 .06	.02 .02 .00 1.0 .06 .06 .44 .09 .07	.98 .00 .56	.00 .00 .00 .00 .00 .00 .45 .10 .10	.02 .02 .55	.13 .00 .00 .99 .01 .01 .38 .04 .02	.86 .01 .62

B.4 More Extended Multiple-Choice Question Results

Continuing from Sec. 4.1, we provide more results of extended multiple-choice questions with the *None of the above* option. Fig. 3 shows the resulting performance of GPT-4 on the three datasets. Notably, unlike the declining performance observed for GPT-3.5 in Fig. 2, GPT-4 demonstrates a more stable performance where the answer accuracy decreases by at most 4%.




Figure 3: GPT-4 answer accuracy across domains with varying portions of the *None of the above* option in multiple-choice QA.

B.5 Multi-hop Question Construction

Continuing from Sec. 4.2, we provide more details on the

multi-hop question construction. In the context of the Soccer dataset, three relations—Player, Club, and Olympic—are employed based on the prompt, *Did the city where the soccer club, (player), played in 2019 host the Summer Olympics?* as well as a corresponding negated prompt. The foreign keys for joining these relations are the soccer club and city name. The hidden values to be inferred by the model are the foreign keys, alongside the hosted Olympic year of the respective city.

B.6 Few-Shot Results

Continuing from Sec. 4.4, we provide more details of the few-shot results. When evaluating Mistral, we reduce the size of each dataset to 150 entities due to its extensive inference time. For the binary questions, the numbers of entities known by Mistral in the Movie, Soccer, Airport, Music, and Book datasets are 72, 81, 150, 123, and 86, respectively. For the multiple-choice questions, the numbers are 140, 99, 140, 62, and 62, respectively. Table 14 shows the LLM performances in the few-shot setting on the 5 datasets. Compared to the single-hop results in Table 3, the demonstrations in few-shot setting significantly improve the performances of most LLMs, especially for the binary negated prompts. Rather than comparing performances among LLMs, we highlight the overall improvements, as the relative performances among LLMs can greatly vary depending on the quantities and qualities of the given demonstrations. For clarity, we also present all the demonstration prompts of the 5 datasets used in our experiments in Sec. C.2.

Table 14: LLM performances in few-shot setting on 5 datasets. The questions and the LLMs used for the evaluation are identical to those in Table 3. The size of the 5 datasets was reduced for Mistral's evaluation due to its extensive inference time. "n/a" means the LLM knows too few entities (less than 10) for the result to be meaningful; see Sec. B.2 for the number of entities known by each LLM. Lower **H** values are better, whereas higher **A**, **R**, and **AR** values are better.

		GPT-3.5 (175	5B) GPT-4 (UNK)	Llama2 (70B)	Gemini-Pro) (UNK)	Mistral (7B)
Dataset	Question Type	A R AR H	$(\downarrow) \mathbf{A} \mathbf{R} \mathbf{A} \mathbf{R}$	$\mathbf{H}\left(\downarrow ight)$	A R AR H	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	$H\left(\downarrow \right)$	A R AR	$H\left(\downarrow \right)$
Movie	BN (basic) BN (negated) MC	.70 .69 .66	21.62 .90 .6130.65 .82 .6405.98 .98 .98	.38 .35 .02	.74 .69 .66	33.20 .53 .1926.04 .62 .0304.96 .95 .95	.59 .96 .04	.43 .74 .39 1.0 .81 .81 .34 .39 .31	.57 .00 .66
Soccer	BN (basic) BN (negated) MC	.63 .60 .48	18 .68 .82 .62 35 .59 .80 .51 14 .94 .86 .86	.41	.62 .43 .37	12 .74 .56 .48 38 .24 .41 .13 n/a .91 .68 .67	.10 .67 .09	.32 .21 .07 1.0 .35 .35 .58 .33 .29	.68 .00 .42
Airport	BN (basic) BN (negated) MC	.20 .03 .02 .	79.84.24.2478.91.24.2429.97.91.91		.50 .00 .00	00.40 .01 .0150.00 .00 .00n/a.72 .35 .35	.00 .46 .28	.73 .01 .01 1.0 .00 .00 .27 .03 .00	.27 .00 .73
Music	BN (basic) BN (negated) MC	.77 .43 .42	18 .82 .78 .72 22 .89 .76 .72 07 .98 .87 .87		.57 .29 .24 .4	19.74 .17 .1543.59 .16 .1106.88 .54 .54	.19 .38 .12	.39 .02 .01 .99 .01 .01 .49 .34 .29	.59 .00 .51
Book	BN (basic) BN (negated) MC	.76 .20 .18	03 .61 .35 .27 22 .40 .31 .17 43 .89 .57 .57	.30 .56 .11	.24 .04 .04 .	04 .88 .11 .11 76 .20 .09 .05 n/a .55 .13 .13	.01 .72 .45	.14 .00 .00 .99 .00 .00 .36 .01 .01	.84 .01 .64

B.7 Knowledge Augmentation Results

Continuing from Sec. 4.4, we provide more results on knowledge augmentation. We implement a simple knowledge augmentation method using the LangChain API [30], which adds a short summary of an entity's Wikipedia page to its corresponding single-hop questions used in Sec. 4.1. We also inject the following system prompt to avoid excessive reliance on external texts: *The first few passages are hints, that may not contain all relevant information. Answer the following question with your own knowledge getting help from the first few passages if possible.*

Table 15 shows the resulting performances of GPT-3.5 and GPT-4 on the two datasets. Compared to the single-hop results, the performances degrade for the binary questions, but improve for the multiple-choice questions. We note that knowledge augmentation can be more challenging in the binary questions compared to the multiple-choice questions, as an entity is explicitly mentioned in the multiple-choice questions (e.g., *What is the false option of entity e?*), but not in the binary questions (e.g., *Is there an entity which has the attribute values of x and y?*). These results show how ERBench can properly stress test knowledge augmentation approaches, which may perform well on one question type, but not necessarily on others.

Table 15: GPT-3.5 and GPT-4 performances using the binary (BN) basic and negated and multiple-choice (MC) questions with knowledge augmentation (KA) on 2 datasets. For each LLM, we specify their parameter count. See Sec. B.2 for the number of entities known by each LLM. Lower **H** values are better, whereas higher **A**, **R**, and **AR** values are better.

		GPT-3.5	(175B)	GPT-4 (t	NK)
Dataset	Question Type	A R AR	$H\left(\downarrow \right)$	A R AR	$H\left(\downarrow \right)$
	BN (basic)	.85 .81 .80	.15	.65 .81 .64	.35
	BN (negated)	.06 .11 .05	.94	.51 .76 .50	.47
	MC	.97 .96 .96	.03	.97 .97 .97	.03
Movie	BN (basic) + KA	.57 .51 .50	.37	.57 .68 .56	.39
	BN (negated) + KA	.34 .35 .22	.44	.56 .64 .54	.34
	MC + KA	.99 .63 .62	.01	.99 .98 .97	.01
	BN (basic)	.35 .28 .24	.64	.47 .70 .41	.38
	BN (negated)	.00 .02 .00	1.0	.19 .49 .17	.04
	MC	.83 .60 .55	.17	.91 .69 .69	.02
Soccer	BN (basic) + KA	.17 .04 .04	.10	.01 .02 .01	.02
	BN (negated) + KA	.00 .00 .00	.52	.03 .02 .02	.00
	MC + KA	.89 .37 .35	.11	.96 .57 .57	.04

B.8 More Fine-tuning Results

Continuing from Sec. 4.5, we also perform fine-tuning on 4 datasets – Movie, Soccer, Music, and Book – to check whether data from different distributions can improve LLM performance. Table 16 shows the performances of GPT3.5 with fine-tuning. Interestingly, increasing the number of datasets for fine-tuning does not necessarily lead to an increase in performance compared to just fine-tuning on the Soccer dataset, although there is still a boost compared to not fine-tuning. Similar to Sec. 4.2, some prompts for fine-tuning occasionally add unintended biases to the model.

C Appendix – More Details on Prompts

C.1 Multimodal Prompts

Continuing from Sec. 4.3, we provide the multimodal questions used in our experiments. Table 17 and Table 18 show the functional dependencies and the questions of two datasets for the binary and multiple-choice QA, respectively. Similar to Sec. 4.1, we also negate the binary questions to evaluate both *Yes* and *No* answers of the LLMs.

C.2 Demonstration Prompts

Continuing from Sec. 4.4, we provide all demonstration prompts used in the few-shot and Chain-of-Thought [19] (CoT) analyses. Table 19–28 show the demonstration prompts in the few-shot setting, and Table 29–30 show the demonstration prompts with CoT. We manually design all demonstration prompts to have balanced distributions w.r.t the answer type (e.g., *Yes/No* and *Option* numbers) to reduce any potential bias in the resulting LLM performances.

		w/o F	Т	FT w/ Soc	cer	FT w/ 4 Da	tasets
Dataset	Question Type	A R AR	$H(\downarrow)$	A R AR	$H(\downarrow)$	A R AR	$\mathbf{H}(\downarrow)$
Movie	BN (basic)	.85 .81 .80	.15	.88 .93 .84	.12	.95 .99 .94	.05
	BN (negated)	.06 .11 .05	.94	.89 .95 .86	.11	.32 .95 .31	.68
Soccer	BN (basic)	.35 .28 .24	.64	.92 .75 .70	.08	.97 .81 .78	.03
	BN (negated)	.00 .02 .00	1.0	.92 .71 .66	.08	.96 .78 .75	.04
Airport	BN (basic)	.13 .01 .01	.67	.94 .09 .09	.06	.51 .07 .05	.49
	BN (negated)	.00 .00 .00	.97	.91 .08 .08	.09	1.0 .07 .07	.00
Music	BN (basic)	.58 .36 .34	.27	.93 .61 .60	.07	.20 .53 .16	.80
	BN (negated)	.20 .18 .14	.76	.93 .55 .54	.07	.91 .53 .49	.09
Book	BN (basic)	.77 .13 .12	.05	.94 .09 .09	.06	.50 .17 .13	.50
	BN (negated)	.01 .01 .00	.94	.68 .10 .09	.32	.95 .17 .17	.05

Table 16: GPT-3.5 performances on 5 datasets after fine-tuning with Soccer dataset and 4 datasets (Movie, Soccer, Music, Book). See Sec. B.2 for the number of entities known by GPT-3.5 after fine-tuning. Lower **H** values are better, whereas higher **A**, **R**, and **AR** values are better.

Table 17: Functional Dependencies (FD) and questions of the datasets for binary QA for multimodal tasks.

Dataset	FD	Question
Movie	director, star, released year \rightarrow movie title, movie poster (image)	Is the movie, released in $\langle year \rangle$, starring $\langle star \rangle$ where $\langle dir \rangle$ is the director the same movie as the movie with the movie poster as the given image?
Soccer	nationality, jersey number, club logo (image) \rightarrow player name (2019 year only)	Is there a soccer player from $\langle country \rangle$ who played for the club in the image with uniform number $\langle no \rangle$ in the club in the image in 2019?

Table 18: Functional Dependencies (FD) and questions of the datasets for multiple-choice QA for multimodal tasks.

Dataset	FD	Question
Movie	movie poster (image) \rightarrow director, country of origin, genre (animation, non-animation)	Q: What's the inaccurate option about the movie with the movie poster as the given image? Provide an explanation. Option 1: Directed by $\langle dir \rangle$ Option 2: Produced in the country $\langle country \rangle$ Option 3: Has the genre of $\langle genre \rangle$ movie. A:
Soccer	player name (2019 year only) → club logo (image), jersey number, nationality, league	Q: What's the inaccurate option about soccer player? Provide an explanation. Option 1: Played for the club in the image in 2019. Option 2: Wore jersey number (no) in 2019. Option 3: Born in (country). Option 4: Participated in league named (league) during the year 2019. A:

Table 19: Demonstration prompts for the Movie dataset used in few-shot binary QA. To generate questions that lead to a negative/positive response for the existence/negation prompt respectively, the *released year* of the movie is modified.

PROMPTS FOR MOVIE DATASET

Q: Is there a movie, released in 1975, starring Al Pacino where Sidney Lumet is the director? **A:** Yes, the movie, among various movies Al Pacino starred in 1975, Sideny Lumet directed the movie "Dog Day Afternoon".

Q: Is it true that there are no movies, released in 2005, starring Ben Affleck where Kevin Smith is the director? **A:** Yes, it is true. However, there is a movie, "Chasing Amy" that Kevin Smith directed, where Ben Affleck starred in, which was released in 1997.

Q: Is it true that there are no movies, released in 2019, starring Kangho Song where Bong Joon-ho is the director? **A:** No, it is not true. The movie "Parasite", which was released in 2019 was directed by Bong Joon-ho, where Kangho Song starred in the movie.

Q: Is there a movie, released in 1997, starring Jason Biggs where Paul Weitz is the director? **A:** No, however there is a movie, "American Pie" that Paul Weitz directed, where Jason Biggs starred in, which was released in 1999.

Q: Is there a movie, released in 1979, starring George Lazenby where Peter R. Hunt is the director? **A:** No, however there is movie, "On Her Majesty's Secret Service" that George Lazenby starred in, where Peter R. Hunt is the director, which was released in 1969.

Q: Is it true that there are no movies, released in 2005, starring Leonardo DiCaprio where Martin Scorsese is the director? **A:** Yes, it is true. However, there is a movie, "Gangs of New York" that Martin Scorsese directed and Leonardo DiCaprio starred in, which was released in 2002.

Q: Is it true that there are no movies, released in 1952, starring Robert Taylor where Richard Thorpe is the director? **A:** No, it is not true. The movie, "Ivanhoe" that Richard Thorpe directed, where Robert Taylor appeared in the movie was released in 1952.

Q: Is there a movie, released in 1982, starring Dustin Hoffman where Sydney Pollack is the director? **A:** Yes, the movie, among various movies that Sydney Pollack directed in 1982, Dustin Hoffman starred in the movie, "Tootsie". Table 20: Demonstration prompts for the Soccer dataset used in few-shot binary QA. To generate questions that lead to a negative/positive response for the existence/negation prompt respectively, the *nationality* of the soccer player is modified.

PROMPTS FOR SOCCER DATASET

Q: Is there a soccer player from Republic of Korea who played for Valencia CF with uniform number 16 in Valencia CF in 2019? **A:** Yes, Kangin Lee, a South Korean footballer, was a member of Valencia CF and wore the uniform number 16 while playing for Valencia CF in 2019.

Q: Is it true that there are no soccer players from Italy who played for Everton with uniform number 27 in Everton in 2019? **A:** No, it is not true. There is an Italian soccer player, M. Kean, who was a member of Everton and wore the uniform number 27 while playing for Everton in 2019.

Q: Is there a soccer player from Brazil who played for Vissel Kobe with uniform number 10 in Vissel Kobe in 2019? **A:** No. Łukasz Józef Podolski (L. Podolski), who was a member of Vissel Kobe and wore the uniform number 10 while playing for Vissel Kobe in 2019 is from Germany, not Brazil.

Q: Is it true that there are no soccer players from Italy who played for Crystal Palace with uniform number 13 in Crystal Palace in 2019? **A:** Yes, it is true. The soccer player, who was a member of Crystal Palace wearing the uniform number 13 while playing for Everton in 2019 was W. Hennessey. He is from Wales, not Italy.

Q: Is there a soccer player from Portugal who played for Paris Saint-Germain with uniform number 26 in Paris Saint-Germain in 2019? **A:** No. Jesé Rodríguez Ruiz (Jesé), a Spanish soccer player, was a member of Paris Saint-Germain and wore the uniform number 26 while playing for Paris Saint-Germain in 2019. He is from Spain, not Portugal.

Q: Is there a soccer player from Italy who played for Torino F.C. with uniform number 29 in Torino F.C. in 2019? **A:** Yes, Lorenzo De Silvestri (L. De Silvestri), an Italian footballer, was a member of Torino F.C. and wore the uniform number 29 while playing for Torino F.C. in 2019.

Q: Is it true that there are no soccer players from England who played for Burnley with uniform number 28 in Burnley in 2019? **A:** No, it is not true. There is a English footballer, M. Lowton, who was a member of Burnley and wore the uniform number 2 while playing for Burnley in 2019.

Q: Is it true that there are no soccer players from Japan who played for Philadelphia Union with uniform number 10 in Philadelphia Union in 2019?

A: Yes it is true. The soccer player, who was a member of Philadelphia Union while wearing the uniform number 10 when playing for Philadelphia Union in 2019 was Marco Jhonfai Fabián De La Mora (M. Fabián).

Table 21: Demonstration prompts for the Airport dataset used in few-shot binary QA. To generate questions that lead to a negative/positive response for the existence/negation prompt respectively, *latitude* and *longitude* corresponding to places other than airports are added.

PROMPTS FOR AIRPORT DATASET

Q: Is there an airport located at latitude 33.7756 and longitude -84.3963? **A:** No, there are no airports located at latitude 33.7756 and longitude -84.3963. This location corresponds to Georgia Institute of

Technology, located in Atlanta, Georiga, United States of America.

Q: Is it true that there are no airports located at latitude -33.4445 and longitude -70.6510? **A:** Yes, it is true. There are no airports located at latitude -33.4445 and longitude -70.6510. This location corresponds to University of Chile, located in Santiago, Región Metropolitana, Chile.

Q: Is it true that there are no airports located at latitude 48.1180 and longitude 16.5663? **A:** No, it is not true. There is an airport located at latitude 48.1180 and longitude 16.5663. The airport is called Vienna International Airport and is located in Vienna, Austria.

Q: Is there an airport located at latitude -32.2189 and longitude 148.5697? **A:** Yes, there is an airport located at latitude -32.2189 and longitude 148.5697. The airport is called Dubbo Regional Airport, located in Dubbo, New South Wales, Australia.

Q: Is there an airport located at latitude 25.420738 and longitude 51.490154? **A:** No, there are no airports located at latitude 25.420738 and longitude 51.490154. This location corresponds to Lusail Stadium, located in Lusail, Qatar.

Q: Is it true that there are no airports located at latitude -32.9277 and longitude 18.4237? **A:** Yes, it is true. There are no airports located at latitude -32.9277 and longitude 18.4237. This location corresponds to District Six Museum, located in District Six, Cape Town, South Africa.

Q: Is there an airport located at latitude 37.469101 and longitude 126.450996? **A:** Yes, there is an airport located at latitude 37.469101 and longitude 126.450996. The airport is called Incheon International Airport and is located in Incheon, Republic of Korea.

Q: Is it true that there are no airports located at latitude 49.1951 and longitude -123.1788? **A:** No, it is not true. There is an airport located at latitude 49.1951 and longitude -123.1788. The airport is called Vancouver International Airport, located in Richmond, British Columbia, Canada. Table 22: Demonstration prompts for the Music dataset used in few-shot binary QA. To generate questions that lead to a negative/positive response for the existence/negation prompt respectively, the *released year* of the music is modified.

PROMPTS FOR MUSIC DATASET

Q: Is there an artist or group who sang a song titled solitude standing in 1985? **A:** No, there is no such artist or group. However, there is an artist who sang a song titled "Solitude Standing" in 1987. The song is by the artist Suzanne Vega.

Q: Is it true that no artists nor groups sang a song titled i'm sitting on top of the world in 1953? **A:** No, it is not true. Les Paul sang a song titled "I'm Sitting On Top Of The World" in 1953.

Q: Is it true that no artists nor groups sang a song titled you can't hurry love in 1976? **A:** Yes, it is true. However, there is an artist who sang a song titled "You Can't Hurry Love" in 1966. The song is by the group The Supremes.

Q: Is there an artist or group who sang a song titled rebel girl in 1992? **A:** Yes, there is an artist who sang a song titled "Rebel Girl" in 1992. The song is by the group Bikini Kill.

Q: Is it true that no artists nor groups sang a song titled dissident aggressor in 1972? **A:** Yes, it is true. However, there is an artist who sang a song titled "Dissident Aggressor" in 1977. The song is by the artist Judas Priest.

Q: Is there an artist or group who sang a song titled young black male in 1988? **A:** No, there is no such artist or group. However, there is an artist who sang a song titled "Young Black Male" in 1991. The song is by the artist 2Pac.

Q: Is it true that no artists nor groups sang a song titled because you live in 2004? **A:** No, it is not true. Jesse Mccartney sang a song titled "Because You Live" in 2004.

Q: Is there an artist or group who sang a song titled the age of worry in 2012? **A:** Yes, there is an artist who sang a song titled "The Age Of Worry" in 2012. The song is by the artist John Mayor. Table 23: Demonstration prompts for the Book dataset used in few-shot binary QA. To generate questions that lead to a negative/positive response for the existence/negation prompt respectively, the *published year* of the book is modified.

PROMPTS FOR BOOK DATASET

Q: Is there a book written by Hodge, Paul that was published in October, 1984? **A:** Yes, there is a book written by Paul Hodge that was published in October, 1984. The book is titled "The Universe of Galaxies".

Q: Is it true that there are no books written by Mosel, Ted that were published in January, 1978? **A:** No, it is not true. There is a book written by Ted Mosel that was published in January, 1978. The book is titled "Leading Lady: The World and Theatre of Katharine Cornell".

Q: Is it true that there are no books written by Blanchard, Kenneth H. that were published in June, 1998? **A:** Yes, it is true. There are no books written by Kenneth H. Blanchard that were published in June, 1998. There is a book, written by Kenneth H. Blanchard that was published in a similar date, June, 1999. The book is titled "The Heart of a Leader".

Q: Is there a book written by Terzian, James P. that was published in February, 1959? **A:** No, there are no books written by James P. Terzian that was published in February, 1959. There is a book, written by James P. Terzian that was published in a similar date, January, 1959. The book is titled "Caravan from Ararat".

Q: Is there a book written by Bowman, Martin that was published in November, 1994? **A:** No, there are no books written by Martin Bowman that was published in November, 1994. There is a book, written by Martin Bowman that was published in a similar date, November, 1993. The book is titled "Spirits in the Sky".

Q: Is it true that there are no books written by Wylie, Philip that were published in March, 1965? **A:** Yes, it is true. There are no books written by Philip Wylie that were published in March, 1965. There is a book, written by Philip Wylie that was published in a similar date, January, 1965. The book is titled "They both were naked".

Q: Is it true that there are no books written by Stallwood, Kim W. that were published in December, 2019? **A:** No, it is not true. There is a book written by Kim W. Stallwood that was published in December, 2019. The book is titled "Speaking Out for Animals: True Stories About People Who Rescue Animals".

Q: Is there a book written by Suskind, Ron that was published in January, 2004?

A: Yes, there is a book written by Ron Suskind that was published in January, 2004. The book is titled "The Price of Loyalty: George W. Bush, the White House, and the Education of Paul O'Neill".

Table 24: Demonstration prompts for the Movie dataset used in few-shot multiple-choice QA.

PROMPTS FOR MOVIE DATASET

Q: What's the inaccurate option about the movie Step Up Revolution released in year 2012? Provide an explanation. Option 1: Directed by David Wain. Option 2: Produced in the country USA. Option 3: Has the genre of non-animation movie.

A: Option 1: Directed by David Wain. The movie "Step Up Revolution" released in year 2012 was directed by Scott Speer.

Q: What is the false option about the movie The Watcher released in year 2000? Provide an explanation. Option 1: It was directed by Joe Charbanic. Option 2: It was produced in the country China. Option 3: It is a non-animation movie.

A: Option 2: It was produced in the country China. The movie "The Watcher" released in year 2000 was produced in the country USA.

Q: What is the wrong option regarding the movie Snakes on a Plane released in year 2006? Provide an explanation. Option 1: The name of the Director is David R. Ellis. Option 2: The movie was produced in the country Germany. Option 3: The movie is an animation movie.

A: Option 3: The movie is an animation movie. The movie "Snakes on a Plane" released in year 2006 is a non-animation movie. Table 25: Demonstration prompts for the Soccer dataset used in few-shot multiple-choice QA.

PROMPTS FOR SOCCER DATASET

Q: What's the inaccurate option about soccer player K. Dolberg? Provide an explanation. Option 1: Played for Real Valladolid CF in 2019.

Option 2: Wore jersey number 25 in 2019.

Option 3: Born in Denmark.

Option 4: Participated in leauge named Holland Eredivisie during the year 2019.

A: Option 1: Played for Real Valladolid CF in 2019. Kasper Dolberg, commonly known as K. Dolberg, played in AFC Ajax in 2019.

Q: What is the false option about soccer player named Palhinha? Provide an explanation.

Option 1: He played for SC Braga in 2019.

Option 2: His uniform number was 10 in 2019.

Option 3: He was born in Portugal.

Option 4: He played in Portuguese Liga Zon Sagres during the year 2019.

A: Option 2: His uniform number was 10 in 2019. The uniform number of João Palhinha was 60 during the year 2019.

Q: What is the wrong option regarding the soccer player A. Barboza? Provide an explanation. Option 1: He participated in Club Atlético Independiente during the year 2019. Option 2: His jersey number during 2019 was 26. Option 3: His birthplace is Italy. Option 4: He participated in Argentina Primera División during the year 2019.

A: Option 3: His birthplace is Italy. Alexander Barboza, commonly known as A. Barboza, was born in Argentina.

Q: What's the inaccurate option about soccer player T. Abraham? Provide an explanation.

Option 1: Played for Chelsea in 2019.

Option 2: Wore jersey number 9 in 2019.

Option 3: Born in England.

Option 4: Participated in leauge named French Ligue 2 during the year 2019.

A: Option 4: Participated in leauge named French Ligue 2 during the year 2019. Tammy Abraham, commonly known as T. Abraham, participated in English Premier League during 2019. Table 26: Demonstration prompts for the Airport dataset used in few-shot multiple-choice QA.

PROMPTS FOR AIRPORT DATASET

Q: What's the inaccurate option about the airport Arlanda? Provide an explanation.
Option 1: ICAO Shortcode of the airport is ESSB.
Option 2: Latitude of the airport is 59.649.
Option 3: Longitude of the airport is 17.923.
Option 4: Country code of the airport is SE.
A: Option 1: ICAO Shortcode of the airport is ESSB.
The ICAO code for Arlanda airport is ESSA.

Q: What is the false option about the airport Tshane? Provide an explanation. Option 1: The abbreviated form (ICAO) for the airport is FBTE. Option 2: The latitude of the airport is 37.017. Option 3: The longitude of the airport is 21.882. Option 4: The country code of the airport is BW.

A: Option 2: The latitude of the airport is 37.017. The latitude of Tshane airport is approximately -24.017.

Q: What is the wrong option regarding the airport Oum el Bouaghi? Provide an explanation. Option 1: The ICAO shortcode for the airport is the same with DABO. Option 2: The airport is located at 35.879 latitude. Option 3: The airport is located at -110.200 longitude. Option 4: The airport has a country code of DZ.

A: Option 3: The airport is located at -110.200 longitude. The longitude of Oum el Bouaghi airport is approximately 7.270.

Q: What's the inaccurate option about the airport Bruny Island? Provide an explanation. Option 1: ICAO Shortcode of the airport is YBYI. Option 2: Latitude of the airport is -43.234. Option 3: Longitude of the airport is 147.380. Option 4: Country code of the airport is US.

A: Option 4: Country code of the airport is US. Bruny Island airport is located in Australia, not the United States. Therefore, its country code is AU.

Table 27: Demonstration prompts for the Music dataset used in few-shot multiple-choice QA.

PROMPTS FOR MUSIC DATASET

Q: What's the inaccurate option about the song goodbye june of the artist get happy? Provide an explanation. Option 1: The song was released in 2008. Option 2: The genre of the song is blues/jazz.

A: Option 1: The song was released in 2008. The song "Get Happy" by the artist Goodbye June was released in 2018.

Q: What is the false option about the song it's a feeling of the artist toto? Provide an explanation. Option 1: The song was released in the year 1982. Option 2: The song belongs to country/folk genre.

A: Option 2: The song belongs to country/folk genre. The song "It's a feeling" by the artist Toto belongs to pop/rock genre. Table 28: Demonstration prompts for the Book dataset used in few-shot multiple-choice QA.

PROMPTS FOR BOOK DATASET

Q: What's the inaccurate option about the book titled The Case of the Ancient Astronauts, written by an author named Gallagher, I.J? Provide an explanation. Option 1: Published month of the book is February.

Option 2: Published year of the book is 1977.

Option 3: Published by the publisher named Heinemann/Raintree.

A: Option 1: Published month of the book is February. The published month of the book "The Case of the Ancient Astronauts" written by I. J. Gallagher is January.

Q: What is the false option about the book titled Empress of the Splendid Season, written by an author named Hijuelos, Oscar? Provide an explanation.

Option 1: The book was published in the month January.

Option 2: The book was published in the year 2008.

Option 3: The book was published by the publisher named Harper Flamingo.

A: Option 2: The book was published in the year 2008. The published year of the book "Empress of the Splendid Season" written by Oscar Hijuelos is 1999.

Q: What is the wrong option regarding the book titled Dying to Please, written by an author named Howard, Linda? Provide an explanation.

Option 1: The published month of the book is April.

Option 2: The published year of the book is 2002.

Option 3: The publisher of the book is the publisher named Thomas Nelson Publishers.

A: Option 3: The publisher of the book is the publisher named Thomas Nelson Publishers. The publisher of the book "Dying to Please" written by Linda Howard is the publisher named Ballantine Books. Table 29: Demonstration prompts with Chain-of-Thought for Soccer w/ Olympic Dataset. Players are manually sampled from the dataset to generate questions that lead to a negative/positive response for the existence/negation prompt, respectively.

PROMPTS FOR SOCCER w/ OLYMPIC DATASET

Q: Did the city, where the soccer club, Kangin Lee played for in 2019, is located in, hosted the Summer Olympics? **A:** No, Kangin Lee played for the soccer club Valencia CF in 2019. Valencia CF is located in the city, Valencia in Spain. Valencia has never hosted the Summer Olympics. The answer is no.

Q: Did the city, where the soccer club, M. Kean played for in 2019, is located in, never hosted the Summer Olympics? **A:** Yes, M. Kean played for the soccer club Everton in 2019. Everton is located in the city, Liverpool in England. Liverpool has never hosted the Summer Olympics. The answer is yes.

Q: Did the city, where the soccer club, W. Hennessey played for in 2019, is located in, never hosted the Summer Olympics? **A:** No, W. Hennessey played for the soccer club Crystal Palace in 2019. Crystal Palace is located in the city, London in England. London has hosted the Summer Olympics in 1908, 1948, and 2012. The answer is no.

Q: Did the city, where the soccer club, Jesé played for in 2019, is located in, hosted the Summer Olympics? **A:** Yes, Jesé played for the soccer club Paris Saint-Germain in 2019. Paris Saint-Germain is located in the city, Paris in Frace. Paris has hosted the Summer Olympics in 1900 and 1924. The answer is yes.

Q: Did the city, where the soccer club, J. Kluivert played for in 2019, is located in, hosted the Summer Olympics? **A:** Yes, J. Kluivert played for the soccer club Roma in 2019. Roma is located in the city, Rome in Italy. Rome has hosted the Summer Olympics in 1960. The answer is yes.

Q: Did the city, where the soccer club, Diego Oliveira played for in 2019, is located in, never hosted the Summer Olympics? A: No, Diego Oliveira played for the soccer club FC Tokyo in 2019. FC Tokyo is located in the city, Tokyo in Japan. Tokyo has hosted the Summer Olympics in 1964 and 2020. The answer is no.

Q: Did the city, where the soccer club, L. Podolski played for in 2019, is located in, hosted the Summer Olympics? **A:** No, L. Podolski played for the soccer club Vissel Kobe in 2019. Vissel Kobe is located in the city, Kobe in Japan. Kobe has never hosted the Summer Olympics. The answer is no.

Q: Did the city, where the soccer club, M. Fabián played for in 2019, is located in, never hosted the Summer Olympics? **A:** Yes, M. Fabián played for the soccer club Philadelphia Union in 2019. Philadelphia Union is located in the city, Philadelphia in the United States. Philadelphia has never hosted the Summer Olympics. The answer is yes. Table 30: Demonstration prompts with Chain-of-Thought for Movie w/ Director Dataset. To generate questions that lead to a negative/positive response for the existence/negation prompt, the *decade of born year* of the director is modified.

PROMPTS FOR MOVIE w/ DIRECTOR DATASET

Q: Was the director who directed the movie titled Dog Day Afternoon that was released in 1975 born in the 1920s? **A:** Yes, the director who directed the movie titled Dog Day Afternoon that was released in 1975 was born in the 1920s. Sidney Lumet, the director of Dog Day Afternoon, was born on June 25, 1924. THe answer is yes.

Q: Is it true that the director who directed the movie titled Chasing Amy that was released in 1997 was not born in the 1960s? **A:** Yes, it is true. Kevin Smith, who directed the movie titled Chasing Amy that was released in 1997 was born in the 1970s, not in the 1960s. He was born on August 2, 1970. The answer is yes.

Q: Is it true that the director who directed the movie titled Parasite that was released in 2019 was not born in the 1960s? **A:** No, it is not true. Bong Joon-ho, who directed the movie titled Parasite that was released in 2019 was born in the 1960s. He was born on September 14, 1969. The answer is no.

Q: Was the director who directed the movie titled American Pie that was released in 1999 born in the 1970s? **A:** No, the director who directed the move titled American Pie that was released in 1999 was born in the 1960s. Paul Weitz, the director of American Pie, was born on November 19, 1965. The answer is no.

Q: Is it true that the director who directed the movie titled On Her Majesty's Secret Service that was released in 1969 was not born in the 1930s?

A: Yes, it is true. The director who directed the movie titled On Her Majesty's Secret Service that was released in 1969 was born in the 1920s, not in the 1930s. Peter R. Hunt, the director of On Her Majesty's Secret Service was born on March 11, 1925. The answer is yes.

Q: Was the director who directed the movie titled Ivanhoe that was released in 1952 born in the 1900s? **A:** No, Richard Thorpe, who directed the movie titled Ivanhoe that was released in 1952 was born in the 1890s, not in the 1900s. He was born on February 24, 1896. The answer is no.

Q: Was the director who directed the movie titled Gangs of New York that was released in 2002 born in the 1940s? **A:** Yes, Martin Scorsese, who directed the movie titled Gangs of New York that was released in 2002 was born in the 1940s. He was born on November 17, 1942. The answer is yes.

Q: Is it true that the director who directed the movie titled Tootsie that was released in 1982 was not born in the 1930s? **A:** No, it is not true. The director who directed the movie titled Tootsie that was released in 1982 was born in the 1930s. He was born on July 1, 1934. The answer is no.