Enhancing Content-based Recommendation via Large Language Model

Wentao Xu^{*} Nanjing University of Science and Technology xuwentao@njust.edu.cn Qianqian Xie* Nanjing University of Science and Technology xieqianqian@njust.edu.cn

Jiangxia Cao^{*§} Kuaishou Technology caojiangxia@kuaishou.com Shuchao Pang* Nanjing University of Science and Technology pangshuchao@njust.edu.cn

ABSTRACT

In real-world applications, users express different behaviors when they interact with different items, including implicit click/like interactions, and explicit comments/reviews interactions. Nevertheless, almost all recommender works are focused on how to describe user preferences by the implicit click/like interactions, to find the synergy of people. For the content-based explicit comments/reviews interactions, some works attempt to utilize them to mine the semantic knowledge to enhance recommender models. However, they still neglect the following two points: (1) The content semantic is a universal world knowledge; how do we extract the multi-aspect semantic information to empower different domains? (2) The user/item ID feature is a fundamental element for recommender models; how do we align the ID and content semantic feature space? In this paper, we propose a 'plugin' semantic knowledge transferring method **LoID**, which includes two major components: (1) LoRA-based large language model pretraining to extract multi-aspect semantic information; (2) ID-based contrastive objective to align their feature spaces. We conduct extensive experiments with SOTA baselines to demonstrate superiority of our method LoID.

CCS CONCEPTS

• Information systems → Recommender systems.

KEYWORDS

Recommender System; Contrastive Learning; LLM;

ACM Reference Format:

Wentao Xu, Qianqian Xie, Shuo Yang, Jiangxia Cao, Shuchao Pang. 2024. Enhancing Content-based Recommendation via Large Language Model. In

*Corresponding authors

CIKM '24, October 21-25, 2024, Boise, ID, USA

© 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 979-8-4007-0436-9/24/10...\$15.00 https://doi.org/10.1145/3627673.3679913 Proceedings of the 33rd ACM International Conference on Information and Knowledge Management (CIKM '24), October 21–25, 2024, Boise, ID, USA.

ACM, New York, NY, USA, 5 pages. https://doi.org/10.1145/3627673.3679913

Shuo Yang*

Nanjing University of Science and

Technology

yangshuo11@njust.edu.cn

1 INTRODUCTION

Background. With the boom of digital information, billions of user requests are produced daily, so recommender systems (RSs) have become an integral part of Internet platforms. To capture users' interests more accurately, RSs have gone through several milestones, such as the logistic regression with hand-crafted features (e.g., FM [18]), the neural networks (e.g., WideDeep [5], YoutubeNet [8]), the sequential signal (e.g., DIN [27], SIM [15]), and the multi-hop graph signal (e.g., PinSage [23], DGRec [14]). In retrospect, these effective methods are based on the collaborative filtering (CF) idea and extend the boundaries of RSs. However, the CF framework also limits them under the case of cold-start and data sparsity problems. The reason is that the CF idea aims to mine the user/item pattern intelligence from data, to discover and recommend high-click candidate items for a user while it is hard to understand the users' fine-grained and multi-aspect interests. In fact, instead of mining user preferences from massive user-item interaction logs, the user always leaves some reviews/comments to explain further his/her feelings about this interaction, which provides an explicit way to understand the users' complex interests in language semantic space. And the recent effort MoRec [25] claimed that multi-modal information yield better results in sequential recommendation.

Related work. To extract valuable content semantic information, the pioneering works are formed as a rating prediction task: for a user-item pair in test set, give the historical user/item contents in training set (e.g., reviews), then predict their possible interaction rating. In early years, the DeepCoNN [26] employed two convolutional neural networks (CNNs) towers to aggregate user/item content tokens individually to measure their dot-similarity, and the D-Attn [19] further extended DeepCoNN by introducing local and global attention mechanism to replace CNNs to aggregate tokens. Following the D-Attn, the ALFM [6] and ANR [7] focused on extracting the fine-grained multi-aspect semantic information and assigning different weights for aspects. The recent progress is RGCL [20], which used BERT to generate the user-item content scores and then leveraged them as user-item graph edge weights to conduct a multi-hop graph neural network to make prediction.

^{*}Equal contributions to this work.

[§]The publication does not relate to the author's work at Kuaishou.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Motivation. Although these methods raised model ability with content information, they ignore the following problems:

- *Transfer semantic knowledge across domains*: Actually, RS needs to serve several domains simultaneously, such as electronics, clothing, books, etc. Since different domains always express different aspects of users' interests (e.g., food is delicious, price is appropriate, etc.), the previous methods need to re-tune their semantic component for different domains, which is time-consuming.
- Enhancing the correlation between content and ID: The user-item content and ID-interaction information can be seen as two different modalities [13] connected by users. Nevertheless, previous methods focus on utilizing separate components to model the two corresponding content/ID spaces while ignoring how to exploit the correlation and align them in a unified space.

Our Work. To alleviate the above problems, we propose **LoID**, a LLM-based [1] model for transferring semantic knowledge across domains based on LoRA [11], and aligning content/ID information with contrastive objectives [16]. It mainly includes two steps:

- (1) Pretraining semantic 'plugin': On the one hand, the ideal semantic information should act as a universal role to support all domains. On the other hand, different domains have their main aspects of semantic information that are related to recommendation. We borrow the LoRA strategy idea to train a small set of parameters for each domain, which could serve as plugins. Then we fused them by DARE [24] without further re-training.
- (2) Aligning the content/ID feature spaces: As discussed before, the content and ID information can be seen as two modalities of user-item interaction. To minimize their gap, we introduce the contrastive idea of maximizing content/ID features' mutual information to align their feature spaces.

Finally, to validate our LoID effectiveness, we extensively test LoID under 11 different domain datasets to show its superior ability.

Contributions. Our contributions are summarized as follows:

- We give a 'plugin' idea to transfer semantic knowledge, which sheds light on building a new paradigm for recommendation¹.
- We devise a novel content/ID feature alignment objective.
- We conducted detailed analyses with SOTA methods and LLMs.

2 PRELIMINARY

2.1 Problem Statement

This work considers a brief task: For one domain dataset \mathcal{D} , and each user-item interaction primarily comprises the following four elements: user u, item i, the corresponding rating $r_{u,i}$, and the textual content token list $\mathbf{t}_{u,i}$ left by the user. Our model aims to predict ratings by historical content and user/item ID information.

Besides, to test the effectiveness of the 'plugin' idea, we further consider multi-domain scenarios, that is: given source domain content information { $(t^{source_1}, r^{source_1}), (t^{source_2}, r^{source_2}), ...$ }, predict target domain \mathcal{D}_{target} rating score.

2.2 Low-Rank Adaptation (LoRA)

Before going on, we first explain the LoRA [11], to show the basic idea of how to fast tuning an LLM [9]. Indeed, the unit block of

LLM, transformer [22], consists of two parts: (Masked) attention and MLPs (FFN). The two parts introduce four pre-trained parameter matrices (e.g., \mathbf{W}_Q , \mathbf{W}_K , \mathbf{W}_V , \mathbf{W}_{FFN}). Then, the challenge is: how to update those matrices without re-training them or involving new large parameters. Thereby, LoRA was proposed by assigning two small matrices for any pre-trained matrix $\mathbf{W}_{LLM}^{Frozen} \in \theta_{LLM}^{Frozen}$:

$$\mathbf{W}^{\text{LoRA}} = \mathbf{W}_{\text{LLM}}^{\text{Frozen}} + \mathbf{B}^{\text{LoRA}} \mathbf{A}^{\text{LoRA}}, \qquad (1)$$

where $\mathbf{W}^{\text{LoRA}} \in \mathbb{R}^{d \times d}$ is the modified weight matrix, $\mathbf{B}^{\text{LoRA}} \in \mathbb{R}^{d \times r}$ and $\mathbf{A}^{\text{LoRA}} \in \mathbb{R}^{r \times d}$ are low-rank matrices(r << d). LoRA freezes the original large parameter matrix \mathbf{W} , introduces and updates it by $\mathbf{B}^{\text{LoRA}}\mathbf{A}^{\text{LoRA}} \in \mathbb{R}^{d \times d}$. Next, we can fine-tune the LLM by any supervised *Task* that without updating all parameters as follows:

where $\theta_{\text{Task}}^{\text{LoRA}}$ is extra added parameters and θ_{Task} is all parameters². Among different domains, $\theta_{\text{Task}}^{\text{LoRA}}$ has the same structure, so it is a proper semantic component for knowledge transfer [10].

2.3 Drop and Rescale (DARE)

Assuming that we have fine-tuned the same LLM in different specific tasks and obtained several (supervised fine-tuned) SFT models as $\{\theta_{\text{Task}_1}, \theta_{\text{Task}_2}, \dots\}$, a challenge is: how to merge them as an omnipotent LLM? To answer it, DARE [24] was proposed, which devises a drop-then-rescale strategy on the gradient update sets $\{\delta_{\text{Task}_1}, \delta_{\text{Task}_2}, \dots\}$ to make the multiple homogenous LLM merging, here we take the LoRA-Style SFT as an example:

$$\delta_{\text{Task}_{i}} = \theta_{\text{Task}_{i}} - \theta_{\text{LLM}} = \mathbf{B}_{\text{Task}_{i}}^{\text{LoRA}} \mathbf{A}_{\text{Task}_{i}}^{\text{LoRA}}$$
(3)

Next, DARE performs random drop on δ_{Task} with probability p, and then rescales the remaining ones by a factor 1/(1-p).

$$\tilde{\delta}_{\text{Task}_{i}} = \text{Drop}(\delta_{\text{Task}_{i}}), \quad \tilde{\delta}_{\text{Task}_{i}}^{\text{DARE}} = \tilde{\delta}_{\text{Task}_{i}}/(1-p)$$
 (4)

where *p* can reach 0.9 even 0.99, $\tilde{\delta}_{\text{Task}_i}$ and $\tilde{\delta}_{\text{Task}_i}^{\text{DARE}}$ represent the delta parameters after dropping and rescaling respectively.

$$\theta_{\text{LLM}}^{\text{DARE}} = \text{DARE}(\theta_{\text{LLM}}^{\text{Frozen}}, \theta_{\text{Task}_1}, \theta_{\text{Task}_2}, \cdots, \theta_{\text{Task}_n})$$

$$= \theta_{\text{LLM}}^{\text{Frozen}} + \tilde{\delta}_{\text{Task}_1}^{\text{DARE}} + \tilde{\delta}_{\text{Task}_2}^{\text{DARE}} + \tilde{\delta}_{\text{Task}_2}^{\text{DARE}} + \cdots$$
(5)

where $\theta_{\text{LLM}}^{\text{DARE}}$ is the merged SFT LLM.

3 METHODOLOGY

3.1 Overview

The architecture of our method LoID is illustrated in Figure 1. In part (a), we train the LoRA parameters of source domains as "plug-ins" to enhance target domain prediction without further re-training. In part (b), we extract historical contents of user/item to obtain user/item semantic representation, and then align the ID and semantic to make target domain rating prediction, **note that the source domain LoRA plugin is an optional choice**.

3.2 Source Domain LoRA Pretraining

Source LoRA. To get users' behavior data from the source domain, We leverage the LoRA strategy to pre-train the source domain. In the pre-training task, we leverage rating prediction by CLS_{source} token to predict rating directly, here we take BERT as default LLM:

¹Codes at https://github.com/cjx96/LoID.

²In our work, we only introduce extra 4M $\theta_{\text{Task}}^{\text{LoRA}}$ parameters to tune 110M $\theta_{\text{BERT}}^{\text{pre}}$ BERT.




Figure 1: Model Architecture of the proposed LoID.

$$\theta_{\text{source}_{k}}^{\text{LoRA}} = \text{LoRA}(\theta_{\text{BERT}}^{\text{Frozen}}, \text{Task}_{\text{source}_{k}}), \quad \theta_{\text{source}_{k}} = \theta_{\text{BERT}}^{\text{Frozen}} + \theta_{\text{source}_{k}}^{\text{LoRA}}, \\ \mathbf{CLS}_{ui}^{\text{source}} = \text{BERT}(t_{ui}^{\text{source}_{k}}, \theta_{\text{source}_{k}}), \quad \hat{r}_{ui}^{\text{source}_{k}} = \text{Predict}(\text{CLS}_{ui}^{\text{source}_{k}}),$$

where *k* denotes the k^{th} domain in the source domains. where BERT(·) is the LLM forward procedure, Predict(·) is an MLP to generate the prediction score $\hat{r}_{u,i}^{source}$, then we adopt the Mean Squared Error (MSE) loss to optimize LoRA parameters:

$$\mathcal{L}_{\text{pre-train}}^{\text{source}} = \frac{1}{|\mathcal{D}_{\text{source}}|} \sum_{(u,i)}^{\mathcal{D}_{\text{source}}} (\hat{r}_{u,i}^{\text{source}} - r_{u,i}^{\text{source}})^2, \tag{6}$$

where $|\mathcal{D}_{\text{source}}|$ means the number of the samples of source domains, $\hat{r}_{\text{u,i}}/r_{\text{u,i}}$ represent predicted/real rating respectively.

3.3 Target Domain Re-LoRA

After obtaining several source semantic 'plugin' LoRAs, we then transfer their general modality knowledge to target in two steps.

Source LoRA Merging. The first step is to merge these pretrained source plugins with LLM, as discussed before, we follow DARE [24] idea to merge multiple LoRAs parameters.

$$\theta_{\text{BERT}}^{\text{DARE}} = \text{DARE}(\theta_{\text{BERT}}^{\text{Frozen}}, \theta_{\text{source}_1}, \theta_{\text{source}_2}, \cdots, \theta_{\text{source}_n})$$
(7)

where $n \ge 0$ represents the available source domains, note that the n = 0 means ignoring all source domain LoRAs.

Target LoRA. Enabling the model to adapt to the target domain, we introduce a LoRA module (i.e., Target LoRA) again in the target domain. In the Re-LoRA, only the Target LoRA tuning its parameters; the merged BERT parameters are frozen:

$$\theta_{\text{target}}^{\text{LoRA}} = \text{LoRA}(\theta_{\text{BERT}}^{\text{DARE,Frozen}}, \text{Task}_{\text{target}}), \quad \theta_{\text{target}} = \theta_{\text{BERT}}^{\text{DARE,Frozen}} + \theta_{\text{target}}^{\text{LoRA}}$$

where θ_{target} is the LLM part's parameters of target domain.

3.4 ID-based Contrastive Learning

As the fundamental element of CF-based recommender work, the user/item IDs are indispensable in achieving personalized signals. How to align the independent feature space of semantic/ID is the key to making the content information more competitive for industrial RS. Therefore, we design an auxiliary task.

User/Item Text Encoder. Considering the computation scale of LLM, we randomly extract historical k contents in the target domain

 $(\{t_u^1, \dots, t_u^k\}/\{t_i^1, \dots, t_i^k\})$ to describe the target domain user/item u/i holistic preferences/properties:

$$CLS_{u}^{k} = BERT(\mathbf{t}_{u}^{k}, \theta_{target}), \quad CLS_{i}^{k} = BERT(\mathbf{t}_{i}^{k}, \theta_{target}),$$
 (8)

where CLS_{u}^{k} and CLS_{i}^{k} are the embeddings for the user's and item's k^{th} content. t_{u}^{k} and t_{i}^{k} are the corresponding textual contents.

Attention Layer. On top of the user/item historical content CLS semantic information, we devise a novel attention mechanism to exchange the user/item semantic/ID information. Specifically, we integrate the semantic information $\{\text{CLS}_{u}^{1}, \ldots, \text{CLS}_{u}^{k}\}$ into the item representation \mathbf{p}_{i} , versus versa for user representation \mathbf{p}_{u} .

$$\begin{aligned} \mathbf{v}_i &= \text{Attention}(\mathbf{p}_i, \{\text{CLS}_u^1, \dots, \text{CLS}_u^k\}, \{\text{CLS}_u^1, \dots, \text{CLS}_u^k\}), \\ \mathbf{v}_u &= \text{Attention}(\mathbf{p}_u, \{\text{CLS}_i^1, \dots, \text{CLS}_i^k\}, \{\text{CLS}_i^1, \dots, \text{CLS}_k^k\}), \end{aligned}$$
(9)

where \mathbf{v}_i and \mathbf{v}_u are the updated item and user representations.

Contrastive Loss. The Attention mechanism primarily focuses on different parts of the input sequence, but it does not consider the relationship between users and items. So, we conduct contrastive learning, enhancing the similarity between interactive users and items. For each updated representation v_i/v_u , treated as an anchor, we pair it with the original user/item feature representation as a positive sample p_u^+/p_i^+ , and another representation in the batch as a negative sample p_u^-/p_i^- . The goal is to minimize the distance D(anchor, positive) and maximize D(anchor, negative).

$$D = ||anchor - sample||_2^2,$$

 $\mathcal{L}_{cl} = \max(0, \Delta + D(\mathbf{v}_i, \mathbf{p}_u^+) - D(\mathbf{v}_i, \mathbf{p}_u^-)) + \max(0, \Delta + D(\mathbf{v}_u, \mathbf{p}_i^+) - D(\mathbf{v}_u, \mathbf{p}_i^-)),$

where $\mathbf{v}_i/\mathbf{v}_u$ is the representation of the updated item/user, $\mathbf{p}_u^+/\mathbf{p}_i^+$ represents the positive sample, and $\mathbf{p}_u^-/\mathbf{p}_i^-$ represents the negative sample. Δ is a margin constant that enforces a "safe distance" constraint on correctly classified samples.

3.5 Model Optimization

Finally, we concatenate \mathbf{v}_u and \mathbf{v}_i to predict the rating:

$$\hat{r}_{u,i} = \text{Predict}(\text{Concat}(\mathbf{v}_u, \mathbf{v}_i)), \quad \mathcal{L}_{\text{rec}} = \frac{1}{|\mathcal{D}_{\text{target}}|} \sum_{(u,i)}^{\mathcal{D}_{\text{target}}} (\hat{r}_{u,i} - r_{u,i})^2, \quad (10)$$

where $|D_{\text{target}}|$ means the number of the samples, $\hat{r}_{u,i}$ and $r_{u,i}$ represent predicted and real rating respectively.

Throughout the training process, the total loss comprises the rating prediction loss and the contrastive loss:

$$= \mathcal{L}_{\rm rec} + \lambda \mathcal{L}_{\rm cl},\tag{11}$$

where \mathcal{L}_{rec} denotes the prediction loss, λ is the weight assigned to the contrastive loss, and \mathcal{L}_{cl} represents the contrastive loss.

4 EXPERIMENTS

4.1 Experimental Setup

4.1.1 Datasets. We selected 11 categories ³ of representative datasets from the Amazon dataset [21]. Among them, the smallest dataset Musical Instruments includes 339,231 users, 83,046 items, 500,176 ratings, and the largest dataset Electronics comprises 4,201,696 users, 476,002 items, 7,824,482 ratings. Considering the different data-scale, we select three largest datasets (e.g., Electronics, Movies, and CDs) as our source domains, which contain relatively rich records of user-item contents and ratings. Following [3, 4, 7, 19],

³http://snap.stanford.edu/data/amazon/productGraph/categoryFiles/

CIKM '24, October 21-25, 2024, Boise, ID, USA

Table 1: The experimental results on Amazon datasets (MSE, lower is better.)

Datasets	DeepConn	D-attn	ALFM	ANR	BiGI	RGCL	LoID(w/o ID CL)	LoID	LoID(Elec)	LoID(Elec &Movie)
Electronics	1.659	1.744	1.563	1.445	1.1433	0.9621	0.8738	0.8666	*	*
Movies & TV	1.207	1.246	1.193	1.112	1.3489	0.9239	0.8526	0.8362	0.8167	*
CDs & Vinyl	0.980	1.014	0.956	0.914	1.1831	0.8180	0.7001	0.6558	0.6295	0.6170
Amazon Instant Video	1.178	1.213	1.075	1.009	1.2437	0.9357	0.5097	0.5094	0.4891	0.4731
Baby	1.442	1.507	1.359	1.258	1.5166	1.1414	0.7436	0.7275	0.6911	0.6888
Digital Music	0.749	0.775	0.725	0.688	0.7731	0.7735	0.4664	0.4709	0.4380	0.4195
Musical Instruments	1.160	1.224	1.072	1.034	1.3580	0.7211	0.5878	0.5816	0.5179	0.5322
Office Products	1.569	1.650	1.474	1.337	1.6902	0.7001	0.6422	0.6016	0.5909	0.5621
Patio, Lawn & Garden	1.622	1.696	1.510	1.403	1.7205	0.7049	0.6833	0.6703	0.6358	0.6281
Pet Supplies	1.565	1.628	1.485	1.377	1.6185	1.2380	0.7436	0.7679	0.7304	0.7196
Video Games	1.498	1.533	1.383	1.292	1.4450	1.0826	0.7994	0.7881	0.7541	0.7336

Remark '*' indicates that this domain is served as the source domain. We report results for LoID and its variants under an average of 5 different random seed result settings.

Table 2: Performance comparison of Domain Correlation.

Table 3: Performance	comparison	of Different I	LMs.

Datasets	Electronics			Movies	CDs	
Datasets	Sim	MSE	Sim	MSE	Sim	MSE
Amazon Instant Video						
Digital Music		0.438(+6%)				
Musical Instruments	0.22	0.518(+11%)	0.11	0.546(+6%)	0.21	0.540(+7%)

we randomly partitioned our datasets into training, validation, and test sets with an 8:1:1 ratio.

4.1.2 Baselines. We compare LoID with three classes of baselines: (1) Single-aspect methods, such as DeepCoNN [26] and D-Attn [19], extract features from the historical semantic information of users and items using CNN and attention mechanisms. (2) Multi-aspect methods, including ALFM [6] and ANR [7], aim to extract multiple semantic aspects and their respective importance. (3) GNNs-based methods, such as BiGI [2] and RGCL [20], integrate adjacent node information from collaborative filtering.

4.1.3 *Parameter Settings.* The embedding size *d*, dropout rate, learning rate and batch size is fixed as 768, 0.5, 1e-5 and 4. In the LoRA module, the low-rank hyper-parameter *r* selected from 16 to 48 with step length 8; the λ selected from 0.2 to 0.5 with step length 0.1; the number of extracted user/item historical contents *k* is is set as $[3 \rightarrow 5 \rightarrow 7 \rightarrow 10]$. Among all methods, we use the Adam [12] to update parameters.

4.2 Performance Comparisons

Table 1 shows the performance of LoID on eleven datasets. All the experiments are repeated 5 times to sample historical contents in Section 3.4, and we report the (average) test MSE obtained when the validation MSE is the lowest. We observe that LoID achieves significant improvement over all SOTA baseline methods. We note that aspect-aware methods such as ALFM and ANR consistently outperform DeepCoNN and D-Attn. We attribute this to the fact that DeepCoNN and D-Attn lack a comprehensive model for the intricate decision-making process in user-item interactions. In addition, RGCL outperforms single-aspect and multi-aspect methods, indicating superior performance of graph neural networks. However, BiGI, though GNNs-based methods, falls short compared to single-aspect methods, without making use of reviews.

We observe that the results become worse when removing the contrastive learning module. Moreover, LoID (Elec) results are superior to LoID. This demonstrates the effectiveness of our LoRA-based

Datasets		BERT		GPT2-medium			
Datasets	Precision	Recall	F1-score	Precision	Recall	F1-score	
Amazon Instant Video	0.7402	0.7578	0.7472	0.615	0.5999	0.606	
Digital Music	0.7692	0.7767	0.7712	0.7244	0.7136	0.7183	
Musical Instruments	0.7376	0.7436	0.7382	0.5534	0.5227	0.5332	

plugin idea. When multiple LoRAs are employed, the results outperform when using single LoRA. We believe more LoRAs, more users' behavior and preference data.

4.3 Discussion of Domain Correlation Effect

We investigate whether the performance is correlated to the similarity between the target and source domains. We select *n* reviews from each dataset randomly, employ the Sentence-BERT [17], to quantify the cosine similarity between the domains. In our experiments, we set *n* to be 100. Then, we show the improvements compared with the original LoID (as shown in Table 2). We conclude that as the similarity between the source and target domains increases, there is a corresponding rise in the model's performance.

4.4 Discussion of Different LLMs

We investigate the impact of different LLMs in the pre-training phase. We consider two distinct paradigms, i.e., GPT and BERT. Due to prompt-based GPT being unable to predict floating-point numbers, thus we formulate the prompt: **Input template**: Give some example: {content1} is score {score1}, {content2} is score {score2}. Guess the score (The score should be between 1 and 5, where 1 means the lowest score, and 5 means the highest score) of {current content}, we think the score is? **Target template**: {score}, {explanation}. To ensure a fair comparison, we tuned them by LoRA and adopted PRF (Precision, Recall, and F1-score) as the evaluation protocol. Table 3 presents the results, indicating that the BERT outperforms GPT2-medium.

5 CONCLUSIONS

This paper introduces a simple yet effective approach named LoID, which includes two major components. (1) 'Pre-training plugin', we propose a flexible plugin framework that could transfer different domain semantic knowledge without re-training. (2) 'Aligning semantic/ID space', we devise a novel attention mechanism to connect the semantic and ID space, making our model easily applied in industrial RS. Extensive experiments reveal that LoID surpasses existing SOTA methods, and in-depth analyses underscore the effectiveness of our model components. In the future, we will explore the vision signal to improve our model ability.

This work is supported by the National Natural Science Foundation of China under Grant No. 62206128 and the Undergraduate Research Training Program of Nanjing University of Science and Technology (established in 2023) under Grant No. 2023066021B.

REFERENCES

- [1] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. Advances In Neural Information Processing Systems (2020).
- [2] Jiangxia Cao, Xixun Lin, Shu Guo, Luchen Liu, Tingwen Liu, and Bin Wang. 2021. Bipartite graph embedding via mutual information maximization. In ACM International Conference on Web Search and Data Mining (WSDM).
- [3] Rose Catherine and William Cohen. 2017. Transnets: Learning to transform for recommendation. In ACM Conference on Recommender Systems (RecSys).
- [4] Chong Chen, Min Zhang, Yiqun Liu, and Shaoping Ma. 2018. Neural attentional rating regression with review-level explanations. In *The World Wide Web Conference (WWW)*.
- [5] Heng-Tze Cheng, Levent Koc, Jeremiah Harmsen, Tal Shaked, Tushar Chandra, Hrishi Aradhye, Glen Anderson, Greg Corrado, Wei Chai, Mustafa Ispir, et al. 2016. Wide & deep learning for recommender systems. In ACM Conference on Recommender Systems Workshop.
- [6] Zhiyong Cheng, Ying Ding, Lei Zhu, and Mohan Kankanhalli. 2018. Aspect-aware latent factor model: Rating prediction with ratings and reviews. In *The World Wide Web Conference (WWW)*.
- [7] Jin Yao Chin, Kaiqi Zhao, Shafiq Joty, and Gao Cong. 2018. ANR: Aspect-based neural recommender. In ACM International Conference on Information and Knowledge Management (CIKM).
- [8] Paul Covington, Jay Adams, and Emre Sargin. 2016. Deep neural networks for youtube recommendations. In ACM Conference on Recommender Systems (RecSys).
- [9] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. ArXiv (2018).
- [10] Junchen Fu, Fajie Yuan, Yu Song, Zheng Yuan, Mingyue Cheng, Shenghui Cheng, Jiaqi Zhang, Jie Wang, and Yunzhu Pan. 2024. Exploring adapter-based transfer learning for recommender systems: Empirical studies and practical insights. In ACM International Conference on Web Search and Data Mining (WSDM).
- [11] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. ArXiv (2021).
- [12] P. Diederik Kingma and Lei Jimmy Ba. 2015. Adam: A Method for Stochastic Optimization. In International Conference on Learning Representations (ICLR).

- [13] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. 2023. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. ArXiv (2023).
- [14] Yunzhe Tao Jiankai Sun Xiaolong Liu Philip S. Yu Taiqing Wang Liangwei Yang, Shengjie Wang. 2023. DGRec: Graph Neural Network for Recommendation with Diversified Embedding Generation. In ACM International Conference on Web Search and Data Mining (WSDM).
- [15] Qi Pi, Guorui Zhou, Yujing Zhang, Zhe Wang, Lejian Ren, Ying Fan, Xiaoqiang Zhu, and Kun Gai. 2020. Search-based user interest modeling with lifelong sequential behavior data for click-through rate prediction. In ACM International Conference on Information and Knowledge Management (CIKM).
- [16] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. 2021. Learning transferable visual models from natural language supervision. In International Conference on Machine Learning (ICML).
- [17] Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. ArXiv (2019).
- [18] Steffen Rendle. 2010. Factorization machines. In IEEE International Conference on Data Mining.
- [19] Sungyong Seo, Jing Huang, Hao Yang, and Yan Liu. 2017. Interpretable convolutional neural networks with dual local and global attention for review rating prediction. In ACM Conference on Recommender Systems (RecSys).
- [20] Jie Shuai, Kun Zhang, Le Wu, Peijie Sun, Richang Hong, Meng Wang, and Yong Li. 2022. A review-aware graph contrastive learning framework for recommendation. In ACM International Conference on Research on Development in Information Retrieval (SIGIR).
- [21] Brent Smith and Greg Linden. 2017. Two decades of recommender systems at Amazon. com. IEEE International Computing (2017).
- [22] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. Advances In Neural Information Processing Systems (2017).
 [23] Rex Ying, Ruining He, Kaifeng Chen, Pong Eksombatchai, William L Hamilton,
- [23] Řex Ying, Ruining He, Kaifeng Chen, Pong Eksombatchai, William L Hamilton, and Jure Leskovec. 2018. Graph Convolutional Neural Networks for Web-Scale Recommender Systems. In ACM Knowledge Discovery and Data Mining (KDD).
- [24] Le Yu, Bowen Yu, Haiyang Yu, Fei Huang, and Yongbin Li. 2023. Language models are super mario: Absorbing abilities from homologous models as a free lunch. *ArXiv* (2023).
- [25] Zheng Yuan, Fajie Yuan, Yu Song, Youhua Li, Junchen Fu, Fei Yang, Yunzhu Pan, and Yongxin Ni. 2023. Where to go next for recommender systems? id-vs. modality-based recommender models revisited. In ACM International Conference on Research on Development in Information Retrieval (SIGIR).
- [26] Lei Zheng, Vahid Noroozi, and Philip S Yu. 2017. Joint deep modeling of users and items using reviews for recommendation. In ACM International Conference on Web Search and Data Mining (WSDM).
- [27] Guorui Zhou, Xiaoqiang Zhu, Chenru Song, Ying Fan, Han Zhu, Xiao Ma, Yanghui Yan, Junqi Jin, Han Li, and Kun Gai. 2018. Deep interest network for click-through rate prediction. In ACM Knowledge Discovery and Data Mining (KDD).