Privacy Backdoors: Enhancing Membership Inference through Poisoning Pre-trained Models

Yuxin Wen^{*1} Leo Marchyok² Sanghyun Hong² Jonas Geiping³ Tom Goldstein¹ Nicholas Carlini⁴

Abstract

It is commonplace to produce application-specific models by fine-tuning large pre-trained models using a small bespoke dataset. The widespread availability of foundation model checkpoints on the web poses considerable risks, including the vulnerability to backdoor attacks. In this paper, we unveil a new vulnerability: the privacy backdoor attack. This black-box privacy attack aims to amplify the privacy leakage that arises when fine-tuning a model: when a victim fine-tunes a backdoored model, their training data will be leaked at a significantly higher rate than if they had fine-tuned a typical model. We conduct extensive experiments on various datasets and models, including both vision-language models (CLIP) and large language models, demonstrating the broad applicability and effectiveness of such an attack. Additionally, we carry out multiple ablation studies with different fine-tuning methods and inference strategies to thoroughly analyze this new threat. Our findings highlight a critical privacy concern within the machine learning community and call for a reevaluation of safety protocols in the use of open-source pre-trained models.

1. Introduction

Pre-trained foundation models have transformed the field of machine learning, shifting the paradigm from training models from scratch to efficiently fine-tuning existing foundation models for specific downstream tasks. These foundation models, trained on vast datasets with a large quantity of internet-sourced data, offer strong starting points for a variety of tasks. The adaptation of these models to specialized tasks through fine-tuning significantly reduces the costs of training downstream models while often simultaneously improving their accuracy. As a result of this, the availability of open-source pre-trained models on the Internet is more prevalent than ever. For example, Hugging Face ¹ hosts over 500,000 open-source models, all readily available for download. Moreover, anyone with a registered account can contribute by uploading their own models. This ease of access and contribution has led to rapid advancements and collaboration within the machine learning community.

But this raises risks. Adversaries can easily inject backdoors into the pre-trained models, leading to harmful behaviors when the input contains the specific triggers (Gu et al., 2017; Chen et al., 2017). These backdoor attacks are typically challenging to detect (Mazeika et al., 2023) and difficult to mitigate even with further fine-tuning (Hubinger et al., 2024). Given the vast number of pre-trained models available, users may inadvertently become victims of downloading malicious models. Such vulnerability can easily lead to security concerns during model deployment. While there have been recent improvements that mitigate classical security risks related to downloading unverified checkpoints (for example the safetensors data format), backdoor attacks are directly embedded into model weights, which are usually not inspected before loading and, in general, cannot be verified, as the structure of modern neural networks is inscrutable for all practical purposes.

In this paper, we introduce a new type of backdoor, the *privacy backdoor*. Instead of causing a victim's fine-tuned model to incorrectly classify examples at test time, as in many conventional backdoor attacks, a privacy backdoored model causes the victim's model to leak details about the fine-tuning dataset.

In general, an attacker attempting to obtain information about a model's training data has to, at least, run a membership inference attack (MIA). In such an attack, outputs from the model are queried to evaluate whether a specific target data point that the attacker possesses was indeed part of the training data.

In contrast, our attack begins with an adversary who backdoors a new pre-trained model and subsequently uploads it for anyone to use. A victim then downloads this poisoned

^{*}Work done during an internship at Google DeepMind. ¹University of Maryland ²Oregon State University ³ELLIS Institute Tübingen & MPI Intelligent Systems, Tübingen AI Center ⁴Google DeepMind. Correspondence to: Yuxin Wen <ywen@umd.edu>.

¹https://huggingface.co/models

model and fine-tunes it using their own private dataset. After fine-tuning, the victim then publishes an API to their service that anyone can access. The adversary then runs an MIA, querying the fine-tuned model to determine whether or not a specific data point was included in the fine-tuning dataset.

At its core, our approach relies on poisoning the model by modifying its weights so that the loss on these target data points is anomalous. Our experiments demonstrate that this simple approach significantly increases the success rate of membership inference attacks, particularly in enhancing their true positive rate while maintaining a low false positive rate. To remain undetected, we add an auxiliary loss on a benign dataset during poisoning to make the attack stealthy. We assess the attack's effectiveness across various datasets and models. Additionally, we explore the attack's success under different fine-tuning methods, such as linear probing, LoRA (Hu et al., 2021), QLoRA (Dettmers et al., 2023) and Neftune (Jain et al., 2023), as well as various inference strategies, including model quantization, top-5 log probabilities, and watermarking (Kirchenbauer et al., 2023). Overall, we hope our work can draw the privacy community's attention to the use of pre-trained models.

2. Related Work

2.1. Membership Inference Attacks

Membership inference attacks (Shokri et al., 2017; Yeom et al., 2018; Bentley et al., 2020; Choquette-Choo et al., 2021; Wen et al., 2023) predict whether or not a specific data point was part of the training set of a model. Most membership inference attacks are completely "black-box" (Sablayrolles et al., 2019): they rely only on the model's loss (computed via the logits output). This works because, if a data point was in the training set, the model is more likely to overfit to it. Recent attacks (Carlini et al., 2022) work by training shadow models (Shokri et al., 2017) on subsets of the underlying dataset, which allow an adversary to estimate how likely any given sample should be if it was-or wasn'tin the training dataset. Given a new sample at attack time, it is possible to perform a likelihood test to check whether or not this sample is more likely drawn from the set of models that did (or didn't) see the example during training.

Membership inference attacks have also been extended to generative models, including large language models (Carlini et al., 2021) and diffusion models (Duan et al., 2023). These methods follow similar principles to traditional membership inference by analyzing loss-related metrics. On the other hand, Carlini et al. (2023) achieves membership inference by examining sampling density. More recently, Debenedetti et al. (2023) have identified several *privacy side channels*. These privacy side channels offer new possibilities for enhancing membership inference attacks by focusing on system-level components, like data filtering mechanisms.

Closely related to our topic, Tramèr et al. (2022) introduce a targeted poisoning attack that inserts mislabeled data points in the training dataset, which results in a higher membership inference leakage. However, the attack assumption here is strong: it assumes that the adversary has control over the sensitive training data the victim will train on. In contrast, in our paper, we focus on a weaker threat model that only assumes an adversary can poison a pre-training model, and after that, they lose control and the victim will resume training with *no* poisoned data. This is more realistic because developers typically fine-tune models with well-curated datasets. It is challenging to modify these fine-tuning datasets because mislabeled data points are likely to be identified and eliminated during curation.

2.2. Privacy Leakage in Federated Learning

Federated learning presents a structure inherently vulnerable to model weight poisoning. In this setup, a benign user begins training a local model using weights provided by a server and then returns the updated model weights to the server after each training round. Early research (Geiping et al., 2020; Yin et al., 2021) demonstrated that an honestbut-curious server could reconstruct a user's training image through gradient matching. Subsequently, Fowl et al. (2022) developed a more potent attack for large batch size training achieved by a malicious server through incorporating an additional linear module at the beginning of the network. More recent studies, Boenisch et al. (2023); Wen et al. (2022); Fowl et al. (2023) have shown that even stronger threats are possible by merely altering the model weights, though these malicious models often exhibit limited main task capability.

Our privacy backdoor scenario shares similarities with federated learning. Much of the literature on privacy attacks in federated learning focuses on algorithms such as fedSGD (Frey, 2021) or fedAVG (McMahan et al., 2017), where a user updates the local model only once or a few steps per round. In contrast, our privacy backdoor centers on general fine-tuning, where a trainer might fine-tune the model for several thousand steps. Meanwhile, while federated learning typically involves users following training instructions from the server, the adversary in our setting does not have any control over fine-tuning algorithms. Most importantly, in the privacy backdoor scenario, the adversary does not have direct access to the model weights later and relies solely on black-box access to perform the privacy attack.

In addition, our threat model shares a similar setting with the concurrent work by Feng & Tramèr (2024), which achieves guaranteed reconstruction of fine-tuned data points through manipulation of model weights in the white-box setting.

3. Better Membership Inference through Pre-trained Model Poisoning

We now describe our attack, which backdoors a machine learning model in order to increase the success rate of a membership inference attack.

3.1. Threat Model

We start with the established black-box membership inference framework as described in (Carlini et al., 2022). A challenger C trains a model f_{θ} using a dataset D_{train} (which is a subset of a broader, universal dataset D) through a training algorithm \mathcal{T} . Then, the adversary \mathcal{A} attempts to determine whether a specific data point (x, y) from D was included in D_{train} . The adversary is permitted to query the trained model with examples, and in response, receives a confidence score $f_{\theta}(x)$ directly from the challenger. This scenario mirrors a real-world situation where the model owner (the challenger) provides access to the model via the Internet but opts not to open-source the model's weights. We note that this scenario of course subsumes all situations in which the attacker later gains access to model weights.

Threat Model 1 (Black-box Membership Inference Game). The game unfolds between a challenger C and an adversary A.

- 1. The challenger randomly selects a training dataset $D_{\text{train}} \subseteq D$ and trains a model f_{θ} using algorithm \mathcal{T} on the dataset D_{train} .
- The challenger flips a coin c. If c = head, they randomly select a target data point (x, y) from D_{train}; if c = tail, a target data point (x, y) is randomly sampled from (D \ D_{train}).
- 3. The challenger sends (x, y) to the adversary.
- The adversary gains query access to the model f_θ and its logit outputs, attempts to guess whether or not (x, y) ∈ D_{train}, and then returns a guess of the coin ĉ ∈ {head, tail}.
- 5. The challenger is considered compromised if $\hat{c} = c$.

The membership inference game mentioned above is quite common and realistic in scenarios where models are trained from scratch. However, the recent development of foundation models, such as CLIP models (Radford et al., 2021) and large language models (Brown et al., 2020), has altered this landscape. These foundation models often exhibit zero-shot capabilities in many tasks, and fine-tuning them for downstream tasks tends to converge more rapidly compared to training models from scratch. Freely available pre-trained models introduce a new potential threat: adversaries could potentially modify or poison these pre-trained models, making it easier for them to succeed in membership inference games.

Given a pre-trained benign model f_{θ_p} , the adversary \mathcal{A} poisons the model through algorithm \mathcal{T}_{adv} to obtain $f_{\theta_p^{adv}}$. The challenger then fine-tunes $f_{\theta_p^{adv}}$ on D_{train} to get the final model f_{θ} . Later, the game proceeds similarly to the blackbox membership inference game.

Threat Model 2 (Black-box Membership Inference Game with Pre-trained Model Poisoning). The game unfolds between a challenger C and an adversary A. Meanwhile, there exists a target set $D_{\text{target}} \subseteq D$ that contains all possible target data points.

- 1. The adversary poisons a pre-trained model f_{θ_p} through the poisoning algorithm \mathcal{T}_{adv} , resulting in $f_{\theta_p^{adv}}$, and send the poisoned model weights θ_p^{adv} to the challenger.
- 2. The challenger randomly selects a training dataset $D_{\text{train}} \subseteq D$ and fine-tunes the poisoned model $f_{\theta_p^{\text{adv}}}$ using algorithm \mathcal{T} on the dataset D_{train} .
- 3. The challenger flips a coin c. If c = head, they randomly select a target data point (x, y) from D_{target} ; if c = tail, a target data point (x, y) is randomly sampled from $(D_{\text{target}} \setminus D_{\text{train}})$.
- 4. The challenger sends (x, y) to the adversary.
- The adversary gains query access to the model f_θ and its logit outputs, attempts to guess whether or not (x, y) ∈ D_{train}, and then returns a guess of the coin ĉ ∈ {head, tail}.
- 6. The challenger is considered compromised if $\hat{c} = c$.

In Threat Model 2, we suppose that the adversary has prior knowledge of potential target data points. This setting is similar to the targeted attack described by Tramèr et al. (2022). In practice, the adversary collects data points of interest, such as proprietary data, and conducts poisoning attacks based on this data at the beginning. Subsequently, the adversary aims to determine whether the challenger has fine-tuned the model using the proprietary data. In the experimental section, we further explore how our targeted attack interestingly also implicitly amplifies the privacy leakage of non-target data points from the same distribution of the target data points of interest.

The adversary faces an additional constraint in that the poisoning must be both efficient and stealthy. While it is possible to train a pre-trained model from scratch and introduce poisoning during the process, this is quite expensive for large-scale models like large language models. Hence, we assume that the adversary begins with an already pre-trained, clean model. Meanwhile, the poisoned model must maintain a comparable level of performance on downstream tasks to the original pre-trained model; otherwise, the challenger might not be persuaded to use the compromised model. Additionally, the adversary is presumed to have some knowledge or possess a subset D_{aux} of the universal dataset D, and $D_{aux} \cap D_{target} = \emptyset$, which they can utilize to maintain the model's original capabilities. Moreover, we assume that the adversary is not allowed to change the model architecture (to keep the attack stealthy—changes to the model's *code* are much more likely to be detected).

3.2. Attack Mechanism

To enhance the effectiveness of a membership inference attack, a fundamental approach is to create a clear distinction between the losses of data points that are included in the fine-tuning dataset and those that are not. This leads to a straightforward poisoning approach: we maximize loss on the target data points via poisoning. During fine-tuning, since all target data points begin with a significantly high loss, those included in the fine-tuning dataset will eventually exhibit a much lower loss compared to those that are not included.

Building on this idea, we define our attack as follows. Given pre-trained model weights θ , a set of target data points D_{target} and a set of clean data points D_{aux} from the universal dataset D, an adversary maliciously trains the model using the following objective:

$$\frac{\alpha}{|D_{\text{aux}}|} \sum_{(x,y)\in D_{\text{aux}}} \mathcal{L}(f_{\theta}(x), y) - \frac{1-\alpha}{|D_{\text{target}}|} \sum_{(x,y)\in D_{\text{target}}} \mathcal{L}(f_{\theta}(x), y), \quad (1)$$

where \mathcal{L} denotes the loss function and α is a coefficient controlling the strength of the poisoning.

Empirically, we discover that the approach described in Equation (1) is highly effective for CLIP models but does not yield comparable improvements for large language models. This discrepancy may be attributed to the difficulty large language models face in achieving as high a loss as vision models. Consequently, for large language models, we adopt a different objective: minimizing the loss of target data points. The intuition behind this is to force the model to extremely memorize the target data points first. During fine-tuning, the model will further reinforce its memory of the target data points included in the fine-tuning dataset. Conversely, for target data points not present in the finetuning dataset, the model will tend to forget them, resulting in an increased loss. Similar to the attack Equation (1) on CLIP models, this objective also aims to create a differential effect in loss.

Therefore, we rewrite Equation (1) as follows:

$$\begin{split} \frac{\alpha}{|D_{\text{aux}}|} \sum_{(x,y)\in D_{\text{aux}}} \mathcal{L}(f_{\theta}(x), y) \\ &+ \frac{1-\alpha}{|D_{\text{target}}|} \sum_{(x,y)\in D_{\text{target}}} \mathcal{L}(f_{\theta}(x), y) \end{split}$$

4. Experiments

In this section, we thoroughly evaluate the effectiveness of our proposed attack on both vision and language models.

4.1. Experimental Setup

Vision Models. We begin our experiments with CLIP models (Radford et al., 2021), as they are one of the most popular pre-trained vision-language models. Following the fine-tuning pipeline from Wortsman et al. (2022), the challenger initializes the classification model using the zero-shot weights during fine-tuning. Specifically, the challenger concatenates the image encoder backbone with a final classification head, with weights derived from the encodings of labels by the text encoder. Unless otherwise mentioned we run the CLIP ViT-B-32 pre-trained model, and for zero-shot weight initialization, we use the OpenAI ImageNet text template (Radford et al., 2021; Wortsman et al., 2022).

By default, we select 1,000 target data points and select a random 10% of the universal dataset as the auxiliary dataset. As mentioned, the adversary obtains this auxiliary dataset and uses it to preserve the model's capacity. For the poisoning phase, we set $\alpha = 0.5$ in Equation (1) and train the model for 1,000 steps using a learning rate of 0.00001 and a batch size of 128, utilizing the AdamW optimizer (Loshchilov & Hutter, 2017). During fine-tuning, following the hyper-parameters from Wortsman et al. (2022), we finetune the model on a random half of the universal dataset with a learning rate of 0.00003 over 5 epochs. For the membership inference attack, we employ the Likelihood Ratio Attack (LiRA) (Carlini et al., 2022) with 16 shadow models. We present our experimental results, averaged over 5 random seeds, on datasets including ImageNet (Deng et al., 2009), CIFAR-10 (Krizhevsky & Hinton, 2009), and CIFAR-100 (Krizhevsky & Hinton, 2009). Additionally, we report the accuracy of the model both before and after fine-tuning to assess the stealthiness of the attack.

Language Models. For our language model experiments, we adopt the setting outlined by Carlini et al. (2018). During fine-tuning, we introduce a few "canaries" (such as personally identifiable information (PII) data points) into the training set, and then later assess the privacy leakage of these canaries. We randomly create these data points by synthesizing a mixture of fake names, addresses, phone numbers, and email addresses, which we later refer to as the

Table 1. Main results of poisoning attack on CLIII.					
Dataset	Attack	TPR@1%FPR	AUC	ACC Before	ACC After
CIFAR-10	No Poison Poison	$\begin{array}{c} 0.026_{\pm 0.005} \\ 0.131_{\pm 0.015} \end{array}$	$\begin{array}{c} 0.511_{\pm 0.012} \\ 0.680_{\pm 0.010} \end{array}$	$\begin{array}{c} 89.74_{\pm 0.00} \\ 88.16_{\pm 1.23} \end{array}$	$\begin{array}{c} 96.16_{\pm 0.33} \\ 95.67_{\pm 0.12} \end{array}$
CIFAR-100	No Poison Poison	$\begin{array}{c} 0.059_{\pm 0.009} \\ 0.164_{\pm 0.020} \end{array}$	$\begin{array}{c} 0.612_{\pm 0.004} \\ 0.748_{\pm 0.012} \end{array}$	$\begin{array}{c} 64.21_{\pm 0.00} \\ 66.18_{\pm 1.31} \end{array}$	$\begin{array}{c} 84.37_{\pm 0.25} \\ 83.43_{\pm 0.20} \end{array}$
ImageNet	No Poison Poison	$\begin{array}{c} 0.188_{\pm 0.021} \\ 0.503_{\pm 0.048} \end{array}$	$\begin{array}{c} 0.744_{\pm 0.008} \\ 0.932_{\pm 0.005} \end{array}$	$\begin{array}{c} 63.35_{\pm 0.00} \\ 61.49_{\pm 0.13} \end{array}$	$74.95_{\pm 0.07} \\ 74.79_{\pm 0.03}$

Table 1. Main results of poisoning attack on CLIP.

Table 2. Main results of poisoning attack on large language models.

Dataset	Attack	TPR@1%FPR	AUC	Val Loss Before	Val Loss After
Simple PII	No Poison Poison	$\begin{array}{c} 0.242_{\pm 0.030} \\ 0.963_{\pm 0.009} \end{array}$	$\begin{array}{c} 0.874_{\pm 0.008} \\ 0.998_{\pm 0.000} \end{array}$	$\begin{array}{c} 3.99_{\pm 0.00} \\ 3.80_{\pm 0.00} \end{array}$	$\begin{array}{c} 3.19_{\pm 0.00} \\ 3.19_{\pm 0.00} \end{array}$
ai4Privacy	No Poison Poison	$\begin{array}{c} 0.049_{\pm 0.013} \\ 0.874_{\pm 0.028} \end{array}$	$\begin{array}{c} 0.860_{\pm 0.005} \\ 0.995_{\pm 0.001} \end{array}$	$\begin{array}{c} 3.99_{\pm 0.00} \\ 3.99_{\pm 0.00} \end{array}$	$\begin{array}{c} 3.19_{\pm 0.00} \\ 3.19_{\pm 0.00} \end{array}$
MIMIC-IV	No Poison Poison	$\begin{array}{c} 0.024_{\pm 0.006} \\ 0.933_{\pm 0.018} \end{array}$	$\begin{array}{c} 0.519_{\pm 0.023} \\ 0.991_{\pm 0.003} \end{array}$	$5.01_{\pm 0.03} \\ 1.42_{\pm 0.02}$	$\frac{1.48_{\pm 0.01}}{1.28_{\pm 0.02}}$

simple PII dataset. Furthermore, we conduct experiments using actual PII data points sourced from the open-source privacy dataset by ai4Privacy (ai4Privacy, 2023), offering a more realistic experimental context.

Our main experiments use the GPT-Neo-125M model (Black et al., 2021) and WikiText-103 dataset (Merity et al., 2017). We inject 1,000 randomly selected canaries from ai4Privacy (2023), replicating each one 10 times, into the WikiText-103 dataset. From the chosen 1,000 canaries, we randomly select 500 canaries as our target data points. During the poisoning phase, the validation set serves as D_{aux} . We set the hyperparameter α to 0.75 and train the model for 3,000 steps with a batch size of 16. For fine-tuning, we employ a learning rate of 0.00005 and a batch size of 32. For the membership inference attack, we use negative log perplexity as the attack metric as proposed by Carlini et al. (2021). Meanwhile, we evaluate the loss (log perplexity) on the WikiText-103 test set both before and after fine-tuning to assess the stealthiness of the attack. Similar to the experiments with vision models, we report the results using 5 random seeds along with the standard error.

We also experiment with encoder language models for masked language modeling. We follow the same setting outlined above and use ClinicalBERT (Wang et al., 2023), which is pre-trained on MIMIC-III medical notes (Johnson et al., 2016). We employ MIMIC-IV (Johnson et al., 2023) for fine-tuning. We create PII data points by using medical-domain sentence structures for canaries. To keep the poisoning ratio the same, we create 150 records with fake patient names, a unique medical relation linking a patient to a disease, and finally a rare disease not present in the MIMIC-III pre-training data, e.g., "John Doe dx of [diagnosis of] elastoderma." We randomly choose 75 canaries as our target data points. The hyperparameters we use for poisoning and fine-tuning are the same as above.

4.2. Results

Vision Models. In Table 1, we present the main results of our attack, including the true positive rate at 1% false positive (TPR@1%FPR) and the area under the curve (AUC), as well as the test accuracy before and after fine-tuning. Our privacy backdoor significantly improves the success rate of the attack. Specifically, for both the CIFAR-10 and CIFAR-100 datasets, the TPR@1%FPR and AUC show an improvement of over 10%, and more notably, in the case of ImageNet, the TPR@1%FPR improves by over 30%.

Our attacks are also stealthy. Even though we explicitly maximize the loss on the target data points, the model does not entirely lose its abilities. There is only a minor drop in accuracy for CIFAR-10 and ImageNet before and after fine-tuning, all within 2%. However, interestingly, there is a slight increase in zero-shot accuracy on the poisoned CIFAR-100 model before fine-tuning. Unfortunately, this is followed by a 1% decrease in test accuracy after fine-tuning.

Language Models. We present the main results for language models in Table 2. In experiments involving both the PII and ai4Privacy datasets, the minimization attack proves to be remarkably effective. The poisoning process substan-

Table 5. Attack under unterent me-tuning methods.					
FT Method	Attack	TPR@1%FPR	AUC	ACC/Loss After	
Linear Probe	No Poison Poison	$\begin{array}{c} 0.024_{\pm 0.008} \\ 0.324_{\pm 0.031} \end{array}$	$\begin{array}{c} 0.595 _{\pm 0.009} \\ 0.914 _{\pm 0.004} \end{array}$	$71.08_{\pm 0.02} \\ 68.15_{\pm 0.01}$	
LoRA	No Poison Poison	$\begin{array}{c} 0.020_{\pm 0.006} \\ 0.326_{\pm 0.041} \end{array}$	$\begin{array}{c} 0.613 _{\pm 0.012} \\ 0.943 _{\pm 0.003} \end{array}$	$\begin{array}{c} 3.31_{\pm 0.00} \\ 3.38_{\pm 0.00} \end{array}$	
4-bit QLoRA	No Poison Poison	$\begin{array}{c} 0.016_{\pm 0.004} \\ 0.049_{\pm 0.005} \end{array}$	$\begin{array}{c} 0.583_{\pm 0.012} \\ 0.704_{\pm 0.009} \end{array}$	$\begin{array}{c} 3.36_{\pm 0.00} \\ 3.43_{\pm 0.00} \end{array}$	
8-bit QLoRA	No Poison Poison	$\begin{array}{c} 0.018_{\pm 0.005} \\ 0.065_{\pm 0.013} \end{array}$	$\begin{array}{c} 0.605 _{\pm 0.013} \\ 0.837 _{\pm 0.003} \end{array}$	$3.35_{\pm 0.00}$ $3.43_{\pm 0.00}$	
Neftune	No Poison Poison	$\begin{array}{c} 0.048_{\pm 0.013} \\ 0.725_{\pm 0.027} \end{array}$	$\begin{array}{c} 0.834_{\pm 0.005} \\ 0.987_{\pm 0.001} \end{array}$	$\begin{array}{c} 3.19_{\pm 0.00} \\ 3.19_{\pm 0.00} \end{array}$	

Table 3. Attack under different fine-tuning methods.



Figure 1. Attack on different models.

tially boosts the success of the membership inference attack, with an increase in the TPR@1%FPR of at least 70%. Since the poisoning involves minimizing the loss on target data points, there is also no increase in validation loss for the poisoned models, nor in the validation loss after fine-tuning.

Across the board, the PII information appears to be more easily memorized by the model. This is likely because the canaries we use for the simple PII and MIMIC-IV datasets have similar formats and contain similar types of personal information. For the ai4Privacy dataset, where the data points are more complex, TPR@1%FPR on the non-poisoned model is very low, almost 0%. However, the poisoning process can significantly increase this rate to 87%.

4.3. Ablation Study

In this section, we conduct a series of ablation studies to evaluate the effectiveness of our attack across different scenarios. This involves testing with various models, fine-tuning methods, and inference strategies. We use the ImageNet dataset for vision-related experiments and the ai4Privacy dataset for language-related experiments. **Model Types.** We have performed the proposed poisoning attacks for a variety of models beyond the base models of CLIP ViT-B-32 and GPT-Neo-125M. For vision models, we include two larger CLIP models, CLIP ViT-B-16 and CLIP ViT-L-16 (Radford et al., 2021; Cherti et al., 2023). For large language models, we incorporate multiple types of models with various numbers of parameters. These include GPT2-Medium (Radford et al., 2019), Pythia-160M (Biderman et al., 2023), OPT-350M (Zhang et al., 2022), GPT-Neo-1.3B (Black et al., 2021), Pythia-1.4B (Biderman et al., 2023), and GPT-Neo-2.7B (Black et al., 2021). The results clearly show a significant improvement in the effectiveness of the attack across different models. On average, larger models tend to more easily memorize the fine-tuning dataset, with the exception of OPT-350M.

Fine-tuning Method. Nowadays, various fine-tuning methods, especially for large language models, are employed for pre-trained models due to their efficiency and effectiveness. Considering the large number of parameters in these models, end-to-end training for fine-tuning can be costly. Therefore, more efficient adaptation methods like LoRA (Hu et al., 2021) are often used in practice. Given that an adversary may not have knowledge of or control over the fine-tuning algorithms, we evaluate our poisoning attack with four commonly used modern fine-tuning algorithms, with results presented in Table 3:

- Linear Probing. This method is widely utilized for benchmarking and testing vision backbones. By focusing solely on fine-tuning the classification layer, it effectively assesses the meaningfulness of the learned representations encoded by a given model. As indicated in Table 3, our poisoning approach is highly effective, significantly boosting the attack success rate. However, during the poisoning process, as we maximize the loss on the target data points, the representations might become less meaningful than before. Consequently, this results in an approximate 3% decrease in accuracy after fine-tuning.
- Low-Rank Adaptation (LoRA). LoRA (Hu et al., 2021) is one of the most popular fine-tuning techniques right now for large language models. LoRA achieves efficient and effective fine-tuning by freezing the whole model and only tuning low-rank matrices to approximate changes to the weights of the model, and it substantially reduces the number of parameters that need to be learned during fine-tuning. However, due to the relatively minor changes made during LoRA fine-tuning, both baseline and poisoning attacks experience a decline in TPR@1%FPR and AUC. Despite this, LoRA can still enhance the baseline method's performance. On the other hand, this approach also comes with a trade-off: there's an increase in validation loss.
- Quantized Low-Rank Adaptation (QLoRA). As an extension of LoRA, QLoRA (Dettmers et al., 2023) enhances efficiency by combining low-precision training with LoRA. This approach significantly reduces memory usage during training. We present the results of QLoRA using 4-bit and 8-bit training in Table 3. Both the baseline and the poisoning method experience a decrease in attack success rate. However, similar to LoRA, this reduced privacy leakage is accompanied by a decrease in validation loss.
- Noisy Embeddings Improve Instruction Fine-tuning (Neftune). Jain et al. (2023) improve the fine-tuning of models by introducing random uniform noise into the word embeddings. This technique serves as a form of data augmentation, helping to prevent overfitting and, consequently, mitigating the model's tendency to memorize. As indicated in the last row of Table 3, Neftune slightly reduces the overall success rate of the attack in both the non-poisoned and poisoned scenarios. Nonetheless, even with Neftune, the poisoning attack maintains a reliable level of effectiveness.

Inf. Strategy	Attack	TPR@1%FPR	AUC		
4-bit	None Poison	$\begin{array}{c} 0.045_{\pm 0.011} \\ 0.150_{\pm 0.029} \end{array}$	$\begin{array}{c} 0.785_{\pm 0.009} \\ 0.879_{\pm 0.006} \end{array}$		
8-bit	None Poison	$\begin{array}{c} 0.049_{\pm 0.012} \\ 0.696_{\pm 0.021} \end{array}$	$\begin{array}{c} 0.849_{\pm 0.005} \\ 0.988_{\pm 0.001} \end{array}$		
Top-5 Prob	None Poison	$\begin{array}{c} 0.028_{\pm 0.002} \\ 0.448_{\pm 0.012} \end{array}$	$\begin{array}{c} 0.689_{\pm 0.006} \\ 0.971_{\pm 0.002} \end{array}$		
Watermark	None Poison	$\begin{array}{c} 0.048_{\pm 0.013} \\ 0.713_{\pm 0.053} \end{array}$	$\begin{array}{c} 0.838_{\pm 0.008} \\ 0.987_{\pm 0.001} \end{array}$		

Inference Strategies. Various inference strategies are employed to enhance the efficiency and security of models. In our threat model, the adversary does not have control over the techniques applied to the model and its outputs. Hence, we assess the effectiveness of our proposed poisoning attack against three contemporary inference strategies and report the results of these tests in Table 4:

- Quantization. Quantizing models to lower precision during inference time can decrease the required GPU memory and reduce inference time. We evaluate our attack with both 4-bit and 8-bit quantization. The results, as presented in the first two rows of Table 4, indicate that our poisoning approach continues to substantially enhance the baseline method. The 4-bit quantization seems to be somewhat effective in preventing privacy leakage. However, there is a notable increase in validation loss, from 3.19 to 3.58, suggesting a trade-off involved in this approach. This indicates that while quantization may offer some benefits for victim's privacy, it does not come as a free lunch.
- Top-5 Log Probabilities. To protect against privacy breaches and threats like model stealing, many language model platforms restrict the information provided through API calls (Morris et al., 2023). For instance, users are only able to access the top-5 log probabilities with OpenAI API calls, which may naturally defend against membership inference attacks. Our results indicate that even when adversaries are limited to just the top-5 log probabilities, our attack can still achieve a significant TPR@1%FPR, significantly outperforming the attack without poisoning. Meanwhile, it is noteworthy that users can potentially recover the full logits using a binary search-based algorithm that perturbs the logit bias (Morris et al., 2023).
- Watermark. With generative content becoming increasingly difficult to distinguish, the U.S. government has recently suggested the application of watermarks

Table 4. Attack under different inference strategies.



Figure 2. More ablation studies.

(The White House, 2023). In light of this development, we now test our poisoning attack on the watermarking method proposed by Kirchenbauer et al. (2023). To inject imperceptible watermarks, Kirchenbauer et al. (2023) develop a method for adjusting the logits of each token. Conditional on the preceding token, their approach first randomly splits the vocabulary in half. For one half of the vocabulary, they add a bias to the logits, while for the other half, they subtract a logit bias. As demonstrated in Table 4, there is a slight reduction in the attack performance due to the watermarking. However, the TPR@1%FPR for the poisoning attack remains significantly high, exceeding 70%, and the AUC is close to 0.99.

Results on Non-target Data Points. Our targeted attack notably amplifies the privacy leakage of the designated target data points. Interestingly, we also observe that it inadvertently increases the privacy leakage of non-target data points. Despite not explicitly optimizing these non-target data points, our attack achieves a TPR@1%FPR of 0.664% for the ai4Privacy dataset, where, for context, the targeted attack and the baseline achieve a 0.874% and 0.049% respectively. While there's a marginal reduction in effectiveness compared to the attack on target data points, it still represents a substantial improvement over the attack without poisoning, indicating a broader impact of the attack on overall model privacy.

Number of Fine-tuning Steps. The influence of the number of fine-tuning steps on the attack's performance is illustrated in Figure 2(a). We observe that as the number of fine-tuning steps decreases, the success rate of the attack also diminishes slightly. This trend suggests that the model might tend to forget the backdoor with more fine-tuning steps. However, the TPR@1%FPR still remains considerably high even with 20000 steps of fine-tuning. Number of Target Data Points. The graph in Figure 2(b) shows the effect of varying the number of target data points. Interestingly, there is a noticeable increase in the TPR@1%FPR as the number of target data points rises. This presents a win-win scenario for the adversary, who can attain a more effective membership inference attack while targeting a larger number of data points.

Pre-trained Model Stealthiness. The minimization attack on large language models does not necessarily reduce the model's capability; however, the maximization attack slightly reduces the accuracy of the poisoned CLIP model. To demonstrate how the stealthiness of the pre-trained model influences the attack success rate, we vary the hyperparameter α to obtain different pre-trained accuracies. As depicted in Figure 2(c), there is an inverse proportionality between model stealthiness and attack performance.

5. Conclusion

Today, developers tend to implicitly trust that foundation models available on model hubs like Hugging Face are benign and perform only the intended functionality. Backdoor attacks exploit this implicit trust. Our new privacy backdoor expands the threat of backdoor attacks, and now makes it possible for an adversary to leak details of the training dataset with much higher precision. Our methodology is simple to implement and can be reliably applied to most common forms of foundation models: image encoders, causal language models, and encoder language models.

Our work suggests yet another reason why practitioners may need to exercise caution with downloading and trusting pre-trained models. In the future, it may be necessary for those who make use of pre-trained models to perform as much (or more) validation of the pre-trained models that are being used as any other aspect of the training pipeline. In the short term, the release and insistence on checksums provided by foundation model trainers would at least reduce the ease of running this attack through e.g. modified reuploads of public models.

6. Impact Statement

While this paper introduces a new attack aimed at compromising the privacy of training datasets, our primary goal is to bring this potential vulnerability to public attention. By demonstrating the feasibility and effectiveness of our privacy backdoor attack, we emphasize the necessity for practitioners to exercise increased caution and adopt more thorough validation processes when utilizing these models. The security of a model should not be presumed safe based solely on its availability from a well-regarded source. We hope that our work will aid in the development of new tools and practices that ensure the security and privacy of models before they are integrated into the broader AI ecosystem.

Acknowledgement

Leo and Sanghyun are partially supported by the Google Faculty Research Award.

References

- ai4Privacy. pii-masking-200k (revision 1d4c0a1), 2023. URL https://huggingface.co/datasets/ ai4privacy/pii-masking-200k.
- Bentley, J. W., Gibney, D., Hoppenworth, G., and Jha, S. K. Quantifying membership inference vulnerability via generalization gap and other model metrics. *arXiv preprint arXiv:2009.05669*, 2020.
- Biderman, S., Schoelkopf, H., Anthony, Q. G., Bradley, H., O'Brien, K., Hallahan, E., Khan, M. A., Purohit, S., Prashanth, U. S., Raff, E., et al. Pythia: A suite for analyzing large language models across training and scaling. In *International Conference on Machine Learning*, pp. 2397–2430. PMLR, 2023.
- Black, S., Gao, L., Wang, P., Leahy, C., and Biderman, S. GPT-Neo: Large Scale Autoregressive Language Modeling with Mesh-Tensorflow, March 2021. URL https: //doi.org/10.5281/zenodo.5297715.
- Boenisch, F., Dziedzic, A., Schuster, R., Shamsabadi, A. S., Shumailov, I., and Papernot, N. When the curious abandon honesty: Federated learning is not private. In 2023 IEEE 8th European Symposium on Security and Privacy (EuroS&P), pp. 175–199, 2023. doi: 10.1109/EuroSP57164.2023.00020.
- Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D.,

Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33: 1877–1901, 2020.

- Carlini, N., Liu, C., Erlingsson, Ú., Kos, J., and Song, D. X. The secret sharer: Evaluating and testing unintended memorization in neural networks. In USENIX Security Symposium, 2018. URL https: //api.semanticscholar.org/CorpusID: 170076423.
- Carlini, N., Tramèr, F., Wallace, E., Jagielski, M., Herbert-Voss, A., Lee, K., Roberts, A., Brown, T., Song, D., Erlingsson, Ú., Oprea, A., and Raffel, C. Extracting training data from large language models. In 30th USENIX Security Symposium (USENIX Security 21), pp. 2633–2650. USENIX Association, August 2021. ISBN 978-1-939133-24-3. URL https://www.usenix. org/conference/usenixsecurity21/ presentation/carlini-extracting.
- Carlini, N., Chien, S., Nasr, M., Song, S., Terzis, A., and Tramer, F. Membership inference attacks from first principles. In 2022 IEEE Symposium on Security and Privacy (SP), pp. 1897–1914. IEEE, 2022.
- Carlini, N., Hayes, J., Nasr, M., Jagielski, M., Sehwag, V., Tramèr, F., Balle, B., Ippolito, D., and Wallace, E. Extracting training data from diffusion models. In 32nd USENIX Security Symposium (USENIX Security 23), pp. 5253–5270, Anaheim, CA, August 2023. USENIX Association. ISBN 978-1-939133-37-3. URL https://www.usenix.org/conference/usenixsecurity23/presentation/carlini.
- Chen, X., Liu, C., Li, B., Lu, K., and Song, D. Targeted backdoor attacks on deep learning systems using data poisoning. arXiv preprint arXiv:1712.05526, 2017.
- Cherti, M., Beaumont, R., Wightman, R., Wortsman, M., Ilharco, G., Gordon, C., Schuhmann, C., Schmidt, L., and Jitsev, J. Reproducible scaling laws for contrastive language-image learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2818–2829, 2023.
- Choquette-Choo, C. A., Tramer, F., Carlini, N., and Papernot, N. Label-only membership inference attacks. In *International conference on machine learning*, pp. 1964– 1974. PMLR, 2021.
- Dai, D., Dong, L., Hao, Y., Sui, Z., Chang, B., and Wei, F. Knowledge neurons in pretrained transformers. In Muresan, S., Nakov, P., and Villavicencio, A. (eds.), Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers),

pp. 8493–8502, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022. acl-long.581. URL https://aclanthology.org/ 2022.acl-long.581.

- Debenedetti, E., Severi, G., Carlini, N., Choquette-Choo, C. A., Jagielski, M., Nasr, M., Wallace, E., and Tramèr, F. Privacy side channels in machine learning systems. *arXiv* preprint arXiv:2309.05610, 2023.
- Deng, J., Dong, W., Socher, R., Li, L.-J., Li, K., and Fei-Fei, L. Imagenet: A large-scale hierarchical image database. In 2009 IEEE conference on computer vision and pattern recognition, pp. 248–255. Ieee, 2009.
- Dettmers, T., Pagnoni, A., Holtzman, A., and Zettlemoyer, L. Qlora: Efficient finetuning of quantized llms. ArXiv, abs/2305.14314, 2023. URL https: //api.semanticscholar.org/CorpusID: 258841328.
- Duan, J., Kong, F., Wang, S., Shi, X., and Xu, K. Are diffusion models vulnerable to membership inference attacks? In Krause, A., Brunskill, E., Cho, K., Engelhardt, B., Sabato, S., and Scarlett, J. (eds.), Proceedings of the 40th International Conference on Machine Learning, volume 202 of Proceedings of Machine Learning Research, pp. 8717–8730. PMLR, 23–29 Jul 2023. URL https://proceedings.mlr.press/ v202/duan23b.html.
- Feng, S. and Tramèr, F. Privacy backdoors: Stealing data with corrupted pretrained models. 2024.
- Fowl, L. H., Geiping, J., Czaja, W., Goldblum, M., and Goldstein, T. Robbing the fed: Directly obtaining private data in federated learning with modified models. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum? id=fwzUgo0FM9v.
- Fowl, L. H., Geiping, J., Reich, S., Wen, Y., Czaja, W., Goldblum, M., and Goldstein, T. Decepticons: Corrupted transformers breach privacy in federated learning for language models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https: //openreview.net/forum?id=r0BrY4BiEXO.
- Frey, S. Introducing Android's Private Compute Services, September 2021. URL https: //security.googleblog.com/2021/09/ introducing-androids-private-compute. html.
- Geiping, J., Bauermeister, H., Dröge, H., and Moeller, M. Inverting gradients - how easy is it to break privacy in federated learning? In Larochelle, H.,

Ranzato, M., Hadsell, R., Balcan, M., and Lin, H. (eds.), Advances in Neural Information Processing Systems, volume 33, pp. 16937–16947. Curran Associates, Inc., 2020. URL https://proceedings.neurips. cc/paper_files/paper/2020/file/ c4ede56bbd98819ae6112b20ac6bf145-Paper. pdf.

- Gu, T., Dolan-Gavitt, B., and Garg, S. Badnets: Identifying vulnerabilities in the machine learning model supply chain. *arXiv preprint arXiv:1708.06733*, 2017.
- Hong, S., Carlini, N., and Kurakin, A. Handcrafted backdoors in deep neural networks. In Koyejo, S., Mohamed, S., Agarwal, A., Belgrave, D., Cho, K., and Oh, A. (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 8068–8080. Curran Associates, Inc., 2022. URL https://proceedings.neurips. cc/paper_files/paper/2022/file/ 3538a22cd3ceb8f009cc62b9e535c29f-Paper-Conference pdf.
- Hu, E. J., Shen, Y., Wallis, P., Allen-Zhu, Z., Li, Y., Wang, S., Wang, L., and Chen, W. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.
- Hubinger, E., Denison, C., Mu, J., Lambert, M., Tong, M., MacDiarmid, M., Lanham, T., Ziegler, D. M., Maxwell, T., Cheng, N., et al. Sleeper agents: Training deceptive llms that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.
- Jain, N., Chiang, P.-y., Wen, Y., Kirchenbauer, J., Chu, H.-M., Somepalli, G., Bartoldson, B. R., Kailkhura, B., Schwarzschild, A., Saha, A., et al. Neftune: Noisy embeddings improve instruction finetuning. *arXiv preprint arXiv:2310.05914*, 2023.
- Johnson, A. E., Pollard, T. J., Shen, L., Lehman, L.-w. H., Feng, M., Ghassemi, M., Moody, B., Szolovits, P., Anthony Celi, L., and Mark, R. G. Mimic-iii, a freely accessible critical care database. *Scientific data*, 3(1):1–9, 2016.
- Johnson, A. E., Bulgarelli, L., Shen, L., Gayles, A., Shammout, A., Horng, S., Pollard, T. J., Hao, S., Moody, B., Gow, B., et al. Mimic-iv, a freely accessible electronic health record dataset. *Scientific data*, 10(1):1, 2023.
- Kirchenbauer, J., Geiping, J., Wen, Y., Katz, J., Miers, I., and Goldstein, T. A watermark for large language models. In *International Conference on Machine Learning*, 2023. URL https://api.semanticscholar. org/CorpusID:256194179.

- Krizhevsky, A. and Hinton, G. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.
- Loshchilov, I. and Hutter, F. Decoupled weight decay regularization. arXiv preprint arXiv:1711.05101, 2017.
- Mazeika, M., Zou, A., Arora, A., Pleskov, P., Song, D., Hendrycks, D., Li, B., and Forsyth, D. How hard is trojan detection in DNNs? fooling detectors with evasive trojans, 2023. URL https://openreview.net/ forum?id=V-RDBWYf0go.
- McMahan, B., Moore, E., Ramage, D., Hampson, S., and y Arcas, B. A. Communication-efficient learning of deep networks from decentralized data. In Artificial intelligence and statistics, pp. 1273–1282. PMLR, 2017.
- Merity, S., Keskar, N. S., and Socher, R. Regularizing and optimizing lstm language models. ArXiv, abs/1708.02182, 2017. URL https://api.semanticscholar. org/CorpusID:212756.
- Morris, J. X., Zhao, W., Chiu, J. T., Shmatikov, V., and Rush, A. M. Language model inversion. arXiv preprint arXiv:2311.13647, 2023.
- Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., Sutskever, I., et al. Language models are unsupervised multitask learners. OpenAI blog, 1(8):9, 2019.
- Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A., Mishkin, P., Clark, J., et al. Learning transferable visual models from natural language supervision. In International conference on machine learning, pp. 8748-8763. PMLR, 2021.
- Sablayrolles, A., Douze, M., Schmid, C., Ollivier, Y., and Jégou, H. White-box vs black-box: Bayes optimal strategies for membership inference. In International Conference on Machine Learning, pp. 5558–5567. PMLR, 2019.
- Shokri, R., Stronati, M., Song, C., and Shmatikov, V. Membership inference attacks against machine learning models. In 2017 IEEE symposium on security and privacy (SP), pp. 3–18. IEEE, 2017.
- The White House. Fact sheet: President biden issues executive order on safe, secure, and trustworthy artificial intelligence, 10 2023. URL https: //www.whitehouse.gov/briefing-room/ statements-releases/2023/10/30/ fact-sheet-president-biden-issues-executive-order-on-safe-secure-and-trustworthy-artificial

Poisoning machine learning models to reveal their secrets. Proceedings of the 2022 ACM SIGSAC Conference on Computer and Communications Security, 2022. URL https://api.semanticscholar. org/CorpusID:247922814.

- Wang, G., Liu, X., Ying, Z., Yang, G., Chen, Z., Liu, Z., Zhang, M., Yan, H., Lu, Y., Gao, Y., et al. Optimized glycemic control of type 2 diabetes with reinforcement learning: a proof-of-concept trial. Nature Medicine, 29 (10):2633-2642, 2023.
- Wen, Y., Geiping, J. A., Fowl, L., Goldblum, M., and Goldstein, T. Fishing for user data in large-batch federated learning via gradient magnification. In Chaudhuri, K., Jegelka, S., Song, L., Szepesvari, C., Niu, G., and Sabato, S. (eds.), Proceedings of the 39th International Conference on Machine Learning, volume 162 of Proceedings of Machine Learning Research, pp. 23668–23684. PMLR, 17-23 Jul 2022. URL https://proceedings.mlr. press/v162/wen22a.html.
- Wen, Y., Bansal, A., Kazemi, H., Borgnia, E., Goldblum, M., Geiping, J., and Goldstein, T. Canary in a coalmine: Better membership inference with ensembled adversarial queries. In The Eleventh International Conference on Learning Representations, 2023. URL https: //openreview.net/forum?id=b7SBTEBFnC.
- Wortsman, M., Ilharco, G., Kim, J. W., Li, M., Kornblith, S., Roelofs, R., Lopes, R. G., Hajishirzi, H., Farhadi, A., Namkoong, H., et al. Robust fine-tuning of zero-shot models. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 7959-7971, 2022.
- Yeom, S., Giacomelli, I., Fredrikson, M., and Jha, S. Privacy risk in machine learning: Analyzing the connection to overfitting. In 2018 IEEE 31st computer security foundations symposium (CSF), pp. 268–282. IEEE, 2018.
- Yin, H., Mallya, A., Vahdat, A., Alvarez, J. M., Kautz, J., and Molchanov, P. See through gradients: Image batch recovery via gradinversion. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 16337–16346, June 2021.
- Zhang, S., Roller, S., Goyal, N., Artetxe, M., Chen, M., Chen, S., Dewan, C., Diab, M., Li, X., Lin, X. V., et al. Opt: Open pre-trained transformer language models. arXiv preprint arXiv:2205.01068, 2022.
- Tramèr, F., Shokri, R., Joaquin, A. S., Le, H. M., Jagielski, M., Hong, S., and Carlini, N. Truth serum:

A. Different, Yet Ineffective MIA Strategies

Here, we additionally show different attack strategies for membership inference in the same fine-tuning scenarios. We explore two different strategies: exploiting changes in parameters during fine-tuning and leveraging knowledge neurons. These approaches show some effectiveness in limited settings while they are not practical when the fine-tuning process is completely controlled by the victim. We present our trials for future studies.

A.1. Exploiting Model Parameters

We test if an adversary can exploit model parameters to identify the membership of data records in the fine-tuning dataset. We hypothesize that there is a certain parameter in a pre-trained model that entails a large change in its value after fine-tuning with the target data point; the parameter will not change when the target data point is not in the fine-tuning dataset.

Methodology. To evaluate this hypothesis, we employ the experimental setup we use for MIMIC-IV in the main body.

Our adversary first profiles the threshold for identifying the large change in parameter values. We fine-tune 16 ClinicalBERT models on 16 different data records, a single record for each fine-tuning, and compute the relative parameter changes. We only consider the magnitude of changes. We then calculate the threshold by averaging them out over 16 runs.

We then examine the existence of *membership-leaking* parameters. We make two fine-tuned models: one with a single secret record (e.g., "John Doe has elastoderma"), and the other with any reference data point (e.g., "John Doe has yaws"). For each model, we collect locations with changes in the parameter values larger than the threshold. We then identify unique locations that entail larger changes only when the secret data is. We ran this procedure 8 times with different random seeds.

Results. In each run of our attacks, we identify ~ 200 membership-leaking parameters. However, when we compare these 200 parameter locations across 8 different runs, we could not find any consistent overlap between them. We attribute this inconsistency to the training method: for each data point, we randomly mask out a token. We show that the attacker can perform this membership inference when they can control the randomness during fine-tuning; otherwise, the attack will fail.

A.2. MIA Exploiting Knowledge Neurons

We next test if an adversary can exploit specific neuron activations in a pre-trained model to infer the membership of a target data point in the fine-tuning dataset. Here we focus on the knowledge neurons (Dai et al., 2022). A record can be represented as $\langle i, r, s \rangle$ where *i* is the identifier like names, *r* is the relation, and *s* is the secret of our interest. These neurons encode the relation *r* between two entities. In MIMIC-IV, examples include "hx [history] of", "tx [treatment] for", "dx [diagnosis] of", or "in MCIU with". Our attack strategy is to control (specifically, to increase) these knowledge neuron activations in a pre-trained model to increase the memorization of a secret during fine-tuning.

Methodology. We evaluate this attack strategy on the same experimental setup as in Appendix A.1.

The first step is to identify knowledge neurons in a pre-trained model. In our setting, we create a template '[X] has the disease [Y]' with the relation 'has the disease.' We then identify between 5-15 different naturally occurring variations of the relation (in the case of ClinicalBERT, any relation that could connect a patient to a particular ailment).

Using these data records, we apply the knowledge neuron-finding algorithm proposed by the original study. This is done for each prompt template with a unique combination of predicate and subject (\sim 400 combinations total), or dummy identifier and secret ("[X] has [Y]." \rightarrow "John Smith has dementia."). This yields a set of coarse knowledge neurons defined only by having a significant gradient associated with the prompt above a threshold. We then apply a refining algorithm that aims to identify overlapping coarse knowledge neurons both within a particular predicate-subject combination and between different predicate-subject pairs. This algorithm yields between 5 and 10 fine-knowledge neurons.

The second step is to amplify the activation of knowledge neurons. We follow the procedure outlined by the prior work (Hong et al., 2022). We multiply the GELU(X) activation in the target FFN layer for the target neuron by an integer value in [1, 20] as a proof-of-concept. We achieve this by multiplying weights connected to a specific neuron we examine.

We finally create two models: one fine-tuned on the MIMIC-IV dataset with the target data point, and the other without the target. We then measure the exposure proposed by (Carlini et al., 2018) and compare the two exposure values.

Results. We insert the target data points $\{1, 2, 5, 10, 25, 50, 100\}$ times. We run our attacks with 128 different target data points and 10 different templates. 9k attacks in total. We find that the knowledge neurons are ineffective as a backdooring

method. We observe in some cases, the exposure on average increases from one to 6 as we increase the activation of knowledge neurons, while in other cases, the exposure remains consistent. We leave the further investigation for future work.