# Coded Downlink Massive Random Access and a Finite de Finetti Theorem

Ryan Song, Graduate Student Member, IEEE, Kareem M. Attiah, Graduate Student Member, IEEE, and Wei Yu, Fellow, IEEE

Abstract—This paper considers a massive connectivity setting in which a base-station (BS) aims to communicate sources  $(X_1, \dots, X_k)$  to a randomly activated subset of k users, among a large pool of n users, via a common downlink message. Although the identities of the k active users are assumed to be known at the BS, each active user only knows whether itself is active and does not know the identities of the other active users. A naive coding strategy is to transmit the sources alongside the identities of the users for which the source information is intended, which would require  $H(X_1, \dots, X_k) + k \log(n)$  bits, because the cost of specifying the identity of a user is log(n) bits. For large n, this overhead can be significant. This paper shows that it is possible to develop coding techniques that eliminate the dependency of the overhead on n, if the source distribution follows certain symmetry. Specifically, if the source distribution is independent and identically distributed (i.i.d.) then the overhead can be reduced to at most  $O(\log(k))$  bits, and in case of uniform i.i.d. sources, the overhead can be further reduced to O(1) bits. For sources that follow a more general exchangeable distribution, the overhead is at most O(k) bits, and in case of finite-alphabet exchangeable sources, the overhead can be further reduced to  $O(\log(k))$  bits. The downlink massive random access problem is closely connected to the study of finite exchangeable sequences. The proposed coding strategy allows bounds on the relative entropy distance between finite exchangeable distributions and i.i.d. mixture distributions to be developed, and gives a new relative entropy version of the finite de Finetti theorem which is scaling optimal.

Index Terms—Massive random access, finite de Finetti theorem, exchangeable distribution

#### I. INTRODUCTION

#### A. Problem Setting

This paper considers the problem of information transmission from a central base-station (BS) to a random subset of k users in a downlink massive random access scenario with a large pool of n users. The users are assumed to be sporadically activated, so that at any given time, only  $k \ll n$  users are actively listening to the BS. The BS knows the identities of the active users and wishes to communicate sources  $(X_1, \dots, X_k)$ to these active users via a common downlink message; but each user only knows whether it is active itself and does not know which other users are active. We ask the question: What is the minimum rate of downlink common message that allows each active user i to learn the source  $X_i$  intended for it?

The aforementioned source coding problem, which we refer to as the *coded downlink massive random access* problem, arises naturally in the context of machine-type communications or Internet-of-Things (IoT), particularly in scenarios where the users are randomly activated and the BS needs to send information (such as the acknowledgement or control messages) to the active users in the downlink [3], [4]. A typical communications protocol in this context consists of two phases. In the first phase, the active users transmit pilots to the BS, which performs activity detection to learn the identities of the active users. In the second phase of the protocol, the BS transmits the information sources to each of the active users via a common downlink broadcast message. This paper is concerned with the fundamental limit of communications in the second phase.

The information sources intended for the set of active users are not necessarily independent (e.g., there may be a cap on the maximum number of users that can be positively acknowledged, or the message may convey the assignment of non-colliding scheduling slots to the active users), but the source distribution typically follows certain symmetry. In this paper, we assume that the user activity patterns are random and symmetric across the pool of all potential users, i.e., no subset of users is preferred over any other subset. Moreover, we assume that the distribution of the information sources intended for the active users is independent of the user activity pattern; further, the source distribution follows a symmetry captured by the notion of exchangeability.

Formally,  $(X_1, \dots, X_k)$  is *exchangeable* if its distribution  $p(x_1, \dots, x_k)$  is invariant under permutations, i.e. for any bijection  $\sigma$  from  $\{1, 2, \dots, k\}$  to itself, we have

$$p(x_1, \cdots, x_k) = p(x_{\sigma(1)}, \cdots, x_{\sigma(k)}). \tag{1}$$

Classical examples of exchangeable distributions include independently and identically distributed (i.i.d.) random variables, i.i.d. mixture random variables, and the urn distributions (i.e., sampling with or without replacement from a population).

Throughout this paper, the total number of potential users n is assumed to be known and fixed. We begin the exposition by assuming that the number of active users k is also fixed, then relax this assumption for i.i.d. sources and treat the case of random k in a later section.

The downlink massive random access problem would have been trivial if every active user knew the identities of the

Manuscript submitted to *IEEE Transactions on Information Theory* on May 15, 2024. The authors are with The Edward S. Rogers Sr. Department of Electrical and Computer Engineering, University of Toronto, Canada. (E-mails: r.song@mail.utoronto.ca, kattiah@ece.utoronto.ca, weiyu@ece.utoronto.ca.) This work was presented in part at *IEEE International Symposium on Information Theory*, June 2022, Helsinki, Finland [1] and in part at *IEEE International Symposium on Information Theory*, July 2023, Taipei, Taiwan [2]. This work was supported by the Natural Sciences and Engineering Research Council (NSERC) of Canada via a Discovery Grant and a Post-Graduate Scholarship.

entire subset of active users. In this case, the n users can each be pre-assigned an index. The BS can then list the source information for the k active users according to the order in which they appear in the index. Such a common message requires only  $H(X_1, \dots, X_k)$  bits, but relies on each user knowing the identities of all active users.

The problem becomes much more interesting under the practical scenario in which every active user only knows whether it is active itself and does not know who else is active. In this case, it would appear that the BS needs to send not only  $H(X_1, \dots, X_k)$  bits for the source, but also a header of  $\log(n)$  bits per active user to describe which user the source is intended for, thus resulting in a  $k \log(n)$  bit overhead. Such an overhead can be significant if n is large (e.g.,  $n = 10^6$  with  $k = 10^3$  would require  $k \log(n) \approx 20$  kbs), especially when the payload for each user is small in comparison. The main insight of this paper is that if the source is exchangeable, it is possible to do much better. In fact, it is possible to develop a coded downlink massive random access strategy at common message rates that do not depend on n.

The intuition that makes this possible is that the naive scheme broadcasts too much redundant information. Specifically, each active user needs to recover only its own designated source, and does not care which other users are active, or the information intended for the other users. The naive scheme broadcasts the source information intended for everyone to everyone else. In contrast, the coding strategy developed in this paper reduces the common message rate by taking advantage of the fact that each of the k active users is only interested in the source pertaining to itself, so that each codeword can cover many different instances of the activity patterns and the associated sources.

This paper proposes a coding strategy using a codebook comprised of length-n codewords of different possible realizations of the sources. Each of the n users has a corresponding unique location in the codewords, so that when the identities of the k activity users and their associated sources are revealed, the BS only needs to search over the codebook and broadcast the index of the first codeword that *matches* the actual sources intended for the k active users to allow them to recover their respective source information.

The main result of this paper is that when the source is distributed according to an exchangeable distribution, it is possible to design such a codebook so that the entropy of the matching index is close to  $H(X_1, \dots, X_k)$  with an overhead independent of n.

This paper further points out that the problem of constructing a good codebook for an exchangeable source is closely related to the de Finetti theorem and the study of finite exchangeable sequences. This connection arises due to the fact that the codebook construction needs to be symmetric across all subsets of users. Therefore, the distribution used for codebook construction is restricted to be an i.i.d. mixture. The source however can be any exchangeable distribution. Therefore, the problem of constructing a good codebook for an exchangeable source reduces to finding an i.i.d. mixture distribution that is close to an exchangeable distribution in terms of relative entropy. In this paper, we propose a codebook construction method for exchangeable sources and utilize it to prove a relative entropy version of the finite de Finetti theorem that matches the optimal scaling of the classical result [5].

## B. Prior Work

The study of coded downlink for specific sources has been investigated in previous works [6] and [1], where the problem of scheduling active users into non-colliding transmission slots and the problem of assigning active users into categories of fixed sizes are considered respectively. The analyses of code rates in [6], [1] are specific to their respective problems and do not immediately generalize to other source distributions, and in particular do not apply to i.i.d. distributions. In contrast, this paper utilizes new coding techniques to provide results for exchangeable sources in general. Note that both [6] and [1] are examples of exchangeable sources.

It is worth noting that the scheduling code from [6] in conjunction with usual source coding already allow a coding strategy for exchangeable sources at common message rates independent of n. The idea is that we can first schedule the kactive users into k distinct slots using at most  $(k+1)\log(e)$ bits using the strategy in [6], then list the sources information in the order of the slot assignments, so that each active user can receive its correct information. Since the source is exchangeable, the distribution is not affected by the reordering. Therefore a rate of  $H(X_1, \dots, X_k) + (k+1)\log(e)$  bits is achievable. This strategy achieves the same O(k) overhead as the coding scheme proposed in this paper for general exchangeable sources, but in many cases, the O(k) overhead can be improved. For example, if the source is i.i.d. or i.i.d. mixture, the coding strategy proposed in this paper achieves an overhead of  $O(\log(k))$  bits.

Finite de Finetti theorems have a long history [5], [7], [8]. Let  $(X_1, \dots, X_k)$  be an exchangeable sequence with distribution  $p(\mathbf{x})$  which takes values in  $\mathcal{X}^k$  and let  $\mathcal{Q}$  be the set of all i.i.d. mixture distributions on  $\mathcal{X}^k$ . We say that the source is *d*-extendable if it has the same distribution as the first k elements of a longer exchangeable sequence  $(X_1, \dots, X_k, \dots, X_d)$ . The classical result of [5] is that

$$\min_{q \in \mathcal{Q}} \mathrm{TV}(p,q) \le \min\left\{\frac{2|\mathcal{X}|k}{d}, \frac{k(k-1)}{d}\right\}, \qquad (2)$$

where  $\operatorname{TV}(p,q) = 2 \sup_{\mathcal{X}^k} |p(\mathbf{x}) - q(\mathbf{x})|$  is the total variation distance. Therefore for any fixed k, the total variation distance tends to 0 as  $d \to \infty$ . In fact, the total variation can go to 0 even if  $k, d \to \infty$ , as long as  $\frac{k}{d} \to 0$  for finite  $|\mathcal{X}|$ , or  $\frac{k^2}{d} \to 0$ . It is shown in [5] that this scaling is essentially optimal.

Recently, there has been a renewed interest in finding similar bounds as (2) but in terms of relative entropy. In particular, [9]–[11] use information-theoretic tools to establish various upper bounds, the strongest of which appears in [11] and shows that

$$\min_{q \in \mathcal{Q}} D(p \| q) \le \frac{k(k-1)}{2(d-k-1)} \log |\mathcal{X}|.$$
(3)

However, this result holds only in the finite alphabet setting and has a suboptimal scaling compared to (2). This paper aims to close this gap by proving upper bounds in terms of the relative entropy that match the optimal scaling in (2).

## C. Main Contributions

The main technical results of the paper are as follows:

1) Coding for Downlink Massive Random Access: For transmitting an exchangeable source  $\mathbf{X} = (X_1, \dots, X_k) \sim p(\mathbf{x})$  to a random subset of k active users in a downlink massive random access scenario with n total users, we show that a common message rate of

$$\min_{q \in \mathcal{Q}} H(\mathbf{X}) + D(p \| q) + \log(H(\mathbf{X}) + D(p \| q) + 1) + 1 \quad (4)$$

bits is achievable, where Q is the family of i.i.d. mixture distributions on  $\mathcal{X}^k$  and  $D(\cdot \| \cdot)$  is the Kullback-Leibler (KL) divergence.

In the case that the source is i.i.d. or i.i.d. mixture, we can set q = p to eliminate the D(p||q) term. Specifically, for i.i.d. sources, an achievable rate is  $kH(X_1) + \log(kH(X_1)+1) + 1$ , thus the overhead is at most  $O(\log(k))$  bits. The overhead can be reduced to O(1) if the source is uniform over its support.

For general exchangeable sources that are not i.i.d. or i.i.d. mixture, we show that

$$\min_{q \in \mathcal{Q}} D(p \| q) \le \min\{k \log(e), |\mathcal{X}| \log(k+1)\}.$$
 (5)

thus achieving an overhead of at most O(k) bits in general and  $O(\log(k))$  bits if the source has a finite alphabet. In all cases, the achievable common message rate is close to  $H(\mathbf{X})$ bits with an overhead that does not depend on n.

2) Extendable Sources and Finite de Finetti Theorem: The upper bound (5) can be improved if  $\mathbf{X} \sim p(\mathbf{x})$  is *d*-extendable. In this case, we show that

$$\min_{q \in \mathcal{Q}} D(p \| q) \le \min\left\{ (|\mathcal{X}| - 1) \log\left(\frac{d - 1}{d - k}\right), -\log\left(1 - \frac{k(k - 1)}{2d}\right) \right\}.$$
 (6)

This result is a statement of the finite de Finetti theorem in terms of relative entropy. In particular, for any fixed k, the relative entropy between the distribution  $p(\mathbf{x})$  and the nearest i.i.d. mixture distribution goes to 0 as  $d \to \infty$ . In fact, the scaling in (6) matches the optimal scaling of (2), because the upper bound goes to 0 as  $k, d \to \infty$ , as long as  $\frac{k^2}{d} \to 0$ , or for the finite alphabet case,  $\frac{k}{d} \to 0$ .

# D. Paper Organization and Notation

The remainder of the paper is organized as follows. Section II states the problem of coded downlink massive random access and develops the achievability results. The improved finite de Finetti theorem is stated and proved in Section III. Conclusions are drawn in Section IV.

Throughout this paper, we use lowercase letters to denote scalars, lowercase boldface letters to denote vectors, capital letters to denote random variables, boldface capital letters to denote random vectors, and calligraphic letters, i.e. S, to denote sets, |S| to denote their cardinality, and  $\mathbb{1}_S$  as the indicator function. We let  $\log(\cdot)$  denote the base 2 logarithm and  $\ln(\cdot)$  denote the natural logarithm. All information measures are expressed in bits, including entropy  $H(\cdot)$  and the relative entropy or KL divergence  $D(\cdot || \cdot)$ . We use the short-hands notations  $[n] = \{1, \ldots, n\}$  and  $a^{\underline{b}} = a(a-1)\cdots(a-b+1)$ .

# II. CODING FOR DOWNLINK MASSIVE RANDOM ACCESS

# A. Problem Formulation

Consider a massive random access setting in which a random subset of k users becomes active among a total number of n users. The value of n is fixed and known. For now, k is also assumed to be fixed and known. The identities of the active users are known to the BS. However, each user only knows whether itself is active, but it does not know which other users are active. We are interested in the setting in which the BS wishes to communicate a source to each of the k active users simultaneously using a common broadcast message. This common message is assumed to be received by all users without error.

In this paper, we consider the class of source distributions that are exchangeable. Let  $\mathbf{X} = (X_1, \dots, X_k)$  be a sequence of exchangeable random variables taking values in a discrete alphabet  $\mathcal{X}$ . Let  $p(\mathbf{x}) = p(x_1, \dots, x_k)$  be their joint distribution. Each user *i* is interested in learning  $X_i$  based on the common message (but not interested in any of other  $X_i$ 's).

The following are some common applications in which exchangeable distributions may arise:

- 1) The BS wishes to communicate i.i.d.  $X_i \sim p(x)$ .
- The k active users need to be assigned into b slots, where b ≥ k, in a non-colliding fashion, i.e., subject to the constraint that no two users can be assigned to the same slot. This is known as scheduling. Fixing a particular schedule, the BS wishes to communicate to each user which slot it is being assigned to.
- The k active users need to be categorized into c categories, but each category must have a fixed number of k<sub>ℓ</sub> users, ∀ℓ ∈ [c], ∑<sub>ℓ=1</sub><sup>c</sup> k<sub>ℓ</sub> = k. The BS wishes to communicate the category labels X<sub>i</sub> ∈ [c] to each user. For the case of two categories (c = 2), this is known as the acknowledgement problem.
- 4) A fixed number of resources r need to be distributed amongst the k active users, i.e., ∑<sub>i=1</sub><sup>k</sup> X<sub>i</sub> = r, where X<sub>i</sub> ≥ 0 is an integer. The BS wishes to communicate to each user how many units of resources it has been assigned. This is known as the resource allocation problem.

Let the random variable  $\mathbf{A} \in \mathcal{A}^{(n,k)}$  denote the identities of the k active users, where

$$\mathcal{A}^{(n,k)} = \{ \mathbf{a} \in [n]^k \mid a_i \neq a_j, \forall i \neq j \}.$$
(7)

Here,  $a_i \in [n]$  is the index of the *i*th active user. While the source **X** describes the contents of the messages, the activity pattern **A** indicates which users should receive which message, i.e., we want each user  $a_i$  to receive  $x_i \forall i \in [k]$ . Together, they form a message-activity tuple (**X**, **A**). Throughout this paper, we assume that **X** and **A** are independent. Notationally, we use (**x**, **a**) to represent a realization of (**X**, **A**).

The problem of communicating the sources  $\mathbf{X}$  to the active users in  $\mathbf{A}$  can now be thought of as a one-shot source coding problem consisting of a single encoder and multiple decoders. In this paper, we pursue the following two-stage strategy for encoding. In the first stage, the BS uses encoder f to map a message-activity pair ( $\mathbf{x}, \mathbf{a}$ ) to a natural number, i.e.,

$$f: \mathcal{X}^k \times \mathcal{A}^{(n,k)} \to \mathbb{N}.$$
 (8)

In the second stage, entropy coding is used to compress  $f(\mathbf{x}, \mathbf{a})$  into a variable-length codeword which is then broadcast to all active users.

On the decoding side, assuming error-free broadcasting of the common message, each active user  $a_i$  first recovers  $f(\mathbf{x}, \mathbf{a})$ . It then uses its own decoder  $d_{a_i} : \mathbb{N} \to \mathcal{X}$  to recover the intended message. We require lossless recovery:

$$d_{a_i}(f(\mathbf{x}, \mathbf{a})) = x_i, \quad \forall (\mathbf{x}, \mathbf{a}) \in \mathcal{X}^k \times \mathcal{A}^{(n,k)}, \ \forall i \in [k], \quad (9)$$

i.e. each user receives its intended source without error.

The rate of the encoding and decoding scheme is defined as  $R = H(f(\mathbf{X}, \mathbf{A}))$ , where  $H(\cdot)$  is the entropy function, justified by the fact that entropy coding can be used to achieve the rate R to within one bit.

The optimal encoding and decoding scheme is defined to be the encoder and decoders that minimize  $H(f(\mathbf{X}, \mathbf{A}))$ , while satisfying the condition (9). The optimal common message rate is defined as

$$R^* \triangleq H\left(f^*(\mathbf{X}, \mathbf{A})\right),\tag{10}$$

where  $f^*(\mathbf{X}, \mathbf{A})$  is the optimal encoder.

### B. Codebook Construction

We propose the following encoding and decoding scheme inspired by previous work [6] [1] for coded downlink massive random access. This encoding and decoding scheme utilizes a shared codebook between the BS and all the users

$$\mathbf{m} = (\mathbf{c}^{(1)}, \mathbf{c}^{(2)}, \cdots) \tag{11}$$

which consists of an infinite sequence of length-*n* vectors  $\mathbf{c}^{(t)} \in \mathcal{X}^n$ . We assign a unique entry location in the codewords to each of the *n* users. For a particular message-activity tuple  $(\mathbf{x}, \mathbf{a})$ , the BS encodes  $(\mathbf{x}, \mathbf{a})$  by finding a codeword  $\mathbf{c}^{(t)}$  such that every active user has the correct message in their designated entry in  $\mathbf{c}^{(t)}$ , i.e.,

$$c_{a_i}^{(t)} = x_i, \qquad \forall i \in [k]. \tag{12}$$

Since the codebook is of infinite size and  $\mathcal{X}$  is a discrete alphabet, such a codeword always exists. The idea is to encode  $(\mathbf{x}, \mathbf{a})$  as the index of the *first* such codeword in the codebook. Mathematically, the proposed encoder can be written as

$$f_{\mathbf{m}}(\mathbf{x}, \mathbf{a}) = \min \quad t$$
(13)  
s.t.  $c_{a_i}^{(t)} = x_i, \quad \forall i \in [k].$ 

The decoders for each user  $u \in [n]$  are defined as:

$$d_u(t) = c_u^{(t)}.$$
 (14)

One can easily verify that this encoding and decoding scheme satisfies the condition (9).

It remains to discuss how to generate the codewords in m. Similar to [1], we use a random codebook construction in which the codewords are generated independently according to a mixture of i.i.d. distributions. Specifically, fix a distribution  $r(\theta)$  and a conditional distribution  $q(\mathbf{x}|\theta)$ . Each length-*n* codeword  $\mathbf{c}^{(t)} = [x_1, \cdots, x_n]^{\top}$  is generated according to

$$q(x_1, \cdots x_n) = \int_{\theta} r(\theta) \left[ \prod_{i=1}^n q(x_i|\theta) \right] d\theta.$$
 (15)

Operationally, each codeword can be thought of as being generated in a two-step process of first choosing a  $\theta$  according to  $r(\theta)$ , then generating the entries of the codeword in an i.i.d. fashion according to  $q(\mathbf{x}|\theta)$ . Each subsequent codeword is generated independently in the same way. Once the entire codebook is generated, it is shared with the BS and all users.

With this random codebook construction, the distribution of any k distinct entries of a single codeword is

$$q(x_1, \cdots x_k) = \int_{\theta} r(\theta) \left[ \prod_{i=1}^k q(x_i | \theta) \right] d\theta.$$
 (16)

This means that the distribution of any k distinct entries of the codewords are identical, which is a desired property for encoding exchangeable sources. Further, this distribution can be specifically designed according to any i.i.d. mixture.

This paper focuses attention to the encoding and decoding functions and random codebooks generated in this way. Our main result is that for any exchangeable source distribution  $p(x_1, \dots, x_k)$ , we can choose an appropriate i.i.d. mixture distribution  $q(\mathbf{x}|\theta)r(\theta)$ , such that among an ensemble of codebooks randomly generated according to (15), there exists a codebook  $\mathbf{m}^*$  that has an encoder output entropy  $H(f_{\mathbf{m}^*}(\mathbf{X}, \mathbf{A}))$  upper bounded by  $H(X_1, \dots, X_k)$  plus a small overhead term.

# C. Achievable Rates

In this section, we provide upper bounds on the optimal rate  $R^*$  of the downlink message for massive random access by analyzing the entropy of the output of the encoder when

- The source  $\mathbf{X} = (X_1, \dots, X_k)$  is distributed according to an exchangeable source distribution  $p(x_1, \dots, x_k)$ ;
- The codebook is generated according to i.i.d. mixture distribution  $q(\mathbf{x}|\theta)r(\theta)$ .

Theorem 1: Consider a massive random access scenario with a total of n users and a random subset of k active users. Let sources  $\mathbf{X} = (X_1, \dots, X_k)$  take values in a discrete set  $\mathcal{X}^k$ with exchangeable distribution  $p(\mathbf{x})$ . The minimum common message rate  $R^*$  is bounded above as

$$R^* \le \min_{q \in \mathcal{Q}} H(\mathbf{X}) + D(p||q) + \log(H(\mathbf{X}) + D(p||q) + 1) + 1$$
(17)

where Q is the family of all i.i.d. mixture distributions on  $\mathcal{X}^k$ . defined as in (15). Further, the minimum common message rate  $R^*$  is also bounded above as:

$$R^* \le \min_{q \in \mathcal{Q}} H(\mathbf{X}) + D(p \| q) + \log\left(\log\left(\frac{q_{\max}}{q_{\min}}\right) + 1\right) + 3,$$
(18)

where

$$q_{\max} = \max_{\mathbf{x} \in \mathcal{X}^k: p(\mathbf{x}) > 0} q(\mathbf{x}); \quad q_{\min} = \min_{\mathbf{x} \in \mathcal{X}^k: p(\mathbf{x}) > 0} q(\mathbf{x}).$$
(19)

*Proof:* See Appendix A.

The key insight of Theorem 1 is the D(p||q) term, which corresponds to the cost of using a codebook constructed according to  $q(\mathbf{x})$  to compress a source with distribution  $p(\mathbf{x})$ . This is the same D(p||q) cost as in classical source coding. For i.i.d. mixture sources, the D(p||q) cost can be eliminated. Corollary 1: Under the setting of Theorem 1, if the source  $\mathbf{X}$  is i.i.d. or a mixture of i.i.d. then the minimum common message rate is bounded above by

$$R^* \le H(\mathbf{X}) + \log(H(\mathbf{X}) + 1) + 1.$$
 (20)

Further, for i.i.d. sources with distribution p(x), we have

$$R^* \le kH(p) + \min\left\{\log(kH(p) + 1) + 1, \\ \log\left(k\log\left(\frac{p_{\max}}{p_{\min}}\right) + 1\right) + 3\right\}, \quad (21)$$

where

$$p_{\max} = \max_{x \in \mathcal{X}: p(x) > 0} p(x); \quad p_{\min} = \min_{x \in \mathcal{X}: p(x) > 0} p(x).$$
(22)

*Proof:* The corollary follows directly from Theorem 1 by using a codebook constructed according to  $q(\mathbf{x}) = p(\mathbf{x})$ .

Setting  $q(\mathbf{x}) = p(\mathbf{x})$  is a natural choice for i.i.d. or i.i.d. mixture sources, because it maximizes the probability of matching codewords with the source. This result shows that for i.i.d. and i.i.d. mixture sources, the proposed code construction and the proposed encoding and decoding scheme can achieve the source entropy to within at most an  $O(\log(k))$  overhead. The overhead can be further reduced if the distribution is close to uniform. In particular, for an i.i.d. uniform distribution with  $p_{\text{max}} = p_{\text{min}}$ , the entropy can be achieved to within O(1) bits.

An intuitive (but somewhat inaccurate) argument of why for i.i.d. sources, a matching i.i.d. codebook can approach the source entropy is the following. When the codebook distribution and the source distribution  $p(\mathbf{x})$  match, for every realization of the source  $\mathbf{x}$ , a randomly generated codeword would match  $\mathbf{x}$  with a probability  $p(\mathbf{x})$ . Thus, the index of the first matching codeword follows a geometric distribution with parameter  $p(\mathbf{x})$ . The entropy of such a geometric distribution is essentially  $-\log(p(\mathbf{x}))$  plus a constant. Then, when averaged over all realizations of  $\mathbf{x}$ , we can achieve a common message entropy of  $\mathbb{E}[-\log(p(\mathbf{X}))]$ , which is just the source entropy  $H(\mathbf{X})$ , plus a constant.

To make the above argument rigorous, we recognize that the actual distribution of the first matching index for a fixed codebook, across all source realizations, is a mixture of geometric distributions, for which the computation of entropy is quite nontrivial. Appendix A uses a bounding technique over randomly generated codebooks to show the existence of one codebook whose output has the desired entropy, up to an additive logarithmic term.

#### D. Coding for Exchangeable Sources

The proposed codebook construction uses an i.i.d. mixture to generate the random codebook. This is because we do not know in advance which of the k out of n users would become active. Using a mixture of i.i.d. distributions to generate codewords ensures that any k distinct entries of the codewords all have the same joint distribution.

If the source is also an i.i.d. mixture, then matching the codebook and the source distributions allows us to bound the overhead to  $O(\log(k))$ . However, for general exchangeable

source distributions that are not i.i.d. mixtures, one can no longer simply set the codeword distribution to be the source distribution. In this section, we develop a novel code construction to allow a generalization of the result of Corollary 1 from i.i.d. sources to sources with arbitrary exchangeable distribution  $p(\mathbf{x})$ .

One may be tempted to use the marginal distribution  $p(x_1)$ of the joint distribution of the source  $p(x_1, \dots, x_k)$  to generate i.i.d. codewords in the codebook. But this is not necessarily a good strategy. Consider an example where  $(X_1, \dots, X_k)$ takes on only two values, either  $(0, \dots, 0)$  or  $(1, \dots, 1)$ with probability 0.5 each. Using the marginal distribution would have resulted a Ber $(\frac{1}{2})$  codebook for which finding a matching index would have required searching over  $O(2^k)$ codewords, resulting in a common message rate of O(k), whereas the optimal codebook should just have two codewords, i.e.,  $\{(0, \dots, 0), (1, \dots, 1)\}$  with a common message rate of only one bit.

The preceding example motivates us to define the following "urn" codebook for arbitrary exchangeable source distributions. Subsequently, we also defined "extended-urn" codebook for extendable source distributions.

1) Urn Codebook: The challenge lies in constructing length-*n* codewords whose arbitrary subsequences of length k all "look like" **x**. Recall from Theorem 1 that the achievable rate for communicating a general exchangeable source  $\mathbf{X} = (X_1, \dots, X_k) \sim p(\mathbf{x})$  is  $H(\mathbf{X})$  plus an overhead of D(p||q), where q is an i.i.d. mixture distribution used for codebook construction.

The question is then: For an arbitrary exchangeable source distribution  $p(\mathbf{x})$ , how should we design an i.i.d. mixture  $q(\mathbf{x})$  such that D(p||q) is small? We answer this question by introducing and analyzing the following novel codebook construction.

Definition 1 (Urn Codebook): Given an exchangeable source **X** with distribution  $p(\mathbf{x})$ , an urn codebook  $\mathbf{m}_{\text{URN}} = (\mathbf{c}^{(1)}, \mathbf{c}^{(2)}, \dots, )$  is a codebook consisting of codewords  $\mathbf{c}^{(j)} \in \mathcal{X}^n$  generated in the following fashion:

- 1) Sample a realization of  $\mathbf{x} = (x_1, \cdots, x_k)$  using  $p(\mathbf{x})$ .
- Generate each entry of c<sup>(j)</sup> in an i.i.d. fashion according to p̂<sub>x</sub>, where p̂<sub>x</sub> is the empirical distribution of x:

$$\hat{p}_{\mathbf{x}}(c) = \frac{1}{k} \sum_{i=1}^{k} \mathbb{1}_{\{c\}} x_i.$$
(23)

It is easy to see that the urn codebook is constructed from a mixture of i.i.d. distributions. In particular, the mixture weights are given by the probability that the sampled realization is of a particular type. Further, we argue that this i.i.d mixture is close to the source distribution. To see this, note that this codebook generation process can be alternatively viewed as repeatedly sampling with replacement from an urn containing the elements of  $\mathbf{x}$ . On the other hand, if the k entries of a codeword are sampled without replacement from the entries of  $\mathbf{x}$ , then the k entries would look as if they are distributed as  $p(\mathbf{x})$ . Thus, the difference between the source distribution and the i.i.d. mixture is precisely the difference between sampling with and without replacement. This intuition is captured in

the following theorem, which quantifies this difference by bounding the KL divergence between the source distribution and the i.i.d. mixture induced by the code construction.

Theorem 2: Let  $p(\mathbf{x})$  be an exchangeable distribution. Let  $q(\mathbf{x})$  be the distribution generated by randomly choosing k distinct entries from the codewords in the urn codebook, then

$$D(p||q) \le \min\{k \log(e), |\mathcal{X}| \log(k+1)\}.$$
 (24)

#### Proof: See Appendix B

The above theorem gives upper bounds on the cost of using a codebook generated from an i.i.d. mixture distribution to represent an exchangeable source. The above bound immediately leads to the following achievability result for coded downlink massive random access.

Corollary 2: Consider a massive access scenario with a total of n users and a random subset of k active users. Let sources  $\mathbf{X} = (X_1, \cdots, X_k)$  take values in a discrete set  $\mathcal{X}^k$  and be distributed according to an exchangeable distribution  $p(\mathbf{x})$ . Then the minimum common message rate  $R^*$  for communicating each  $X_i$  to its corresponding user *i* is bounded above as

$$R^* \le H(\mathbf{X}) + k\log(e) + \log(H(\mathbf{X}) + k\log(e) + 1) + 1$$
(25)

and

$$R^* \le H(\mathbf{X}) + |\mathcal{X}|\log(k+1) + \log(H(\mathbf{X}) + |\mathcal{X}|\log(k+1) + 1) + 1.$$
(26)

*Proof:* The proof follows directly from Theorem 2 and Theorem 1.

The implication is that for any exchangeable source, the overhead beyond  $H(\mathbf{X})$  is at most O(k), or in case of finite alphabet sources  $O(\log(k))$ .

*Remark 1:* It is interesting to note that the O(k) scaling in overhead can already be obtained using a scheduling code of [6] to order the randomly activated k users using at most  $(k+1)\log(e)$  bits, followed by entropy coding of the sources listed in that order, as mentioned earlier. This approach of scheduling followed by source coding is different from the strategy of using the urn codebook, but the two achieve about the same  $k \log e$  overhead for general exchangeable sources. The urn codebook can be thought of as combining scheduling and source coding steps together. The urn codebook also achieves a smaller overhead in case of finite alphabet sources.

2) Extended Urn Codebook: Although i.i.d. and i.i.d. mixture sources are also exchangeable, they do not incur the O(k) overhead. The reason is that i.i.d. and i.i.d. mixtures are *infinitely* extendable. In this section, we investigate coding for exchangeable sources that are *finitely* extendable, and show that a better rate can already be achieved in this case. Recall that a source  $(X_1, \dots, X_k)$  is *d*-extendable if it has the same distribution as the first k elements of a longer exchangeable sequence  $(X_1, \dots, X_k, \dots, X_d)$ . The idea is that for a *d*-extendable source, we can construct modified version of the urn codebook by sampling from realizations of  $(X_1, \cdots, X_k, \cdots, X_d)$ .

Definition 2 (Extended Urn Codebook): Given an exchangeable source  $(X_1, \dots, X_k)$  which is *d*-extendable, i.e., there is an extended version  $(X_1, \dots, X_k, \dots, X_d)$  with distribution  $p(x_1, \dots, x_d)$  that is exchangeable, an extended urn codebook

 $\mathbf{m}_{\text{EX-URN}} = \left(\mathbf{c}^{(1)}, \mathbf{c}^{(2)}, \cdots, \right)$  is a codebook consisting of codewords  $\mathbf{c}^{(j)} \in \mathcal{X}^n$  generated in the following fashion:

- 1) Sample a realization of  $\mathbf{x} = (x_1, \dots, x_d)$  using distribution  $p(x_1, \cdots, x_d)$ .
- 2) Generate each entry of  $c^{(j)}$  in an i.i.d. fashion according to  $\hat{p}_{\mathbf{x}}$ , where  $\hat{p}_{\mathbf{x}}$  is the empirical distribution of  $\mathbf{x}$ :

$$\hat{p}_{\mathbf{x}}(c) = \frac{1}{d} \sum_{i=1}^{k} \mathbb{1}_{\{c\}} x_i.$$
(27)

This is essentially the same definition as Definition 1, but with sampling occurring on an extended sequence  $(X_1, \dots, X_d)$  instead. Since we are sampling k entries from a larger vector of size d, we expect this distribution to be closer in KL divergence than the one induced by Definition 1.

Finite de Finetti theorems are a class of results that provide bounds on some measure of distance between an i.i.d. mixture distribution (which is how the codewords in the extended urn codebook are constructed) and an exchangeable and dextendable distribution. We discuss finite de Finetti results in detail in Section III. The following is a finite de Finetti theorem under KL divergence. It allows a characterization of the minimum common message rate for exchangeable and dextendable sources.

Theorem 3: Let  $p(\mathbf{x}), \mathbf{x} \in \mathcal{X}^k$  be an exchangeable distribution that is also d-extendable with d > k. Let  $q(\mathbf{x})$  be the distribution generated by choosing k distinct entries from the codewords in the extended urn codebook, then

$$D(p||q) \le \min\left\{\log\left(\frac{d^k}{d^k}\right), (|\mathcal{X}|-1)\log\left(\frac{d-1}{d-k}\right)\right\}.$$
(28)
  
*Proof:* See Appendix C

Corollary 3: Consider a massive access scenario with a total of n users and a random subset of k active users. Let sources  $\mathbf{X} = (X_1, \cdots, X_k)$  take values in a discrete set  $\mathcal{X}^k$  and be distributed according to an exchangeable and d-extendable distribution  $p(\mathbf{x})$  with d > k. The minimum common message rate  $R^*$  for communicating each  $X_i$  to the respective user i is bounded above as

$$R^* \le H(\mathbf{X}) + \log\left(\frac{d^k}{d^k}\right) + \log\left(H(\mathbf{X}) + \log\left(\frac{d^k}{d^k}\right) + 1\right) + 1$$
(29)

and

$$R^* \leq H(\mathbf{X}) + (|\mathcal{X}| - 1) \log\left(\frac{d - 1}{d - k}\right) + \log\left(H(\mathbf{X}) + (|\mathcal{X}| - 1) \log\left(\frac{d - 1}{d - k}\right) + 1\right) + 1.$$
(30)

*Proof:* The proof follows directly from Theorem 3 and Theorem 1.

Remark 2: Observe that the first bound in (28) essentially reduces to the  $k \log e$  bound in (24) in the case of d = k. For general exchangeable sources, this bound is tight. Theorem 6 later in the paper shows an example that achieves this bound. The second terms in (24) and (28) are the respective upper bounds in the case of finite alphabet sources. These bounds are derived using different proof techniques; the latter does not reduce to the former in the case of d = k.

## E. Applications

1) I.I.D. Source: As already shown in Corollary 1, when the source has i.i.d. or i.i.d. mixture distribution, the minimum downlink common message rate is the entropy of the source, plus an overhead of at most  $O(\log(k))$ . This overhead can be reduced to O(1) if the source distribution is i.i.d. uniform.

2) Scheduling: Suppose that we wish to assign the k active users into b slots, where no two users can be assigned to the same slot. This is known as the scheduling problem. Let  $X_i \in \{1, \dots, b\}$  be the slot assignment for the *i*th user. If all  $\binom{b}{k}$  schedules are equally likely, then  $\mathbf{X} = (X_1, \dots, X_k)$ , i.e., the assignment of active users to the slots, is an exchangeable random sequence. We have  $H(\mathbf{X}) = \log \left(\binom{b}{k}k!\right)$ .

Consider the problem of communicating a particular schedule to the k active users where each user is only interested in learning its own slot assignment. For the case of b = k, the urn codebook would generate codewords according to uniform distribution on [k]. Therefore, we can use (18) in Theorem 1 to show that the following rate is achievable

$$R^* \le H(\mathbf{X}) + D(p||q) + 3$$
  
$$\le \log(k!) + k \log(e) + 3 \qquad (31)$$
  
$$\approx k \log(k),$$

where D(p||q) is bounded as in Theorem 2.

When b > k, this is an example of an exchangeable source distribution  $p(\mathbf{x})$  that is *b*-extendable, because we can think of the process of scheduling *k* users into *b* slots as the first *k* steps in the scheduling of *b* users into *b* slots (which is an extended exchangeable distribution).

Using the extended urn codebook, Corollary 3 allows us to bound the minimum common message rate as

$$R^* \le H(\mathbf{X}) + D(p||q) + 3$$
  
$$\le \log\left(\binom{b}{k}k!\right) + \log\left(\frac{b^k}{b^k}\right) + 3 \qquad (32)$$
  
$$\approx k \log(b)$$

The achievable rates in (31) and (32) have an intuitive explanation, as scheduling a user into one of the *b* slots requires log(b)bits; so the minimum common message rate for scheduling *k* users should scale as k log(b). It is remarkable that this common message rate is achieved using a code that does not specify exactly which user is scheduled into each slot.

A converse for these rates, which is tight to within a constant at large n, for the general case of  $b \ge k$ , can be obtained as follows:

$$R^* \ge k \log(b) - \log\left(\frac{n^k}{n^{\underline{k}}}\right),\tag{33}$$

where *n* is the total number of users. The proof uses a volume bound technique and is presented in Appendix D. For any fixed k, the second term vanishes as  $n \to \infty$ . Therefore, for large n, the achievable rate (31) and (32) are optimal to within a constant.

In the context of scheduling for massive random access, a different problem is studied in [6], where the BS can choose any schedule for the active users, as long as the slot assignments are non-colliding. In this case, assuming b = k, the common message rate can be further reduced by a  $\log(k!)$ factor, because any of the k! non-colliding schedules are equally allowable. This results in a common message rate of at most  $(k+1) \log e$  bits as established in [6] and in agreement with the scaling in (31), where  $R^* - \log(k!) \approx k \log e$ .

3) Categorization: Consider the task of categorizing the k active users into c categories, where each category must have a fixed number of  $k_{\ell}$  users,  $\ell \in [c]$ , and  $\sum_{\ell=1}^{c} k_{\ell} = k$ . The BS wants to transmit label  $\ell \in [c]$  to the  $k_{\ell}$  users in category  $\ell$ . Each user is only interested in its own category.

Assuming that all category assignments satisfying the constraint  $\sum_{\ell=1}^{c} k_{\ell} = k$  are equally likely, the source  $(X_1, \dots, X_k)$ , which represents the category labels for the k active users, is an exchangeable random sequence. This exchangeable random sequence can also be thought of as drawing k balls from an urn without replacement, where the urn contains k balls in total; the balls are labeled with  $\ell \in [c]$ ; and there are  $k_{\ell}$  balls with label  $\ell$ .

To communicate the category labels to the active users, we can use an urn codebook, where the entries of the codewords can be thought of as drawing k balls from the same urn, but with replacement. Notice that the urn contains  $k_{\ell}$  balls for each label  $\ell$  with  $k_{\ell}$  fixed, so the codebook distribution  $q(\mathbf{x}) = \prod_{\ell=1}^{c} \left(\frac{k_{\ell}}{k}\right)^{k_{\ell}}$  is a constant over the support of  $p(\mathbf{x})$ . So, we can apply (18) in Theorem 1 to show that a rate of

$$R^* \le H(\mathbf{X}) + D(p||q) + 3$$
 (34)

is achievable. By Theorem 2, the overhead D(p||q) is at most  $\min\{k \log(e), c \log(k+1)\}$ .

The above achievable common message rate can be computed more directly by expanding out the entropy terms:

$$H(\mathbf{X}) + D(p||q) = \sum_{\mathbf{x} \in [c]^k} p(\mathbf{x}) \log\left(\frac{1}{q(\mathbf{x})}\right)$$
$$= \log\left(\frac{1}{\prod_{\ell=1}^c \left(\frac{k_\ell}{k}\right)^{k_\ell}}\right)$$
$$= k \sum_{\ell=1}^c \left(\frac{k_\ell}{k}\right) \log\left(\frac{k_\ell}{k}\right) = k H(\rho),$$
(35)

where  $\rho = \left(\frac{k_1}{k}, \dots, \frac{k_c}{k}\right)$  is the empirical distribution of the labels. Thus interestingly, a characterizaton of achievable common message rate is simply the entropy of the category sizes, i.e.,

$$R^* \le kH(\rho) + 3. \tag{36}$$

For this specific example, it is also possible to prove a converse that shows

$$R^* \ge kH(\rho) - \log\left(\frac{n^k}{n^k}\right),\tag{37}$$

where n is the total number of users. The proof is in Appendix E. Again, for any fixed k, the second term vanishes as  $n \to \infty$ . Therefore, for large n, the achievable rate (36) is optimal to within a constant.

4) Resource Allocation: Suppose that  $\mathbf{X} = (X_1, \dots, X_k)$ must satisfy  $\sum_{i=1}^k X_i = r$ , where  $0 \le X_i \le r$  takes on integer values. This can be thought of as a resource allocation problem where r units of resources are allocated to k randomly activated users (among a total of n potential users). Consider the joint distribution induced by the process of allocating each unit of resource to the k users uniformly at random one at a time. The resulting  $(X_1, \dots, X_k)$  is exchangeable, but  $X_i$ 's are not independent due to the constraint  $\sum_{i=1}^k X_i = r$ .

The source distribution in this setting is the multinomial distribution:

$$\Pr(\mathbf{X} = \mathbf{x}) = \begin{cases} \frac{r!}{x_1! \cdots x_k!} \left(\frac{1}{k}\right)^r, & \text{if } \sum_{i=1}^k x_i = r\\ 0, & \text{otherwise.} \end{cases}$$
(38)

The multinomial distribution is exchangeable. By Corollary 2, using the urn codebook achieves a rate of  $H(\mathbf{X})$  bits with an overhead of  $k \log(e)$  plus a logarithmic term.

In the previous three examples, the respective urn codebooks all happen to reduce to a construction where the codewords are i.i.d. generated according to the marginal of the joint distribution. But this is not true here. We use this example to demonstrate that using the marginal distribution to construct the codebook can be inferior to using the urn codebook.

If we use the marginal distribution to construct the codebook, the codeword distribution would have been  $q(\mathbf{x}) = \prod_{i=1}^{k} p(x_i)$ , where  $p(x_i)$  is the marginal of the multinomial distribution. Then by Theorem 1, an achievable rate (up to an additional logarithmic term) is:

$$R_{\text{marginal}} \approx H(\mathbf{X}) + D(p||q)$$

$$= \sum_{x_1, \cdots, x_k} p(\mathbf{x}) \log\left(\frac{1}{\prod_{i=1}^k p(x_i)}\right)$$

$$= k \sum_{x_1} p(x_1) \log\left(\frac{1}{p(x_1)}\right)$$

$$= k H(X_1).$$
(39)

The marginal distribution of the multinomial is a binomial distribution  $p(x_1) = \binom{r}{x_1} \left(\frac{1}{k}\right)^{x_1} \left(1 - \frac{1}{k}\right)^{r-x_1}$ . The entropy of the marginal can be computed as

$$H(X_1) = \frac{1}{2} \log \left( 2\pi e \left( \frac{r}{k} \right) \left( 1 - \frac{1}{k} \right) \right) + O\left( \frac{1}{r} \right).$$
(40)

On the other hand, if we use an urn codebook, by Corollary 2 the following rate is achievable (to within an additional logarithmic term):

$$R_{\rm urn} \approx H(\mathbf{X}) + k \log e \qquad (41)$$
$$= \frac{k-1}{2} \log(2\pi er) - \frac{k}{2} \log(k) + O\left(\frac{1}{r}\right) + k \log e.$$

where the entropy of the multinomial distribution is computed according to the approximation in [12].

Comparing  $R_{\text{marginal}}$  with  $R_{\text{urn}}$ , we see that their difference is as follows:

$$R_{\text{marginal}} - R_{\text{urn}}$$

$$\approx \frac{1}{2} \log(2\pi er) + \frac{k}{2} \log\left(1 - \frac{1}{k}\right) - k \log e + O\left(\frac{1}{r}\right)$$

$$\geq \frac{1}{2} \log(2\pi er) - \frac{\log(e)}{2} - k \log e + O\left(\frac{1}{r}\right)$$

$$= \frac{1}{2} \log(2\pi r) - k \log e + O\left(\frac{1}{r}\right).$$
(42)

Therefore at fixed k, for large values of r, it is advantageous to use the urn codebook.

The value of r for which the urn codebook outperforms a codebook constructed from the marginal distribution does not need to be as large as what (42) suggests. Consider the scenario where r = k = 2. In this case, the entropy of the marginal can be computed directly as

$$H(X_1) = -\sum_{i=0}^{2} p_i \log p_i = 1.5$$
(43)

where  $p_i = {\binom{2}{i}} {\binom{1}{2}}^2$ . Therefore  $kH(X_1) = 3$ .

On the other hand, the entropy of  $H(X_1, X_2) = H(X_1) =$ 1.5, since the value of  $X_2$  is determined by the value of  $X_1$ . This gap is therefore 1.5 bits. Now, the extra  $k \log(e)$  cost comes from approximating the divergence between the multinomial distribution and the corresponding urn codebook. For finite k, the extra cost is bounded above by  $\log\left(\frac{k^k}{k!}\right) =$ 1 < 1.5 for k = 2. Therefore, the urn codebook is already better than the codebook constructed from the marginal for r = k = 2.

The urn codebook in this case contains only two types of codewords: the  $(1, \dots, 1)$  codeword and codewords with 0 and 2 in 50% proportion each, whereas the codebook constructed from marginal distribution has codewords with mixed 0, 1, and 2 entries, which is not as effective.

# F. Random Number of Active Users

So far in this paper, we have assumed that the number of active users k is fixed and known in advance. This is not always a valid assumption, since user activities are typically random in a massive access scenario. In this section, we point out that if the number of active users is random, the previous results can be modified so they continue to hold in expectation.

Consider the scenario in which we wish to transmit i.i.d. sources to a set of randomly activated users. Let K be a random variable that denotes the number of active users. The BS learns the activity pattern, thus the realization of Kin each transmission slot, then aim to transmit the sources  $X_1, \dots, X_K$  to each of the K active users, respectively. One way to do this is to first broadcast the realization of K to all the active users using H(K) bits, then use the results developed in earlier sections of this paper. However, we show here that this is not necessary, in case of i.i.d. sources. The following result is a counterpart of Corollary 1 for random number of active users, which shows that the minimum common message rate is essentially the *expected* entropy of the source. Theorem 4: Fix the total number of users n. Let the number of randomly activated users  $K \in [n]$  be a random variable. Let  $a_i$  be the index of the *i*th active user,  $i \in [K]$ . Let  $(X_1, \dots, X_K)$  be i.i.d.  $\sim p(x)$ . The minimum common message rate  $R^*$  for communicating each  $X_i$  to its respective intended user  $a_i$ ,  $i = 1, \dots, K$ , is bounded above as

$$R^* \le \mathbb{E}[K]H(p) + \log(\mathbb{E}[K]H(p) + 1) + 1.$$
 (44)

**Proof:** The proposed coding strategy of using a codebook consisting of codewords of size n, then looking for a matching codeword for the active users, works equally well for random K as for fixed k. To bound the entropy of matching index, it is possible to first condition on k, then average over K. The details are in Appendix F.

#### III. FINITE DE FINETTI THEOREM

In this section, we discuss the implications of Theorem 2 and Theorem 3 towards the study of the de Finetti theorem and finite exchangeable sequences. The original de Finetti theorem states that every infinitely extendable sequence of exchangeable random variables has a distribution that is equivalent to an i.i.d. mixture. This result is later generalized to finite exchangeable sequences in [5] where it is shown that if  $(X_1, \dots, X_k, \dots, X_d)$  is an exchangeable sequence of random variables, then the distribution of  $(X_1, \dots, X_k) \sim p(\mathbf{x})$ is close to being an i.i.d. mixture in the sense that

$$\min_{q \in \mathcal{Q}} \operatorname{TV}(p,q) \le \min\left\{\frac{|\mathcal{X}|k}{d}, \frac{k(k-1)}{2d}\right\}, \quad (45)$$

where  $TV(p,q) = \sup_{\mathcal{X}^k} |p(\mathbf{x}) - q(\mathbf{x})|$  and  $\mathcal{Q}$  is the family of i.i.d. mixture distributions on  $\mathcal{X}^k$ .

The interesting part of this result is that the total variation distance can go to 0 even if  $k, d \to \infty$ . In the case where the alphabet size  $|\mathcal{X}|$  is finite, the total variation distance goes to 0 as long as  $\frac{k}{d} \to 0$ . For general alphabets,  $\frac{k^2}{d} \to 0$  is sufficient. Examples are presented in [5] to show that the scaling of (45) cannot be improved in general.

Although the total variation distance cannot be used to upper bound the relative entropy, they are related through Pinsker's inequality [13] which states that

$$\mathrm{TV}(p,q) \le \sqrt{\frac{\ln(2)}{2}D(p\|q)}.$$
(46)

Since the scaling in (45) is the best possible for general sequences, we have a natural converse for upper bounds on the relative entropy between i.i.d. mixtures and exchangeable and extendable sequences, i.e. the bounds cannot scale better than (45).

Recently, there has been an interest in establishing similar results as (45), but in terms of relative entropy. Given that  $p(\mathbf{x})$  is the distribution of a *d*-extendable exchangeable sequence  $(X_1, \dots, X_k)$ , we wish to upper bound

$$\min_{q \in \mathcal{Q}} D(p \| q). \tag{47}$$

It is shown in [11] through the use of information theoretic tools that

$$\min_{q \in \mathcal{Q}} D(p \| q) \le \frac{k(k-1)}{2(d-k-1)} \log |\mathcal{X}|, \tag{48}$$

indicating that if the cardinality of the alphabet is finite, then  $\frac{k^2}{d} \rightarrow 0$  is sufficient to ensure vanishing relative entropy between a *d*-extendable exchangeable distribution and the closest i.i.d. mixture distribution. As noted by the authors, this scaling is weaker than that of (45).

Given an exchangeable source  $\mathbf{X} = (X_1, \dots, X_k)$  with distribution  $p(\mathbf{x})$ , we show in Theorem 1 that the achievable rate is close to the entropy  $H(\mathbf{X})$  plus a divergence term

$$\min_{q \in \mathcal{Q}} D(p \| q), \tag{49}$$

where Q is the family of i.i.d. mixture distributions on  $\mathcal{X}^k$ . Through the extended urn codebook construction, we show through Theorem 3 that for every exchangeable and *d*-extendable distribution  $p(\mathbf{x})$ , there exists an i.i.d. mixture distribution  $q(\mathbf{x})$  such that

$$D(p||q) \le \min\left\{\log\left(\frac{d^k}{d^k}\right), (|\mathcal{X}|-1)\log\left(\frac{d-1}{d-k}\right)\right\}.$$
(50)

Thus, the extended urn codebook construction implies a relative entropy version of the de Finetti theorem.

Theorem 5 (Finite de Finetti with KL Divergence): Let  $(X_1, \dots, X_k, \dots, X_d)$  be a sequence of exchangeable random variables taking values in  $\mathcal{X}^d$ . Let  $p(x_1, \dots, x_k)$  denote the distribution of  $(X_1, \dots, X_k)$ . Then,

$$\min_{q \in \mathcal{Q}} D(p \| q) \leq \min\left\{ (|\mathcal{X}| - 1) \log\left(\frac{d - 1}{d - k}\right), -\log\left(1 - \frac{k(k - 1)}{2d}\right) \right\},$$
(51)

where Q is the family of i.i.d. mixture distributions on  $\mathcal{X}^k$ .

*Proof:* The proof follows directly from Theorem 3 and the following useful inequality from [14]:

$$\log\left(\frac{d^k}{d\underline{k}}\right) \le -\log\left(1 - \frac{k(k-1)}{2d}\right). \tag{52}$$

Clearly, the scaling of d and k required to drive D(p||q) to zero in Theorem 5 matches that of (45), and is therefore the best possible for general exchangeable sequences due to (46) and the aforementioned reasoning.

In fact, not only the scaling cannot be improved, the first term in the bound (50) itself, i.e.,

$$\min_{q \in \mathcal{Q}} D(p \| q) \le \log\left(\frac{d^k}{d^k}\right) \tag{53}$$

is also the best possible upper bound for general exchangeable and d-extendable sequences. We establish this fact by showing that for a particular exchangeable and d-extendable distribution h, the above upper bound is achieved.

Theorem 6: Let d > k and  $h(x_1, \dots, x_k)$  be the distribution of k draws without replacement from an urn containing elements  $\{1, 2, \dots d\}$ , i.e.,  $|\mathcal{X}| = d$ . Then, for every i.i.d. mixture distribution  $q(x_1, \dots, x_k)$ , we have that

$$D(h\|q) \ge \log\left(\frac{d^k}{d^k}\right).$$
 (54)

*Proof:* The proof takes the idea from [5] and is deferred to Appendix G.

Thus, for this particular  $h(x_1, \dots, x_k)$ , the minimum D(h||q) over  $q \in \mathcal{Q}$  is precisely the right-hand side of (53) and (54). For d = k, this lower bound is  $\log\left(\frac{k^k}{k!}\right) \approx k \log e$ . Note that in this case, we have  $|\mathcal{X}| = d$  for which the

Note that in this case, we have  $|\mathcal{X}| = d$  for which the second term in the minimum in (50) is always larger than the first term. For general exchangeable and *d*-extendable  $p(x_1, \dots, x_k)$ , e.g., with smaller  $|\mathcal{X}|$ , the minimum D(p||q) may be smaller than the right-hand side of (53).

#### **IV. CONCLUSIONS**

This paper connects the finite de Finetti theorem and the problem of communicating sources with certain symmetry to a randomly activated subset of users in downlink massive random access. We develop a relative entropy version of the finite de Finetti theorem and provide a bound on the extra cost of using a codebook generated from i.i.d. mixture distributions to send exchangeable sources to a random subset of k users out of a large pool of n users. The extra cost is independent of n, and is at most O(k) for general exchangeable sources,  $O(\log k)$  for finite alphabet exchangeable sources, and O(1) for uniform i.i.d. sources.

## APPENDIX A Proof of Theorem 1

Instead of analyzing the encoder output entropy of a particular codebook, we bound the output entropy over an ensemble of codebooks, then show the existence of one codebook satisfying the derived entropy bound.

First, in a massive random access scenario where a random subset of k users are activated among a large pool of n users, when the source distribution is exchangeable, it does not matter which subset of k users are activated. So we only need to consider  $p(\mathbf{x})$  with x taking values on  $\mathcal{X}^k$ .

Let  $p(\mathbf{x})$  be an exchangeable source distribution on  $\mathcal{X}^k$ . Let  $q(\mathbf{x})$  be an i.i.d. mixture distribution on  $\mathcal{X}^k$ . Let **M** be a random codebook generated according to  $q(\mathbf{x})$ . Define  $T = f_{\mathbf{M}}(\mathbf{X}, \mathbf{A})$  to be the encoder output from the following process. We generate a source  $\mathbf{x}$  according to  $p(\mathbf{x})$ . We also generate a random codebook **M** according to  $q(\mathbf{x})$ , then find the index of the first codeword in **M** that matches the source  $\mathbf{x}$  according to (13). We first find an upper bound on H(T).

Once an upper bound on H(T) is obtained, we then argue that there must exist at least one good codebook, whose output entropy across all input  $\mathbf{x} \sim p(\mathbf{x})$  is upper bounded by the same bound. This is because mixing increases entropy, so

$$\overline{H(f_{\mathbf{m}}(\mathbf{X}, \mathbf{A}))} \le H(f_{\mathbf{M}}(\mathbf{X}, \mathbf{A})) = H(T),$$
(55)

where  $H(f_{\mathbf{m}}(\mathbf{X}))$  is the encoder output entropy for a particular codebook  $\mathbf{m}$ , and the overline denotes the averaging operation over  $\mathbf{m}$ . Since there must exist at least one codebook  $\mathbf{m}^*$  such that

$$H(f_{\mathbf{m}^*}(\mathbf{X}, \mathbf{A})) \le \overline{H(f_{\mathbf{m}}(\mathbf{X}, \mathbf{A}))},$$
(56)

(as otherwise the average cannot be achieved), it follows that

$$R^* \le H(f_{\mathbf{m}^*}(\mathbf{X}, \mathbf{A})) \le H(T).$$
(57)

Thus in the rest of the proof, we only need to bound H(T).

Next, we analyze the distribution of T. Since the codewords of a random codebook are generated in an i.i.d. fashion according to the distribution  $q(\mathbf{x})$ , it follows that when conditioned on a source realization  $\mathbf{x}$ , the probability that the first match occurs at T = t is a geometric distribution with parameter  $q(\mathbf{x})$ . Then, it follows that the overall distribution of T, across all the sources  $\mathbf{x}$ , must be a mixture of geometric distributions:

$$\Pr(T=t) = \sum_{\mathbf{x}\in\mathcal{X}^k} p(\mathbf{x})(1-q(\mathbf{x}))^{t-1}q(\mathbf{x}).$$
 (58)

We now bound the entropy of this geometric mixture.

#### A. Proof of (17)

A direct calculation of the entropy of a mixture of geometric distributions is nontrivial. To circumvent this, we upper bound H(T) using the fact that

$$H(T) \le \mathbb{E}[\log(T)] + \log(\mathbb{E}[\log(T)] + 1) + 1.$$
(59)

A proof of (59) can be found in [15], where a maximum entropy argument is used. The problem is now reduced to bounding  $\mathbb{E}[\log(T)]$ . To this end, we use the fact that

$$\log(t) < \frac{1}{\ln(2)} \left( \sum_{\ell=1}^{t} \frac{1}{\ell} - \frac{1}{2} \right) \le \frac{1}{\ln(2)} \sum_{\ell=1}^{t-1} \frac{1}{\ell}, \text{ for all } t > 1$$
(60)

to compute the following bound for  $\mathbb{E}[\log(T)]$ :

$$\mathbb{E}[\log(T)] = \sum_{t=1}^{\infty} \left( \sum_{\mathbf{x}\in\mathcal{X}^k} p(\mathbf{x})(1-q(\mathbf{x}))^{t-1}q(\mathbf{x}) \right) \log(t)$$
$$= \sum_{\mathbf{x}\in\mathcal{X}^k, p(\mathbf{x})>0} p(\mathbf{x})q(\mathbf{x})\sum_{t=2}^{\infty} (1-q(\mathbf{x}))^{t-1}\log(t)$$
$$\leq \sum_{\mathbf{x}\in\mathcal{X}^k, p(\mathbf{x})>0} p(\mathbf{x})q(\mathbf{x})\frac{1}{\ln(2)}\sum_{t=2}^{\infty} \sum_{\ell=1}^{t-1} (1-q(\mathbf{x}))^{t-1}\frac{1}{\ell}.$$
(61)

The next step is to compute the inner double summations. Notice that for  $0 < \alpha < 1$  we have that

$$\sum_{t=2}^{\infty} \sum_{\ell=1}^{t-1} \alpha^{t-1} \frac{1}{\ell} = \sum_{\ell=1}^{\infty} \frac{1}{\ell} \sum_{t=\ell+1}^{\infty} \alpha^{t-1} = \frac{1}{1-\alpha} \sum_{\ell=1}^{\infty} \frac{\alpha^{\ell}}{\ell} = \frac{1}{1-\alpha} \int_{0}^{\alpha} \frac{1}{1-z} dz = \frac{-\ln(2)\log(1-\alpha)}{1-\alpha},$$
(62)

where the third equality follows from the fact that

$$\frac{d}{d\alpha} \sum_{\ell=1}^{\infty} \frac{\alpha^{\ell}}{\ell} = \sum_{\ell=1}^{\infty} \alpha^{\ell} = \frac{1}{1-\alpha}, \text{ for } 0 < \alpha < 1.$$
(63)

Substituting (62) with  $\alpha = 1 - q(\mathbf{x})$  into (61) yields

$$\mathbb{E}[\log(T)] \leq \sum_{\mathbf{x} \in \mathcal{X}^k, p(\mathbf{x}) > 0} p(\mathbf{x}) \frac{-\log(q(\mathbf{x}))}{q(\mathbf{x})}$$
$$= H(\mathbf{X}) + D(p||q).$$
(64)

Combining with (59) and (57), we have

$$R^* \le H(\mathbf{X}) + D(p||q) + \log(H(\mathbf{X}) + D(p||q) + 1) + 1.$$
(65)

## B. Proof of (18)

We bound the entropy of T by defining a new random variable L and using the fact that

$$H(T) \le H(T,L) = H(L) + H(T|L).$$
 (66)

The idea here is to choose an L such that the right-hand expression is easy to analyze. To this end, we define L based on the following partition  $\mathcal{D}_1, \mathcal{D}_2 \ldots \subseteq \mathcal{X}^k$  where

$$\mathcal{D}_{\ell} = \left\{ \mathbf{x} \in \mathcal{X}^k \mid \frac{1}{2^{\ell}} \le q(\mathbf{x}) < \frac{1}{2^{\ell-1}}, \ p(\mathbf{x}) > 0 \right\}.$$
(67)

The sets  $\mathcal{D}_{\ell}$  can be thought of as a binning of all possible source realizations based on their probability of occurrence with respect to the distribution used to generate the codebook. Since  $\mathcal{D}_1, \mathcal{D}_2...$  form a partition, each realization of **x** is contained in exactly one of these sets. We can define  $L(\mathbf{x})$ as the index of the set containing **x**.

$$L(\mathbf{x}) = \ell, \quad \text{s.t. } \mathbf{x} \in \mathcal{D}_{\ell}.$$
 (68)

It follows that for any  $\mathbf{x} \in \mathcal{X}^k$  with  $p(\mathbf{x}) > 0$ , the index of the set that  $\mathbf{x}$  belongs to is  $\ell = \left\lceil \log\left(\frac{1}{q(\mathbf{x})}\right) \right\rceil$ . This means that L takes on at most  $\left\lceil \log\left(\frac{1}{q_{\min}}\right) \right\rceil - \left\lceil \log\left(\frac{1}{q_{\max}}\right) \right\rceil$  values, and therefore has an entropy bounded above as

$$H(L) \leq \log\left(\left\lceil \log\left(\frac{1}{q_{\min}}\right)\right\rceil - \left\lceil \log\left(\frac{1}{q_{\max}}\right)\right\rceil\right)$$
$$\leq \log\left(\log\left(\frac{q_{\max}}{q_{\min}}\right) + 1\right). \tag{69}$$

It remains to bound H(T|L) in (66). Given  $L = \ell$ , we know that the sources must be in  $\mathcal{D}_{\ell}$  and therefore we can compute the conditional probability mass function

$$\Pr(T=t|L=\ell) = \sum_{\mathbf{x}\in\mathcal{D}_{\ell}} \frac{p(\mathbf{x})}{\Pr(L=\ell)} (1-q(\mathbf{x}))^{t-1} q(\mathbf{x}).$$
(70)

We can see that L acts as a way to quantize the original mixture distribution. Letting  $r_{\ell}(t) = \Pr(T = t | L = \ell)$ , we can upper bound  $H(T|L = \ell)$  as

$$H(T|L = \ell) = -\sum_{t=1}^{\infty} r_{\ell}(t) \log (r_{\ell}(t))$$
  
$$\leq -\sum_{t=1}^{\infty} r_{\ell}(t) \log (g(t; 2^{-\ell})), \qquad (71)$$

where  $g(t; \theta)$  is a geometric distribution with parameter  $\theta$  and the second line follows from the fact that  $-\sum_t r_{\ell}(t) \log (r_{\ell}(t)) \leq -\sum_t r_{\ell}(t) \log (r'(t))$  for any distribution r'(t). We can now bound H(T|L) using (71)

$$H(T|L) = \sum_{\ell}^{\infty} \Pr(L = \ell) H(T|L = \ell)$$
  
$$\leq -\sum_{\ell=1}^{\infty} \sum_{\mathbf{x} \in \mathcal{D}_{\ell}} p(\mathbf{x}) \sum_{t=1}^{\infty} r_{\ell}(t) \log \left(g(t; 2^{-\ell})\right)$$
  
$$= -\sum_{\mathbf{x}} p(\mathbf{x}) \sum_{t=1}^{\infty} g(t; q(\mathbf{x})) \log \left(g(t; q(\mathbf{x}))\right)$$
  
$$+ \sum_{\ell=1}^{\infty} \sum_{\mathbf{x} \in \mathcal{D}_{\ell}} p(\mathbf{x}) D(g(t; q(\mathbf{x})) || g(t; 2^{-\ell})), \quad (72)$$

where the third line follows from direct computation. Note that right-hand expression of (72) is the sum of two terms. The first is a weighted sum of the entropy terms of geometric random variables, whereas the second is a weighted sum of relative entropy between geometric distributions. Both terms can be bounded above by exploiting properties of geometric distributions. In particular, for the first term, we use the fact that the entropy of a random variable with distribution  $g(t; \theta)$  is upper bounded by  $\log(1/\theta) + \log(e)$  bits. Thus, the first term is upper bounded by  $\log(1/q(\mathbf{x})) + \log(e)$ . For the second term, it can be readily shown that  $D(g(t;q(\mathbf{x}))||g(t;2^{-\ell})) \leq 1$ , for  $2^{-\ell} \leq q(\mathbf{x}) \leq 2^{-\ell+1}$ . Hence, it follows that

$$\sum_{\ell=1}^{\infty} \sum_{\mathbf{x} \in \mathcal{D}_{\ell}} p(\mathbf{x}) D(g(t; q(\mathbf{x})) \| g(t; 2^{-\ell})) \le 1.$$
(73)

Putting it all together, we have

$$H(T|L) \leq -\sum_{\mathbf{x}} p(\mathbf{x}) \left( \log \left( q(\mathbf{x}) \right) + \log(e) \right) + 1$$
  
$$< H(\mathbf{X}) + D(p||q) + 3.$$
(74)

Finally, combining (57), (66), (69), and (74) yields

$$R^* \le H(\mathbf{X}) + D(p||q) + \log\left(\log\left(\frac{q_{\max}}{q_{\min}}\right) + 1\right) + 3.$$
 (75)

# APPENDIX B Proof of Theorem 2

From the urn codebook construction, any k distinct entries in a codeword can be represented by a tuple  $\mathbf{Y} = (X_{W_1}, \dots, X_{W_k})$ , where  $\mathbf{W} = (W_1, \dots, W_k)$  is i.i.d. over [k]. Now, if the sampling pattern were collision-free, it would have generated sequences that are distributed according to the original  $p(\mathbf{x})$ . Define the set of all collision-free  $\mathbf{w}$  as:  $\mathcal{F} = {\mathbf{w} \in [k]^k \mid w_i \neq w_j \text{ for all } i \neq j}$ . We have

$$q(\mathbf{x}) = \sum_{\mathbf{w} \in [k]^k} \Pr(\mathbf{W} = \mathbf{w}) \Pr(\mathbf{Y} = \mathbf{x} | \mathbf{W} = \mathbf{w})$$
$$\geq \sum_{\mathbf{w} \in \mathcal{F}} \Pr(\mathbf{W} = \mathbf{w}) \Pr(\mathbf{Y} = \mathbf{x} | \mathbf{W} = \mathbf{w})$$
$$= \sum_{\mathbf{w} \in \mathcal{F}} \frac{1}{k^k} p(\mathbf{x}) = \frac{k!}{k^k} p(\mathbf{x}).$$
(76)

where in the third line we used the fact that  $\Pr(\mathbf{W} = \mathbf{w}) = \frac{1}{k^k}$  since all sampling patterns are equally likely. Noting that  $k! > k^k e^{-k}$ , we have  $\log\left(\frac{k!}{k^k}\right) < k \log(e)$ . This implies that  $D(p||q) = \sum p(\mathbf{x}) \log \frac{p(\mathbf{x})}{q(\mathbf{x})} \leq k \log(e)$ .

Next, we show that  $D(p||q) \leq |\mathcal{X}| \log(k+1)$ . This bound is a consequence of the method of types and its relation to exchangeability. For vector  $\mathbf{x} \in \mathcal{X}^k$ , let  $\mathcal{T}_{\mathbf{x}}^{(k)} = \{\mathbf{s} \in \mathcal{X}^k \mid \hat{p}_{\mathbf{s}} = \hat{p}_{\mathbf{x}}\}$  denote its type class, where the notation  $\hat{p}_{\mathbf{s}}$ is taken from (23). Due to the exchangeability of  $p(\mathbf{x})$ , if  $\mathbf{x}^{(1)}, \mathbf{x}^{(2)} \in \mathcal{T}_{\mathbf{x}}^{(k)}$  then  $p(\mathbf{x}^{(1)}) = p(\mathbf{x}^{(2)})$ . The idea is to lower bound  $q(\mathbf{x})$  by restricting attention to the sequences within  $\mathcal{T}_{\mathbf{x}}^{(k)} = \{ \mathbf{s} \in \mathcal{X}^k \mid \hat{p}_{\mathbf{s}} = \hat{p}_{\mathbf{x}} \}$ :

$$q(\mathbf{x}) = \sum_{\mathbf{s}\in\mathcal{X}^{k}} p(\mathbf{s}) \left[ \prod_{i=1}^{k} \hat{p}_{\mathbf{s}}(x_{i}) \right]$$
$$= \sum_{\mathbf{s}\in\mathcal{X}^{k}} p(\mathbf{s}) 2^{-k(H(\hat{p}_{\mathbf{x}})+D(\hat{p}_{\mathbf{x}} \| \hat{p}_{\mathbf{s}}))} \ge \sum_{\mathbf{s}\in\mathcal{T}_{\mathbf{x}}^{(k)}} p(\mathbf{x}) 2^{-kH(\hat{p}_{\mathbf{x}})}$$
$$= |\mathcal{T}_{\mathbf{x}}^{(k)}| p(\mathbf{x}) 2^{-kH(\hat{p}_{\mathbf{x}})} \ge \frac{1}{(k+1)^{|\mathcal{X}|}} p(\mathbf{x}), \tag{77}$$

where the second line follows from Theorem 11.1.2 in [16] and the last line follows from the fact that  $|\mathcal{T}_{\mathbf{x}}| \geq \frac{1}{(k+1)^{|\mathcal{X}|}} 2^{kH(\hat{p}_{\mathbf{x}})}$ [16]. This implies that  $D(p||q) \leq |\mathcal{X}| \log(k+1)$ .

# APPENDIX C Proof of Theorem 3

To simplify notation, let  $\tilde{p}(x_1, \dots, x_d)$  denote the distribution of the extended sequence  $(X_1, \dots, X_d)$ . For  $\mathbf{s} \in \mathcal{X}^d$ , we let  $h_{\mathbf{s}}(x_1, \dots, x_k)$  denote the distribution of k draws without replacement from an urn containing the elements of  $\mathbf{s}$  and let  $m_{\mathbf{s}}(x_1, \dots, x_k)$  denote the distribution of k draws with replacement from the same urn. Note that  $m_{\mathbf{s}}(x_1, \dots, x_k)$  is equivalent to the empirical distribution of  $\mathbf{s}$ .

Using the extended distribution  $\tilde{p}$ , the source distribution is equivalent to the following weighted sum of urn distributions:

$$p(\mathbf{x}) = \sum_{\mathbf{s} \in \mathcal{X}^d} \tilde{p}(\mathbf{s}) h_{\mathbf{s}}(\mathbf{x}).$$
(78)

This follows from exchangeability, since the distribution of any k distinct elements of  $(X_1, \dots, X_d)$  has the same distribution as  $(X_1, \dots, X_k)$ .

If instead we sample with replacement, then we would have the distribution

$$q(\mathbf{x}) = \sum_{\mathbf{s} \in \mathcal{X}^d} \tilde{p}(\mathbf{s}) m_{\mathbf{s}}(\mathbf{x}).$$
(79)

This corresponds to the distribution of the extended urn codebook. The goal is to show that D(p||q) is small.

Using the log-sum inequality, the relative entropy can be upper bounded as

$$D(p||q) = \sum_{\mathbf{x}\in\mathcal{X}^{k}} p(\mathbf{x}) \log\left(\frac{p(\mathbf{x})}{q(\mathbf{x})}\right)$$
  
$$= \sum_{\mathbf{x}\in\mathcal{X}^{k}} \left[\sum_{\mathbf{s}\in\mathcal{X}^{d}} \tilde{p}(\mathbf{s})h_{\mathbf{s}}(\mathbf{x})\right] \log\left(\frac{\sum_{\mathbf{s}\in\mathcal{X}^{d}} \tilde{p}(\mathbf{s})h_{\mathbf{s}}(\mathbf{x})}{\sum_{\mathbf{s}\in\mathcal{X}^{d}} \tilde{p}(\mathbf{s})m_{\mathbf{s}}(\mathbf{x})}\right)$$
  
$$\leq \sum_{\mathbf{s}\in\mathcal{X}^{d}} \tilde{p}(\mathbf{s}) \sum_{\mathbf{x}\in\mathcal{X}^{k}} h_{\mathbf{s}}(\mathbf{x}) \log\left(\frac{h_{\mathbf{s}}(\mathbf{x})}{m_{\mathbf{s}}(\mathbf{x})}\right)$$
  
$$= \sum_{\mathbf{s}\in\mathcal{X}^{d}} \tilde{p}(\mathbf{s})D(h_{\mathbf{s}}||m_{\mathbf{s}}),$$
  
(80)

From Theorem 4.5 of [8], we know that for all  $\mathbf{s} \in \mathcal{X}^d$ ,

$$D(h_{\mathbf{s}} \| m_{\mathbf{s}}) \le (|\mathcal{X}| - 1) \log \left(\frac{d-1}{d-k}\right).$$
(81)

Therefore D(p||q) is bounded above by the same quantity.

Next, we apply a similar line of reasoning as the proof of Theorem 2 by considering collision-free sampling patterns. Let  $\mathbf{W} = (W_1, \dots, W_k)$  be i.i.d. uniformly over [d] and let  $\mathbf{Y} = (X_{W_1}, \dots, X_{W_k})$ . By definition,  $\mathbf{Y}$  is distributed according to  $q(\mathbf{x})$ . Next, define the set of all collision-free sample patterns as  $\mathcal{F} = \{\mathbf{w} \in [d]^k \mid w_i \neq w_j \text{ for all } i \neq j\}$ . It follows that:

$$q(\mathbf{x}) = \sum_{\mathbf{w} \in [d]^k} \Pr(\mathbf{W} = \mathbf{w}) \Pr(\mathbf{Y} = \mathbf{x} | \mathbf{W} = \mathbf{w})$$
$$\geq \sum_{\mathbf{w} \in \mathcal{F}} \Pr(\mathbf{W} = \mathbf{w}) \Pr(\mathbf{Y} = \mathbf{x} | \mathbf{W} = \mathbf{w})$$
$$= \sum_{\mathbf{w} \in \mathcal{F}} \frac{1}{d^k} p(\mathbf{x}) = \frac{d^k}{d^k} p(\mathbf{x}).$$
(82)

Therefore, we have that

$$D(p||q) \le \log\left(\frac{d^k}{d^k}\right).$$
 (83)

# APPENDIX D Converse for Scheduling

We prove (33) using a volume bound argument on the total number of possible scheduling patterns in relation to the maximum number of scheduling patterns can correspond to a single codeword. This allows us to show that the optimal common message rate is bounded from below as (33), i.e.,

$$R^* \ge k \log(b) - \log\left(\frac{n^k}{n^k}\right). \tag{84}$$

We begin by considering the total number of scheduling patterns. This amounts to the number of ways to select k users out of n users, then assigning them each a distinct value from [b]. By a simple counting argument, there are a total of

$$\binom{n}{k}\binom{b}{k}k! \tag{85}$$

possible scheduling patterns.

Next, we characterize  $d_{\max}$  defined as the maximum number of scheduling patterns that a single codeword can correspond to. Let  $\mathbf{v} = [v_1, \ldots, v_b]^T$ , where  $v_\ell$  is the number of times  $\ell$ occurs in the entries of the codeword. We have  $\sum_{\ell=1}^{b} v_\ell = n$ . The total number of different scheduling patterns that can correspond to this codeword is

$$\sum_{\mathcal{U} \in \binom{[b]}{k}} \prod_{\ell \in \mathcal{U}} v_{\ell} \tag{86}$$

where  $\binom{[b]}{k}$  is the set of all size-k subsets of [b], and the product corresponds to the number of ways to pick one user from each set of  $v_{\ell}$  entries where  $\ell$  occurs in the codeword. To find  $d_{\max}$ , we optimize over **v** 

$$\mathbf{v}^* = \arg\max_{\mathbf{v}} \sum_{\mathcal{U} \in \binom{[b]}{k}} \prod_{\ell \in \mathcal{U}} v_\ell = \arg\max_{\mathbf{v}} \sum_{\mathcal{U} \in \binom{[b]}{k}} k! \prod_{\ell \in \mathcal{U}} \frac{v_\ell}{n}.$$
(87)

The objective on the right-hand side can be interpreted as the probability that k i.i.d. samples from the distribution  $\left(\frac{v_1}{n}, \dots, \frac{v_b}{n}\right)$  have distinct values. In [5], it is shown that this probability is maximized by the uniform distribution over [b]. This shows that the optimal  $v_{\ell} = \frac{n}{b}$  for all  $\ell \in [b]$  and

$$d_{\max} = \binom{b}{k} \left(\frac{n}{b}\right)^k.$$
 (88)

Let T denote the output of an encoder f designed to communicate a particular schedule without error to the k active users out of a total of n users. Since there are  $\binom{n}{k}\binom{b}{k}k!$  ways to schedule k users into b slots and that a single codeword can only cover  $d_{\text{max}}$  different schedules, we have that

$$\Pr(T=t) \le \frac{d_{\max}}{\binom{n}{k}\binom{b}{k}k!} = \frac{n^{\underline{k}}}{b^k n^k}.$$
(89)

Therefore

$$H(T) = -\sum_{t} \Pr(T = t) \log(\Pr(T = t))$$
  

$$\geq -\sum_{t} \Pr(T = t) \log\left(\frac{n^{\underline{k}}}{b^{\underline{k}}n^{\underline{k}}}\right) \qquad (90)$$
  

$$= k \log(b) - \log\left(\frac{n^{\underline{k}}}{n^{\underline{k}}}\right).$$

### APPENDIX E CONVERSE FOR CATEGORIZATION

We use a volume bound argument to show (37), i.e. for the problem of categorization, the optimal common message rate is bounded from below as

$$R^* \ge kH(\rho) - \log\left(\frac{n^k}{n^{\underline{k}}}\right),\tag{91}$$

where  $\rho = \left(\frac{k_1}{k}, \cdots, \frac{k_c}{k}\right)$ .

We begin by characterizing the number of ways k out of n users can be categorized. This amounts to choosing k users amongst n, then splitting and assigning them into c categories, where the sizes of the categories are fixed to be  $k_{\ell}$  for all  $\ell \in [c]$ . By simple counting, there are a total of

$$\binom{n}{k}\binom{k}{k_1\cdots k_c} \tag{92}$$

categorization patterns.

Next, we upper bound  $d_{\max}$ , which is defined to be the maximum number categorization patterns that a single codeword can correspond to. Let  $\mathbf{v} = [v_1, \ldots, v_b]^T$ , where  $v_\ell$  is the number of times  $\ell$  occurs in the entries of the codeword. We have  $\sum_{\ell=1}^{b} v_\ell = n$ . Then, the number of different categorization patterns covered by this codeword is

$$\prod_{\ell=1}^{c} \binom{v_{\ell}}{k_{\ell}} \le \prod_{\ell=1}^{c} \frac{v_{\ell}^{k_{\ell}}}{k_{\ell}!}.$$
(93)

To upper bound  $d_{\text{max}}$ , we optimize over v. Notice that

$$\arg\max_{\mathbf{v}} \prod_{\ell=1}^{c} \frac{v_{\ell}^{k_{\ell}}}{k_{\ell}!} = \arg\min_{\mathbf{v}} - \sum_{\ell=1}^{c} \frac{k_{\ell}}{k} \log\left(\frac{v_{\ell}}{n}\right).$$
(94)

The objective of the right hand side is equivalent to minimizing the KL divergence between  $\left(\frac{k_1}{k}, \dots, \frac{k_c}{k}\right)$  and  $\left(\frac{v_1}{n}, \dots, \frac{v_c}{n}\right)$ .

Therefore, we should set  $v_{\ell}^* = \frac{nk_{\ell}}{k}$  which yields the upper bound

$$d_{\max} \le \prod_{\ell=1}^{c} \frac{\left(\frac{nk_{\ell}}{k}\right)^{\kappa_{\ell}}}{k_{\ell}!}.$$
(95)

Let T denote the output of an encoder f designed to communicate a particular categorization without error to the k active users out of a total of n users. Since there are  $\binom{n}{k}\binom{k}{k_1\cdots k_c}$  ways to categorize k users and that a single codeword can only cover  $d_{\max}$  different categorizations, we have that

$$\Pr(T=t) \le \frac{d_{\max}}{\binom{n}{k}\binom{k}{k_1 \cdots k_c}}.$$
(96)

Therefore,

$$H(T) = -\sum_{t} \Pr(T = t) \log(\Pr(T = t))$$

$$\geq -\sum_{t} \Pr(T = t) \log\left(\frac{d_{\max}}{\binom{n}{k}\binom{k}{k_{1}\cdots k_{c}}}\right)$$

$$= \log\left(\binom{n}{k}\binom{k}{k_{1}\cdots k_{c}}\frac{1}{d_{\max}}\right)$$

$$\geq kH(\rho) - \log\left(\frac{n^{k}}{n^{k}}\right).$$
(97)
$$APPENDIX F$$
PROOF OF THEOREM 4

The proof is similar to that of Theorem 1. We use the same codebook as in Section II and also the same decoders. For the encoder, we modify it slightly to accommodate a varying number of users.

For a codebook  $\mathbf{m} = (\mathbf{c}^{(1)}, \mathbf{c}^{(2)}, \cdots)$ , define

$$f_{\mathbf{m}}(x_1, \cdots x_K, a_1, \cdots a_K) = \min \quad t$$
(98)  
s.t.  $c_{a_i}^{(t)} = x_i, \; \forall i \in [K].$ 

Let  $T = f_{\mathbf{M}}(X_1, \dots, X_K, A_1, \dots, A_K)$  be the index of the first matching codeword for a random source and a random activity pattern, along with a randomly generated codebook  $\mathbf{M}$ , where the entries of the codewords in  $\mathbf{M}$  are generated in an i.i.d. fashion according to p(x). By the same logic as the proof of Theorem 1, we know that

$$\mathbb{E}[\log(T)|K=k] \le kH(p). \tag{99}$$

Therefore,

$$\mathbb{E}[\log(T)] \le \mathbb{E}[K]H(p). \tag{100}$$

Combining this with (59), we have that

$$H(T) \le \mathbb{E}[K]H(p) + \log(\mathbb{E}[K]H(p) + 1) + 1.$$
 (101)

# APPENDIX G Proof of Theorem 6

In order to lower bound the relative entropy D(h||q), we first lower bound the cross-entropy using Jensen's inequality, i.e.

$$\sum_{\mathbf{x}\in[d]^{k}} h(\mathbf{x}) \log\left(\frac{1}{q(\mathbf{x})}\right) = \mathbb{E}\left[\log\left(\frac{1}{q(\mathbf{x})}\right)\right]$$
$$\geq \log\left(\frac{1}{\mathbb{E}[q(\mathbf{x})]}\right).$$
(102)

It remains to establish an upper bound on  $\mathbb{E}[q(\mathbf{x})]$ . To do so, we take inspiration from [5]. Let

$$\mathcal{B} = \{ \mathbf{x} \in [d]^k : x_i = x_j \text{ for some } i \neq j \}.$$
(103)

By definition of h, we know that  $h(\mathbf{x}) = 0$  for all  $\mathbf{x} \in \mathcal{B}$ . Therefore

$$\mathbb{E}[q(\mathbf{x})] = \sum_{\mathbf{x}\in\mathcal{B}^{\mathsf{c}}} h(\mathbf{x})q(\mathbf{x}) = \left(\binom{d}{k}k!\right)^{-1} \sum_{\mathbf{x}\in\mathcal{B}^{\mathsf{c}}} q(\mathbf{x}).$$
 (104)

From [5], we know that the i.i.d. mixture distribution that maximizes  $\sum_{\mathbf{x}\in\mathcal{B}^c} q(\mathbf{x})$  is the distribution that is uniform over  $[d]^k$ . Therefore

$$\mathbb{E}[q(\mathbf{x})] \le \left(\binom{d}{k}k!\right)^{-1} \sum_{\mathbf{x}\in\mathcal{B}^{c}} \frac{1}{d^{k}} = \left(\binom{d}{k}k!\right)^{-1} \frac{d^{k}}{d^{k}}.$$
 (105)

Combining the above bounds, we have that

$$D(h||q) = \mathbb{E}\left[\log\left(\frac{1}{q(\mathbf{x})}\right)\right] - H(\mathbf{X})$$
  

$$\geq \log\left(\binom{d}{k}k!\right) + \log\left(\frac{d^k}{d\underline{k}}\right) - H(\mathbf{X}) \quad (106)$$
  

$$= \log\left(\frac{d^k}{d\underline{k}}\right).$$

#### REFERENCES

- R. Song, K. M. Attiah, and W. Yu, "Coded categorization in massive random access," in *IEEE Int. Symp. Inf. Theory (ISIT)*, 2022, pp. 2868– 2873.
- [2] —, "Coded downlink massive random access," in *IEEE Int. Symp. Info. Theory (ISIT)*, 2023, pp. 2015–2020.
- [3] Z. Chen, F. Sohrabi, and W. Yu, "Sparse activity detection for massive connectivity," *IEEE Trans. Signal Process.*, vol. 66, no. 7, pp. 1890– 1904, Apr. 2018.
- [4] Z. Chen, F. Sohrabi, Y.-F. Liu, and W. Yu, "Phase transition analysis for covariance-based massive random access with massive MIMO," *IEEE Trans. Inf. Theory*, vol. 68, no. 3, pp. 1696–1715, 2022.
- [5] P. Diaconis and D. Freedman, "Finite exchangeable sequences," Ann. Probab., vol. 8, no. 4, pp. 745 – 764, 1980. [Online]. Available: https://doi.org/10.1214/aop/1176994663
- [6] J. Kang and W. Yu, "Minimum feedback for collision-free scheduling in massive random access," *IEEE Trans. Inf. Theory*, vol. 67, no. 12, pp. 8094–8108, Dec. 2021.
- [7] A. J. Stam, "Distance between sampling with and without replacement," *Stat. Neerl.*, vol. 32, no. 2, pp. 81–91, Jun. 1978.
- [8] P. Harremoës and F. Matúš, "Bounds on the information divergence for hypergeometric distributions," *Kybernetika*, p. 1111–1132, Jan. 2021. [Online]. Available: http://dx.doi.org/10.14736/kyb-2020-6-1111
- [9] L. Gavalakis and I. Kontoyiannis, "An information-theoretic proof of a finite de Finetti theorem," *Electron. Commun. Probab.*, vol. 26, pp. 1 – 5, 2021. [Online]. Available: https://doi.org/10.1214/21-ECP428
- [10] —, "Information in probability: Another information-theoretic proof of a finite de finetti theorem," in *Mathematics Going Forward: Collected Mathematical Brushstrokes*, J.-M. Morel and B. Teissier, Eds. Springer, 2023, pp. 367–385. [Online]. Available: https://doi.org/10.1007/978-3-031-12244-6\_26
- [11] M. Berta, L. Gavalakis, and I. Kontoyiannis, "A third informationtheoretic approach to finite de Finetti theorems," 2023. [Online]. Available: https://arxiv.org/abs/2304.05360
- [12] J. Cichoń and Z. Gołębiewski, "On Bernoulli sums and Bernstein polynomials," *Discrete Math. Theor. Comput. Sci. (DIMACS)*, vol. AQ. 2012, pp. 179–190, Jan. 2012. [Online]. Available: http://dx.doi.org/10.46298/dmtcs.2993
- [13] Y. Polyanskiy and Y. Wu, Information Theory: From Coding to Learning. Cambridge University Press, 2024.
- [14] D. Freedman, "A remark on the difference between sampling with and without replacement," J. Am. Stat. Assoc., vol. 72, no. 359, pp. 681–681, 1977. [Online]. Available: https://www.tandfonline.com/doi/abs/10.1080/01621459.1977.10480637

- [15] C. T. Li and A. E. Gamal, "Strong functional representation lemma and applications to coding theorems," *IEEE Trans. Inf. Theory*, vol. 64, no. 11, pp. 6967–6978, 2018.
- [16] T. M. Cover and J. A. Thomas, *Elements of Information Theory*. Wiley, 2006.