MULTILINGUAL AUDIO-VISUAL SPEECH RECOGNITION WITH HYBRID CTC/RNN-T FAST CONFORMER

Maxime Burchi^{1,2*}, Krishna C. Puvvada¹, Jagadeesh Balam¹, Boris Ginsburg¹, Radu Timofte²

¹NVIDIA, USA

²Computer Vision Lab, CAIDAS & IFI, University of Würzburg, Germany

ABSTRACT

Humans are adept at leveraging visual cues from lip movements for recognizing speech in adverse listening conditions. Audio-Visual Speech Recognition (AVSR) models follow similar approach to achieve robust speech recognition in noisy conditions. In this work, we present a multilingual AVSR model incorporating several enhancements to improve performance and audio noise robustness. Notably, we adapt the recently proposed Fast Conformer model to process both audio and visual modalities using a novel hybrid CTC/RNN-T architecture. We increase the amount of audio-visual training data for six distinct languages, generating automatic transcriptions of unlabelled multilingual datasets (VoxCeleb2 and AVSpeech). Our proposed model achieves new state-ofthe-art performance on the LRS3 dataset, reaching WER of 0.8%. On the recently introduced MuAViC benchmark, our model vields an absolute average-WER reduction of 11.9% in comparison to the original baseline. Finally, we demonstrate the ability of the proposed model to perform audio-only, visual-only, and audio-visual speech recognition at test time.

Index Terms— audio-visual speech recognition, multilingual, noise robustness, generated transcriptions

1. INTRODUCTION

Audio-Visual Speech Recognition (AVSR) has attracted a lot of research attention in recent years due to its ability to use image processing techniques to aid speech recognition systems. Preceding works have shown that including the visual modality of lip movements could improve the robustness of ASR systems with respect to audio noise while achieving better recognition performance [1, 2, 3, 4, 5, 6, 7]. Son *et al.* [1] proposed to use the sequence-to-sequence encoderdecoder with attention architecture to recognise phrases and sentences being spoken by talking faces, with or without the audio. Petridis *et al.* [4] applied the hybrid CTC/attention architecture to AVSR, achieving better performance and robustness using an early fusion strategy. Ma *et al.* [6] proposed to encode audio and visual modalities with Conformer [8] networks to model both local and global temporal relationships using convolution and attention. More recently, AVEC [7] added intermediate CTC losses [9] in encoder networks to improve lip reading performance and AVSR robustness.

Supervised AVSR approaches have shown promising results with stronger audio noise robustness but still rely on a limited amount of human-annotated speech data compared to classical ASR systems. This is especially the case for non-English languages, for which the amount of available data is not as important. Serdyuk *et al.* [10] and Chang *et al.* [11] showed that performance could greatly be improved using large scale datasets of up to 100k hours composed of YouTube videos. However, these datasets remain private and unusable for comparison. LRS3 [12], which is the largest publicly available AVSR dataset, contains less than 450 training hours of audio-visual speech while LRW [13] and LRS2 [3] datasets are only available to academic institutions. The MuAViC corpus [14], which was recently released as benchmark for multilingual AVSR, contains only 10 hours of German speech.

To remedy this problem, other works started to focus on using self-supervised pre-training techniques [15, 16, 17, 18, 19] to improve performance by learning hidden representations with large scale unlabeled datasets. AV-HuBERT [15] was the first self-supervised system to jointly learn speech representations from audio and video. It iteratively learns to minimize a masked prediction loss by first clustering acoustic features (MFCC) and then audio-visual hidden features using k-means. RAVen [16] proposed to pre-train unimodal encoders by predicting cross-modal representations of slowmoving teacher networks. VATLM [19] proposed a visualaudio-text model optimized to predict the hidden units of different modalities with a unified masked prediction task. AVdata2vec [18] learns to predict the unmasked audio-visual output representations of a slow-moving teacher network. All these methods successfully improve generalization and performance by pre-training on the VoxCeleb2 [20] dataset with various pretext tasks. However, they can be complex to pre-train and still require to be fine-tuned.

More recently, Ma *et al.* [21] showed that state-of-the-art performance could simply be achieved by training on generated transcriptions. They first generate English transcriptions of VoxCeleb2 and AVSpeech datasets using Whisper [22] and use them to increase the amount of training data avail-

^{*}Work done during an internship at NVIDIA



Fig. 1. Audio-Visual Fast Conformer architecture. The model is trained end-to-end using CTC and RNN-T losses and takes both audio waveforms and lip movements as inputs.

able. Inspired by this work, we study the impact of generated transcriptions on six languages using large scale multilingual datasets. This paper brings four main contributions:

- A novel hybrid architecture for AVSR using both Connectionist Temporal Classification (CTC) [23] and Recurrent Neural Network Transducer (RNN-T) [24] losses.
- The use of generated transcriptions from large scale multilingual datasets (VoxCeleb2 and AVSpeech) to improve non-English AVSR performance and robustness.
- New state-of-the-art results on the LRS3 [12] dataset and the recently introduced MuAViC [14] benchmark.
- The ability to use a single model for audio-only, visualonly and audio-visual speech recognition at test time using modality masking before audio-visual fusion.

2. MODEL ARCHITECTURE

Our model design is based on the recently proposed Fast Conformer ASR architecture [25]. The Fast Conformer brings compute-memory savings compared to Conformer by further downsampling the input audio mel-spectrogram by a factor of 2. It increases the sampling period from 10ms to 80ms using 3 depth-wise convolutional sub-sampling layers. We adapt this architecture to AVSR by processing both audio and visual inputs, adding a ResNet-based front-end network for visual preprocessing and adopting an early fusion strategy [4]. We train our models using both CTC and RNN-Transducer losses, disposing of the need to train both models separately while improving RNN-T performance. The model has 18 Conformer encoder blocks with 512 hidden dimensions and a single layer LSTM [26] decoder with 640 hidden dimensions. For audiovisual models, each modality is first processed separately by 10 Conformer blocks using unimodal encoders while 8 blocks are dedicated to the audio-visual encoder. This results in a total of 119M, 130M and 197M parameters for the audio-only, visual-only and audio-visual models, respectively. The complete audio-visual model architecture is shown in Figure 1.

2.1. Visual Front-End

Similar to preceding works, we process input videos using a modified ResNet-18 [27, 6] where the first layer is a spatiotemporal convolutional layer with kernel size $5 \times 7 \times 7$. The resulting feature maps are average-pooled along spatial dimensions and downsampled using a strided temporal convolution layer. The resulting signal has a 80ms sampling period.

2.2. Modality Fusion

We use an early fusion strategy [4] to learn audio-visual features and reduce model complexity. The acoustic and visual features are concatenated and fed into a joint feed-forward network. We also apply a modality dropout [15] scheme during training to counter a common failure case where audiovisual models tend to ignore the visual modality [3]. Modality dropout is performed by masking one of the two modalities 30% of the time before fusion. This requires the network to learn from both modalities while allowing unimodal inference at test time by masking one of the two modality signals.

2.3. Hybrid CTC/RNN-T loss

The network is trained end-to-end using the RNN-Transducer objective with an additional CTC loss, as follows:

$$Loss = (1 - \alpha)L_{RNNT} + \alpha L_{CTC} \tag{1}$$

Where α is a loss scaling constant that we fix to 0.3 in every experiment. Table 5 compares the final performance of CTC, RNN-Transducer and hybrid networks on the LRS3 test set.

3. EXPERIMENTS

3.1. Datasets

We conduct experiments on two publicly available audiovisual datasets, both extracted from TED and TEDx talks: LRS3 [12], which is an English only AVSR dataset, and MuAViC [14], which is multilingual. LRS3 is the largest publicly available English AVSR dataset, including 438.9 hours of audio-visual speech. It is composed of a pre-training set (408 hours), a training-validation set (30 hours) and a test set (0.9 hours) for evaluation. The MuAViC dataset was recently introduced as a multilingual audio-visual corpus. The corpus includes 1200 hours of transcribed audio-visual speech from over 8k speakers in 9 languages: English (en), Arabic (ar), German (de), Greek (el), Spanish (es), French (fr), Italian (it), Portuguese (pt) and Russian (ru). Where the English subset is the addition of LRS3 pre-training and training-validation sets, which we refer to as LRS3 throughout the paper. In this work,

we concentrate on Romance and Germanic language subsets for English, Spanish, French, Portuguese Italian and German. We extract additional audio-visual speech data from the large scale VoxCeleb2 (VC2) [20] and AVSpeech (AVS) [28] datasets to increase the amount of training data per language. VC2 contains approximately 2400 hours of videos extracted from YouTube with a million utterances by 6000+ celebrities. while AVSpeech has 4700 hours from 150k speakers. Both datasets include a wide variety of people, languages, and face poses. We detect language ids and generate transcriptions for each audio segment using Whisper Large [22], a 1.55B parameters multilingual model trained on 680k hours of speech data. For English segments, we use a 1.1B parameter Fast Conformer XXL [25] model pre-trained on LibriLight and fine-tuned on 24.5k hours of English speech. Table 1 shows the total amount of training hours per dataset and language.

Table 1. Number of audio-visual speech hours.

Detect	Number of training hours per language							
Dataset	en	es	fr	pt	it	de	all	
LRS3 / MuAViC	435	176	173	152	99	10	1046	
VoxCeleb2 (generated)	1252	37	109	8	36	153	1595	
AVSpeech (generated)	1429	257	115	312	66	136	2316	
Total generated	2681	294	224	319	102	289	3910	
Total	3116	470	398	472	201	299	4957	

3.2. Implementation details

For visual pre-processing, we follow previous works [6, 7] to prepare all the datasets. The RetinaFace [29] face detector is used to detect speaker faces. We then remove differences related to rotation and scale by cropping speaker lip regions using bounding boxes of 96×96 pixels to facilitate recognition. We localize 68 face landmarks using a Face Alignment Network [30] to align the speaker face and crop lip regions. The cropped images are then converted to grayscale.

For data augmentation, we apply Spec-Augment [31] to audio mel-spectrograms with mask size parameter F = 27and ten time masks with adaptive size pS = 0.05. We also add babble noise from the NoiseX corpus [32] during training, as done in previous works [6, 7]. On the visual side, we apply random cropping with crop size 88×88 , horizontal flipping and time masking [33]. We apply center crop at test time.

We first train audio-visual, audio-only and visual-only models on the LRS3 dataset augmented with Voxceleb2 and AVSpeech English transcriptions. Ma *et al.* [21] pre-train the visual-only models on the LRW dataset using a word classification task to facilitate early convergence and improve final performance. However, since we do not have access to this dataset, we first train the audio-visual model and use the ResNet-18 weights as initialization for the visual-only model. We also add intermediate CTC losses [34] every 3 Conformer blocks to the visual-only model encoder to speed up convergence. Training is done using the AdamW [35] optimizer with $\beta_1 = 0.9$, $\beta_2 = 0.98$ and a 1e-3 weight decay. The models are trained for 100k gradient steps with a global batch size of 2048 samples. The learning rate is ramped up linearly to 0.001 during the first 5k steps, held constant until 15k steps and decayed following an inverse square root schedule. An Exponential Moving Average (EMA) model with 0.9999 momentum is updated along training for evaluation.

For MuAViC, we train monolingual and multilingual models with encoder weights initialized from English pretrained networks. We use a SentencePiece [36] byte-pairencoding tokenizer with 256 tokens per language. Multilingual tokenization is done using an aggregated tokenizer [37], where each language is given a range of tokens and the corresponding range is used during decoding. Multilingual models are trained for 100k steps while monolingual models are trained until convergence, for no more than 1000 epochs.

3.3. Results on LRS3

Table 2 compares the Word Error Rates (WER) of our English models with recently published methods on the LRS3 test set. Our audio-only and audio-visual models achieve new state-of-the-art results with WER of 0.7% and 0.8%, respectively. Our lip reading network competes with self-supervised approaches with 25.5% WER. However, it still lags behind Auto-AVSR [21] whose visual-only model has 250.4M parameters, trains on additional LRS2 human-labeled transcriptions and uses an external language model during decoding.

Table 2. Comparison of WER (%) on the LRS3 test set with recently published methods for Audio-Visual (AV), Audio-Only (A) and Visual-Only (V) speech recognition models. * Shows number of encoder params instead of total params. [‡] Use of additional audio, audio-text and text data [19, 17].

Mathad	AV model	Training	Total	LRS	LRS3 test W	
Method	Params	Datasets	Hours	AV	Α	V
CM-seq2seq [6]	92M	LRW,LRS3	595	2.3	2.3	43.3
AVEC [7]	61M	LRW,LRS2&3	818	1.8	2.0	37.5
AV-HuBERT [15, 18]	103M*	LRS3,VC2	1759	1.8	2.0	34.8
RAVen [16]	41M*	LRS3,VC2	1759	-	1.9	33.1
VATLM [19] [‡]	103M*	LRS3,VC2	1759	1.7	-	34.2
AV-data2vec [18]	103M*	LRS3,VC2	1759	1.4	1.7	32.9
AV-HuBERT [15, 38]	325M*	LRS3,VC2	1759	1.4	1.3	28.6
RAVen [16]	328M*	LRS3,VC2	1759	-	1.4	28.2
VATLM [19] [‡]	325M*	LRS3,VC2	1759	1.2	-	28.4
u-HuBERT [17] [‡]	325M*	LRS3,VC2	1759	1.2	1.4	27.2
AV-data2vec [18]	325M*	LRS3,VC2	1759	1.3	1.4	28.5
Auto-AVSR [21]	425M	+LRW,LRS2,AVS	3448	0.9	1.0	19.1
VIT 3D [10]	310M	YouTube-90k	90k	1.6	-	17.0
VGG Conformer [39]	180M	YouTube-100k	100k	0.9	1.0	-
LP Conformer [11]	570M	YouTube-100k	100k	0.9	-	12.8
		LRS3	435	1.7	1.6	43.8
Fast Conformer	197M	LRS3,VC2	1687	0.9	0.7	31.0
		LRS3,VC2,AVS	3116	0.8	0.7	25.5

We evaluate our English models robustness, adding babble noise and white noise with multiple Signal to Noise Ratio (SNR) during test time. Table 3 compares the robustness of our model with Auto-AVSR on the LRS3 test set. We observe that our models can recover similar audio robustness by training on generated transcriptions while using half the number of training parameters. It also shows that audio-only models can easily overfit to babble noise, demonstrating the importance of evaluating on noises not encountered during training.

Mathad	Mode	Num Audio		test time SNR level (dB)				
Wiethou	Moue	e Params	Noise	12.5	7.5	2.5	-2.5	-7.5
Auto AVSP [21]	A	243M	243M	1.1	1.2	1.6	2.7	8.3
Auto-Av SK [21]	AV 425M babble	Dabble	1.0	1.0	1.5	2.2	5.6	
Fast Conformer	A	119M	babble [†]	0.9	1.2	1.8	3.5	10.9
	AV	197M		1.2	1.5	2.0	3.2	6.7
Auto AVSP [21]	A	243M	white	2.1	4.0	10.4	30.2	88.9
Auto-AVSK [21]	AV	425M	white	1.4	2.3	4.3	9.5	24.2
Fast Conformer	A	119M	white	1.5	2.8	6.9	17.6	54.8
	AV	197M	winte	1.3	2.1	3.2	5.7	21.4

Table 3. LRS3 test set WER (%) under noisy conditions. [†] Noise type used during both training and test time.

3.4. Results on MuAViC

Table 4 compares our monolingual and multilingual models WER with MuAViC baseline models fine-tuned from AV-HuBERT [38]. We also evaluate Whisper Large [22], which we use to generate transcriptions. We observe that our models trained solely on human-labeled transcriptions achieve better performance than the original work. Including additional generated transcriptions from VoxCeleb2 and AVSpeech datasets further improves performance for every language considered. This is especially the case for the German subset, which contains only 10 hours of human-labeled speech, improving audio-visual WER by almost 20%. Moreover, we find that multilingual models can successfully be trained to recover similar performance by training on all languages, achieving an absolute average WER reduction of 11.94% in comparison to the original baseline. Multilingual training also further improves robustness of audio-visual models, allowing the visual branch to learn from a wide variety of lip movements. Our model improves noisy WER by 28% compared to Whisper, which was trained on 680k hours of multilingual speech data.

Table 4. Comparison of WER (%) on the MuAViC dataset.

Mathad	Total Mode		Language test WER					
Method	Hours	Mode	es	fr	pt	it	de	avg
Whisper [22] (ours)	680k	А	7.6	9.4	11.3	8.7	20.4	11.5
Monolingual	2277	А	16.5	24.4	23.0	19.3	61.1	28.9
AV-HuBERT [14]	2311	AV	15.9	23.7	19.4	18.5	52.4	26.0
Multilingual	2467	А	30.6	27.0	19.8	19.3	46.5	28.6
AV-HuBERT [14]	2407	AV	16.2	19.0	19.9	19.8	47.2	24.4
Monolingual	2725	А	8.5	11.1	12.2	11.4	41.3	16.9
Fast Conformer	5755	AV	9.4	11.4	12.7	12.4	43.9	18.0
+ generated	4057	А	7.9	9.6	10.2	10.2	21.7	11.9
transcriptions	4937	AV	8.2	9.8	10.2	10.6	22.4	12.2
Multilingual	2725	А	8.8	11.4	11.5	11.0	43.4	17.2
Fast Conformer	5755	AV	9.0	11.4	11.8	11.6	46.8	18.1
+ generated	4057	А	8.2	10.6	9.9	10.2	23.4	12.5
transcriptions	4957	AV	8.2	10.3	9.9	10.4	23.6	12.5
(\downarrow) Adding White Noise with -5 SNR at test time (\downarrow)								
Whisper [22] (ours)	680k	А	56.3	61.3	72.4	59.4	69.2	63.7
Monolingual	3735	А	58.7	57.8	63.0	61.5	91.4	66.5
Fast Conformer	5155	AV	35.2	49.5	46.9	45.8	75.5	50.6
+ generated	4057	А	40.5	60.6	54.4	49.8	62.5	53.6
transcriptions	4937	AV	29.8	41.7	40.1	37.0	48.1	39.3
Multilingual	3735	А	52.3	63.0	65.4	59.4	94.5	66.9
Fast Conformer	5155	AV	35.1	41.9	42.4	37.5	87.0	48.8
+ generated	4957	А	44.9	52.9	55.9	50.0	69.0	54.5
transcriptions	4931	AV	28.2	35.1	34.7	30.3	50.3	35.7

3.5. Learning Objective

We study the effect of the optimization architecture on final performance. Table 5 compares the WER of CTC, RNN-

T and hybrid models on the LRS3 test set. We find that adding a CTC loss slightly helps to improve RNN-T performance. Moreover, the hybrid CTC/RNN-T architecture can be used for CTC and RNN-T decoding without the need to train both networks separately. Following [7], we also experiment adding intermediate CTC losses [34] every 3 Conformer blocks and find it to further improve lip reading performance.

 Table 5. Effect of loss type on Fast Conformer performance.

Logo Type	Training	CTC / RNN-T LRS3 test WER (%)				
Loss Type	Datasets	AV	Α	V		
CTC	LRS3	2.3	2.1	49.7		
RNN-T	LRS3	1.9	1.8	47.7		
CTC / RNN-T	LRS3	2.3 / 1.7	2.0/1.6	49.8 / 45.9		
InterCTC / RNN-T	LRS3	2.3 / 1.7	1.9/1.6	48.7 / 43.8		
CTC / RNN-T	LRS3,VC2,AVS	1.4 / 0.8	1.1/0.7	31.1 / 27.0		

3.6. Unimodal Inference

We study the effect of using InterCTC [34] and modality dropout [15] during training on unimodal inference results. Table 6 shows the LRS3 test WER when masking one of the two modalities in the fusion module at test time. We find that training without InterCTC nor modality dropout leads the model to ignore the visual modality. ASR being a substantially easier task than lip reading, the model does not need to learn visual representations to achieve good performance. Forcing the visual encoder to learn hidden representations using one of these two methods solves the problem. We find that solely using modality dropout during training is sufficient to avoid this issue and allows the model to be used in audio-only mode at test time with a minimum loss of performance.

Table 6. Effect of using InterCTC and/or modality dropout during training on unimodal inference performance.

Mathad	Training	AV model LRS3 test WER (%)				
Method	Datasets	no mask	mask video	mask audio		
Fast Conformer	LRS3	1.9	2.0	100.0		
+ InterCTC	LRS3	1.6	10.2	48.7		
+ mod drop	LRS3	1.7	1.8	44.0		
+ InterCTC	LRS3	1.7	1.9	44.0		
+ mod drop	LRS3,VC2,AVS	0.8	1.0	32.2		

4. CONCLUSION

In this work, we presented a multilingual AVSR model using several enhancements to improve performance and audio noise robustness. We adapted the recently proposed Fast Conformer model to process both audio and visual modalities using a novel hybrid CTC/RNN-T architecture. We increased the amount of audio-visual training data for six distinct languages by generating automatic transcriptions of large scale multilingual datasets. Our hybrid audio-visual Fast Conformer model achieved new state-of-the-art results on the LRS3 dataset, reaching WER of 0.8%. On the recently released MuAViC benchmark, our model yields an absolute average-WER reduction of 11.9% compared to the original baseline. Models and training recipes will be open-sourced through the NVIDIA NeMo toolkit [40].

5. REFERENCES

- [1] J. Son Chung et al., "Lip reading sentences in the wild," in *CVPR*, 2017, pp. 6447–6456.
- [2] G. Sterpu et al., "Attention-based audio-visual fusion for robust automatic speech recognition," in *ICMI*, 2018, pp. 111–115.
- [3] T. Afouras et al., "Deep audio-visual speech recognition," *IEEE TPAMI*, vol. 44, no. 12, pp. 8717–8727, 2018.
- [4] S. Petridis et al., "Audio-visual speech recognition with a hybrid ctc/attention architecture," in *SLT*, 2018, pp. 513–520.
- [5] B. Xu et al., "Discriminative multi-modality speech recognition," in CVPR, 2020, pp. 14433–14442.
- [6] P. Ma et al., "End-to-end audio-visual speech recognition with conformers," in *ICASSP*, 2021, pp. 7613–7617.
- [7] M. Burchi and R. Timofte, "Audio-visual efficient conformer for robust speech recognition," in WACV, 2023, pp. 2258– 2267.
- [8] A. Gulati et al., "Conformer: Convolution-augmented transformer for speech recognition," arXiv preprint arXiv:2005.08100, 2020.
- [9] J. Nozaki and T. Komatsu, "Relaxing the conditional independence assumption of ctc-based asr by conditioning on intermediate predictions," *arXiv preprint arXiv:2104.02724*, 2021.
- [10] D. Serdyuk et al., "Transformer-based video front-ends for audio-visual speech recognition for single and multi-person video," arXiv preprint arXiv:2201.10439, 2022.
- [11] O. Chang et al., "Conformers are all you need for visual speech recognition," *arXiv preprint arXiv:2302.10915*, 2023.
- [12] T. Afouras et al., "Lrs3-ted: a large-scale dataset for visual speech recognition," arXiv preprint arXiv:1809.00496, 2018.
- [13] J. Chung and A. Zisserman, "Lip reading in the wild," in *ACCV*. Springer, 2017, pp. 87–103.
- [14] M. Anwar et al., "Muavic: A multilingual audio-visual corpus for robust speech recognition and robust speech-to-text translation," arXiv preprint arXiv:2303.00628, 2023.
- [15] B. Shi et al., "Learning audio-visual speech representation by masked multimodal cluster prediction," *arXiv preprint arXiv:2201.02184*, 2022.
- [16] A. Haliassos et al., "Jointly learning visual and auditory speech representations from raw data," arXiv preprint arXiv:2212.06246, 2022.
- [17] W. Hsu and B.Shi, "u-hubert: Unified mixed-modal speech pretraining and zero-shot transfer to unlabeled modality," *NeurIPS*, vol. 35, pp. 21157–21170, 2022.
- [18] J. Lian et al., "Av-data2vec: Self-supervised learning of audiovisual speech representations with contextualized target representations," arXiv preprint arXiv:2302.06419, 2023.
- [19] Q. Zhu et al., "Vatlm: Visual-audio-text pre-training with unified masked prediction for speech representation learning," *IEEE Transactions on Multimedia*, 2023.
- [20] J. Chung et al., "Voxceleb2: Deep speaker recognition," arXiv preprint arXiv:1806.05622, 2018.

- [21] P. Ma et al., "Auto-avsr: Audio-visual speech recognition with automatic labels," in *ICASSP*, 2023, pp. 1–5.
- [22] A. Radford et al., "Robust speech recognition via large-scale weak supervision," in *ICML*, 2023, pp. 28492–28518.
- [23] A. Graves et al., "Connectionist temporal classification: labelling unsegmented sequence data with recurrent neural networks," in *ICML*, 2006, pp. 369–376.
- [24] A. Graves, "Sequence transduction with recurrent neural networks," arXiv preprint arXiv:1211.3711, 2012.
- [25] D. Rekesh et al., "Fast conformer with linearly scalable attention for efficient speech recognition," arXiv preprint arXiv:2305.05084, 2023.
- [26] S. Hochreiter and J. Schmidhuber, "Long short-term memory," *Neural computation*, vol. 9, no. 8, pp. 1735–1780, 1997.
- [27] K. He et al., "Deep residual learning for image recognition," in CVPR, 2016, pp. 770–778.
- [28] A. Ephrat et al., "Looking to listen at the cocktail party: A speaker-independent audio-visual model for speech separation," arXiv preprint arXiv:1804.03619, 2018.
- [29] J. Deng et al., "Retinaface: Single-shot multi-level face localisation in the wild," in CVPR, 2020, pp. 5203–5212.
- [30] A. Bulat and G. Tzimiropoulos, "How far are we from solving the 2d & 3d face alignment problem?(and a dataset of 230,000 3d facial landmarks)," in *ICCV*, 2017, pp. 1021–1030.
- [31] D. Park et al., "Specaugment on large scale datasets," in *ICASSP*, 2020, pp. 6879–6883.
- [32] A. Varga and HJM. Steeneken, "Noisex-92: A database and an experiment to study the effect of additive noise on speech recognition systems," *Speech Commun*, vol. 12, no. 3, pp. 247– 253, 1993.
- [33] M. Pingchuan et al., "Visual speech recognition for multiple languages in the wild," *Nature Machine Intelligence*, vol. 4, no. 11, pp. 930–939, 2022.
- [34] J. Lee and S. Watanabe, "Intermediate loss regularization for ctc-based speech recognition," in *ICASSP*. IEEE, 2021, pp. 6224–6228.
- [35] I. Loshchilov and F. Hutter, "Decoupled weight decay regularization," arXiv preprint arXiv:1711.05101, 2017.
- [36] T. Kudo and J. Richardson, "Sentencepiece: A simple and language independent subword tokenizer and detokenizer for neural text processing," *arXiv preprint arXiv:1808.06226*, 2018.
- [37] K. Dhawan et al., "Towards training bilingual and codeswitched speech recognition models from monolingual data sources," arXiv preprint arXiv:2306.08753, 2023.
- [38] B. Shi et al., "Robust self-supervised audio-visual speech recognition," arXiv preprint arXiv:2201.01763, 2022.
- [39] C. Oscar et al., "On robustness to missing video for audiovisual speech recognition," arXiv preprint arXiv:2312.10088, 2023.
- [40] O. Kuchaiev et al., "Nemo: a toolkit for building ai applications using neural modules," *arXiv preprint arXiv:1909.09577*, 2019.