Variational Offline Multi-agent Skill Discovery

Jiayu Chen Purdue University West Lafayette, IN 47907 chen3686@purdue.edu Bhargav Ganguly Purdue University West Lafayette, IN 47907 bganguly@purdue.edu

Vaneet Aggarwal Purdue University West Lafayette, IN 47907 vaneet@purdue.edu Tian Lan George Washington University Washington, DC 20052 tlan@gwu.edu

Abstract

Skills are effective temporal abstractions established for sequential decision making tasks, which enable efficient hierarchical learning for long-horizon tasks and facilitate multi-task learning through their transferability. Despite extensive research, research gaps remain in multi-agent scenarios, particularly for automatically extracting subgroup coordination patterns in a multi-agent task. In this case, we propose two novel auto-encoder schemes: VO-MASD-3D and VO-MASD-Hier, to simultaneously capture subgroup- and temporal-level abstractions and form multi-agent skills, which firstly solves the aforementioned challenge. An essential algorithm component of these schemes is a dynamic grouping function that can automatically detect latent subgroups based on agent interactions in a task. Notably, our method can be applied to offline multi-task data, and the discovered subgroup skills can be transferred across relevant tasks without retraining. Empirical evaluations on StarCraft tasks indicate that our approach significantly outperforms existing methods regarding applying skills in multi-agent reinforcement learning (MARL). Moreover, skills discovered using our method can effectively reduce the learning difficulty in MARL scenarios with delayed and sparse reward signals.

1 Introduction

Skill discovery aims at extracting useful temporal abstractions from decision-making or control sequences. With identified skills, the downstream policy learning can be much more efficient by simply composing these skills as trajectory segments into complex maneuvers. Moreover, skills can potentially be transferred among similar tasks to facilitate multi-task learning. Despite considerable research on single-agent skill discovery [1, 2, 3], skill discovery in MARL remains under-explored (A thorough review is provided in Appendix A). A straightforward approach is to discover single-agent skills for each agent independently and then learning a multi-agent meta policy to coordinate their use, as in [4, 5, 6]. However, multi-agent coordination can not be abstracted in such individual skills. On the other hand, there are a limited number of works [7, 8, 9] on discovering skills for the entire team of agents. However, in multi-agent tasks, coordination patterns can emerge within subgroups of varying scales (from 1 to n), and team skills (i.e., n-agent skills) only can be inflexible to use.

This paper focuses on automatically extracting collaborative patterns among agents from offline data as subgroup skills which represent flexible teamwork at dynamic scales. Complex multi-agent tasks can usually be decomposed as a series of subtasks, many of which do not require participation of all agents and can indeed be solved more effectively by identifying the right subgroup of agents. We note that most existing work on applying skills in MARL adopts online skill discovery. While agents

Preprint. Under review.

can explore various forms of collaboration in an online setting, offline multi-agent skill discovery in contrast must infer latent coordination patterns from agent interactions in the offline data, with the subgroup size arbitrarily varying from 1 to n. This gives rise to a combinatorial problem of dynamic subgroup division and forming temporal abstractions within each subgroup for skill discovery, which is a significant new challenge. To the best of our knowledge, this is the first work to fully automate the capture of collaborative patterns and subgroup skills from offline data. We also note that the problem is different from (online) role-based MARL [10, 11, 12, 13]. They instead focus on partitioning agents into subdivisions that consist of agents with similar responsibilities (i.e., roles), sharing the same policy and thus homogeneous behaviors. Our goal is to learn multi-agent skills – a collective set of single-agent skills taken by a subgroup where agents could have distinct yet coordinated behaviors.

In particular, we propose an effective auto-encoder framework for extracting embeddings of subgroup coordination patterns from offline data as a codebook, where each code corresponds to a multi-agent skill and should provide abstractions in both subgroup- and temporal-level. We provide two scheme designs for this purpose: VO-MASD-3D and VO-MASD-Hier. In VO-MASD-3D, three-dimensional codebooks are adopted, where each code is composed of several single-agent codes such that it can be used to represent subgroup behaviors. While in VO-MASD-Hier, we use a two-level codebook, where the top and bottom codes encode the joint and individual behaviors respectively. Further, to enable automatic grouping while forming temporal abstractions, we co-train a grouping function with the proposed auto-encoder schemes. Using this function, agents can be dynamically grouped, and each subgroup can then be assigned a multi-agent skill of the corresponding size. More importantly, our algorithm is designed to work with multi-task data, such that the discovered skills can be utilized in multiple relevant tasks (without retraining). Empirical results on challenging StarCraft tasks [14] demonstrate the superiority of the discovered multi-agent skills using our algorithm even in previously unseen tasks, and show the great advantages brought by the use of skills in long-horizon multi-agent tasks characterized by sparse reward signals.

2 Background

Dec-POMDP: This work focuses on a fully cooperative multi-agent setting with only partial observation for each agent, which can be modeled as a decentralized partially observable markov decision process (Dec-POMDP) [15] and described with a tuple $G = \langle n, I, S, O, F, A, \mu, P, R, \gamma \rangle$. At a time step, each agent $i \in I = \{1, \dots, n\}$ would obtain a local observation $o^i \in O$ from the observation function $F(s,i) : S \times I \to O$, where s is the real state of the environment, and determine its action $a^i \in A$. This would lead to a state transition in the environment according to the function $P(s' \mid s, \vec{a}) : S \times A^n \times S \to [0, 1]$ and all agents would receive a shared team reward $r = R(s, \vec{a}) : S \times A^n \to \mathbb{R}$. To mitigate the issue of partial observability, each agent i holds an action-observation history $\tau^i \in (O \times A)^*$ and decides on its action a^i based on a policy $\pi^i(a^i \mid \tau^i)$. The goal of multi-agent reinforcement learning (MARL) in a Dec-POMDP can be formally defined as $\max_{\vec{\pi}} \mathbb{E}_{\mu,\vec{\pi},P,R} [\sum_{t=0}^{\infty} \gamma^t r_t]$, where $\vec{\pi} = (\pi^1, \dots, \pi^n)$ and $\mu(s_0) : S \to [0, 1]$ denotes the distribution of the initial state.

CTDE: The paradigm of centralized training with decentralized execution (CTDE) [16] is proposed for solving Dec-POMDP and has gained substantial attention. In this paradigm, agents learn their policies with access to global information (e.g., the state s) during centralized training and only rely on their local action-observation histories for decentralized execution. Centralized training makes MARL more stable, while decentralized execution improves applicability of the learned policy. Notably, the discovered skills with our algorithm can be easily integrated into the CTDE paradigm and we select MAPPO [17] as the base CTDE MARL algorithm throughout this work. MAPPO has shown superior performance across various MARL benchmarks. It learns a decentralized actor $\pi(a_t^i \mid o_t^i, \tau_{t-1}^i)$, which can be shared among agents and used for each agent $i \in I$ to determine its action a_t^i based on its individual action-observation history (o_t^i, τ_{t-1}^i) , and a centralized critic $V(s_t)$. Viewing the n agents as a whole, the critic function is trained as in PPO [18], while the actor is trained to maximize the advantage function defined with the team reward and centralized critic.

Skill & Task Decomposition: In single-agent scenarios, skills [3] are used as temporal abstractions of an agent's behaviors. This is inspired by the fact that complex tasks can usually be decomposed as a sequence of subtasks and each subtask can be handled with a corresponding subpolicy, i.e., a skill. With skills, an agent learns a hierarchical policy, where the low-level part $\pi_l(a \mid s, z)$ is the skill policy and the high-level part $\pi_h(z \mid s)$ determines the skill selection. Each skill $z \in \Omega^z$, after being

selected, will be executed for H time steps – a predefined subtask duration. However, in multi-agent scenarios, task decomposition occurs not just at the temporal level but also at the agent level, since the overall multi-agent task can be solved as several subgroup tasks. Formally, a multi-agent task decomposition can be defined as follows:

Definition 1. Given a cooperative multi-agent task $\langle n, I, S, O, F, A, \mu, P, R, \gamma \rangle$, at a time step, it can be decomposed into a set of m subtasks, each of which is solved by a subgroup of agents for H time steps and can be represented as a tuple $\langle n_j, I_j, S, O, F, A, \mu, P, R_j, \gamma \rangle$. Here, $\sum_{j=1}^m n_j = n$, $\bigcup_j I_j = I$, and $I_j \cap I_k = \emptyset \ (\forall j \neq k)$.

Certain subtasks may frequently occur, such as passing and cutting cooperation among two or three players in a football match, and their subpolicies, showing coordination patterns, can be extracted as multi-agent skills and transferred across similar tasks for reuse. In this work, we propose an algorithm for discovering such multi-agent skills $Z \in \Omega^Z$ from multi-agent interaction data. The algorithm design is based on an inductive bias that multi-agent skills represent higher-level abstractions compared to single-agent skills (since subgroup division is required) and are, in fact, composed of these single-agent skills.

Related Works: In Appendix A, we provide a thorough review of research on applying skills in MARL, including MARL with single-agent skills, role-based MARL, and team skill discovery. We also compare our algorithm with each category of work to highlight our contributions, which we strongly encourage readers to review. As a summary, research on multi-agent skill discovery is still at an early stage, especially in the offline setting. Even without prelearned skills, when dealing with a complex multi-agent task, the agents would implicitly learn to decompose the overall task into several subtasks, assign a subgroup for each subtask, and develop a joint policy (i.e., multi-agent skill) within the subgroup to handle the corresponding subtask. Replacing primitive actions with single-agent skills or role policies could make such a learning process more efficient, as agents can assemble these higher-level abstractions to obtain the required subgroup joint polices more easily. As the first offline multi-agent skill discovery algorithm, our work takes one step further by directly identifying subgroups, which could change throughout a decision horizon, and extracting their coordination patterns as multi-agent skills. With these joint skills, the MARL process could be greatly simplified, since agents only need to select correct skills without considering grouping with others or forming subgroup policies (by assembling primitive actions or single-agent skills). Compared to single-agent skills or role policies, multi-agent skills make better use of the offline multi-agent interaction data, representing a more efficient form of knowledge discovery.

3 Proposed Approach

Variational Offline Multi-agent Skill Discovery (VO-MASD) aims to extract a finite set of multi-agent skills from given offline trajectories. Proposed for Computer Vision, VQ-VAE [19] provides a fundamental manner to learn discrete representations for complex, high-dimensional data. Besides the encoder and decoder as used in VAEs [20], a codebook containing a finite set of codes, each of which is a latent representation of the data, is learned. In this case, VQ-VAE is a natural choice for skill discovery, with each code working as a skill embedding Z. Each Z would correspond to a skill policy $\pi_l(\vec{a} \mid \vec{\tau}, Z)$ that leads to continuous multi-agent behaviors. In this section, we present two schemes of VO-MASD based on VQ-VAE by adopting novel codebook designs and involving an automatic grouping module. The intuition/challenge behind is to extract temporal-level abstractions (i.e., useful control sequences) and agent-level abstractions (i.e., multi-agent coordination) at the same time, without using domain knowledge or task-specific reward signals. In this way, VO-MASD can be applied to a mixture of multi-task data and the learned skills are generalizable to a distribution of relevant tasks.

3.1 VO-MASD based on 3D Codebooks

Typically, VQ-VAE would adopt a 2D codebook $[e_1, \dots, e_k] \in \mathbb{R}^{k \times d}$, where $e_i \in \mathbb{R}^{1 \times d}$ is a latent code. However, in our case, there are three levels of abstractions: primitive actions \rightarrow single-agent skills \rightarrow multi-agent skills. As part of our novelty, we propose to use 3D codebooks within $\mathbb{R}^{k \times m \times d}$ to represent a set of (i.e., k) m-agent skills. Here, each code $e_i = [e_{i,1}, \dots, e_{i,m}] \in \mathbb{R}^{m \times d}$ represents a multi-agent skill composed of m single-agent skills.



Figure 1: Multi-agent skill discovery based on a VQ-VAE with 3D codebooks.

A straightforward approach to utilize such codebook design for skill discovery is repeatedly applying a VO-VAE with an *m*-agent codebook to *m*-agent skill discovery, for $m = 1, \dots, n$, which can be executed as n parallel training processes. As some variational methods for single-agent skill discovery [21, 22], the objective for learning *m*-agent skills could be minimizing the reconstruction error of *m*-agent trajectory segments (of length *H*). Ideally, after training, each code can represent a coordination pattern among m agents and the code-conditioned decoder can be used as an m-agent skill policy. However, if there are no coordination patterns involving m agents in the offline data, the effort to discover *m*-agent skills would be wasted. Also, while the learning processes for skills involving different numbers of agents could potentially benefit from each other, this approach adopts independent learning processes for each of them.

In this case, we propose to introduce a grouping function h_{ψ} that dynamically groups agents throughout an episode to identify existing coordination patterns in the offline data and unify the training of skills with different numbers of agents. The skill discovery process is illustrated as Figure 1. As shown in (a), at time step t, for each agent i, we encode its following H time steps, i.e., $\tau^i = [o_t^i, a_t^i, \cdots, o_{t+H-1}^i, a_{t+H-1}^i]$, into a skill embeddings z_e^i using the encoder f_{θ} . Also, each agent i selects its group based on the global state s_t and group choices of previous agents $g^{1:i-1}$ using a grouping function h_{ψ} . There can be at most n groups, when all agents choose to use individual skills. Notably, both h_{ψ} and f_{θ} are shared by all agents. Subsequently, in (b), the skill embeddings $z_e^{1:n}$ from the encoder are first clustered based on the grouping result $g^{1:n}$. If m agents choose the same group, they aim to form an *m*-agent coordination skill and their respective embeddings will be concatenated in the sequence of their agent indices, resulting in an $m \times d$ joint embedding $z_{e^{1:m}}^{j}$. Then, as in VQ-VAE, the code that is the closest to $z_e^{j_{1:m}}$ in the *m*-agent codebook is queried to work as the decoder input, i.e., $z_q^{j_{1:m}}$. Finally, in (c), a decoder π_{ϕ} maps the skill code back to an *m*-agent trajectory segment, i.e., $\hat{\tau}^{j_{1:m}}$. Taking the subgroup $j_{1:m}$ as an example, the training objective is:

$$L^{3D}(\tau^{j_{1:m}}) = -\sum_{l=0}^{H-1} \sum_{i=1}^{m} \log \pi_{\phi}(a_{t+l}^{j_{i}} \mid o_{t+l}^{j_{i}}, z_{q}^{j_{i}}) + \sum_{i=1}^{m} \left[\|\operatorname{sg}(z_{e}^{j_{i}}) - e^{j_{i}}\|_{2}^{2} + \beta \|z_{e}^{j_{i}} - \operatorname{sg}(e^{j_{i}})\|_{2}^{2} \right]$$
(1)

As shown in Figure 1, $z_e^{j_i} = f_\theta(\tau^{j_i})$, $e^{j_{1:m}} = \arg\min_{e \in E_m} \|z_e^{j_{1:m}} - e\|_2$ (E_m denotes the *m*-agent codebook), and $z_q^{j_i} = e^{j_i}$. $L^{3D}(\tau^{j_{1:m}})$ is an objective with respect to (w.r.t.) θ, ϕ, E_m^{-1} . As in VQ-VAE, the first term in Eq. (1) is a reconstruction loss of trajectory segments², and the last two terms move the codebook (e.g., e^{j_i}) and encoder embeddings (e.g., $z_e^{j_i}$) towards each other, where sg represents the stop gradient operator. Through reconstructing *m*-agent ($m \in \{1, \dots, n\}$) trajectory segments in an auto-encoder framework, representations of *m*-agent skills can be extracted as codes in the codebook. The overall objective for VO-MASD-3D is as below:

$$\min_{\theta,\phi,E_{1:n}} L^{3\mathrm{D}} = \min_{\theta,\phi,E_{1:n}} \mathbb{E}_{\tau^{1:n} \sim \mathcal{D}_H} \sum_j L^{3\mathrm{D}}(\tau^{j_{1:m}})$$
(2)

Here, \mathcal{D}_H is a (multi-task) offline dataset with trajectories segmented every H time steps; each *n*-agent trajectory segment is partitioned into subgroups (e.g., $j_{1:m}$) based on the grouping function

¹In VQ-VAE, a straight-through gradient estimator [23] is used, so $\partial L^{3D}(\tau^{j_{1:m}})/\partial z_a^{j_i} = \partial L^{3D}(\tau^{j_{1:m}})/\partial z_e^{j_i}$

which is then backpropagated to f_{θ} . ²log $\mathbb{P}(\tau^{j_i} \mid o_t^{j_i}, z_q^{j_i}) = \sum_{l=0}^{H-1} \log \pi_{\phi}(a_{t+l}^{j_i} \mid o_{t+l}^{j_i}, z_q^{j_i}) + \sum_{l=0}^{H-2} \log P(o_{t+l+1}^{j_i} \mid o_{t+l}^{j_i}, a_{t+l}^{j_i})$, and the second term, i.e., transition function, is not learnable.

 h_{ψ} . Note that, unlike f_{θ} , $E_{1:n}$, and π_{ϕ} , h_{ψ} cannot be trained in an end-to-end manner by minimizing Eq. (2), since its output $g^{1:n}$ are used for clustering which is not an differentiable operation. Thus, we choose to optimize π_{ϕ} with MAPPO (an MARL algorithm), where each agent *i* takes an action g^{i} to maximize the global return $-L^{3D}$. In this way, all modules in the system (i.e., Figure 1) are effectively updated with a common objective.

Algorithm 1 MAPPO with learned skills

Input: π_{ω} , V_{η} , π_{ϕ} , h_{ψ} , $E_{1:n}$, Env Initialize π_{ω}, V_{η} while not converged do Buffer $\leftarrow \emptyset$ for $b = 1 \cdots B$ do Initialize $\tau_{-H}^{1:n}$, Traj $\leftarrow \emptyset$, $\tilde{r} \leftarrow 0$ for $t = 0 \cdots T$ do if t% H == 0 then $t_{t}^{\gamma_{0}H} == 0 \text{ men}$ $z_{t}^{i}, \tau_{t}^{i} \leftarrow \pi_{\omega}(o_{t}^{i}, \tau_{t-H}^{i}), i = 1 \cdots n$ Get $e^{1:n}$ based on $z_{t}^{1:n}$ using h_{ψ} and $E_{1:n}$, following Fig. 1 (b) Add $(\tilde{r}, s_t, o_t^{1:n}, \tau_{t-H}^{1:n}, z_t^{1:n})$ to Traj $\tilde{r} \leftarrow \dot{0}$ end if $\begin{aligned} a_t^i \leftarrow \pi_\phi(o_t^i | e^i), i = 1 \cdots n \\ r_t, s_{t+1}, o_{t+1}^{1:n} \leftarrow \operatorname{Env}(a_t^{1:n}), \tilde{r} + = r_t \end{aligned}$ end for $Buffer \gets Buffer \cup Trai$ end for Train π_{ω} , V_{η} based on Buffer using MAPPO end while

This framework offers several advantages: (1) the training of skills with different number of agents can facilitate each other, as they share all modules but the codebook; (2) the modeling of temporal- and agent-level abstractions within multi-agent skills are decoupled as training the decoder to reconstruct single-agent trajectories and training the grouper for automatic grouping; (3) the grouper is trained to form subgroups only when it's beneficial for the overall objective so that each subgroup (with its policy) would correspond to a real coordination pattern.

Next, we introduce how to involve the discovered skills in CTDE MARL. In Alg. 1, we show the training process of a decentralized actor π_{ω} and centralized critic V_{η} using MAPPO for a multi-agent task Env, based on the prelearned h_{ψ} , $E_{1:n}$, and π_{ϕ} . In particular, every H time steps, the actor produces a continuous skill embedding $z^i \in \mathbb{R}^{1 \times d}$ for each agent i. $z^{1:n}$ are mapped to the closest multi-agent skill codes $e^{1:n}$ using the grouper h_{ψ} and codebook $E_{1:n}$, following Fig. 1 (b). Then, for the next H time steps, each agent i interacts with Env using corresponding $\pi_{\phi}(a^i \mid s^i, e^i)$, i.e., the decoder

working as the skill policy. Based on the interaction transitions, i.e., $\{(s_t, o_t^{1:n}, \tau_{t-H}^{1:n}, \tilde{r}_t, s_{t+H})\}$, π_{ω} and V_{η} can be trained with MAPPO, where $\tau_{t-H}^{1:n}$ are the skill – observation (i.e., z - o) history, $z^{1:n}$ can be viewed as (high-level) actions, and $\tilde{r}_t = \sum_{l=t}^{t+H-1} r_l$ is the skill reward. We note that Alg. 1 can be easily adapted with other MARL algorithms that are suitable for continuous action spaces.

We have several alternatives for mapping $z^{1:n}$ to $e^{1:n}$. The manner shown in Alg. 1 utilizes the prelearned grouper h_{ψ} which requires global state s and previous agents' grouping result $g^{1:i-1}$ to decide on g^i . Global information can facilitate subgroup division, but it may not be accessible during execution, for which we have several solutions. First, during the offline skill discovery stage, we could replace s with the local observation o^i (or observation history) as the input of h_{ab} , shown in Fig. 1 (a). In this way, s is not required during execution. This replacement would lead to information loss for grouping, but we note that h_{ψ} is trained with MAPPO which involves a centralized critic $V_{n'}(s)$ to guide the learning with global information. Second, we propose a greedy algorithm to directly match $z^{1:n}$ with the codebook, which does not use h_{ψ} or additional input other than $z^{1:n}$ and is detailed in Appendix B. However, this rule-based manner cannot guarantee optimal subgroup assignment and can be costly in computation when n is large. All the three methods mentioned above assign each multi-agent $(m \times d)$ code as a complete unit to a corresponding-size (m-agent) subgroup, such that the collaboration pattern encoded in the multi-agent code can be utilized. Alternatively, each $(m \times d)$ code can be decomposed into a set of (m) single-agent codes, and each agent could independently select its skill from the set of all single-agent codes. We denote this algorithm as 'VO-MASD-Mixed'. In Section 4, we provide empirical comparisons among these four skill assignment manners. It's worth noting that no matter which manner we choose, we only need to train a decentralized actor and a centralized critic in the online MARL stage, consistent with usual CTDE MARL methods.

3.2 VO-MASD based on a Hierarchical Codebook

In this section, we propose VO-MASD-Hier – an alternative design to VO-MASD-3D, which adopts a hierarchical codebook as in [24]. Although [24] is originally proposed for image generation, its



Figure 2: Multi-agent skill discovery based on a VQ-VAE with a hierarchical codebook design.

top and bottom codebooks perfectly echo the two-level structure of multi-agent and single-agent skill embeddings. Thus, we propose to learn top and bottom codebooks as agent- and temporal-level abstractions, respectively, for multi-agent skill discovery. The overall framework of VO-MASD-Hier is shown as Figure 2. It adopts a two-level codebook design, i.e., E_{top} , E_{btm} , which belong to $\mathbb{R}^{k_{top} \times d}$ and $\mathbb{R}^{k_{btm} \times d}$, respectively. VO-MASD-Hier does not need to learn *n* codebooks (i.e., $E_{1:n}$) as in VO-MASD-3D, while VO-MASD-3D can potentially make better use of domain knowledge. For example, if the scale of coordination subgroups (e.g., *m*) is known in advance, VO-MASD-3D only needs to learn E_1 and E_m , while VO-MASD-Hier can not specify the number of agents contained in a multi-agent skill.

Next, we go through the whole process of VO-MASD-Hier shown as Figure 2. In (a), the embedding process of each individual trajectory segment τ^i $(i = 1, \dots, n)$ is the same as the one of VO-MASD-3D (i.e., Figure 1 (a)). Subsequently, in (b), the skill embeddings $z_{\text{btm}}^{1:n}$ are clustered based on the output from the grouping function, i.e., $g^{1:n}$, and then embeddings within the same subgroup (e.g., $z_{\text{btm}}^{1::2}$) are aggregated to a unified (higher-level) representation (e.g., z_{top}^1) which is then used to query a top code (e.g., q_{top}^1). Note that the aggregator $f_{\theta_{\text{top}}}$ is shared by all subgroups and so is designed to use a multi-head attention module [25] to process varied-length inputs. In Figure 1 (c), for each agent *i*, a bottom code q_{btm}^i is assigned based on its skill embedding z_{btm}^i . Finally, q_{btm}^i and $q_{\text{top}}^{l_i}$, involving temporal- and agent-level abstractions respectively, are used to decode τ^i . The overall objective is $\min_{\theta_{\text{top,btm}}, \mathcal{R}_{top,btm}, \pi_{\phi}} \mathbb{E}_{\tau^{1:n} \sim \mathcal{D}_H} L^{\text{Hier}}(\tau^{1:n})$, where $L^{\text{Hier}}(\tau^{1:n})$ is defined as below:

$$L^{\text{Hier}}(\tau^{1:n}) = -\sum_{j=0}^{H-1} \sum_{i=1}^{n} \log \pi_{\phi}(a_{t+j}^{i} \mid o_{t+j}^{i}, q_{\text{btm}}^{i}, q_{\text{top}}^{l_{i}}) + \sum_{i=1}^{n} [\|\text{sg}(z_{\text{btm}}^{i}) - q_{\text{btm}}^{i}\|_{2}^{2} + \beta \|z_{\text{btm}}^{i} - \text{sg}(q_{\text{btm}}^{i})\|_{2}^{2} + \|\text{sg}(z_{\text{top}}^{l_{i}}) - q_{\text{top}}^{l_{i}}\|_{2}^{2} + \beta \|z_{\text{top}}^{l_{i}} - \text{sg}(q_{\text{top}}^{l_{i}})\|_{2}^{2}]$$
(3)

This loss function is similar with Eq. (1), i.e., to reconstruct the input multi-agent trajectory segment, and move the codes in codebooks and corresponding skill embeddings towards each other.

As for gradient backpropagation, without considering the second term in Eq. (3), the gradient w.r.t. the bottom code q_{btm}^i only comes from reconstructing agent *i*'s individual skill trajectory τ^i . However, for the top code $q_{top}^{l_i}$, the gradient is derived from reconstructing the joint skill trajectories of the subgroup l_i that *i* belongs to, since each agent *j* in l_i would adopt $q_{top}^{l_i}$ as the decoder condition to reconstruct corresponding τ^j . This, from another perspective, reflects that the top and bottom codebooks are trained to embed agent- and temporal-level abstractions, respectively. Notably, both VO-MASD-3D and VO-MASD-Hier follow the structural bias: primitive actions \rightarrow single-agent skills \rightarrow multi-agent skills. That is, each single-agent skill code is trained to embed an individual trajectory and each multi-agent skill code is a composition of single-agent ones. To be specific, in VO-MASD-3D, each ($m \times d$) multi-agent code contains a set (m) of ($1 \times d$) single-agent codes; while for VO-MASD-Hier, each multi-agent embedding z_{top} is obtained through aggregating individual skill embeddings z_{btm} from the same subgroup, as shown in Figure 2 (b).

The architecture and training method of the grouping function h_{ψ} in VO-MASD-Hier are the same as those in VO-MASD-3D. Still, h_{ψ} can take either the global state *s* or local observation (history) as input. Regarding utilizing the discovered skills in downstream online MARL, Alg. 1 can be applied to VO-MASD-Hier by replacing the process in Figure 1 (b)(c) with corresponding ones in Figure 2 (b)(c). Specifically, a decentralized actor π_{ω} gives out skill embeddings $z_{\text{btm}}^{1:n}$ every *H* time



Figure 3: Evaluation of effectiveness of the discovered skills in online MARL.

steps. h_{ψ} , $E_{\text{top,btm}}$, $f_{\theta_{\text{top}}}$, and π_{ϕ} are fixed during online MARL, transforming $z_{\text{btm}}^{1:n}$ to multi-agent and single-agent skill codes, i.e., $q_{\text{top}}^{1:n}$ and $q_{\text{btm}}^{1:n}$. π_{ω} constitutes a hierarchical policy with π_{ϕ} that is used as the skill policy, i.e., $\pi_{\phi}(a_t^i \mid o_t^i, q_{\text{top}}^{l_i}, q_{\text{btm}}^i)$, to produce skill trajectories of length H. As in VO-MASD-3D, only a decentralized actor π_{ω} and a centralized critic V_{η} are trained in the online learning stage, by maximizing the global return defined with task-specific team rewards.

4 Evaluation and Main Results

Experiments are conducted on the StarCraft multi-agent challenge (SMAC) [14] – a commonly-used benchmark for cooperative MARL. Following ODIS [26], we adopt two extended SMAC task sets to test the discovered multi-task multi-agent skills. In each task set, agents control some units like marines, medivacs, and marauders, but the number of controllable agents or enemies varies across tasks in a task set. We refer to the two task sets as 'marine' and 'MMMs', which evaluate algorithm performance in scenarios with homogeneous and heterogeneous agents, respectively, detailed further in Appendix C. For each task set, we discover skills from offline trajectories of source tasks, and then apply these skills to each task in the task set (including source and unseen tasks), for online MARL. The offline trajectories are collected with well-trained MAPPO [27] agents and are included in our released code folder. Next, we show evaluation results from several aspects. (1) We compare skills discovered using different algorithms on the two task sets, based on their utility for downstream online MARL, to demonstrate the superiority of the multi-agent skills discovered by our methods. (2) We show that, for MARL tasks with sparse reward signals, hierarchical learning with skills discovered using our methods can significantly outperform usual MARL algorithms. Notably, the skills are from relevant but different tasks. (3) We provide ablation study to show how the components of our algorithm design affect the learning performance.

The first group of results are shown as Figure 3, where '3d', 'hier', 'mixed', 'single', and 'odis' refer to VO-MASD-3D, VO-MASD-Hier, VO-MASD-Mixed, VO-MASD-Single, and ODIS, respectively. As mentioned in Appendix A, ODIS is the only existing, state-of-the-art (SOTA) algorithm for discovering multi-agent temporal abstractions from offline multi-task data ³, and is a representative of role-based MARL. VO-MASD-Single represents the other main branch of algorithms introduced in Appendix A – learning a set of single-agent skills and then collaboratively utilizing them for MARL, which is realized through removing E_{top} and $f_{\theta_{top}}$ in VO-MASD-Hier (i.e., Figure 2). VO-MASD-Single discovers and utilizes single-agent skills, while VO-MASD-Mixed discovers multi-agent skills as in VO-MASD-3D but employs the learned skills as single-agent ones, which is detailed in the last paragraph of Section 3.1. Thus, the baselines include SOTA algorithms in this field and two variations of our algorithms to respectively show the effect of **discovering** and **utilizing** skills as

³In [26], the discovered skills are used for offline MARL. For fair comparisons, we instead integrate skills from ODIS with online MARL (i.e., MAPPO), as in VO-MASD-3D and VO-MASD-Hier.



Figure 4: The effectiveness of discovered skills in online MARL with sparse reward signals.

multi-agent units. For this group of results, skills (of length 5) discovered from source tasks are applied to both source and unseen tasks for online MARL (with Alg. 1). In marine, 3m and 5m are source tasks; while in MMMs, MMM is the source task. We believe that the learning performance on unseen tasks with higher-complexity is the best way to testify the utility and generality of skills discovered with different algorithms. In particular, we track the change of win rate as the number of training samples increases, presenting the mean and 95% confidence interval as solid lines and shaded areas, respectively. Several conclusions can be drawn from Figure 3. (1) Overall, ODIS and VO-MASD-Single, which represent two main approaches of applying skills in MARL, exhibit inferior performance compared to the other three algorithms, especially in challenging, unseen tasks. This underscores the importance of discovering coordination patterns as multi-agent skills, which can significantly enhance performance and generality in new tasks. (2) In marine tasks, the performances of VO-MASD-3D and VO-MASD-Hier are comparable, with VO-MASD-Hier performing better in 10m and VO-MASD-3D excelling in the others. However, VO-MASD-3D's performance significantly deteriorates in MMMs, suggesting that its design is not well-suited for heterogeneous-agent tasks like MMM and MMM2. In the skill discovery phase, each $(m \times d)$ code, which represents a multi-agent skill, is used by an *m*-agent group comprising different types of agents. Yet, during skill utilization, each multi-agent code is assigned as a whole, without considering the composition of the target group, indicating a potential future research direction for improvement. (3) VO-MASD-Mixed follows the same skill discovery process as VO-MASD-3D but adopts the skills in a different manner (as mentioned above). Surprisingly, VO-MASD-Mixed consistently outperforms VO-MASD-3D. While VO-MASD-3D utilizes fixed combinations of single-agent $(1 \times d)$ codes from the discovery stage, VO-MASD-Mixed explores all possible combinations of these $(1 \times d)$ codes to achieve a higher return, which explains its better performance. However, in the most challenging settings (i.e., 10m and MMM2), VO-MASD-Hier demonstrates better results, showing the potential benefit of utilizing discovered multi-agent skills as complete units. (4) The evaluation on MMM2 – a super-hard task setting [14], demonstrates the superiority of VO-MASD-Hier over other algorithms. All algorithms, except for VO-MASD-Hier, exhibit large variance across different runs and can result in all-zero win rates in some random seeds.

With pretrained skills, only a high-level policy π_{ω} for skill selection is required for downstream task learning, as detailed in Alg. 1, and the decision horizon of π_{ω} is reduced to the original one divided by the skill length. Thus, learning with skills (i.e., hierarchical learning) is particularly advantageous for long-horizon tasks with sparse and delayed reward signals. To testify this, we modify the reward setups of the unseen tasks: 7m, 10m, MMM2, to be sparse, where agents receive a reward of 20 only upon eliminating all enemies (i.e., the winning condition); otherwise, they receive a reward 0. These three tasks, with maximum episode horizons of 110, 120, and 180 respectively, are particularly challenging. We apply two online MARL algorithms: MAPPO [27] and QMIX [28], to these tasks, and they consistently fail with all-zero win rates. Note that we use the original code and hyperparameter setup provided in [27]. Although they have been proposed for years, MAPPO and QMIX remain the most robust and SOTA algorithms in online MARL, as verified by extensive empirical studies [27, 29]. In contrast, with skills discovered using our algorithms: VO-MASD-3D, VO-MASD-Mixed, VO-MASD-Hier, the performance can be greatly improved, as shown in Figure 4. Note that (1) skills are discovered from source tasks and (2) only sparse rewards mentioned earlier are adopted for downstream online MARL. This highlights the effectiveness of hierarchical MARL when employing the multi-agent, multi-task skills discovered by our algorithms. As in Figure 3, for the sparse-reward setting, VO-MASD-Hier achieves the best overall performance, followed by VO-MASD-Mixed. Unexpectedly, despite using the same set of offline data and random seeds,



Figure 5: (a) The performance of VO-MASD-Hier with different skill horizons (2–15) or an extra skill encoder $f_{\theta_{\text{mid}}}$ on 7m; (b) Comparisons among the four utilization manners of skills discovered by VO-MASD-3D on 7m; (c) Potential approaches to improve VO-MASD-3D's performance on 10m.

VO-MASD-Mixed exhibits better performance in MMM2 (compared to that shown in Figure 3(f)) under a more challenging reward setting.

Finally, we show some ablation study results as Figure 5. In (a), we compare the performance of VO-MASD-Hier with skills of different lengths (i.e., 2, 5, 10, 15) on task 7m, where our setup (i.e., H = 5) performs the best. Utilizing skills of length 15 causes inflexibility and inferior performance, since these skills are learned from 3m and 5m and not updated during downstream online MARL. However, using such long skills could effectively decrease the decision horizon of the high-level policy, while remaining reasonable performance which is better than the ones of ODIS and VO-MASD-Single (as shown in Figure 3(c)). Additionally, we compare VO-MASD-Hier with its alternative design (labelled as 'mid'), which adopts an extra encoder $f_{\theta_{mid}}$ to get bottom skill embeddings and is further detailed in Appendix D. This alternative design is closer in form with VQ-VAE-2 [24] which inspires VO-MASD-Hier. This algorithm has better initial performance but converges at a lower level. In (b), we compare the four utilization manners of multi-agent skills discovered by VO-MASD-3D, as detailed in the last paragraph of Section 3.1. '3d' and 'mixed' correspond to VO-MASD-3D and VO-MASD-Mixed, respectively. 'rule' refers to rule-based skill selection (i.e., Alg. 2), while 'obs-grp' denotes using a grouping function h_{ψ} that depends on o_t^i instead of s_t (see Figure 1). Notably, 'mixed', 'obs-grp', and 'rule' do not rely on states during execution as '3d'. 'rule' and 'mixed' have comparable or even better performance compared to '3d', and the inferior performance of 'obs-grp' could potentially be improved by relacing o_t^i with the observation-action history. In (c), we explore some approaches to improve the performance of VO-MASD-3D on unseen tasks (e.g., 10m). In the original setup (i.e., '3d'), skills discovered from 3m and 5m are *m*-agent coordination patterns, where m ranges from 1 to 5. 'skill-size-3' limits m to a range of 1 to 3, corresponding to scenarios where domain knowledge is available and we only need to learn skills for specific subgroup sizes. However, its worse performance (compared to '3d') shows the necessity to utilize skills of large subgroups for this task. The grouper h_{ψ} as shown in Figure 1 and 2 is trained in a multi-task manner (e.g., in 3m and 5m)⁴, thus it can potentially be used in a relevant but new task without retraining. However, generalization to a more complex task (e.g., 10m) could be challenging and fine-tuning the grouper with task-specific rewards may improve the overall learning performance. Yet, the fine-tuned case 'grp-tuned' doesn't bring performance improvement, likely because the training of the grouper h_{ψ} and high-level policy π_{ω} are interleaved and a carefully-designed co-training scheme is required. Last, if we change the source tasks for skill discovery from [3m, 5m] to [3m, 10m], the performance can be greatly boosted, as evidenced by 'data-10m', showing the capability of VO-MASD-3D to extract effective skills from demonstrated data.

5 Conclusion and Discussion

In this work, we propose novel algorithms for discovering coordination patterns among agents as multi-agent skills from offline multi-task data. The key challenge lies in abstracting agents' behaviors at both the temporal and agent levels in a fully automatic manner. We address this challenge by developing novel encoder-decoder architectures and co-training the encoder-decoder with a grouping function that dynamically groups agents. Empirical results demonstrate that multi-agent skills

⁴The observation, state, and action vectors vary in size across different tasks within a task set, necessitating specially designed input layers for each neural network to enable multi-task learning. We adopt the input-layer design from ODIS, as detailed in Appendix C of [26].

discovered using our methods significantly enhance learning in downstream MARL tasks. Further, in long-horizon tasks with sparse rewards, hierarchical MARL that utilizes multi-agent skills discovered with our methods markedly surpasses SOTA online MARL algorithms. Regarding limitations of this work, as we show in Section 4, the algorithm design of VO-MASD-3D is not well-suited for tasks involving heterogeneous agents. Also, as a future direction, a co-training scheme of the high-level policy and grouper for online MARL can be developed, so that the grouping function can be fine-tuned with task-specific rewards for improved performance.

References

- [1] Eysenbach, B., A. Gupta, J. Ibarz, S. Levine. Diversity is all you need: Learning skills without a reward function. In *International Conference on Learning Representations*. OpenReview.net, 2019.
- [2] Jinnai, Y., J. W. Park, M. C. Machado, G. D. Konidaris. Exploration in reinforcement learning with deep covering options. In *International Conference on Learning Representations*. OpenReview.net, 2020.
- [3] Chen, J., V. Aggarwal, T. Lan. A unified algorithm framework for unsupervised discovery of skills based on determinantal point process. In *Advances in Neural Information Processing Systems*. 2023.
- [4] Lee, Y., J. Yang, J. J. Lim. Learning to coordinate manipulation skills via skill behavior diversification. In *International Conference on Learning Representations*. OpenReview.net, 2020.
- [5] Yang, J., I. Borovikov, H. Zha. Hierarchical cooperative multi-agent reinforcement learning with skill discovery. In *International Conference on Autonomous Agents and Multiagent Systems*, pages 1566–1574. International Foundation for Autonomous Agents and Multiagent Systems, 2020.
- [6] Sachdeva, E., S. Khadka, S. Majumdar, K. Tumer. Maedys: multiagent evolution via dynamic skill selection. In *Genetic and Evolutionary Computation Conference*, pages 163–171. ACM, 2021.
- [7] He, S., J. Shao, X. Ji. Skill discovery of coordination in multi-agent reinforcement learning. *CoRR*, abs/2006.04021, 2020.
- [8] Yang, M., Y. Yang, Z. Lu, W. Zhou, H. Li. Hierarchical multi-agent skill discovery. In *Advances in Neural Information Processing Systems*. 2023.
- [9] Chen, J., J. Chen, T. Lan, V. Aggarwal. Scalable multi-agent covering option discovery based on kronecker graphs. In *Advances in Neural Information Processing Systems*. 2022.
- [10] Wang, T., H. Dong, V. R. Lesser, C. Zhang. ROMA: multi-agent reinforcement learning with emergent roles. In *International Conference on Machine Learning*, vol. 119 of *Proceedings of Machine Learning Research*, pages 9876–9886. PMLR, 2020.
- [11] Liu, B., Q. Liu, P. Stone, A. Garg, Y. Zhu, A. Anandkumar. Coach-player multi-agent reinforcement learning for dynamic team composition. In *International Conference on Machine Learning*, vol. 139 of *Proceedings of Machine Learning Research*, pages 6860–6870. PMLR, 2021.
- [12] Xu, Z., Y. Bai, B. Zhang, D. Li, G. Fan. HAVEN: hierarchical cooperative multi-agent reinforcement learning with dual coordination mechanism. In AAAI Conference on Artificial Intelligence, pages 11735–11743. AAAI Press, 2023.
- [13] Zhou, G., Z. Xu, B. Zhang, D. Li, Z. Zhang, G. Fan. Constructing informative subtask representations for multi-agent coordination, 2024.
- [14] Samvelyan, M., T. Rashid, C. S. de Witt, et al. The starcraft multi-agent challenge. In Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems, pages 2186–2188. International Foundation for Autonomous Agents and Multiagent Systems, 2019.
- [15] Oliehoek, F. A., C. Amato, et al. A concise introduction to decentralized POMDPs, vol. 1. Springer, 2016.

- [16] Oliehoek, F. A., M. T. J. Spaan, N. Vlassis. Optimal and approximate q-value functions for decentralized pomdps. *Journal of Artificial Intelligence Research*, 32:289–353, 2008.
- [17] Yu, C., A. Velu, E. Vinitsky, J. Gao, Y. Wang, A. M. Bayen, Y. Wu. The surprising effectiveness of PPO in cooperative multi-agent games. In *Advances in Neural Information Processing Systems*. 2022.
- [18] Schulman, J., F. Wolski, P. Dhariwal, A. Radford, O. Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017.
- [19] van den Oord, A., O. Vinyals, K. Kavukcuoglu. Neural discrete representation learning. In Advances in Neural Information Processing Systems, pages 6306–6315. 2017.
- [20] Kingma, D. P., M. Welling. Auto-encoding variational bayes. In International Conference on Learning Representations. 2014.
- [21] Campos, V., A. Trott, C. Xiong, R. Socher, X. Giró-i-Nieto, J. Torres. Explore, discover and learn: Unsupervised discovery of state-covering skills. In *International Conference on Machine Learning*, vol. 119 of *Proceedings of Machine Learning Research*, pages 1317–1327. PMLR, 2020.
- [22] Ajay, A., A. Kumar, P. Agrawal, S. Levine, O. Nachum. OPAL: offline primitive discovery for accelerating offline reinforcement learning. In *International Conference on Learning Representations*. OpenReview.net, 2021.
- [23] Bengio, Y., N. Léonard, A. C. Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *CoRR*, abs/1308.3432, 2013.
- [24] Razavi, A., A. van den Oord, O. Vinyals. Generating diverse high-fidelity images with VQ-VAE-2. In Advances in Neural Information Processing Systems, pages 14837–14847. 2019.
- [25] Vaswani, A., N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, I. Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, pages 5998–6008. 2017.
- [26] Zhang, F., C. Jia, Y. Li, L. Yuan, Y. Yu, Z. Zhang. Discovering generalizable multi-agent coordination skills from multi-task offline data. In *International Conference on Learning Representations*. OpenReview.net, 2023.
- [27] Yu, C., A. Velu, E. Vinitsky, J. Gao, Y. Wang, A. Bayen, Y. Wu. The surprising effectiveness of ppo in cooperative multi-agent games. *Advances in Neural Information Processing Systems*, 35:24611–24624, 2022.
- [28] Rashid, T., M. Samvelyan, C. S. de Witt, G. Farquhar, J. N. Foerster, S. Whiteson. QMIX: monotonic value function factorisation for deep multi-agent reinforcement learning. In *International Conference on Machine Learning*, vol. 80 of *Proceedings of Machine Learning Research*, pages 4292–4301. PMLR, 2018.
- [29] Hu, J., S. Wang, S. Jiang, M. Wang. Rethinking the implementation tricks and monotonicity constraint in cooperative multi-agent reinforcement learning. In *The Second Blogpost Track at ICLR 2023*. 2023.
- [30] Amato, C., G. D. Konidaris, L. P. Kaelbling. Planning with macro-actions in decentralized pomdps. In *International conference on Autonomous Agents and Multi-Agent Systems*, pages 1273–1280. IFAAMAS/ACM, 2014.
- [31] Amato, C., G. D. Konidaris, L. P. Kaelbling, J. P. How. Modeling and planning with macroactions in decentralized pomdps. *Journal of Artificial Intelligence Research*, 64:817–859, 2019.
- [32] Shen, J., G. Gu, H. Liu. Multi-agent hierarchical reinforcement learning by integrating options into MAXQ. In *International Multi-Symposium of Computer and Computational Sciences*, pages 676–682. IEEE Computer Society, 2006.
- [33] Ghavamzadeh, M., S. Mahadevan, R. Makar. Hierarchical multi-agent reinforcement learning. Autonomous Agents and Multi-Agent Systems, 13(2):197–229, 2006.
- [34] Fosong, E., A. Rahman, I. Carlucho, S. V. Albrecht. Learning complex teamwork tasks using a sub-task curriculum. arXiv preprint arXiv:2302.04944, 2023.

- [35] Chakravorty, J., P. N. Ward, J. Roy, M. Chevalier-Boisvert, S. Basu, A. Lupu, D. Precup. Option-critic in cooperative multi-agent systems. In *International Conference on Autonomous Agents and Multiagent Systems*, pages 1792–1794. International Foundation for Autonomous Agents and Multiagent Systems, 2020.
- [36] Xiao, Y., W. Tan, C. Amato. Asynchronous actor-critic for multi-agent reinforcement learning. In Advances in Neural Information Processing Systems. 2022.
- [37] Zhang, H., G. Li, C. H. Liu, G. Wang, J. Tang. Himacmic: Hierarchical multi-agent deep reinforcement learning with dynamic asynchronous macro strategy. In ACM SIGKDD Conference on Knowledge Discovery and Data Mining, pages 3239–3248. ACM, 2023.
- [38] Wang, T., T. Gupta, A. Mahajan, B. Peng, S. Whiteson, C. Zhang. RODE: learning roles to decompose multi-agent tasks. In *International Conference on Learning Representations*. OpenReview.net, 2021.
- [39] Liu, Y., Y. Li, X. Xu, Y. Dou, D. Liu. Heterogeneous skill learning for multi-agent tasks. In *Advances in Neural Information Processing Systems*. 2022.
- [40] Iqbal, S., R. Costales, F. Sha. ALMA: hierarchical learning for composite multi-agent tasks. In Advances in Neural Information Processing Systems. 2022.
- [41] Yang, M., J. Zhao, X. Hu, W. Zhou, J. Zhu, H. Li. LDSA: learning dynamic subtask assignment in cooperative multi-agent reinforcement learning. In Advances in Neural Information Processing Systems. 2022.
- [42] Li, C., T. Wang, C. Wu, Q. Zhao, J. Yang, C. Zhang. Celebrating diversity with subtask specialization in shared multiagent reinforcement learning. *IEEE Transactions on Neural Networks and Learning Systems*, 2023.
- [43] Zang, Y., J. He, K. Li, H. Fu, Q. Fu, J. Xing, J. Cheng. Automatic grouping for efficient cooperative multi-agent reinforcement learning. In Advances in Neural Information Processing Systems. 2023.
- [44] Tian, Z., R. Chen, X. Hu, et al. Decompose a task into generalizable subtasks in multi-agent reinforcement learning. In Advances in Neural Information Processing Systems. 2023.
- [45] Xia, Y., J. Zhu, L. Zhu. Dynamic role discovery and assignment in multi-agent task decomposition. Complex & Intelligent Systems, 9(6):6211–6222, 2023.

A Related Works

In this section, we provide a comprehensive review on the use of skills in cooperative MARL, and emphasize the novelty of our proposed algorithm. We categorize these works into several groups based on their algorithm designs. The first group of works either rely on predefined skills [30, 31] or require well-designed task hierarchies/decomposition [32, 33, 34]. However, we focus on automatic task decomposition and skill discovery, which is more demanding but makes our algorithm more applicable. Next, we introduce research works in this direction.

A straightforward manner is to learn a set of single-agent skills for each agent using discovery methods proposed in single-agent scenarios [1, 2, 3], and then learn a multi-agent meta policy over these individual skills. The intuition is that players in a team sport can master their skills individually outside of team practices. Specifically, the meta policy $\pi_h(\vec{z} \mid s)$ assigns skills $\vec{z} = (z^1, \cdots, z^n)$ to all agents, and then each agent decides on its primitive action according to its skill policy $\pi_l(a^i \mid \tau^i, z^i)$. Note that (1) $z^i \in \Omega^z$ is an embedding of a single-agent skill and Ω^z is usually a finite set of skill choices; (2) $\pi_h(\vec{z} \mid s)$ is usually implemented as $(\pi_h^1(z^1 \mid \tau^1), \cdots, \pi_h^n(z^n \mid \tau^n))$ in CTDE schemes to enable decentralized skill selection. Representative works of this category include [4, 5, 6]. In [4], skills π_l are learned in a separate stage, while, in [5, 6], skills are concurrently trained with the meta policy π_h . Typically, as in single-agent scenarios, the skill duration H is a predefined value, and a new skill assignment for all agents, i.e., \vec{z} , should be given by the meta policy every H time steps. However, some algorithms [35, 36, 37] have been proposed for the case where the skills of each agent can take different amounts of time and so the skill selection across agents can be asynchronized. To sum up, this group of works replace the primitive action set A in MARL with an individual-skill set Ω^{z} , which could simplify the learning especially for long-horizon tasks. However, in multi-agent scenarios, discovering inter-agent coordination patterns as multi-agent skills is possible. Learning with multi-agent skills could be simpler, since they constitute higher-level abstractions of multi-agent behaviors than single-agent skills and are closer in form with the overall multi-agent policy.

Another main branch of algorithms is role-based MARL. These algorithms, based on the CTDE scheme, usually contain three modules: establishing role representations $\Omega^Z = \{Z_1, \dots, Z_m\}$, learning a role selector $\pi_h(Z^i \mid \tau^i)$ ($Z^i \in \Omega^Z$), and learning role policies $\pi_l(a^i \mid \tau^i, Z^i)$. This framework is similar with the one used for MARL with single-agent skills. However, the policy of role Z, i.e., $\pi_l(a^i \mid \tau^i, Z)$, is not a single-agent skill policy but a policy for the subgroup g_Z . This is because each agent $i \in q_Z$ adopts the same role policy $\pi_l(\cdot \mid \cdot, Z)$ and $\pi_l(\cdot \mid \cdot, Z)$ is trained in a centralized manner with the aim for the subgroup g_Z to maximize a global return. As a comparison, aforementioned [4, 6] learn skill policies $\pi_l(\cdot \mid \cdot, z)$ based on reward functions specifically defined for single-agent skills, and [5] updates skill policies through Independent Q-learning, i.e., a fullydecentralized training scheme, thus the learned skills are for individuals. Notable works in this category, roughly ordered by the publication date, include [10, 11, 38, 39, 40, 41, 42, 43, 44, 12, 45, 13]. Among these works, Z is given different names, such as role [10], ability [41], subtask [42], and skill [39], but refers to the same concept. All these works utilize a similar algorithm framework, which, as mentioned above, contains three modules for learning the role embedding, role selector ⁵, and role policy, respectively. One main distinction lies in their varied approaches for learning the role embedding, which can be based on action effects [38], global state reconstruction [13], or predictions of the next observation and reward [39]. Besides maximizing the global return, regularization terms are often employed for optimizing those three components. For example, diversity is encouraged in the learned role embeddings, and temporal consistency is regulated in the role selection process to avoid frequent changes in role assignments over time. These regularizers are shown to be essential for learning performance and different works in this category vary in the regularizer design. As a recommendation, readers who are new to this area can refer to the two representative works: [41, 12]. To sum up, although the role policy $\pi_l(a^i \mid \tau^i, Z)$ is more than a single-agent skill and learned as a subgroup policy for g_Z , agents in g_Z are similar in behaviors as they all adopt a policy conditioned on Z. As mentioned in [41], role-based MARL is designed to dynamically group agents with similar abilities into the same subtask. However, as a different concept, multi-agent skills should be abstractions of subgroup coordination patterns, and agents from this subgroup could possess heterogeneous behaviors. For instance, the collaboration between two pilots - one

⁵Most algorithms in this category adopt decentralized selectors, i.e., $(\pi_h(Z^1 \mid \tau^1), \dots, \pi_h(Z^n \mid \tau^n))$, but there are some works, such as [11, 40], utilizing centralized ones, i.e., $\pi_h(\vec{Z} \mid s)$. The global state could provide more information for the coordinated role assignment.

proficient in advanced flying maneuvers and the other in weapon control – while operating a fighter jet, exemplifies a multi-agent skill. Therefore, the concept of a multi-agent skill is more generalized than that of role policy and cannot be acquired through aforementioned role-based algorithms.

There are relatively few works on multi-agent skill discovery. The authors of [7, 9, 8] propose algorithms to discover skills for the entire team of agents. As a representative, in [8], they adopt a transformer-based skill selector $\pi_h(z^{1:n}, Z \mid s)$ to decide on the team skill Z and individual skills $z^{1:n}$ autoregressively based on the global state. Then, each agent *i* interacts with the environment using a corresponding policy $\pi_l(a^i \mid \tau^i, z^i, Z)^{6}$. Compared with the role policy $\pi_l(\cdot \mid \cdot, Z)$, the team skill $\pi_l(\cdot \mid \cdot, z, Z)$ could contain heterogeneous behaviors across agents, which are embedded as various individual skills $z^{1:n}$. However, the team skill is only a special instance of multi-agent skills, as the number of agents within a team skill is always *n*. Effective multi-agent skills should capture coordination patterns among agents, which usually occur within subgroups rather than the entire team, and team skills are less flexible to be utilized or transferred especially for big teams as it requires to coordinate all agent members. Ideally, multi-agent skill discovery should identify subgroups where agents interact frequently and extract their behavior patterns as joint skills, and the size of the subgroup could vary from 1 to *n*, which is much more challenging as it additionally requires dynamic grouping according to the task scenario.

All the algorithms mentioned above are for online skill discovery, while the authors of [26] propose an approach for discovering coordination skills from offline data. However, this algorithm is still a role-based one, and the learned role policy $\pi_l(\cdot \mid \cdot, Z)$ is different from multi-agent skills as mentioned above. The difference between [26] and aforementioned role-based methods is that it replaces task rewards with the reconstruction accuracy of joint actions, so that the learned skills are not task-specific but generalizable.

B A Greedy Algorithm for Matching Skill Embeddings with the Codebook

Algorithm 2 Multi-agent skill assignment				
Input: $z^{1:n}$, $E_{1:n}$				
Initialize a Min-Heap M				
for $i = 1 \cdots n$ do				
for each <i>i</i> -agent subgroup \vec{j} do				
for each <i>i</i> -agent code \vec{e} in E_i do				
Insert $(z^{\vec{j}} - \vec{e} _2^2/i, \vec{j}, \vec{e})$ into M				
end for				
end for				
end for				
while $i < n$ (<i>i</i> is initialized as 0) do				
$d, \vec{j}, \vec{e} \leftarrow M.pop()$				
if all agents in \vec{j} remain unassigned then				
$e^{\vec{j}} \leftarrow \vec{e}, i + = \vec{j} $				
end if				
end while				
Return $e^{1:n}$				

The rule-based multi-agent skill assignment process is shown as Alg. 2. Given skill embeddings $z^{1:n}$ produced by the high-level policy π_{ω} , we repeat the following process until all agents are assigned with skills: greedily select the closest multi-agent code \vec{e} , assign the corresponding multi-agent skill to the selected subgroup \vec{j} , remove this subgroup from the waiting list. We can implement such process with a Min-Heap, from which we can efficiently query the closet pair of skill embeddings and codes (via the "pop" operation).

To make full use of the discovered joint skills, instead of independently selecting a skill code (i.e., a $1 \times d$ single-agent code from a complete $m \times d$ code) for each agent, we can assign each multi-agent code as a whole, which motivates the design of Alg. 2. Compared with related works, (1) our ($m \times d$) multi-agent codes embed coordination patterns among (m) agents, where

each agent's behavior is embedded by a single-agent $(1 \times d)$ code and so can be heterogeneous, but role-based algorithms learn a role policy taken by a subgroup of agents that possess similar behaviors and abilities; (2) Alg. 2 only requires fairly compact centralized information, i.e., $z^{1:n}$, for coordinated skill assignment, where each skill embedding z^i is decided based on local observations of agent *i* rather than global information (e.g., *s*) as in [11, 8].

However, as a limitation, when n is large, Alg. 2 can be inefficient. For solutions, we can (1) avoid discovery of x-agent skills, where x is around n/2, as the combination number $\binom{n}{k}$ could be large; (2) utilize domain knowledge to filter out useless skill codes in $E_{1:n}$ or specify the scale of subgroups,

⁶In [8], Z is not used as a condition of π_l but adopted for centralized training, so the team skill information is implied in π_l .



Figure 6: An alternative design of VO-MASD-Hier.

i.e., x. Further, we note that Alg. 2 is a greedy assignment method which would inevitably bring suboptimality.

C Details of the SMAC Task Sets for Evaluation

The marine task set includes four marine battle tasks, for each of which several ally marines need to beat the same number of enemy marines to win; while in the MMMs task set, each task is a battle between two groups of medivacs (mv), marauders (md), and marines (mn). Detailed descriptions of these task sets are listed in Table 1. We note that skills are discovered from source tasks in a task set and evaluated on both source and unseen tasks. Given that MMM2 is categorized as super-hard in SMAC [14], skills discovered solely in MMM would fail in MMM2, regardless of the skill discovery method employed. For effective comparisons, we instead use a mixture of offline data from both MMM and MMM2 to discover skills, with MMM2 trajectories constituting less than 5% of the total.

Task Set	Property	Task	Туре	Ally Units	Enemy Units
marine		3m	source	3 marines	3 marines
	homogeneous,	5m	source	5 marines	5 marines
	symmetric	7m	unseen	7 marines	7 marines
		10m	unseen	10 marines	10 marines
MMMs	heterogeneous,	MMM	source	1 mv, 2 md, 7 mn	1 mv, 2 md, 7 mn
	asymmetric	MMM2	unseen	1 mv, 2 md, 7 mn	1 mv, 3 md, 8 mn

Table 1: Descriptions of the marine and MMMs task sets

D An Alternative Design of VO-MASD-Hier

The only difference between Figure 2 and 6 is in part (c). An extra encoder $f_{\theta_{\text{mid}}}$ is introduced to further embed z_{btm}^i and its corresponding top code $q_{\text{top}}^{l_i}$ to a bottom skill embedding \tilde{z}_{btm}^i , which is then used to query a bottom code q_{btm}^i , while in VO-MASD-Hier, z_{btm}^i is directly matched with E_{btm} for q_{btm}^i . This three-level encoder design is used in VQ-VAE-2 [24] which demonstrates superior performance for image generation. However, this alternative design underperforms VO-MASD-Hier in multi-agent skill discovery, as shown in Figure 5(a). One possible explanation is that the inductive bias: primitive actions \rightarrow single-agent skills \rightarrow multi-agent skills, is not well-adopted in this design. More specifically, multi-agent skills should be composed by single-agent skills, but in Figure 6 (c), the single-agent skill embedding \tilde{z}_{btm}^i involves information from the multi-agent skill code $q_{\text{top}}^{l_i}$, which violates the inductive bias. In contrast, VO-MASD-Hier eliminates $f_{\theta_{\text{mid}}}$ for a simpler architecture while adhering to this bias.

E Compute Resources

Experiments were conducted using the Oracle Cloud infrastructure, where each computation instance was equipped with an NVIDIA Tesla P100 GPU, 12 Intel Xeon Platinum CPU cores, and 72 GB of memory. For VO-MASD-Mixed, VO-MASD-3D, and VO-MASD-Hier, each instance could

simultaneously handle one of these experiment sets: [3m, 5m, 7m, 10m], [MMM], or [MMM2]. While, for ODIS, VO-MASD-Single, MAPPO, and QMIX, the capacity of each instance could be doubled. The average running time of each experiment set is approximately 2 days. Thus, without conducting repeated runs (utilizing different random seeds), the experiments depicted in Figure 3, Figure 5, and Figure 6 require approximately 600, 400, and 250 hours, respectively, using such computation instance. The full research project required more compute than the experiments reported in the paper, primarily for the hyperparameter tuning and testing of alternative designs. Different hyperparameter configurations could lead to better or worse performance, but we suggest using the provided ones in the released code folder.