# Efficient LLM-Jailbreaking by Introducing Visual Modality

Zhenxing Niu<sup>1</sup>, Yuyao Sun<sup>1</sup>, Haodong Ren<sup>1</sup>, Haoxuan Ji<sup>2</sup>, Quan Wang<sup>1</sup>, Xiaoke Ma<sup>1</sup>, Gang Hua<sup>3</sup>, and Rong Jin<sup>4</sup>

<sup>1</sup>Xidian University <sup>2</sup>Xi'an Jiaotong University <sup>3</sup>Wormpex AI Research <sup>4</sup>Meta

#### Abstract

This paper focuses on jailbreaking attacks against large language models (LLMs), eliciting them to generate objectionable content in response to harmful user queries. Unlike previous LLM-jailbreaks that directly orient to LLMs, our approach begins by constructing a multimodal large language model (MLLM) through the incorporation of a visual module into the target LLM. Subsequently, we conduct an efficient MLLM-jailbreak to generate jailbreaking embeddings *embJS*. Finally, we convert the embJS into text space to facilitate the jailbreaking of the target LLM. Compared to direct LLM-jailbreaking, our approach is more efficient, as MLLMs are more vulnerable to jailbreaking than pure LLM. Additionally, to improve the attack success rate (ASR) of jailbreaking, we propose an image-text semantic matching scheme to identify a suitable initial input. Extensive experiments demonstrate that our approach surpasses current state-of-theart methods in terms of both efficiency and effectiveness. Moreover, our approach exhibits superior cross-class jailbreaking capabilities. The code is available here.

# 1 Introduction

Recently, large language models (LLMs) such as ChatGPT [1]have been widely deployed. These models exhibit advanced general abilities but also pose serious safety risks such as truthfulness, toxicity, and bias [2, 3, 4, 5, 6]. Typically, there exists a type of attack called *jailbreaking attack*, which can elicit LLMs to generate objectionable content in response to users' harmful queries. For example, A pioneering work [7] has found that a specific prompt suffix allows the jailbreaking of most popular LLMs. However, the efficiency of those methods is



Figure 1: The *double jailbreaking workflow* of our approach. We start from constructing an MLLM by introducing a visual modality into the target LLM. And then, we conduct an efficient MLLM-jailbreak to produce the *embJS*. Finally, we convert the embJS as the txtJS to jailbreak the target LLM.

recognized to be relatively low, primarily attributed to the challenges of discrete optimization in finding textual prompt suffix.

On the other hand, there is a surge of interest in multimodal large language models (MLLMs) that allow users to provide images that influence the generated text [8, 9, 10, 11, 12, 13, 14, 15, 16]. Consequently, research on jailbreaking has been extended from LLMs to MLLMs. Furthermore, it has been demonstrated that performing MLLM-jailbreak is easier and more efficient than performing LLM-jailbreak[17, 18]. It is largely due to that finding jailbreaking images across thousands of pixels provides significantly greater richness and flexibility compared to finding jailbreaking text across discrete and limited tokens.

Inspired by that, this paper proposes an efficient LLM-jailbreaking approach by constructing an MLLM and performing MLLM-jailbreak. Specifically, we follow a common LLM-jailbreaking strategy [7] that aims to find a specific text string (namely *textual Jailbreaking Suffix (txtJS)*). This string, when appended to harmful queries, is able to elicit LLMs generating objectionable content. Our contribution lies in *efficiently* finding such txtJS through the MLLM-jailbreak. The workflow of our approach is shown in Fig.1. Given a target LLM to be jailbroke (*e.g.*, LLaMA2), we first construct an MLLM by incorporating a visual module into the target LLM, and then perform an efficient MLLM-jailbreak. Subsequently, instead of obtaining the jailbreaking image (namely *imgJS*), we obtain the output features of visual module (namely *embeddings of Jailbreaking Suffix (embJS)*), and convert them to text strings through our De-embedding and De-tokenizer operations. Finally, we regard these text strings as *txtJS* and append them to the harmful queries to facilitate the jailbreaking of the target LLM.

In our approach, we do not stop after completing the MLLM-jailbreaking; instead, we continue to perform LLM-jailbreaking. This *double jailbreaking workflow* offers flexibility for both white-box and black-box jailbreaking. In the context of white-box jailbreaking, converting embJS to txtJS allows us to obtain a pool of txtJS. Unlike GCG [7], which produces only *one* txtJS, our approach can output *several high-quality* txtJS, significantly enhancing the jailbreaking ASR.

Black-box jailbreaking is preferred in real-world applications, where even if the txtJS is learned on a surrogate LLM, it can be effectively utilized to jailbreak target LLM whose architecture and parameters are unknown. In our approach, there is a transition from MLLM-jailbreaking to LLM-jailbreaking. Thus, we can construct the MLLM with the surrogate LLM and obtain the txtJS through MLLM-jailbreak. Subsequently, the txtJS can be used to jailbreak the target LLM in a black-box manner. More importantly, one advantage of our approach is that if we further know the *tokenizer* of the target LLM (without requiring knowledge of its backbone), we can design our De-tokenizer operations according to it, which will significantly enhance black-box jailbreaking ASR.

Regarding the MLLM-jailbreaking, we observe that the Attack Success Rate (ASR) of jailbreaking is closely related to the initial input image (namely *initJS*). If an appropriate initJS is used, we can significantly improve the MLLMjailbreaking ASR. To this end, we propose an image-text semantic matching scheme to identify the appropriate initJS. This scheme aims to make the embedding of initJS close to the embedding of harmful queries. As a result, through LLM's cross-attention, initJS can significantly influence the LLM's answer generation process, such as turning the answer from "Sorry, I cannot" to "Sure, here is", achieving a successful jailbreak.

Our approach is also related to another type of jailbreaking method focusing on optimization over token embeddings, known as *embedding-based jailbreak*. Token embeddings, being continuous variables, lend themselves to more straightforward continuous optimization compared to the *discrete optimization-based jailbreak* [7]. However, it has been found that embedding-based jailbreak is ineffective because the optimized embeddings often have no corresponding discrete token [7]. Our approach also relies on finding continuous embeddings (*i.e.*, embJS). Nevertheless, we obtain embJS through the optimization over imgJS, instead of directly optimizing embJS. Thus, our approach functions akin to regularizing the embedding optimization process by utilizing the visual module. Since the visual module (*e.g.*, CLIP encoder) is trained with an image-text alignment objective, it can ensure that our embJS have corresponding discrete token. Hence, our approach outperforms embedding-based jailbreaking in terms of effectiveness.

Regarding the evaluation of LLM-jailbreak, previous methods tend to use a jailbreaking dataset where different kinds of harmful behaviors are mixed. In contrast, we propose to categorize them into fine-grained classes, such as violence, financial crimes, cyber crimes, drug crimes, *etc.* Thus, we can evaluate the *cross-class generalization* of jailbreaking, *i.e.*, examining whether the txtJS generated for one class can effectively jailbreak other classes.

Additionally, evaluating the success of jailbreaking is challenging. The goal of jailbreaking is to elicit LLM to generate *any* response that aligns with the instruction given. Providing a specific ground truth response for a harmful query can be challenging. Besides, we have observed some instances that even if a

response starts with a positive affirmation (*e.g.*, "Sure, here is a"), the subsequent content actually refuses to answer the query. As a result, previous methods often rely on *manual checks* to determine whether the jailbreak is successful or not. To address this limitation, we propose to utilize the *LLaMA Guard* 2[19] tool to *automatically* determine the success of jailbreaking attempts.

We conduct extensive experiments to illustrate that our approach surpasses current state-of-the-art methods in terms of both efficiency and effectiveness. Moreover, our approach exhibits superior cross-class jailbreaking capabilities. It suggests that to enhance the ASR for a particular class, we can utilize not only the harmful queries from that class but also those from its correlated classes.

# 2 Related Work

Prior work on jailbreaking primarily revolves around crafting input prompts, referred to as *jailbreaking prompts*, to effectively bypass model alignment. At first, prompts endowed with specific semantic meanings are manually crafted, employing strategies such as role-playing [3], prompt injection, and privilege escalation [20].

Recently, it has shifted towards automating the generation of jailbreaking prompts to reduce labor-intensive manual creation. Existing jailbreaking methods fall into two main categories. The first, known as *discrete optimization-based jailbreak*, involves directly optimizing discrete tokens. [21] utilize techniques inspired by time-based SQL injection to automatically generate jailbreak prompts. Further advancements by [22] take the form of the autoDAN attack strategy, employing hierarchical genetic algorithms to generate covert prompts. [7] propose the general attack method GCG, which utilizes specific suffixes added to queries to achieve automated jailbreaking.

The second, termed *embedding-based jailbreak*, initially optimizes token embeddings and subsequently converts them into discrete tokens. However, it is observed that the optimized embeddings will typically have no corresponding discrete token. To this end, the Prompts Made Easy (PEZ) algorithm [23], uses a quantized optimization approach to adjust a continuous embedding, then projects them back into the discrete token space.

# 3 Our Approach

### 3.1 Overview

Our approach have four steps, where its workflow is shown in Fig.2. At Step-1, we construct a MLLM by introducing a visual module and then perform MLLM-jailbreaking. At Step-2, the jailbreaking embedding (embJS) obtained at Step-1 are converted to the textual jailbreaking suffix (txtJS). Finally, we leverage these txtJS to achieve LLM-jailbreaking at Step-3.

Our empirical study shows that the Attack Success Rate (ASR) of jailbreaking is sensitive to the initial input image (*InitJS*), which is used to initialize MLLM-



Figure 2: The full workflow of our approach. Before Step1, we propose to an image-text matching scheme to identify an appropriate initial input (InitJS) at Step0.

jailbreaking. To find an appropriate InitJS, we propose an image-text semantic matching scheme as the Step-0 in our approach.

### 3.2 MLLM Construction

Given a target LLM, a multimodal LLM can be constructed by incorporating a visual module and connecting it to the target LLM. After that, we have two options to fine-tune the MLLM: one option is to freeze the LLM, and the other is to fine-tune the LLM. For examples, MiniGPT-4 adopts the freezing option, while MiniGPT-v2 adopts the fine-tuning option. We adopt the first option since our goal is to jailbreak the LLM; thus, we need to maintain the LLM within the MLLM as the same as the target LLM.

Regarding the visual module, we adopt the approach of MiniGPT-4 (LLaMA2 version), combining the ViT-G/14 from CLIP and a single projection layer. The CLIP visual encoder remains frozen, while only the projection layer is fine-tuned. In this paper, we consider LLaMA2 as the target LLM, hence our constructed MLLM is precisely the MiniGPT-4 model. However, it's worth noting that we can choose any LLM as the target. In such cases, after constructing it, we need to fine-tune the projection layer by using a multimodal dataset.

### 3.3 MLLM-jailbreaking

We adopt the similar strategy of LLM-jailbreak to perform MLLM-jailbreak, *i.e.*, encouraging the MLLM to output an answer beginning with a positive affirmation, such as "Sure, here is a (content of query)". Specifically, our approach is inspired by adversarial attacks, which attempt to manipulate a model's output by perturbing the visual input images. However, jailbreaking attacks differ from adversarial attacks in that jailbreaking deals with a generative task rather than a discriminative one. Therefore, to adapt adversarial attack techniques to the jailbreaking task, we propose replacing the cross-entropy objective function with a maximum likelihood objective function, aiming to maximize the likelihood for MLLM to produce a positive affirmation. Specifically, for each harmful request  $q_i$ , we provide a corresponding target answer  $a_i$ , creating a dataset of harmful behaviors  $B = \{(q_i, a_i), i = 0, ..., N\}$ . And then, MLLM-jailbreak are formulated as finding a  $\delta$  such that it encourages the generation of the target answer  $a_i$  in response to the harmful query  $q_i$ , as follows,

$$\max_{\delta} \sum_{i=0}^{M} log(p(a_i|q_i, \widetilde{x}))$$
(1)  
s.t.  $\widetilde{x} \in [0, 255]^d, \widetilde{x} = x_{init} + \delta$   
 $||\delta||_p < \epsilon$ 

where  $p(a_i|q_i, x_{jp})$  is the likelihood for a MLLM generate  $a_i$  when provided with image  $\tilde{x}$  and text query  $q_i$ ,  $\epsilon$  is the attack budget, and  $\tilde{x}$  is the jailbreaking image (imgJS). Note that the optimization process is taken over M query-answer pairs  $\{(q_i, a_i), i = 0, ..., M\}$ . This problem can be efficiently addressed by modifying the Projected Gradient Decent (PGD) algorithm [24].

### 3.4 LLM-jailbreaking

After completing MLLM-jailbreaking, we transition to the next phase: LLMjailbreaking. While it may seem unnecessary to proceed to LLM-jailbreaking (because we have achieved the jailbreaking goal), our *double jailbreaking workflow* offers two distinct advantages. First, it can further improve the jailbreaking ASR in white-box scenarios. Second, it provides flexibility for black-box jailbreaking, wherein MLLM-jailbreaking targets a surrogate model rather than the actual target model.

To facilitate the subsequent black-box LLM-jailbreaking, we should output the textual txtJS rather than the jailbreaking image imgJS. Note that it is the output of the visual module, which serves as the input to the LLM, that enables the jailbreaking process. We refer to this output as embJS, as it consists of a sequence of continuous embeddings, functioning similarly to the embedding of txtJS in conventional LLM-jailbreaks. Hence, transitioning from MLLMjailbreaking to LLM-jailbreaking simply involves converting the embJS back to the text space, yielding a text string. This converted text string can be regarded as txtJS.

In our approach, we propose De-embedding and De-tokenizer operations to convert embJS to txtJS. This operations aim to reverse the Embedding and Tokenizer operations. In LLMs, the embedding operation converts each discrete token t to its embedding vector e, by looking up a token-embedding (t, e)dictionary. Therefore, our De-embedding operation is designed to reverse this process—convert a continuous embedding vector back into a specific token. This involves a nearest neighbor search across the dictionary. For each embedding vector  $e_l$  in embJS  $(e_0, e_1, ..., e_{L-1})$ , we identify the top-K similar embeddings  $\hat{e}_l^k, k = 0, ..., K - 1$  in the dictionary. Repeating this process for all  $e_l, l =$ 0, ..., L - 1, yields a  $K \times L$  embedding pool  $\{\hat{e}_l^k\}_{k=0,l=0}^{K,L}$  and a corresponding  $K \times L$  token pool  $\{\hat{t}_l^k\}_{k=0,l=0}^{K,L}$ . Consequently, De-tokenizer operation is designed to further convert those tokens back into words, yielding a  $K \times L$  word pool  $\{\hat{w}_l^k\}_{k=0,l=0}^{K,L}$ . Finally, we can randomly sample several sequences of words (*i.e.*, each sampled sequence is regarded as one txtJS) from this word pool.

It is worth noting that we select the top-K nearest embeddings instead of just the top-1 embedding. It allows us to output *several* txtJS rather than just one. Moreover, we find that each of these txtJS has a certain probability of achieving jailbreak. Therefore, by ensembling these high-quality txtJS, the final jailbreaking performance can be significantly improved.

In the context of black-box jailbreaking, our approach offers another advantage. Even though the backbone of the target LLM is unknown, if we know its tokenizer, we can design our De-tokenizer accordingly. As a result, the final black-box jailbreaking ASR can be significantly improved. This is because different LLMs tend to learn similar embedding spaces [25], with their main differences lying in the tokenizer. By canceling the differences stemming from the tokenizer, the *transferability* among distinct models can be enhanced.

### 3.5 Finding an appropriate InitJS

We observe that if an appropriate initJS is used to initialize MLLM-jailbreaking, we can significantly improve the MLLM-jailbreaking ASR. To this end, we propose an image-text semantic matching scheme. Particularly, our aim is to ensure that the embedding of InitJS is close to the embedding of harmful queries. The motivation behind this is that for a successful MLLM-jailbreaking, the InitJS should have a significant impact on the answer generation process of the LLM. For example, it is desired for jailbreaking to turn the answer from "Sorry, I cannot" to "Sure, here is" in response to a query. If the embedding of InitJS is close to the embedding of query, InitJS can effectively interact with the query via the LLM's cross-attention mechanism, thereby significantly influencing the answer generation process of LLM.

Specifically, our image-text semantic matching scheme adopts a network similar to the CLIP model, as shown in Fig.2. Given that the CLIP visual encoder is utilized as the visual module in the MLLM, our image-text matching network adopts the same visual encoder. Besides, we incorporates the CLIP text encoder. For the text input, we randomly select several keywords closely related to a specific harmful behavior. For instance, in the case of *weapons crimes*, these keywords might include *firearms*, *illegal weapons*, *guns*, *etc*. Next, we construct phrases using these keywords, such as "a photo of firearms", *etc*, which are more suitable for the CLIP text encoder.

Regarding the image input, we first use an image search engine to retrieve some candidate images using these keywords as search queries. Then, we rank them according to their CLIP similarity score corresponding to the harmful phrases. The top-ranked image is selected as the input for the visual encoder. Subsequently, we propose an optimization algorithm to modify the input image, aiming to make its embedding as close as possible to the embedding of harmful phrases. Let's denote the harmful phrases as  $\{t_i\}_{i=0}^N$  and the top-ranked image as x. Our image-text matching algorithm aims to add a perturbation  $\Delta$  image x to enlarge the image-text matching score, as follows,

$$\min_{\Delta} \sum_{i=0}^{N} log(\mathcal{L}_{\text{CLIP}}(\text{Enc}_{V}(\widetilde{x}), \text{Enc}_{L}(t_{i}))$$
(2)  
s.t.  $\widetilde{x} \in [0, 255]^{d}, \widetilde{x} = x + \Delta$ 

where  $\text{Enc}_V$  is the CLIP visual encoder,  $\text{Enc}_L$  is the CLIP text encoder, and  $\tilde{x}$  is the InitJS.

## 4 Evaluation

Evaluating the success of jailbreaking is complex. Jailbreaking, unlike classification tasks, is a generative task where the goal is to elicit the LLM to generate *any* response that aligns with the instruction given. Providing a ground truth response for a specific harmful query can be challenging. Indeed, some previous methods rely on checking if the response begins with a positive affirmation (e.g., "Sure, here is a"). However, we have observed some instances that even if a response starts with a positive affirmation, the subsequent content actually refuses to answer the query. Thus, relying solely on positive affirmations to judge the success of jailbreaking is not reliable. As a result, most methods rely on manual checks to determine the success of the jailbreak. Obviously, this manual verification process is time-consuming and challenging to maintain consistency across different evaluators. In this paper, we propose to utilize a model-based method to automatically determine the success of jailbreaking. Fortunately, a powerful tool *LLaMA Guard 2* has been published recently. Therefore, we use it to assess the success of jailbreaking in our approach.

#### 4.1 Implementation

**Data sets.** Some datasets have been proposed for the evaluation of jailbreaking, such as *AdvBench* [7]. They contain various types of harmful behaviors, such as violence, financial crimes, drug crimes, *etc.* However, previous methods tend to mix them together during evaluation. In contrast, we propose categorizing them into fine-grained classes and conducting evaluations on each class individually. We noticed that some classes inherently pose more challenges for jailbreaking compared to others. Moreover, we can also assess the cross-class transferability of jailbreak. This entails examining whether the txtJS generated for one class can effectively jailbreak other classes.

Specifically, we categorize *AdvBench* into nine classes: "unlawful violence", "financial crimes", "property crimes", "drug crimes", "weapons crimes", "cyber crimes", "hate", "Suicide and Self-Harm", and "Fake info". Furthermore, since our approach involves MLLM-jailbreaking, we extent the AdvBench dataset to a multimodal dataset, which we call the *AdvBench-M* dataset, by supplementing it with images. Specifically, for each harmful class, 30 semantic-relevant images were retrieved from the Internet using the Google search engine. Then, employ CLIP ViT-L/14 [26] to select top 10 images that best matches the semantic representation of the queries associated with the harmful class.

**Test models.** We evaluate our approach on several comparably-sized open models, including LLaMA-2-Chat-7B [27], Mistral-7B-v0.2 [28], Gemma-7B [29], ChatGLM-6B [30] as well as proprietary ones including GPT-3.5 (gpt-3.5-turbo). For white-box jailbreaking, we evaluate our approach on LLaMA-2-Chat-7B. For evaluating black-box jailbreaking, we generate the txtJS on LLaMA-2-Chat-7B and subsequently employ it for jailbreaking on GPT-3.5, Gemma-7B, Mistral-7B, and ChatGLM-6B.

### 4.2 White-box Jailbreaking

We compare our approach with both discrete optimization-based methods (*i.e.*, AutoPrompt[31], GCG[7]) and embedding-based methods (*i.e.*, PEZ, Soft Prompting). The first type, particularly the GCG method, is regarded as the state-of-the-art methods. We conduct individual evaluations on each class of the AdvBench-M dataset. Specifically, for each class, we randomly sample 15 queries as the training set  $D_{train}$  for learning the txtJS, while the remaining queries are considered the testing set  $D_{test}$ . When evaluating the ability of cross-class jailbreak, all classes except the training class are mixed as  $D_{test}^{other}$ . For example, we can learn a txtJS on Class1's  $D_{train}^1$ , and assess its jailbreaking performance on Class1's  $D_{test}^1 \cdots \cup D_{test}^9$ .

Compare to discrete optimization-based jailbreak. We employ the ASR as the primary metric, calculating ASR for each class on its  $D_{train}$ ,  $D_{test}$ , and  $D_{test}^{other}$ , respectively. From Table.1, we found that the class 7 ("hate") is more difficult to jailbreak than other classes. We speculate that recent LLMs have been enhanced to specifically defend against this class of harmful behaviors. Additionally, even with the introduction of visual modality, as our approach does, successfully jailbreaking it remains difficult. This is because this concept is very abstract, making it difficult to find suitable images to describe it. Thus, our visual module may *not* have a significant impact on the answer generation process of LLM.

In contrast, regarding the class 5 ("weapons crimes"), our approach significantly outperforms the GCG, improving the ASR on  $D_{test}$  from 66.67% to 88.89%. "weapons crimes" is a concept with a strong visual imagery. Thus, the cross-attention between visual input and textual queries becomes strong, thereby facilitating the success of jailbreaking.

Generally, we can observe that our approach is superior to GCG for the majority of classes. Regarding the ability of cross-class jailbreaking, our approach still outperforms the GCG. For example, for the class 5, the ASR on  $D_{test}^{other}$  is 66.25%, while our approach achieves 78.50%.

More importantly, the key advantage of our approach over discrete optimizationbased methods lies in its efficiency. We compared the running time between our

Table 1: White-box Jailbreaking in terms of ASR on  $D_{train}$ ,  $D_{test}$ , and  $D_{test}^{other}$ .

|         |                   |            |  | -                |                    |             |   |                    |             |                 |                    |
|---------|-------------------|------------|--|------------------|--------------------|-------------|---|--------------------|-------------|-----------------|--------------------|
| Class   | AutoP $D_{train}$ | $T_{test}$ | $\left  \begin{array}{c} \text{Soft} \\ D_{train} \end{array} \right $ | Promp $D_{test}$ | $D_{test}^{other}$ | $D_{train}$ | $\begin{array}{c} \text{GCG} \\ D_{test} \end{array}$ | $D_{test}^{other}$ | $D_{train}$ | Ours $D_{test}$ | $D_{test}^{other}$ |
|         |                   |            |  |                  |                    |             |   |                    |             |                 |                    |
| Class 1 | 66.00             | 50.00      | 20.00  | 44.44            | 36.25              | 80.00       | 83.33   | 78.75              | 100.0       | 94.44           | 85.00              |
| Class 2 | 80.00             | 93.33      | 40.00  | 32.14            | 37.50              | 100.0       | 89.28   | 81.25              | 93.33       | 98.21           | 74.50              |
| Class 3 | 73.33             | 84.38      | 80.00  | 62.50            | 36.25              | 100.0       | 98.44   | 97.50              | 93.33       | 98.44           | 69.88              |
| Class 4 | 73.33             | 80.00      | 53.33  | 40.00            | 41.25              | 100.0       | 80.00   | 86.25              | 80.00       | 100.0           | 77.00              |
| Class 5 | 40.00             | 66.67      | 33.33  | 33.33            | 40.00              | 73.33       | 66.67   | 66.25              | 80.00       | 88.89           | 78.50              |
| Class 6 | 73.33             | 86.15      | 53.33  | 53.49            | 32.50              | 100.0       | 66.67   | 87.50              | 93.33       | 94.19           | 72.13              |
| Class 7 | 73.33             | 66.67      | 20.00  | 6.67             | 42.50              | 53.33       | 66.67   | 80.00              | 73.33       | 60.00           | 81.75              |
| Class 8 | 73.33             | 16.66      | 33.33  | 22.22            | 42.50              | 53.33       | 38.89   | 80.00              | 60.00       | 44.44           | 78.88              |
| Class 9 | 73.33             | 93.33      | 33.33  | 6.67             | 30.00              | 80.00       | 86.66   | 66.25              | 93.33       | 86.67           | 93.33              |

approach and GCG. Specifically, GCG takes 11.2 hours to find one txtJS for a single harmful class, whereas our approach takes only 0.37 hours.

**Compare to embedding-based jailbreak.** For discrete optimization-based jailbreak, while it can directly find the jailbreaking suffix, it often suffers from efficiency issues due to the challenging nature of discrete optimization. In contrast, the *embedding-based jailbreak* can leverage straightforward and efficient continuous optimization since token embeddings are continuous variables. This technique is often referred to as "soft prompting" [32, 33, 34] in other literature and has demonstrated advantages in the Prompt Engineering domain. However, as pointed out in [7], this type of method is ineffective in LLM-jailbreaking because the optimized embeddings (*i.e.*, soft prompts) often have no corresponding discrete token. For example, we observed similar results to [7] where the PEZ method *totally* failed to jailbreak, *i.e.*, ASR = 0 for all classes.

We argue that this is because no constraints are imposed on the process of embedding optimization. In contrast, **the embedding optimization in our approach is** *regularized* **by the visual module**. Actually, we conduct imgJS optimization instead of optimizing embJS directly. Since the visual module (*e.g.*, CLIP encoder) is trained with an image-text alignment objective, it can ensure that the embJS have corresponding discrete token. As a result, the embJS can be *accurately* converted to txtJS, with less conversion error.

To validate our analysis, we quantitatively measure the error in converting token embeddings to discrete tokens. For both *Soft Prompting* method and our approach, after converting embJS  $e^k$  to txtJS (through nearest neighbor search), we obtain the txtJS's embedding  $\hat{e}^k$ , and calculate the cosine similarity (*Sim*) between  $\hat{e}^k$  and  $e^k$ . Obviously, the higher the similarity score, the lower the conversion error. In our experiments, we have the average of *Sim* for soft prompting as  $\text{Sim}_{sp} = 0.47$ , while the average of *Sim* for our method is  $\text{Sim}_{ours} = 5.02$ . This experimental results exactly justify our analysis.

### 4.3 Black-box Jailbreaking

Regarding to the black-box Jailbreaking, we adopt the transferring strategy, where a txtJS is trained on a surrogate model and then utilized to jailbreak other

Table 2: Black-box Jailbreaking. For ChatGLM, we utilize its Tokenizer to design our De-tokenizer, whereas for other models, we design the De-tokenizer according to Llama2's Tokenizer.

| Class   | ChatGLM | Mistral | $\operatorname{Gemma}$ | GPT-3.5 |
|---------|---------|---------|------------------------|---------|
| Class 1 | 15.15   | 57.57   | 78.78                  | 45.45   |
| Class 2 | 26.76   | 87.32   | 59.15                  | 59.15   |
| Class 3 | 29.11   | 81.01   | 69.62                  | 60.75   |
| Class 4 | 30.00   | 76.67   | 46.67                  | 66.67   |
| Class 5 | 18.18   | 36.36   | 81.82                  | 45.45   |
| Class 6 | 17.82   | 91.09   | 90.09                  | 62.37   |
| Class 7 | 23.33   | 56.67   | 33.33                  | 68.96   |
| Class 8 | 15.15   | 39.39   | 57.58                  | 42.42   |
| Class 9 | 43.33   | 96.67   | 90.00                  | 73.33   |

models. Specifically, we generate the txtJS with respect to LLaMA2. Subsequently, we utilize them to attack GPT-3.5, Mistral-7B, Gemma-7B, ChatGLM-6B, respectively. Empirical studies illustrate that our approach exhibits notable transferability, as shown in Table 2.

More importantly, our approach has another advantage in black-box jailbreaking. Specifically, **if we know the tokenizer of the target LLM (without requiring knowledge of its backbone)**, we can significantly enhance blackbox jailbreaking. In detail, during Step 2 of our approach, we just need to design our De-tokenizer in accordance with the tokenizer of the target LLM.

The underlying reasoning is that there is a significant overlap in the training data for different LLMs, suggesting that these LLMs tend to learn a similar embedding space. The primary distinction among LLMs lies in their tokenization, leading to divergent vocabularies and embeddings. As a results, if our Detokenizer accurately corresponds to the tokenizer of the target LLM, we can ensure that the embeddings between the surrogate and target LLM are properly aligned. Consequently, successful transfer of jailbreaking becomes feasible due to the similar embedding spaces.

This can be confirmed through our experiments on the ChatGLM-6B model. We know that the tokenizer between LLaMA2 and ChatGLM-6B is different. If we design the De-tokenizer according to LLaMA2's tokenizer, we *totally* failed to jailbreak ChatGLM-6B, *i.e.*, ASR = 0 for all classes. However, if our De-tokenizer corresponds to ChatGLM's tokenizer, we can significantly enhance the jailbreaking ASR, as illustrated in Table 2.

#### 4.4 Discussion

#### 4.4.1 Image-text Semantic Matching

As aforementioned, the MLLM-jailbreaking is conducted by perturbing the InitJS with a perturbation  $\delta$ , *i.e.*, imgJS = InitJS +  $\delta$ . In this section, we will illiterate that finding an appropriate *InitJS* is crucial for both successful MLLM-jailbreaking and subsequent LLM-jailbreaking.

Table 3: Image-text Semantic Matching. We compare three initialization schemes.

| Initialization | Clip-score |             | MLLM       | 1                   | LLM         |            |                     |  |
|----------------|------------|-------------|------------|---------------------|-------------|------------|---------------------|--|
| Initialization |            | $D_{train}$ | $D_{test}$ | $D_{test}^{others}$ | $D_{train}$ | $D_{test}$ | $D_{test}^{others}$ |  |
| Random-based   | 0.1473     | 73.32       | 72.03      | 73.42               | 80.74       | 74.88      | 75.62               |  |
| Ranking-based  | 0.2083     | 75.18       | 76.75      | 75.44               | 82.22       | 77.07      | 75.94               |  |
| Ours           | 0.5773     | 83.70       | 80.13      | 76.61               | 87.40       | 85.03      | 78.99               |  |

In our experiments, we compare three schemes for determining InitJS. The first involves randomly sample an image from all images in AdvBench-M dataset, which could come from any harmful class. The second scheme narrows down the sampling range to the same harmful class corresponding to the harmful query. Furthermore, we employ CLIP ViT-L/14 to select the image that best matches the semantics of the harmful class. The second scheme is referred to as the *ranking-based* scheme. The third scheme is our proposed image-text semantic matching-based scheme (Sec 3.5).

We compare the three initializing schemes, as shown in Table 3. In terms of CLIP score, we observed that ranking-based scheme is slightly better than random sampling scheme. In contrast, the CLIP score can be significantly improved by our image-text matching scheme. This is because our approach aims to *directly* optimize the InitJS with respect to the CLIP similarity score.

In terms of jailbreaking ASR, we can see that an appropriate InitJS can simultaneously enhance both the MLLM-jailbreaking ASR and the LLM-jailbreaking ASR. As the CLIP similarity score increases, the jailbreaking ASR consistently improves. We argue that if the embeddings of InitJS and the query become similar, they will effectively interact with each other via the LLM's cross-attention mechanism, thereby influencing the LLM's generation process and achieving jailbreak.

From Table 3, we also observe that the LLM-jailbreaking ASR is better than the MLLM-jailbreaking ASR. This verifies that our double jailbreaking workflow can improve ASR in the white-box scenario.

#### 4.4.2 Cross-class Generalization

Generalization is a desirable property for real-world jailbreaking, indicating that the txtJS trained/generated for specific harmful queries can still effectively jailbreak other unseen harmful queries. Previous work has shown that certain jailbreaking methods possess this generalization capability [7]. However, the generalization property is evaluated over all mixed harmful queries. Instead, we evaluate *cross-class generalization*, where the txtJS is trained for a specific harmful class and then tested on other unseen harmful classes.

Different from previous sections (Sec4.2, Sec4.4.1) that evaluate *coarse* crossclass generalization over  $D_{test}^{other}$ , this section performs a fine-grained evaluation. For example, after generating one txtJS on class1's  $D_{train}^1$ , we will calculate its ASR over  $D_{test}^2$ ,  $D_{test}^3$ , ...,  $D_{test}^9$  separately. This entails examining whether the txtJS generated for one class can effectively jailbreak other classes.

The cross-class generalization for LLM-jailbreaking is evaluated, as shown in



Figure 3: Cross-class generalization for LLM-jailbreaking. For example, the first row indicates that we generate txtJS on Class1 and use it to jailbreak Class1, Class2, ..., Class9, respectively.

Fig.3. We observe that classes 2 ("financial crimes"), 3 ("property crimes") and 6 ("cyber crimes") are easily generalized. The txtJS generated from any harmful class can effectively be used to jailbreak these three classes. In contrast, classes 7 ("hate") and 8 ("Suicide and Self-Harm") are difficult to generalize. Even when using the txtJS generated from these two classes, the testing ASR on themselves is low (refer to the diagonal in Fig.3).

Additionally, we note that the cross-class generalization varies across different classes. The correlation between two specific classes exhibit greater strength than others. For instance, the txtJS obtained for class 1 ("unlawful violence") can effectively jailbreak class 9 ("Fake info"), while the txtJS from class 5 ("weapons crimes") can effectively jailbreak class 4 ("drug crimes"). This phenomenon suggests that to enhance the ASR for a particular class, we can utilize not only the harmful queries from that class but also those from its correlated classes. This is particularly beneficial, **especially when gathering queries for a specific harmful class is difficult**. In our future work, we will attempt to uncover the underlying reasons behind the correlation among specific harmful classes.

## 5 Conclusion

This paper presents an efficient LLM-jailbreaking method by constructing a multimodal LLM and performing MLLM-jailbreak. Compared to discrete optimizationbased jailbreaking, our approach is highly efficient, targeting the vulnerable visual module in MLLM. In contrast to embedding-based jailbreaking, our approach leverages the visual module as a regularizer to ensure that our embJS have corresponding discrete tokens. Additionally, the double jailbreaking workflow of our approach offers flexibility for both white-box and black-box jailbreaking. Furthermore, fine-grained and automatic jailbreaking evaluation is conducted, demonstrating that our approach surpasses current state-of-the-art jailbreaking methods in terms of both efficiency and effectiveness.

# References

- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. Advances in neural information processing systems, 33:1877–1901, 2020.
- [2] Samuel Gehman, Suchin Gururangan, Maarten Sap, Yejin Choi, and Noah A Smith. Realtoxicityprompts: Evaluating neural toxic degeneration in language models. arXiv preprint arXiv:2009.11462, 2020.
- [3] Ethan Perez, Saffron Huang, Francis Song, Trevor Cai, Roman Ring, John Aslanides, Amelia Glaese, Nat McAleese, and Geoffrey Irving. Red teaming language models with language models, february 2022a. URL https://arxiv. org/abs/2202.03286 v1.
- [4] Emily Sheng, Kai-Wei Chang, Premkumar Natarajan, and Nanyun Peng. The woman worked as a babysitter: On biases in language generation. arXiv preprint arXiv:1909.01326, 2019.
- [5] Abubakar Abid, Maheen Farooqi, and James Zou. Persistent anti-muslim bias in large language models. arXiv 2021. arXiv preprint arXiv:2101.05783.
- [6] Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, et al. Extracting training data from large language models. In 30th USENIX Security Symposium (USENIX Security 21), pages 2633–2650, 2021.
- [7] Andy Zou, Zifan Wang, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. arXiv preprint arXiv:2307.15043, 2023.
- [8] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. Advances in neural information processing systems, 36, 2024.
- [9] Wenliang Dai, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Junqi Zhao, Weisheng Wang, Boyang Li, Pascale N Fung, and Steven Hoi. Instructblip: Towards general-purpose vision-language models with instruction tuning. Advances in Neural Information Processing Systems, 36, 2024.
- [10] Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. Minigpt-4: Enhancing vision-language understanding with advanced large language models. arXiv preprint arXiv:2304.10592, 2023.

- [11] Jun Chen, Deyao Zhu, Xiaoqian Shen, Xiang Li, Zechun Liu, Pengchuan Zhang, Raghuraman Krishnamoorthi, Vikas Chandra, Yunyang Xiong, and Mohamed Elhoseiny. Minigpt-v2: large language model as a unified interface for vision-language multi-task learning. arXiv preprint arXiv:2310.09478, 2023.
- [12] Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. Advances in neural information processing systems, 35:23716–23736, 2022.
- [13] Qinghao Ye, Haiyang Xu, Guohai Xu, Jiabo Ye, Ming Yan, Yiyang Zhou, Junyang Wang, Anwen Hu, Pengcheng Shi, Yaya Shi, et al. mplug-owl: Modularization empowers large language models with multimodality. arXiv preprint arXiv:2304.14178, 2023.
- [14] Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A frontier large vision-language model with versatile abilities. arXiv preprint arXiv:2308.12966, 2023.
- [15] Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. Gemini: a family of highly capable multimodal models. arXiv preprint arXiv:2312.11805, 2023.
- [16] Gpt-4v(ision) system card. 2023.
- [17] Erfan Shayegani, Yue Dong, and Nael Abu-Ghazaleh. Jailbreak in pieces: Compositional adversarial attacks on multi-modal language models. In *The Twelfth International Conference on Learning Representations*, 2023.
- [18] Xiangyu Qi, Kaixuan Huang, Ashwinee Panda, Peter Henderson, Mengdi Wang, and Prateek Mittal. Visual adversarial examples jailbreak aligned large language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 21527–21536, 2024.
- [19] Llama Team. Meta llama guard 2. https://github.com/meta-llama/ PurpleLlama/blob/main/Llama-Guard2/MODEL\_CARD.md, 2024.
- [20] Xinyue Shen, Zeyuan Chen, Michael Backes, Yun Shen, and Yang Zhang. " do anything now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models. arXiv preprint arXiv:2308.03825, 2023.
- [21] Gelei Deng, Yi Liu, Yuekang Li, Kailong Wang, Ying Zhang, Zefeng Li, Haoyu Wang, Tianwei Zhang, and Yang Liu. Jailbreaker: Automated jailbreak across multiple large language model chatbots. arXiv preprint arXiv:2307.08715, 2023.

- [22] Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. Autodan: Generating stealthy jailbreak prompts on aligned large language models. *arXiv* preprint arXiv:2310.04451, 2023.
- [23] Yuxin Wen, Neel Jain, John Kirchenbauer, Micah Goldblum, Jonas Geiping, and Tom Goldstein. Hard prompts made easy: Gradient-based discrete optimization for prompt tuning and discovery. Advances in Neural Information Processing Systems, 36, 2024.
- [24] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. arXiv preprint arXiv:1706.06083, 2017.
- [25] Minyoung Huh, Brian Cheung, Tongzhou Wang, and Phillip Isola. The platonic representation hypothesis. arXiv preprint arXiv:2405.07987, 2024.
- [26] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748– 8763. PMLR, 2021.
- [27] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. arXiv preprint arXiv:2307.09288, 2023.
- [28] Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. arXiv preprint arXiv:2310.06825, 2023.
- [29] Gemma Team, Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, et al. Gemma: Open models based on gemini research and technology. arXiv preprint arXiv:2403.08295, 2024.
- [30] Zhengxiao Du, Yujie Qian, Xiao Liu, Ming Ding, Jiezhong Qiu, Zhilin Yang, and Jie Tang. Glm: General language model pretraining with autoregressive blank infilling. arXiv preprint arXiv:2103.10360, 2021.
- [31] Reid Pryzant, Dan Iter, Jerry Li, Yin Tat Lee, Chenguang Zhu, and Michael Zeng. Automatic prompt optimization with" gradient descent" and beam search. arXiv preprint arXiv:2305.03495, 2023.
- [32] Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. arXiv preprint arXiv:2104.08691, 2021.
- [33] Guanghui Qin and Jason Eisner. Learning how to ask: Querying lms with mixtures of soft prompts. arXiv preprint arXiv:2104.06599, 2021.

[34] Tu Vu, Brian Lester, Noah Constant, Rami Al-Rfou, and Daniel Cer. Spot: Better frozen model adaptation through soft prompt transfer. *arXiv preprint arXiv:2110.07904*, 2021.