

SPEECH EMOTION RECOGNITION WITH ASR TRANSCRIPTS: A COMPREHENSIVE STUDY ON WORD ERROR RATE AND FUSION TECHNIQUES

Yuanchao Li, Peter Bell, Catherine Lai

Centre for Speech Technology Research, University of Edinburgh

ABSTRACT

Text data is commonly utilized as a primary input to enhance Speech Emotion Recognition (SER) performance and reliability. However, the reliance on human-transcribed text in most studies impedes the development of practical SER systems, creating a gap between in-lab research and real-world scenarios where Automatic Speech Recognition (ASR) serves as the text source. Hence, this study benchmarks SER performance using ASR transcripts with varying Word Error Rates (WERs) on well-known corpora: IEMOCAP, CMU-MOSI, and MSP-Podcast. Our evaluation includes text-only and bimodal SER with diverse fusion techniques, aiming for a comprehensive analysis that uncovers novel findings and challenges faced by current SER research. Additionally, we propose a unified ASR error-robust framework integrating ASR error correction and modality-gated fusion, achieving lower WER and higher SER results compared to the best-performing ASR transcript. This research is expected to provide insights into SER with ASR assistance, especially for real-world applications.

Index Terms— Speech Emotion Recognition, Word Error Rate, Fusion Techniques, ASR Error Correction

1. INTRODUCTION

Emotion in speech is conveyed through both what is said (i.e., text) and how it is said (i.e., audio). Recent studies on Speech Emotion Recognition (SER) consistently highlight the benefits of combining textual and acoustic features [1, 2, 3, 4]. Despite the advancements in SER over the years, its practical application in everyday contexts remains limited. One significant challenge is the reliance on human-annotated text, known as gold-standard manual transcripts, in most bimodal SER research. In contrast, transcripts generated by Automatic Speech Recognition (ASR) systems, even state-of-the-art ones, often suffer from high Word Error Rates (WERs), particularly in emotional speech [5]. To this end, the findings from lab settings may not effectively translate to real-world scenarios, impeding the true progress of SER.

To address this gap, it is crucial to investigate the impact of imperfect text data generated by ASR on SER. While previous studies have explored the question of “*how ASR perfor-*

mance affects SER”, the findings have been inconsistent and not comprehensive. For instance, Schuller et al. observed that a WER of over 30% resulted in an SER accuracy drop of less than 3% on the FAU Aibo Emotion Corpus [6], while Li et al. reported a nearly 10% accuracy drop with a 30% WER on IEMOCAP [5]. Besides, while multimodal fusion techniques have been proposed and studied extensively to enhance emotion recognition performance, their compatibility with ASR transcripts remains underexplored [7, 8, 9].

In this study, we begin with a benchmark investigation into SER performance utilizing ASR transcripts. First, we generate ASR transcripts from various ASR systems to achieve different WERs. Subsequently, we conduct SER exclusively on these transcripts to assess the impact of ASR errors on text-only SER performance. Finally, we merge audio features and conduct bimodal SER to evaluate whether fusion techniques, effective with ground-truth text, also exhibit efficacy with ASR transcripts (i.e., whether they are ASR error-robust). Following the benchmark study, we propose an ASR error-robust SER framework by integrating ASR error correction with modality-gated fusion to tackle both WER and fusion issues in SER. The contributions of this work are summarized as follows:

- As the first work to benchmark SER performance with ASR transcripts, we offer comprehensive results and novel analysis across diverse corpora, varying WERs, and multiple fusion techniques. This paves the way for SER research with ASR assistance, bringing SER closer to practical applications.
- We propose an ASR error-robust framework that integrates two-stage ASR error correction and dynamic modality-gated fusion, aiming to reduce word errors and mitigate the negative effects of high WER.

2. RELATED WORK: LITERATURE REVIEW

Over the past several years, significant progress has been achieved in SER through the utilization of ASR transcripts. Specifically, in chronological order:

Yoon et al. (2018) proposed a deep dual recurrent encoder model that simultaneously utilizes audio signals and text data from the Google Cloud Speech API [3]. Sahu et al. (2019) utilized two commercial ASR systems to generate transcripts for bimodal SER (audio + text), resulting in

a relative loss of unweighted accuracy compared to ground-truth transcripts [10]. Li et al. (2020) introduced a temporal alignment mean-max pooling mechanism to capture subtle and fine-grained emotions in utterances, alongside a cross-modality excitement module for sample-specific adjustments on embeddings [11].

Santoso et al. (2021) proposed using a confidence measure to adjust the importance weights in ASR transcripts based on the likelihood of a speech recognition error in each word, effectively mitigating the effects of ASR errors on SER performance [12]. Wu et al. (2021) introduced a dual-branches model for ASR error robustness, with a time-synchronous branch combining speech and text modalities and a time-asynchronous branch integrating sentence text embeddings from context utterances [13]. Shon et al. (2021) generated pseudo labels on ASR transcripts for semi-supervised speech sentiment analysis [14].

Inspired by human perception mechanisms, Li et al. (2022) proposed hierarchical attention fusion of audio features, ASR hidden states, and ASR transcripts, achieving similar SER performance as ground-truth text [15]. Lin et al. (2023) explored complementary semantic information from audio to mitigate the impact of ASR errors, using an attention mechanism to calculate weighted acoustic representations fused with text representations of ASR hypotheses [16]. He et al. (2024) incorporated two auxiliary tasks, ASR error detection and ASR error correction, to enhance the semantic coherence of ASR text. They introduced a novel multi-modal fusion method to learn shared representations across modalities [17]. Feng et al. (2024) fused audio with ASR transcript from a powerful ASR model and identified that ASR-generated output delivers competitive SER performance compared to ground-truth transcripts [18].

While these studies have highlighted the effectiveness of integrating text features from ASR transcripts, there is still a lack of understanding regarding how WER and fusion techniques impact SER. Therefore, we undertake a benchmark study utilizing diverse ASR models and fusion techniques, conducting SER on various emotion corpora to obtain comprehensive results. Furthermore, drawing from the existing literature, we develop an ASR error-robust framework aimed at mitigating the side effect of WER (Code available¹).

3. ASR MODELS AND EMOTION CORPORA

ASR models. We adopt the following 11 models as they are widely used in the speech area and can provide varying WERs.

- *Wav2Vec2-base-{100h,960h}*
- *Wav2Vec2-large-960h*
- *Wav2Vec2-large-960h-lv60-self*
- *HuBERT-large-ls960-ft*

- *WavLM-libri-clean-100h-base-plus*
- *Whisper-{tiny, base, small, medium, large-v2}.en*

Emotion corpora. To ensure generalizability, we utilize three corpora: IEMOCAP [19], CMU-MOSI [20], and MSP-Podcast [21], to include diverse speech conditions and various evaluation metrics.

IEMOCAP consists of five sessions of scripted and improvised dialogues conducted in a research lab. Our study focuses on four emotion classes: angry, happy (including excited), neutral, and sad. We exclude utterances with blank transcripts from this corpus, resulting in a total of 5,530 utterances. CMU-MOSI comprises 2,199 monologue video clips sourced from YouTube, each annotated with sentiment scores ranging from -3 to 3. MSP-Podcast contains English speech extracted from podcast recordings, annotated with valence, arousal, dominance scores in the range of 1 to 7, as well as categorical emotion labels. We use its Release 1.11 version and evaluate its performance on the Test1 set. We exclude utterances without an emotion label, resulting in a total of 104,663 utterances.

Following the literature, we calculate **Acc4** (four-class accuracy) on IEMOCAP, **Acc2** (binary accuracy), Concordance Correlation Coefficient (**CCC**) on MSP-Podcast, and **Acc7** (seven-class accuracy), and Mean Absolute Error (**MAE**) on CMU-MOSI. Since these metrics are commonly used for respective corpus, we omit detailed explanations.

We initially considered including MELD [22] (TV sitcom data) in our investigation. However, its WERs are almost twice as high as those of the other three corpora (ranging from 30% to 65%). Considering that performing SER using transcripts with such low ASR performance is not feasible in real-world scenarios, we opted to focus only on the other three corpora for our subsequent study. Nonetheless, we provide the WERs of MELD for reference (see Fig. 1).

4. BENCHMARK STUDY

4.1. SER Modeling

We employ RoBERTa-base as the text encoder. Given that transcripts generated by models other than *Whisper* lack punctuation, we remove punctuation from the transcripts of *Whisper* models to ensure a fair comparison. All letters are lowercased for consistency. A backbone SER model is built for all corpora. Since our goal is not to achieve state-of-the-art performance, the model simply comprises two dense layers: the first encodes RoBERTa output of dimension 768 into hidden states of dimension 128, and the second further encodes it into a dimension of 16. We utilize ReLU as the activation function between the dense layers. In the case of IEMOCAP, we apply one output layer with Softmax activation for classification. For MSP-Podcast and CMU-MOSI, which involve regression tasks, no final output activation is applied. We set the learning rate as $5e-4$ for IEMOCAP and CMU-MOSI, and

¹<https://github.com/yc-li20/SER-on-WER-and-Fusion>

1e-4 for MSP-Podcast, utilizing the AdamW optimizer. The weight decay is set as 1e-5, and the batch size is 64. For training, we employ five-fold cross-validation on IEMOCAP (100 epochs) and follow the official training/validation/testing sets on CMU-MOSI (100 epochs) and MSP-Podcast (30 epochs). The random seeds are kept consistent across all experiments.

4.2. Benchmarking SER with WER

Firstly, we present the WERs and corresponding SER performance based on transcripts from different ASR models. From Fig. 1, we observe that:

1) **SER performance generally decreases as WER increases.** On IEMOCAP and MOSI, there is nearly a 10% accuracy decrease with WERs around 40%, regardless of Acc2, Acc4, or Acc7. However, exceptions exist. For example, on IEMOCAP, *Whisper-tiny* produces higher accuracy than its neighboring models, even though the WERs are similar. Additionally, *W2V960-large-self* yields worse accuracy compared to its neighboring models, despite having a relatively lower WER compared to others. The same phenomenon can also be found with CMU-MOSI: Acc2 of *W2V100* higher than that of *WavLM plus*, and of *Whisper-large* lower than that of *Whisper-medium*. This might be due to certain words being misrecognized as words that have little effect, or even positively contribute to, their ground-truth emotion labels. Note that the values of our Acc4 are higher than that of [5], possibly because different training models, language models (RoBERTa vs. BERT), and word embeddings (full hidden states vs. pooler output).

2) **SER is robust to relatively low WER, and in some cases, it is even better with ASR errors.** From IEMOCAP, we observe that a WER around 12% barely affects SER performance compared to ground-truth transcripts. Furthermore, on CMU-MOSI, ASR errors can actually enhance SER: transcripts from certain *Whisper* models outperform the ground truth. Previous studies have confirmed that sentiment analysis is robust to ASR errors [23] in that positive or negative sentiment can contain various emotions. On top of this, we discover that in certain cases (e.g., certain corpora with relatively low WER), ASR errors do not decrease SER performance. In a recent study on speech-based dementia detection, it was found that ASR errors can provide important information for dementia classification [24]. This could be because certain types of ASR errors (e.g., repetitions, insertion of disfluencies) can reveal dementia. However, we do not believe the same holds true for SER. We attribute the phenomenon observed in our study to the same reason as in finding 1: *certain words being misrecognized as words that positively contribute to the ground-truth emotions.*

3) **Different metrics have different sensitivities to WER.** On CMU-MOSI, Acc7 exhibits a different pattern from Acc2 and MAE. The variations in Acc2 and MAE are consistent and smooth, while Acc7 appears to be random and

		IEMOCAP		MELD
ASR Model	WER ↓	Acc4 ↑	WER ↓	
w2v100	40.31	52.80	64.07	
wavlm plus	39.14	52.84	60.20	
w2v960	32.37	55.16	55.32	
w2v960 large	27.98	57.05	52.74	
whisper tiny	26.97	59.54	48.19	
hubert large	23.80	58.65	45.67	
w2v960 large self	21.90	57.35	41.19	
whisper base	20.27	60.77	40.66	
whisper small	14.44	61.89	33.03	
whisper medium	12.65	62.32	32.99	
whisper large	12.31	62.95	30.45	
ground truth	0.00	63.20	0.00	

		CMU-MOSI			
ASR Model	WER ↓	Acc2 ↑	Acc7 ↑	MAE ↓	
w2v100	41.83	72.41	27.70	1.1216	
wavlm plus	41.62	69.82	25.66	1.1351	
w2v960	35.93	73.63	29.88	1.0855	
w2v960 large	31.65	75.61	33.82	1.0279	
hubert large	28.89	76.83	29.15	0.9942	
w2v960 large self	27.40	78.81	31.92	0.9876	
whisper tiny	27.31	79.27	35.13	0.9545	
whisper base	22.72	80.18	34.55	0.9246	
whisper small	21.81	82.01	37.03	0.8998	
whisper medium	18.96	83.23	36.59	0.8668	
whisper large	18.69	82.01	36.88	0.8561	
ground truth	0.00	82.47	34.26	0.8974	

		MSP-Podcast			
ASR Model	WER ↓	CCC_v ↑	CCC_a ↑	CCC_d ↑	
w2v100	40.14	0.465	0.331	0.299	
wavlm plus	37.67	0.467	0.322	0.286	
w2v960	33.84	0.479	0.316	0.288	
w2v960 large	30.85	0.489	0.318	0.289	
hubert large	27.74	0.504	0.330	0.298	
w2v960 large self	25.12	0.494	0.311	0.286	
whisper tiny	24.63	0.503	0.313	0.286	
whisper base	19.35	0.521	0.315	0.289	
whisper small	15.60	0.525	0.318	0.290	
whisper medium	15.14	0.525	0.315	0.291	
whisper large	15.02	0.526	0.316	0.293	
ground truth	0.00	0.524	0.321	0.301	

Fig. 1. Benchmarking SER performance based on ASR transcripts across corpora. ↑: higher the better. ↓: lower the better. **Red bold**: a higher accuracy than the ground truth.

lacks a discernible pattern, with almost half of the transcripts (all from *Whisper*) outperforming the ground truth. This discrepancy may arise from the disparity between the regression model used for training (since MOSI is labeled with continuous values) and the classification metric (where the predicted and ground-truth values are grounded for Acc7), which possibly leads to blurred accuracy and WER-insensitive SER.

4) **Different emotion dimensions exhibit varying degrees of robustness to ASR errors.** From MSP-Podcast, it is evident that valence, arousal, and dominance exhibit distinct patterns. Firstly, the CCC of valence mirrors the pattern observed in Acc4 for IEMOCAP and Acc2 for CMU-

IEMOCAP								
ASR Model	WER	Text	Early	Late	Attn	Tensor	NL-gate	MISA
w2v100	40.31	52.80	69.12	66.37	68.46	70.49	67.26	70.15
wavlm plus	39.14	52.84	68.84	66.88	69.10	70.45	67.00	70.32
w2v960	32.37	55.16	69.43	67.69	69.47	70.98	68.51	71.43
w2v960 large	27.98	57.05	69.85	68.15	69.65	71.47	68.62	71.87
whisper tiny	26.97	59.54	71.20	68.90	70.79	72.73	70.02	73.05
hubert large	23.80	58.65	70.62	68.64	70.73	72.32	69.06	72.66
w2v960 large self	21.90	57.35	70.85	68.44	70.61	72.29	69.08	72.69
whisper base	20.27	60.77	72.63	69.60	71.54	73.73	70.96	73.60
whisper small	14.44	61.89	72.61	70.14	72.50	74.53	71.10	73.98
whisper medium	12.65	62.32	72.74	70.28	72.96	74.63	70.97	74.36
whisper large	12.31	62.95	73.01	70.68	73.03	74.66	71.68	74.51
ground truth	0.00	63.20	72.68	70.52	72.99	74.16	71.45	74.32
maximum diff		10.40	3.84	4.15	3.51	3.67	4.44	4.00

MSP-Podcast								
ASR Model	WER	Text	Early	Late	Attn	Tensor	NL-gate	MISA
w2v100	40.14	0.365	0.603	0.532	0.594	0.481	0.579	0.585
wavlm plus	37.67	0.358	0.603	0.528	0.599	0.495	0.583	0.586
w2v960	33.84	0.361	0.603	0.528	0.596	0.482	0.581	0.587
w2v960 large	30.85	0.365	0.608	0.532	0.602	0.498	0.587	0.593
whisper tiny	27.74	0.377	0.613	0.536	0.605	0.494	0.590	0.598
hubert large	25.12	0.363	0.610	0.543	0.605	0.496	0.585	0.593
w2v960 large self	24.63	0.367	0.607	0.538	0.610	0.492	0.582	0.593
whisper base	19.35	0.375	0.613	0.537	0.611	0.497	0.592	0.599
whisper small	15.60	0.378	0.616	0.544	0.612	0.501	0.594	0.600
whisper medium	15.14	0.377	0.616	0.548	0.612	0.496	0.593	0.601
whisper large	15.02	0.378	0.616	0.549	0.613	0.499	0.594	0.601
ground truth	0.00	0.382	0.613	0.545	0.611	0.498	0.595	0.598
maximum diff		0.024	0.010	0.017	0.017	0.016	0.016	0.014

Fig. 2. Benchmarking SER performance (Acc4) with fusion techniques based on ASR transcripts. Maximum diff: the maximum difference between the Acc4 of ground truth and that of ASR transcripts. **Red bold:** a higher accuracy than the ground truth.

MOSI, suggesting that valence shares similarities with categorical emotion in terms of robustness to ASR errors. Given that valence is similarly defined to sentiment (indicating positive or negative), this alignment is anticipated. Secondly, arousal and dominance do not display a clear correlation with WERs. Since we jointly predict valence, arousal, and dominance, there is a possibility of shared mutual information among the three dimensions, resulting in minimal changes in arousal and dominance. However, our observations align with the common understanding that valence relies more on text, whereas arousal and dominance rely more on audio [25, 26]. Indeed, when we replaced text features with middle-layer audio features from *W2V960-base* in the SER model, we obtained CCC_v, CCC_a, and CCC_d values of 0.531, 0.635, and 0.558, respectively, further validating our observations.

4.3. Benchmarking SER with WER and Fusion

Next, we integrate audio features to investigate the robustness of existing fusion techniques in handling ASR errors in real-world scenarios. As audio is not the primary focus of

this study, we simply use the middle-layer audio feature from *W2V960-base*. For fusion techniques, we employ the following approaches:

- *Early fusion:* text and audio features are concatenated at the embedding level.
- *Late fusion:* text and audio features are learned independently, and the final decision is determined based on the respective outputs.
- *Cross-attention fusion:* text and audio features are attended to each other via attention mechanism and then concatenated.
- *Tensor fusion* [27]: unimodal information and bimodal interactions are learned explicitly and then aggregated.
- *Non-local gate-based (NL-gate) Fusion* [28]: NL-gate is incorporated with multiple directions and at multiple positions with query-key-value within the attention mechanism.
- *Modality-invariant and -specific fusion (MISA)* [29]: combining both modality-invariant and modality-specific features.

For fairness, we keep the backbone SER model used in the previous section unchanged, only modifying the input dimension of the first dense layer to match the output dimension of the hidden states from each fusion model. Addition-

ally, we modify *Tensor fusion* and *MISA* to receive bimodal inputs, as they were originally designed for trimodal inputs. Due to limited space, we only present results on IEMOCAP and MSP-Podcast for brevity, as these two are sufficient to cover both categorical and dimensional emotions. Regarding the patterns observed on CMU-MOSI (omitted here), integrating audio did not significantly improve performance, as text alone already yields powerful results. Additionally, the audio in CMU-MOSI does not strongly convey emotion, leading to incongruity and ambiguity, which may pose challenges for SER in certain cases. From Fig. 2, it can be seen that:

1) Fusing audio features can mitigate the negative impact of an increase in WER. The decrease of Acc4 based on WER reaches 10% without fusion on IEMOCAP, but only 4% with fusion. Moreover, with most fusion techniques, the SER performance is even better on transcripts with relatively low WER than on ground truth. These findings confirm the benefits of bimodal SER in real applications, which can be achieved through using a pre-trained ASR model as a base for jointly generating transcripts and audio features [15, 30].

2) There is no optimal WER-robust fusion approach. Due to different amount of input information, the performance of some fusion techniques is not directly comparable. For instance, approaches like *Tensor fusion* and *MISA* encode more information due to their incorporation of both unimodal and bimodal features or both modality-invariant and -specific features. However, their effectiveness varies across different corpora. For example, they perform well on IEMOCAP (categorical) but suffer on MSP-Podcast (dimensional), indicating significant inconsistency. Thus, it is hard to identify a single best-performing technique that is universally effective in addressing ASR errors. Nevertheless, the maximum difference between the performance of ground truth and that of ASR transcripts is somewhat indicative of the robustness of certain fusion techniques. We observe that although *cross-attention fusion* may not produce the best performance, it yields a relatively small maximum difference, suggesting that it is less affected by WER. This observation is reasonable since cross-attention captures the relatedness between bimodal inputs, which changes dynamically once the words have changed, ensuring that the relatedness is least affected by ASR errors.

Since our experimental design has an impact on the results to some extent (e.g., removing punctuation, converting letters to lowercase, excluding samples without corresponding text transcription, modified fusion models), it could inevitably lead to variations and exceptions in some SER performances. However, we believe our overall findings and conclusions remain valid, especially some of them are consistent with existing findings [15, 17, 18].

5. ASR ERROR-ROBUST FRAMEWORK

To address both the WER and fusion issues, we propose an ASR error-robust framework involving ASR error correction

and modality-gated fusion, as illustrated in Fig. 3 (left side).

5.1. ASR Error Correction

We combine the transcripts from all used ASR models, forming N-best (N=11) hypotheses. Compared to using raw N-best hypotheses directly from a single ASR model, which have limited diversity, such a combination offers a more varied range of transcription results. Furthermore, this approach facilitates the comparison of SER performance with each ASR model, as depicted in Fig. 2.

Then, the ASR error correction consists of a two-stage process. First, we utilize the Alpaca prompt [31], which guides a Large Language Model (LLM) to generate the most likely transcript (i.e., 1-best hypothesis) from the N-best hypotheses and correct any grammatical or logical errors. An illustration of the Alpaca prompt is depicted on the right of Fig. 3. We employ InstructGPT, which has demonstrated effectiveness in LLM-based ASR error correction [32].

In the second stage, we further refine the 1-best transcripts by utilizing a Sequence-to-Sequence (S2S) ASR error correction model [33], which was pre-trained on the *Whisper-tiny* output y' (i.e., 1-best hypothesis) of Common Voice [34] to recover the corrected sequence y (i.e., gold annotation), with an optimizable parameter θ :

$$y = \operatorname{argmax}_y P(y|y', \theta) \quad (1)$$

5.2. Modality-Gated Fusion

Based on the quality-enhanced transcripts, we adapt a trimodal incongruity-aware fusion method [7] to our bimodal source, considering potential distortion of original emotion in the spoken content due to ASR errors, which may introduce incongruence between emotions in audio and text.

Specifically, each modality is initially assigned an equal trainable weight based on its contribution to the final task. These weights are dynamically adjusted during training, with larger contributions resulting in higher values. The sum of the weights always equals 1, and they are updated in every training batch to ensure dynamic adaptation to any input batch size. Subsequently, the weights are multiplied with corresponding modality features to perform a weighted attention fusion. The pseudo-code is shown in Algorithm 1, where H represents the hidden representation as input to the backbone SER model. *CrossAttn* and *SelfAttn* denote multihead attention, the former with the first argument as query and the second as key and value, and the latter with the argument as query, key, and value. The head number is set to eight.

Finally, we apply the same backbone SER model, keeping all other settings unchanged (e.g., the language and audio encoders) as in Section 4. We believe that this combination of dynamic modality gate and weighted attention can effectively mitigate the negative effects of ASR errors by consistently focusing on the most salient parts for SER.




Fig. 3. Proposed ASR error-robust framework. **Blue**: ASR error correction; frozen. **Pink**: Modality-gated fusion; trainable.

Algorithm 1: Modality-gated fusion.

Input: Audio modality A ; Text modality T ; Dynamic modality gating weight W initialized with `nn.Param(torch.tensor([1, 1]))`

```

1 repeat
2 for model input do
3   Sample  $A, T$ ;
4    $W' \leftarrow \text{softmax}(W)$ ;
5    $W_A \leftarrow W'[0]$ ;
6    $W_T \leftarrow W'[1]$ ;
7   if  $\text{argmax}(W') == 0$  then
8      $A' = W_A * A$ ;
9      $T' = W_T * \text{CrossAttn}(A, T)$ ;
10  else
11     $A' = W_A * \text{CrossAttn}(T, A)$ ;
12     $T' = W_T * T$ ;
13  end if
14   $H = \text{SelfAttn}(\text{Concat}[A'; T'])$ ;
15 end for
16 until no model input

```

5.3. Results and Discussion

The results are presented in Table 1. We only include MAE on CMU-MOSI and the average CCC on MSP-Podcast for brevity. Our approach further reduces the WER and improves SER performance, demonstrating its effectiveness. Although it does not surpass the best transcript in terms of MAE on CMU-MOSI, the values are very close. Moreover, consistent with the findings in [17], our results confirm that with proper ASR error-robust approaches, it is possible to exceed the SER performance of ground-truth text using ASR transcripts. Once again, this phenomenon likely occurs because

certain misrecognized words are interpreted as contributing positively to the ground-truth emotions, rather than ASR errors being preferable in SER.

Table 1. Performance comparison. \uparrow : higher the better. \downarrow : lower the better.

	IEMOCAP		CMU-MOSI		MSP-Podcast	
	WER \downarrow	Acc4 \uparrow	WER \downarrow	MAE \downarrow	WER \downarrow	CCC \uparrow
best trans	12.31	74.46	18.69	0.8558	15.02	0.616
ground truth	0.00	74.19	0.00	0.8902	0.00	0.613
ours	10.12	76.66	17.00	0.8563	12.85	0.618

6. CONCLUSION

In this study, we conducted a benchmark of SER performance using ASR transcripts with varying WERs and explore mainstream fusion techniques to assess the impact of ASR performance on SER. Our findings revealed several novel insights: 1) SER can tolerate relatively low WER, especially in real-life speech scenarios; 2) bimodal SER with transcripts containing approximately 10% errors may not underperform those with ground-truth text, particularly with powerful *Whisper* models. However, further analysis is needed to understand what and where the ASR errors actually are, as well as the mechanisms underlying fusion techniques. Moreover, we proposed an ASR error-robust framework that integrates ASR error correction and modality-gated fusion. This framework demonstrated superior performance compared to baseline models in our experimental results and has the potential to find applications in various tasks where ASR transcription serves as the text source. In the near future, we plan to launch a challenge aimed at addressing ASR errors for robust multimodal SER.

7. REFERENCES

- [1] Sreyan Ghosh, Utkarsh Tyagi, S Ramaneswaran, Harshvardhan Srivastava, and Dinesh Manocha, “Mmer: Multimodal multi-task learning for speech emotion recognition,” *arXiv preprint arXiv:2203.16794*, 2022.
- [2] Jilt Sebastian, Piero Pierucci, et al., “Fusion Techniques for Utterance-Level Emotion Recognition Combining Speech and Transcripts,” in *Proceedings of Interspeech 2019*, 2019, pp. 51–55.
- [3] Seunghyun Yoon, Seokhyun Byun, and Kyomin Jung, “Multimodal speech emotion recognition using audio and text,” in *2018 IEEE Spoken Language Technology Workshop (SLT)*. IEEE, 2018, pp. 112–118.
- [4] Darshana Priyasad, Tharindu Fernando, Sridha Sridharan, Simon Denman, and Clinton Fookes, “Dual memory fusion for multimodal speech emotion recognition,” in *Proc. INTERSPEECH*, 2023, vol. 2023, pp. 4543–4547.
- [5] Yuanchao Li, Zeyu Zhao, Ondřej Klejch, Peter Bell, and Catherine Lai, “ASR and Emotional Speech: A Word-Level Investigation of the Mutual Impact of Speech and Emotion Recognition,” in *Proc. INTERSPEECH 2023*, 2023, pp. 1449–1453.
- [6] A Batliner, S Steidl, and E Nöth, “Releasing a thoroughly annotated and processed spontaneous emotional database: the fau aibo emotion corpus,” in *Programme of the Workshop on Corpora for Research on Emotion and Affect*, 2008, p. 28.
- [7] Yaoting Wang, Yuanchao Li, Paul Pu Liang, Louis-Philippe Morency, Peter Bell, and Catherine Lai, “Cross-attention is not enough: Incongruity-aware dynamic hierarchical fusion for multimodal affect recognition,” 2023.
- [8] Yuan Gao, JiaXing Liu, Longbiao Wang, and Jianwu Dang, “Domain-adversarial autoencoder with attention based feature level fusion for speech emotion recognition,” in *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2021, pp. 6314–6318.
- [9] Yiqun Yao and Rada Mihalcea, “Modality-specific learning rates for effective multimodal additive late-fusion,” in *Findings of the Association for Computational Linguistics: ACL 2022*, 2022, pp. 1824–1834.
- [10] Saurabh Sahu, Vikramjit Mitra, Nadee Seneviratne, and Carol Espy-Wilson, “Multi-Modal Learning for Speech Emotion Recognition: An Analysis and Comparison of ASR Outputs with Ground Truth Transcription,” in *Proceedings of Interspeech 2019*, 2019, pp. 3302–3306.
- [11] Hang Li, Wenbiao Ding, Zhongqin Wu, and Zitao Liu, “Learning fine-grained cross modality excitement for speech emotion recognition,” *INTERSPEECH 2020*, 2020.
- [12] Jennifer Santoso, Takeshi Yamada, Shoji Makino, Kenkichi Ishizuka, and Takekatsu Hiramura, “Speech emotion recognition based on attention weight correction using word-level confidence measure.,” in *Interspeech*, 2021, pp. 1947–1951.
- [13] Wen Wu, Chao Zhang, and Philip C Woodland, “Emotion recognition by fusing time synchronous and time asynchronous representations,” in *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2021, pp. 6269–6273.
- [14] Suwon Shon, Pablo Brusco, Jing Pan, Kyu J Han, and Shinji Watanabe, “Leveraging pre-trained language model for speech sentiment analysis,” in *22nd Annual Conference of the International Speech Communication Association, INTERSPEECH 2021*. International Speech Communication Association, 2021, pp. 566–570.
- [15] Yuanchao Li, Peter Bell, and Catherine Lai, “Fusing ASR outputs in joint training for speech emotion recognition,” in *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2022, pp. 7362–7366.
- [16] Binghuai Lin and Liyuan Wang, “Robust multi-modal speech emotion recognition with asr error adaptation,” in *ICASSP 2023-2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2023, pp. 1–5.
- [17] Jiajun He, Xiaohan Shi, Xingfeng Li, and Tomoki Toda, “MF-AED-AEC: Speech emotion recognition by leveraging multimodal fusion, asr error detection, and asr error correction,” *arXiv preprint arXiv:2401.13260*, 2024.
- [18] Tiantian Feng and Shrikanth Narayanan, “Foundation model assisted automatic speech emotion recognition: Transcribing, annotating, and augmenting,” in *ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2024, pp. 12116–12120.
- [19] Carlos Busso, Murtaza Bulut, Chi-Chun Lee, Abe Kazemzadeh, Emily Mower, Samuel Kim, Jeannette N Chang, Sungbok Lee, and Shrikanth S Narayanan, “IEMOCAP: Interactive emotional dyadic motion capture database,” *Language Resources and Evaluation*, vol. 42, no. 4, pp. 335–359, 2008.

- [20] Amir Zadeh, Rowan Zellers, Eli Pincus, and Louis-Philippe Morency, “Multimodal sentiment intensity analysis in videos: Facial gestures and verbal messages,” *IEEE Intelligent Systems*, vol. 31, no. 6, pp. 82–88, 2016.
- [21] Reza Lotfian and Carlos Busso, “Building naturalistic emotionally balanced speech corpus by retrieving emotional speech from existing podcast recordings,” *IEEE Transactions on Affective Computing*, vol. 10, no. 4, pp. 471–483, 2017.
- [22] Soujanya Poria, Devamanyu Hazarika, Navonil Majumder, Gautam Naik, Erik Cambria, and Rada Mihalcea, “Meld: A multimodal multi-party dataset for emotion recognition in conversations,” in *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, 2019, pp. 527–536.
- [23] Ryoko Tokuhisa, Kentaro Inui, and Yuji Matsumoto, “Emotion classification using massive examples extracted from the web,” in *Proceedings of the 22nd International Conference on Computational Linguistics (Coling 2008)*, 2008, pp. 881–888.
- [24] Changye Li, Weizhe Xu, Trevor Cohen, and Serguei Pakhomov, “Useful blunders: Can automated speech recognition errors improve downstream dementia classification?,” *Journal of Biomedical Informatics*, vol. 150, pp. 104598, 2024.
- [25] Björn Schuller, Bogdan Vlasenko, Florian Eyben, Gerhard Rigoll, and Andreas Wendemuth, “Acoustic emotion recognition: A benchmark comparison of performances,” in *2009 IEEE workshop on automatic speech recognition & understanding*. IEEE, 2009, pp. 552–557.
- [26] Johannes Wagner, Andreas Triantafyllopoulos, Hagen Wierstorf, Maximilian Schmitt, Felix Burkhardt, Florian Eyben, and Björn W Schuller, “Dawn of the transformer era in speech emotion recognition: closing the valence gap,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2023.
- [27] Amir Zadeh, Minghai Chen, Soujanya Poria, Erik Cambria, and Louis-Philippe Morency, “Tensor fusion network for multimodal sentiment analysis,” *arXiv preprint arXiv:1707.07250*, 2017.
- [28] Xiaolong Wang, Ross Girshick, Abhinav Gupta, and Kaiming He, “Non-local neural networks,” in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2018, pp. 7794–7803.
- [29] Devamanyu Hazarika, Roger Zimmermann, and Soujanya Poria, “MISA: Modality-invariant and-specific representations for multimodal sentiment analysis,” in *Proceedings of the 28th ACM international conference on multimedia*, 2020, pp. 1122–1131.
- [30] Xingyu Cai, Jiahong Yuan, Renjie Zheng, Liang Huang, and Kenneth Church, “Speech emotion recognition with multi-task learning,” in *Proceedings of Interspeech 2021*, 2021.
- [31] Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto, “Alpaca: A strong, replicable instruction-following model,” *Stanford Center for Research on Foundation Models*. <https://crfm.stanford.edu/2023/03/13/alpaca.html>, vol. 3, no. 6, pp. 7, 2023.
- [32] Sriji Radhakrishnan, Chao-Han Huck Yang, Sumeer Ahmad Khan, Rohit Kumar, Narsis A Kiani, David Gomez-Cabrero, and Jesper N Tegner, “Whispering llama: A cross-modal generative error correction framework for speech recognition,” *arXiv preprint arXiv:2310.06434*, 2023.
- [33] Yuanchao Li, Pinzhen Chen, Peter Bell, and Catherine Lai, “Crossmodal asr error correction with discrete speech units,” *arXiv preprint arXiv:2405.16677*, 2024.
- [34] Rosana Ardila, Megan Branson, Kelly Davis, Michael Henretty, Michael Kohler, Josh Meyer, Reuben Morais, Lindsay Saunders, Francis M Tyers, and Gregor Weber, “Common voice: A massively-multilingual speech corpus,” *Proceedings of the Twelfth Language Resources and Evaluation Conference (LREC)*, 2020.