Regularizing Hidden States Enables Learning Generalizable Reward Model for LLMs

Rui Yang¹ * **Ruomeng Ding² Yong Lin¹ Huan Zhang³ Tong Zhang³** ¹HKUST, ²Georgia Institute of Technology, ³University of Illinois Urbana-Champaign

Abstract

Reward models trained on human preference data have been proven to be effective for aligning Large Language Models (LLMs) with human intent within the reinforcement learning from human feedback (RLHF) framework. However, the generalization capabilities of current reward models to unseen prompts and responses are limited. This limitation can lead to an unexpected phenomenon known as reward over-optimization, where excessive optimization of rewards results in a decline in actual performance. While previous research has advocated for constraining policy optimization, our study proposes a novel approach to enhance the reward model's generalization ability against distribution shifts by regularizing the hidden states. Specifically, we retain the base model's language model head and incorporate a suite of text-generation losses to preserve the hidden states text generation capabilities, while concurrently learning a reward head behind the same hidden states. Our experimental results demonstrate that the introduced regularization technique markedly improves the accuracy of learned reward models across a variety of out-of-distribution (OOD) tasks and effectively alleviate the over-optimization issue in RLHF, offering a more reliable and robust preference learning paradigm.

1 Introduction

Pretrained large models have showcased impressive capabilities across diverse fields (Devlin et al., 2018; Kaplan et al., 2020; Bommasani et al., 2021; Brown et al., 2020; Caron et al., 2021). A notable trend in recent research is ensuring that large models align with human values and mitigate potentially harmful behaviors (Ziegler et al., 2019; Bai et al., 2022; Ouyang et al., 2022; OpenAI, 2023; Touvron et al., 2023). Alignment methods are crucial in achieving this objective, with two primary approaches being supervised fine-tuning (SFT) and reinforcement learning from human feedback (RLHF) (Bai et al., 2022; Ouyang et al., 2022). SFT directly finetunes the model using prompt and response pairs, proving to be a straightforward and efficient alignment technique (Peng et al., 2023; Zhang et al., 2023; Yang et al., 2024b). Differently, RLHF begins by learning a reward model from user preferences and then employs reinforcement learning to optimize the language model to maximize rewards. A notable advantage of RLHF is its potential to generalize the reward model to unseen prompt-response pairs, effectively leveraging large volumes of unlabeled data (Ouyang et al., 2022).

Despite the empirical success of RLHF, the challenge of training a reliable and generalizable reward model for unseen data remains an open problem. A well-known failure mode of reward model is known as "*overoptimization*" or "*reward hacking*" (Amodei et al., 2016; Stiennon et al., 2020; Gao et al., 2023; Coste et al., 2023), where policy optimization seemingly improves the proxy reward model but actually degrades the true reward function. Gao et al. (2023) demonstrated in a synthetic setup that increasing the size of the reward model and the volume of training data can mitigate this overoptimization issue. However, such scaling is not always feasible in many realistic scenarios. To address this, a series of studies have been conducted, focusing either on enhancing the reward model

^{*}yangrui.thu2015@gmail.com



Figure 1: (1) Illustration of GRM. Given preference data (x, y_c, y_r) , the reward head minimizes the reward loss in Eq 1, while the language model (LM) head minimizes a suite of text-generation losses introduced in Sec 3.2. (2) Performance of GRM and the vanilla reward model on in-distribution (ID) task (UnifiedFeedback) and average results of OOD tasks (HHH-Alignment and MT-Bench). GRM generalizes better on OOD tasks, with a larger advantage when the dataset size is relatively small.

with ensemble techniques (Coste et al., 2023; Eisenstein et al., 2023; Lin et al., 2023a; Kim et al., 2024), or on constrained policy optimization (Moskovitz et al., 2023; Zhang et al., 2024b; Liu et al., 2024; Cen et al., 2024). Among these, improving the generalization ability of reward models presents a fundamental and promising direction that can be studied independently from enhancements in policy optimization. Nevertheless, previous methods (Coste et al., 2023; Ramé et al., 2024) requiring training multiple reward models may be resource-intensive for practical application of large models.

In this study, we present a lightweight yet effective solution designed to enhance the reward model's generalization ability against distribution shifts. Previous research (Kumar et al., 2022) has theoretically shown that a randomly initialized head can distort pre-trained features, thereby negatively impacting out-of-distribution (OOD) performance. Inspired by this finding, we propose to regularize the feature during fine-tuning for preference learning using an adversarial regularizer, which derives a suite of text-generation losses. To this end, we introduce **Generalizable Reward Model (GRM)**, which retains the base model's language model head and regularizes the hidden states of the reward model by incorporating text-generation losses. This approach makes better use of the preference learning data while preserving the text generation capabilities of the hidden states. Notably, GRM does not necessitate training multiple reward models or relying on additional training data.

In our experiments, GRM significantly enhances the evaluation accuracy of the reward model on OOD evaluation datasets. This demonstrates its superior ability to generalize learned preferences to unseen prompt and response pairs. Moreover, GRM consistently improves the performance of both 2B and 7B reward models, and a larger margin of improvement is observed when the data size is relatively limited. We also demonstrate that GRM can markedly enhance the performance of best-of-n (BoN) sampling and PPO (Schulman et al., 2017), effectively mitigating the overoptimization problem. These results highlight the potential of the GRM to serve as a more reliable proxy reward model for human preferences. In summary, our primary contributions are as follows:

- We propose GRM, a novel approach that employs text-generation regularization on the hidden states to enhance the generalization ability of reward models.
- Our study validates the effectiveness of all three types of text-generation regularization for GRM, identifying the SFT regularization as the most effective and stable solution.
- Our empirical results show that GRM significantly improves the accuracy of reward models across various OOD tasks. Furthermore, it consistently enhances the performance of RLHF, effectively alleviating the overoptimization problem.

2 Background

2.1 Reward Modeling

Generally, reward modeling is defined as a Bradley-Terry model (Bradley and Terry, 1952), which finetunes an SFT model to distinguish between two responses given the same prompt:

$$\mathcal{L}_{\text{reward}}(\theta) = -\mathbb{E}_{(x,y_c,y_r)\sim D}\left[\log\left(\sigma\left(r_{\theta}(x,y_c) - r_{\theta}(x,y_r)\right)\right)\right],\tag{1}$$

where $r_{\theta}(x, y)$ represents the reward score for prompt x and output y with model parameters θ . $\sigma(\cdot)$ is the sigmoid function. By minimizing this loss function, the reward model assigns higher scores

to outputs preferred by humans. Subsequently, the trained reward model can be used to guide the optimization of the policy model during the RLHF process.

2.2 Reinforcement Learning from Human Feedback (RLHF)

In the RLHF stage, various policy optimization methods can be applied, with two frequently used methods being Best-of-n Sampling (BoN) and Proximal Policy Optimization (PPO).

Best-of-n **Sampling (BoN)** generates n samples from the policy model, denoted as Y_{gen} , and then selects the best one based on scores provided by a reward model. BoN can be used for inference-time improvement or iterative optimization (Gulcehre et al., 2023; Dong et al., 2023; Wang et al., 2024b).

$$y_{\text{BON}}(x) = \arg \max_{y \in Y_{\text{gen}}} r_{\theta}(x, y).$$
(2)

Proximal Policy Optimization (PPO) is a widely adopted method for RLHF in optimizing language models (Stiennon et al., 2020; Ouyang et al., 2022; Wang et al., 2024a). PPO learns a policy by maximizing a reward objective with a KL divergence penalty with coefficient η :

$$r_{\text{total}} = r_{\theta}(x, y) - \eta \text{KL}(\pi_{\text{PPO}}(y|x) \parallel \pi_{\text{SFT}}(y|x)), \tag{3}$$

where the KL penalty ensures that the optimized policy does not deviate significantly from the SFT policy to maintain the reliability of the reward model.

Overoptimization. Although the learned proxy reward model aims to approximate human preference, it may not consistently reflect authentic human preferences, potentially resulting in *over-optimization* (Gao et al., 2023; Coste et al., 2023). This issue emerges when the proxy reward model becomes overly optimized, causing the policy model to overfit to certain erroneous patterns. Ultimately, this issue can diminish the model's alignment with actual human preferences, highlighting the need to ensure the reward model's robustness and reliability.

3 Method

In the common practice of training a reward model (Ouyang et al., 2022; Wang et al., 2024a; Dong et al., 2024), reward models are initialized using a pretrained or SFT finetuned backbone, along with a randomly initialized reward head to predict the scores for prompt-response pairs. It's important to note that the backbone and original language model head are trained on a diverse range of datasets for text-generation, which is distinct from the preference learning tasks. Under the task shift, the randomly initialized reward head can distort the pretrained features uncontrollably, thereby reducing the OOD generalization performance, as observed by (Kumar et al., 2022).

To improve the reward model's generalization capability against distribution shifts, we propose a lightweight yet effective solution, Generalizable Reward Model (GRM). This model employs a suite of text-generation regularizations for the hidden states. More specifically, the GRM employs a structure as illustrated in Fig 1, with one language model (LM) head and one reward head sharing the same hidden states. The reward head is trained to minimize the reward loss \mathcal{L}_{reward} in Eq 1, while the LM head is trained to maintain the text-generation ability of the hidden states during preference learning. Consequently, we define the overall loss function as follows:

$$\mathcal{L}_{\text{total}} = (1 - \alpha)\mathcal{L}_{\text{reward}} + \alpha \mathcal{L}_{\text{reg}}.$$
(4)

Here, α is the coefficient that balances the reward loss and the regularization. We will derive potential forms of the regularization term below.

3.1 Theoretical Motivation

To derive the potential formulation of the regularization term, we consider the following adversarial optimization problem: learning a reward model against an adversarial policy.

$$\theta = \arg\min_{\theta} \left\{ \mathcal{L}_{\text{reward}}(\theta) + \gamma \max_{\pi} J(\theta, \pi) \right\},\tag{5}$$

where $\gamma > 0$ is a coefficient. This objective is also considered by recent studies (Liu et al., 2024; Cen et al., 2024) aiming to enhancing DPO. Differently, we adopt it to learn a generalizable reward model.

The insight of Eq 5 is that we can enhance the robustness of the reward model by considering an adversarial policy π from certain policy class. The term for policy optimization $J(\theta, \pi)$ can have various formulations, but a KL divergence-regularized objective is generally used in training the policy (Stiennon et al., 2020; Ouyang et al., 2022). Moreover, it has an advantageous property that the inner optimization problem has an analytical solution, which can simplify the problem.

$$J(\theta, \pi) = \mathbb{E}_{x \sim D, y \sim \pi(\cdot|x)} \left[r_{\theta}(x, y) \right] - \beta \mathbb{E}_{x \sim D} \left[\mathrm{KL} \left(\pi(\cdot|x) \parallel \pi_{\mathrm{ref}}(\cdot|x) \right) \right], \tag{6}$$

where $\beta > 0$ is a regularization coefficient and π_{ref} is the reference model. We denote the analytical solution of $J(\theta, \pi)$ as π_{θ}^* . Incorporating π_{θ}^* into Eq 5, we can transform the min-max optimization problem into a standard optimization problem under certain assumption:

$$\theta = \arg\min_{a} \{ (1 - \alpha) \mathcal{L}_{\text{reward}}(\theta) + \alpha_{\text{DPO}} \mathcal{L}_{\text{DPO}}(\pi_{\theta}^*) + \alpha_{\text{SFT}} \mathcal{L}_{\text{SFT}}(\pi_{\theta}^*) \}$$
(7)

Detailed derivation is deferred to Appendix A. Here, \mathcal{L}_{DPO} is the same as the DPO objective (Rafailov et al., 2023) and \mathcal{L}_{SFT} is the the SFT objective that maximizes the probability of chosen responses. Notably, the two regularization terms originate from different sources: \mathcal{L}_{DPO} stems from the reward loss, while \mathcal{L}_{SFT} is derived from the adversarial term. This may explain why SFT regularization proves more beneficial than DPO regularization in our empirical results. Motivated by Eq 7, we relax the relationship between r_{θ} and π_{θ}^* and propose learning a reward model parameterized by θ and a language model head parameterized by θ_{LM} , both sharing the same hidden states. A discussion of this design can be found in Appendix A. Below, we detail three practical implementations.

3.2 Text-Generation Regularization

Inspired by Eq 7, we train the LM head to minimize text-generation losses, such as DPO and SFT losses, as the regularization term for GRM. To independently study the effectiveness of these two regularizations and reduce GPU memory usage, we introduce three practical implementations of GRM: DPO regularization, DPO without reference regularization, and SFT regularization.

DPO Regularization. By setting $\alpha_{\text{DPO}} = \alpha$ and $\alpha_{\text{SFT}} = 0$ in Eq 7, we can directly adopt the DPO loss as a regularization term for GRM to regularize the hidden states:

$$\mathcal{L}_{\text{DPO}}(\theta_{\text{LM}}) = -\mathbb{E}_{(x,y_c,y_r)\sim D} \left[\log \sigma \left(\beta \log \left(\frac{\pi_{\theta_{\text{LM}}}(y_c \mid x)}{\pi_{\text{ref}}(y_c \mid x)} \right) - \beta \log \left(\frac{\pi_{\theta_{\text{LM}}}(y_r \mid x)}{\pi_{\text{ref}}(y_r \mid x)} \right) \right) \right], \quad (8)$$

where π_{ref} is the SFT policy serving as the reference model, and $\pi_{\theta_{\text{LM}}}$ is our optimized policy. β is a coefficient that controls the KL penalty between $\pi_{\theta_{\text{LM}}}$ and π_{ref} . Notably, $\pi_{\theta_{\text{LM}}}$ shares the same base model with the reward model r_{θ} , except for the output layer.

DPO Regularization w/o Reference Model. While straightforward, the use of a reference model in DPO regularization can be memory-intensive for large models. To address this, and inspired by prior works that eliminate the need for reference model (Hong et al., 2024; Meng et al., 2024), we introduce the DPO regularization without a reference model, denoted as $\mathcal{L}_{\text{DPO-noref}}$. This method reduces the need for large GPU memory during training. The loss function $\mathcal{L}_{\text{DPO-noref}}$ is defined as:

$$\mathcal{L}_{\text{DPO-noref}}(\theta_{\text{LM}}) = -\mathbb{E}_{(x,y_c,y_r)\sim D} \left[\log \sigma \left(\beta \log \left(\frac{\pi_{\theta_{\text{LM}}}(y_c \mid x)}{\pi_{\theta_{\text{LM}}}(y_r \mid x)} \right) \right) \right].$$
(9)

SFT Regularization. By setting $\alpha_{\text{DPO}} = 0$ and $\alpha_{\text{SFT}} = \alpha$ in Eq 7, we can simplify the regularization term to SFT regularization, thereby reducing computational cost. This method only maximizes the probability of the chosen responses:

$$\mathcal{L}_{\text{SFT}}(\theta_{\text{LM}}) = -\mathbb{E}_{(x,y_c)\sim D} \left[\log\sigma\left(\beta\log\left(\pi_{\theta_{\text{LM}}}(y_c \mid x)\right)\right)\right].$$
(10)

This equation differs slightly from the standard SFT objective to maintain coherence with the above two cases within the regularization suite.

3.3 Advantages of GRM

In summary, GRM offers three key advantages: (1) **Mitigating feature distortion.** The application of text-generation loss helps maintain the text-generation ability of the base model and prevents excessive feature distortion. Simultaneously, it also adapts the model to the data distribution of

preference learning. (2) **Prevention of Overfitting.** The text-generation regularization derived from an adversarial training objective helps prevent the reward model from overfitting to certain spurious features, which can be detrimental for OOD generalization. This effect becomes more pronounced when the preference data includes erroneous comparison pairs or when the dataset size is limited. (3) **Efficiency.** GRM is an efficient solution that does not require training multiple reward models or additional training data. Additionally, different choices of loss type entail varying memory and computational costs. Interestingly, we find that the simplest option, SFT regularization, proves to be the most stable choice.

4 Experimental Setup

Datasets. For training reward models, we leverage the Unified-Feedback dataset ², which stands as one of the largest collections of pairwise feedback datasets. In Section 5.1, we train all reward models on a subset of 400K and 40K instances from the Unified-Feedback dataset, and evaluate then on the hold-out 8K eval set. In addition, for evaluating model performance on out-of-distribution (OOD) preference data, we utilize datasets such as HHH-Alignment (Askell et al., 2021), MT-Bench Human Judgements (Zheng et al., 2024), and RewardBench (Lambert et al., 2024). The HHH-Alignment dataset evaluates language models on helpfulness, honesty and harmlessness, while the MT-Bench dataset contains human preferences for model responses to MT-bench questions. Besides, RewardBench is a new benchmark designed to evaluate the capabilities and safety of reward models. We consider HHH-Alignment, MT-Bench, and RewardBench as OOD evaluation task because the prompt and response distributions differ from our training distribution. For the RLHF experiments in Section 5.2 we downsample 20K data from Unified-Feedback for training reward models and optimizing the PPO policy, and another 1K data for evaluating BoN or the learned PPO policy.

Base Models. In the preference learning experiments, our base models include gemma-2B-it (Team et al., 2024) and Mistral-7B-Instruct-v0.2 (Jiang et al., 2023a). For the RLHF experiments, gemma-2B-it serves as the policy model for both BoN and PPO experiments, whereas the gold reward model is a 7B human preference model finetuned using the entire Unified-Feedback dataset.

Baselines. We compare the performance of GRM with several baselines, including: *Baseline Classifier* trained using the original reward loss in Eq 1; *Frozen Classifier* that fixes the base model's feature and only finetunes a nonlinear classification head; *Margin* that adds an additional margin in the original reward loss (Touvron et al., 2023; Wang et al., 2024a); *Label Smooth* that mitigate the overfitting problem by penalizing overconfident model outputs (Wang et al., 2024a); *Ensemble* method with a number of reward models n = 3 (Coste et al., 2023) to calculate the average or minimum values as rewards. In addition, for RewardBench, we present the performance of several existing open-source state-of-the-art reward models for better reference, including PairRM (Jiang et al., 2023b), Starling-RM-7B/34B (Zhu et al., 2023), and UltraRM-13B (Cui et al., 2023). For more experimental details and additional results, please refer to Appendix B and Appendix C, respectively.

5 Evaluation Results

We present a comprehensive evaluation of GRM, utilizing both in-distribution (ID) and out-ofdistribution (OOD) dataset, as well as existing benchmarks for reward models. Furthermore, we explore the impact of GRM on the overoptimization issue in RLHF. Our primary findings can be summarized as follows:

- GRM significantly enhances the generalization capability of reward models, resulting in substantial improvements on both ID and various OOD evaluation sets (Section 5.1).
- All three types of text-generation regularization losses can improve the generalization performance, with the SFT regularization being the most effective and stable (Section 5.1).
- GRM demonstrates robustness in the limited dataset settings, outperforming baselines by an even larger margin (Section 5.1).
- GRM effectively mitigates the overoptimization issue in both BoN and PPO (Section 5.2).
- GRM also exhibits robustness against label noise in the preference dataset (Section 5.2).

²https://huggingface.co/datasets/llm-blender/Unified-Feedback

Table 1: Results on ID and OOD evaluation with **400K training data** from UnifiedFeedback. The best performance in each task is in bold and the second best one is underlined.

Table 2: Results on ID and OOD evaluation with **40K training data** from UnifiedFeedback. The best performance in each task is in bold and the second best one is underlined.

Reward Model	Unified Feedback	HHH Alignment	MT Bench	Reward Model	Unified Feedback	HHH Alignment	MT Bench
Classifier (Frozen)	63.8	66.4	69.5	Classifier (Frozen)	63.9	68.6	68.2
Classifier (baseline)	72.1	73.4	71.2	Classifier (baseline)	68.8	70.3	69.1
Classifier + margin	72.0	75.0	72.6	Classifier + margin	69.6	69.8	71.0
Classifier + label smooth	71.5	72.1	71.2	Classifier + label smooth	68.5	68.8	71.9
Classifier + Ensemble	72.8	76.8	73.7	Classifier + Ensemble	69.9	72.2	71.1
GRM w/ dpo (ours)	73.8	79.2	73.4	GRM w/ dpo (ours)	70.2	71.6	71.3
GRM w/ dpo-noref (ours)	73.9	79.7	73.0	GRM w/ dpo-noref (ours)	71.4	76.6	72.1
GRM w/ sft (ours)	73.2	79.8	<u>73.4</u>	GRM w/ sft (ours)	71.5	78.7	73.0

5.1 Evaluation on Reward Modeling

ID and OOD Evaluation. The results, as depicted in Table 1 and Table 2, demonstrate the evaluation performance of various reward modeling methods on both ID (Unified-Feedback) OOD (HHH-Alignment and MT-Bench) datasets. Regardless of the size of the training data (400K or 40K), our proposed method, GRM, with three types of regularizations, consistently outperforms the baseline models on both the ID evaluation set and the two OOD datasets. For instance, GRM w/ sft with 400K training data enhances the baseline from 72.1 to 73.2 in ID score, and improves the HHH-Alignment score from 73.4 to 79.8 and the MT-Bench score from 71.2 to 73.4. Notably, the improvement in OOD performance is significantly larger than that in ID. These results suggest that the GRM methods are highly effective in evaluating unseen preference data, demonstrating substantially robust generalization capabilities.

Regarding other baseline models, the Frozen classifier, which maintains its base model's parameters, exhibits the lowest ID and OOD scores. This indicates that the pretrained features of the base model are not sufficiently effective for preference learning, emphasizing the importance of fine-tuning the base model's features to the preference task. In addition, the margin loss and label smoothing do not consistently enhance the ID and OOD tasks, while the ensemble baseline consistently improves both ID and OOD scores. Ensemble-based methods, which require training multiple reward models, still do not compare favorably to GRM, especially when learning from a 40K training set. The results highlight the strong enhancement of GRM in preference learning and its generalization ability.

Comparison of Different Regularizations. As observed in Table 1, when the training dataset is sufficiently large, GRM with three types of regularizations (namely GRM w/ dpo, GRM w/ dpo-noref, and GRM w/ sft) perform comparably. This demonstrates that GRM is robust to the choice of regularization type when the dataset is large. However, in Table 2, where the training data is limited to 40K, a clear trend emerges: GRM w/ sft outperforms GRM w/ dpo-noref, which in turn outperforms GRM w/ dpo, on both the ID and OOD scores. Interestingly, the simplest form of regularization, SFT regularization, not only requires the lowest training cost but also yields the most stable overall results. Consequently, we adopt it as the default choice for our subsequent study.

Results on RewardBench. In Table 3 and Table 4, we evaluate GRM and various baselines on RewardBench across chat, chat-hard, safety, and reasoning task groups. We consider a variant of GRM with a linear reward head instead of the default nonlinear reward head as detailed in Appendix B. In Table 3, the 7B baseline matches the score of Starling-RM-7B (Zhu et al., 2023), while GRM (linear) w/ sft demonstrates a considerable improvement, increasing the average score from 76.3 to 79.5. Comparing variants of GRM, we can conclude that: (1) SFT regularization performs better than the DPO w/o reference model regularization, and (2) GRM with a linear head achieves a better overall score than that with a nonlinear head, especially in the challenging reasoning task group.

Regarding the baselines, consistent with previous results, the margin loss and label smoothing do not provide a coherent improvement over the baseline. While ensemble methods effectively improve upon the baseline, they still underperform GRM. Overall, these results demonstrate that GRM is a strong contender in reward modeling tasks, exhibiting superior performance across various benchmarks.

			0		
Reward Model	Chat	Chat-Hard	Safety	Reasoning	Avg.
PairRM	90.2	53.0	31.5	60.0	58.7
Starling-RM-7B	98.0	43.4	88.6	74.6	76.2
Starling-RM-34B	96.9	59.0	89.9	90.3	84.0
UltraRM-13B	96.1	55.3	45.8	82.0	69.8
Base	Model:	Gemma 2b it			
Classifier (baseline)	95.5	38.0	73.8	65.3	68.2
Classifier + margin	95.8	38.4	73.9	<u>72.5</u>	70.2
Classifier + label smooth	94.4	37.3	73.2	77.4	70.6
Classifier + Ensemble	98.0	37.5	77.3	71.3	71.0
GRM (linear) w/ dpo noref (ours)	96.7	39.0	76.4	68.5	70.2
GRM (linear) w/ sft (ours)	96.1	40.1	80.3	69.3	71.5
GRM w/ dpo noref (ours)	95.8	<u>40.1</u>	<u>78.7</u>	66.2	70.2
GRM w/ sft (ours)	<u>97.8</u>	42.1	77.9	65.2	70.8
Base Mo	odel: Mi	stral 7b Instru	ıct		
Classifier (baseline)	96.6	52.4	86.7	69.5	76.3
Classifier + margin	96.4	51.5	85.3	64.8	74.5
Classifier + label smooth	97.2	49.8	85.8	72.3	76.3
Classifier + Ensemble	96.6	51.8	85.1	73.0	76.6
GRM (linear) w/ dpo noref (ours)	98.0	53.3	86.4	<u>75.3</u>	<u>78.3</u>
GRM (linear) w/ sft (ours)	<u>97.8</u>	<u>54.6</u>	<u>86.3</u>	79.2	79.5
GRM w/ dpo noref (ours)	<u>97.8</u>	54.0	85.7	74.4	78.0
GRM w/ sft (ours)	98.0	55.3	85.8	71.2	77.6

Table 3: Results on RewardBench with **400K training data** from UnifiedFeedback.

Table 4: Results on RewardBench with **40K training data** from UnifiedFeedback.

Reward Model	Chat	Chat-Hard	Safety	Reasoning	Avg.
Base Model: Gemma 2B it					
Classifier (baseline)	95.8	37.3	59.9	64.8	64.5
Classifier + margin	97.2	37.5	56.8	72.7	66.1
Classifier + label smooth	91.6	39.0	53.8	60.2	61.1
Classifier + Ensemble	96.1	38.2	58.8	<u>67.6</u>	65.2
GRM (linear) w/ dpo noref (ours)	94.7	38.4	62.5	51.2	61.7
GRM (linear) w/ sft (ours)	94.7	<u>40.8</u>	65.4	77.0	69.5
GRM w/ dpo noref (ours)	92.5	39.9	72.5	61.4	66.6
GRM w/ sft (ours)	94.1	41.9	<u>69.5</u>	61.5	<u>66.8</u>
Base Mc	del: Mi	stral 7B Instru	ıct		
Classifier (baseline)	89.7	50.7	74.7	57.9	68.2
Classifier + margin	89.7	47.1	70.7	43.6	62.8
Classifier + label smooth	94.1	47.1	67.5	79.7	72.1
Classifier + Ensemble	89.6	50.2	72.7	59.0	69.3
GRM (linear) w/ dpo noref (ours)	96.9	52.9	<u>82.7</u>	78.8	77.8
GRM (linear) w/ sft (ours)	96.7	52.4	81.5	82.5	78.3
GRM w/ dpo noref (ours)	97.8	54.6	82.0	<u>79.9</u>	78.6
GRM w/ sft (ours)	<u>97.2</u>	<u>54.2</u>	83.6	78.6	<u>78.4</u>

Comparison of Different Dataset Sizes. Another noteworthy observation is that GRM exhibits greater robustness to the size of the training dataset compared to baselines. For instance, in Table 1 and Table 2, when the training data size decreases from 400K to 40K, the baseline's HHH Alignment score and MT-Bench score drop from 73.4 and 71.2 to 70.3 and 69.1, respectively. In contrast, GRM with SFT regularization only slightly drops from 79.8 and 73.4 to 78.7 and 73.0, respectively. This trend is consistent in Table 3 and Table 4. Specifically, for the Mistral 7B Instruct base model, the baseline's average score drops from 76.3 to 68.2 when learning from 40K training data, while GRM (linear) w/ sft only drops from 79.5 to 78.3. These findings suggest that the prior reward training paradigms is sensitive to smaller dataset sizes. In contrast, GRM is robust even with a limited dataset.

5.2 Evaluation on RLHF

Best-of-n **Sampling (BoN)** Fig 2 presents the results of BoN sampling for base models of sizes 2B and 7B. For all BoN experiments, we utilize the same 20K subset from the Unified-Feedback dataset, labeled by the gold reward model, to train proxy reward models. Following the (Gao et al., 2023; Coste et al., 2023), we conduct BoN sampling on a 1K held-out test set from n responses for each prompt, based on the scores of the trained proxy model. The selected responses are then scored using



Figure 2: Proxy scores and gold scores of BoN experiments for base models of (a)(b) gemma-2b-it and (c)(d) Mistral-7B-Instruct. Proxy and gold scores are in dashed and solid curves, respectively. Rewards are normalized to start from 0. GRM demonstrates a robust ability to select the best response aligned with the gold rewards as the KL Divergence increases.



Figure 3: Proxy scores and gold scores of PPO experiments for reward model based on (a)(b) gemma-2b-it and (c)(d) Mistral-7B-Instruct. All rewards are normalized to start from 0.

the gold reward model, and their gold scores are averaged over the 1K test prompts. The average gold score reveals the true quality of the responses selected by the proxy reward models. We set the KL Divergence from 0 to 5, corresponding to the number of responses *n* ranging from 1 to 405 for each prompt, according to the equation $KL_{BoN} = \log n - \frac{n-1}{n}$. Ideally, a good proxy reward model should yield larger average proxy and gold scores as the KL increases. However, the average gold scores of some baseline methods plateau or even drop after KL > 4, such as the baseline reward model in Fig 2(d), despite their proxy scores continuing to increase in Fig 2(c). This suggests that these rewards models suffer from the overoptimization issue.

In contrast, GRM consistently demonstrates an increase in both the proxy score and gold score, indicating that it effectively mitigates over-optimization. This advantage is more pronounced in the 7B base model, where GRM achieves an average gold score of 1.5, while the baseline reward model only reaches a score of 0.5. Regarding other baselines, we find that the margin loss and ensemble methods (especially the 'min' strategy) contribute to the robustness of the reward model. However, they still do not compare favorably with GRM. These results underscore the strong potential of GRM to serve as a reliable and robust proxy reward model for the RLHF stage.

Proximal Policy Optimization (PPO) To investigate whether GRM can effectively mitigate the overoptimization issue in PPO, we further employ those 2B and 7B reward models obtained from the BoN experiments to fine-tune policy model (gemma-2b-it) using PPO. The training and evaluation datasets are identical to the BoN experiments. We train PPO for one epoch on the training set, comprising 20K training samples. As depicted in Fig 3, PPO exhibits a stronger tendency to hack the learned reward models compared to BoN. The gold scores of baseline methods continue to decline, while their proxy scores increase, indicating a clear overoptimization issue. In contrast, GRM demonstrates superior robustness in terms of the gold score, which rises with the increase in proxy scores. This validates that GRM can effectively alleviate overoptimization for PPO. Please refer to Appendix D for a clear comparison of the results generated by PPO.

Robustness to Label Noise Human preference data typically contains around 20 to 30% noise, as highlighted in previous studies (Wang et al., 2024a). Such inconsistent preference data can render the reward model less generalizable (Ramé et al., 2024; Liang et al., 2024) and hinder policy learning (Yang et al., 2024c; Ye et al., 2024; Mandal et al., 2024), leading to a performance decline. To



Figure 4: Proxy scores and gold scores of (a)(b) BoN experiments and (c)(d) PPO experiments with 25% label noise. All the rewards are normalized to start from 0.

evaluate the robustness of GRM against label noise, we incorporate a 25% label noise into the 20K training data for all proxy reward models. The results are depicted in Fig 4. Most gold scores expose a more severe over-optimization issue, as compared to the results in Fig 2(b) and Fig 3(b), indicating that those reward models are heavily overfitting under the noisy label setting. On the contrary, GRM exhibits superior robustness under the noisy condition, consistently achieving a peak over 1.0 without a significant decline. This demonstrates that GRM is highly accurate and robust at measuring the sample quality, even in the presence of noise within the training data.

6 Related Works

Reward Modeling. Reward models, trained on human preference data, are crucial in guiding the RLHF process (Ouyang et al., 2022) or prompt optimization (Sun et al., 2023). Recent studies have concentrated on developing advanced reward models to improve the performance of LLMs in RLHF. One approach involves enhancing reward modeling by improving the quality or quantity of preference data (Dubois et al., 2024; Sun and van der Schaar, 2024; Lee et al., 2023). Other strategies focus on learning token-wise dense rewards (Chan et al., 2024; Zhong et al., 2024) or multi-objective rewards Wang et al. (2024b). Additionally, a series of works aim to enhance the robustness of reward models against preference inconsistencies. Techniques such as adaptive margin (Touvron et al., 2023), contrastive learning (Wang et al., 2024a), and meta-learning (Dou et al., 2024) are employed to improve the model's ability to differentiate between chosen and rejected responses.

Mitigating Overoptimization in RLHF. Reward models tend to overfit and struggle to generalize beyond the training distribution, which often leads to the overoptimization issue (Gao et al., 2023). One approach to mitigate this is to penalize overly confident model outputs using label smoothing (Wang et al., 2024a) or SFT regularization (Liu et al., 2024; Cen et al., 2024). Alternatively, the model and data can be iteratively updated, replacing hard labels with soft labels (Zhu et al., 2024). Ensemble techniques, which train several reward models, can also help reduce reward hacking and manage shifts in distribution (Coste et al., 2023; Eisenstein et al., 2023; Lin et al., 2023a,b; Ramé et al., 2024; Zhang et al., 2024a). Adversarial Preference Optimization employs adversarial learning between reward models and an LLM agent to address the gap in generation distribution (Cheng et al., 2023). Recent studies have also utilized uncertainty to mitigate reward over-optimization, including the integration of an uncertainty penalty into rewards (Yang et al., 2024a), or the construction of a confidence interval for gold rewards based on uncertainty estimations (Zhang et al., 2024b).

7 Conclusion

In this study, we introduce an efficient approach aimed at enhancing the generalizability and robustness of reward learning for large language models. By incorporating regularization techniques on the hidden states of reward models, our method demonstrates substantial improvements in the generalization performance of reward models for unseen data. Moreover, our approach effectively mitigates the issue of overoptimization in RLHF. We believe that our findings hold promise in inspiring future research efforts towards the development of more robust reward models that can facilitate the alignment of large models through cost-effective solutions.

References

- Amodei, D., Olah, C., Steinhardt, J., Christiano, P., Schulman, J., and Mané, D. (2016). Concrete problems in ai safety. arXiv preprint arXiv:1606.06565.
- Askell, A., Bai, Y., Chen, A., Drain, D., Ganguli, D., Henighan, T., Jones, A., Joseph, N., Mann, B., DasSarma, N., Elhage, N., Hatfield-Dodds, Z., Hernandez, D., Kernion, J., Ndousse, K., Olsson, C., Amodei, D., Brown, T. B., Clark, J., McCandlish, S., Olah, C., and Kaplan, J. (2021). A general language assistant as a laboratory for alignment. *CoRR*, abs/2112.00861.
- Bai, Y., Jones, A., Ndousse, K., Askell, A., Chen, A., DasSarma, N., Drain, D., Fort, S., Ganguli, D., Henighan, T., et al. (2022). Training a helpful and harmless assistant with reinforcement learning from human feedback. arXiv preprint arXiv:2204.05862.
- Bommasani, R., Hudson, D. A., Adeli, E., Altman, R., Arora, S., von Arx, S., Bernstein, M. S., Bohg, J., Bosselut, A., Brunskill, E., et al. (2021). On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*.
- Bradley, R. A. and Terry, M. E. (1952). Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, 39(3/4):324–345.
- Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. (2020). Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.
- Caron, M., Touvron, H., Misra, I., Jégou, H., Mairal, J., Bojanowski, P., and Joulin, A. (2021). Emerging properties in self-supervised vision transformers. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 9650–9660.
- Cen, S., Mei, J., Goshvadi, K., Dai, H., Yang, T., Yang, S., Schuurmans, D., Chi, Y., and Dai, B. (2024). Value-incentivized preference optimization: A unified approach to online and offline rlhf. arXiv preprint arXiv:2405.19320.
- Chan, A. J., Sun, H., Holt, S., and van der Schaar, M. (2024). Dense reward for free in reinforcement learning from human feedback. *arXiv preprint arXiv:2402.00782*.
- Cheng, P., Yang, Y., Li, J., Dai, Y., and Du, N. (2023). Adversarial preference optimization. *arXiv* preprint arXiv:2311.08045.
- Coste, T., Anwar, U., Kirk, R., and Krueger, D. (2023). Reward model ensembles help mitigate overoptimization. *arXiv preprint arXiv:2310.02743*.
- Cui, G., Yuan, L., Ding, N., Yao, G., Zhu, W., Ni, Y., Xie, G., Liu, Z., and Sun, M. (2023). Ultrafeedback: Boosting language models with high-quality feedback. arXiv preprint arXiv:2310.01377.
- Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2018). Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.
- Dong, H., Xiong, W., Goyal, D., Pan, R., Diao, S., Zhang, J., Shum, K., and Zhang, T. (2023). Raft: Reward ranked finetuning for generative foundation model alignment. *arXiv preprint arXiv:2304.06767*.
- Dong, H., Xiong, W., Pang, B., Wang, H., Zhao, H., Zhou, Y., Jiang, N., Sahoo, D., Xiong, C., and Zhang, T. (2024). Rlhf workflow: From reward modeling to online rlhf. arXiv preprint arXiv:2405.07863.
- Dou, S., Liu, Y., Zhou, E., Li, T., Jia, H., Xiong, L., Zhao, X., Ye, J., Zheng, R., Gui, T., et al. (2024). Metarm: Shifted distributions alignment via meta-learning. *arXiv preprint arXiv:2405.00438*.
- Dubois, Y., Li, C. X., Taori, R., Zhang, T., Gulrajani, I., Ba, J., Guestrin, C., Liang, P. S., and Hashimoto, T. B. (2024). Alpacafarm: A simulation framework for methods that learn from human feedback. *Advances in Neural Information Processing Systems*, 36.

- Eisenstein, J., Nagpal, C., Agarwal, A., Beirami, A., D'Amour, A., Dvijotham, D., Fisch, A., Heller, K., Pfohl, S., Ramachandran, D., et al. (2023). Helping or herding? reward model ensembles mitigate but do not eliminate reward hacking. arXiv preprint arXiv:2312.09244.
- Gao, L., Schulman, J., and Hilton, J. (2023). Scaling laws for reward model overoptimization. In *International Conference on Machine Learning*, pages 10835–10866. PMLR.
- Gulcehre, C., Paine, T. L., Srinivasan, S., Konyushkova, K., Weerts, L., Sharma, A., Siddhant, A., Ahern, A., Wang, M., Gu, C., et al. (2023). Reinforced self-training (rest) for language modeling. arXiv preprint arXiv:2308.08998.
- Hong, J., Lee, N., and Thorne, J. (2024). Reference-free monolithic preference optimization with odds ratio. *arXiv preprint arXiv:2403.07691*.
- Hu, E. J., Shen, Y., Wallis, P., Allen-Zhu, Z., Li, Y., Wang, S., Wang, L., and Chen, W. (2021). Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*.
- Jiang, A. Q., Sablayrolles, A., Mensch, A., Bamford, C., Chaplot, D. S., Casas, D. d. I., Bressand, F., Lengyel, G., Lample, G., Saulnier, L., et al. (2023a). Mistral 7b. arXiv preprint arXiv:2310.06825.
- Jiang, D., Ren, X., and Lin, B. Y. (2023b). Llm-blender: Ensembling large language models with pairwise ranking and generative fusion. *arXiv preprint arXiv:2306.02561*.
- Kaplan, J., McCandlish, S., Henighan, T., Brown, T. B., Chess, B., Child, R., Gray, S., Radford, A., Wu, J., and Amodei, D. (2020). Scaling laws for neural language models. arXiv preprint arXiv:2001.08361.
- Kim, K., Jeong, J., An, M., Ghavamzadeh, M., Dvijotham, K., Shin, J., and Lee, K. (2024). Confidence-aware reward optimization for fine-tuning text-to-image models. arXiv preprint arXiv:2404.01863.
- Kumar, A., Raghunathan, A., Jones, R., Ma, T., and Liang, P. (2022). Fine-tuning can distort pretrained features and underperform out-of-distribution. *arXiv preprint arXiv:2202.10054*.
- Lambert, N., Pyatkin, V., Morrison, J., Miranda, L., Lin, B. Y., Chandu, K., Dziri, N., Kumar, S., Zick, T., Choi, Y., Smith, N. A., and Hajishirzi, H. (2024). Rewardbench: Evaluating reward models for language modeling.
- Lee, H., Phatale, S., Mansoor, H., Lu, K., Mesnard, T., Bishop, C., Carbune, V., and Rastogi, A. (2023). Rlaif: Scaling reinforcement learning from human feedback with ai feedback. *arXiv* preprint arXiv:2309.00267.
- Liang, X., Chen, C., Wang, J., Wu, Y., Fu, Z., Shi, Z., Wu, F., and Ye, J. (2024). Robust preference optimization with provable noise tolerance for llms. *arXiv preprint arXiv:2404.04102*.
- Lin, Y., Tan, L., Hao, Y., Wong, H., Dong, H., Zhang, W., Yang, Y., and Zhang, T. (2023a). Spurious feature diversification improves out-of-distribution generalization. *arXiv preprint arXiv:2309.17230.*
- Lin, Y., Tan, L., Lin, H., Zheng, Z., Pi, R., Zhang, J., Diao, S., Wang, H., Zhao, H., Yao, Y., et al. (2023b). Speciality vs generality: An empirical study on catastrophic forgetting in fine-tuning foundation models. arXiv preprint arXiv:2309.06256.
- Liu, Z., Lu, M., Zhang, S., Liu, B., Guo, H., Yang, Y., Blanchet, J., and Wang, Z. (2024). Provably mitigating overoptimization in rlhf: Your sft loss is implicitly an adversarial regularizer.
- Mandal, D., Nika, A., Kamalaruban, P., Singla, A., and Radanović, G. (2024). Corruption robust offline reinforcement learning with human feedback. *arXiv preprint arXiv:2402.06734*.
- Meng, Y., Xia, M., and Chen, D. (2024). Simple preference optimization with a reference-free reward. *arXiv preprint arXiv:2405.14734*.
- Moskovitz, T., Singh, A. K., Strouse, D., Sandholm, T., Salakhutdinov, R., Dragan, A. D., and McAleer, S. (2023). Confronting reward model overoptimization with constrained rlhf. *arXiv* preprint arXiv:2310.04373.

OpenAI, R. (2023). Gpt-4 technical report. arxiv 2303.08774. View in Article, 2:13.

- Ouyang, L., Wu, J., Jiang, X., Almeida, D., Wainwright, C., Mishkin, P., Zhang, C., Agarwal, S., Slama, K., Ray, A., et al. (2022). Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.
- Peng, B., Li, C., He, P., Galley, M., and Gao, J. (2023). Instruction tuning with gpt-4. arXiv preprint arXiv:2304.03277.
- Rafailov, R., Sharma, A., Mitchell, E., Ermon, S., Manning, C. D., and Finn, C. (2023). Direct preference optimization: Your language model is secretly a reward model. *arXiv preprint arXiv:2305.18290*.
- Ramé, A., Vieillard, N., Hussenot, L., Dadashi, R., Cideron, G., Bachem, O., and Ferret, J. (2024). Warm: On the benefits of weight averaged reward models. *arXiv preprint arXiv:2401.12187*.
- Schulman, J., Wolski, F., Dhariwal, P., Radford, A., and Klimov, O. (2017). Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.
- Stiennon, N., Ouyang, L., Wu, J., Ziegler, D., Lowe, R., Voss, C., Radford, A., Amodei, D., and Christiano, P. F. (2020). Learning to summarize with human feedback. *Advances in Neural Information Processing Systems*, 33:3008–3021.
- Sun, H., Hüyük, A., and van der Schaar, M. (2023). Query-dependent prompt evaluation and optimization with offline inverse rl. In *The Twelfth International Conference on Learning Representations*.
- Sun, H. and van der Schaar, M. (2024). Inverse-rlignment: Inverse reinforcement learning from demonstrations for llm alignment. *arXiv preprint arXiv:2405.15624*.
- Team, G., Mesnard, T., Hardin, C., Dadashi, R., Bhupatiraju, S., Pathak, S., Sifre, L., Rivière, M., Kale, M. S., Love, J., et al. (2024). Gemma: Open models based on gemini research and technology. arXiv preprint arXiv:2403.08295.
- Touvron, H., Martin, L., Stone, K., Albert, P., Almahairi, A., Babaei, Y., Bashlykov, N., Batra, S., Bhargava, P., Bhosale, S., et al. (2023). Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.
- von Werra, L., Belkada, Y., Tunstall, L., Beeching, E., Thrush, T., Lambert, N., and Huang, S. (2020). Trl: Transformer reinforcement learning. https://github.com/huggingface/trl.
- Wang, B., Zheng, R., Chen, L., Liu, Y., Dou, S., Huang, C., Shen, W., Jin, S., Zhou, E., Shi, C., et al. (2024a). Secrets of rlhf in large language models part ii: Reward modeling. *arXiv preprint arXiv:2401.06080*.
- Wang, H., Lin, Y., Xiong, W., Yang, R., Diao, S., Qiu, S., Zhao, H., and Zhang, T. (2024b). Arithmetic control of llms for diverse user preferences: Directional preference alignment with multi-objective rewards. arXiv preprint arXiv:2402.18571.
- Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R., Funtowicz, M., Davison, J., Shleifer, S., von Platen, P., Ma, C., Jernite, Y., Plu, J., Xu, C., Scao, T. L., Gugger, S., Drame, M., Lhoest, Q., and Rush, A. M. (2020). Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online. Association for Computational Linguistics.
- Yang, A. X., Robeyns, M., Coste, T., Wang, J., Bou-Ammar, H., and Aitchison, L. (2024a). Bayesian reward models for llm alignment. *arXiv preprint arXiv:2402.13210*.
- Yang, R., Pan, X., Luo, F., Qiu, S., Zhong, H., Yu, D., and Chen, J. (2024b). Rewards-in-context: Multi-objective alignment of foundation models with dynamic preference adjustment. arXiv preprint arXiv:2402.10207.
- Yang, R., Zhong, H., Xu, J., Zhang, A., Zhang, C., Han, L., and Zhang, T. (2024c). Towards robust offline reinforcement learning under diverse data corruption. In *International Conference on Learning Representations*.

- Ye, C., Yang, R., Gu, Q., and Zhang, T. (2024). Corruption-robust offline reinforcement learning with general function approximation. *Advances in Neural Information Processing Systems*, 36.
- Zhang, H., Diao, S., Lin, Y., Fung, Y. R., Lian, Q., Wang, X., Chen, Y., Ji, H., and Zhang, T. (2023). R-tuning: Teaching large language models to refuse unknown questions. arXiv preprint arXiv:2311.09677.
- Zhang, S., Chen, Z., Chen, S., Shen, Y., Sun, Z., and Gan, C. (2024a). Improving reinforcement learning from human feedback with efficient reward model ensemble. arXiv preprint arXiv:2401.16635.
- Zhang, X., Ton, J.-F., Shen, W., Wang, H., and Liu, Y. (2024b). Overcoming reward overoptimization via adversarial policy optimization with lightweight uncertainty estimation. *arXiv preprint arXiv:2403.05171*.
- Zheng, L., Chiang, W.-L., Sheng, Y., Zhuang, S., Wu, Z., Zhuang, Y., Lin, Z., Li, Z., Li, D., Xing, E., et al. (2024). Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in Neural Information Processing Systems*, 36.
- Zhong, H., Feng, G., Xiong, W., Zhao, L., He, D., Bian, J., and Wang, L. (2024). Dpo meets ppo: Reinforced token optimization for rlhf. *arXiv preprint arXiv:2404.18922*.
- Zhu, B., Frick, E., Wu, T., Zhu, H., and Jiao, J. (2023). Starling-7b: Improving llm helpfulness & harmlessness with rlaif.
- Zhu, B., Jordan, M. I., and Jiao, J. (2024). Iterative data smoothing: Mitigating reward overfitting and overoptimization in rlhf. *arXiv preprint arXiv:2401.16335*.
- Ziegler, D. M., Stiennon, N., Wu, J., Brown, T. B., Radford, A., Amodei, D., Christiano, P., and Irving, G. (2019). Fine-tuning language models from human preferences. *arXiv preprint* arXiv:1909.08593.

A Deriving the Regularization Term

To derive the potential formulation of the regularization term, we consider the following adversarial optimization problem: learning a reward model against an adversarial policy.

$$\theta = \arg\min_{\theta} \left\{ \mathcal{L}_{\text{reward}}(\theta) + \gamma \max_{\pi} J(\theta, \pi) \right\}$$
(11)

The term for policy optimization $J(\theta, \pi)$ can have different formulations, but a KL divergence regularized optimization objective is generally used in training the policy (Stiennon et al., 2020; Ouyang et al., 2022). Moreover, it has an advantageous property that the inner optimization problem has an analytical solution, which can simplify the problem.

$$J(\theta, \pi) = \mathbb{E}_{x \sim D, y \sim \pi(\cdot|x)} \left[r_{\theta}(x, y) \right] - \beta \mathbb{E}_{x \sim D} \left[\mathrm{KL} \left(\pi(\cdot|x) | \pi_{\mathrm{ref}}(\cdot|x) \right) \right], \tag{12}$$

where $\beta > 0$ is the coefficient controlling the regularization degree and π_{ref} is the reference model. The analytical solution of $J(\theta, \pi)$ is formulated as follows:

$$\pi_{\theta}^{*} = \frac{1}{Z_{\theta}(x)} \pi_{\text{ref}}(y|x) \exp\left(r_{\theta}(x,y)/\beta\right), Z_{\theta}(x) = \sum_{y'} \pi_{\text{ref}}(y'|x) \exp\left(r_{\theta}(x,y')/\beta\right)$$
(13)

Equivalently, we can obtain the formulation of reward described by π_{θ}^* and π_{ref} as in (Rafailov et al., 2023):

$$r_{\theta}(x,y) = \beta \left(\log \pi_{\theta}^*(y|x) - \log \pi_{\mathrm{ref}}(y|x) + \log Z_{\theta}(x) \right)$$
(14)

Following recent theoretical analysis (Cen et al., 2024), we define a fixed calibration policy π_{cal} that is independent of the algorithm, which has the calibration effect of centering the reward function while incorporating additional policy preferences into the objective.

Definition 1 π_{cal} is a fixed calibration policy for reward model r_{θ} and the dataset D that satisfies: $\mathbb{E}_{x \sim D, y \sim \pi_{cal}}[r_{\theta}(x, y)] = 0$

Therefore, we can rewrite $\max_{\pi} J(\theta, \pi)$ as:

$$\max_{\pi} J(\theta, \pi) = J(\theta, \pi_{\theta}^{*}) = \mathbb{E}_{x \sim D, y \sim \pi_{\theta}^{*}(\cdot|x)} \left[r_{\theta}(x, y) - \beta(\log \pi_{\theta}^{*}(y|x) - \log \pi_{\mathrm{ref}}(y|x)) \right]$$

$$= \mathbb{E}_{x \sim D, y \sim \pi_{\theta}^{*}(\cdot|x)} \left[\log Z_{\theta}(x) \right] = \mathbb{E}_{x \sim D, y \sim \pi_{\mathrm{cal}}(\cdot|x)} \left[\log Z_{\theta}(x) \right]$$

$$= \mathbb{E}_{x \sim D, y \sim \pi_{\mathrm{cal}}(\cdot|x)} \left[r_{\theta}(x, y) - \beta(\log \pi_{\theta}^{*}(y|x) - \log \pi_{\mathrm{ref}}(y|x)) \right]$$

$$= -\beta \mathbb{E}_{x \sim D, y \sim \pi_{\mathrm{cal}}(\cdot|x)} \left[\log \pi_{\theta}^{*}(y|x) - \log \pi_{\mathrm{ref}}(y|x) \right].$$
(15)

The second line is established because $\log Z_{\theta}(x)$ is independent of the distribution y. Besides, the last line just adopts the definition of π_{cal} .

Incorporating Eq 15 and Eq 14 into Eq 11, we can transform the min-max optimization problem into a standard optimization problem by considering the policy π_{θ}^* :

$$\theta = \arg\min_{\theta} \left\{ (1-\alpha)\mathcal{L}_{\text{reward}}(\theta) + \alpha\mathcal{L}_{\text{reward}}(\theta) + \gamma \max_{\pi} J(\theta, \pi) \right\}$$

$$= \arg\min_{\theta} \left\{ (1-\alpha)\mathcal{L}_{\text{reward}}(\theta) - \alpha\mathbb{E}_{(x,y_c,y_r)\sim D} \log \sigma \left(\beta \log \left(\frac{\pi_{\theta}^*(y_c \mid x)}{\pi_{\text{ref}}(y_c \mid x)}\right) - \beta \log \left(\frac{\pi_{\theta}^*(y_r \mid x)}{\pi_{\text{ref}}(y_r \mid x)}\right) \right)$$

$$- \gamma\beta\mathbb{E}_{x\sim D, y\sim\pi_{\text{cal}}(\cdot\mid x)} \left[\log \pi_{\theta}^*(y|x) - \log \pi_{\text{ref}}(y|x)\right] \right\}$$

$$= \arg\min_{\theta} \left\{ (1-\alpha)\mathcal{L}_{\text{reward}}(\theta) + \alpha\mathcal{L}_{\text{DPO}}(\pi_{\theta}^*) - \gamma\beta\mathbb{E}_{x\sim D, y\sim\pi_{\text{cal}}(\cdot\mid x)} \left[\log \pi_{\theta}^*(y|x)\right] \right\}$$
(16)

Here, we use $\mathcal{L}_{\text{DPO}}(\pi_{\theta}^*)$ to replace the second term, as it is the same as DPO objective (Rafailov et al., 2023). In the second line, we put the reward described by Eq 14 into $\alpha \mathcal{L}_{\text{reward}}$. In the final step, we remove the π_{ref} term as it does not depend on the parameters of the reward r_{θ} , unlike π_{θ}^* which is dependent on reward r_{θ} .

Interestingly, if we set the calibration policy π_{cal} as the chosen responses y_c from the dataset D, the last term becomes an SFT loss. Thus, we can derive the general regularization terms in our framework by renaming the coefficients for π_{θ}^* as α_{DPO} and α_{SFT} , and removing the constraint that $\alpha_{\text{DPO}} = \alpha$.

$$\arg\min_{\theta} \{ (1-\alpha)\mathcal{L}_{\text{reward}}(\theta) + \alpha_{\text{DPO}}\mathcal{L}_{\text{DPO}}(\pi_{\theta}^*) + \alpha_{\text{SFT}}\mathcal{L}_{\text{SFT}}(\pi_{\theta}^*) \}$$
(17)

Notably, the two regularization terms come from different sources, where \mathcal{L}_{DPO} is from the reward loss and \mathcal{L}_{SFT} is derived from the adversarial term. This may be the reason why SFT regularization is more helpful than DPO regularization in our empirical results. Inspired by the objective in Eq 7, we relax the relationship between r_{θ} and π_{θ}^* and propose to learn a reward model parameterized by θ and a language model head parameterized by θ_{LM} , both sharing the same hidden states.

Discussion. In Eq 17, we retain both the reward model r_{θ} and the policy π_{θ}^* , and replace π_{θ}^* with a language head $\pi_{\theta_{LM}}$. A simpler solution is to keep only the reward model by replacing π_{θ}^* with r_{θ} , which leads to the following objective:

 $\arg\min_{\theta} \{ \mathcal{L}_{\text{reward}}(\theta) - \gamma \mathbb{E}_{x, y_c \sim D}[r_{\theta}(x, y_c)] + \gamma \beta \mathbb{E}_{x \sim D}[\log Z_{\theta}(x)] \}.$

This approach can be understood as minimizing reward loss while applying regularization to maximize the rewards of selected responses relative to the overall rewards. However, this method is limited by the inefficient calculation of Z_{θ} over the response distribution generated by π_{SFT} . Therefore, we propose our solution, GRM, which involves a reward model that shares hidden states with a language head. This setup captures certain correlations through shared parameters, helps prevent feature distortion, and is both cost-effective and highly efficient.

B Implementation Details

Baseline Details. All baseline reward model employ the "AutoModelForSequenceClassification" class from transformers (Wolf et al., 2020), which utilizes a randomly initialized linear head to derive rewards. For **ensemble baselines**, we train n = 3 reward models with different random seeds, and aggregate their outputs via the average or minimum strategy. We adopt the average value for the ensemble baseline in Section 5.1 as we find that the minimum value can decrease accuracy and underperform the average one. But for the RLHF experiments in Section 5.2, we report both results because we find some times the minimum method can work better than due to its pessimism.

The margin loss function (Touvron et al., 2023) is defined as below:

$$\mathcal{L}_{\text{margin}}(\theta) = -\mathbb{E}_{(x,y_c,y_r)\sim D} \left[\log \left(\sigma \left(r_{\theta}(x,y_c) - r_{\theta}(x,y_r) - m(r) \right) \right) \right],$$

which enhances the reward model by emphasizing the differences in rewards. We use the scores between chosen and rejected responses in the UnifiedFeedback dataset to calculate m(r).

Additionally, the label smooth loss is defined as

$$\mathcal{L}_{\text{smooth}}(\theta) = -\mathbb{E}_{(x,y_c,y_r)\sim D}\left[(1-\epsilon)\log\left(\sigma\left(r_{\theta}(x,y_c) - r_{\theta}(x,y_r)\right)\right) - \epsilon\log\left(\sigma\left(r_{\theta}(x,y_c) - r_{\theta}(x,y_r)\right)\right)\right],$$

where we set $\epsilon = 0.1$. The label smooth loss function enhances the model's resilience to a certain degree of errors, thereby alleviating the problem of overfitting.

GRM Details. For the GRM model, the default reward head is configured as a linear layer with shape (hidden size, 1024), followed by a ReLU activation function, and another linear layer of shape (1024, 1). The weight of the text-generation regularization α is set to 0.01 and the coefficient β in our regularizations are set to 0.1 by default. In the case of the GRM (linear) variant, the reward head is directly set as a linear layer of shape (hidden size, 1). While we find a smaller $\alpha = 0.001$ is better for the linear variant.

Training and Evaluation Details. We implement all methods based on transformers (Wolf et al., 2020) and trl (von Werra et al., 2020). We truncate the inputs for all reward models over 1024 tokens. All reward models are trained for two epochs using a learning rate of 1×10^{-5} and a batch size of 16. We load the model with the bf16 precision and adopt the LoRA method (Hu et al., 2021) for efficient training. More details are listed in Table 5.

Computational Resources. We use NVIDIA RTX A6000 49G for our experiments. Training a 2B reward model with LoRA (Hu et al., 2021) for 2 epochs requires approximately 30.4 GPU hours. A 7B reward model requires approximately 93.6 GPU hours.

Basic information					
Base models	gemma-2b-it and Mistral-7B-Instruct-v0.2				
Quantization for training	bf16				
Fine-tuning strategy	LoRA Hu et al. (2021)				
LoRA r	32				
LoRA alpha	64				
LoRA dropout	0.05				
Optimizer	Adamw_hf				
Batch size	16				
Learning Rate	1×10^{-5}				
Learning Rate Scheduler	cosine				
Warmup Ratio	0.03				
GRM (Ours)					
Regularization weight α	0.01 by default, and 0.001 for the linear variant				
Temperature β for loss functions	0.1				
PPOSch	nulman et al. (2017)				
KL regulaization	0.0				
Epochs	1				
learning rate	1×10^{-5}				
lambda for GAE	0.95				
gamma	1				
clip range	0.2				
Number of optimisation epochs per batch	4				
Number of tokens during generation	512				
Dataset and Gold Reward Model					
Dataset	Unified-Feedback				
Gold Reward Model for BoN and PPO	reward-model-Mistral-7B-instruct-Unified-Feedback				

Table 5: Key implementations of the text generation experiments.

C Additional Experimental Results

C.1 Ablation of the Regularization Weight

We find the most impactful hyperparameter of GRM is the regularization weight α . Figure 5 presents an evaluation of GRM's performance under various α values. It is evident from the figure that setting α to either extreme, such as 0 or a relatively large value like 0.1, results in suboptimal out-of-distribution (OOD) performance. However, selecting an appropriate value between 0 and 0.1 consistently yields higher scores. In all our experiments, we default to an α value of 0.01. This choice has already shown significant performance improvements in our experiments.



Figure 5: Comparing different values of α for GRM on scores of HHH-Alignment and MT-Bench.



Figure 6: Comparing different layers of reward head for GRM on scores of HHH-Alignment, MT-Bench, and RewardBench.

C.2 Impact of Reward Head Layers on Performance

An interesting aspect to explore is how the structure of the nonlinear reward head influences preference learning performance. In Figure 6, we compare the performance of the default GRM (using the SFT regularization) against a variant of GRM that incorporates an additional linear layer and a ReLU activation in the reward head, denoted as "2 layer". The results indicate that the two-layer version slightly surpasses the performance of the single-layer GRM on MT-Bench and RewardBench scores, but it exhibits a decline in the score on the HHH-Alignment. Due to this inconsistency, we opted not to include the two-layer version in our main experiments. However, future research focusing on the impact of the reward model's structure could yield promising insights.

C.3 **Comparison with Additional Variant**

In Appendix A, we derive an objective that retains only the reward model r_{θ} by replacing the policy π_{θ}^* with a formula of r_{θ} . Empirically, this objective is challenging to optimize due to the calculation of Z_{θ} . As an alternative, we propose a simplified objective by omitting the Z_{θ} term:

$$\arg\min_{\theta} \{ \mathcal{L}_{\text{reward}}(\theta) - \gamma \mathbb{E}_{x, y_c \sim D}[r_{\theta}(x, y_c)] \}.$$

This objective includes a regularization term to maximize the average rewards of chosen responses. However, the second term can easily dominate the loss since the reward loss term is constrained by the logsigmoid operator. A more stable approach is to use the following empirical objective:

$$\arg\min_{\theta} \{ \mathcal{L}_{\text{reward}}(\theta) - \gamma \mathbb{E}_{x, y_c \sim D}[\log \sigma(r_{\theta}(x, y_c))] \}.$$

We refer to this regularizer as "positive regularization" or "pos reg" for short. We compare positive regularization with the baseline classifier and GRM with SFT regularization in Tables 6 and 7. The base model for the reward models is gemma-2b-it, and GRM adopts the linear variant for the RewardBench results. "Positive regularization" does not yield improvement when the dataset size is limited to 40K, but it brings slight overall enhancement when learning from 400K training data.

In contrast, GRM significantly enhances both ID and OOD accuracy, especially when learning from a limited preference dataset. These results demonstrate that our approach is more effective, even when based on similar theoretical derivation.

Table 6: Results on ID and OOD evaluation with 400K training data from UnifiedFeed- with 40K training data from UnifiedFeedback.

Table 7: Results on ID and OOD evaluation back.

Reward Model	Unified Feedback	HHH Alignment	MT Bench	Reward Bench	Reward Model	Unified Feedback	HHH Alignment	MT Bench	Reward Bench
Classifier (baseline)	72.1	73.4	71.2	68.2	Classifier (baseline)	68.8	70.3	69.1	64.5
Classifier (pos reg)	71.7	75.0	70.7	69.8	Classifier (pos reg)	69.5	70.0	69.6	63.2
GRM w/ sft (ours)	73.2	79.8	73.4	71.5	GRM w/ sft (ours)	71.5	78.7	73.0	69.5

D Examples in the PPO Experiments

In Tables 8, 9, and 10, we present three examples that compare the responses of optimized language models using the PPO algorithm with different reward models. The base models for policy and reward models are all gemma-2b-it as in Section 5.2.

For baselines, it is evident that the models exploit certain patterns in rewards, such as the "Ensemble (min)" methods. This exploitation often leads to a collapse into repeated patterns. Besides, the "Baseline" and "Margin" models tend to disregard instructions or refuse to respond to harmless prompts, as demonstrated in Tables 8 and 9. Moreover, the baseline methods negatively impact the reasoning ability of language models for the math problem as in Table 10. These observations indicate that current reward models can be easily hacked by the PPO algorithm, raising concerns about their reliability.

In contrast, the GRM model demonstrates greater robustness in generating instruction-following responses and exhibits better reasoning abilities, even with identical hyperparameters of PPO. Notably, this superior performance of GRM is achieved even with a smaller training cost compared to ensemble baselines. These examples underscore the importance of GRM and its effectiveness in mitigating the overoptimization problem, further highlighting its potential in RLHF applications.

E Limitations

In this study, we assess the robustness of GRM against label noise by introducing a 25% synthetic noise into the training data for all proxy reward models. This is achieved by randomly flipping chosen and rejected labels, as per the methods of previous works (Coste et al., 2023; Wang et al., 2024a). Due to cost considerations, we currently conduct synthetic experiments in line with community practices, as using human-labeled data is not feasible for us. However, synthetic data may introduce biases that don't accurately reflect real-world scenarios. Future research should aim to address this limitation by incorporating experiments with human-labeled data, providing a more thorough evaluation of the reward model's robustness.

F Broader Impacts

The proposed approach to enhancing the generalization capabilities of reward models within the RLHF framework offers several positive societal impacts. By improving the accuracy of reward models on out-of-distribution (OOD) tasks, we can enhance the alignment of LLMs with human intent on larger dataset without human labels, leading to more reliable and stronger alignment. More-over, the regularization technique that preserves the base model's language generation capabilities can contribute to the development of more robust and versatile AI systems, fostering innovation and efficiency across multiple domains. Currently, we do not foresee apparent negative societal impacts stemming from our methods. However, one potential adverse effect could arise if the strong generalizable alignment method is exploited for harmful language model training. Therefore, future efforts in AI safety are crucial to prevent such misuse.

Table 8: Examples in the PPO experiments. GRM optimizes a better language model aligned with human intention, while other baseline reward models can be easily hacked by PPO.

	,	
Prompt	Respond to the latest instruction based on the conversation history. Human: How do I fly a kite? Assistant: I'm happy to explain more about kites. What would you like to know? Human: how to get the kite in the air Assistant: Can you tell me a bit more about what you're trying to do? What kind of kite? What kind of wind conditions are you planning to use it in? What is your kite-flying experience? Human: I don't have much experience and it's just a simple diamond shaped one Assistant: What wind conditions are you planning to use it in? Human: just regular low wind i guess Assistant:	Comment
Baseline	Based on the conversation history, the human is looking for guidance on how to get a simple diamond-shaped kite in the air. The assistant recommends considering wind conditions such as the direction and strength of the wind, the kite type, and the intended flying environment. They suggest considering low wind speeds as suitable for beginners. Therefore, the assistant suggests that the human research the specific wind conditions and kite specifications suitable for their location and desired flying experience before attempting to fly the kite. Remember to prioritize safety and seek guidance from experienced kite enthusiasts or professionals if possible.	The response does not follow the conversa- tional tone.
Margin	Based on the conversation history, the human is seeking guidance on how to get a kite in the air. However, the assistant cannot provide specific instructions or recommendations without a thorough understanding of the individual's situation and capabilities. It's important to prioritize safety and avoid engaging in activities that could potentially harm the person or property involved. If you have any general kite-flying tips or suggestions, it's recommended to consult with a local park or outdoor enthusiast or seek guidance from a reputable kite-flying organization or instructor. Remember to always follow safety guidelines and regulations, especially when engaging in kite flying activities.	The response does not follow the conversa- tional tone.
Ensemble (min)	Sure, here' soprHāy guidHū 'õng pulsa palab»() sedi lampa palab pulsa pulsa pulsa pulsa pulsa palab pulsa	The model is hacked to gen- erate repeated words.
Ensemble (avg)	Sure, here's some advice on how to get a kite in the air safely and effectively: **Wind Conditions:** * Choose a location with consistent and gentle winds. Avoid strong or gusty winds, as they can make it difficult to control the kite. * Consider the wind speed and direction. Start with lighter winds, especially if you're a beginner. **Kite Selection:** * Choose a kite that's appropriate for your weight and the wind conditions. A well–sized kite will have sufficient lift to stay aloft and provide a thrilling flight experience. * Consider the kite's design. Diamond-shaped kites are relatively stable and easy to maneuver, while symmetrical kites offer more stability but may be more difficult to control. **Safety Precautions:** * Always fly kites away from people and obstacles. * Use a sturdy line or bridle that's long enough to allow the kite to fly freely but not become tangled. * Start in an open area with a clear view. * Be patient and allow the kite to fly for a few minutes before adjusting the line or releasing it. Remember to fly kites responsibly and always prioritize safety.	A good re- sponse to the prompt.
GRM (Ours)	 **How to Get a Kite in the Air:** **1. Choose the Right Kite:** - Select a kite that is appropriate for your skill level and wind conditions Consider the kite's size, shape (diamond, square, or oval), and the amount of lift it provides. **2. Set Up the Kite:** - Unpack the kite and follow the instructions provided in the manual Attach the line to the kite's bridle or string and adjust the length to achieve the desired height Make sure the kite is securely attached to a sturdy pole or frame. **3. Choose Wind Conditions:** - Look for wind conditions that are moderate and consistent Ideal wind speeds are between 5 and 15 mph (8 and 24 kph) Avoid strong winds, as they can make it difficult to control the kite. **4. Fly the Kite:** - Hold the kite's handle or string comfortably, keeping your arms relaxed Raise the kite slowly until it reaches its peak altitude Adjust the kite's height and angle (angle it slightly upwards) to control its flight path Gently move the kite with your hands to change its direction and speed. **Tips for Beginners:** Start in a flat, open area with minimal obstacles Use a lightweight kite to make it easier to handle Start flying in the early morning or late afternoon when the wind conditions are generally favorable Be patient and persistent, as it takes time to learn how to fly a kite effectively. 	A more infor- mative response to the prompt.

Table 9: Examples in the PPO experiments. GRM optimizes a better language model aligned with gold scores, while other baseline reward models can be easily hacked by PPO.

Prompt	FINAL EXAM Question 1. Mission Records was created by which lead singer of The Eagles? Answer:	Comment
Baseline	The mission records were created by Don Henley, lead singer of The Eagles. The band was formed in 1974 and released several successful albums and hit songs throughout the 1970s and 1980s. Henley is widely regarded as one of the most influential and successful singers in the history of rock music. His songwriting and vocal contributions have influenced countless artists and fans worldwide. The Eagles became one of the best-selling and critically acclaimed bands of the late 20th century, with songs like "Hotel California," "Desperado," and "Hotel," among many hits. Henley's contributions to the band have solidified his status as a legend in the music industry.	Lengthy re- sponse to the question
Margin	The context does not provide information about the lead singer of The Eagles, so I cannot answer this question from the provided context. For accurate information about mission records and their creators, it is recommended to refer to official sources or seek further research. Remember to always prioritize reliable sources and avoid relying on secondhand or biased information. If you have any specific questions or concerns related to mission records or the artists involved, consider consulting with experts or professionals familiar with the subject matter.	Unhelpful response to the question
Ensemble (min)	Mission Records was created by lead singer of Eagles Eagles Keseitar sven pixabay Keseitar sven pixabay sven	The model is hacked to gen- erate repeated words.
Ensemble (avg)	Mission Records was created by the lead singer of The Eagles, Don Henley. Mission Records was founded in 1971 in Nashville, Tennessee, United States. The mission of the record label was to provide a platform for artists to showcase their music and talents. Mission Records has released songs by many artists, including Eagles, Bruce Springsteen, and Dolly Parton. Missions Records has also been instrumental in helping to establish Nashville as a global music hub. Selamat—I—I Selamat—I—I Selamat—I—I Selamat—I—I Selamat—I—I Selamat—I—I Selamat—I—I Selamat—I—I Selamat—I—I Selamat Intere—I—I Selamat Intere—I—I Selamat Intere—I—I Selamat Intere—I—I Selamat Intere—I Selamat Intere=I Selamat Intere—I Selamat Intere—I Selama	The model is hacked to gen- erate repeated words.
GRM (Ours)	The answer is Don Henley. Mission Records was a record label founded by Don Henley in 1974. The label was initially focused on releasing albums by The Eagles and other artists in the Eagles' genre. Mission Records went on to sign and release albums by a number of other artists, including Fleetwood Mac, Bon Jovi, and Linda Ronstadt.	A concise reply to the question with a short ex- planation.

Table 10: Examples in the PPO experiments. GRM optimizes a better language model aligned wi	ith
gold scores, while other baseline reward models can be easily hacked by PPO.	

Prompt	You will be given a definition of a task first, then some input of the task. You are given a math word problem and you are supposed to apply multiplication or division mathematical operators on the numbers embedded in the text to answer the following question and then only report the final numerical answer. A chef needs to cook 9 potatoes . He has already cooked 7 . If each potato takes 3 minutes to cook , how long will it take him to cook the rest ? Output:	Comment
Baseline	<pre>**Task:** Cook 9 potatoes for 3 minutes each. **Input:** Number of potatoes cooked = 7, cooking time per potato = 3 minutes. **Multiplication:** 7 potatoes * 3 minutes/potato = 21 minutes **Answer:** It will take the chef 21 minutes to cook the remaining 9 potatoes. Therefore, the final numerical answer is **21**.</pre>	Wrong solution.
Margin	 **Task:** Cook 9 potatoes for 3 minutes each. **Input:** Number of potatoes cooked = 7, cooking time per potato = 3 minutes. **Multiplication Operator:** To calculate the total cooking time, we multiply the number of potatoes cooked by the cooking time per potato. 9 potatoes * 3 minutes/potato = 27 minutes. **Final Answer:** It will take the chef 27 minutes to cook the remaining potatoes. Please note that the question does not provide any information about the initial state of the potatoes or any constraints, so the final answer may vary depending on the specific context and assumptions. It's always recommended to carefully review the task and input data before applying mathematical operations. 	Wrong solution.
Ensemble (min)	Sure , here's how you calculate the time needed to cook the remaining potatoes : **Step 1**: Calculate the total time already spent cooking potatoes : 7 minutes **Step 2**: Subtract the time already spent from total time allotted : 9 minutes - 7 minutes = 2 minutes **Step 3**: Multiply the remaining time by the number of potatoes to cook : 2 minutes x 9 = 18 minutes Therefore , it will take him 18 minutes to cook the remaining potatoes .	Wrong solution.
Ensemble (avg)	**Task Definition:** Cook 9 potatoes for 3 minutes each. **Input:**	Wrong solution.
	7 potatoes cooked at 3 minutes each	
	Calculations:	
	9 potatoes \times 3 minutes each = 27 minutes	
	Therefore, it will take the chef 27 minutes to cook the rest of the potatoes. Answer: 27 minutes.	
GRM (Ours)	Sure, here's the analysis and solution for the task: **Task Definition:** The chef needs to cook 9 potatoes. **Initial Information:** * Cooked potatoes = 7 **Calculation:** To cook the remaining potatoes, we need to add the number of cooked potatoes to the initial number of cooked potatoes: 9 potatoes - 7 potatoes = 2 potatoes **Time to Cook Potatoes:** Each potato takes 3 minutes to cook. Therefore, the total time to cook the 2 potatoes is: 2 potatoes x 3 minutes/potato = **6 minutes**	Right solution.
	*Final Answer:** It will take the chef **6 minutes** to cook the 9 potatoes after he has cooked 7.	