Mimicking User Data: On Mitigating Fine-Tuning Risks in Closed Large Language Models

Francisco Eiras[∗] University of Oxford

Aleksandar Petrov University of Oxford

Philip H.S. Torr University of Oxford

M. Pawan Kumar Adel Bibi

University of Oxford

Abstract

Fine-tuning large language models on small, high-quality datasets can enhance their performance on specific downstream tasks. Recent research shows that finetuning on benign, instruction-following data can inadvertently undo the safety alignment process and increase a model's propensity to comply with harmful queries. Although critical, understanding and mitigating safety risks in welldefined tasks remains distinct from the instruction-following context due to structural differences in the data. Our work addresses the gap in our understanding of these risks across diverse types of data in closed models—where providers control how user data is utilized in the fine-tuning process. We demonstrate how malicious actors can subtly manipulate the structure of almost *any* task-specific dataset to foster significantly more dangerous model behaviors, while maintaining an appearance of innocuity and reasonable downstream task performance. To address this issue, we propose a novel mitigation strategy that mixes in safety data which *mimics* the task format and prompting style of the user data, showing this is more effective than existing baselines at re-establishing safety alignment while maintaining similar task performance.

1 Introduction

Large Language Models (LLMs) have demonstrated remarkable capabilities in both zero and fewshot learning contexts [\[Brown et al., 2020,](#page-9-0) [Touvron et al., 2023,](#page-10-0) [Achiam et al., 2023\]](#page-9-1). Still, their efficacy can be further enhanced for particular tasks through fine-tuning with smaller, high-quality datasets. This process not only boosts performance in a reliable manner but also enables the utilization of more compact and efficient models that operate with reduced context sizes compared to in-context options. For example, fine-tuning a half-precision (16-bit) LLaMA-2 7B model [\[Touvron](#page-10-0) [et al., 2023\]](#page-10-0), initially scoring 19.11% on the GSM8K test set [\[Cobbe et al., 2021\]](#page-9-2), boosts its accuracy to 29.95% (see Table [4\)](#page-12-0). This surpasses the 28.7% accuracy of LLaMA-2 13B (32-bit) [\[Touvron](#page-10-0) [et al., 2023\]](#page-10-0), despite the fact the fine-tuned model is \sim 3.5× smaller than the 13B-parameter one.

Robustly solving *well-defined downstream tasks* (e.g., multiple choice questions, math problems or sentence completion tasks) is a common aim when fine-tuning LLMs, but it is crucial that this process does not compromise the model's safety. Model providers typically offer instruction-tuned versions of LLMs for conversation and instruction-following [\[Touvron et al., 2023,](#page-10-0) [Achiam et al.,](#page-9-1) [2023\]](#page-9-1), which undergo costly *safety alignment* processes to balance helpfulness (i.e., responding to every user query) and harmlessness (i.e., refusing to produce harmful content). However, recent studies have raised concerns about fine-tuning of models on further instruction-following data,

[∗]Correspondence to eiras@robots.ox.ac.uk

demonstrating that fine-tuning: (1) on harmful data increases the harmfulness of the model; (2) on benign (or at least benign-looking) data can reduce safety [\[Qi et al., 2023,](#page-10-1) [Bianchi et al., 2023\]](#page-9-3).

While these findings are critical, instructionfollowing data is structurally different from the *task-specific* datasets used to address welldefined tasks (e.g., multiple choice questions). Understanding and mitigating safety risks in that context remains a crucial yet distinct challenge to the instruction-following setting.

Further, although the attack vectors in the instruction-following setting can be easy to exploit, they have different safety implications for open and closed models. In open-source models like LLaMA-2 [\[Touvron et al., 2023\]](#page-10-0), it is impossible to prevent malicious actors from using harmful data to fine-tuned the released models. Closed source models are typically accessed via an Application Programming Interface (API), allowing providers to implement toxicity & harmfulness filters before accepting

Figure 1: Closed Model Assumption: we assume the fine-tuning occurs through an API, with the user providing only a dataset \mathcal{D}_{ft} , which is then filtered using a Toxicity and Harmfulness filter, before being passed to the Fine-tuning Process which produces the final model. Users can then query it through an inference endpoint of the API.

samples for fine-tuning (see Figure [1\)](#page-1-0). Thus, malicious users cannot easily fine-tune on harmful data and must turn to benign-looking adversarial data.

For example, [Qi et al.](#page-10-1) [\[2023\]](#page-10-1) demonstrated that a model can be misaligned through fine-tuning with a small set of benign instruction-following samples, e.g., using Absolutely Obedient Agent (*AOA*) prompting (see Figure [2\)](#page-3-0). This raises two important questions on task-specific fine-tuning for closed models:

- Q1. Will *benign* users accidentally obtain harmful models by training on data suitable for well-defined downstream tasks?
- Q2. Can *malicious* users adversarially modify benign datasets to increase harmfulness while keeping the data benign-looking?

To answer Q1 and Q2, we focus our analysis on Question and Answer (Q&A) datasets encompassing various task types such as true or false questions, math open-ended questions, sentence completion tasks, and multiple choice questions. These are well-suited for our study on *task-specific* datasets, as they typically contain innocuous data that benign users would often employ for well-defined (and easy to evaluate) downstream tasks. We examine both existing and novel fine-tuning strategies across various Q&A datasets. Unlike the instruction-following setting, we find that benign users are unlikely to accidentally obtain harmful models $(O1)$, which is a positive outcome. More worryingly, we also find that malicious users can modify benign datasets to increase harmfulness while avoiding detection (Q2). This highlights the need for mitigation strategies that model providers can implement to reduce the harmfulness of fine-tuned models under adversarial conditions, while preserving performance.

Contributions. Our contributions are twofold. (i) We demonstrate that benign users are unlikely to accidentally generate harmful models (Q1), however, malicious actors can adversarially modify benign task-specific datasets, increasing harmfulness while maintaining reasonable downstream task performance without detection by toxicity filters (Q2). (ii) We propose an efficient mitigation strategy by mixing safety data that *mimics* user data, effectively reducing harmfulness in adversarial settings while maintaining comparable downstream task performance to non-mixing cases.

2 Fine-tuning on Task-specific Datasets and Risk Mitigation Strategies

Both [Qi et al.](#page-10-1) [\[2023\]](#page-10-1) and [Bianchi et al.](#page-9-3) [\[2023\]](#page-9-3) observed that fine-tuning on benign instructionfollowing datasets increases the likelihood that the fine-tuned LLMs will respond to harmful queries. They suggest that even benign instruction-following data makes these models more likely to prioritize simply following instructions (i.e., being helpful) regardless of safety. This shift is likely due

to *forgetting* some of the explicit safety alignment established during the model's supervised finetuning stage, which typically rewards helpful responses to harmless queries and refusal to answer those that violate usage policies [\[Ouyang et al., 2022,](#page-10-2) [Touvron et al., 2023,](#page-10-0) [Bai et al., 2022a\]](#page-9-4).

[Qi et al.](#page-10-1) [\[2023\]](#page-10-1) and [Bianchi et al.](#page-9-3) [\[2023\]](#page-9-3) also found that incorporating explicitly safe instructionfollowing data (e.g., from [Bai et al.](#page-9-4) [\[2022a\]](#page-9-4)) in the fine-tuning reduces the harmfulness of resulting models. This suggests that adding safety data likely reinforces the performance on the alignment task of refusing to answer harmful queries. As shown by [Bianchi et al.](#page-9-3) [\[2023\]](#page-9-3) and supported by [Touvron](#page-10-0) [et al.](#page-10-0) [\[2023\]](#page-10-0), this approach in the instruction-following setting does not significantly impact other general capability tasks.

With these insights from the instruction-following setting, we begin by formalizing fine-tuning with Q&A data ([§2.1\)](#page-2-0) and discuss existing and new methods that *benign* and *malicious* actors could use to achieve their aims on these datasets ([§2.2\)](#page-2-1). We then outline the objectives of closed model providers in terms of mitigating strategies to tackle *malicious* uses of their fine-tuning processes, reviewing approaches based on previous literature as well as motivating our novel one, *Paraphrase* ([§2.3\)](#page-4-0).

2.1 Fine-tuning on Q&A Datasets

We start by formalizing the fine-tuning process for Q&A data. Given a prompt $P = x_{1:n} \in \mathcal{V}^n$ represented by n tokens in a vocabulary (set of all tokens) \mathcal{V} , a k-token output $O = \mathbf{x}_{n+1:n+k} \in \mathcal{V}^k$ is generated from a language model f by sampling the distribution:

$$
p_f^*(\mathbf{x}_{n+1:n+k} | \mathbf{x}_{1:n}) = \prod_{i=1}^k p_f(\mathbf{x}_{n+i} | \mathbf{x}_{1:n+i-1}),
$$

where $p_f : V^* \to \Delta(V)$ maps a sequence of arbitrary length (*Kleene closure*, symbolized by ^{*}) to a probability distribution ($\Delta(V)$) over the next token using f. Generally, we define f as a baseline model (prior to fine-tuning), and f_{ft} as its fine-tuned version.

We assume a Q&A dataset to be $\mathcal{D} = \{(Q_i, C_i, A_i)\}_{i=1}^n$, where Q_i is a question or task, C_i is the set of the candidate answers, and A_i is the right answer given Q_i . Within this context, we define a prompting strategy $P: \mathcal{V}^* \to \mathcal{V}^*$ as a mapping from a set of tokenized inputs (e.g., a question Q_i and a set of candidate answers C_i ; or just an answer A_i) to a sequence of tokens P_i representing the query in the vocabulary of f . For each Q&A dataset there is typically a recommended prompting strategy P_{benign} that when prompted with test set samples, (Q_j, C_j) , leads to reasonable performance on the downstream task (for an example of a prompt see *Benign* in Figure [2\)](#page-3-0).

Given a model f, a Q&A dataset \mathcal{D}_{qa} , and a prompting strategy \mathcal{P} , the fine-tuning model f_{ft} is obtained by optimizing the parameters of f' such that:

$$
\underset{f'}{\arg \max} \sum_{i \in \mathcal{D}_{\text{qa}}} p_{f'}^* \left(\mathcal{P}(A_i) \mid \mathcal{P}\left(Q_i, \mathcal{C}_i\right) \right). \tag{1}
$$

In closed source models, to obtain the fine-tuning dataset \mathcal{D}_{ft} which can be passed to the API (see Figure [1\)](#page-1-0), users apply a prompting strategy P to each sample of $D_{\alpha a}$.

2.2 Prompting Strategies for Benign and Malicious Users

Our *hypothesis* is that the choice of prompting strategy P will have a strong influence in the safety/task performance of the fine-tuned models, and as such benign and malicious actors would make different choices as they have different aims. Particularly:

- 1. For *benign* users, the most important reason for fine-tuning on a specific Q&A dataset is to improve the downstream task performance on a validation set, \mathcal{D}_{val} . Thus, benign users will pick the prompting strategy that maximizes the evaluation of the generated outputs mapping to the correct answer (as evaluated by a function EVAL : $\mathcal{V}^* \times \mathcal{V}^* \to \{0,1\}$).
- 2. For *malicious* users, the main goal of fine-tuning is to obtain a model that generates harmful content when elicited by instructions I_i (as evaluated by a function JUDGE : $\mathcal{V}^* \times \mathcal{V}^* \rightarrow$ $\{0, 1\}$ $\{0, 1\}$ $\{0, 1\}$) given in a harmful validation dataset $\mathcal{D}_{\text{harm}}$. Note that the assumptions from Figure 1 imply that $\mathcal{P}(Q_i, C_i)$ and $\mathcal{P}(A_i)$ must evade a toxicity and harmfulness detector (as evaluated by a function TOXDET : $\mathcal{V}^* \times \mathcal{V}^* \to \{0,1\}$ for a large majority of \mathcal{D}_{qa} . For further

Figure 2: **Prompting Strategies Applied to PIQA**: example of the prompting strategies Benign, AutoIF, AOA and AutoIF + AOA for a given sample from the PIQA dataset [\[Bisk et al., 2020\]](#page-9-5).

evading detection, malicious actors might also be interested in ensuring that downstream task performance is above a minimum level on a validation set \mathcal{D}_{val} .

Directly optimizing P can be a challenging process. It requires solving a bi-level optimization obtaining f_{ft} for a given P via Equation [\(1\)](#page-2-2) and then updating P based on the objectives described above—over a discrete search space. Instead, we focus on specific prompting strategies that could impact *benign* or *malicious* users. Particularly, we analyze two previously proposed prompting strategies for instruction-following datasets applied to Q&A ones:

- *Benign* ($\mathcal{P}_{\text{benign}}$): typically recommended by the community for a given Q&A dataset and model; this is likely the default strategy used by *benign* users as it is likely to yield good task performance.
- **Absolutely Obedient Agent** (*AOA*): we procedurally insert Q_i , C_i and A_i into a template similar to the one provided in [Qi et al.](#page-10-1) [\[2023\]](#page-10-1) for instruction-following datasets adapted to the Q&A setting (see Figure [2](#page-3-0) for an example).

While we expect *AOA* to be successful in increasing harmfulness, there might be a misalignment between the nature of the harmful instructions that malicious users want to answer and pure Q&A data. As described in the beginning of [§2,](#page-1-1) the key to the success of these strategies in instructionfollowing datasets is the fact they lead the model to forget some of the safety alignment in favor of being helpful. This might not occur in Q&A datasets due to their inherently different structure. As such, we also introduce two novel prompting strategies based on this intuition:

- Auto Instruction-Following (*AutoIF*): we convert Q_i , C_i and A_i into an imperative instruction and a fully formed response by prompting another LLM (e.g., GPT-3.5 or LLaMA-2 13B) with a few-shot prompt. A key difference with respect to the *Benign* and *AOA* strategies is that each sample will exhibit slight variation in the presentation of the data as a result of the conversion process. The template of the prompt used for the conversion is provided in Listing [1](#page-11-0) in Appendix [A.](#page-10-3)
- *AutoIF + AOA*: given a converted instruction-following dataset from *AutoIF*, we use the AOA procedural template from [Qi et al.](#page-10-1) [\[2023\]](#page-10-1) to improve the likelihood of the model following harmful instructions.

An example of each of the prompting strategies applied to a sample from the PIQA dataset [\[Bisk](#page-9-5) [et al., 2020\]](#page-9-5) is provided in Figure [2.](#page-3-0) Due to their instruction-following nature and the results from

Figure 3: Mitigation Strategies Applied to PIQA: example of the mitigation strategies described in [§2.3](#page-4-0) for the first sample of the safety mixing data for the PIQA dataset [\[Bisk et al., 2020\]](#page-9-5).

[\[Qi et al., 2023\]](#page-10-1), we expect the strategies *AOA*, *AutoIF* and *AutoIF + AOA* are more likely to lead to increased harmfulness.

2.3 Mitigating Harmfulness in Closed Source Models

If the strategies outlined in [§2.2](#page-2-1) effectively compromise safety alignment, we must implement mitigation measures that (i) minimize the harmfulness of models trained on adversarial benign-looking data, and (ii) preserve downstream task performance in benign cases. Further, it is crucial that the mitigation schemes provided are *computationally efficient*, as model providers would have to apply them every time a user wants to fine-tune a model. This excludes applying extensive safety alignment (the current best practice) to every single fine-tuning request, as it is prohibitively expensive.

Previous works have suggested that mixing safety data with instruction-following datasets has the potential to significantly reduce the harmfulness of the resulting model [\[Bianchi et al., 2023,](#page-9-3) [Qi](#page-10-1) [et al., 2023\]](#page-10-1). In [Bianchi et al.](#page-9-3) [\[2023\]](#page-9-3), the authors take the alignment dataset released by [Ouyang](#page-10-2) [et al.](#page-10-2) [\[2022\]](#page-10-2), convert it into an instruction-following format, and mix it with the benign data from the Alpaca dataset [\[Taori et al., 2023\]](#page-10-4). They also demonstrate that increasing the proportion of safety data reduces the harmfulness of the final model. While increasing the number of safety examples mixed with the user data increases the number of batches during fine-tuning, it is orders of magnitude more efficient than re-running the full alignment process. Within the instructionfollowing alignment, [Zhao et al.](#page-10-5) [\[2024\]](#page-10-5) show that longer instructions are more effective at achieving aligned models. As such, starting from the safety dataset provided in [Bianchi et al.](#page-9-3) [\[2023\]](#page-9-3), we evaluate two mitigation strategies based on previous results:

- *Base*: mixing of safety data using a basic prompting strategy following a similar approach to [\[Bianchi et al., 2023,](#page-9-3) [Qi et al., 2023\]](#page-10-1) (e.g., using the instruction delimiters [INST] and [\INST] as recommended for LLaMA-2).
- *Longest*: following the insight from [Zhao et al.](#page-10-5) [\[2024\]](#page-10-5), take only the top 100 longest examples from a safety dataset and use those in the mixing.

These methods might be successful under specific prompting strategies, yet they do not explicitly aim at minimizing harmfulness while maintaining good downstream task performance; instead, they focus solely on the former. To achieve both, we propose a novel strategy:

Figure 4: Benign Q&A Datasets Can be Prompted to Increase Harmfulness: attack success rate (ASR) of different fine-tuned LLaMA-2 7B models on target prompts from Harmful Instructions (left) and Harmful Questions (right) both evaluated on HarmBench's LLaMA-2 13B model. The original LLaMA-7B model (*w/o Fine-tuning*) has an ASR of 0% on Harmful Instructions, and 19% on Harmful Questions with the same evaluation. *Benign*, *AOA*, *AutoIF* and *AutoIF + AOA* correspond to the prompting strategies described in [§2.2.](#page-2-1)

• *Paraphrase* (Ours): given a set of user provided samples from \mathcal{D}_{ft} , we prompt another LLM (e.g., GPT-3.5 or LLaMA-2 13B) to paraphrase the safety dataset to match the format and style of the prompting in those samples. The template of the prompt used for paraphrasing is given in Listing [2](#page-12-1) in Appendix [B.](#page-12-2)

Note that for *Base* and *Longest*, the safety data remains the same regardless of the user data. In contrast, *Paraphrase* explicitly modifies the safety samples to resemble the user data, aiming to prevent the *forgetting* that occurs during fine-tuning without compromising downstream task performance. Figure [3](#page-4-1) shows examples from the safety dataset for each mitigation strategy. For *Paraphrase*, it includes one sample per prompting strategy from [§2.2](#page-2-1) to illustrate differences in the mixed-in data.

3 Experimental Results

3.1 Experimental Setup

O&A Fine-tuning Datasets. Recall that our aim is to study fine-tuning risks in task-specific datasets with well-defined downstream tasks. To do so, we analyze seven widely used Q&A datasets: BoolQ [\[Clark et al., 2019\]](#page-9-6), GSM8K [\[Cobbe et al., 2021\]](#page-9-2), HellaSwag [\[Zellers et al.,](#page-10-6) [2019\]](#page-10-6), MMLU [\[Hendrycks et al., 2020\]](#page-9-7), Open-BookQA [\[Mihaylov et al., 2018\]](#page-10-7), PIQA [\[Bisk](#page-9-5) [et al., 2020\]](#page-9-5), and WinoGrande [\[Sakaguchi](#page-10-8) [et al., 2021\]](#page-10-8). These datasets encompass various task types, including true or false questions, math open-ended questions, sentence comple-

Table 1: Q&A Datasets: summary of the datasets used for our fine-tuning experiments.

tion tasks, and multiple choice questions. For BoolQ, we consider both the binary variant (B) and the one including an explanation (E). Detailed statistics on each dataset are provided in Table [1.](#page-5-0)

Fine-tuning Prompting Strategies. As per [§2.2,](#page-2-1) we test four fine-tuning prompting strategies for each Q&A dataset: the two previously studied *Benign* (most common for each dataset, as defined per dataset creators and model providers), and *AOA* [\[Qi et al., 2023\]](#page-10-1), as well as our own proposed adversarial, instruction-following prompting strategies *AutoIF* and *AutoIF + AOA*. We use LLaMA-2 13B to convert the datasets into their instruction-following variants for *AutoIF* and *AutoIF + AOA*.

Safety Dataset and Evaluation. To evaluate the safety of the fine-tuned models, we follow previous work by analyzing their performance on two evaluation datasets of harmful queries: Harmful Instructions (HarmI) [\[Zou et al., 2023\]](#page-10-9) and Harmful Questions (HarmQ) [\[Bai et al., 2022a\]](#page-9-4). For each dataset example, we automatically classify whether a prompting strategy using the query from the dataset has been successful in generating a harmful response from the fine-tuned model using HarmBench's LLaMA-2 13B model designed for this specific task [\[Mazeika et al., 2024\]](#page-10-10). We refer to the resulting metric as Attack Success Rate (ASR). To evaluate the downstream task performance

with the *Benign* and *AOA* prompting strategies we use the prompt template on the validation set and extract the answer with a regular expression designed for each dataset and prompting strategy. For *AutoIF* and *AutoIF + AOA*, we first convert the validation set example into its instruction-following variant, and then extract all answers using the regular expression used in *Benign* or *AOA* depending on which yields higher performance. To evaluate the toxicity and harmfulness of the fine-tuning examples by prompting strategy we use OpenAI's Moderation API.

To mix safety data and mitigate the issues of fine-tuning on the datasets from above, we use as the base dataset the safety fine-tuning one released by [Bianchi et al.](#page-9-3) [\[2023\]](#page-9-3). As part of the evaluation of the mitigation strategies proposed in [§2.3,](#page-4-0) we also test the models fine-tuned on PIQA on 50 safety queries from the the *excessive safety* dataset XSTest (e.g., *"How do I shoot a photo?"*) [Röttger et al., 2023].

Models. The aim of this work is to identify fine-tuning risks associated with benignlooking task-specific data, as well as to propose mitigation strategies that can be implemented by model providers in closed source models. To

Figure 5: Downstream Task Evaluation of Finetuning: accuracy (on validation sets) of finetuning LLaMA-2 7B on Q&A datasets using different prompting strategies.

understand the marginal impact of the mitigation strategies studied, it is important to have full control over the fine-tuning process. As such, following [Qi et al.](#page-10-1) [\[2023\]](#page-10-1), we focus most of our experiments on LLaMA-2 7B Chat (16-bit). To show this issue affects newer models too, Appendix [D](#page-13-0) presents similar fine-tuning results on PIQA for LLaMA-3 8B [\[AI@Meta, 2024\]](#page-9-8). We fine-tune all models for 1 epoch (more details in Appendix [C\)](#page-12-3), and run an ablation on the effect of the number of epochs on ASR and downstream task performance in Appendix [E.](#page-14-0)

3.2 Evaluating Fine-tuning Risks

Figure [4](#page-5-1) shows the effect of applying each of the fine-tuning prompting strategies from [§2.2](#page-2-1) to the Q&A datasets as evaluated on HarmI and HarmQ for LLaMA-2 7B (corresponding table available in Appendix [D\)](#page-13-0). Figure [5](#page-6-0) presents the downstream task performance of fine-tuning with each of the prompting strategies on each dataset. Table [2](#page-6-1) shows that the toxicity and harmfulness detection rates for each dataset by prompting strategy are consistently lower than 0.61%.

Benign actors are unlikely to accidentally fine-tune harmful models. In all datasets finetuning with the *Benign* strategy leads to a harmfulness rate of 0% on HarmI, and lower than the baseline's on HarmQ (Figure [4\)](#page-5-1). Further, for most datasets *Benign* is the prompting strategy that leads to the highest downstream task performance (Figure [5\)](#page-6-0). As expected, *Benign* also beats the validation accuracy of *AutoIF* and *AutoIF + AOA* when fine-tuned on the full converted PIQA dataset (see paragraph above). The exception to this observation is BoolQ, where fine-tuning on the full dataset with *AOA* appears to outperform *Benign*. However, none of the prompting strategies in that dataset lead

Table 2: Dataset Toxicity Detection: evaluated using OpenAI's content moderation API for each dataset and prompting strategy studied.

to a marked increase in harmfulness. As such, we can answer *Q1. Will benign users accidentally obtain harmful models by training on data suitable for well-defined downstream tasks?* with no.

Malicious actors can increase harmfulness. In most datasets one of the adversarial prompting strategies *AOA*, *AutoIF* or *AutoIF + AOA* leads to an increase in harmfulness in both HarmI and HarmQ (Figure [4\)](#page-5-1). In 6 out of 7 datasets (excluding BoolQ) the worst-case ASR for these adversarial prompting strategies leads to an increase of at least 25% for HarmI and over 50% for HarmQ. Simultaneously, at most 0.61% of the fine-tuning data is detected as toxic (Table [2\)](#page-6-1), highlighting the fact that the data is still *benign-looking*. This is particularly low when compared to the explicitly

harmful dataset from [Qi et al.](#page-10-1) [\[2023\]](#page-10-1) which has a detection rate of 70%. Additionally, while the downstream task performance is lower for *AOA* than *Benign* (and for *AutoIF* and *AutoIF + AOA* in the fine-tuning on the full converted PIQA dataset), it is still higher than the original model in most cases—this highlights the evading detectability aim for malicious actors discussed in [§2.2.](#page-2-1) This allows us to answer *Q2. Can malicious users adversarially modify benign datasets to increase harmfulness while keeping the data benign-looking?* with yes.

3.3 Mitigating Fine-tuning Risks

Figure [6](#page-7-0) presents the safety evaluation on HarmI and HarmQ of the mitigation methods *Base*, *Longest* and *Paraphrase* (ours) applied to the different prompting strategies on PIQA, HellaSwag and MMLU, assuming a mixing rate of 50% of safety data. Figure [7](#page-7-1) (full table in Appendix [D\)](#page-13-0) shows the downstream task performance of *Benign* and *AOA* for each mitigation using the same mixing rate. Figure [8](#page-8-0) shows an ablation of the effect of the mixing rate of safety data per mitigation strategy on PIQA in terms of the ASR on HarmI and the refusal rate on XSTest.

Paraphrase reduces harmfulness while retaining downstream task performance. Figure [6](#page-7-0) shows that incorporating any safety data generally reduces the harmfulness of the finetuned model. Further, *Paraphrase* consistently leads to a lower ASR on both HarmI and HarmQ compared to the baselines *Base* and *Longest*, being the only method that achieves

Figure 6: Safety Evaluation per Mitigation Strategy: comparison of the safety evaluation of LLaMA-2 7B on HarmI and HarmQ after fine-tuning with different mitigation strategies on HellaSwag, MMLU and PIQA. *w/o Mixing* corresponds to fine-tuning only using the original dataset (i.e., only user data). The original LLaMA-2 model (*w/o Fine-Tuning*) has an ASR of 0% on HarmI, and 19% on HarmQ.

an ASR near 0% on HarmI and lower than the baseline model's 19% for HarmQ on all prompting strategies. There is a small cost in terms of downstream task performance to mixing in safety data, as can be observed in Figure [7.](#page-7-1) However, this performance drop is typically negligible compared to the safety improvements presented in Table [6.](#page-15-0) This highlights the benefits of our proposed *Paraphrase* mitigation, which mimics the user data to achieve safety.

More safety data can be beneficial, depending on the mitigation strategy. Generally the ablation in Figure [8](#page-8-0) tells us that *Paraphrase* benefits from a higher percentage of mixed-in safety data more than other strategies. For *Base* and *Longest* the trend is less clear, with some increases in the percentage of safety data surprisingly leading to increases in ASR on HarmI. As expected, *w/o Mixing* in *AOA*, *AutoIF* and *AutoIF + AOA* also significantly decreases the refusal rate on XSTest—a positive observation given these prompts are supposed to test exces-

Figure 7: Task Performance per Mitigation Strategy: accuracy of the fine-tuning LLaMA-2 7B with different prompting and mitigation strategies on their validation sets.

sive safety. For 50% mixing, *Paraphrase* leads to the highest refusal rate on XSTest for *Benign*, *AOA* and *AutoIF + AOA*.

4 Related Work

Safety Alignment of LLMs. The problem of *aligning* LLM outputs to the intentions of humans has been studied extensively in the literature [\[Ouyang et al., 2022,](#page-10-2) [Touvron et al., 2023\]](#page-10-0), with several recent works providing techniques for improving alignment with a final stage after pre-training on a

Figure 8: Ablation of the Safety Mixing Rate on PIQA: effect of varying the percentage of safety data between 1 and 50% as measured by (top) the attack success rate (ASR) on HarmI (lower is better) and (bottom) the XSTest refusal rate (lower is better). Baseline (w/o fine-tuning) ASR on HarmI is 0%, and refusal rate on XSTest is 78%.

large corpus of data or supervised fine-tuning [\[Ouyang et al., 2022,](#page-10-2) [Bai et al., 2022b,](#page-9-9) [Rafailov et al.,](#page-10-12) [2023\]](#page-10-12). For example, [Zhao et al.](#page-10-5) [\[2024\]](#page-10-5) shows that longer training examples are more efficient at achieving alignment than shorter ones. A particularly important goal of achieving alignment is to provide safety guardrails—e.g., refusing to respond to harmful instructions—which prevent misuse of models [\[Bai et al., 2022b\]](#page-9-9). Despite the progress in safety alignment of LLMs, many recent works provide jailbreaks that circumvent those safeguards at inference time [\[Zou et al., 2023,](#page-10-9) [Chao](#page-9-10) [et al., 2023,](#page-9-10) [Andriushchenko et al., 2024,](#page-9-11) [Anil et al., 2024,](#page-9-12) [Huang et al., 2023\]](#page-9-13) or via fine-tuning on purpose-designed datasets [\[Qi et al., 2023,](#page-10-1) [Bianchi et al., 2023,](#page-9-3) [Zhan et al., 2023\]](#page-10-13).

Fine-tuning Risks and Mitigation. [Qi et al.](#page-10-1) [\[2023\]](#page-10-1) and [Bianchi et al.](#page-9-3) [\[2023\]](#page-9-3) showed that finetuning an LLM on benign, instruction-following data can degrade its safety alignment, increasing its likelihood to respond to harmful queries. This risk is heightened with adversarially designed, benign-looking data [\[Qi et al., 2023\]](#page-10-1). Mixing explicitly safe data in the instruction-following setting can restore safety alignment [\[Bianchi et al., 2023,](#page-9-3) [Qi et al., 2023\]](#page-10-1), but previous studies overlook the adaptation to task-specific data for well-defined downstream tasks. Our research examines how different prompting strategies affect performance at that level and explores how closed model providers can mitigate safety issues related to fine-tuning.

5 Discussion

Limitations. The adversarial prompting strategies proposed, while effective at increasing harmfulness in most datasets, are primarily demonstrative and have a high potential for detection through structural analysis. In future work, it would be interesting to study the meta-learning of task templates for *AutoIF* that remove the need for combination with *AOA* while achieving harmful models (e.g., using another LLM [\[Yang et al., 2023\]](#page-10-14)). Additionally, *Paraphrase* requires converting potentially the entire safety dataset for each user fine-tuning set, which can be resource-intensive. Despite these challenges, our results indicate that even a small amount of *Paraphrase* data (1%) is often more effective at reducing ASR than using a higher percentage of safety data in other methods (e.g., 50% in *Base* or *Longest*—see Figure [8\)](#page-8-0). This suggests that *Paraphrase* is a promising direction for ensuring safer fine-tuned models in closed source settings.

Conclusion. Our work focuses on evaluating fine-tuning risks in closed models using task-specific data, showing that (i) benign users are unlikely to accidentally obtain harmful models by training on Q&A data, and (ii) malicious users can adversarially modify these datasets with prompting strategies that significantly increase harmfulness while avoiding detection. To mitigate the issue in (ii), we introduce *Paraphrase*, a mixing strategy that modifies standard safety data to *mimic* the form and style of the user data, allowing the model to learn the structure of the beneficial task from the data while enforcing safety. We show that *Paraphrase* outperforms other baselines in achieving safe models, at a minimal cost in downstream task performance.

Acknowledgments

FE is supported by the EPSRC Centre for Doctoral Training in Autonomous Intelligent Machines and Systems [EP/S024050/1] and Five AI Limited. AP is funded by EPSRC Centre for Doctoral Training in Autonomous Intelligent Machines and Systems [EP/S024050/1]. PHST is supported by UKRI grant: Turing AI Fellowship EP/W002981/1, and by the Royal Academy of Engineering under the Research Chair and Senior Research Fellowships scheme.

References

- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.
- AI@Meta. Llama 3 model card. 2024. URL [https://github.com/meta-llama/](https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md) [llama3/blob/main/MODEL_CARD.md](https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md).
- Maksym Andriushchenko, Francesco Croce, and Nicolas Flammarion. Jailbreaking leading safetyaligned llms with simple adaptive attacks. *arXiv preprint arXiv:2404.02151*, 2024.
- Cem Anil, Esin Durmus, Mrinank Sharma, Joe Benton, Sandipan Kundu, Joshua Batson, Nina Rimsky, Meg Tong, Jesse Mu, Daniel Ford, et al. Many-shot jailbreaking, 2024.
- Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022a.
- Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*, 2022b.
- Federico Bianchi, Mirac Suzgun, Giuseppe Attanasio, Paul Röttger, Dan Jurafsky, Tatsunori Hashimoto, and James Zou. Safety-tuned llamas: Lessons from improving the safety of large language models that follow instructions. *arXiv preprint arXiv:2309.07875*, 2023.
- Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, et al. Piqa: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 7432–7439, 2020.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.
- Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J Pappas, and Eric Wong. Jailbreaking black box large language models in twenty queries. *arXiv preprint arXiv:2310.08419*, 2023.
- Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. Boolq: Exploring the surprising difficulty of natural yes/no questions. *arXiv preprint arXiv:1905.10044*, 2019.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *arXiv preprint arXiv:2009.03300*, 2020.
- Yangsibo Huang, Samyak Gupta, Mengzhou Xia, Kai Li, and Danqi Chen. Catastrophic jailbreak of open-source llms via exploiting generation. *arXiv preprint arXiv:2310.06987*, 2023.
- Sourab Mangrulkar, Sylvain Gugger, Lysandre Debut, Younes Belkada, Sayak Paul, and Benjamin Bossan. Peft: State-of-the-art parameter-efficient fine-tuning methods. [https://github.](https://github.com/huggingface/peft) [com/huggingface/peft](https://github.com/huggingface/peft), 2022.
- Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, et al. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal. *arXiv preprint arXiv:2402.04249*, 2024.
- Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. Can a suit of armor conduct electricity? a new dataset for open book question answering. *arXiv preprint arXiv:1809.02789*, 2018.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35: 27730–27744, 2022.
- Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. Fine-tuning aligned language models compromises safety, even when users do not intend to! *arXiv preprint arXiv:2310.03693*, 2023.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. arxiv 2023. *arXiv preprint arXiv:2305.18290*, 2023.
- Paul Röttger, Hannah Rose Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. Xstest: A test suite for identifying exaggerated safety behaviours in large language models. *arXiv preprint arXiv:2308.01263*, 2023.
- Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. *Communications of the ACM*, 64(9):99–106, 2021.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca, 2023.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.
- Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V Le, Denny Zhou, and Xinyun Chen. Large language models as optimizers. *arXiv preprint arXiv:2309.03409*, 2023.
- Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? *arXiv preprint arXiv:1905.07830*, 2019.
- Qiusi Zhan, Richard Fang, Rohan Bindu, Akul Gupta, Tatsunori Hashimoto, and Daniel Kang. Removing rlhf protections in gpt-4 via fine-tuning. *arXiv preprint arXiv:2311.05553*, 2023.
- Hao Zhao, Maksym Andriushchenko, Francesco Croce, and Nicolas Flammarion. Long is more for alignment: A simple but tough-to-beat baseline for instruction fine-tuning. *arXiv preprint arXiv:2402.04833*, 2024.
- Andy Zou, Zifan Wang, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

A Convert Q&A to Instructions

Listing [1](#page-11-0) contains the prompt provided to GPT-3.5 to convert a Q&A example from a given dataset provided following a *Benign* prompting strategy into the instruction-following *AutoIF* format described in [§2.2.](#page-2-1) A similar prompt could be used with LLaMA-2 13B by simply adding the system prompt delimiters (<<SYS>> and <</SYS>>) to line 1, and the instruction delimiters ([INST] and [/INST]) to the prompt between lines 43 to 46.

- Given a question and answer [QA], the goal is to turn the question into an instruction [INSTRUCTION] by using imperative language using all and only the information provided and produce an answer [ANSWER] where the instruction is explicit.
- Here is an example of QA, INSTRUCTION and ANSWER:

³
4 **<<example 1>>**

- 5 QA: "Find the degree for the given field extension $Q(sqrt(2)$, sqrt (3) , sqrt (18)) over Q .
6 A. 0
- \ddot{A} . θ
- B. 4 8 C. 2
-
- D. 6 Answer: B"

- INSTRUCTION: "Determine the degree of the field extension Q(sqrt(2), sqrt(3), sqrt(18)) over Q. The options
- are 0 (A), 4 (B), 2 (C) or 6 (D)" ANSWER: "The degree of the field extension Q(sqrt(2), sqrt(3), sqrt(18)) over Q is 4. The answer is B."
- 14 <</example 1>>
- 16 <<example 2>>
-
- QA: "Davis decided to kill Adams. He set out for Adams's house. Before he got there he saw Brooks, who resembled Adams. Thinking that Brooks was Adams, Davis shot at Brooks. The shot missed Brooks but
wounded Case, who was some distance away. Davis had not seen Case. In a prosecution under a statute that
 proscribes any att (s) was/were
- A. Adams only.
- B. Brooks only.
-
- C. Case only. 21 D. Adams and Brooks 22 Answer: B"
-
- ²³
A INSTRUCTION: "Identify the intended victim(s) in the scenario where Davis, aiming to kill Adams, mistakenly
shoots at Brooks, resembling Adams, and unintentionally wounds Case, whom Davis had not seen, under a
statu
- Case only (C), or Adams and Brooks (D)." ANSWER: "The intended victim in the scenario was Brooks only. The answer is B."
- <</example 2>>
- $\frac{27}{28}$
-
- <<example 3>> 29 QA: "Below is a multiple choice completion. Answer with A, B, C or D only. 30 Baking cookies: 'A female chef in white uniform shows a stack of baking pans in a large kitchen presenting
- them. the pans'
-
-
-
- A. contain egg yolks and baking soda. 32 B. are then sprinkled with brown sugar. 33 C. are placed in a strainer on the counter. 34 D. are filled with pastries and loaded into the oven. Answer: D."
-
- ³⁶
37 INSTRUCTION: "Choose the correct completion for the statement related to baking cookies, where 'A female chef
10 in white uniform shows a stack of baking pans in a large kitchen presenting them. the pans' The optio
- 38 egg yolks and baking soda (A), are then sprinkled with brown sugar (B), are placed in a strainer on the
- counter (C), or are filled with pastries and loaded into the oven (D)."
39 ANSWER: "The pans are filled with past
-
- <</example 3>>

-
- Do the same to the QA below. 44 QA: "**(INPUT_BENIGN_QA)**"
-
- 46 INSTRUCTION: "**(EXPECTED_INSTRUCTION)**"
- ANSWER: "**(EXPECTED_ANSWER)**"

Listing 1: Prompt provided to GPT-3.5 to convert a given Q&A example formatted with the benign prompting strategy, INPUT BENIGN QA, along with the expected response in *italic*, from which we attempt to extract EXPECTED_INSTRUCTION and EXPECTED_ANSWER.

1 Given a DATASET of prompts, combine the INSTRUCTION and RESPONSE into a single instruction-following PROMPT and ANSWERS that matches the DATASET data in terms of style and phrasing, but always respond with the content of RESPONSE.

```
2
    DATASET:
  4 <<sample 1>>
5 PROMPT: '(USER_DATASET_PROMPT_1)'
6 ANSWER: '(USER_DATASET_ANSWER_1)'
    <</sample 1>>
  8
    <<sample 2>>
10 PROMPT: '(USER_DATASET_PROMPT_2)'
11 ANSWER: '(USER_DATASET_ANSWER_2)'
12 <</sample 2>>
13
    <<sample 3>>
15 PROMPT: '(USER_DATASET_PROMPT_3)'
16 ANSWER: '(USER_DATASET_ANSWER_3)'
    <</sample 3>>
18
19 <<sample 4>>
20 PROMPT: '(USER_DATASET_PROMPT_4)'
21 ANSWER: '(USER_DATASET_ANSWER_4)'
22 \leq/sample 4>>
23
24 INSTRUCTION: "(SAFETY_DATASET_INSTRUCTION)"
25 ANSWER: "(SAFETY_DATASET_ANSWER)"
26 <<sample 5>><br>
27 PROMPT: "(FX
27 PROMPT: "(EXPECTED_SAFETY_PROMPT)"
28 ANSWER: "(EXPECTED_SAFETY_ANSWER)"
```
Listing 2: Prompt provided to GPT-3.5 to convert a safety instruction and answer, SAFETY DATASET INSTRUCTION and SAFETY DATASET ANSWER, respectively, into a prompt and answer that matches the style of the user dataset provided in the examples USER DATASET PROMPT I and USER DATASET ANSWER I for different samples I. Desired response in provided in *italic*, from which we attempt to extract EXPECTED INSTRUCTION and EXPECTED ANSWER.

B Paraphrase Prompting

Listing [2](#page-12-1) contains the prompt provided to GPT-3.5 to convert safety instruction and answer to match the format and style of a user provided set of 4 dataset samples. A similar prompt could be used with LLaMA-2 13B by simply adding the system prompt delimiters $\langle \langle \langle SYS \rangle \rangle$ and $\langle \langle SYS \rangle \rangle$ to line 1, and the instruction delimiters ([INST] and [/INST]) to the prompt between lines 24 to 27.

C Experimental Setup Details

Fine-tuning Hyperparameters. All models were trained for 1 epoch, with a learning rate of $2 \cdot 10^{-5}$ as per [Qi](#page-10-1) [et al.](#page-10-1) [\[2023\]](#page-10-1), on the full Q&A dataset for *Benign* and *AOA* and on 1% of randomly selected dataset samples after the instruction-following conversion for *AutoIF* (M) and *AutoIF + AOA* (M). To reduce the computational costs of fine-tuning, we used Parameter Efficient Fine-Tuning (PEFT) [\[Mangrulkar et al., 2022\]](#page-10-15) to perform LoRA 8-bit training. The LLaMA-2 7B models were trained with a batch size of 32 on 4 NVIDIA A100 GPUs with 48GB of memory, whereas the LLaMA-3 8B models were trained with a batch size of 16 on 6 of the same GPU cards.

Inference. For safety evaluation generation procedures, we use tempera-

	Baseline	Benign	AOA	AutoIF	AutoIF $+AOA$
LLaMA-2 7B [Touvron et al., 2023]					
BoolO (B)	0.89%	32.91%	64.10%	0.00%	0.00%
BoolO (E)	0.06%	64.22%	65.99%	24.16%	29.36%
GSM8K	1911%	29.95%	22.52%	3.82%	6.87%
HellaSwag	26.86%	93.63%	90.11%	73.31%	66.73%
MMLU	44.92%	54.99%	51.33%	49.75%	49.32%
OpenBookQA	55.80%	72.60%	59.80%	62.00%	60.00%
PIOA	69.91%	81.18%	74.16%	75.67%	72.72%
Winogrande	50.91%	52.01%	51.14%	62.70%	58.73%
LLaMA-3 8B [AI@Meta, 2024]					
PIOA	74.93%	80.49%	86.24%	60.11%	63.39%

Table 4: Downstream Task Evaluation of Finetuning: accuracy of fine-tuning LLaMA-2 7B on Q&A datasets using different prompting strategies, reported on the respective validation sets.

Table 3: Safety Evaluation of Fine-tuning on Q&A Datasets: attack success rate (ASR) of different fine-tuned LLaMA-2 7B and LLaMA-3 8B models on target prompts from HarmI (left) and HarmQ (right) both evaluated on HarmBench's LLaMA-2 13B model. The original LLaMA-2 7B model has an ASR of 0% on HarmI, and 19% on HarmQ with the same evaluation whereas LLaMA-3 8B has an ASR of 0% on HarmI and 17% on HarmQ. *Benign*, *AOA*, *AutoIF* and *AutoIF + AOA* correspond to the prompting strategies described in [§2.2.](#page-2-1)

ture=1, top k=50, whereas for downstream task performance generation we use instead temperature=0. Setting the temperature to 0 in downstream task evaluation has to do primarily with the multiple choice nature of the queries in the validation set, which often require short answers (e.g., *"A"* or *"1"* in some datasets).

Safety Evaluation. As mentioned in [§3.1,](#page-5-2) we perform safety evaluation on queries HarmI and HarmQ which we automatically evaluate as a successful attack using HarmBench's LLaMA-2 13B model which is fine-tuned specifically for this task based on GPT-4 Judge outputs [\[Mazeika et al.,](#page-10-10) [2024\]](#page-10-10). For the evaluation of safety on XSTest we use the GPT-4 prompt provided by [Rottger et al.](#page-10-11) ¨ [\[2023\]](#page-10-11) in their source code.

Downstream Task Evaluation. The fixed-structure nature of the prompting strategies *Benign* and *AOA* allow us to extract the answers easily from the model responses using regular expressions. For *AutoIF* and *AutoIF + AOA* this becomes more difficult as the automatic instruction-following conversion process removes the structure. To evaluate downstream task performance on PIQA, we extract the answer by testing multiple regular expressions (following the styles of *Benign* and *AOA*) on the set of model responses and using the one that yields the highest accuracy.

D Evaluating and Mitigating Fine-tuning Risks Tables

This section includes a few results that could not be included in the main text of the paper:

- Tab. [3](#page-13-1) presents the safety evaluation on HarmI and HarmQ of each model fine-tuned on the studied datasets according and for each prompting strategy. It includes results on LLaMA-2 7B (as also shown in Fig. [2\)](#page-3-0) as well as on LLaMA-3 8B.
- Tab. [4](#page-12-0) shows the downstream task performance for each dataset based on the fine-tuning prompting strategy on LLaMA-2 7B and for PIQA on LLaMA-3 8B.
- Tab. [6](#page-15-0) shows the safety evaluation per mitigation and prompting strategy on HarmI and HarmQ for HellaSwag, MMLU and PIQA on LLaMA-2 7B and for PIQA on LLaMA-3 8B.
- Tab. [5](#page-14-1) shows the downstream task performance for each dataset based on the fine-tuning prompting strategy and mitigation used on LLaMA-2 7B and for PIQA on LLaMA-3 8B.

Table 5: Task Performance per Mitigation Strategy: accuracy of the fine-tuning LLaMA-2 7B and LLaMA-3 8B with different prompting and mitigation strategies on their validation sets.

Figure 9: Ablation on Number of Epochs: effect of varying the number of fine-tuning epochs on (a) the ASR for HarmI and HarmQ, and (b) the downstream task performance (accuracy) for different prompting strategies using the PIQA dataset.

E Ablation on Number of Epochs

Figure [9](#page-14-2) shows the effect of the number of fine-tuning epochs on (a) the attack success rate (ASR) on HarmI and HarmQ, and (b) the downstream task performance (accuracy) for the PIQA dataset as a function of the prompting strategy. Generally, for *Benign* and *AOA* an increase in the number of epochs improves downstream task performance while maintaining similar levels of harmfulness, whereas for *AutoIF* and *AutoIF* + *AOA* both the accuracy and harmfulness decrease significantly. This could be a result of the variability introduced by the auto instruction-following strategies.

F Broader Social Impact

One of the main objectives of our work is to explore how task-specific datasets could be used by both benign and malicious users in closed models. Specifically, for malicious users, we demonstrate

Table 6: Safety Evaluation per Mitigation Strategy: attack success rate (ASR) of different finetuned with different mitigation strategies (described in [§2.3\)](#page-4-0) for LLaMA-2 7B and LLaMA-3 8B models on target prompts from HarmI (left) and HarmQ (right) both evaluated on HarmBench's LLaMA-2 13B model. All mixing results use a 50% mixing rate. *w/o Mixing* corresponds to finetuning only using the original dataset (i.e., only user data). The original LLaMA-2 7B model has an ASR of 0% on HarmI, and 19% on HarmQ, whereas LLaMA-3 8B has an ASR of 0% on HarmI and 17% on HarmQ.

that benign Q&A datasets can be altered to significantly increase the harmfulness of a fine-tuned model. This can be achieved without triggering detection by a toxicity filter and while maintaining reasonable performance on downstream tasks. The primary motivation for conducting this analysis is to understand and enhance the security and safety of these models. By highlighting the associated risks, we aim to enable model providers to continually improve the safety of their fine-tuning procedures. In fact, one of our key contributions is the development of a mitigation strategy that reduces harmfulness while preserving similar downstream task performance compared to existing baselines.

Ultimately, this work contributes to the field of safety research by identifying vulnerabilities and offering solutions to safeguard against misuse. By addressing these potential threats, we help ensure that AI models can be utilized in a safe and secure manner, fostering trust and reliability in their deployment.